
First published in the *Government Gazette*, Electronic Edition, on 9th September 2016 at 5.00 pm.

No. S 427

STRATEGIC GOODS (CONTROL) ACT
(CHAPTER 300)

STRATEGIC GOODS (CONTROL)
ORDER 2016

ARRANGEMENT OF PARAGRAPHS

Paragraph

1. Citation and commencement
 2. Strategic goods and strategic goods technology
 3. Revocation
- The Schedule
-

In exercise of the powers conferred by section 4A(1) of the Strategic Goods (Control) Act, the Minister for Trade and Industry makes the following Order:

Citation and commencement

1. This Order is the Strategic Goods (Control) Order 2016 and comes into operation on 1 November 2016.

Strategic goods and strategic goods technology

2. The goods and technology specified in the Schedule are strategic goods and strategic goods technology, respectively, for the purposes of the Act.

Revocation

3. The Strategic Goods (Control) Order 2015 (G.N. No. S 542/2015) is revoked.

THE SCHEDULE

Paragraph 2

PART 1

MILITARY GOODS THE EXPORT, TRANSHIPMENT OR BRINGING IN TRANSIT OF WHICH, AND TECHNOLOGY THE EXPORT OR TRANSMISSION OF WHICH, REQUIRE A PERMIT

Division 1 — Preliminary Provisions

Subdivision 1 — General Notes

1. Non-controlled goods (including plant) containing one or more controlled components set out in Division 2 shall be considered as being controlled goods within Division 2 if the controlled components are the principal element of the non-controlled goods and can feasibly be removed or used for other purposes.
2. In determining whether goods are to be considered the principal element of other goods for the purposes of paragraph 1, factors such as the quantity, value and technological know-how involved and other special circumstances which might establish the goods as the principal element of those other goods must be weighed.
3. Goods specified in Division 2 include both new and used goods.
4. Chemicals in Division 2 are listed by name and CAS number. Chemicals of the same structural formula (including hydrates) as chemicals listed in Division 2 are to be considered as coming within the descriptions of the second-mentioned chemicals regardless of name or CAS number. CAS numbers are shown in order to assist in identifying whether a particular chemical or mixture is a chemical within Division 2, irrespective of nomenclature. CAS numbers are not intended to be used as unique identifiers because some forms of the listed chemical have different CAS numbers, and mixtures containing a listed chemical may also have different CAS numbers.
5. Specially formulated pharmaceutical products that contain any item under Category Code ML8 in Division 2 shall not be treated as coming under that Division.
6. An aircraft shall not be treated as coming under Category Code ML10 in Division 2 if it has no item listed in that Division and it is not configured for military use.

Subdivision 2 — Definitions of Words and Expressions in this Part

7. In this Part, words and expressions in quotation marks (“ ”) take the definitions set out against them in this paragraph:

“adapted for use in war” (ML7) means any modification or selection (such as altering purity, shelf life, virulence, dissemination characteristics, or resistance to UV radiation) designed to increase the effectiveness in producing casualties in humans or animals, degrading equipment or damaging crops or the environment;

“additives” (ML8) means substances used in explosive formulations to improve their properties;

“aircraft” (ML8, ML10, ML14) means a fixed wing, swivel wing, rotary wing (helicopter), tilt rotor or tilt-wing airborne vehicle;

“automated command and control systems” (ML11) means electronic systems, through which information essential to the effective operation of the grouping, major formation, tactical formation, unit, ship, subunit or weapons under command is entered, processed and transmitted. This is achieved by the use of computer and other specialised hardware designed to support the functions of a military command and control organisation. The main functions of an automated command and control system are: the efficient automated collection, accumulation, storage and processing of information; the display of the situation and the circumstances affecting the preparation and conduct of combat operations; operational and tactical calculations for the allocation of resources among force groupings or elements of the operational order of battle or battle deployment according to the mission or stage of the operation; the preparation of data for appreciation of the situation and decision-making at any point during operation or battle; computer simulation of operations;

“biocatalysts” (ML7, ML22) means ‘enzymes’ for specific chemical or biochemical reactions or other biological compounds which bind to and accelerate the degradation of CW agents;

Technical Note

‘Enzymes’ means “biocatalysts” for specific chemical or biochemical reactions.

“biopolymers” (ML7) means the following biological macromolecules:

- a. Enzymes for specific chemical or biochemical reactions;
- b. ‘Anti-idiotypic’, ‘monoclonal’ or ‘polyclonal’ ‘antibodies’;
- c. Specially designed or specially processed ‘receptors’;

Technical Notes

1. *'Anti-idiotypic antibodies' means antibodies which bind to the specific antigen binding sites of other antibodies.*
2. *'Monoclonal antibodies' means proteins which bind to one antigenic site and are produced by a single clone of cells.*
3. *'Polyclonal antibodies' means a mixture of proteins which bind to the specific antigen and are produced by more than one clone of cells.*
4. *'Receptors' means biological macromolecular structures capable of binding ligands, the binding of which affects physiological functions.*

“civil aircraft” (ML4, ML10) means an “aircraft” listed by designation in published airworthiness certification lists by civil aviation authorities of one or more “participating states” to fly commercial civil internal and external routes or for legitimate civil, private or business use;

“deactivated firearm” (ML1) means a firearm that has been made incapable of firing any projectile by processes. These processes permanently modify the essential elements of the firearm. Deactivation of the firearm may be attested by a certificate delivered by a competent authority of the country in which the firearm is deactivated and may be marked on the firearm by a stamp on an essential part;

“development” (All Categories) has the same meaning as in the Act;

“end-effectors” (ML17) means grippers, ‘active tooling units’ and any other tooling that is attached to the baseplate on the end of a “robot” manipulator arm;

Technical Note

'Active tooling units' means devices for applying motive power, process energy or sensing to a workpiece.

“energetic materials” (ML8) means substances or mixtures that react chemically to release energy required for their intended application. “Explosives”, “pyrotechnics” and “propellants” are subclasses of energetic materials;

“explosives” (ML8) means solid, liquid or gaseous substances or mixtures of substances which, in their application as primary, booster, or main charges in warheads, demolition and other applications, are required to detonate;

“expression vectors” (ML7) means carriers (e.g. plasmid and virus) used to introduce genetic material into host cells;

“fibrous or filamentary materials” (ML13) includes:

- a. Continuous monofilaments;
- b. Continuous yarns and rovings;
- c. Tapes, fabrics, random mats and braids;
- d. Chopped fibres, staple fibres and coherent fibre blankets;
- e. Whiskers, either monocrystalline or polycrystalline, of any length;
and
- f. Aromatic polyamide pulp;

“first generation image intensifier tubes” (ML15) means electrostatically focused tubes, employing input and output fibre optic or glass face plates, multi-alkali photocathodes (S-20 or S-25), but not microchannel plate amplifiers;

“fuel cell” (ML17) means an electrochemical device that converts chemical energy directly into Direct Current (DC) electricity by consuming fuel from an external source;

“laser” (ML9, ML17, ML19) means an item that produces spatially and temporally coherent light through amplification by stimulated emission of radiation;

“library” (parametric technical database) (ML17) means a collection of technical information, reference to which may enhance the performance of relevant systems, equipment or components;

“lighter-than-air vehicles” (ML10) means balloons and ‘airships’ that rely on hot air or on lighter-than-air gases such as helium or hydrogen for their lift;

Technical Note

‘airship’ means a power-driven airborne vehicle that is kept buoyant by a body of gas (usually helium, formerly hydrogen) which is lighter than air.

“nuclear reactor” (ML17) includes the items within or attached directly to the reactor vessel, the equipment which controls the level of power in the core, and the components which normally contain or come into direct contact with or control the primary coolant of the reactor core;

“participating state” (ML4, ML10) means a state participating in the Wassenaar Arrangement (details of which are set out in <http://www.wassenaar.org/participants/index.html>);

“precursors” (ML8) means speciality chemicals used in the manufacture of “explosives”;

“production” (All Categories) has the same meaning as in the Act;

“propellants” (ML8) means substances or mixtures that react chemically to produce large volumes of hot gases at controlled rates to perform mechanical work;

“pyrotechnic(s)” (ML4, ML8) means mixtures of solid or liquid fuels and oxidisers which, when ignited, undergo an energetic chemical reaction at a controlled rate intended to produce specific time delays, or quantities of heat, noise, smoke, visible light or infrared radiation. Pyrophorics are a subclass of “pyrotechnics”, which contain no oxidisers but ignite spontaneously on contact with air;

“required” (ML22), in relation to “technology”, means only that portion of “technology” which is peculiarly responsible for achieving or exceeding the controlled performance levels, characteristics or functions. Such “required” “technology” may be shared by different products;

“riot control agents” (ML7) means substances which, under the expected conditions of use for riot control purposes, produce rapidly in humans sensory irritation or disabling physical effects which disappear within a short time following termination of exposure. (Tear gases are a subset of “riot control agents”);

“robot” (ML17) means a manipulation mechanism of the continuous path or the point-to-point variety, may use sensors, and has all the following characteristics:

- a. it is multifunctional;
- b. it is capable of positioning or orienting material, parts, tools or special devices through variable movements in three dimensional space;
- c. it incorporates three or more closed or open loop servo-devices which may include stepping motors; and
- d. it has ‘user-accessible programmability’ by means of the teach/playback method or by means of an electronic computer which may be a programmable logic controller, i.e. without mechanical intervention;

Technical Note

'User-accessible programmability' means the facility allowing a user to insert, modify or replace 'programmes' by means other than:

- a. A physical change in wiring or interconnections; or*
- b. The setting of function controls including entry of parameters;*

Technical Note

'Programme' means a sequence of instructions to carry out a process in, or convertible into, a form executable by an electronic computer.

Note

"Robot" does not include the following devices:

- a. Manipulation mechanisms which are only manually or teleoperator controllable;*
- b. Fixed sequence manipulation mechanisms which are automated moving devices, operating according to mechanically fixed programmed motions. The programme is mechanically limited by fixed stops, such as pins or cams. The sequence of motions and the selection of paths or angles are not variable or changeable by mechanical, electronic or electrical means;*
- c. Mechanically controlled variable sequence manipulation mechanisms which are automated moving devices, operating according to mechanically fixed programmed motions. The programme is mechanically limited by fixed, but adjustable stops such as pins or cams. The sequence of motions and the selection of paths or angles are variable within the fixed programme pattern. Variations or modifications of the programme pattern (e.g. changes of pins or exchanges of cams) in one or more motion axes are accomplished only through mechanical operations;*
- d. Non-servo-controlled variable sequence manipulation mechanisms which are automated moving devices, operating according to mechanically fixed programmed motions, where the programme is variable but the sequence proceeds only by the binary signal from mechanically fixed electrical binary devices or adjustable stops;*

- e. *Stacker cranes defined as Cartesian coordinate manipulator systems manufactured as an integral part of a vertical array of storage bins and designed to access the contents of those bins for storage or retrieval.*

“software” (All Categories) means a collection of one or more ‘programmes’ or ‘microprogrammes’ recorded, stored or embodied in any device;

Technical Notes

1. *‘Programme’ means a sequence of instructions to carry out a process in, or convertible into, a form executable by an electronic computer.*
2. *‘Microprogramme’ means a sequence of elementary instructions, maintained in a special storage, the execution of which is initiated by the introduction of its reference instruction into an instruction register.*

“spacecraft” (ML11) means active and passive satellites and space probes;

“space-qualified” (ML19) means designed, manufactured, or qualified through successful testing, for operation at altitudes greater than 100 km above the surface of the Earth;

Note

A determination that a specific item is “space-qualified” by virtue of testing does not mean that other items in the same production run or model series are “space-qualified” if not individually tested.

“superconductive” (ML20), in relation to any equipment, means the equipment is made of any material (such as a metal, alloy or compound) which can lose all electrical resistance (i.e. it can attain infinite electrical conductivity and carry very large electrical currents without Joule heating);

Technical Note

The “superconductive” state of a material is individually characterised by a ‘critical temperature’, a critical magnetic field, which is a function of temperature, and a critical current density which is, however, a function of both magnetic field and temperature.

Technical Note

'Critical temperature' (sometimes referred to as the transition temperature) of a specific "superconductive" material is the temperature at which the material loses all resistance to the flow of direct electrical current.

"technology" (All Categories) means information (including information comprised in such documents as specifications, blueprints, plans, manuals, models, diagrams, formulae, tables and designs) that is necessary for the "development", "production" or 'use' of any goods;

Technical Note

'Use' has the same meaning as in the Act.

"unmanned aerial vehicle" ("UAV") (ML10) means any "aircraft" capable of initiating flight and sustaining controlled flight and navigation without any human presence on board.

8. In paragraph 7, a reference to a Category Code (prefixed with the abbreviation "ML") in brackets is a reference to that Category Code in Division 2 in which the defined word or expression appears.
9. In this Part, a word or expression enclosed with single quotation marks (') takes the definition set out against it in the Technical Note that follows immediately after the definition in which the word or expression appears.

Division 2 — List of Military Goods

<i>Category Code</i>	<i>Item Description</i>
ML1	<p>Smooth-bore weapons with a calibre of less than 20 mm, other arms and automatic weapons with a calibre of 12.7 mm (calibre 0.50 inches) or less and accessories, as follows, and specially designed components therefor:</p> <p><u>Note</u></p> <p><i>Category Code ML1 does not apply to the following:</i></p> <ol style="list-style-type: none"> a. <i>Firearms specially designed for dummy ammunition and which are incapable of discharging a projectile;</i> b. <i>Firearms specially designed to launch tethered projectiles having no high explosive charge or communications link, to a range of less than or equal to 500 m;</i> c. <i>Weapons using non-centre fire cased ammunition and which are not of the fully automatic firing type;</i> d. <i>"Deactivated firearms".</i>

<i>Category Code</i>	<i>Item Description</i>
	<p>a. Rifles and combination guns, handguns, machine, sub-machine and volley guns;</p> <p><u>Note</u> <i>Category Code ML1.a. does not apply to the following:</i></p> <p>a. <i>Rifles and combination guns, manufactured earlier than 1938;</i></p> <p>b. <i>Reproductions of rifles and combination guns, the originals of which were manufactured earlier than 1890;</i></p> <p>c. <i>Handguns, volley guns and machine guns, manufactured earlier than 1890, and their reproductions;</i></p> <p>d. <i>Rifles or handguns, specially designed to discharge an inert projectile by compressed air or CO₂.</i></p> <p>b. Smooth-bore weapons as follows:</p> <p>1. Smooth-bore weapons specially designed for military use;</p> <p>2. Other smooth-bore weapons as follows:</p> <p>a. Fully automatic type weapons;</p> <p>b. Semi-automatic or pump-action type weapons;</p> <p><u>Note</u> <i>Category Code ML1.b.2. does not apply to weapons specially designed to discharge an inert projectile by compressed air or CO₂.</i></p> <p><u>Note</u> <i>Category Code ML1.b. does not apply to the following:</i></p> <p>a. <i>Smooth-bore weapons manufactured earlier than 1938;</i></p> <p>b. <i>Reproductions of smooth-bore weapons, the originals of which were manufactured earlier than 1890;</i></p>

<i>Category Code</i>	<i>Item Description</i>
	<p data-bbox="440 329 1143 458">c. <i>Smooth-bore weapons used for hunting or sporting purposes. These weapons must not be specially designed for military use or of the fully automatic firing type;</i></p> <p data-bbox="440 477 1143 544">d. <i>Smooth-bore weapons specially designed for any of the following:</i></p> <ol data-bbox="528 563 1143 830" style="list-style-type: none"> <li data-bbox="528 563 995 595">1. <i>Slaughtering of domestic animals;</i> <li data-bbox="528 614 892 647">2. <i>Tranquilizing of animals;</i> <li data-bbox="528 666 776 698">3. <i>Seismic testing;</i> <li data-bbox="528 717 995 750">4. <i>Firing of industrial projectiles; <u>or</u></i> <li data-bbox="528 769 1143 830">5. <i>Disrupting Improvised Explosive Devices (IEDs).</i> <p data-bbox="588 849 646 881"><u><i>N.B.</i></u></p> <p data-bbox="588 891 1143 991"><i>For disruptors, see Category Code ML4 and Category Code IA006 in Division 2 of Part 2 of this Schedule.</i></p> <p data-bbox="377 1011 884 1043">c. <i>Weapons using caseless ammunition;</i></p> <p data-bbox="377 1062 1143 1191">d. <i>Detachable cartridge magazines, sound suppressors or moderators, special gun-mountings, optical weapon-sights and flash suppressors, for arms specified in Category Code ML1.a., ML1.b. or ML1.c.</i></p> <p data-bbox="440 1210 498 1243"><u><i>Note</i></u></p> <p data-bbox="440 1252 1143 1448"><i>Category Code ML1.d. does not apply to optical weapon-sights without electronic image processing, with a magnification of 9 times or less, provided they are not specially designed or modified for military use, or incorporate any reticles specially designed for military use.</i></p>

<i>Category Code</i>	<i>Item Description</i>
ML2	<p>Smooth-bore weapons with a calibre of 20 mm or more, other weapons or armament with a calibre greater than 12.7 mm (calibre 0.50 inches), projectors and accessories, as follows, and specially designed components therefor:</p> <p>a. Guns, howitzers, cannon, mortars, anti-tank weapons, projectile launchers, military flame throwers, rifles, recoilless rifles, smooth-bore weapons and signature reduction devices therefor;</p> <p><i>Note 1</i> <i>Category Code ML2.a. includes injectors, metering devices, storage tanks and other specially designed components for use with liquid propelling charges for any of the equipment specified in Category Code ML2.a.</i></p> <p><i>Note 2</i> <i>Category Code ML2.a. does not apply to weapons as follows:</i></p> <p>a. <i>Rifles, smooth-bore weapons and combination guns, manufactured earlier than 1938;</i></p> <p>b. <i>Reproductions of rifles, smooth-bore weapons and combination guns, the originals of which were manufactured earlier than 1890;</i></p> <p>c. <i>Guns, howitzers, cannons and mortars, manufactured earlier than 1890;</i></p> <p>d. <i>Smooth-bore weapons used for hunting or sporting purposes. These weapons must not be specially designed for military use or of the fully automatic firing type;</i></p> <p>e. <i>Smooth-bore weapons specially designed for any of the following:</i></p> <ol style="list-style-type: none"> 1. <i>Slaughtering of domestic animals;</i> 2. <i>Tranquilizing of animals;</i> 3. <i>Seismic testing;</i> 4. <i>Firing of industrial projectiles; <u>or</u></i> 5. <i>Disrupting Improvised Explosive Devices (IEDs);</i>

Category Code	Item Description
	<p style="text-align: center;"><u>N.B.</u> For disruptors, see Category Code ML4 and Category Code IA006 in Division 2 of Part 2 of this Schedule.</p> <p>f. Hand-held projectile launchers specially designed to launch tethered projectiles having no high explosive charge or communications link, to a range of less than or equal to 500 m.</p> <p>b. Smoke, gas and pyrotechnic projectors or generators, specially designed or modified for military use;</p> <p style="text-align: center;"><u>Note</u> Category Code ML2.b. does not apply to signal pistols.</p> <p>c. Weapon-sights and weapon-sight mounts, having all of the following:</p> <ol style="list-style-type: none"> 1. Specially designed for military use; <u>and</u> 2. Specially designed for weapons specified in Category Code ML2.a.; <p>d. Mountings and detachable cartridge magazines, specially designed for the weapons specified in Category Code ML2.a.</p>
ML3	<p>Ammunition and fuse setting devices, as follows, and specially designed components therefor:</p> <p>a. Ammunition for weapons specified in Category Code ML1, ML2 or ML12;</p> <p>b. Fuse setting devices specially designed for ammunition specified in Category Code ML3.a.</p> <p style="text-align: center;"><u>Note 1</u> Specially designed components specified in Category Code ML3 include:</p> <p>a. Metal or plastic fabrications such as primer anvils, bullet cups, cartridge links, rotating bands and munitions metal parts;</p>

Category Code	Item Description
	<p>b. <i>Safing and arming devices, fuses, sensors and initiation devices;</i></p> <p>c. <i>Power supplies with high one-time operational output;</i></p> <p>d. <i>Combustible cases for charges;</i></p> <p>e. <i>Submunitions including bomblets, minelets and terminally guided projectiles.</i></p> <p><u>Note 2</u> <i>Category Code ML3.a. does not apply to any of the following:</i></p> <p>a. <i>Ammunition crimped without a projectile (blank star);</i></p> <p>b. <i>Dummy ammunition with a pierced powder chamber;</i></p> <p>c. <i>Other blank and dummy ammunition, not incorporating components designed for live ammunition; <u>or</u></i></p> <p>d. <i>Components specially designed for blank or dummy ammunition, specified in this Note 2.a., b., or c.</i></p> <p><u>Note 3</u> <i>Category Code ML3.a. does not apply to cartridges specially designed for any of the following purposes:</i></p> <p>a. <i>Signalling;</i></p> <p>b. <i>Bird scaring; <u>or</u></i></p> <p>c. <i>Lighting of gas flares at oil wells.</i></p>
ML4	<p>Bombs, torpedoes, rockets, missiles, other explosive devices and charges and related equipment and accessories, as follows, and specially designed components therefor:</p> <p><u>N.B. 1</u> <i>For guidance and navigation equipment, see Category Code ML11.</i></p> <p><u>N.B. 2</u> <i>For Aircraft Missile Protection Systems (AMPS), see Category Code ML4.c.</i></p>

<i>Category Code</i>	<i>Item Description</i>
	<p>a. Bombs, torpedoes, grenades, smoke canisters, rockets, mines, missiles, depth charges, demolition-charges, demolition-devices, demolition-kits, “pyrotechnic” devices, cartridges and simulators (i.e. equipment simulating the characteristics of any of these items), specially designed for military use;</p> <p><i>Note</i> <i>Category Code ML4.a. includes:</i></p> <p>a. <i>Smoke grenades, fire bombs, incendiary bombs and explosive devices;</i></p> <p>b. <i>Missile rocket nozzles and re-entry vehicle nosetips.</i></p> <p>b. Equipment having all of the following:</p> <p>1. Specially designed for military use; <u>and</u></p> <p>2. Specially designed for ‘activities’ relating to any of the following:</p> <p>a. Items specified in Category Code ML4.a.; <u>or</u></p> <p>b. Improvised Explosive Devices (IEDs);</p> <p><i>Technical Note</i> <i>For the purpose of Category Code ML4.b.2., ‘activities’ applies to handling, launching, laying, controlling, discharging, detonating, activating, powering with one-time operational output, decoying, jamming, sweeping, detecting, disrupting or disposing.</i></p> <p><i>Note 1</i> <i>Category Code ML4.b. includes:</i></p> <p>a. <i>Mobile gas liquefying equipment capable of producing 1,000 kg or more per day of gas in liquid form;</i></p> <p>b. <i>Buoyant electric conducting cable suitable for sweeping magnetic mines.</i></p>

<i>Category Code</i>	<i>Item Description</i>
	<p data-bbox="440 325 521 354"><u>Note 2</u></p> <p data-bbox="440 367 1143 500"><i>Category Code ML4.b. does not apply to hand-held devices limited by design solely to the detection of metal objects and incapable of distinguishing between mines and other metal objects.</i></p> <p data-bbox="377 519 978 548">c. <i>Aircraft Missile Protection Systems (AMPS).</i></p> <p data-bbox="440 567 501 595"><u>Note</u></p> <p data-bbox="440 609 1143 675"><i>Category Code ML4.c. does not apply to AMPS having all of the following:</i></p> <p data-bbox="440 694 1045 723">a. <i>Any of the following missile warning sensors:</i></p> <ol data-bbox="528 742 1143 891" style="list-style-type: none"> <li data-bbox="528 742 1143 809">1. <i>Passive sensors having peak response between 100 nm - 400 nm; <u>or</u></i> <li data-bbox="528 828 1143 891">2. <i>Active pulsed Doppler missile warning sensors;</i> <p data-bbox="440 910 955 938">b. <i>Countermeasures dispensing systems;</i></p> <p data-bbox="440 957 1143 1062">c. <i>Flares, which exhibit both a visible signature and an infrared signature, for decoying surface-to-air missiles; <u>and</u></i></p> <p data-bbox="440 1081 1143 1148">d. <i>Installed on “civil aircraft” and having all of the following:</i></p> <ol data-bbox="528 1167 1143 1538" style="list-style-type: none"> <li data-bbox="528 1167 1143 1300">1. <i>The AMPS is only operable in a specific “civil aircraft” in which the specific AMPS is installed and for which any of the following has been issued:</i> <ol data-bbox="588 1319 1143 1538" style="list-style-type: none"> <li data-bbox="588 1319 1143 1424">a. <i>A civil Type Certificate issued by civil aviation authorities of one or more “participating states”; <u>or</u></i> <li data-bbox="588 1443 1143 1538">b. <i>An equivalent document recognised by the International Civil Aviation Organisation (ICAO);</i>

<i>Category Code</i>	<i>Item Description</i>
ML5	<p data-bbox="525 325 1143 392">2. <i>The AMPS employs protection to prevent unauthorised access to “software”; and</i></p> <p data-bbox="525 411 1143 540">3. <i>The AMPS incorporates an active mechanism that forces the system not to function when it is removed from the “civil aircraft” in which it was installed.</i></p> <p data-bbox="377 611 1143 744">Fire control, and related alerting and warning equipment, and related systems, test and alignment and countermeasure equipment, as follows, specially designed for military use, and specially designed components and accessories therefor:</p> <p data-bbox="377 763 1143 830">a. <i>Weapon-sights, bombing computers, gun laying equipment and weapon control systems;</i></p> <p data-bbox="377 849 1143 982">b. <i>Target acquisition, designation, range-finding, surveillance or tracking systems; detection, data fusion, recognition or identification equipment; and sensor integration equipment;</i></p> <p data-bbox="377 1001 1143 1068">c. <i>Countermeasure equipment for items specified in Category Code ML5.a. or ML5.b.;</i></p> <p data-bbox="438 1087 498 1115"><u><i>Note</i></u></p> <p data-bbox="438 1125 1143 1191"><i>For the purpose of Category Code ML5.c., countermeasure equipment includes detection equipment.</i></p> <p data-bbox="377 1210 1143 1306">d. <i>Field test or alignment equipment, specially designed for items specified in Category Code ML5.a., ML5.b. or ML5.c.</i></p>
ML6	<p data-bbox="377 1382 915 1410">Ground vehicles and components, as follows:</p> <p data-bbox="377 1429 431 1458"><u><i>N.B.</i></u></p> <p data-bbox="377 1467 1143 1534"><i>For guidance and navigation equipment, see Category Code ML11.</i></p> <p data-bbox="377 1553 1143 1620">a. <i>Ground vehicles and components therefor, specially designed or modified for military use;</i></p> <p data-bbox="438 1639 626 1667"><u><i>Technical Note</i></u></p> <p data-bbox="438 1677 1143 1744"><i>For the purpose of Category Code ML6.a., the term ground vehicles includes trailers.</i></p>

<i>Category Code</i>	<i>Item Description</i>
	<p>b. Other ground vehicles and components, as follows:</p> <ol style="list-style-type: none"> 1. Vehicles having all of the following: <ol style="list-style-type: none"> a. Manufactured or fitted with materials or components to provide ballistic protection to level III (NIJ 0108.01, September 1985, or comparable national standard) or better; b. A transmission to provide drive to both front and rear wheels simultaneously, including those vehicles having additional wheels for load bearing purposes whether driven or not; c. Gross Vehicle Weight Rating (GVWR) greater than 4,500 kg; <u>and</u> d. Designed or modified for off-road use; 2. Components having all of the following: <ol style="list-style-type: none"> a. Specially designed for vehicles specified in Category Code ML6.b.1.; <u>and</u> b. Providing ballistic protection to level III (NIJ 0108.01, September 1985, or comparable national standard) or better. <p><u>N.B.</u> <i>See also Category Code ML13.a.</i></p> <p><u>Note 1</u> <i>Category Code ML6.a. includes:</i></p> <ol style="list-style-type: none"> a. <i>Tanks and other military armed vehicles and military vehicles fitted with mountings for arms or equipment for mine laying or the launching of munitions specified in Category Code ML4;</i> b. <i>Armoured vehicles;</i> c. <i>Amphibious and deep water fording vehicles;</i> d. <i>Recovery vehicles and vehicles for towing or transporting ammunition or weapon systems and associated load handling equipment.</i>

<i>Category Code</i>	<i>Item Description</i>
	<p><u>Note 2</u> <i>Under Category Code ML6.a., modification of a ground vehicle for military use entails a structural, electrical or mechanical change involving one or more components that are specially designed for military use. Such components include:</i></p> <ol style="list-style-type: none"> <i>a. Pneumatic tyre casings of a kind specially designed to be bullet-proof;</i> <i>b. Armoured protection of vital parts (e.g. fuel tanks or vehicle cabs);</i> <i>c. Special reinforcements or mountings for weapons;</i> <i>d. Black-out lighting.</i> <p><u>Note 3</u> <i>Category Code ML6 does not apply to civil vehicles designed or modified for transporting money or valuables.</i></p> <p><u>Note 4</u> <i>Category Code ML6 does not apply to vehicles that meet all of the following:</i></p> <ol style="list-style-type: none"> <i>a. Were manufactured before 1946;</i> <i>b. Do not have items specified in any part of this Division and manufactured after 1945, except for reproductions of original components or accessories for the vehicle; <u>and</u></i> <i>c. Do not incorporate weapons specified in Category Code ML1, ML2 or ML4 unless they are inoperable and incapable of discharging a projectile.</i>
ML7	<p>Chemical or biological toxic agents, “riot control agents”, radioactive materials, related equipment, components and materials, as follows:</p> <ol style="list-style-type: none"> a. Biological agents or radioactive materials, “adapted for use in war” to produce casualties in humans or animals, degrade equipment or damage crops or the environment;

<i>Category Code</i>	<i>Item Description</i>
	<p>b. Chemical warfare (CW) agents, including:</p> <ol style="list-style-type: none"> 1. CW nerve agents: <ol style="list-style-type: none"> a. O-Alkyl (equal to or less than C₁₀, including cycloalkyl) alkyl (Methyl, Ethyl, n-Propyl or Isopropyl)-phosphonofluoridates, such as: Sarin (GB):O-Isopropyl methylphosphonofluoridate (107-44-8); <u>and</u> Soman (GD):O-Pinacolyl methylphosphonofluoridate (96-64-0); b. O-Alkyl (equal to or less than C₁₀, including cycloalkyl) N,N-dialkyl (Methyl, Ethyl, n-Propyl or Isopropyl) phosphoramidocyanidates, such as: Tabun (GA):O-Ethyl N,N-dimethylphosphoramidocyanidate (77-81-6); c. O-Alkyl (H or equal to or less than C₁₀, including cycloalkyl) S-2-dialkyl (Methyl, Ethyl, n-Propyl or Isopropyl)-aminoethyl alkyl (Methyl, Ethyl, n-Propyl or Isopropyl) phosphonothiolates and corresponding alkylated and protonated salts, such as: VX: O-Ethyl S-2-diisopropylaminoethyl methyl phosphonothiolate (50782-69-9); 2. CW vesicant agents: <ol style="list-style-type: none"> a. Sulphur mustards, such as: <ol style="list-style-type: none"> 1. 2-Chloroethylchloromethylsulphide (2625-76-5); 2. Bis(2-chloroethyl) sulphide (505-60-2); 3. Bis(2-chloroethylthio) methane (63869-13-6); 4. 1,2-bis (2-chloroethylthio) ethane (3563-36-8); 5. 1,3-bis (2-chloroethylthio) -n-propane (63905-10-2);

<i>Category Code</i>	<i>Item Description</i>
	6. 1,4-bis (2-chloroethylthio) -n-butane (142868-93-7);
	7. 1,5-bis (2-chloroethylthio) -n-pentane (142868-94-8);
	8. Bis (2-chloroethylthiomethyl) ether (63918-90-1);
	9. Bis (2-chloroethylthioethyl) ether (63918-89-8);
	b. Lewisites, such as:
	1. 2-chlorovinyl dichloroarsine (541-25-3);
	2. Tris (2-chlorovinyl) arsine (40334-70-1);
	3. Bis (2-chlorovinyl) chloroarsine (40334-69-8);
	c. Nitrogen mustards, such as:
	1. HN1: bis (2-chloroethyl) ethylamine (538-07-8);
	2. HN2: bis (2-chloroethyl) methylamine (51-75-2);
	3. HN3: tris (2-chloroethyl) amine (555-77-1);
	3. CW incapacitating agents, such as:
	a. 3-Quinuclidinyl benzilate (BZ) (6581-06-2);
	4. CW defoliants, such as
	a. Butyl 2-chloro-4-fluorophenoxyacetate (LNF);
	b. 2,4,5-trichlorophenoxyacetic acid (93-76-5) mixed with 2,4-dichlorophenoxyacetic acid (94-75-7) (Agent Orange (39277-47-9));

<i>Category Code</i>	<i>Item Description</i>
	<p>c. CW binary precursors and key precursors, as follows:</p> <ol style="list-style-type: none"> 1. Alkyl (Methyl, Ethyl, n-Propyl or Isopropyl) Phosphonyl Difluorides, such as: DF: Methyl Phosphonyldifluoride (676-99-3); 2. O-Alkyl (H or equal to or less than C₁₀, including cycloalkyl) O-2-dialkyl (Methyl, Ethyl, n-Propyl or Isopropyl)-aminoethyl alkyl (Methyl, Ethyl, n-Propyl or Isopropyl) phosphonites and corresponding alkylated and protonated salts, such as: QL: O-Ethyl O-2-di-isopropylaminoethyl methylphosphonite (57856-11-8); 3. Chlorosarin: O-Isopropyl methylphosphonochloridate (1445-76-7); 4. Chlorosoman: O-Pinacolyl methylphosphonochloridate (7040-57-5); <p>d. “Riot control agents”, active constituent chemicals and combinations thereof, including:</p> <ol style="list-style-type: none"> 1. α-Bromobenzeneacetonitrile, (Bromobenzyl cyanide) (CA) (5798-79-8); 2. [(2-chlorophenyl) methylene] propanedinitrile, (o-Chlorobenzylidenemalononitrile) (CS) (2698-41-1); 3. 2-Chloro-1-phenylethanone, Phenylacetyl chloride (ω-chloroacetophenone) (CN) (532-27-4); 4. Dibenz-(b,f)-1,4-oxazepine, (CR) (257-07-8); 5. 10-Chloro-5,10-dihydrophenarsazine, (Phenarsazine chloride), (Adamsite), (DM) (578-94-9); 6. N-Nonanoylmorpholine, (MPA) (5299-64-9); <p><i>Note 1</i> Category Code ML7.d. does not apply to “riot control agents” individually packaged for personal self-defence purposes.</p>

<i>Category Code</i>	<i>Item Description</i>
	<p data-bbox="440 325 521 354"><u>Note 2</u></p> <p data-bbox="440 367 1143 500"><i>Category Code ML7.d. does not apply to active constituent chemicals, and combinations thereof, identified and packaged for food production or medical purposes.</i></p> <p data-bbox="377 519 1143 649">e. Equipment, specially designed or modified for military use, designed or modified for the dissemination of any of the following, and specially designed components therefor:</p> <ol data-bbox="440 668 1143 820" style="list-style-type: none"> <li data-bbox="440 668 1143 734">1. Materials or agents specified in Category Code ML7.a., ML7.b. or ML7.d.; <u>or</u> <li data-bbox="440 753 1143 820">2. CW agents made up of precursors specified in Category Code ML7.c.; <p data-bbox="377 839 1143 934">f. Protective and decontamination equipment, specially designed or modified for military use, components and chemical mixtures, as follows:</p> <ol data-bbox="440 953 1143 1391" style="list-style-type: none"> <li data-bbox="440 953 1143 1087">1. Equipment designed or modified for defence against materials specified in Category Code ML7.a., ML7.b. or ML7.d., and specially designed components therefor; <li data-bbox="440 1106 1143 1239">2. Equipment designed or modified for decontamination of objects contaminated with materials specified in Category Code ML7.a. or ML7.b., and specially designed components therefor; <li data-bbox="440 1258 1143 1391">3. Chemical mixtures specially developed or formulated for the decontamination of objects contaminated with materials specified in Category Code ML7.a. or ML7.b.; <p data-bbox="440 1410 501 1439"><u>Note</u></p> <p data-bbox="440 1452 848 1481"><i>Category Code ML7.f.1. includes:</i></p> <ol data-bbox="440 1500 1143 1624" style="list-style-type: none"> <li data-bbox="440 1500 1143 1566">a. <i>Air conditioning units specially designed or modified for nuclear, biological or chemical filtration;</i> <li data-bbox="440 1586 740 1614">b. <i>Protective clothing.</i>

<i>Category Code</i>	<i>Item Description</i>
	<p data-bbox="440 325 494 354"><u><i>N.B.</i></u></p> <p data-bbox="440 369 1143 464"><i>For civil gas masks, protective and decontamination equipment, see also Category Code IA004 in Division 2 of Part 2 of this Schedule.</i></p> <p data-bbox="377 487 1143 616">g. Equipment, specially designed or modified for military use designed or modified for the detection or identification of materials specified in Category Code ML7.a., ML7.b. or ML7.d., and specially designed components therefor;</p> <p data-bbox="440 639 494 668"><u><i>Note</i></u></p> <p data-bbox="440 683 1143 740"><i>Category Code ML7.g. does not apply to personal radiation monitoring dosimeters.</i></p> <p data-bbox="440 763 494 792"><u><i>N.B.</i></u></p> <p data-bbox="440 807 1143 864"><i>See also Category Code IA004 in Division 2 of Part 2 of this Schedule.</i></p> <p data-bbox="377 887 1143 1016">h. “Biopolymers” specially designed or processed for the detection or identification of CW agents specified in Category Code ML7.b., and the cultures of specific cells used to produce them;</p> <p data-bbox="377 1039 1143 1096">i. “Biocatalysts” for the decontamination or degradation of CW agents, and biological systems therefor, as follows:</p> <ol data-bbox="440 1125 1143 1593" style="list-style-type: none"> <li data-bbox="440 1125 1143 1287">1. “Biocatalysts” specially designed for the decontamination or degradation of CW agents specified in Category Code ML7.b., and resulting from directed laboratory selection or genetic manipulation of biological systems; <li data-bbox="440 1309 1143 1593">2. Biological systems containing the genetic information specific to the production of “biocatalysts” specified in Category Code ML7.i.1., as follows: <ol data-bbox="525 1462 848 1593" style="list-style-type: none"> <li data-bbox="525 1462 848 1490">a. “Expression vectors”; <li data-bbox="525 1513 686 1542">b. Viruses; <li data-bbox="525 1565 780 1593">c. Cultures of cells.

<i>Category Code</i>	<i>Item Description</i>
	<p><u>Note 1</u></p> <p><i>Category Codes ML7.b. and ML7.d. do not apply to the following:</i></p> <ul style="list-style-type: none"> <i>a. Cyanogen chloride (506-77-4);</i> <i>b. Hydrocyanic acid (74-90-8);</i> <i>c. Chlorine (7782-50-5);</i> <i>d. Carbonyl chloride (phosgene) (75-44-5);</i> <i>e. Diphosgene (trichloromethyl-chloroformate) (503-38-8);</i> <i>f. Not used;</i> <i>g. Xylyl bromide, ortho: (89-92-9), meta: (620-13-3), para: (104-81-4);</i> <i>h. Benzyl bromide (100-39-0);</i> <i>i. Benzyl iodide (620-05-3);</i> <i>j. Bromo acetone (598-31-2);</i> <i>k. Cyanogen bromide (506-68-3);</i> <i>l. Bromo methylethylketone (816-40-0);</i> <i>m. Chloro acetone (78-95-5);</i> <i>n. Ethyl iodoacetate (623-48-3);</i> <i>o. Iodo acetone (3019-04-3);</i> <i>p. Chloropicrin (76-06-2).</i> <p><u>Note 2</u></p> <p><i>The cultures of cells and biological systems specified in Category Codes ML7.h. and ML7.i.2. are exclusive and these sub-items do not apply to cells or biological systems for civil purposes, such as agricultural, pharmaceutical, medical, veterinary, environmental, waste management, or in the food industry.</i></p>

<i>Category Code</i>	<i>Item Description</i>
ML8	<p>“Energetic materials” and related substances, as follows:</p> <p><u>N.B. 1</u> <i>See also Category Code IC011 in Division 2 of Part 2 of this Schedule.</i></p> <p><u>N.B. 2</u> <i>For charges and devices, see Category Code ML4 and Category Code IA008 in Division 2 of Part 2 of this Schedule.</i></p> <p><u>Technical Notes</u></p> <ol style="list-style-type: none"> 1. <i>For the purpose of Category Code ML8, excluding Category Code ML8.c.11. or ML8.c.12., ‘mixture’ refers to a composition of two or more substances with at least one substance being listed in the sub-items under this Category Code.</i> 2. <i>Any substance listed in the sub-items under Category Code ML8 is treated as coming within the description of that substance even when utilised in an application other than that indicated. (e.g. TAGN is predominantly used as an explosive but can also be used either as a fuel or an oxidiser.)</i> 3. <i>For the purpose of Category Code ML8, particle size is the mean particle diameter on a weight or volume basis. International or equivalent national standards will be used in sampling and determining particle size.</i> <p>a. “Explosives” as follows, and ‘mixtures’ thereof:</p> <ol style="list-style-type: none"> 1. ADNBF (aminodinitrobenzofuroxan or 7-amino-4,6-dinitrobenzofurazane-1-oxide) (97096-78-1); 2. BNCP (cis-bis (5-nitrotetrazolato) tetra amine-cobalt (III) perchlorate) (117412-28-9); 3. CL-14 (diamino dinitrobenzofuroxan or 5,7-diamino-4,6-dinitrobenzofurazane-1-oxide) (117907-74-1); 4. CL-20 (HNIW or Hexanitrohexaazaisowurtzitane) (135285-90-4); chlathrates of CL-20 (see also Category Codes ML8.g.3. and g.4. for its “precursors”);

<i>Category Code</i>	<i>Item Description</i>
	5. CP (2-(5-cyanotetrazolato) penta amine-cobalt (III) perchlorate) (70247-32-4);
	6. DADE (1,1-diamino-2,2-dinitroethylene, FOX7) (145250-81-3);
	7. DATB (diaminotrinitrobenzene) (1630-08-6);
	8. DDFP (1,4-dinitrodifurazanopiperazine);
	9. DDPO (2,6-diamino-3,5-dinitropyrazine-1-oxide, PZO) (194486-77-6);
	10. DIPAM (3,3'-diamino-2,2',4,4',6,6'-hexanitrobiphenyl or dipicramide) (17215-44-0);
	11. DNGU (DINGU or dinitroglycoluril) (55510-04-8);
	12. Furazans as follows: <ul style="list-style-type: none"> a. DAAOF (DAAF, DAAFox, or diaminoazoxyfurazan); b. DAAzF (diaminoazofurazan) (78644-90-3);
	13. HMX and derivatives (see also Category Code ML8.g.5. for its “precursors”), as follows: <ul style="list-style-type: none"> a. HMX (Cyclotetramethylenetetranitramine, octahydro-1,3,5,7-tetranitro-1,3,5,7-tetrazine, 1,3,5,7-tetranitro-1,3,5,7-tetraza-cyclooctane, octogen or octogene) (2691-41-0); b. Difluoroaminated analogs of HMX; c. K-55 (2,4,6,8-tetranitro-2,4,6,8-tetraazabicyclo [3,3,0]-octanone-3, tetranitrosemiglycouril or keto-bicyclic HMX) (130256-72-3);
	14. HNAD (hexanitroadamantane) (143850-71-9);
	15. HNS (hexanitrostilbene) (20062-22-0);
	16. Imidazoles as follows: <ul style="list-style-type: none"> a. BNNII (Octahydro-2,5-bis(nitroimino)imidazo [4,5-d]imidazole); b. DNI (2,4-dinitroimidazole) (5213-49-0); c. FDIA (1-fluoro-2,4-dinitroimidazole);

<i>Category Code</i>	<i>Item Description</i>
	d. NTDNIA (N-(2-nitrotriazolo)-2,4-dinitroimidazole);
	e. PTIA (1-picryl-2,4,5-trinitroimidazole);
	17. NTNMMH (1-(2-nitrotriazolo)-2-dinitromethylene hydrazine);
	18. NTO (ONTA or 3-nitro-1,2,4-triazol-5-one) (932-64-9);
	19. Polynitrocubanes with more than four nitro groups;
	20. PYX (2,6-Bis(picrylamino)-3,5-dinitropyridine) (38082-89-2);
	21. RDX and derivatives, as follows:
	a. RDX (cyclotrimethylenetrinitramine, cyclonite, T4, hexahydro-1,3,5-trinitro-1,3,5-triazine, 1,3,5-trinitro-1,3,5-triazacyclohexane, hexogen or hexogene) (121-82-4);
	b. Keto-RDX (K-6 or 2,4,6-trinitro-2,4,6-triazacyclohexanone) (115029-35-1);
	22. TAGN (triaminoguanidinenitrate) (4000-16-2);
	23. TATB (triaminotrinitrobenzene) (3058-38-6) (see also Category Code ML8.g.7. for its “precursors”);
	24. TEDDZ (3,3,7,7-tetrabis(difluoroamine) octahydro-1,5-dinitro-1,5-diazocine);
	25. Tetrazoles as follows:
	a. NTAT (nitrotriazol aminotetrazole);
	b. NTNT (1-N-(2-nitrotriazolo)-4-nitrotetrazole);
	26. Tetryl (trinitrophenylmethylnitramine) (479-45-8);
	27. TNAD (1,4,5,8-tetranitro-1,4,5,8-tetraazadecalin) (135877-16-6) (see also Category Code ML8.g.6. for its “precursors”);
	28. TNAZ (1,3,3-trinitroazetidine) (97645-24-4) (see also Category Code ML8.g.2. for its “precursors”);

<i>Category Code</i>	<i>Item Description</i>
	<p>29. TNGU (SORGUYL or tetranitroglycoluril) (55510-03-7);</p> <p>30. TNP (1,4,5,8-tetranitro-pyridazino[4,5-d]pyridazine) (229176-04-9);</p> <p>31. Triazines as follows:</p> <ul style="list-style-type: none"> a. DNAM (2-oxy-4,6-dinitroamino-s-triazine) (19899-80-0); b. NNHT (2-nitroimino-5-nitro-hexahydro-1,3,5-triazine) (130400-13-4); <p>32. Triazoles as follows:</p> <ul style="list-style-type: none"> a. 5-azido-2-nitrotriazole; b. ADHTDN (4-amino-3,5-dihydrazino-1,2,4-triazole dinitramide) (1614-08-0); c. ADNT (1-amino-3,5-dinitro-1,2,4-triazole); d. BDNTA ((bis-dinitrotriazole)amine); e. DBT (3,3'-dinitro-5,5-bi-1,2,4-triazole) (30003-46-4); f. DNBT (dinitrobistriazole) (70890-46-9); g. Not used; h. NTDNT (1-N-(2-nitrotriazolo) 3,5-dinitrotriazole); i. PDNT (1-picryl-3,5-dinitrotriazole); j. TACOT (tetranitrobenzotriazolobenzotriazole) (25243-36-1); <p>33. Explosives not listed elsewhere in Category Code ML8.a. and having any of the following:</p> <ul style="list-style-type: none"> a. Detonation velocity exceeding 8,700 m/s, at maximum density; <u>or</u> b. Detonation pressure exceeding 34 GPa (340 kbar); <p>34. Not used;</p>

<i>Category Code</i>	<i>Item Description</i>
	<p>35. DNAN (2,4-dinitroanisole) (119-27-7);</p> <p>36. TEX (4,10-Dinitro-2,6,8,12-tetraoxa-4,10-diazaisowurtzitane);</p> <p>37. GUDN (Guanylurea dinitramide) FOX-12 (217464-38-5);</p> <p>38. Tetrazines as follows:</p> <ol style="list-style-type: none"> a. BTAT (Bis(2,2,2-trinitroethyl)-3,6-diaminotetrazine); b. LAX-112 (3,6-diamino-1,2,4,5-tetrazine-1,4-dioxide); <p>39. Energetic ionic materials melting between 343 K (70°C) and 373 K (100°C) and with detonation velocity exceeding 6,800 m/s or detonation pressure exceeding 18 GPa (180 kbar);</p> <p>40. BTNEN (Bis(2,2,2-trinitroethyl)-nitramine) (19836-28-3);</p> <p><i>Note</i> <i>Category Code ML8.a. includes ‘explosive co-crystals’.</i></p> <p><i>Technical Note</i> <i>An ‘explosive co-crystal’ is a solid material consisting of an ordered three dimensional arrangement of two or more explosive molecules, where at least one is specified in Category Code ML8.a.</i></p> <p>b. “Propellants” as follows:</p> <ol style="list-style-type: none"> 1. Any solid “propellant” with a theoretical specific impulse (under standard conditions) of more than: <ol style="list-style-type: none"> a. 240 seconds for non-metallised, non-halogenised “propellant”; b. 250 seconds for non-metallised, halogenised “propellant”; <u>or</u> c. 260 seconds for metallised “propellant”; 2. Not used;

<i>Category Code</i>	<i>Item Description</i>
	<ol style="list-style-type: none"> 3. "Propellants" having a force constant of more than 1,200 kJ/kg; 4. "Propellants" that can sustain a steady-state linear burning rate of more than 38 mm/s under standard conditions (as measured in the form of an inhibited single strand) of 6.89 MPa (68.9 bar) pressure and 294 K (21°C); 5. Elastomer Modified Cast Double Base (EMCDB) "propellants" with extensibility at maximum stress of more than 5% at 233 K (-40°C); 6. Any "propellant" containing substances specified in Category Code ML8.a.; 7. "Propellants", not specified elsewhere in any part of this Division, specially designed for military use; <p>c. "Pyrotechnics", fuels and related substances, as follows, and 'mixtures' thereof:</p> <ol style="list-style-type: none"> 1. "Aircraft" fuels specially formulated for military purposes; <p><i>Note</i> <i>"Aircraft" fuels specified in Category Code ML8.c.1. are finished products, not their constituents.</i></p> <ol style="list-style-type: none"> 2. Alane (aluminium hydride) (7784-21-6); 3. Carboranes; decaborane (17702-41-9); pentaboranes (19624-22-7 and 18433-84-6) and their derivatives; 4. Hydrazine and derivatives, as follows (see also Category Codes ML8.d.8. and d.9. for oxidising hydrazine derivatives): <ol style="list-style-type: none"> a. Hydrazine (302-01-2) in concentrations of 70% or more; b. Monomethyl hydrazine (60-34-4); c. Symmetrical dimethyl hydrazine (540-73-8); d. Unsymmetrical dimethyl hydrazine (57-14-7);

<i>Category Code</i>	<i>Item Description</i>
	<p data-bbox="502 325 561 354"><u>Note</u></p> <p data-bbox="502 367 1142 462"><i>Category Code ML8.c.4.a. does not apply to hydrazine ‘mixtures’ specially formulated for corrosion control.</i></p> <p data-bbox="440 483 1142 649">5. Metal fuels, fuel ‘mixtures’ or “pyrotechnic” ‘mixtures’, in particle form whether spherical, atomised, spheroidal, flaked or ground, manufactured from material consisting of 99% or more of any of the following:</p> <p data-bbox="525 670 1080 698">a. Metals as follows and ‘mixtures’ thereof:</p> <ol data-bbox="592 719 1142 902" style="list-style-type: none"> <li data-bbox="592 719 1142 786">1. Beryllium (7440-41-7) in particle sizes of less than 60 µm; <li data-bbox="592 807 1142 902">2. Iron powder (7439-89-6) with particle size of 3 µm or less produced by reduction of iron oxide with hydrogen; <p data-bbox="525 923 1107 952">b. ‘Mixtures’ containing any of the following:</p> <ol data-bbox="592 972 1142 1220" style="list-style-type: none"> <li data-bbox="592 972 1142 1068">1. Zirconium (7440-67-7), magnesium (7439-95-4) or alloys of these in particle sizes of less than 60 µm; <u>or</u> <li data-bbox="592 1089 1142 1220">2. Boron (7440-42-8) or boron carbide (12069-32-8) fuels of 85% purity or higher and particle sizes of less than 60 µm; <p data-bbox="502 1241 585 1269"><u>Note 1</u></p> <p data-bbox="502 1283 1142 1416"><i>Category Code ML8.c.5. applies to “explosives” and fuels, whether or not the metals or alloys are encapsulated in aluminium, magnesium, zirconium, or beryllium.</i></p> <p data-bbox="502 1437 585 1466"><u>Note 2</u></p> <p data-bbox="502 1479 1142 1677"><i>Category Code ML8.c.5.b. only applies to metal fuels in particle form when they are mixed with other substances to form a ‘mixture’ formulated for military purposes such as liquid “propellant” slurries, solid “propellants”, or “pyrotechnic” ‘mixtures’.</i></p>

<i>Category Code</i>	<i>Item Description</i>
	<p data-bbox="505 325 585 354"><u>Note 3</u></p> <p data-bbox="505 367 1143 464"><i>Category Code ML8.c.5.b.2. does not apply to boron and boron carbide enriched with boron-10 (20% or more of total boron-10 content).</i></p> <ol style="list-style-type: none"> <li data-bbox="440 485 1143 616">6. Military materials, containing thickeners for hydrocarbon fuels, specially formulated for use in flame throwers or incendiary munitions, such as metal stearates (e.g. octal (637-12-7)) or palmitates; <li data-bbox="440 637 1143 734">7. Perchlorates, chlorates and chromates, composited with powdered metal or other high energy fuel components; <li data-bbox="440 755 1143 887">8. Spherical or spheroidal aluminium powder (7429-90-5) with a particle size of 60 µm or less and manufactured from material with an aluminium content of 99% or more; <li data-bbox="440 908 1143 967">9. Titanium subhydride (TiH_n) of stoichiometry equivalent to n = 0.65-1.68; <li data-bbox="440 988 1143 1428">10. Liquid high energy density fuels not specified in Category Code ML8.c.1., as follows: <ol style="list-style-type: none"> <li data-bbox="528 1075 1143 1207">a. Mixed fuels, that incorporate both solid and liquid fuels (e.g. boron slurry), having a mass-based energy density of 40 MJ/kg or greater; <li data-bbox="528 1228 1143 1428">b. Other high energy density fuels and fuel additives (e.g. cubane, ionic solutions, JP-7, JP-10), having a volume-based energy density of 37.5 GJ per cubic metre or greater, measured at 293 K (20°C) and one atmosphere (101.325 kPa) pressure; <p data-bbox="590 1448 650 1477"><u>Note</u></p> <p data-bbox="590 1490 1143 1624"><i>Category Code ML8.c.10.b. does not apply to JP-4, JP-8, fossil refined fuels or biofuels, or fuels for engines certified for used in civil aviation.</i></p>

<i>Category Code</i>	<i>Item Description</i>
	<p>11. “Pyrotechnic” and pyrophoric materials, as follows:</p> <ol style="list-style-type: none"> a. “Pyrotechnic” and pyrophoric materials specifically formulated to enhance or control the production of radiated energy in any part of the IR spectrum; b. Mixtures of magnesium, polytetrafluoroethylene (PTFE) and a vinylidene difluoride-hexafluoropropylene copolymer (e.g. MTV); <p>12. Fuel mixtures, “pyrotechnic” mixtures or “energetic materials”, not specified elsewhere in Category Code ML8, having all of the following:</p> <ol style="list-style-type: none"> a. Containing greater than 0.5% of particles of any of the following: <ol style="list-style-type: none"> 1. Aluminium; 2. Beryllium; 3. Boron; 4. Zirconium; 5. Magnesium; <u>or</u> 6. Titanium; b. Particles specified in Category Code ML8.c.12.a. with a size less than 200 nm in any direction; <u>and</u> c. Particles specified in Category Code ML8.c.12.a. with a metal content of 60% or greater; <p>d. Oxidisers as follows, and ‘mixtures’ thereof:</p> <ol style="list-style-type: none"> 1. ADN (ammonium dinitramide or SR 12) (140456-78-6); 2. AP (ammonium perchlorate) (7790-98-9);

<i>Category Code</i>	<i>Item Description</i>
	<p>3. Compounds composed of fluorine and any of the following:</p> <ol style="list-style-type: none"> a. Other halogens; b. Oxygen; <u>or</u> c. Nitrogen; <p><u>Note 1</u> <i>Category Code ML8.d.3. does not apply to chlorine trifluoride (7790-91-2).</i></p> <p><u>Note 2</u> <i>Category Code ML8.d.3. does not apply to nitrogen trifluoride (7783-54-2) in its gaseous state.</i></p> <p>4. DNAD (1,3-dinitro-1,3-diazetidine) (78246-06-7);</p> <p>5. HAN (hydroxylammonium nitrate) (13465-08-2);</p> <p>6. HAP (hydroxylammonium perchlorate) (15588-62-2);</p> <p>7. HNF (hydrazinium nitroformate) (20773-28-8);</p> <p>8. Hydrazine nitrate (37836-27-4);</p> <p>9. Hydrazine perchlorate (27978-54-7);</p> <p>10. Liquid oxidisers comprised of or containing inhibited red fuming nitric acid (IRFNA) (8007-58-7);</p> <p><u>Note</u> <i>Category Code ML8.d.10. does not apply to non-inhibited fuming nitric acid.</i></p> <p>e. Binders, plasticisers, monomers and polymers, as follows:</p> <ol style="list-style-type: none"> 1. AMMO (azidomethylmethyloxetane and its polymers) (90683-29-7) (see also Category Code ML8.g.1. for its “precursors”); 2. BAMO (3,3-bis(azidomethyl)oxetane and its polymers) (17607-20-4) (see also Category Code ML8.g.1. for its “precursors”); 3. BDNPA (bis (2,2-dinitropropyl)acetal) (5108-69-0); 4. BDNPF (bis (2,2-dinitropropyl)formal) (5917-61-3);

<i>Category Code</i>	<i>Item Description</i>
	<ol style="list-style-type: none"> 5. BTTN (butanetrioltrinitrate) (6659-60-5) (see also Category Code ML8.g.8. for its “precursors”); 6. Energetic monomers, plasticisers or polymers, specially formulated for military use and containing any of the following: <ol style="list-style-type: none"> a. Nitro groups; b. Azido groups; c. Nitrate groups; d. Nitraza groups; <u>or</u> e. Difluoroamino groups; 7. FAMAO (3-difluoroaminomethyl-3-azidomethyl oxetane) and its polymers; 8. FEFO (bis-(2-fluoro-2,2-dinitroethyl) formal) (17003-79-1); 9. FPF-1 (poly-2,2,3,3,4,4-hexafluoropentane-1,5-diol formal) (376-90-9); 10. FPF-3 (poly-2,4,4,5,5,6,6-heptafluoro-2-trifluoromethyl-3-oxaheptane-1,7-diol formal); 11. GAP (glycidylazide polymer) (143178-24-9) and its derivatives; 12. HTPB (hydroxyl terminated polybutadiene) with a hydroxyl functionality equal to or greater than 2.2 and less than or equal to 2.4, a hydroxyl value of less than 0.77 meq/g, and a viscosity at 30°C of less than 47 poise (69102-90-5); 13. Alcohol functionalised poly(epichlorohydrin) with a molecular weight of less than 10,000, as follows: <ol style="list-style-type: none"> a. Poly(epichlorohydrindiol); b. Poly(epichlorohydrintriol); 14. NENAs (nitrate ethylnitramine compounds) (17096-47-8, 85068-73-1, 82486-83-7, 82486-82-6 and 85954-06-9); 15. PGN (poly-GLYN, polyglycidyl nitrate or poly(nitratomethyl oxirane)) (27814-48-8);

<i>Category Code</i>	<i>Item Description</i>
	<ol style="list-style-type: none"> 16. Poly-NIMMO (poly nitratomethylmethyloxetane), poly-NMMO or (poly(3-Nitratomethyl-3-methyloxetane)) (84051-81-0); 17. Polynitroorthocarbonates; 18. TVOPA (1,2,3-tris[1,2-bis(difluoroamino)ethoxy] propane or tris vinoxyl propane adduct) (53159-39-0); 19. 4,5 diazidomethyl-2-methyl-1,2,3-triazole (iso-DAMTR); 20. PNO (Poly(3-nitrato oxetane)); <p>f. "Additives" as follows:</p> <ol style="list-style-type: none"> 1. Basic copper salicylate (62320-94-9); 2. BHEGA (bis-(2-hydroxyethyl) glycolamide) (17409-41-5); 3. BNO (butadienenitrileoxide); 4. Ferrocene derivatives, as follows: <ol style="list-style-type: none"> a. Butacene (125856-62-4); b. Catocene (2,2-bis-ethylferrocenyl propane) (37206-42-1); c. Ferrocene carboxylic acids and ferrocene carboxylic acid esters; d. n-butyl ferrocene (31904-29-7); e. Other adducted polymer ferrocene derivatives not specified elsewhere in Category Code ML8.f.4.; f. Ethyl ferrocene (1273-89-8); g. Propyl ferrocene; h. Pentyl ferrocene (1274-00-6); i. Dicyclopentyl ferrocene; j. Dicyclohexyl ferrocene; k. Diethyl ferrocene (1273-97-8); l. Dipropyl ferrocene;

<i>Category Code</i>	<i>Item Description</i>
	<ul style="list-style-type: none"> m. Dibutyl ferrocene (1274-08-4); n. Dihexyl ferrocene (93894-59-8); o. Acetyl ferrocene (1271-55-2)/1,1'-diacetyl ferrocene (1273-94-5);
	5. Lead beta-resorcyate (20936-32-7);
	6. Lead citrate (14450-60-3);
	7. Lead-copper chelates of beta-resorcyate or salicylates (68411-07-4);
	8. Lead maleate (19136-34-6);
	9. Lead salicylate (15748-73-9);
	10. Lead stannate (12036-31-6);
	11. MAPO (tris-1-(2-methyl)aziridinyl phosphine oxide) (57-39-6); BOBBA 8 (bis(2-methyl aziridinyl) 2-(2-hydroxypropanoxy) propylamino phosphine oxide); and other MAPO derivatives;
	12. Methyl BAPO (bis(2-methyl aziridinyl) methylamino phosphine oxide) (85068-72-0);
	13. N-methyl-p-nitroaniline (100-15-2);
	14. 3-Nitroazirane-1,5-pentane diisocyanate (7406-61-9);
	15. Organo-metallic coupling agents as follows: <ul style="list-style-type: none"> a. Neopentyl[diallyl]oxy, tri[dioctyl]phosphato-titanate (103850-22-2); also known as titanium IV, 2,2[bis 2-propenolato-methyl, butanolato, tris (dioctyl) phosphato] (110438-25-0); or LICA 12 (103850-22-2); b. Titanium IV, [(2-propenolato-1) methyl, n-propanolatomethyl] butanolato-1, tris[dioctyl] pyrophosphate or KR3538; c. Titanium IV, [(2-propenolato-1)methyl, n-propanolatomethyl] butanolato-1, tris(dioctyl)phosphate;

<i>Category Code</i>	<i>Item Description</i>
	<p>16. Polycyanodifluoroaminoethyleneoxide;</p> <p>17. Bonding agents as follows:</p> <ol style="list-style-type: none"> a. 1,1R,1S-trimesoyl-tris(2-ethylaziridine) (HX-868, BITA) (7722-73-8); b. Polyfunctional aziridine amides with isophthalic, trimesic, isocyanuric or trimethyladipic backbone also having a 2-methyl or 2-ethyl aziridine group; <p><i>Note</i> <i>Category Code ML8.f.17.b. includes:</i></p> <ol style="list-style-type: none"> a. 1,1 H-Isophthaloyl-bis(2-methylaziridine) (HX-752) (7652-64-4); b. 2,4,6-tris(2-ethyl-1-aziridinyl)-1,3,5-triazine (HX-874) (18924-91-9); c. 1,1'-trimethyladipoyl-bis(2-ethylaziridine) (HX-877) (71463-62-2). <p>18. Propyleneimine (2-methylaziridine) (75-55-8);</p> <p>19. Superfine iron oxide (Fe₂O₃) (1317-60-8) with a specific surface area more than 250 m²/g and an average particle size of 3 nm or less;</p> <p>20. TEPAN (tetraethylenepentaamineacrylonitrile) (68412-45-3); cyanoethylated polyamines and their salts;</p> <p>21. TEPANOL (tetraethylenepentaamineacrylonitrileglycidol) (68412-46-4); cyanoethylated polyamines adducted with glycidol and their salts;</p> <p>22. TPB (triphenyl bismuth) (603-33-8);</p> <p>23. TEPB (Tris (ethoxyphenyl) bismuth) (90591-48-3);</p>

<i>Category Code</i>	<i>Item Description</i>
	<p>g. “Precursors” as follows:</p> <p><i>N.B.</i> <i>The references in Category Code ML8.g. are specified “energetic materials” manufactured from these substances.</i></p> <ol style="list-style-type: none"> 1. BCMO (3,3-bis(chloromethyl)oxetane) (78-71-7) (see also Category Codes ML8.e.1. and e.2.); 2. Dinitroazetidine-t-butyl salt (125735-38-8) (see also Category Code ML8.a.28.); 3. Hexaazaisowurtzitane derivatives including HBIW (hexabenzylhexaazaisowurtzitane) (124782-15-6) (see also Category Code ML8.a.4.) and TAIW (tetraacetyldibenzylhexaazaisowurtzitane) (182763-60-6) (see also Category Code ML8.a.4.); 4. Not used; 5. TAT (1,3,5,7 tetraacetyl-1,3,5,7,-tetraaza cyclooctane) (41378-98-7) (see also Category Code ML8.a.13.); 6. 1,4,5,8-tetraazadecalin (5409-42-7) (see also Category Code ML8.a.27.); 7. 1,3,5-trichlorobenzene (108-70-3) (see also Category Code ML8.a.23.); 8. 1,2,4-trihydroxybutane (1,2,4-butanetriol) (3068-00-6) (see also Category Code ML8.e.5.); 9. DADN (1,5-diacetyl-3,7-dinitro-1, 3, 5, 7-tetraaza-cyclooctane) (see also Category Code ML8.a.13.). <p><i>Note 1</i></p> <p><i>Category Code ML8 does not apply to the following substances unless they are compounded or mixed with the “energetic material” specified in Category Code ML8.a. or powdered metals specified in Category Code ML8.c.:</i></p> <ol style="list-style-type: none"> a. <i>Ammonium picrate (131-74-8);</i> b. <i>Black powder;</i> c. <i>Hexanitrodiphenylamine (131-73-7);</i>

<i>Category Code</i>	<i>Item Description</i>
d.	<i>Difluoroamine (10405-27-3);</i>
e.	<i>Nitrostarch (9056-38-6);</i>
f.	<i>Potassium nitrate (7757-79-1);</i>
g.	<i>Tetranitronaphthalene;</i>
h.	<i>Trinitroanisol;</i>
i.	<i>Trinitronaphthalene;</i>
j.	<i>Trinitroxylene;</i>
k.	<i>N-pyrrolidinone; 1-methyl-2-pyrrolidinone (872-50-4);</i>
l.	<i>Dioctylmaleate (142-16-5);</i>
m.	<i>Ethylhexylacrylate (103-11-7);</i>
n.	<i>Triethylaluminium (TEA) (97-93-8), trimethylaluminium (TMA) (75-24-1), and other pyrophoric metal alkyls and aryls of lithium, sodium, magnesium, zinc or boron;</i>
o.	<i>Nitrocellulose (9004-70-0);</i>
p.	<i>Nitroglycerin (or glyceroltrinitrate, trinitroglycerine) (NG) (55-63-0);</i>
q.	<i>2,4,6-trinitrotoluene (TNT) (118-96-7);</i>
r.	<i>Ethylenediaminedinitrate (EDDN) (20829-66-7);</i>
s.	<i>Pentaerythritoltetranitrate (PETN) (78-11-5);</i>
t.	<i>Lead azide (13424-46-9), normal lead styphnate (15245-44-0) and basic lead styphnate (12403-82-6), and primary explosives or priming compositions containing azides or azide complexes;</i>
u.	<i>Triethyleneglycoldinitrate (TEGDN) (111-22-8);</i>
v.	<i>2,4,6-trinitroresorcinol (styphnic acid) (82-71-3);</i>
w.	<i>Diethyldiphenylurea (85-98-3); dimethyldiphenylurea (611-92-7); methylethyldiphenylurea; [Centralites];</i>

Category Code	Item Description
x.	<i>N,N</i> -diphenylurea (unsymmetrical diphenylurea) (603-54-3);
y.	<i>Methyl-N,N</i> -diphenylurea (methyl unsymmetrical diphenylurea) (13114-72-2);
z.	<i>Ethyl-N,N</i> -diphenylurea (ethyl unsymmetrical diphenylurea) (64544-71-4);
aa.	2-Nitrodiphenylamine (2-NDPA) (119-75-5);
bb.	4-Nitrodiphenylamine (4-NDPA) (836-30-6);
cc.	2,2-dinitropropanol (918-52-5);
dd.	Nitroguanidine (556-88-7) (see Category Code 1C011.d. in Division 2 of Part 2 of this Schedule).
	<u>Note 2</u>
	Category Code ML8 does not apply to ammonium perchlorate (Category Code ML8.d.2.), NTO (Category Code ML8.a.18.) or catocene (Category Code ML8.f.4.b.), and meeting all of the following:
a.	Specially shaped and formulated for civil-use gas generation devices;
b.	Compounded or mixed, with non-active thermoset binders or plasticisers, and having a mass of less than 250 g;
c.	Having a maximum of 80% ammonium perchlorate (Category Code ML8.d.2.) in mass of active material;
d.	Having less than or equal to 4 g of NTO (Category Code ML8.a.18.); <u>and</u>
e.	Having less than or equal to 1 g of catocene (Category Code ML8.f.4.b.).

<i>Category Code</i>	<i>Item Description</i>
ML9	<p>Vessels of war (surface or underwater), special naval equipment, accessories, components and other surface vessels, as follows:</p> <p><u><i>N.B.</i></u></p> <p><i>For guidance and navigation equipment, see Category Code ML11.</i></p> <p>a. Vessels and components, as follows:</p> <ol style="list-style-type: none"> 1. Vessels (surface or underwater) specially designed or modified for military use, regardless of current state of repair or operating condition, and whether or not they contain weapon delivery systems or armour, and hulls or parts of hulls for such vessels, and components therefor specially designed for military use; 2. Surface vessels, other than those specified in Category Code ML9.a.1., having any of the following, fixed or integrated into the vessel: <ol style="list-style-type: none"> a. Automatic weapons specified in Category Code ML1, or weapons specified in Category Code ML2, ML4, ML12 or ML19, or 'mountings' or hard points for weapons having a calibre of 12.7 mm or greater; <p><u><i>Technical Note</i></u></p> <p><i>'Mountings' refers to weapon mounts or structural strengthening for the purpose of installing weapons.</i></p> <ol style="list-style-type: none"> b. Fire control systems specified in Category Code ML5;

<i>Category Code</i>	<i>Item Description</i>
	<p>c. Having all of the following:</p> <ol style="list-style-type: none"> 1. ‘Chemical, Biological, Radiological and Nuclear (CBRN) protection’; <u>and</u> 2. ‘Pre-wet or wash down system’ designed for decontamination purposes; <u>or</u> <p><i>Technical Notes</i></p> <ol style="list-style-type: none"> 1. ‘CBRN protection’ is a self-contained interior space containing features such as over-pressurisation, isolation of ventilation systems, limited ventilation openings with CBRN filters and limited personnel access points incorporating air-locks. 2. ‘Pre-wet or wash down system’ is a seawater spray system capable of simultaneously wetting the exterior superstructure and decks of a vessel. <p>d. Active weapon countermeasure systems specified in Category Code ML4.b., ML5.c. or ML11.a. and having any of the following:</p> <ol style="list-style-type: none"> 1. ‘CBRN protection’; 2. Hull and superstructure, specially designed to reduce the radar cross section; 3. Thermal signature reduction devices, (e.g. an exhaust gas cooling system), excluding those specially designed to increase overall power plant efficiency or to reduce the environmental impact; <u>or</u>

<i>Category Code</i>	<i>Item Description</i>
	<p data-bbox="592 325 1153 420">4. A degaussing system designed to reduce the magnetic signature of the whole vessel;</p> <p data-bbox="655 439 838 472"><i>Technical Note</i></p> <p data-bbox="655 483 1153 715">'CBRN protection' is a self-contained interior space containing features such as over-pressurisation, isolation of ventilation systems, limited ventilation openings with CBRN filters and limited personnel access points incorporating air-locks.</p> <p data-bbox="377 738 1153 833">b. Engines and propulsion systems, as follows, specially designed for military use and components therefor specially designed for military use:</p> <p data-bbox="444 852 1153 919">1. Diesel engines specially designed for submarines and having all of the following:</p> <p data-bbox="525 938 1153 1005">a. Power output of 1.12 MW (1,500 hp) or more; <u>and</u></p> <p data-bbox="525 1024 995 1056">b. Rotary speed of 700 rpm or more;</p> <p data-bbox="444 1075 1153 1142">2. Electric motors specially designed for submarines and having all of the following:</p> <p data-bbox="525 1161 1153 1228">a. Power output of more than 0.75 MW (1,000 hp);</p> <p data-bbox="525 1247 790 1279">b. Quick reversing;</p> <p data-bbox="525 1298 817 1330">c. Liquid cooled; <u>and</u></p> <p data-bbox="525 1349 798 1382">d. Totally enclosed;</p> <p data-bbox="444 1401 1153 1467">3. Non-magnetic diesel engines having all of the following:</p> <p data-bbox="525 1487 1153 1553">a. Power output of 37.3 kW (50 hp) or more; <u>and</u></p> <p data-bbox="525 1572 1153 1629">b. Non-magnetic content in excess of 75% of total mass;</p>

<i>Category Code</i>	<i>Item Description</i>
	<p>4. ‘Air Independent Propulsion’ (AIP) systems specially designed for submarines;</p> <p><i>Technical Note</i> ‘Air Independent Propulsion’ (AIP) allows a submerged submarine to operate its propulsion system, without access to atmospheric oxygen, for a longer time than the batteries would have otherwise allowed. For the purpose of Category Code ML9.b.4., AIP does not include nuclear power.</p> <p>c. Underwater detection devices, specially designed for military use, controls therefor and components therefor specially designed for military use;</p> <p>d. Anti-submarine nets and anti-torpedo nets, specially designed for military use;</p> <p>e. Not used;</p> <p>f. Hull penetrators and connectors, specially designed for military use, that enable interaction with equipment external to a vessel, and components therefor specially designed for military use;</p> <p><i>Note</i> Category Code ML9.f. includes connectors for vessels which are of the single-conductor, multi-conductor, coaxial or waveguide type, and hull penetrators for vessels, both of which are capable of remaining impervious to leakage from without and of retaining required characteristics at marine depths exceeding 100 m; and fibre-optic connectors and optical hull penetrators, specially designed for “laser” beam transmission, regardless of depth. Category Code ML9.f. does not apply to ordinary propulsive shaft and hydrodynamic control-rod hull penetrators.</p>

<i>Category Code</i>	<i>Item Description</i>
ML10	<p data-bbox="377 329 1143 424">g. Silent bearings having any of the following, components therefor and equipment containing those bearings, specially designed for military use:</p> <ol data-bbox="440 443 877 576" style="list-style-type: none"> <li data-bbox="440 443 848 477">1. Gas or magnetic suspension; <li data-bbox="440 493 848 527">2. Active signature controls; <u>or</u> <li data-bbox="440 542 877 576">3. Vibration suppression controls. <p data-bbox="377 643 1143 776">“Aircraft”, “lighter-than-air vehicles”, “Unmanned Aerial Vehicles” (“UAVs”), aero-engines and “aircraft” equipment, related equipment and components, as follows, specially designed or modified for military use:</p> <p data-bbox="377 795 431 830"><u>N.B.</u></p> <p data-bbox="377 839 1143 900"><i>For guidance and navigation equipment, see Category Code ML11.</i></p> <ol data-bbox="377 919 1143 1745" style="list-style-type: none"> <li data-bbox="377 919 1143 986">a. Manned “aircraft” and “lighter-than-air vehicles”, and specially designed components therefor; <li data-bbox="377 1005 559 1039">b. Not used; <li data-bbox="377 1058 1143 1153">c. Unmanned “aircraft” and “lighter-than-air vehicles”, and related equipment, as follows, and specially designed components therefor: <ol data-bbox="440 1172 1143 1405" style="list-style-type: none"> <li data-bbox="440 1172 1143 1268">1. “UAVs”, Remotely Piloted Air Vehicles (RPVs), autonomous programmable vehicles and unmanned “lighter-than-air vehicles”; <li data-bbox="440 1287 1143 1353">2. Launchers, recovery equipment and ground support equipment; <li data-bbox="440 1372 1049 1405">3. Equipment designed for command or control; <li data-bbox="377 1424 1143 1490">d. Propulsion aero-engines and specially designed components therefor; <li data-bbox="377 1509 1143 1605">e. Airborne refuelling equipment specially designed or modified for any of the following, and specially designed components therefor: <ol data-bbox="440 1624 1143 1745" style="list-style-type: none"> <li data-bbox="440 1624 1110 1658">1. “Aircraft” specified in Category Code ML10.a.; <u>or</u> <li data-bbox="440 1677 1143 1745">2. Unmanned “aircraft” specified in Category Code ML10.c.;

<i>Category Code</i>	<i>Item Description</i>
	<p>f. 'Ground equipment' specially designed for "aircraft" specified in Category Code ML10.a. or aero-engines specified in Category Code ML10.d.;</p> <p><u>Technical Note</u> <i>'Ground equipment' includes pressure refuelling equipment and equipment designed to facilitate operations in confined areas.</i></p> <p>g. Aircrew life support equipment, aircrew safety equipment and other devices for emergency escape, not specified in Category Code ML10.a., designed for "aircraft" specified in Category Code ML10.a.;</p> <p><u>Note</u> <i>Category Code ML10.g. does not include aircrew helmets that do not incorporate, or have mountings or fittings for, equipment specified in any part of this Division.</i></p> <p><u>N.B.</u> <i>For helmets, see also Category Code ML13.c.</i></p> <p>h. Parachutes, paragliders and related equipment, as follows, and specially designed components therefor:</p> <ol style="list-style-type: none"> 1. Parachutes not specified elsewhere in any part of this Division; 2. Paragliders; 3. Equipment specially designed for high altitude parachutists (e.g. suits, special helmets, breathing systems, navigation equipment); <p>i. Controlled opening equipment or automatic piloting systems, designed for parachuted loads.</p>

<i>Category Code</i>	<i>Item Description</i>
	<p><u>Note 1</u></p> <p><i>Category Code ML10.a. does not apply to “aircraft” and “lighter-than-air vehicles” or variants of those “aircraft”, specially designed for military use and which are all of the following:</i></p> <ul style="list-style-type: none"> <i>a. Not a combat “aircraft”;</i> <i>b. Not configured for military use and not fitted with equipment or attachments specially designed or modified for military use; <u>and</u></i> <i>c. Certified for civil use by civil aviation authorities of one or more “participating states”.</i> <p><u>Note 2</u></p> <p><i>Category Code ML10.d. does not apply to:</i></p> <ul style="list-style-type: none"> <i>a. Aero-engines designed or modified for military use which have been certified by civil aviation authorities of one or more “participating states” for use in “civil aircraft”, or specially designed components therefor;</i> <i>b. Reciprocating engines or specially designed components therefor, except those specially designed for “UAVs”.</i> <p><u>Note 3</u></p> <p><i>For the purposes of Category Codes ML10.a. and ML10.d., specially designed components and related equipment for non-military “aircraft” or aero-engines modified for military use applies only to those military components and to military related equipment required for the modification to military use.</i></p> <p><u>Note 4</u></p> <p><i>For the purpose of Category Code ML10.a., military use includes: combat, military reconnaissance, assault, military training, logistics support, and transporting and airdropping troops or military equipment.</i></p>

Category Code	Item Description
	<p><u>Note 5</u> <i>Category Code ML10.a. does not apply to “aircraft” that meet all of the following:</i></p> <ul style="list-style-type: none"> <i>a. Were first manufactured before 1946;</i> <i>b. Do not incorporate items specified in any part of this Division, unless the items are required to meet safety or airworthiness standards of civil aviation authorities of one or more “participating states”; <u>and</u></i> <i>c. Do not incorporate weapons specified in any part of this Division, unless inoperable and incapable of being returned to operation.</i>
ML11	<p>Electronic equipment, “spacecraft” and components, not specified elsewhere in any part of this Division, as follows:</p> <ul style="list-style-type: none"> <i>a. Electronic equipment specially designed for military use and specially designed components therefor;</i> <p><u>Note</u> <i>Category Code ML11.a. includes:</i></p> <ul style="list-style-type: none"> <i>a. Electronic countermeasure and electronic counter-countermeasure equipment (i.e. equipment designed to introduce extraneous or erroneous signals into radar or radio communication receivers or otherwise hinder the reception, operation or effectiveness of adversary electronic receivers including their countermeasure equipment), including jamming and counter-jamming equipment;</i> <i>b. Frequency agile tubes;</i> <i>c. Electronic systems or equipment, designed either for surveillance and monitoring of the electromagnetic spectrum for military intelligence or security purposes or for counteracting such surveillance and monitoring;</i> <i>d. Underwater countermeasures, including acoustic and magnetic jamming and decoy, equipment designed to introduce extraneous or erroneous signals into sonar receivers;</i>

<i>Category Code</i>	<i>Item Description</i>
	<p>e. <i>Data processing security equipment, data security equipment and transmission and signalling line security equipment, using ciphering processes;</i></p> <p>f. <i>Identification, authentication and keyloader equipment and key management, manufacturing and distribution equipment;</i></p> <p>g. <i>Guidance and navigation equipment;</i></p> <p>h. <i>Digital troposcatter-radio communications transmission equipment;</i></p> <p>i. <i>Digital demodulators specially designed for signals intelligence;</i></p> <p>j. <i>“Automated Command and Control Systems”.</i></p> <p><u><i>N.B.</i></u> <i>For “software” associated with military “Software” Defined Radio (SDR), see Category Code ML21.</i></p> <p>b. <i>Global Navigation Satellite Systems (GNSS) jamming equipment and specially designed components therefor;</i></p> <p>c. <i>“Spacecraft” specially designed or modified for military use, and “spacecraft” components specially designed for military use.</i></p>
ML12	<p>High velocity kinetic energy weapon systems and related equipment, as follows, and specially designed components therefor:</p> <p>a. <i>Kinetic energy weapon systems specially designed for destruction or effecting mission-abort of a target;</i></p> <p>b. <i>Specially designed test and evaluation facilities and test models, including diagnostic instrumentation and targets, for dynamic testing of kinetic energy projectiles and systems.</i></p> <p><u><i>N.B.</i></u> <i>For weapon systems using sub-calibre ammunition or employing solely chemical propulsion, and ammunition therefor, see Category Codes ML1 to ML4.</i></p>

<i>Category Code</i>	<i>Item Description</i>
	<p><u>Note 1</u></p> <p><i>Category Code ML12 includes the following when specially designed for kinetic energy weapon systems:</i></p> <ul style="list-style-type: none"> <i>a. Launch propulsion systems capable of accelerating masses larger than 0.1 g to velocities in excess of 1.6 km/s, in single or rapid fire modes;</i> <i>b. Prime power generation, electric armour, energy storage (e.g. high energy storage capacitors), thermal management, conditioning, switching or fuel-handling equipment; and electrical interfaces between power supply, gun and other turret electric drive functions;</i> <p><u>N.B.</u></p> <p><i>See also Category Code 3A001.e.2. in Division 2 of Part 2 of this Schedule for high energy storage capacitors.</i></p> <ul style="list-style-type: none"> <i>c. Target acquisition, tracking, fire control or damage assessment systems;</i> <i>d. Homing seeker, guidance or divert propulsion (lateral acceleration) systems for projectiles.</i> <p><u>Note 2</u></p> <p><i>Category Code ML12 applies to weapon systems using any of the following methods of propulsion:</i></p> <ul style="list-style-type: none"> <i>a. Electromagnetic;</i> <i>b. Electrothermal;</i> <i>c. Plasma;</i> <i>d. Light gas; <u>or</u></i> <i>e. Chemical (when used in combination with any of the above).</i>

<i>Category Code</i>	<i>Item Description</i>
ML13	<p>Armoured or protective equipment, constructions and components, as follows:</p> <p>a. Metallic or non-metallic armoured plate, having any of the following:</p> <ol style="list-style-type: none"> 1. Manufactured to comply with a military standard or specification; <u>or</u> 2. Suitable for military use; <p><i>N.B.</i> <i>For body armour plate, see Category Code ML13.d.2.</i></p> <p>b. Constructions of metallic or non-metallic materials, or combinations thereof, specially designed to provide ballistic protection for military systems, and specially designed components therefor;</p> <p>c. Helmets manufactured according to military standards or specifications, or comparable national standards, and specially designed helmet shells, liners, or comfort pads, therefor;</p> <p><i>N.B.</i> <i>For other military helmet components or accessories, see the relevant Category Code in this Division.</i></p> <p>d. Body armour or protective garments, and components therefor, as follows:</p> <ol style="list-style-type: none"> 1. Soft body armour or protective garments, manufactured to military standards or specifications, or to their equivalents, and specially designed components therefor; <p><i>Note</i> <i>For the purpose of Category Code ML13.d.1., military standards or specifications include, at a minimum, specifications for fragmentation protection.</i></p> <ol style="list-style-type: none"> 2. Hard body armour plates providing ballistic protection equal to or greater than level III (NIJ 0101.06, July 2008) or national equivalents.

<i>Category Code</i>	<i>Item Description</i>
	<p><u>Note 1</u> <i>Category Code ML13.b. includes materials specially designed to form explosive reactive armour or to construct military shelters.</i></p> <p><u>Note 2</u> <i>Category Code ML13.c. does not apply to conventional steel helmets, neither modified or designed to accept, nor equipped with any type of accessory device.</i></p> <p><u>Note 3</u> <i>Category Codes ML13.c. and ML13.d. do not apply to helmets, body armour or protective garments, when accompanying their user for the user's own personal protection.</i></p> <p><u>Note 4</u> <i>The only helmets specially designed for bomb disposal personnel that are specified in Category Code ML13 are those specially designed for military use.</i></p> <p><u>N.B. 1</u> <i>See also Category Code IA005 in Division 2 of Part 2 of this Schedule.</i></p> <p><u>N.B. 2</u> <i>For "fibrous or filamentary materials" used in the manufacture of body armour and helmets, see Category Code IC010 in Division 2 of Part 2 of this Schedule.</i></p>

<i>Category Code</i>	<i>Item Description</i>
ML14	<p data-bbox="377 325 1146 491">‘Specialised equipment for military training’ or for simulating military scenarios, simulators specially designed for training in the use of any firearm or weapon specified in Category Code ML1 or ML2, and specially designed components and accessories therefor.</p> <p data-bbox="377 510 561 540"><u>Technical Note</u></p> <p data-bbox="377 554 1146 891"><i>The term ‘specialised equipment for military training’ includes military types of attack trainers, operational flight trainers, radar target trainers, radar target generators, gunnery training devices, anti-submarine warfare trainers, flight simulators (including human-rated centrifuges for pilot/astronaut training), radar trainers, instrument flight trainers, navigation trainers, missile launch trainers, target equipment, drone “aircraft”, armament trainers, pilotless “aircraft” trainers, mobile training units and training equipment for ground military operations.</i></p> <p data-bbox="377 910 458 940"><u>Note 1</u></p> <p data-bbox="377 953 1146 1049"><i>Category Code ML14 includes image generating and interactive environment systems for simulators, when specially designed or modified for military use.</i></p> <p data-bbox="377 1068 458 1098"><u>Note 2</u></p> <p data-bbox="377 1111 1146 1176"><i>Category Code ML14 does not apply to equipment specially designed for training in the use of hunting or sporting weapons.</i></p>
ML15	<p data-bbox="377 1245 1146 1340">Imaging or countermeasure equipment, as follows, specially designed for military use, and specially designed components and accessories therefor:</p> <ol data-bbox="377 1359 1146 1576" style="list-style-type: none"> <li data-bbox="377 1359 969 1389">a. Recorders and image processing equipment; <li data-bbox="377 1408 1146 1473">b. Cameras, photographic equipment and film processing equipment; <li data-bbox="377 1492 784 1523">c. Image intensifier equipment; <li data-bbox="377 1542 915 1572">d. Infrared or thermal imaging equipment;

<i>Category Code</i>	<i>Item Description</i>
	<p>e. Imaging radar sensor equipment;</p> <p>f. Countermeasure or counter-countermeasure equipment, for the equipment specified in Category Codes ML15.a. to ML15.e.</p> <p><u>Note</u> <i>Category Code ML15.f. includes equipment designed to degrade the operation or effectiveness of military imaging systems or to minimise such degrading effects.</i></p> <p><u>Note 1</u> <i>In Category Code ML15, the term specially designed components includes the following, when specially designed for military use:</i></p> <p>a. <i>Infrared image converter tubes;</i></p> <p>b. <i>Image intensifier tubes (other than first generation);</i></p> <p>c. <i>Microchannel plates;</i></p> <p>d. <i>Low-light-level television camera tubes;</i></p> <p>e. <i>Detector arrays (including electronic interconnection or read out systems);</i></p> <p>f. <i>Pyroelectric television camera tubes;</i></p> <p>g. <i>Cooling systems for imaging systems;</i></p> <p>h. <i>Electrically triggered shutters of the photochromic or electro-optical type having a shutter speed of less than 100 μs, except in the case of shutters which are an essential part of a high speed camera;</i></p> <p>i. <i>Fibre optic image inverters;</i></p> <p>j. <i>Compound semiconductor photocathodes.</i></p> <p><u>Note 2</u> <i>Category Code ML15 does not apply to “first generation image intensifier tubes” or equipment specially designed to incorporate “first generation image intensifier tubes”.</i></p>

<i>Category Code</i>	<i>Item Description</i>
	<p><u>N.B.</u> For the classification of weapons-sights incorporating “first generation image intensifier tubes” see Category Codes ML1, ML2 and ML5.a.</p> <p><u>N.B.</u> See also Category Codes 6A002.a.2. and 6A002.b. in Division 2 of Part 2 of this Schedule.</p>
ML16	<p>Forgings, castings and other unfinished products, specially designed for items specified in Category Code ML1 to ML4, ML6, ML9, ML10, ML12 or ML19.</p> <p><u>Note</u> Category Code ML16 applies to unfinished products when they are identifiable by material composition, geometry or function.</p>
ML17	<p>Miscellaneous equipment, materials and “libraries”, as follows, and specially designed components therefor:</p> <ol style="list-style-type: none"> a. Diving and underwater swimming apparatus, specially designed or modified for military use, as follows: <ol style="list-style-type: none"> 1. Self-contained diving rebreathers, closed or semi-closed circuit; 2. Underwater swimming apparatus specially designed for use with the diving apparatus specified in Category Code ML17.a.1.; <p><u>N.B.</u> See also Category Code 8A002.q. in Division 2 of Part 2 of this Schedule.</p> <ol style="list-style-type: none"> b. Construction equipment specially designed for military use; c. Fittings, coatings and treatments, for signature suppression, specially designed for military use; d. Field engineer equipment specially designed for use in a combat zone;

<i>Category Code</i>	<i>Item Description</i>
	<p>e. “Robots”, “robot” controllers and “robot” “end-effectors”, having any of the following characteristics:</p> <ol style="list-style-type: none"> 1. Specially designed for military use; 2. Incorporating means of protecting hydraulic lines against externally induced punctures caused by ballistic fragments (e.g. incorporating self-sealing lines) and designed to use hydraulic fluids with flash points higher than 839 K (566°C); <u>or</u> 3. Specially designed or rated for operating in an electromagnetic pulse (EMP) environment; <p><i>Technical Note</i> <i>Electromagnetic pulse does not refer to unintentional interference caused by electromagnetic radiation from nearby equipment (e.g. machinery, appliances or electronics) or lightning.</i></p> <p>f. “Libraries” specially designed or modified for military use with systems, equipment or components, specified in this Division;</p> <p>g. Nuclear power generating equipment or propulsion equipment, including “nuclear reactors”, specially designed for military use and components therefor specially designed or ‘modified’ for military use;</p> <p>h. Equipment and material, coated or treated for signature suppression, specially designed for military use, other than those specified elsewhere in this Division;</p> <p>i. Simulators specially designed for military “nuclear reactors”;</p> <p>j. Mobile repair shops specially designed or ‘modified’ to service military equipment;</p> <p>k. Field generators specially designed or ‘modified’ for military use;</p> <p>l. Containers specially designed or ‘modified’ for military use;</p> <p>m. Ferries, other than those specified elsewhere in this Division, bridges and pontoons, specially designed for military use;</p>

<i>Category Code</i>	<i>Item Description</i>
	<p>n. Test models specially designed for the “development” of items specified in Category Code ML4, ML6, ML9 or ML10;</p> <p>o. “Laser” protection equipment (e.g. eye and sensor protection) specially designed for military use;</p> <p>p. “Fuel cells”, other than those specified elsewhere in this Division, specially designed or ‘modified’ for military use.</p> <p><u>Technical Notes</u></p> <p>1. <i>Not used.</i></p> <p>2. <i>For the purpose of Category Code ML17, ‘modified’ means any structural, electrical, mechanical, or other change that provides a non-military item with military capabilities equivalent to an item which is specially designed for military use.</i></p>
ML18	<p>‘Production’ equipment and components, as follows:</p> <p>a. Specially designed or modified ‘production’ equipment for the ‘production’ of products specified in this Division, and specially designed components therefor;</p> <p>b. Specially designed environmental test facilities and specially designed equipment therefor, for the certification, qualification or testing of products specified in this Division.</p> <p><u>Technical Note</u></p> <p><i>For the purpose of Category Code ML18, the term ‘production’ includes design, examination, manufacture, testing and checking.</i></p> <p><u>Note</u></p> <p><i>Category Codes ML18.a. and ML18.b. include the following equipment:</i></p> <p>a. <i>Continuous nitrators;</i></p>

Category Code	Item Description
	<p>b. Centrifugal testing apparatus or equipment, having any of the following:</p> <ol style="list-style-type: none"> 1. Driven by a motor or motors having a total rated horsepower of more than 298 kW (400 hp); 2. Capable of carrying a payload of 113 kg or more; <u>or</u> 3. Capable of exerting a centrifugal acceleration of 8 g or more on a payload of 91 kg or more; <p>c. Dehydration presses;</p> <p>d. Screw extruders specially designed or modified for military explosive extrusion;</p> <p>e. Cutting machines for the sizing of extruded propellants;</p> <p>f. Sweetie barrels (tumblers) 1.85 m or more in diameter and having over 227 kg product capacity;</p> <p>g. Continuous mixers for solid propellants;</p> <p>h. Fluid energy mills for grinding or milling the ingredients of military explosives;</p> <p>i. Equipment to achieve both sphericity and uniform particle size in metal powder listed in Category Code ML8.c.8.;</p> <p>j. Convection current converters for the conversion of materials listed in Category Code ML8.c.3.</p>
ML19	<p>Directed Energy Weapon (DEW) systems, related or countermeasure equipment and test models, as follows, and specially designed components therefor:</p> <ol style="list-style-type: none"> a. "Laser" systems specially designed for destruction or effecting mission-abort of a target; b. Particle beam systems capable of destruction or effecting mission-abort of a target; c. High power Radio-Frequency (RF) systems capable of destruction or effecting mission-abort of a target; d. Equipment specially designed for the detection or identification of, or defence against, systems specified in Category Codes ML19.a. to ML19.c.;

<i>Category Code</i>	<i>Item Description</i>
	<p>e. Physical test models for the systems, equipment and components, specified in Category Code ML19;</p> <p>f. “Laser” systems specially designed to cause permanent blindness to unenhanced vision, i.e. to the naked eye or to the eye with corrective eyesight devices.</p> <p><u>Note 1</u> <i>DEW systems specified in Category Code ML19 include systems whose capability is derived from the controlled application of:</i></p> <p>a. “Lasers” of sufficient power to effect destruction similar to the manner of conventional ammunition;</p> <p>b. Particle accelerators which project a charged or neutral particle beam with destructive power;</p> <p>c. High pulsed power or high average power radio frequency beam transmitters, which produce fields sufficiently intense to disable electronic circuitry at a distant target.</p> <p><u>Note 2</u> <i>Category Code ML19 includes the following when specially designed for DEW systems:</i></p> <p>a. Prime power generation, energy storage, switching, power conditioning or fuel-handling equipment;</p> <p>b. Target acquisition or tracking systems;</p> <p>c. Systems capable of assessing target damage, destruction or mission-abort;</p> <p>d. Beam-handling, propagation or pointing equipment;</p> <p>e. Equipment with rapid beam slew capability for rapid multiple target operations;</p> <p>f. Adaptive optics and phase conjugators;</p> <p>g. Current injectors for negative hydrogen ion beams;</p> <p>h. “Space-qualified” accelerator components;</p>

<i>Category Code</i>	<i>Item Description</i>
ML20	<p data-bbox="373 325 1142 525"> <i>i. Negative ion beam funnelling equipment;</i> <i>j. Equipment for controlling and slewing a high energy ion beam;</i> <i>k. “Space-qualified” foils for neutralising negative hydrogen isotope beams.</i> </p> <p data-bbox="373 592 1142 658"> Cryogenic and “superconductive” equipment, as follows, and specially designed components and accessories therefor: </p> <p data-bbox="373 677 1142 843"> a. Equipment specially designed or configured to be installed in a vehicle for military ground, marine, airborne or space applications, capable of operating while in motion and of producing or maintaining temperatures below 103 K (-170°C); </p> <p data-bbox="438 862 498 891"> <u>Note</u> </p> <p data-bbox="438 906 1142 1071"> <i>Category Code ML20.a. includes mobile systems incorporating or employing accessories or components manufactured from non-metallic or non-electrical conductive materials, such as plastics or epoxy-impregnated materials.</i> </p> <p data-bbox="373 1090 1142 1256"> b. “Superconductive” electrical equipment (rotating machinery and transformers) specially designed or configured to be installed in a vehicle for military ground, marine, airborne or space applications and capable of operating while in motion. </p> <p data-bbox="438 1275 498 1304"> <u>Note</u> </p> <p data-bbox="438 1319 1142 1521"> <i>Category Code ML20.b. does not apply to direct-current hybrid homopolar generators that have single-pole normal metal armatures which rotate in a magnetic field produced by superconducting windings, provided those windings are the only superconducting components in the generator.</i> </p>

<i>Category Code</i>	<i>Item Description</i>
ML21	<p>“Software” as follows:</p> <ol style="list-style-type: none"> a. “Software” specially designed or modified for any of the following: <ol style="list-style-type: none"> 1. “Development”, “production”, operation or maintenance of equipment specified in this Division; 2. “Development” or “production” of materials specified in this Division; <u>or</u> 3. “Development”, “production”, operation or maintenance of “software” specified in this Division; b. Specific “software”, other than that specified in Category Code ML21.a., as follows: <ol style="list-style-type: none"> 1. “Software” specially designed for military use and specially designed for modelling, simulating or evaluating military weapon systems; 2. “Software” specially designed for military use and specially designed for modelling or simulating military operational scenarios; 3. “Software” for determining the effects of conventional, nuclear, chemical or biological weapons; 4. “Software” specially designed for military use and specially designed for Command, Communications, Control and Intelligence (C³I) or Command, Communications, Control, Computer and Intelligence (C⁴I) applications; c. “Software”, not specified in Category Code ML21.a. or ML21.b., specially designed or modified to enable equipment not specified in this Division to perform the military functions of equipment specified in this Division.

<i>Category Code</i>	<i>Item Description</i>
ML22	<p>“Technology” as follows:</p> <ol style="list-style-type: none"> a. “Technology”, other than specified in Category Code ML22.b., which is “required” for the “development”, “production”, operation, installation, maintenance (checking), repair, overhaul or refurbishing of items specified in this Division; b. “Technology” as follows: <ol style="list-style-type: none"> 1. “Technology” “required” for the design of, the assembly of components into, and the operation, maintenance and repair of, complete production installations for items specified in this Division, even if the components of such production installations are not specified; 2. “Technology” “required” for the “development” and “production” of small arms, even if used to produce reproductions of antique small arms; 3. Not used; <i>N.B.</i> <i>See Category Code ML22.a. for “technology” previously specified by Category Code ML22.b.3.</i> 4. Not used; <i>N.B.</i> <i>See Category Code ML22.a. for “technology” previously specified by Category Code ML22.b.4.</i> 5. “Technology” “required” exclusively for the incorporation of “biocatalysts”, specified in Category Code ML7.i.1., into military carrier substances or military material. <p><i>Note 1</i></p> <p><i>“Technology” “required” for the “development”, “production”, operation, installation, maintenance (checking), repair, overhaul or refurbishing of items specified in this Division is considered to fall within Category Code ML22 even when applicable to any goods which are not specified in this Division.</i></p>

<i>Category Code</i>	<i>Item Description</i>
	<p><i>Note 2</i></p> <p><i>Category Code ML22 does not include “technology” for magnetic induction for continuous propulsion of civil transport devices.</i></p>

PART 2

DUAL-USE GOODS THE EXPORT, TRANSHIPMENT OR
BRINGING IN TRANSIT OF WHICH, AND TECHNOLOGY
THE EXPORT OR TRANSMISSION OF WHICH, REQUIRE A PERMIT

*Division 1 — Preliminary Provisions**Subdivision 1 — General Notes*

1. Non-controlled goods (including plant) containing one or more controlled components set out in Division 2 shall be considered as being controlled goods within Division 2 if the controlled components are the principal element of the non-controlled goods and can feasibly be removed or used for other purposes.
2. In determining whether goods are to be considered the principal element of other goods for the purposes of paragraph 1, factors such as the quantity, value and technological know-how involved and other special circumstances which might establish the goods as the principal element of the other goods must be weighed.
3. Goods specified in Division 2 include both new and used goods.
4. Chemicals in Division 2 are listed by name and CAS number. Chemicals of the same structural formula (including hydrates) as chemicals listed in Division 2 are to be considered as coming within the descriptions of the second-mentioned chemicals regardless of name or CAS number. CAS numbers are shown in order to assist in identifying whether a particular chemical or mixture is a chemical within Division 2, irrespective of nomenclature. CAS numbers are not intended to be used as unique identifiers because some forms of the listed chemical have different CAS numbers, and mixtures containing a listed chemical may also have different CAS numbers.

Subdivision 2 — Nuclear Technology Note (NTN)

(To be read in conjunction with section E of Category 0.)

5. “Technology” for the “development”, “production” or “use” of goods specified in Category 0 are considered to be “technology” under section E of that Category even when applicable to goods not so specified.

Subdivision 3 — General Technology Note (GTN)

(To be read in conjunction with section E of Categories 1 to 9.)

6. “Technology” under section E of Categories 1 to 9 is “technology” which is “required” for the “development”, “production” or “use” of goods specified in those Categories.

“Technology” for the “development”, “production” or “use” of goods specified in Categories 1 to 9 are considered to be “technology” under section E of those Categories even when applicable to goods not so specified.

Subdivision 4 — General Software Note (GSN)

7. Categories 0 to 9 of Division 2 do not include “software” which is any of the following:
- a. Generally available to the public by being:
 1. Sold from stock at retail selling points, without restriction, by means of:
 - a. Over-the-counter transactions;
 - b. Mail order transactions;
 - c. Electronic transactions; or
 - d. Telephone order transactions; and
 2. Designed for installation by the user without further substantial support by the supplier; or
 - b. The minimum necessary “object code” for the installation, operation, maintenance (checking) or repair of those items whose export has been authorised.

Note

Paragraph 7 does not extend to “software” specified in Category 5 — Part 2 (“Information Security”).

Subdivision 5 — Definitions of Words and Expressions in this Part

8. In this Part, words and expressions in quotation marks (“ ”) take the definitions set out against them in this paragraph:

“accuracy” (Categories 2, 6), usually measured in terms of inaccuracy, means the maximum deviation, positive or negative, of an indicated value from an accepted standard or true value;

“active flight control systems” (Category 7) means systems that function to prevent undesirable “aircraft” and missile motions or structural loads by autonomously processing outputs from multiple sensors and then providing the necessary preventive commands to effect automatic control;

“active pixel” (Categories 6, 8) means a minimum (single) element of the solid state array which has a photoelectric transfer function when exposed to light (electromagnetic) radiation;

“adapted for use in war” (Category 1) means any modification or selection (such as altering purity, shelf life, virulence, dissemination characteristics, or resistance to UV radiation) designed to increase the effectiveness in producing casualties in humans or animals, degrading equipment or damaging crops or the environment;

“adjusted peak performance” (Category 4) means an adjusted peak rate at which “digital computers” perform 64-bit or larger floating point additions and multiplications, and is expressed in Weighted TeraFLOPS (WT) with units of 10^{12} adjusted floating point operations per second;

N.B.

See Category 4, Technical Note.

“aircraft” (Categories 1, 7, 9) means a fixed wing, swivel wing, rotary wing (helicopter), tilt rotor or tilt-wing airborne vehicle;

N.B.

See also “civil aircraft”.

“airship” (Category 9) means a power-driven airborne vehicle that is kept buoyant by a body of gas (usually helium, formerly hydrogen) which is lighter than air;

“all compensations available” (Category 2) means after all feasible measures available to the manufacturer to minimise all systematic positioning errors for the particular machine-tool model or measuring errors for the particular coordinate measuring machine are considered;

“allocated by the ITU” (Categories 3, 5) means the allocation of frequency bands according to the current edition of the ITU Radio Regulations for primary, permitted and secondary services;

Note

Additional and alternative allocations are not included.

“angle random walk” (Category 7) means the angular error build-up with time that is due to white noise in angular rate (Ref. IEEE STD 528-2001);

“angular position deviation” (Category 2) means the maximum difference between angular position and the actual, very accurately measured angular position after the workpiece mount of the table has been turned out of its initial position;

“APP” (Category 4) is equivalent to “Adjusted Peak Performance”;

“asymmetric algorithm” (Category 5) means a cryptographic algorithm using different, mathematically-related keys for encryption and decryption;

Note

A common use of “asymmetric algorithms” is key management.

“automatic target tracking” (Category 6) means a processing technique that automatically determines and provides as output an extrapolated value of the most probable position of the target in real time;

“average output power” (Category 6) means the total “laser” output energy, in joules, divided by the period over which a series of consecutive pulses is emitted, in seconds. For a series of uniformly spaced pulses it is equal to the total “laser” output energy in a single pulse, in joules, multiplied by the pulse frequency of the “laser”, in Hertz;

“basic gate propagation delay time” (Category 3) means the propagation delay time value corresponding to the basic gate used in a “monolithic integrated circuit”. For a ‘family’ of “monolithic integrated circuits”, this may be specified either as the propagation delay time per typical gate within the given ‘family’ or as the typical propagation delay time per gate within the given ‘family’;

Note 1

“Basic gate propagation delay time” is not to be confused with the input or output delay time of a complex “monolithic integrated circuit”.

Note 2

'Family' consists of all integrated circuits to which all of the following are applied as their manufacturing methodology and specifications except their respective functions:

- a. The common hardware and software architecture;*
- b. The common design and process technology; and*
- c. The common basic characteristics.*

“bias” (accelerometer) (Category 7) means the average over a specified time of accelerometer output, measured at specified operating conditions, that has no correlation with input acceleration or rotation. “Bias” is expressed in g or in metres per second squared (g or m/s²). (Ref. IEEE Std 528-2001) (Micro g equals 1×10^{-6} g);

“bias” (gyro) (Category 7) means the average over a specified time of gyro output measured at specified operating conditions that has no correlation with input rotation or acceleration. “Bias” is typically expressed in degrees per hour (deg/hr). (Ref. IEEE Std 528-2001);

“camming” (Category 2) means axial displacement in one revolution of the main spindle measured in a plane perpendicular to the spindle faceplate, at a point next to the circumference of the spindle faceplate (Ref. ISO 230/1 1986, paragraph 5.63);

“carbon fibre preforms” (Category 1) means an ordered arrangement of uncoated or coated fibres intended to constitute a framework of a part before the “matrix” is introduced to form a “composite”;

“CEP” (circle of equal probability) (Category 7) means a measure of accuracy; the radius of the circle centred at the target, at a specific range, in which 50% of the payloads impact;

“chemical laser” (Category 6) means a “laser” in which the excited species is produced by the output energy from a chemical reaction;

“chemical mixture” (Category 1) means a solid, liquid or gaseous product made up of two or more components which do not react together under the conditions under which the mixture is stored;

“circulation-controlled anti-torque or circulation-controlled direction control systems” (Category 7) means systems that use air blown over aerodynamic surfaces to increase or control the forces generated by the surfaces;

“civil aircraft” (Categories 1, 3, 4, 7) means an “aircraft” listed by designation in published airworthiness certification lists by the civil aviation authorities of a “participating state” to fly commercial civil internal and external routes or for legitimate civil, private or business use;

N.B.

See also “aircraft”.

“commingled” (Category 1) means filament to filament blending of thermoplastic fibres and reinforcement fibres in order to produce a fibre reinforcement “matrix” mix in total fibre form;

“comminution” (Category 1) means a process to reduce a material to particles by crushing or grinding;

“communications channel controller” (Category 4) means the physical interface which controls the flow of synchronous or asynchronous digital information. It is an assembly that can be integrated into computer or telecommunications equipment to provide communications access;

“compensation systems” (Category 6) means systems which consist of the primary scalar sensor, one or more reference sensors (e.g. vector magnetometers) together with software that permit reduction of rigid body rotation noise of the platform;

“composite” (Categories 1, 2, 6, 8, 9) means a “matrix” and an additional phase or additional phases consisting of particles, whiskers, fibres or any combination thereof, present for a specific purpose or purposes;

“compound rotary table” (Category 2) means a table allowing the workpiece to rotate and tilt about two non-parallel axes, which can be coordinated simultaneously for “contouring control”;

“III/V compounds” (Categories 3, 6) means polycrystalline or binary or complex monocrystalline products consisting of elements of groups IIIA and VA of Mendeleev’s periodic classification table (e.g. gallium arsenide, gallium-aluminium arsenide, indium phosphide);

“contouring control” (Category 2) means two or more “numerically controlled” motions operating in accordance with instructions that specify the next required position and the required feed rates to that position. These feed rates are varied in relation to each other so that a desired contour is generated (Ref. ISO/DIS 2806-1980);

“critical temperature” (Categories 1, 3, 5) (sometimes referred to as the transition temperature) of a specific “superconductive” material means the temperature at which the material loses all resistance to the flow of direct electrical current;

“cryptographic activation” (Category 5) means any technique that activates or enables cryptographic capability of an item, by means of a secure mechanism implemented by the manufacturer of the item, where this mechanism is uniquely bound to any of the following:

- a. A single instance of the item; or
- b. One customer, for multiple instances of the item;

Technical Notes

1. “Cryptographic activation” techniques and mechanisms may be implemented as hardware, “software” or “technology”.
2. Mechanisms for “cryptographic activation” can, for example, be serial number-based licence keys or authentication instruments such as digitally signed certificates.

“cryptography” (Category 5) means the discipline which embodies principles, means and methods for the transformation of data in order to hide its information content, prevent its undetected modification or prevent its unauthorised use. “Cryptography” is limited to the transformation of information using one or more ‘secret parameters’ (e.g. crypto variables) or associated key management;

Note

“Crypography” does not include ‘fixed’ data compression or coding techniques.

Technical Note

‘Fixed’ means the coding or compression algorithm cannot accept externally supplied parameters (e.g. cryptographic or key variables) and cannot be modified by the user.

Technical Note

‘Secret parameter’ means a constant or key kept from the knowledge of others or shared only within a group.

“CW laser” (Category 6) means a “laser” that produces a nominally constant output energy for greater than 0.25 seconds;

“Data-Based Referenced Navigation” (“DBRN”) (Category 7) Systems means systems which use various sources of previously measured geo-mapping data integrated to provide accurate navigation information under dynamic conditions. Data sources include bathymetric maps, stellar maps, gravity maps, magnetic maps or 3-D digital terrain maps;

“deformable mirrors” (Category 6) (also known as adaptive optic mirrors) means mirrors having:

- a. A single continuous optical reflecting surface which is dynamically deformed by the application of individual torques or forces to compensate for distortions in the optical waveform incident upon the mirror; or
- b. Multiple optical reflecting elements that can be individually and dynamically repositioned by the application of torques or forces to compensate for distortions in the optical waveform incident upon the mirror;

“depleted uranium” (Category 0) means uranium depleted in the isotope 235 below that occurring in nature;

“development” (GTN, NTN, All Categories) has the same meaning as in the Act;

“diffusion bonding” (Categories 1, 2, 9) means a solid state joining of at least two separate pieces of metals into a single piece with a joint strength equivalent to that of the weakest material, wherein the principal mechanism is interdiffusion of atoms across the interface;

“digital computer” (Categories 4, 5) means equipment which can, in the form of one or more discrete variables, perform all of the following:

- a. Accept data;
- b. Store data or instructions in fixed or alterable (writable) storage devices;
- c. Process data by means of a stored sequence of instructions which is modifiable; and
- d. Provide output of data;

Note

Modifications of a stored sequence of instructions include replacement of fixed storage devices, but not a physical change in wiring or inter-connections.

“digital transfer rate” (Category 5) means the total bit rate of the information that is directly transferred on any type of medium;

N.B.

See also “total digital transfer rate”.

“direct-acting hydraulic pressing” (Category 2) means a deformation process which uses a fluid-filled flexible bladder in direct contact with the workpiece;

“drift rate” (gyro) (Category 7) means the component of gyro output that is functionally independent of input rotation. It is expressed as an angular rate. (Ref. IEEE STD 528-2001);

“effective gramme” (Categories 0, 1) of “special fissile material” means:

- a. For plutonium isotopes and uranium-233, the isotope weight in grammes;
- b. For uranium enriched 1 per cent or greater in the isotope uranium-235, the element weight in grammes multiplied by the square of its enrichment expressed as a decimal weight fraction;
- c. For uranium enriched below 1 per cent in the isotope uranium-235, the element weight in grammes multiplied by 0.0001;

“electronic assembly” (Categories 2, 3, 4) means a number of electronic components (i.e. ‘circuit elements’, ‘discrete components’, integrated circuits, etc.) connected together to perform one or more specific functions, replaceable as an entity and normally capable of being disassembled;

Technical Note 1

‘Circuit element’ means a single active or passive functional part of an electronic circuit, such as one diode, one transistor, one resistor, one capacitor, etc.

Technical Note 2

‘Discrete component’ means a separately packaged ‘circuit element’ with its own external connections.

“electronically steerable phased array antenna” (Categories 5, 6) means an antenna which forms a beam by means of phase coupling, i.e. the beam direction is controlled by the complex excitation coefficients of the radiating elements and the direction of that beam can be varied in azimuth or in elevation, or both, by application, both in transmission and reception, of an electrical signal;

“energetic materials” (Category 1) means substances or mixtures that react chemically to release energy required for their intended application. “Explosives”, ‘pyrotechnics’ and ‘propellants’ are subclasses of energetic materials;

Technical Note 1

‘Pyrotechnics’ means mixtures of solid or liquid fuels and oxidisers which, when ignited, undergo an energetic chemical reaction at a controlled rate intended to produce specific time delays, or quantities of heat, noise, smoke, visible light or infrared radiation. Pyrophorics are a subclass of ‘pyrotechnics’, which contain no oxidisers but ignite spontaneously on contact with air.

Technical Note 2

‘Propellants’ means substances or mixtures that react chemically to produce large volumes of hot gases at controlled rates to perform mechanical work.

“end-effectors” (Category 2) means grippers, ‘active tooling units’ and any other tooling that is attached to the baseplate on the end of a “robot” manipulator arm;

Technical Note

‘Active tooling unit’ means a device for applying motive power, process energy or sensing to the workpiece.

“equivalent density” (Category 6) means the mass of an optic per unit optical area projected onto the optical surface;

“explosives” (Category 1) means solid, liquid or gaseous substances or mixtures of substances which, in their application as primary, booster, or main charges in warheads, demolition and other applications, are required to detonate;

“FADEC Systems” (Category 9) means Full Authority Digital Engine Control Systems – A digital electronic control system for a gas turbine engine that is able to autonomously control the engine throughout its whole operating range from demanded engine start until demanded engine shut-down, in both normal and fault conditions;

“fibrous or filamentary materials” (Categories 0, 1, 2, 8, 9) includes:

- a. Continuous “monofilaments”;
- b. Continuous “yarns” and “rovings”;
- c. “Tapes”, fabrics, random mats and braids;
- d. Chopped fibres, staple fibres and coherent fibre blankets;
- e. Whiskers, either monocrystalline or polycrystalline, of any length;
- f. Aromatic polyamide pulp;

“film type integrated circuit” (Category 3) means an array of ‘circuit elements’ and metallic interconnections formed by deposition of a thick or thin film on an insulating “substrate”;

Technical Note

‘Circuit element’ means a single active or passive functional part of an electronic circuit, such as one diode, one transistor, one resistor, one capacitor, etc.

“flight control optical sensor array” (Category 7) means a network of distributed optical sensors, using “laser” beams, to provide real-time flight control data for on-board processing;

“flight path optimisation” (Category 7) means a procedure that minimises deviations from a four-dimensional (space and time) desired trajectory based on maximising performance or effectiveness for mission tasks;

“fly-by-light system” (Category 7) means a primary digital flight control system employing feedback to control the aircraft during flight, where the commands to the effectors or actuators are optical signals;

“fly-by-wire system” (Category 7) means a primary digital flight control system employing feedback to control the aircraft during flight, where the commands to the effectors or actuators are electrical signals;

“focal plane array” (Category 6) means a linear or two-dimensional planar layer, or combination of planar layers, of individual detector elements, with or without readout electronics, which work in the focal plane;

Note

“Focal plane array” does not include a stack of single detector elements or any two, three or four element detectors provided time delay and integration is not performed within the element.

“fractional bandwidth” (Categories 3, 5) means the “instantaneous bandwidth” divided by the centre frequency, expressed as a percentage;

“frequency hopping” (Categories 5, 6) means a form of “spread spectrum” in which the transmission frequency of a single communication channel is made to change by a random or pseudo-random sequence of discrete steps;

“frequency mask trigger” (Category 3) for “signal analysers” means a mechanism where the trigger function is able to select a frequency range to be triggered on as a subset of the acquisition bandwidth while ignoring other signals that may also be present within the same acquisition bandwidth. A “frequency mask trigger” may contain more than one independent set of limits;

“frequency switching time” (Category 3) means the time (i.e. delay) taken by a signal when switched from an initial specified output frequency, to arrive at or within $\pm 0.05\%$ of a final specified output frequency. Items having a specified frequency range of less than $\pm 0.05\%$ around their centre frequency are defined to be incapable of frequency switching;

“frequency synthesiser” (Category 3) means any kind of frequency source, regardless of the actual technique used, providing a multiplicity of simultaneous or alternative output frequencies, from one or more outputs, controlled by, derived from or disciplined by a lesser number of standard (or master) frequencies;

“fuel cell” (Category 8) means an electrochemical device that converts chemical energy directly into Direct Current (DC) electricity by consuming fuel from an external source;

“fusible” (Category 1) means capable of being cross-linked or polymerised further (cured) by the use of heat, radiation, catalysts, etc., or that can be melted without pyrolysis (charring);

“gas atomisation” (Category 1) means a process to reduce a molten stream of metal alloy to droplets of 500 micrometre diameter or less by a high pressure gas stream;

“geographically dispersed” (Category 6) means a state where each location is distant from any other more than 1,500 m in any direction. Mobile sensors are always considered “geographically dispersed”;

“guidance set” (Category 7) means systems that integrate the process of measuring and computing a vehicle’s position and velocity (i.e. navigation) with that of computing and sending commands to the vehicle’s flight control systems to correct the trajectory;

“hot isostatic densification” (Category 2) means the process of pressurising a casting at temperatures exceeding 375 K (102°C) in a closed cavity through various media (gas, liquid, solid particles, etc.) to create equal force in all directions to reduce or eliminate internal voids in the casting;

“hybrid integrated circuit” (Category 3) means any combination of integrated circuit or circuits, or integrated circuit with ‘circuit elements’ or ‘discrete components’ connected together to perform one or more specific functions, and having all of the following characteristics:

- a. Containing at least one unencapsulated device;
- b. Connected together using typical IC production methods;
- c. Replaceable as an entity; and
- d. Not normally capable of being disassembled;

Technical Note 1

‘Circuit element’ means a single active or passive functional part of an electronic circuit, such as one diode, one transistor, one resistor, one capacitor, etc.

Technical Note 2

‘Discrete component’ means a separately packaged ‘circuit element’ with its own external connections.

“image enhancement” (Category 4) means the processing of externally derived information-bearing images by algorithms such as time compression, filtering, extraction, selection, correlation, convolution or transformations between domains (e.g. fast Fourier transform or Walsh transform). This does not include algorithms using only linear or rotational transformation of a single image, such as translation, feature extraction, registration or false coloration;

“immunotoxin” (Category 1) means a conjugate of one cell specific monoclonal antibody and a “toxin” or “sub-unit of toxin”, that selectively affects diseased cells;

“information security” (Categories 4, 5) means all the means and functions ensuring the accessibility, confidentiality or integrity of information or communications, excluding the means and functions intended to safeguard against malfunctions. “Information security” includes “cryptography”, “cryptographic activation”, ‘cryptanalysis’, protection against compromising emanations and computer security;

Technical Note

‘Cryptanalysis’ means analysis of a cryptographic system or its inputs and outputs to derive confidential variables or sensitive data, including clear text.

“instantaneous bandwidth” (Categories 3, 5) means the bandwidth over which output power remains constant within 3 dB without adjustment of other operating parameters;

“instrumented range” (Category 6) means the specified unambiguous display range of a radar;

“insulation” (Category 9) means insulation that is applied to the components of a rocket motor, i.e. the case, nozzle, inlets, case closures, and includes cured or semi-cured compounded rubber sheet stock containing an insulating or refractory material. It may also be incorporated as stress relief boots or flaps;

“interior lining” (Category 9) means interior lining that is suited for the bond interface between the solid propellant and the case or insulating liner, and is usually a liquid polymer based dispersion of refractory or insulating materials, e.g. carbon filled hydroxyl terminated polybutadiene (HTPB) or other polymer with added curing agents sprayed or screeded over a case interior;

“intrinsic magnetic gradiometer” (Category 6) means a single magnetic field gradient sensing element and associated electronics the output of which is a measure of magnetic field gradient;

N.B.

See also “magnetic gradiometer”.

“intrusion software” (Category 4) means “software” specially designed or modified to avoid detection by ‘monitoring tools’, or to defeat ‘protective countermeasures’, of a computer or network-capable device, and performing any of the following:

- a. The extraction of data or information, from a computer or network-capable device, or the modification of system or user data; or
- b. The modification of the standard execution path of a programme or process in order to allow the execution of externally provided instructions;

Note 1

“Intrusion software” does not include any of the following:

- a. *Hypervisors, debuggers or Software Reverse Engineering (SRE) tools;*
- b. *Digital Rights Management (DRM) “software”; or*
- c. *“Software” designed to be installed by manufacturers, administrators or users, for the purposes of asset tracking or recovery.*

Note 2

Network-capable devices include mobile devices and smart meters.

Technical Notes

1. *‘Monitoring tools’ means “software” or hardware devices, that monitor system behaviours or processes running on a device. This includes antivirus (AV) products, end point security products, Personal Security Products (PSP), Intrusion Detection Systems (IDS), Intrusion Prevention Systems (IPS) or firewalls.*

2. *‘Protective countermeasures’ means techniques designed to ensure the safe execution of code, such as Data Execution Prevention (DEP), Address Space Layout Randomisation (ASLR) or sandboxing.*

“isolated live cultures” (Category 1) includes live cultures in dormant form and in dried preparations;

“isostatic presses” (Category 2) means equipment capable of pressurising a closed cavity through various media (e.g. gas, liquid, solid particles, etc.) to create equal pressure in all directions within the cavity upon a workpiece or material;

“laser” (Categories 0, 2, 3, 5, 6, 7, 8, 9) means an assembly of components which produce both spatially and temporally coherent light that is amplified by stimulated emission of radiation;

N.B.

See also:

- “Chemical laser”;
- “Super High Power Laser”;
- “Transfer laser”.

“library” (Category 1) (parametric technical database) means a collection of technical information, reference to which may enhance the performance of relevant systems, equipment or components;

“lighter-than-air vehicles” (Category 9) means balloons and airships that rely on hot air or other lighter-than-air gases such as helium or hydrogen for their lift;

“linearity” (Category 2) (usually measured in terms of non-linearity) means the maximum deviation of the actual characteristic (average of upscale and downscale readings), positive or negative, from a straight line so positioned as to equalise and minimise the maximum deviations;

“local area network” (Categories 4, 5) means a data communication system having all of the following characteristics:

- a. Allows an arbitrary number of independent ‘data devices’ to communicate directly with each other; and
- b. Is confined to a geographical area of moderate size (e.g. office building, plant, campus, warehouse);

Technical Note

‘Data device’ means equipment capable of transmitting or receiving sequences of digital information.

“magnetic gradiometers” (Category 6) means instruments designed to detect the spatial variation of magnetic fields from sources external to the instrument. They consist of multiple “magnetometers” and associated electronics the output of which is a measure of magnetic field gradient;

N.B.

See also “intrinsic magnetic gradiometer”.

“magnetometers” (Category 6) means instruments designed to detect magnetic fields from sources external to the instrument. They consist of a single magnetic field sensing element and associated electronics the output of which is a measure of the magnetic field;

“main storage” (Category 4) means the primary storage for data or instructions for rapid access by a central processing unit. It consists of the internal storage of a “digital computer” and any hierarchical extension thereto, such as cache storage or non-sequentially accessed extended storage;

“materials resistant to corrosion by UF₆” (Category 0) means copper, copper alloys, stainless steel, aluminium, aluminium oxide, aluminium alloys, nickel or alloys containing 60% or more nickel by weight and fluorinated hydrocarbon polymers;

“matrix” (Categories 1, 2, 9) means a substantially continuous phase that fills the space between particles, whiskers or fibres;

“measurement uncertainty” (Category 2) means the characteristic parameter which specifies in what range around the output value the correct value of the measurable variable lies with a confidence level of 95%. It includes the uncorrected systematic deviations, the uncorrected backlash and the random deviations (Ref. ISO 10360-2);

“mechanical alloying” (Category 1) means an alloying process resulting from the bonding, fracturing and rebonding of elemental and master alloy powders by mechanical impact. Non-metallic particles may be incorporated in the alloy by addition of the appropriate powders;

“melt extraction” (Category 1) means a process to ‘solidify rapidly’ and extract a ribbon-like alloy product by the insertion of a short segment of a rotating chilled block into a bath of a molten metal alloy;

Technical Note

‘Solidify rapidly’ means solidification of molten material at cooling rates exceeding 1,000 K/s.

“melt spinning” (Category 1) means a process to ‘solidify rapidly’ a molten metal stream impinging upon a rotating chilled block, forming a flake, ribbon or rod-like product;

Technical Note

‘Solidify rapidly’ means solidification of molten material at cooling rates exceeding 1,000 K/s.

“microcomputer microcircuit” (Category 3) means a “monolithic integrated circuit” or “multichip integrated circuit” containing an arithmetic logic unit (ALU) capable of executing general purpose instructions from an internal storage, on data contained in the internal storage;

Note

The internal storage may be augmented by an external storage.

“microprocessor microcircuit” (Category 3) means a “monolithic integrated circuit” or “multichip integrated circuit” containing an arithmetic logic unit (ALU) capable of executing a series of general purpose instructions from an external storage;

Note 1

“Microprocessor microcircuit” normally does not contain integral user-accessible storage, although storage present on-the-chip may be used in performing its logic function.

Note 2

“Microprocessor microcircuit” includes chip sets which are designed to operate together to provide the function of a “microprocessor microcircuit”.

“microorganisms” (Category 2) means bacteria, viruses, mycoplasmas, rickettsiae, chlamydiae or fungi, whether natural, enhanced or modified, either in the form of “isolated live cultures” or as material including living material which has been deliberately inoculated or contaminated with such cultures;

“missiles” (Categories 1, 3, 6, 7, 9) means complete rocket systems and unmanned aerial vehicle systems, capable of delivering at least 500 kg payload to a range of at least 300 km;

“monofilament” (Category 1) or filament means the smallest increment of fibre, usually several micrometres in diameter;

“monolithic integrated circuit” (Category 3) means a combination of passive or active ‘circuit elements’ or both which:

- a. Are formed by means of diffusion processes, implantation processes or deposition processes in or on a single semiconducting piece of material, a so-called ‘chip’;
- b. Can be considered as indivisibly associated; and
- c. Perform the function or functions of a circuit;

Technical Note

‘Circuit element’ means a single active or passive functional part of an electronic circuit, such as one diode, one transistor, one resistor or one capacitor, etc.

“monospectral imaging sensors” (Category 6) means sensors capable of acquisition of imaging data from one discrete spectral band;

“multichip integrated circuit” (Category 3) means two or more “monolithic integrated circuits” bonded to a common “substrate”;

“multispectral imaging sensors” (Category 6) means sensors capable of simultaneous or serial acquisition of imaging data from two or more discrete spectral bands. Sensors having more than twenty discrete spectral bands are sometimes referred to as hyperspectral imaging sensors;

“natural uranium” (Category 0) means uranium containing the mixtures of isotopes occurring in nature;

“network access controller” (Category 4) means a physical interface to a distributed switching network. It uses a common medium which operates throughout at the same “digital transfer rate” using arbitration (e.g. token or carrier sense) for transmission. Independently from any other, it selects data packets or data groups (e.g. Ref. IEEE 802) addressed to it. It is an assembly that can be integrated into computer or telecommunications equipment to provide communications access;

“neural computer” (Category 4) means a computational device designed or modified to mimic the behaviour of a neuron or a collection of neurons, i.e. a computational device which is distinguished by its hardware capability to modulate the weights and numbers of the interconnections of a multiplicity of computational components based on previous data;

“nuclear reactor” (Category 0) means a complete reactor capable of operation so as to maintain a controlled self-sustaining fission chain reaction. A “nuclear reactor” includes all the items within or attached directly to the reactor vessel, the equipment which controls the level of power in the core, and the components which normally contain, come into direct contact with or control the primary coolant of the reactor core;

“numerical control” (Category 2) means the automatic control of a process performed by a device that makes use of numeric data usually introduced as the operation is in progress (Ref. ISO 2382);

“object code” (GSN) means an equipment executable form of a convenient expression of one or more processes (“source code” or source language) which has been compiled by programming system;

“Operations, Administration or Maintenance” (“OAM”) (Category 5) means performing one or more of the following tasks:

- a. Establishing or managing any of the following:
 1. Accounts or privileges of users or administrators;
 2. Settings of an item; or
 3. Authentication data in support of the tasks described in paragraph a.1. or a.2.;
- b. Monitoring or managing the operating condition or performance of an item; or
- c. Managing logs or audit data in support of any of the tasks described in paragraph a. or b.;

Note

“OAM” does not include any of the following tasks or their associated key management functions:

- a. *Provisioning or upgrading any cryptographic functionality that is not directly related to establishing or managing authentication data in support of the tasks described in paragraph a.1. or a.2. above; or*
- b. *Performing any cryptographic functionality on the forwarding or data plane of an item.*

“optical amplification” (Category 5) in optical communications, means an amplification technique that introduces a gain of optical signals that have been generated by a separate optical source, without conversion to electrical signals, i.e. using semiconductor optical amplifiers, optical fibre luminescent amplifiers;

“optical computer” (Category 4) means a computer designed or modified to use light to represent data and whose computational logic elements are based on directly coupled optical devices;

“optical integrated circuit” (Category 3) means a “monolithic integrated circuit” or a “hybrid integrated circuit”, containing one or more parts designed to function as a photosensor or photoemitter or to perform an optical or an electro-optical function or functions;

“optical switching” (Category 5) means the routing of or switching of signals in optical form without conversion to electrical signals;

“overall current density” (Category 3) means the total number of ampere-turns in the coil (i.e. the sum of the number of turns multiplied by the maximum current carried by each turn) divided by the total cross-section of the coil (comprising the superconducting filaments, the metallic matrix in which the superconducting filaments are embedded, the encapsulating material, any cooling channels, etc.);

“participating state” (Categories 7, 9) means a state participating in the Wassenaar Arrangement (details of which are set out in <http://www.wassenaar.org/participants/index.html>);

“peak power” (Category 6) means the highest power attained in the “pulse duration”;

“personal area network” (Category 5) means a data communication system having all of the following characteristics:

- a. Allows an arbitrary number of independent or interconnected ‘data devices’ to communicate directly with each other; and
- b. Is confined to the communication between devices within the immediate vicinity of an individual person or device controller (e.g. single room, office, or automobile and their nearby surrounding spaces);

Technical Note

‘Data device’ means equipment capable of transmitting or receiving sequences of digital information.

“plasma atomisation” (Category 1) means a process to reduce a molten stream or solid metal to droplets of 500 µm diameter or less, using plasma torches in an inert gas environment;

“power management” (Category 7) means changing the transmitted power of the altimeter signal so that received power at the “aircraft” altitude is always at the minimum necessary to determine the altitude;

“previously separated” (Category 1) means the application of any process intended to increase the concentration of the controlled isotope;

“primary flight control” (Category 7) means an “aircraft” stability or manoeuvring control using force or moment generators, i.e. aerodynamic control surfaces or propulsive thrust vectoring;

“principal element” (Category 4), as it applies in Category 4, is a “principal element” when its replacement value is more than 35% of the total value of the system of which it is an element. Element value is the price paid for the element by the manufacturer of the system, or by the system integrator. Total value is the normal international selling price to unrelated parties at the point of manufacture or consolidation of shipment;

“production” (GTN, NTN, All Categories) has the same meaning as in the Act;

“production equipment” (Categories 1, 7, 9) means tooling, templates, jigs, mandrels, moulds, dies, fixtures, alignment mechanisms, test equipment, other machinery and components therefor, limited to those specially designed or modified for “development” or for one or more phases of “production”;

“production facilities” (Categories 7, 9) means “production equipment” and specially designed software therefor integrated into installations for “development” or for one or more phases of “production”;

“programme” (Categories 2, 6) means a sequence of instructions to carry out a process in, or convertible into, a form executable by an electronic computer;

“pulse compression” (Category 6) means the coding and processing of a radar signal pulse of long time duration to one of short time duration, while maintaining the benefits of high pulse energy;

“pulse duration” (Category 6) means the duration of a “laser” pulse and means the time between the half-power points on the leading edge and trailing edge of an individual pulse;

“pulsed laser” (Category 6) means a “laser” having a “pulse duration” that is less than or equal to 0.25 seconds;

“quantum cryptography” (Category 5) means a family of techniques for the establishment of shared key for “cryptography” by measuring the quantum-mechanical properties of a physical system (including those physical properties explicitly governed by quantum optics, quantum field theory or quantum electrodynamics);

“radar frequency agility” (Category 6) means any technique which changes, in a pseudo-random sequence, the carrier frequency of a pulsed radar transmitter between pulses or between groups of pulses by an amount equal to or larger than the pulse bandwidth;

“radar spread spectrum” (Category 6) means any modulation technique for spreading energy originating from a signal with a relatively narrow frequency band, over a much wider band of frequencies, by using random or pseudo-random coding;

“radiant sensitivity” (Category 6) means Radiant sensitivity (mA/W) = $0.807 \times (\text{wavelength in nm}) \times \text{Quantum Efficiency (QE)}$;

Technical Note

QE is usually expressed as a percentage; however, for the purposes of this formula QE is expressed as a decimal number less than one, e.g. 78% is 0.78.

“real-time bandwidth” (Category 3) for “signal analysers” means the widest frequency range for which the analyser can continuously transform time-domain data entirely into frequency-domain results, using a Fourier or other discrete time transformation that processes every incoming time point without gaps or windowing effects that causes a reduction of measured amplitude of more than 3 dB below the actual signal amplitude, while outputting or displaying the transformed data;

“real-time processing” (Category 6) means the processing of data by a computer system providing a required level of service, as a function of available resources, within a guaranteed response time, regardless of the load of the system, when stimulated by an external event;

“repeatability” (Category 7) means the closeness of agreement among repeated measurements of the same variable under the same operating conditions when changes in conditions or non-operating periods occur between measurements (Ref. IEEE STD 528-2001 (one sigma standard deviation));

“required” (GTN, Categories 1-9), as applied to “technology”, refers to only that portion of “technology” which is peculiarly responsible for achieving or extending the controlled performance levels, characteristics or functions. Such “required” “technology” may be shared by different goods;

“resolution” (Category 2) means the least increment of a measuring device; on digital instruments, the least significant bit. (Ref. ANSI B-89.1.12);

“riot control agent” (Category 1) means substances which, under the expected conditions of use for riot control purposes, produce rapidly in human sensory irritation or disabling physical effects which disappear within a short time following termination of exposure;

Technical Note

Tear gases are a subset of “riot control agents”.

“robot” (Categories 2, 8) means a manipulation mechanism, which may be of the continuous path or of the point-to-point variety, may use sensors, and has all the following characteristics:

- a. Is multifunctional;
- b. Is capable of positioning or orienting material, parts, tools or special devices through variable movements in three dimensional space;
- c. Incorporates three or more closed or open loop servo-devices which may include stepping motors; and
- d. Has “user-accessible programmability” by means of teach or playback method or by means of an electronic computer which may be a programmable logic controller, i.e. without mechanical intervention;

Note

“Robot” does not include the following devices:

- a. *Manipulation mechanisms which are only manually or teleoperator controllable;*
- b. *Fixed sequence manipulation mechanisms which are automated moving devices, operating according to mechanically fixed programmed motions. The programme is mechanically limited by fixed stops, such as pins or cams. The sequence of motions and the selection of paths or angles are not variable or changeable by mechanical, electronic or electrical means;*
- c. *Mechanically controlled variable sequence manipulation mechanisms which are automated moving devices, operating according to mechanically fixed programmed motions. The programme is mechanically limited by fixed, but adjustable stops, such as pins or cams. The sequence of motions and the selection of paths or angles are variable within the fixed programme pattern. Variations or modifications of the programme pattern (e.g. changes of pins or exchanges of cams) in one or more motion axes are accomplished only through mechanical operations;*
- d. *Non-servo-controlled variable sequence manipulation mechanisms which are automated moving devices, operating according to mechanically fixed programmed motions. The programme is variable but the sequence proceeds only by the binary signal from mechanically fixed electrical binary devices or adjustable stops;*

- e. *Stacker cranes defined as Cartesian coordinate manipulator systems manufactured as an integral part of a vertical array of storage bins and designed to access the contents of those bins for storage or retrieval.*

“rotary atomisation” (Category 1) means a process to reduce a stream or pool of molten metal to droplets to a diameter of 500 micrometre or less by centrifugal force;

“roving” (Category 1) means a bundle (typically 12-120) of approximately parallel ‘strands’;

Technical Note

‘Strand’ means a bundle of “monofilaments” (typically over 200) arranged approximately parallel to each other.

“run-out” (Category 2) (out-of-true running) means radial displacement in one revolution of the main spindle measured in a plane perpendicular to the spindle axis at a point on the external or internal revolving surface to be tested. (Ref. ISO 230/1 1986, paragraph 5.61);

“scale factor” (gyro or accelerometer) (Category 7) means the ratio of change in output to a change in the input intended to be measured. “Scale factor” is generally evaluated as the slope of the straight line that can be fitted by the method of least squares to input-output data obtained by varying the input cyclically over the input range;

“settling time” (Category 3) means the time required for the output to come within one-half bit of the final value when switching between any two levels of the converter;

“SHPL” is equivalent to “super high power laser”;

“signal analysers” (Category 3) means apparatus capable of measuring and displaying basic properties of the single-frequency components of multi-frequency signals;

“signal processing” (Categories 3, 4, 5, 6) means the processing of externally derived information-bearing signals by algorithms such as time compression, filtering, extraction, selection, correlation, convolution or transformations between domains (e.g. fast Fourier transform or Walsh transform);

“software” (GSN, All Categories) means a collection of one or more “programmes” or ‘microprogrammes’ recorded, stored or embodied in any device;

Technical Note

‘Microprogramme’ means a sequence of elementary instructions, maintained in a special storage, the execution of which is initiated by the introduction of its reference instruction into an instruction register.

“source code” (or source language) (Categories 6, 7, 9) means a convenient expression of one or more processes which may be turned by a programming system into equipment executable form (“object code” (or object language));

“spacecraft” (Category 9) means active and passive satellites and space probes;

“spacecraft bus” (Category 9) means equipment that provides the support infrastructure of the “spacecraft” and location for the “spacecraft payload”;

“spacecraft payload” (Category 9) means equipment, attached to the “spacecraft bus”, designed to perform a mission in space (e.g. communications, observation, science);

“space-qualified” (Categories 3, 6, 7) means designed, manufactured or qualified through successful testing, for operation at altitudes greater than 100 km above the surface of the Earth;

Note

A determination that a specific item is “space-qualified” by virtue of testing does not mean that other items in the same production run or model series are “space-qualified” if not individually tested.

“special fissile material” (Category 0) means plutonium-239, uranium-233, ‘uranium enriched in the isotopes 235 or 233’, and any material containing the foregoing;

Technical Note

‘uranium enriched in the isotopes 235 or 233’ means uranium containing the isotopes 235 or 233, or both, in an amount such that the abundance ratio of the sum of these isotopes to the isotope 238 is more than the ratio of the isotope 235 to the isotope 238 occurring in nature (isotopic ratio 0.71 per cent).

“specific modulus” (Categories 0, 1, 9) means Young’s modulus in pascals, equivalent to N/m^2 divided by specific weight in N/m^3 , measured at a temperature of (296 ± 2) K ($(23 \pm 2)^\circ C$) and a relative humidity of $(50 \pm 5)\%$;

“specific tensile strength” (Categories 0, 1, 9) means ultimate tensile strength in pascals, equivalent to N/m^2 divided by specific weight in N/m^3 , measured at a temperature of (296 ± 2) K ($(23 \pm 2)^\circ C$) and a relative humidity of $(50 \pm 5)\%$;

“spinning mass gyros” (Category 7) means gyros which use a continually rotating mass to sense angular motion;

“splat quenching” (Category 1) means a process to ‘solidify rapidly’ a molten metal stream impinging upon a chilled block, forming a flake-like product;

Technical Note

‘Solidify rapidly’ means solidification of molten material at cooling rates exceeding 1,000 K/s.

“spread spectrum” (Category 5) means the technique whereby energy in a relatively narrow-band communication channel is spread over a much wider energy spectrum;

“spread spectrum” radar (Category 6) – see “radar spread spectrum”;

“stability” (Category 7) means the standard deviation (1 sigma) of the variation of a particular parameter from its calibrated value measured under stable temperature conditions. It can be expressed as a function of time;

“substrate” (Category 3) means a sheet of base material with or without an interconnection pattern and on which or within which ‘discrete components’ or integrated circuits or both can be located;

Technical Note

‘Discrete component’ means a separately packaged ‘circuit element’ with its own external connections.

Technical Note

‘Circuit element’ means a single active or passive functional part of an electronic circuit, such as one diode, one transistor, one resistor or one capacitor, etc.

“substrate blanks” (Categories 3, 6) means monolithic compounds with dimensions suitable for the production of optical elements such as mirrors or optical windows;

“sub-unit of toxin” (Category 1) means a structurally and functionally discrete component of a whole “toxin”;

“superalloys” (Categories 2, 9) means nickel-, cobalt- or iron-base alloys having strengths superior to any alloys in the AISI 300 series at temperatures over 922 K (649°C) under severe environmental and operating conditions;

“superconductive” (Categories 1, 3, 5, 6, 8) means materials, i.e. metals, alloys or compounds, which can lose all electrical resistance, i.e. which can attain infinite electrical conductivity and carry very large electrical currents without Joule heating;

Note

The “superconductive” state of a material is individually characterised by a “critical temperature”, a critical magnetic field, which is a function of temperature, and a critical current density which is, however, a function of both magnetic field and temperature.

“Super High Power Laser” (“SHPL”) (Category 6) means a “laser” capable of delivering (the total or any portion of) the output energy exceeding 1 kJ within 50 ms or having an average or CW power exceeding 20 kW;

“superplastic forming” (Categories 1, 2) means a deformation process using heat for metals that are normally characterised by low values of elongation (less than 20%) at the breaking point as determined at room temperature by conventional tensile strength testing, in order to achieve elongations during processing which are at least 2 times those values;

“symmetric algorithm” (Category 5) means a cryptographic algorithm using an identical key for both encryption and decryption;

Note

A common use of “symmetric algorithms” is to safeguard confidentiality of data.

“systolic array computer” (Category 4) means a computer where the flow and modification of the data is dynamically controllable at the logic gate level by the user;

“tape” (Category 1) means a material constructed of interlaced or unidirectional “monofilaments”, ‘strands’, ‘rovings’, ‘tows’, ‘yarns’, etc., usually pre-impregnated with resin;

Technical Note

‘Strand’ is a bundle of “monofilaments” (typically over 200) arranged approximately parallel to each other.

“technology” (GTN, NTN, All Categories) means information (including information comprised in such documents as specifications, blueprints, plans, manuals, models, diagrams, formulae, tables and designs) that is necessary for the “development”, “production” or “use” of any goods;

“three dimensional integrated circuit” (Category 3) means a collection of semiconductor die, integrated together, and having vias passing completely through at least one die to establish interconnections between die;

“tilting spindle” (Category 2) means a tool-holding spindle which alters, during the machining process, the angular position of its centre line with respect to any other axis;

“time constant” (Category 6) means the time taken from the application of a light stimulus for the current increment to reach a value of $1-1/e$ times the final value (i.e. 63% of the final value);

“tip shroud” (Category 9) means a stationary ring component (solid or segmented) attached to the inner surface of the engine turbine casing or a feature at the outer tip of the turbine blade, which primarily provides a gas seal between the stationary and rotating components;

“total control of flight” (Category 7) means an automated control of “aircraft” state variables and flight path to meet mission objectives responding to real-time changes in data regarding objectives, hazards or other “aircraft”;

“total digital transfer rate” (Category 5) means the number of bits, including line coding, overhead and so forth per unit time passing between corresponding equipment in a digital transmission system;

N.B.

See also “digital transfer rate”.

“tow” (Category 1) means a bundle of “monofilaments”, usually approximately parallel to each other;

“toxins” (Categories 1, 2) means toxins in the form of deliberately isolated preparations or mixtures, no matter how produced, other than toxins present as contaminants of other materials such as pathological specimens, crops, foodstuffs or seed stocks of “microorganisms”;

“transfer laser” (Category 6) means a “laser” in which the lasing species is excited through the transfer of energy by collision of a non-lasing atom or molecule with a lasing atom or molecule species;

“tunable” (Category 6) means the ability of a “laser” to produce a continuous output at all wavelengths over a range of several “laser” transitions. A line selectable “laser” produces discrete wavelengths within one “laser” transition and is not considered “tunable”;

“unidirectional positioning repeatability” (Category 2) means the smaller of values R_{\uparrow} and R_{\downarrow} (forward and backward), as defined by 3.21 of ISO 230-2:2014 or national equivalents, of an individual machine tool axis;

“Unmanned Aerial Vehicle” (“UAV”) (Category 9) means any aircraft capable of initiating flight and sustaining controlled flight and navigation without any human presence on board;

“use” (GTN, NTN, All Categories) has the same meaning as in the Act;

“user accessible programmability” (Category 6) means the facility allowing a user to insert, modify or replace “programmes” by means other than:

- a. A physical change in wiring or interconnections; or
- b. The setting of function controls including entry of parameters;

“vaccine” (Category 1) means a medicinal product in a pharmaceutical formulation licensed by, or having marketing or clinical trial authorisation from, the regulatory authorities of either the country of manufacture or of use, which is intended to stimulate a protective immunological response in humans or animals in order to prevent disease in those to whom or to which it is administered;

“vacuum atomisation” (Category 1) means a process to reduce a molten stream of metal to droplets of a diameter of 500 micrometre or less by the rapid evolution of a dissolved gas upon exposure to a vacuum;

“variable geometry airfoils” (Category 7) means the use of trailing edge flaps or tabs, or leading edge slats or pivoted nose droop, the position of which can be controlled in flight;

“yarn” (Category 1) means a bundle of twisted ‘strands’.

Technical Note

‘Strand’ means a bundle of “monofilaments” (typically over 200) arranged approximately parallel to each other.

9. In this Part, a word or expression enclosed with single quotation marks (‘ ’) takes the definition set out against it in the Technical Note that follows immediately after the provision in which the word or expression appears.

Subdivision 6 — Acronyms and Abbreviations used in this Part

The acronyms and abbreviations used in this Part and set out in the first column have the meanings set out against them in the second column.

<i>Acronym or Abbreviation</i>	<i>Meaning</i>
ABEC	Annular Bearing Engineers Committee
AGMA	American Gear Manufacturers' Association
AHRS	attitude and heading reference systems
AISI	American Iron and Steel Institute
ALU	arithmetic logic unit
ANSI	American National Standards Institute
ASTM	the American Society for Testing and Materials
ATC	air traffic control
CAD	computer-aided design
CAS	Chemical Abstract Service
CDU	control and display unit
CEP	circular error probable
CNTD	controlled nucleation thermal disposition
CPU	Central processing unit
CVD	chemical vapour deposition
CW	chemical warfare
CW (for lasers)	continuous wave
DME	distance measuring equipment
DS	directionally solidified
EB-PVD	electron beam physical vapour deposition
ECM	electro-chemical machining
EDM	electrical discharge machines
EEPROMS	electrically erasable programmable read only memory
EMC	electromagnetic compatibility
FFT	Fast Fourier Transform
GLONASS	global navigation satellite system

GPS	global positioning system
HBT	hetero-bipolar transistors
HEMT	high electron mobility transistors
ICAO	International Civil Aviation Organisation
IEC	International Electro-technical Commission
IEEE	Institute of Electrical and Electronic Engineers
IFOV	instantaneous-field-of-view
ILS	instrument landing system
ISA	international standard atmosphere
ISAR	inverse synthetic aperture radar
ISO	International Organisation for Standardisation
ITU	International Telecommunication Union
JT	Joule-Thomson
LIDAR	light detection and ranging
LRU	line replaceable unit
Mach	ratio of speed of an object to speed of sound (after Ernst Mach)
MLS	microwave landing systems
MOCVD	metal organic chemical vapour deposition
MRI	magnetic resonance imaging
MTBF	mean-time-between-failures
MTTF	mean-time-to-failure
NDT	non-destructive test
PAR	precision approach radar
PIN	personal identification number
ppm	parts per million
QAM	quadrature-amplitude-modulation
RF	radio frequency
SACMA	Suppliers of Advanced Composite Materials Association
SAR	synthetic aperture radar
SC	single crystal

SLAR	sidelooking airborne radar
SRA	shoe replaceable assembly
SRAM	static random access memory
SSB	single sideband
SSR	secondary surveillance radar
TIR	total indicated reading
UV	ultraviolet
UTS	ultimate tensile strength
VOR	very high frequency omni-directional range
YAG	yttrium/aluminium garnet

Division 2 — List of Dual-Use Goods

<i>Category Code</i>	<i>Item Description</i>
CATEGORY 0 — NUCLEAR MATERIALS, FACILITIES, AND EQUIPMENT	
0A	Systems, Equipment and Components
0A001	<p>“Nuclear reactors” and specially designed or prepared equipment and components therefor, as follows:</p> <ol style="list-style-type: none"> a. “Nuclear reactors”; b. Metal vessels, or major shop-fabricated parts therefor, including the reactor vessel head for a reactor pressure vessel, specially designed or prepared to contain the core of a “nuclear reactor”; c. Manipulative equipment specially designed or prepared for inserting or removing fuel in a “nuclear reactor”; d. Control rods specially designed or prepared for the control of the fission process in a “nuclear reactor”, support or suspension structures therefor, rod drive mechanisms and rod guide tubes; e. Pressure tubes specially designed or prepared to contain both fuel elements and the primary coolant in a “nuclear reactor”; f. Zirconium metal tubes or zirconium alloy tubes (or assemblies of tubes) specially designed or prepared for use as fuel cladding in a “nuclear reactor”, and in quantities exceeding 10 kg; <p><u><i>N.B.</i></u></p> <p><i>For zirconium pressure tubes, see Category Code 0A001.e. and for calandria tubes, see Category Code 0A001.h.</i></p> <ol style="list-style-type: none"> g. Coolant pumps or circulators specially designed or prepared for circulating the primary coolant of “nuclear reactors”; h. ‘Nuclear reactor internals’ specially designed or prepared for use in a “nuclear reactor”, including support columns for the core, fuel channels, calandria tubes, thermal shields, baffles, core grid plates, and diffuser plates;

Category Code	Item Description
	<p data-bbox="413 325 596 354"><u>Technical Note</u></p> <p data-bbox="413 367 1142 567"><i>In Category Code 0A001.h., ‘nuclear reactor internals’ means any major structure within a reactor vessel which has one or more functions such as supporting the core, maintaining fuel alignment, directing primary coolant flow, providing radiation shields for the reactor vessel, and guiding in-core instrumentation.</i></p> <p data-bbox="346 586 747 614">i. Heat exchangers as follows:</p> <ol data-bbox="413 634 1142 852" style="list-style-type: none"> <li data-bbox="413 634 1142 738">1. Steam generators specially designed or prepared for the primary, or intermediate, coolant circuit of a “nuclear reactor”; <li data-bbox="413 757 1142 852">2. Other heat exchangers specially designed or prepared for use in the primary coolant circuit of a “nuclear reactor”; <p data-bbox="413 872 473 900"><u>Note</u></p> <p data-bbox="413 913 1142 1018"><i>Category Code 0A001.i. does not include heat exchangers for the supporting systems of the reactor, e.g. the emergency cooling system or the decay heat cooling system.</i></p> <p data-bbox="346 1037 1142 1132">j. Neutron detectors specially designed or prepared for determining neutron flux levels within the core of a “nuclear reactor”;</p> <p data-bbox="346 1151 1142 1247">k. ‘External thermal shields’ specially designed or prepared for use in a “nuclear reactor” for the reduction of heat loss and also for the containment vessel protection.</p> <p data-bbox="413 1266 596 1294"><u>Technical Note</u></p> <p data-bbox="413 1308 1142 1443"><i>In Category Code 0A001.k., ‘external thermal shields’ means major structures placed over the reactor vessel which reduce heat loss from the reactor and reduce temperature within the containment vessel.</i></p>

<i>Category Code</i>	<i>Item Description</i>
<p>0B</p> <p>0B001</p>	<p>Test, Inspection and Production Equipment</p> <p>Plant for the separation of isotopes of “natural uranium”, “depleted uranium” or “special fissile materials”, and specially designed or prepared equipment and components therefor, as follows:</p> <p>a. Plant specially designed for separating isotopes of “natural uranium”, “depleted uranium”, and “special fissile materials”, as follows:</p> <ol style="list-style-type: none"> 1. Gas centrifuge separation plant; 2. Gaseous diffusion separation plant; 3. Aerodynamic separation plant; 4. Chemical exchange separation plant; 5. Ion-exchange separation plant; 6. Atomic vapour “laser” isotope separation plant; 7. Molecular “laser” isotope separation plant; 8. Plasma separation plant; 9. Electromagnetic separation plant; <p>b. Gas centrifuges and assemblies and components, specially designed or prepared for gas centrifuge separation process, as follows:</p> <p><i>Technical Note</i></p> <p><i>In Category Code 0B001.b., ‘high strength-to-density ratio material’ means any of the following:</i></p> <ol style="list-style-type: none"> a. <i>Maraging steel capable of an ultimate tensile strength of 1.95 GPa or more;</i> b. <i>Aluminium alloys capable of an ultimate tensile strength of 0.46 GPa or more; <u>or</u></i> c. <i>“Fibrous or filamentary materials” with a “specific modulus” of more than 3.18×10^6 m and a “specific tensile strength” greater than 7.62×10^4 m.</i>

<i>Category Code</i>	<i>Item Description</i>
	<ol style="list-style-type: none"> 1. Gas centrifuges; 2. Complete rotor assemblies; 3. Rotor tube cylinders with a wall thickness of 12 mm or less, a diameter of between 75 mm and 650 mm, made from ‘high strength-to-density ratio materials’; 4. Rings or bellows with a wall thickness of 3 mm or less and a diameter of between 75 mm and 650 mm and designed to give local support to a rotor tube or to join a number together, made from ‘high strength-to-density ratio materials’; 5. Baffles of between 75 mm and 650 mm diameter for mounting inside a rotor tube, made from ‘high strength-to-density ratio materials’; 6. Top or bottom caps of between 75 mm and 650 mm diameter to fit the ends of a rotor tube, made from ‘high strength-to-density ratio materials’; 7. Magnetic suspension bearings as follows: <ol style="list-style-type: none"> a. Bearing assemblies consisting of an annular magnet suspended within a housing made of or protected by “materials resistant to corrosion by UF₆” containing a damping medium and having the magnet coupling with a pole piece or second magnet fitted to the top cap of the rotor; b. Active magnetic bearings specially designed or prepared for use with gas centrifuges; 8. Specially prepared bearings comprising a pivot-cup assembly mounted on a damper; 9. Molecular pumps comprised of cylinders having internally machined or extruded helical grooves and internally machined bores; 10. Ring-shaped motor stators for multiphase AC hysteresis (or reluctance) motors for synchronous operation within a vacuum at a frequency of 600 Hz or more and a power of 40 VA or more;

<i>Category Code</i>	<i>Item Description</i>
	<ol style="list-style-type: none"> <li data-bbox="417 325 1153 525">11. Centrifuge housing/recipients to contain the rotor tube assembly of a gas centrifuge, consisting of a rigid cylinder of wall thickness up to 30 mm with precision machined ends that are parallel to each other and perpendicular to the cylinder's longitudinal axis to within 0.05 degrees or less; <li data-bbox="417 544 1153 677">12. Scoops consisting of specially designed or prepared tubes for the extraction of UF₆ gas from within the rotor tube by a Pitot tube action and capable of being fixed to the central gas extraction system; <li data-bbox="417 696 1153 1030">13. Frequency changers (converters or inverters) specially designed or prepared to supply motor stators for gas centrifuge enrichment, having all of the following characteristics, and specially designed components therefor: <ol style="list-style-type: none"> <li data-bbox="498 887 1153 944">a. A multiphase frequency output of 600 Hz or greater; <u>and</u> <li data-bbox="498 963 1153 1030">b. High stability (with frequency control better than 0.2%); <li data-bbox="417 1049 1153 1422">14. Shut-off and control valves, as follows: <ol style="list-style-type: none"> <li data-bbox="498 1106 1153 1201">a. Shut-off valves specially designed or prepared to act on the feed, product or tails UF₆ gaseous streams of an individual gas centrifuge; <li data-bbox="498 1220 1153 1422">b. Bellows-sealed valves, shut-off or control, made of or protected by "materials resistant to corrosion by UF₆", with an inside diameter of 10 mm to 160 mm, specially designed or prepared for use in main or auxiliary systems of gas centrifuge enrichment plants;

<i>Category Code</i>	<i>Item Description</i>
	<p>c. Equipment and components, specially designed or prepared for gaseous diffusion separation process, as follows:</p> <ol style="list-style-type: none"> 1. Gaseous diffusion barriers made of porous metallic, polymer or ceramic “materials resistant to corrosion by UF₆” with a pore size of 10 nm to 100 nm, a thickness of 5 mm or less, and, for tubular forms, a diameter of 25 mm or less; 2. Gaseous diffuser housings made of or protected by “materials resistant to corrosion by UF₆”; 3. Compressors or gas blowers with a suction volume capacity of 1 m³/min or more of UF₆, discharge pressure up to 500 kPa and having a pressure ratio of 10:1 or less, and made of or protected by “materials resistant to corrosion by UF₆”; 4. Rotary shaft seals for compressors or blowers specified in Category Code 0B001.c.3. and designed for a buffer gas in-leakage rate of less than 1,000 cm³/min; 5. Heat exchangers made of or protected by “materials resistant to corrosion by UF₆”, and designed for a leakage pressure rate of less than 10 Pa per hour under a pressure differential of 100 kPa; 6. Bellows-sealed valves, manual or automated, shut-off or control, made of or protected by “materials resistant to corrosion by UF₆”; <p>d. Equipment and components, specially designed or prepared for aerodynamic separation process, as follows:</p> <ol style="list-style-type: none"> 1. Separation nozzles consisting of slit-shaped, curved channels having a radius of curvature less than 1 mm, resistant to corrosion by UF₆, and having a knife-edge contained within the nozzle which separates the gas flowing through the nozzle into two streams; 2. Cylindrical or conical tubes, (vortex tubes), made of or protected by “materials resistant to corrosion by UF₆” and with one or more tangential inlets; 3. Compressors or gas blowers made of or protected by “materials resistant to corrosion by UF₆”, and rotary shaft seals therefor;

<i>Category Code</i>	<i>Item Description</i>
	<ol style="list-style-type: none"> 4. Heat exchangers made of or protected by “materials resistant to corrosion by UF₆”; 5. Separation element housings, made of or protected by “materials resistant to corrosion by UF₆” to contain vortex tubes or separation nozzles; 6. Bellows-sealed valves, manual or automated, shut-off or control, made of or protected by “materials resistant to corrosion by UF₆”, with a diameter of 40 mm or more; 7. Process systems for separating UF₆ from carrier gas (hydrogen or helium) to 1 ppm UF₆ content or less, including: <ol style="list-style-type: none"> a. Cryogenic heat exchangers and cryoseparators capable of temperatures of 153 K (-120°C) or less; b. Cryogenic refrigeration units capable of temperatures of 153 K (-120°C) or less; c. Separation nozzle or vortex tube units for the separation of UF₆ from carrier gas; d. UF₆ cold traps capable of freezing out UF₆; e. Equipment and components, specially designed or prepared for chemical exchange separation process, as follows: <ol style="list-style-type: none"> 1. Fast-exchange liquid-liquid pulse columns with stage residence time of 30 seconds or less and resistant to concentrated hydrochloric acid (e.g. made of or protected by suitable plastic materials such as fluorinated hydrocarbon polymers or glass); 2. Fast-exchange liquid-liquid centrifugal contactors with stage residence time of 30 seconds or less and resistant to concentrated hydrochloric acid (e.g. made of or protected by suitable plastic materials such as fluorinated hydrocarbon polymers or glass); 3. Electrochemical reduction cells resistant to concentrated hydrochloric acid solutions, for reduction of uranium from one valence state to another;

<i>Category Code</i>	<i>Item Description</i>
	<ol style="list-style-type: none"> <li data-bbox="413 325 1145 525">4. Electrochemical reduction cells feed equipment to take U^{+4} from the organic stream and, for those parts in contact with the process stream, made of or protected by suitable materials (e.g. glass, fluorocarbon polymers, polyphenyl sulphate, polyether sulfone and resin-impregnated graphite); <li data-bbox="413 544 1145 706">5. Feed preparation systems for producing high purity uranium chloride solution consisting of dissolution, solvent extraction and/or ion exchange equipment for purification and electrolytic cells for reducing the uranium U^{+6} or U^{+4} to U^{+3}; <li data-bbox="413 725 1145 763">6. Uranium oxidation systems for oxidation of U^{+3} to U^{+4}; <p data-bbox="350 782 1145 849">f. Equipment and components, specially designed or prepared for ion-exchange separation process, as follows:</p> <ol style="list-style-type: none"> <li data-bbox="413 868 1145 1229">1. Fast reacting ion-exchange resins, pellicular or porous macro-reticulated resins in which the active chemical exchange groups are limited to a coating on the surface of an inactive porous support structure, and other composite structures in any suitable form, including particles or fibres, with diameters of 0.2 mm or less, resistant to concentrated hydrochloric acid and designed to have an exchange rate half-time of less than 10 seconds and capable of operating at temperatures in the range of 373 K (100°C) to 473 K (200°C); <li data-bbox="413 1249 1145 1487">2. Ion exchange columns (cylindrical) with a diameter greater than 1,000 mm, made of or protected by materials resistant to concentrated hydrochloric acid (e.g. titanium or fluorocarbon plastics) and capable of operating at temperatures in the range of 373 K (100°C) to 473 K (200°C) and pressures above 0.7 MPa; <li data-bbox="413 1506 1145 1643">3. Ion exchange reflux systems (chemical or electrochemical oxidation or reduction systems) for regeneration of the chemical reducing or oxidising agents used in ion exchange enrichment cascades;

<i>Category Code</i>	<i>Item Description</i>
	<p>g. Equipment and components, specially designed or prepared for laser-based separation processes using atomic vapour laser isotope separation, as follows:</p> <ol style="list-style-type: none"> 1. Uranium metal vaporisation systems designed to achieve a delivered power of 1 kW or more on the target for use in laser enrichment; 2. Liquid or vapour uranium metal handling systems specially designed or prepared for handling molten uranium, molten uranium alloys or uranium metal vapour for use in laser enrichment, and specially designed components therefor; <p><u>N.B.</u> See also Category Code 2A225.</p> <ol style="list-style-type: none"> 3. Product and tails collector assemblies for uranium metal in liquid or solid form, made of or protected by materials resistant to the heat and corrosion of uranium metal vapour or liquid, such as yttria-coated graphite or tantalum; 4. Separator module housings (cylindrical or rectangular vessels) for containing the uranium metal vapour source, the electron beam gun and the product and tails collectors; 5. “Lasers” or “laser” systems specially designed or prepared for the separation of uranium isotopes with a spectrum frequency stabilisation for operation over extended periods of time; <p><u>N.B.</u> See also Category Codes 6A005 and 6A205.</p>

<i>Category Code</i>	<i>Item Description</i>
	<p>h. Equipment and components, specially designed or prepared for laser-based separation processes using molecular laser isotope separation, as follows:</p> <ol style="list-style-type: none"> 1. Supersonic expansion nozzles for cooling mixtures of UF₆ and carrier gas to 150 K (-123°C) or less and made from “materials resistant to corrosion by UF₆”; 2. Product or tails collector components or devices specially designed or prepared for collecting uranium material or uranium tails material following illumination with laser light, made of “materials resistant to corrosion by UF₆”; 3. Compressors made of or protected by “materials resistant to corrosion by UF₆”, and rotary shaft seals therefor; 4. Equipment for fluorinating UF₅ (solid) to UF₆ (gas); 5. Process systems for separating UF₆ from carrier gas (e.g. nitrogen, argon or other gas) including: <ol style="list-style-type: none"> a. Cryogenic heat exchangers and cryoseparators capable of temperatures of 153 K (-120°C) or less; b. Cryogenic refrigeration units capable of temperatures of 153 K (-120°C) or less; c. UF₆ cold traps capable of freezing out UF₆; 6. “Lasers” or “laser” systems specially designed or prepared for the separation of uranium isotopes with a spectrum frequency stabilisation for operation over extended periods of time; <p><u>N.B.</u> See also Category Codes 6A005 and 6A205.</p>

<i>Category Code</i>	<i>Item Description</i>
	<p>i. Equipment and components, specially designed or prepared for plasma separation process, as follows:</p> <ol style="list-style-type: none"> 1. Microwave power sources and antennae for producing or accelerating ions, with an output frequency greater than 30 GHz and mean power output greater than 50 kW; 2. Radio frequency ion excitation coils for frequencies of more than 100 kHz and capable of handling more than 40 kW mean power; 3. Uranium plasma generation systems; 4. Not used; 5. Product and tails collector assemblies for uranium metal in solid form, made of or protected by materials resistant to the heat and corrosion of uranium vapour such as yttria-coated graphite or tantalum; 6. Separator module housings (cylindrical) for containing the uranium plasma source, radio-frequency drive coil and the product and tails collectors and made of a suitable non-magnetic material (e.g. stainless steel); <p>j. Equipment and components, specially designed or prepared for electromagnetic separation process, as follows:</p> <ol style="list-style-type: none"> 1. Ion sources, single or multiple, consisting of a vapour source, ioniser, and beam accelerator made of suitable non-magnetic materials (e.g. graphite, stainless steel, or copper) and capable of providing a total ion beam current of 50 mA or greater; 2. Ion collector plates for collection of enriched or depleted uranium ion beams, consisting of two or more slits and pockets and made of suitable non-magnetic materials (e.g. graphite or stainless steel); 3. Vacuum housings for uranium electromagnetic separators made of non-magnetic materials (e.g. stainless steel) and designed to operate at pressures of 0.1 Pa or lower; 4. Magnet pole pieces with a diameter greater than 2 m;

<i>Category Code</i>	<i>Item Description</i>
	<p>5. High voltage power supplies for ion sources, having all of the following characteristics:</p> <ol style="list-style-type: none"> a. Capable of continuous operation; b. Output voltage of 20,000 V or greater; c. Output current of 1 A or greater; <u>and</u> d. Voltage regulation of better than 0.01% over a period of 8 hours; <p><u>N.B.</u> See also Category Code 3A227.</p> <p>6. Magnet power supplies (high power, direct current) having all of the following characteristics:</p> <ol style="list-style-type: none"> a. Capable of continuous operation with a current output of 500 A or greater at a voltage of 100 V or greater; <u>and</u> b. Current or voltage regulation better than 0.01% over a period of 8 hours. <p><u>N.B.</u> See also Category Code 3A226.</p>
0B002	<p>Specially designed or prepared auxiliary systems, equipment and components, as follows, for isotope separation plant specified in Category Code 0B001, made of or protected by “materials resistant to corrosion by UF₆”:</p> <ol style="list-style-type: none"> a. Feed autoclaves, ovens or systems used for passing UF₆ to the enrichment process; b. Desublimers or cold traps, used to remove UF₆ from the enrichment process for subsequent transfer upon heating; c. Product and tails stations for transferring UF₆ into containers; d. Liquefaction or solidification stations used to remove UF₆ from the enrichment process by compressing, cooling and converting UF₆ to a liquid or solid form;

<i>Category Code</i>	<i>Item Description</i>
	<ul style="list-style-type: none"> e. Piping systems and header systems specially designed or prepared for handling UF₆ within gaseous diffusion, centrifuge or aerodynamic cascades; f. Vacuum systems and pumps, as follows: <ul style="list-style-type: none"> 1. Vacuum manifolds, vacuum headers or vacuum pumps having a suction capacity of 5 m³/minute or more; 2. Vacuum pumps specially designed for use in UF₆-bearing atmospheres made of, or protected by “materials resistant to corrosion by UF₆”; 3. Vacuum systems consisting of vacuum manifolds, vacuum headers and vacuum pumps, and designed for service in UF₆-bearing atmospheres; g. UF₆ mass spectrometers/ion sources capable of taking on-line samples from UF₆ gas streams and having all of the following: <ul style="list-style-type: none"> 1. Capable of measuring ions of 320 atomic mass units or greater and having a resolution of better than 1 part in 320; 2. Ion sources constructed of or protected by nickel, nickel-copper alloys with a nickel content of 60% or more by weight, or nickel-chrome alloys; 3. Electron bombardment ionisation sources; <u>and</u> 4. Having a collector system suitable for isotopic analysis.
0B003	<p>Plant for the conversion of uranium and equipment specially designed or prepared therefor, as follows:</p> <ul style="list-style-type: none"> a. Systems for the conversion of uranium ore concentrates to UO₃; b. Systems for the conversion of UO₃ to UF₆; c. Systems for the conversion of UO₃ to UO₂; d. Systems for the conversion of UO₂ to UF₄; e. Systems for the conversion of UF₄ to UF₆; f. Systems for the conversion of UF₄ to uranium metal;

<i>Category Code</i>	<i>Item Description</i>
	<ul style="list-style-type: none"> g. Systems for the conversion of UF₆ to UO₂; h. Systems for the conversion of UF₆ to UF₄; i. Systems for the conversion of UO₂ to UCl₄.
0B004	<p>Plant for the production or concentration of heavy water, deuterium and deuterium compounds and specially designed or prepared equipment and components therefor, as follows:</p> <ul style="list-style-type: none"> a. Plant for the production of heavy water, deuterium or deuterium compounds, as follows: <ul style="list-style-type: none"> 1. Water-hydrogen sulphide exchange plants; 2. Ammonia-hydrogen exchange plants; b. Equipment and components, as follows: <ul style="list-style-type: none"> 1. Water-hydrogen sulphide exchange towers with diameters of 1.5 m or more, capable of operating at pressures greater than or equal to 2 MPa; 2. Single stage, low head (i.e. 0.2 MPa) centrifugal blowers or compressors for hydrogen sulphide gas circulation (i.e. gas containing more than 70% H₂S) with a throughput capacity greater than or equal to 56 m³/second when operating at pressures greater than or equal to 1.8 MPa suction and having seals designed for wet H₂S service; 3. Ammonia-hydrogen exchange towers greater than or equal to 35 m in height with diameters of 1.5 m to 2.5 m capable of operating at pressures greater than 15 MPa; 4. Tower internals, including stage contactors, and stage pumps, including those which are submersible, for heavy water production utilising the ammonia-hydrogen exchange process; 5. Ammonia crackers with operating pressures greater than or equal to 3 MPa for heavy water production utilising the ammonia-hydrogen exchange process;

<i>Category Code</i>	<i>Item Description</i>
	<ol style="list-style-type: none"> 6. Infrared absorption analysers capable of on-line hydrogen/deuterium ratio analysis where deuterium concentrations are equal to or greater than 90%; 7. Catalytic burners for the conversion of enriched deuterium gas into heavy water utilising the ammonia-hydrogen exchange process; 8. Complete heavy water upgrade systems, or columns therefor, for the upgrade of heavy water to reactor-grade deuterium concentration; 9. Ammonia synthesis converters or synthesis units specially designed or prepared for heavy water production utilising the ammonia-hydrogen exchange process.
0B005	<p>Plant specially designed for the fabrication of “nuclear reactor” fuel elements and specially designed or prepared equipment therefor.</p> <p><u>Technical Note</u> <i>Specially designed or prepared equipment for the fabrication of “nuclear reactor” fuel elements includes equipment which:</i></p> <ol style="list-style-type: none"> a. <i>Normally comes into direct contact with or directly processes or controls the production flow of nuclear materials;</i> b. <i>Seals the nuclear materials within the cladding;</i> c. <i>Checks the integrity of the cladding or the seal;</i> d. <i>Checks the finish treatment of the sealed fuel; <u>or</u></i> e. <i>Is used for assembling reactor elements.</i>

Category Code	Item Description
0B006	<p>Plant for the reprocessing of irradiated “nuclear reactor” fuel elements, and specially designed or prepared equipment and components therefor.</p> <p><u>Note</u></p> <p>Category Code 0B006 includes:</p> <ol style="list-style-type: none"> a. <i>Plant for the reprocessing of irradiated “nuclear reactor” fuel elements including equipment and components which normally come into direct contact with and directly control the irradiated fuel and the major nuclear material and fission product processing streams;</i> b. <i>Fuel element chopping or shredding machines, i.e. remotely operated equipment to cut, chop or shear irradiated “nuclear reactor” fuel assemblies, bundles or rods;</i> c. <i>Dissolvers, critically safe tanks (e.g. small diameter, annular or slab tanks) specially designed or prepared for the dissolution of irradiated “nuclear reactor” fuel, which are capable of withstanding hot, highly corrosive liquids, and which can be remotely loaded and maintained;</i> d. <i>Solvent extractors, such as packed or pulsed columns, mixer settlers or centrifugal contactors, resistant to the corrosive effects of nitric acid and specially designed or prepared for use in a plant for the reprocessing of irradiated “natural uranium”, “depleted uranium” or “special fissile materials”;</i> e. <i>Holding or storage vessels specially designed to be critically safe and resistant to the corrosive effects of nitric acid;</i> <p><u>Technical Note</u></p> <p>Holding or storage vessels may have the following features:</p> <ol style="list-style-type: none"> 1. <i>Walls or internal structures with a boron equivalent (calculated for all constituent elements as defined in the note to Category Code 0C004) of at least two per cent;</i> 2. <i>A maximum diameter of 175 mm for cylindrical vessels; <u>or</u></i> 3. <i>A maximum width of 75 mm for either a slab or annular vessel.</i>

Category Code	Item Description
	<p><i>f. Neutron measurement systems specially designed or prepared for integration and use with automated process control systems in a plant for the reprocessing of irradiated “natural uranium”, “depleted uranium” or “special fissile materials”.</i></p>
0B007	<p>Plant for the conversion of plutonium and equipment specially designed or prepared therefor, as follows:</p> <ul style="list-style-type: none"> a. Systems for the conversion of plutonium nitrate to oxide; b. Systems for plutonium metal production.
0C	Materials
0C001	<p>“Natural uranium” or “depleted uranium” or thorium in the form of metal, alloy, chemical compound or concentrate and any other material containing one or more of the foregoing.</p> <p><u>Note</u></p> <p><i>Category Code 0C001 does not include the following:</i></p> <ul style="list-style-type: none"> a. <i>Four grammes or less of “natural uranium” or “depleted uranium” when contained in a sensing component in instruments;</i> b. <i>“Depleted uranium” specially fabricated for the following civil non-nuclear applications:</i> <ul style="list-style-type: none"> 1. <i>Shielding;</i> 2. <i>Packaging;</i> 3. <i>Ballasts having a mass not greater than 100 kg;</i> 4. <i>Counter-weights having a mass not greater than 100 kg;</i> c. <i>Alloys containing less than 5% thorium;</i> d. <i>Ceramic products containing thorium, which have been manufactured for non-nuclear use.</i>

Category Code	Item Description
0C002	<p>“Special fissile materials”.</p> <p><u>Note</u> <i>Category Code 0C002 does not include four “effective grammes” or less when contained in a sensing component in instruments.</i></p>
0C003	<p>Deuterium, heavy water (deuterium oxide) and other compounds of deuterium, and mixtures and solutions containing deuterium, in which the isotopic ratio of deuterium to hydrogen exceeds 1:5,000.</p>
0C004	<p>Graphite having a purity level of better than 5 parts per million ‘boron equivalent’ and with a density greater than 1.5 g/cm³ for use in a “nuclear reactor”, in quantities exceeding 1 kg.</p> <p><u>N.B.</u> <i>See also Category Code 1C107.</i></p> <p><u>Note 1</u> <i>For the purpose of Category Code 0C004, whether or not the exports of graphite meeting the above specifications are for “nuclear reactor” use is determined, at or before the time of export, by the competent authorities of the country in which the exporter is established.</i></p> <p><u>Note 2</u> <i>In Category Code 0C004, ‘boron equivalent’ (BE) means the sum of BE_Z for impurities (excluding BE_{carbon} since carbon is not considered an impurity) including boron, where:</i></p> $BE_z (\text{ppm}) = CF \times \text{concentration of element Z in ppm};$ <p>where CF is the conversion factor = $\frac{\sigma_z \times A_B}{\sigma_B \times A_z}$</p> <p><i>and σ_B and σ_z are the thermal neutron capture cross sections (in barns) for naturally occurring boron and element Z respectively; and A_B and A_z are the atomic masses of naturally occurring boron and element Z respectively.</i></p>

<i>Category Code</i>	<i>Item Description</i>
0C005	Specially prepared compounds or powders for the manufacture of gaseous diffusion barriers, resistant to corrosion by UF ₆ (e.g. nickel or alloy containing 60% or more nickel by weight, aluminium oxide and fully fluorinated hydrocarbon polymers), having a purity of 99.9% by weight or more and a particle size less than 10 µm measured by American Society for Testing and Materials (ASTM) B330 standard and a high degree of particle size uniformity.
0D	Software
0D001	“Software” specially designed or modified for the “development”, “production” or “use” of goods specified in this Category.
0E	Technology
0E001	“Technology” (according to the Nuclear Technology Note) for the “development”, “production” or “use” of goods specified in this Category.

<i>Category Code</i>	<i>Item Description</i>
CATEGORY 1 — SPECIAL MATERIALS AND RELATED EQUIPMENT	
1A	Systems, Equipment and Components
1A001	<p>Components made from fluorinated compounds, as follows:</p> <ol style="list-style-type: none"> a. Seals, gaskets, sealants or fuel bladders, specially designed for “aircraft” or aerospace use, made from more than 50% by weight of any of the materials specified in Category Code 1C009.b. or 1C009.c.; b. Piezoelectric polymers and copolymers, made from vinylidene fluoride (75-38-7) materials, specified in Category Code 1C009.a., having all of the following: <ol style="list-style-type: none"> 1. In sheet or film form; <u>and</u> 2. With a thickness exceeding 200 µm; c. Seals, gaskets, valve seats, bladders or diaphragms, having all of the following: <ol style="list-style-type: none"> 1. Made from fluoroelastomers containing at least one vinyl ether group as a constitutional unit; <u>and</u> 2. Specially designed for “aircraft”, aerospace or ‘missile’ use. <p style="margin-left: 2em;"><u>Note</u> <i>In Category Code 1A001.c., ‘missile’ means complete rocket systems and unmanned aerial vehicle systems.</i></p>
1A002	<p>“Composite” structures or laminates, having any of the following:</p> <p><u>N.B.</u> <i>See also Category Codes 1A202, 9A010 and 9A110.</i></p> <ol style="list-style-type: none"> a. Consisting of an organic “matrix” and materials specified in Category Code 1C010.c., 1C010.d. or 1C010.e.; <u>or</u>

<i>Category Code</i>	<i>Item Description</i>
	<p>b. Consisting of a metal or carbon “matrix”, and any of the following:</p> <ol style="list-style-type: none"> 1. Carbon “fibrous or filamentary materials” having all of the following: <ol style="list-style-type: none"> a. A “specific modulus” exceeding 10.15×10^6 m; <u>and</u> b. A “specific tensile strength” exceeding 17.7×10^4 m; <u>or</u> 2. Materials specified in Category Code 1C010.c. <p><u>Note 1</u> <i>Category Code 1A002 does not include composite structures or laminates made from epoxy resin impregnated carbon “fibrous or filamentary materials” for the repair of “civil aircraft” structures or laminates, having all of the following:</i></p> <ol style="list-style-type: none"> a. <i>An area not exceeding 1 m²;</i> b. <i>A length not exceeding 2.5 m; <u>and</u></i> c. <i>A width exceeding 15 mm.</i> <p><u>Note 2</u> <i>Category Code 1A002 does not include semi-finished items, specially designed for purely civilian applications, as follows:</i></p> <ol style="list-style-type: none"> a. <i>Sporting goods;</i> b. <i>Automotive industry;</i> c. <i>Machine tool industry;</i> d. <i>Medical applications.</i> <p><u>Note 3</u> <i>Category Code 1A002.b.1. does not include semi-finished items containing a maximum of two dimensions of interwoven filaments and specially designed for applications, as follows:</i></p> <ol style="list-style-type: none"> a. <i>Metal heat-treatment furnaces for tempering metals;</i> b. <i>Silicon boule production equipment.</i>

Category Code	Item Description
	<p><u>Note 4</u> <i>Category Code 1A002 does not include finished items specially designed for a specific application.</i></p>
1A003	<p>Manufactures of non-“fusible” aromatic polyimides in film, sheet, tape or ribbon form having any of the following:</p>
	<p>a. A thickness exceeding 0.254 mm; <u>or</u></p>
	<p>b. Coated or laminated with carbon, graphite, metals or magnetic substances.</p>
	<p><u>Note</u> <i>Category Code 1A003 does not include manufactures when coated or laminated with copper and designed for the production of electronic printed circuit boards.</i></p>
	<p><u>N.B.</u> <i>For “fusible” aromatic polyimides in any form, see Category Code 1C008.a.3.</i></p>
1A004	<p>Protective and detection equipment and components not specially designed for military use, as follows:</p>
	<p><u>N.B.</u> <i>See also Division 2 of Part 1 of this Schedule, and Category Codes 2B351 and 2B352.</i></p>
	<p>a. Full face masks, filter canisters and decontamination equipment therefor, designed or modified for defence against any of the following, and specially designed components therefor:</p>
	<p><u>Note</u> <i>Category Code 1A004.a. includes Powered Air Purifying Respirators (PAPR) that are designed or modified for defence against agents or materials, listed in Category Code 1A004.a.</i></p>

<i>Category Code</i>	<i>Item Description</i>
	<p data-bbox="413 325 599 357"><u>Technical Note</u></p> <p data-bbox="413 367 948 399"><i>For the purpose of Category Code 1A004.a.:</i></p> <ol style="list-style-type: none"> <li data-bbox="413 416 1022 449">1. Full face masks are also known as gas masks. <li data-bbox="413 466 955 498">2. Filter canisters include filter cartridges. <ol style="list-style-type: none"> <li data-bbox="413 515 991 548">1. Biological agents “adapted for use in war”; <li data-bbox="413 565 1042 597">2. Radioactive materials “adapted for use in war”; <li data-bbox="413 614 892 647">3. Chemical warfare (CW) agents; <u>or</u> <li data-bbox="413 664 1143 1239">4. “Riot control agents”, including: <ol style="list-style-type: none"> <li data-bbox="498 715 1089 782">a. α-Bromobenzeneacetonitrile, (Bromobenzyl cyanide) (CA) (5798-79-8); <li data-bbox="498 799 1123 902">b. [(2-chlorophenyl) methylene] propanedinitrile, (o-Chlorobenzylidenemalononitrile) (CS) (2698-41-1); <li data-bbox="498 919 1139 1022">c. 2-Chloro-1-phenylethanone, Phenylacetyl chloride (ω-chloroacetophenone) (CN) (532-27-4); <li data-bbox="498 1039 1116 1071">d. Dibenz-(b,f)-1,4-oxazepine (CR) (257-07-8); <li data-bbox="498 1089 1143 1191">e. 10-Chloro-5,10-dihydrophenarsazine, (Phenarsazine chloride), (Adamsite), (DM) (578-94-9); <li data-bbox="498 1209 1110 1239">f. N-Nonanoylmorpholine, (MPA) (5299-64-9); <ol style="list-style-type: none"> <li data-bbox="350 1256 1143 1323">b. Protective suits, gloves and shoes, specially designed or modified for defence against any of the following: <ol style="list-style-type: none"> <li data-bbox="413 1340 991 1372">1. Biological agents “adapted for use in war”; <li data-bbox="413 1389 1079 1422">2. Radioactive materials “adapted for use in war”; <li data-bbox="413 1439 858 1471">3. Chemical warfare (CW) agents; <li data-bbox="350 1488 1143 1591">c. Detection systems, specially designed or modified for detection or identification of any of the following, and specially designed components therefor: <ol style="list-style-type: none"> <li data-bbox="413 1608 991 1641">1. Biological agents “adapted for use in war”; <li data-bbox="413 1658 1079 1690">2. Radioactive materials “adapted for use in war”; <li data-bbox="413 1707 858 1740">3. Chemical warfare (CW) agents;

<i>Category Code</i>	<i>Item Description</i>
	<p>d. Electronic equipment designed for automatically detecting or identifying the presence of “explosives” residues and utilising ‘trace detection’ techniques (e.g. surface acoustic wave, ion mobility spectrometry, differential mobility spectrometry, mass spectrometry).</p> <p><u>Technical Note</u> ‘Trace detection’ is defined as the capability to detect less than 1 ppm vapour, or 1 mg solid or liquid.</p> <p><u>Note 1</u> Category Code 1A004.d. does not include equipment specially designed for laboratory use.</p> <p><u>Note 2</u> Category Code 1A004.d. does not include non-contact walk-through security portals.</p> <p><u>Note</u> Category Code 1A004 does not include:</p> <p>a. Personal radiation monitoring dosimeters;</p> <p>b. Occupational health or safety equipment limited by design or function to protect against hazards specific to residential safety or civil industries, including:</p> <ol style="list-style-type: none"> 1. Mining; 2. Quarrying; 3. Agriculture; 4. Pharmaceutical; 5. Medical; 6. Veterinary; 7. Environmental; 8. Waste management; 9. Food industry.

Category Code	Item Description
1A005	<p><u>Technical Notes</u></p> <ol style="list-style-type: none"> 1. <i>Category Code 1A004 includes equipment and components that have been identified, successfully tested to national standards or otherwise proven effective, for the detection of or defence against radioactive materials “adapted for use in war”, biological agents “adapted for use in war”, chemical warfare agents, ‘simulants’ or “riot control agents”, even if such equipment or components are used in civil industries such as mining, quarrying, agriculture, pharmaceuticals, medical, veterinary, environmental, waste management, or the food industry.</i> 2. <i>‘Simulant’ is a substance or material that is used in place of toxic agent (chemical or biological) in training, research, testing or evaluation.</i> <p>Body armour and components therefor, as follows:</p> <p><u>N.B.</u> See also Division 2 of Part 1 of this Schedule.</p> <ol style="list-style-type: none"> a. <i>Soft body armour not manufactured to military standards or specifications, or to their equivalents, and specially designed components therefor;</i> b. <i>Hard body armour plates providing ballistic protection equal to or less than level IIIA (NIJ 0101.06, July 2008) or national equivalents.</i> <p><u>N.B.</u> <i>For “fibrous or filamentary materials” used in the manufacture of body armour, see Category Code 1C010.</i></p> <p><u>Note 1</u> <i>Category Code 1A005 does not include body armour when accompanying its user for the user’s own personal protection.</i></p> <p><u>Note 2</u> <i>Category Code 1A005 does not include body armour designed to provide frontal protection only from both fragment and blast from non-military explosive devices.</i></p>

Category Code	Item Description
	<p><u>Note 3</u> <i>Category Code 1A005 does not include body armour designed to provide protection only from knife, spike, needle or blunt trauma.</i></p>
1A006	<p>Equipment, specially designed or modified for the disposal of improvised explosive devices, as follows, and specially designed components and accessories therefor:</p> <p><u>N.B.</u> <i>See also Division 2 of Part 1 of this Schedule.</i></p> <p>a. Remotely operated vehicles;</p> <p>b. ‘Disruptors’.</p> <p><u>Technical Note</u> <i>‘Disruptors’ are devices specially designed for the purpose of preventing the operation of an explosive device by projecting a liquid, solid or frangible projectile.</i></p> <p><u>Note</u> <i>Category Code 1A006 does not include equipment when accompanying its operator.</i></p>
1A007	<p>Equipment and devices, specially designed to initiate charges and devices containing “energetic materials”, by electrical means, as follows:</p> <p><u>N.B.</u> <i>See also Division 2 of Part 1 of this Schedule, and Category Codes 3A229 and 3A232.</i></p> <p>a. Explosive detonator firing sets designed to drive explosive detonators specified in Category Code 1A007.b.;</p> <p>b. Electrically driven explosive detonators as follows:</p> <ol style="list-style-type: none"> 1. Exploding bridge (EB); 2. Exploding bridge wire (EBW); 3. Slapper; 4. Exploding foil initiators (EFI).

Category Code	Item Description
1A008	<p data-bbox="350 325 545 357"><u>Technical Notes</u></p> <ol data-bbox="350 367 1154 891" style="list-style-type: none"> <li data-bbox="350 367 1154 434">1. <i>The word initiator or igniter is sometimes used in place of the word detonator.</i> <li data-bbox="350 453 1154 891">2. <i>For the purpose of Category Code 1A007.b. the detonators of concern all utilise a small electrical conductor (bridge, bridge wire, or foil) that explosively vaporises when a fast, high-current electrical pulse is passed through it. In non-slapper types, the exploding conductor starts a chemical detonation in a contacting high explosive material such as PETN (pentaerythritoltetranitrate). In slapper detonators, the explosive vaporisation of the electrical conductor drives a flyer or slapper across a gap, and the impact of the slapper on an explosive starts a chemical detonation. The slapper in some designs is driven by magnetic force. The term exploding foil detonator may refer to either an EB or a slapper-type detonator.</i> <p data-bbox="350 957 897 990">Charges, devices and components, as follows:</p> <ol data-bbox="350 1009 1154 1532" style="list-style-type: none"> <li data-bbox="350 1009 1154 1142">a. ‘Shaped charges’ having all of the following: <ol data-bbox="417 1056 1154 1142" style="list-style-type: none"> <li data-bbox="417 1056 1154 1094">1. Net Explosive Quantity (NEQ) greater than 90 g; <u>and</u> <li data-bbox="417 1104 1154 1142">2. Outer casing diameter equal to or greater than 75 mm; <li data-bbox="350 1161 1154 1323">b. Linear shaped cutting charges having all of the following, and specially designed components therefor: <ol data-bbox="417 1247 1154 1323" style="list-style-type: none"> <li data-bbox="417 1247 1154 1285">1. An explosive load greater than 40 g/m; <u>and</u> <li data-bbox="417 1294 1154 1323">2. A width of 10 mm or more; <li data-bbox="350 1342 1154 1408">c. Detonating cord with explosive core load greater than 64 g/m; <li data-bbox="350 1428 1154 1532">d. Cutters, other than those specified in Category Code 1A008.b., and severing tools, having a Net Explosive Quantity (NEQ) greater than 3.5 kg. <p data-bbox="350 1551 545 1584"><u>Technical Note</u></p> <p data-bbox="350 1593 1154 1652"><i>‘Shaped charges’ are explosive charges shaped to focus the effects of the explosive blast.</i></p>

<i>Category Code</i>	<i>Item Description</i>
1A102	Resaturated pyrolised carbon-carbon components designed for space launch vehicles specified in Category Code 9A004 or sounding rockets specified in Category Code 9A104.
1A202	<p>Composite structures, other than those specified in Category Code 1A002, in the form of tubes and having both of the following characteristics:</p> <p><u>N.B.</u> <i>See also Category Codes 9A010 and 9A110.</i></p> <ul style="list-style-type: none"> a. An inside diameter of between 75 mm and 400 mm; <u>and</u> b. Made with any of the “fibrous or filamentary materials” specified in Category Code 1C010.a. or 1C010.b. or 1C210.a. or with carbon prepreg materials specified in Category Code 1C210.c.
1A225	Platinised catalysts specially designed or prepared for promoting the hydrogen isotope exchange reaction between hydrogen and water for the recovery of tritium from heavy water or for the production of heavy water.
1A226	<p>Specialised packings which may be used in separating heavy water from ordinary water, having both of the following characteristics:</p> <ul style="list-style-type: none"> a. Made of phosphor bronze mesh chemically treated to improve wettability; <u>and</u> b. Designed to be used in vacuum distillation towers.

<i>Category Code</i>	<i>Item Description</i>
1A227	<p>High-density (lead glass or other) radiation shielding windows, having all of the following characteristics, and specially designed frames therefor:</p> <ol style="list-style-type: none"> a. A 'cold area' greater than 0.09 m²; b. A density greater than 3 g/cm³; <u>and</u> c. A thickness of 100 mm or greater. <p><u>Technical Note</u> <i>In Category Code 1A227, 'cold area' means the viewing area of the window exposed to the lowest level of radiation in the design application.</i></p>
<p>1B</p> <p>1B001</p>	<p>Test, Inspection and Production Equipment</p> <p>Equipment for the production or inspection of "composite" structures or laminates specified in Category Code 1A002 or "fibrous or filamentary materials" specified in Category Code 1C010, as follows, and specially designed components and accessories therefor:</p> <p><u>N.B.</u> <i>See also Category Codes 1B101 and 1B201.</i></p> <ol style="list-style-type: none"> a. Filament winding machines, of which the motions for positioning, wrapping and winding fibres are coordinated and programmed in three or more 'primary servo positioning' axes, specially designed for the manufacture of "composite" structures or laminates, from "fibrous or filamentary materials"; b. 'Tape-laying machines', of which the motions for positioning and laying tape are coordinated and programmed in five or more 'primary servo positioning' axes, specially designed for the manufacture of "composite" airframe or 'missile' structures; <p><u>Note</u> <i>In Category Code 1B001.b., 'missile' means complete rocket systems and unmanned aerial vehicle systems.</i></p>

<i>Category Code</i>	<i>Item Description</i>
	<p data-bbox="413 325 596 354"><u>Technical Note</u></p> <p data-bbox="413 367 1145 535"><i>For the purpose of Category Code 1B001.b., ‘tape-laying machines’ have the ability to lay one or more ‘filament bands’ limited to widths greater than 25 mm and less than or equal to 305 mm, and to cut and restart individual ‘filament band’ courses during the laying process.</i></p> <p data-bbox="350 554 1145 681">c. Multidirectional, multidimensional weaving machines or interlacing machines, including adapters and modification kits, specially designed or modified for weaving, interlacing or braiding fibres, for “composite” structures;</p> <p data-bbox="413 706 596 734"><u>Technical Note</u></p> <p data-bbox="413 748 1145 811"><i>For the purpose of Category Code 1B001.c., the technique of interlacing includes knitting.</i></p> <p data-bbox="350 830 1145 892">d. Equipment specially designed or adapted for the production of reinforcement fibres, as follows:</p> <ol data-bbox="413 915 1145 1334" style="list-style-type: none"> <li data-bbox="413 915 1145 1049">1. Equipment for converting polymeric fibres (e.g. polyacrylonitrile, rayon, pitch or polycarbosilane) into carbon fibres or silicon carbide fibres, including special equipment to strain the fibre during heating; <li data-bbox="413 1068 1145 1163">2. Equipment for the chemical vapour deposition of elements or compounds, on heated filamentary substrates, to manufacture silicon carbide fibres; <li data-bbox="413 1182 1145 1245">3. Equipment for the wet-spinning of refractory ceramics (e.g. aluminium oxide); <li data-bbox="413 1264 1145 1327">4. Equipment for converting aluminium containing precursor fibres into alumina fibres by heat treatment; <p data-bbox="350 1353 1145 1416">e. Equipment for producing prepregs specified in Category Code 1C010.e. by the hot melt method;</p>

<i>Category Code</i>	<i>Item Description</i>
	<p>f. Non-destructive inspection equipment specially designed for “composite” materials, as follows:</p> <ol style="list-style-type: none"> 1. X-ray tomography systems for three dimensional defect inspection; 2. Numerically controlled ultrasonic testing machines of which the motions for positioning transmitters or receivers are simultaneously coordinated and programmed in four or more axes to follow the three dimensional contours of the component under inspection; <p>g. ‘Tow-placement machines’, of which the motions for positioning and laying tows are coordinated and programmed in two or more ‘primary servo positioning’ axes, specially designed for the manufacture of “composite” airframe or ‘missile’ structures.</p> <p><u>Technical Note</u></p> <p><i>For the purpose of Category Code 1B001.g., ‘tow-placement machines’ have the ability to place one or more ‘filament bands’ having widths less than or equal to 25 mm, and to cut and restart individual ‘filament band’ courses during the placement process.</i></p> <p><u>Technical Notes</u></p> <ol style="list-style-type: none"> 1. <i>For the purpose of Category Code 1B001, ‘primary servo positioning’ axes control, under computer programme direction, the position of the end-effector (i.e. head) in space relative to the workpiece at the correct orientation and direction to achieve the desired process.</i> 2. <i>For the purpose of Category Code 1B001, a ‘filament band’ is a single continuous width of fully or partially resin-impregnated tape, tow or fibre.</i>

<i>Category Code</i>	<i>Item Description</i>
1B002	<p>Equipment for producing metal alloys, metal alloy powder or alloyed materials, specially designed to avoid contamination and specially designed for use in one of the processes specified in Category Code 1C002.c.2.</p> <p><u>N.B.</u> See also Category Code 1B102.</p>
1B003	<p>Tools, dies, moulds or fixtures, for “superplastic forming” or “diffusion bonding” titanium, aluminium or their alloys, specially designed for the manufacture of any of the following:</p> <ol style="list-style-type: none"> a. Airframe or aerospace structures; b. “Aircraft” or aerospace engines; <u>or</u> c. Specially designed components for structures specified in Category Code 1B003.a. or for engines specified in Category Code 1B003.b.
1B101	<p>Equipment, other than that specified in Category Code 1B001, for the “production” of structural composites as follows; and specially designed components and accessories therefor:</p> <p><u>N.B.</u> See also Category Code 1B201.</p> <p><u>Note</u> <i>Components and accessories specified in Category Code 1B101 include moulds, mandrels, dies, fixtures and tooling for the preform pressing, curing, casting, sintering or bonding of composite structures, laminates and manufactures thereof.</i></p> <ol style="list-style-type: none"> a. Filament winding machines or fibre placement machines, of which the motions for positioning, wrapping and winding fibres can be coordinated and programmed in three or more axes, designed to fabricate composite structures or laminates from fibrous or filamentary materials, and coordinating and programming controls;

<i>Category Code</i>	<i>Item Description</i>
	<p>b. Tape-laying machines of which the motions for positioning and laying tape and sheets can be coordinated and programmed in two or more axes, designed for the manufacture of composite airframe and “missile” structures;</p> <p>c. Equipment designed or modified for the “production” of “fibrous or filamentary materials” as follows:</p> <ol style="list-style-type: none"> 1. Equipment for converting polymeric fibres (e.g. polyacrylonitrile, rayon or polycarbosilane) including special provision to strain the fibre during heating; 2. Equipment for the vapour deposition of elements or compounds on heated filament substrates; 3. Equipment for the wet-spinning of refractory ceramics (e.g. aluminium oxide); <p>d. Equipment designed or modified for special fibre surface treatment or for producing prepregs and preforms specified in Category Code 9C110.</p> <p><i>Note</i> <i>Category Code 1B101.d. includes rollers, tension stretchers, coating equipment, cutting equipment and clicker dies.</i></p>
1B102	<p>Metal powder “production equipment”, other than that specified in Category Code 1B002, and components, as follows:</p> <p><i>N.B.</i> <i>See also Category Code 1B115.b.</i></p> <p>a. Metal powder “production equipment” usable for the “production”, in a controlled environment, of spherical, spheroidal or atomised materials specified in Category Code 1C011.a., 1C011.b., 1C111.a.1., 1C111.a.2. or in Division 2 of Part 1 of this Schedule;</p>

Category Code	Item Description
	<p>b. Specially designed components for “production equipment” specified in Category Code 1B002 or 1B102.a.</p> <p><u>Note</u> <i>Category Code 1B102 includes:</i></p> <p>a. <i>Plasma generators (high frequency arc-jet) usable for obtaining sputtered or spherical metallic powders with organisation of the process in an argon-water environment;</i></p> <p>b. <i>Electroburst equipment usable for obtaining sputtered or spherical metallic powders with organisation of the process in an argon-water environment;</i></p> <p>c. <i>Equipment usable for the “production” of spherical aluminium powders by powdering a melt in an inert medium (e.g. nitrogen).</i></p>
1B115	<p>Equipment, other than that specified in Category Code 1B002 or 1B102, for the production of propellant and propellant constituents, as follows, and specially designed components therefor:</p> <p>a. “Production equipment” for the “production”, handling or acceptance testing of liquid propellants or propellant constituents specified in Category Code 1C011.a., 1C011.b., 1C111 or in Division 2 of Part 1 of this Schedule;</p> <p>b. “Production equipment” for the “production”, handling, mixing, curing, casting, pressing, machining, extruding or acceptance testing of solid propellants or propellant constituents specified in Category Code 1C011.a., 1C011.b., 1C111 or in Division 2 of Part 1 of this Schedule.</p> <p><u>Note</u> <i>Category Code 1B115.b. does not include batch mixers, continuous mixers or fluid energy mills. For batch mixers, continuous mixers and fluid energy mills, see Category Codes 1B117, 1B118 and 1B119.</i></p> <p><u>Note 1</u> <i>For equipment specially designed for the production of military goods, see Division 2 of Part 1 of this Schedule.</i></p>

Category Code	Item Description
	<p><u>Note 2</u> Category Code 1B115 does not include equipment for the “production”, handling and acceptance testing of boron carbide.</p>
1B116	<p>Specially designed nozzles for producing pyrolytically derived materials formed on a mould, mandrel or other substrate from precursor gases which decompose in the 1,573 K (1,300°C) to 3,173 K (2,900°C) temperature range at pressures of 130 Pa to 20 kPa.</p>
1B117	<p>Batch mixers with provision for mixing under vacuum in the range of zero to 13.326 kPa and with temperature control capability of the mixing chamber and having all of the following, and specially designed components therefor:</p> <ul style="list-style-type: none"> a. A total volumetric capacity of 110 litres or more; <u>and</u> b. At least one ‘mixing/kneading shaft’ mounted off centre. <p><u>Note</u> In Category Code 1B117.b., ‘mixing/kneading shaft’ does not refer to deagglomerators or knife-spindles.</p>
1B118	<p>Continuous mixers with provision for mixing under vacuum in the range of zero to 13.326 kPa and with a temperature control capability of the mixing chamber having any of the following, and specially designed components therefor:</p> <ul style="list-style-type: none"> a. Two or more mixing/kneading shafts; <u>or</u> b. A single rotating shaft which oscillates and having kneading teeth/pins on the shaft as well as inside the casing of the mixing chamber.
1B119	<p>Fluid energy mills usable for grinding or milling substances specified in Category Code 1C011.a., 1C011.b., 1C111 or in Division 2 of Part 1 of this Schedule, and specially designed components therefor.</p>

<i>Category Code</i>	<i>Item Description</i>
1B201	<p>Filament winding machines, other than those specified in Category Code 1B001 or 1B101, and related equipment, as follows:</p> <ol style="list-style-type: none"> a. Filament winding machines having all of the following characteristics: <ol style="list-style-type: none"> 1. Having motions for positioning, wrapping, and winding fibres coordinated and programmed in two or more axes; 2. Specially designed to fabricate composite structures or laminates from “fibrous or filamentary materials”; <u>and</u> 3. Capable of winding cylindrical tubes with an internal diameter between 75 mm and 650 mm and lengths of 300 mm or greater; b. Coordinating and programming controls for the filament winding machines specified in Category Code 1B201.a.; c. Precision mandrels for the filament winding machines specified in Category Code 1B201.a.
1B225	<p>Electrolytic cells for fluorine production with an output capacity greater than 250 g of fluorine per hour.</p>
1B226	<p>Electromagnetic isotope separators designed for, or equipped with, single or multiple ion sources capable of providing a total ion beam current of 50 mA or greater.</p> <p><u>Note</u> <i>Category Code 1B226 includes separators:</i></p> <ol style="list-style-type: none"> a. <i>Capable of enriching stable isotopes;</i> b. <i>With the ion sources and collectors both in the magnetic field and those configurations in which they are external to the field.</i>

<i>Category Code</i>	<i>Item Description</i>
1B228	<p>Hydrogen-cryogenic distillation columns having all of the following characteristics:</p> <ol style="list-style-type: none"> a. Designed for operation with internal temperatures of 35 K (-238°C) or less; b. Designed for operation at an internal pressure of 0.5 MPa to 5 MPa; c. Constructed of either: <ol style="list-style-type: none"> 1. Stainless steel of the 300 series with low sulphur content and with an austenitic ASTM (or equivalent standard) grain size number of 5 or greater; <u>or</u> 2. Equivalent materials which are both cryogenic and H₂-compatible; <u>and</u> d. With internal diameters of 30 cm or greater and ‘effective lengths’ of 4 m or greater. <p><i><u>Technical Note</u></i> <i>In Category Code 1B228, ‘effective length’ means the active height of packing material in a packed-type column, or the active height of internal contactor plates in a plate-type column.</i></p>
1B229	<p>Water-hydrogen sulphide exchange tray columns and ‘internal contactors’, as follows:</p> <p><i><u>N.B.</u></i> <i>For columns which are specially designed or prepared for the production of heavy water, see Category Code 0B004.</i></p> <ol style="list-style-type: none"> a. Water-hydrogen sulphide exchange tray columns, having all of the following characteristics: <ol style="list-style-type: none"> 1. Can operate at pressures of 2 MPa or greater; 2. Constructed of carbon steel having an austenitic ASTM (or equivalent standard) grain size number of 5 or greater; <u>and</u> 3. With a diameter of 1.8 m or greater;

Category Code	Item Description
	<p>b. 'Internal contactors' for the water-hydrogen sulphide exchange tray columns specified in Category Code 1B229.a.</p> <p><i>Technical Note</i></p> <p><i>'Internal contactors' of the columns are segmented trays which have an effective assembled diameter of 1.8 m or greater, are designed to facilitate countercurrent contacting and are constructed of stainless steels with a carbon content of 0.03% or less. These may be sieve trays, valve trays, bubble cap trays, or turbogrid trays.</i></p>
1B230	<p>Pumps capable of circulating solutions of concentrated or dilute potassium amide catalyst in liquid ammonia (KNH_2/NH_3), having all of the following characteristics:</p> <p>a. Airtight (i.e. hermetically sealed);</p> <p>b. A capacity greater than $8.5 \text{ m}^3/\text{h}$; <u>and</u></p> <p>c. Either of the following characteristics:</p> <ol style="list-style-type: none"> 1. For concentrated potassium amide solutions (1% or greater), an operating pressure of 1.5 MPa to 60 MPa; <u>or</u> 2. For dilute potassium amide solutions (less than 1%), an operating pressure of 20 MPa to 60 MPa.
1B231	<p>Tritium facilities or plants, and equipment therefor, as follows:</p> <p>a. Facilities or plants for the production, recovery, extraction, concentration, or handling of tritium;</p> <p>b. Equipment for tritium facilities or plants, as follows:</p> <ol style="list-style-type: none"> 1. Hydrogen or helium refrigeration units capable of cooling to 23 K (-250°C) or less, with heat removal capacity greater than 150 W; 2. Hydrogen isotope storage or purification systems using metal hydrides as the storage or purification medium.

<i>Category Code</i>	<i>Item Description</i>
1B232	<p>Turboexpanders or turboexpander-compressor sets having both of the following characteristics:</p> <ul style="list-style-type: none"> a. Designed for operation with an outlet temperature of 35 K (-238°C) or less; <u>and</u> b. Designed for a throughput of hydrogen gas of 1,000 kg/h or greater.
1B233	<p>Lithium isotope separation facilities or plants, and systems and equipment therefor, as follows:</p> <ul style="list-style-type: none"> a. Facilities or plants for the separation of lithium isotopes; b. Equipment for the separation of lithium isotopes based on the lithium-mercury amalgam process, as follows: <ul style="list-style-type: none"> 1. Packed liquid-liquid exchange columns specially designed for lithium amalgams; 2. Mercury or lithium amalgam pumps; 3. Lithium amalgam electrolysis cells; 4. Evaporators for concentrated lithium hydroxide solution; c. Ion exchange systems specially designed for lithium isotope separation, and specially designed components therefor; d. Chemical exchange systems (employing crown ethers, cryptands, or lariat ethers), specially designed for lithium isotope separation, and specially designed components therefor.

<i>Category Code</i>	<i>Item Description</i>
1B234	<p>High explosive containment vessels, chambers, containers and other similar containment devices designed for the testing of high explosives or explosive devices and having both of the following characteristics:</p> <p><u>N.B.</u></p> <p><i>See also Division 2 of Part 1 of this Schedule.</i></p> <ol style="list-style-type: none"> a. Designed to fully contain an explosion equivalent to 2 kg of TNT or greater; <u>and</u> b. Having design elements or features enabling real time or delayed transfer of diagnostic or measurement information.
1C	<p>Materials</p> <p><u>Technical Note</u></p> <p><i>Unless provision to the contrary is made, the words ‘metals’ and ‘alloys’ in Category Codes 1C001 to 1C012 cover crude and semi-fabricated forms, as follows:</i></p> <p><i>Crude forms, in relation to materials, means anodes, balls, bars (including notched bars and wire bars), billets, blocks, blooms, brickets, cakes, cathodes, crystals, cubes, dice, grains, granules, ingots, lumps, pellets, pigs, powder, rondelles, shot, slabs, slugs, sponge, sticks;</i></p> <p><i>Semi-fabricated forms, in relation to materials, means any of the following:</i></p> <ol style="list-style-type: none"> a. <i>Wrought or worked materials fabricated by rolling, drawing, extruding, forging, impact extruding, pressing, graining, atomising, and grinding, i.e.: angles, channels, circles, discs, dust, flakes, foils and leaf, forging, plate, powder, pressings and stampings, ribbons, rings, rods (including bare welding rods, wire rods, and rolled wire), sections, shapes, sheets, strip, pipe and tubes (including tube rounds, squares, and hollows), drawn or extruded wire;</i>

Category Code	Item Description
1C001	<p data-bbox="350 325 1146 458">b. Cast material produced by casting in sand, die, metal, plaster or other types of moulds, including high pressure castings, sintered forms, and forms made by powder metallurgy;</p> <p data-bbox="350 477 946 510"><i>whether or not coated, plated, drilled or punched.</i></p> <p data-bbox="350 529 1146 624"><i>Category 1C includes non-listed forms of those materials which are purportedly finished products but are in reality crude forms or semi-fabricated forms.</i></p> <p data-bbox="350 693 1146 788">Materials specially designed for use as absorbers of electromagnetic waves, or intrinsically conductive polymers, as follows:</p> <p data-bbox="350 814 408 847"><u>N.B.</u></p> <p data-bbox="350 852 731 885"><i>See also Category Code 1C101.</i></p> <p data-bbox="350 904 1146 967">a. Materials for absorbing frequencies exceeding 2×10^8 Hz but less than 3×10^{12} Hz;</p> <p data-bbox="413 991 494 1024"><u>Note 1</u></p> <p data-bbox="413 1030 924 1062"><i>Category Code 1C001.a. does not include:</i></p> <p data-bbox="413 1081 1146 1182">a. <i>Hair type absorbers, constructed of natural or synthetic fibres, with non-magnetic loading to provide absorption;</i></p> <p data-bbox="413 1201 1146 1302">b. <i>Absorbers having no magnetic loss and whose incident surface is non-planar in shape, including pyramids, cones, wedges and convoluted surfaces;</i></p> <p data-bbox="413 1321 1146 1384">c. <i>Planar absorbers, having all of the following characteristics:</i></p> <p data-bbox="502 1403 951 1435">1. <i>Made from any of the following:</i></p> <p data-bbox="565 1454 1146 1723">a. <i>Plastic foam materials (flexible or non-flexible) with carbon-loading, or organic materials, including binders, providing more than 5% echo compared with metal over a bandwidth exceeding $\pm 15\%$ of the centre frequency of the incident energy, and not capable of withstanding temperatures exceeding 450 K (177°C); <u>or</u></i></p>

Category Code	Item Description
	<p data-bbox="561 325 1142 525">b. Ceramic materials providing more than 20% echo compared with metal over a bandwidth exceeding $\pm 15\%$ of the centre frequency of the incident energy, and not capable of withstanding temperatures exceeding 800 K (527°C);</p> <p data-bbox="561 544 747 576"><u>Technical Note</u></p> <p data-bbox="561 586 1142 753">Absorption test samples for Category Code 1C001.a. Note 1.c.1. should be a square at least 5 wavelengths of the centre frequency on a side and positioned in the far field of the radiating element.</p> <p data-bbox="498 773 1094 805">2. Tensile strength less than 7×10^6 N/m²; <u>and</u></p> <p data-bbox="498 824 1120 856">3. Compressive strength less than 14×10^6 N/m²;</p> <p data-bbox="413 873 1142 938">d. Planar absorbers made of sintered ferrite, having all of the following:</p> <p data-bbox="498 957 1005 990">1. A specific gravity exceeding 4.4; <u>and</u></p> <p data-bbox="498 1009 1142 1073">2. A maximum operating temperature of 548 K (275°C).</p> <p data-bbox="413 1092 494 1125"><u>Note 2</u></p> <p data-bbox="413 1134 1142 1233">Nothing in Note 1 to Category Code 1C001.a. releases magnetic materials to provide absorption when contained in paint.</p> <p data-bbox="350 1252 1142 1351">b. Materials for absorbing frequencies exceeding 1.5×10^{14} Hz but less than 3.7×10^{14} Hz and not transparent to visible light;</p> <p data-bbox="413 1370 475 1403"><u>Note</u></p> <p data-bbox="413 1412 1142 1511">Category Code 1C001.b. does not include materials, specially designed or formulated for any of the following applications:</p> <p data-bbox="413 1530 844 1563">a. Laser marking of polymers; <u>or</u></p> <p data-bbox="413 1582 801 1614">b. Laser welding of polymers.</p>

<i>Category Code</i>	<i>Item Description</i>
	<p>c. Intrinsically conductive polymeric materials with a ‘bulk electrical conductivity’ exceeding 10,000 S/m (Siemens per metre) or a ‘sheet (surface) resistivity’ of less than 100 ohms/square, based on any of the following polymers:</p> <ol style="list-style-type: none"> 1. Polyaniline; 2. Polypyrrole; 3. Polythiophene; 4. Poly phenylene-vinylene; <u>or</u> 5. Poly thienylene-vinylene. <p><u>Note</u> <i>Category Code 1C001.c. does not include materials in a liquid form.</i></p> <p><u>Technical Note</u> <i>‘Bulk electrical conductivity’ and ‘sheet (surface) resistivity’ should be determined using ASTM D-257 or national equivalents.</i></p>
1C002	<p>Metal alloys, metal alloy powder and alloyed materials, as follows:</p> <p><u>N.B.</u> <i>See also Category Code 1C202.</i></p> <p><u>Note</u> <i>Category Code 1C002 does not include metal alloys, metal alloy powder and alloyed materials for coating substrates.</i></p> <p><u>Technical Notes</u></p> <ol style="list-style-type: none"> 1. <i>The metal alloys in Category Code 1C002 are those containing a higher percentage by weight of the stated metal than of any other element.</i> 2. <i>‘Stress-rupture life’ is measured in accordance with ASTM standard E-139 or national equivalents.</i>

Category Code	Item Description
	<p>3. <i>‘Low cycle fatigue life’ is measured in accordance with ASTM standard E-606 ‘Recommended Practice for Constant-Amplitude Low-Cycle Fatigue Testing’ or national equivalents. Testing should be axial with an average stress ratio equal to 1 and a stress-concentration factor (K_t) equal to 1. The average stress is defined as maximum stress minus minimum stress divided by maximum stress.</i></p> <p>a. Aluminides, as follows:</p> <ol style="list-style-type: none"> 1. Nickel aluminides containing a minimum of 15% by weight aluminium, a maximum of 38% by weight aluminium and at least one additional alloying element; 2. Titanium aluminides containing 10% by weight or more aluminium and at least one additional alloying element; <p>b. Metal alloys, as follows, made from the powder or particulate material specified in Category Code 1C002.c.:</p> <ol style="list-style-type: none"> 1. Nickel alloys having any of the following: <ol style="list-style-type: none"> a. A ‘stress-rupture life’ of 10,000 hours or longer at 923 K (650°C) at a stress of 676 MPa; <u>or</u> b. A ‘low cycle fatigue life’ of 10,000 cycles or more at 823 K (550°C) at a maximum stress of 1,095 MPa; 2. Niobium alloys having any of the following: <ol style="list-style-type: none"> a. A ‘stress-rupture life’ of 10,000 hours or longer at 1,073 K (800°C) at a stress of 400 MPa; <u>or</u> b. A ‘low cycle fatigue life’ of 10,000 cycles or more at 973 K (700°C) at a maximum stress of 700 MPa; 3. Titanium alloys having any of the following: <ol style="list-style-type: none"> a. A ‘stress-rupture life’ of 10,000 hours or longer at 723 K (450°C) at a stress of 200 MPa; <u>or</u> b. A ‘low cycle fatigue life’ of 10,000 cycles or more at 723 K (450°C) at a maximum stress of 400 MPa;

<i>Category Code</i>	<i>Item Description</i>
	<p>4. Aluminium alloys having any of the following:</p> <ol style="list-style-type: none"> a. A tensile strength of 240 MPa or more at 473 K (200°C); <u>or</u> b. A tensile strength of 415 MPa or more at 298 K (25°C); <p>5. Magnesium alloys having all of the following:</p> <ol style="list-style-type: none"> a. A tensile strength of 345 MPa or more; <u>and</u> b. A corrosion rate of less than 1 mm/year in 3% sodium chloride aqueous solution measured in accordance with ASTM standard G-31 or national equivalents; <p>c. Metal alloy powder or particulate material, having all of the following:</p> <ol style="list-style-type: none"> 1. Made from any of the following composition systems: <u>Technical Note</u> <i>X in the following equals one or more alloying elements.</i> <ol style="list-style-type: none"> a. Nickel alloys (Ni-Al-X, Ni-X-Al) qualified for turbine engine parts or components, i.e. with less than 3 non-metallic particles (introduced during the manufacturing process) larger than 100 µm in 10⁹ alloy particles; b. Niobium alloys (Nb-Al-X or Nb-X-Al, Nb-Si-X or Nb-X-Si, Nb-Ti-X or Nb-X-Ti); c. Titanium alloys (Ti-Al-X or Ti-X-Al); d. Aluminium alloys (Al-Mg-X or Al-X-Mg, Al-Zn-X or Al-X-Zn, Al-Fe-X or Al-X-Fe); <u>or</u> e. Magnesium alloys (Mg-Al-X or Mg-X-Al); 2. Made in a controlled environment by any of the following processes: <ol style="list-style-type: none"> a. “Vacuum atomisation”; b. “Gas atomisation”; c. “Rotary atomisation”;

<i>Category Code</i>	<i>Item Description</i>
	<ul style="list-style-type: none"> d. "Splat quenching"; e. "Melt spinning" and "comminution"; f. "Melt extraction" and "comminution"; g. "Mechanical alloying"; <u>or</u> h. "Plasma atomisation"; <u>and</u> <ul style="list-style-type: none"> 3. Capable of forming materials specified in Category Code 1C002.a. or 1C002.b.; <ul style="list-style-type: none"> d. Alloyed materials having all of the following: <ul style="list-style-type: none"> 1. Made from any of the composition systems specified in Category Code 1C002.c.1.; 2. In the form of uncomminuted flakes, ribbons or thin rods; <u>and</u> 3. Produced in a controlled environment by any of the following: <ul style="list-style-type: none"> a. "Splat quenching"; b. "Melt spinning"; <u>or</u> c. "Melt extraction".
1C003	<p>Magnetic metals, of all types and of whatever form, having any of the following:</p> <ul style="list-style-type: none"> a. Initial relative permeability of 120,000 or more and a thickness of 0.05 mm or less; <p><i>Technical Note</i></p> <p><i>Measurement of initial relative permeability is that performed on fully annealed materials.</i></p> <ul style="list-style-type: none"> b. Magnetostrictive alloys having any of the following: <ul style="list-style-type: none"> 1. A saturation magnetostriction of more than 5×10^{-4}; <u>or</u> 2. A magnetomechanical coupling factor (k) of more than 0.8; <u>or</u>

<i>Category Code</i>	<i>Item Description</i>
	<p>c. Amorphous or ‘nanocrystalline’ alloy strips, having all of the following:</p> <ol style="list-style-type: none"> 1. A composition having a minimum of 75% by weight of iron, cobalt or nickel; 2. A saturation magnetic induction (B_s) of 1.6 T or more; <u>and</u> 3. Any of the following: <ol style="list-style-type: none"> a. A strip thickness of 0.02 mm or less; <u>or</u> b. An electrical resistivity of 2×10^{-4} ohm cm or more. <p><u>Technical Note</u> <i>‘Nanocrystalline’ materials in Category Code 1C003.c. are those materials having a crystal grain size of 50 nm or less, as determined by X-ray diffraction.</i></p>
1C004	<p>Uranium titanium alloys or tungsten alloys with a “matrix” based on iron, nickel or copper, having all of the following:</p> <ol style="list-style-type: none"> a. A density exceeding 17.5 g/cm³; b. An elastic limit exceeding 880 MPa; c. An ultimate tensile strength exceeding 1,270 MPa; <u>and</u> d. An elongation exceeding 8%.
1C005	<p>“Superconductive” “composite” conductors in lengths exceeding 100 m or with a mass exceeding 100 g, as follows:</p> <ol style="list-style-type: none"> a. “Superconductive” “composite” conductors containing one or more niobium-titanium ‘filaments’, having both of the following: <ol style="list-style-type: none"> 1. Embedded in a “matrix” other than a copper or copper-based mixed “matrix”; <u>and</u> 2. Having a cross-section area less than 0.28×10^{-4} mm² (6 μm in diameter for circular ‘filaments’);

<i>Category Code</i>	<i>Item Description</i>
	<p>b. “Superconductive” “composite” conductors consisting of one or more “superconductive” ‘filaments’ other than niobium-titanium, having all of the following:</p> <ol style="list-style-type: none"> 1. A “critical temperature” at zero magnetic induction exceeding 9.85 K (-263.31°C); <u>and</u> 2. Remaining in the “superconductive” state at a temperature of 4.2 K (-268.96°C) when exposed to a magnetic field oriented in any direction perpendicular to the longitudinal axis of conductor and corresponding to a magnetic induction of 12 T with critical current density exceeding 1,750 A/mm² on overall cross-section of the conductor; <p>c. “Superconductive” “composite” conductors consisting of one or more “superconductive” ‘filaments’ which remain “superconductive” above 115 K (-158.16°C).</p> <p><u>Technical Note</u> <i>For the purpose of Category Code 1C005, ‘filaments’ may be in wire, cylinder, film, tape or ribbon form.</i></p>
1C006	<p>Fluids and lubricating materials, as follows:</p> <p>a. Hydraulic fluids containing, as their principal ingredients, any of the following:</p> <ol style="list-style-type: none"> 1. Synthetic ‘silahydrocarbon oils’ having all of the following: <p><u>Technical Note</u> <i>For the purpose of Category Code 1C006.a.1., ‘silahydrocarbon oils’ contain exclusively silicon, hydrogen and carbon.</i></p> <ol style="list-style-type: none"> a. A ‘flash point’ exceeding 477 K (204°C); b. A ‘pour point’ at 239 K (-34°C) or less; c. A ‘viscosity index’ of 75 or more; <u>and</u> d. A ‘thermal stability’ at 616 K (343°C); <u>or</u>

<i>Category Code</i>	<i>Item Description</i>
	<p>2. ‘Chlorofluorocarbons’ having all of the following:</p> <p><i>Technical Note</i> <i>For the purpose of Category Code 1C006.a.2., ‘chlorofluorocarbons’ contain exclusively carbon, fluorine and chlorine.</i></p> <ol style="list-style-type: none"> a. No ‘flash point’; b. An ‘autogenous ignition temperature’ exceeding 977 K (704°C); c. A ‘pour point’ at 219 K (-54°C) or less; d. A ‘viscosity index’ of 80 or more; <u>and</u> e. A boiling point at 473 K (200°C) or higher; <p>b. Lubricating materials containing, as their principal ingredients, any of the following:</p> <ol style="list-style-type: none"> 1. Phenylene or alkylphenylene ethers or thio-ethers, or their mixtures, containing more than two ether or thio-ether functions or mixtures thereof; <u>or</u> 2. Fluorinated silicone fluids with a kinematic viscosity of less than 5,000 mm²/s (5,000 centistokes) measured at 298 K (25°C); <p>c. Damping or flotation fluids having all of the following:</p> <ol style="list-style-type: none"> 1. Purity exceeding 99.8%; 2. Containing less than 25 particles of 200 µm or larger in size per 100 ml; <u>and</u> 3. Made from at least 85% of any of the following: <ol style="list-style-type: none"> a. Dibromotetrafluoroethane (25497-30-7, 124-73-2, 27336-23-8); b. Polychlorotrifluoroethylene (oily and waxy modifications only); <u>or</u> c. Polybromotrifluoroethylene;

Category Code	Item Description
	<p>d. Fluorocarbon electronic cooling fluids having all of the following:</p> <ol style="list-style-type: none"> 1. Containing 85% by weight or more of any of the following, or mixtures thereof: <ol style="list-style-type: none"> a. Monomeric forms of perfluoropolyalkylether-triazines or perfluoroaliphatic-ethers; b. Perfluoroalkylamines; c. Perfluorocycloalkanes; <u>or</u> d. Perfluoroalkanes; 2. Density at 298 K (25°C) of 1.5 g/ml or more; 3. In a liquid state at 273 K (0°C); <u>and</u> 4. Containing 60% or more by weight of fluorine. <p><u>Note</u> <i>Category Code 1C006.d. does not apply to materials specified and packaged as medical products.</i></p> <p><u>Technical Note</u> <i>For the purpose of Category Code 1C006:</i></p> <ol style="list-style-type: none"> a. 'Flash point' is determined using the Cleveland Open Cup Method described in ASTM D-92 or national equivalents; b. 'Pour point' is determined using the method described in ASTM D-97 or national equivalents; c. 'Viscosity index' is determined using the method described in ASTM D-2270 or national equivalents; d. 'Thermal stability' is determined by the following test procedure or national equivalents: <i>Twenty ml of the fluid under test is placed in a 46 ml type 317 stainless steel chamber containing one each of 12.5 mm (nominal) diameter balls of M-10 tool steel, 52,100 steel and naval bronze (60% Cu, 39% Zn, 0.75% Sn);</i> <i>The chamber is purged with nitrogen, sealed at atmospheric pressure and the temperature raised to and maintained at 644 ± 6 K ($371 \pm 6^\circ\text{C}$) for six hours;</i>

Category Code	Item Description
1C007	<p data-bbox="413 325 1143 424"><i>The specimen will be considered thermally stable if, on completion of the above procedure, all of the following conditions are met:</i></p> <ol data-bbox="413 439 1143 643" style="list-style-type: none"> <li data-bbox="413 439 1143 510">1. <i>The loss in weight of each ball is less than 10 mg/mm² of ball surface;</i> <li data-bbox="413 525 1143 595">2. <i>The change in original viscosity as determined at 311 K (38°C) is less than 25%; <u>and</u></i> <li data-bbox="413 611 1143 643">3. <i>The total acid or base number is less than 0.40;</i> <p data-bbox="350 658 1143 729">e. <i>‘Autogenous ignition’ temperature is determined using the method described in ASTM E-659 or national equivalents.</i></p> <p data-bbox="350 795 1143 891">Ceramic powders, non-“composite” ceramic materials, ceramic-“matrix” “composite” materials and precursor materials, as follows:</p> <p data-bbox="350 910 407 942"><u>N.B.</u></p> <p data-bbox="350 953 731 986"><i>See also Category Code 1C107.</i></p> <ol data-bbox="350 1005 1143 1290" style="list-style-type: none"> <li data-bbox="350 1005 1143 1176">a. <i>Ceramic powders of single or complex borides of titanium, having total metallic impurities, excluding intentional additions, of less than 5,000 ppm, an average particle size equal to or less than 5 µm and no more than 10% of the particles larger than 10 µm;</i> <li data-bbox="350 1191 1143 1290">b. <i>Non-“composite” ceramic materials in crude or semi-fabricated form, composed of borides of titanium with a density of 98% or more of the theoretical density;</i> <p data-bbox="413 1309 475 1342"><u>Note</u></p> <p data-bbox="413 1353 1040 1386"><i>Category Code 1C007.b. does not include abrasives.</i></p> <ol data-bbox="350 1405 1143 1755" style="list-style-type: none"> <li data-bbox="350 1405 1143 1755">c. <i>Ceramic-ceramic “composite” materials with a glass or oxide-“matrix” and reinforced with fibres having all of the following:</i> <ol data-bbox="413 1519 986 1755" style="list-style-type: none"> <li data-bbox="413 1519 986 1551">1. <i>Made from any of the following materials:</i> <ol data-bbox="498 1570 736 1755" style="list-style-type: none"> <li data-bbox="498 1570 628 1603">a. <i>Si-N;</i> <li data-bbox="498 1618 628 1650">b. <i>Si-C;</i> <li data-bbox="498 1666 736 1698">c. <i>Si-Al-O-N; <u>or</u></i> <li data-bbox="498 1713 713 1745">d. <i>Si-O-N; <u>and</u></i>

<i>Category Code</i>	<i>Item Description</i>
	<p>2. Having a “specific tensile strength” exceeding 12.7×10^3 m;</p> <p>d. Ceramic-ceramic “composite” materials, with or without a continuous metallic phase, incorporating particles, whiskers or fibres, where carbides or nitrides of silicon, zirconium or boron form the “matrix”;</p> <p>e. Precursor materials (i.e. special purpose polymeric or metallo-organic materials) for producing any phase or phases of the materials specified in Category Code 1C007.c., as follows:</p> <ol style="list-style-type: none"> 1. Polydiorganosilanes (for producing silicon carbide); 2. Polysilazanes (for producing silicon nitride); 3. Polycarbosilazanes (for producing ceramics with silicon, carbon and nitrogen components); <p>f. Ceramic-ceramic “composite” materials with an oxide or glass “matrix” reinforced with continuous fibres from any of the following systems:</p> <ol style="list-style-type: none"> 1. Al_2O_3 (1344-28-1); <u>or</u> 2. Si-C-N. <p><u>Note</u> <i>Category Code 1C007.f. does not include “composites” containing fibres from these systems with a fibre tensile strength of less than 700 MPa at 1,273 K (1,000°C) or fibre tensile creep resistance of more than 1% creep strain at 100 MPa load and 1,273 K (1,000°C) for 100 hours.</i></p>
1C008	<p>Non-fluorinated polymeric substances as follows:</p> <p>a. Imides, as follows:</p> <ol style="list-style-type: none"> 1. Bismaleimides; 2. Aromatic polyamide-imides (PAI) having a ‘glass transition temperature (T_g)’ exceeding 563 K (290°C); 3. Aromatic polyimides having a ‘glass transition temperature (T_g)’ exceeding 505 K (232°C);

Category Code	Item Description
	<p>4. Aromatic polyetherimides having a ‘glass transition temperature (T_g)’ exceeding 563 K (290°C);</p> <p><u>Note</u> Category Code 1C008.a. includes substances in liquid or solid “fusible” form, including resin, powder, pellet, film, sheet, tape or ribbon.</p> <p><u>N.B.</u> For non-“fusible” aromatic polyimides in film, sheet, tape or ribbon form, see Category Code 1A003.</p> <p>b. Not used;</p> <p>c. Not used;</p> <p>d. Polyarylene ketones;</p> <p>e. Polyarylene sulphides, where the arylene group is biphenylene, triphenylene or combinations thereof;</p> <p>f. Polybiphenylenethersulphone having a ‘glass transition temperature (T_g)’ exceeding 563 K (290°C).</p> <p><u>Technical Notes</u></p> <p>1. The ‘glass transition temperature (T_g)’ for Category Code 1C008.a.2. thermoplastic materials and Category Code 1C008.a.4. materials is determined using the method described in ISO 11357-2 (1999) or national equivalents.</p> <p>2. The ‘glass transition temperature (T_g)’ for Category Code 1C008.a.2. thermosetting materials and Category Code 1C008.a.3. materials is determined using the 3-point bend method described in ASTM D 7028-07 or equivalent national standard. The test is to be performed using a dry test specimen which has attained a minimum of 90% degree of cure as specified by ASTM E 2160-04 or equivalent national standard, and was cured using the combination of standard and post-cure processes that yield the highest T_g.</p>

<i>Category Code</i>	<i>Item Description</i>
1C009	<p>Unprocessed fluorinated compounds as follows:</p> <ol style="list-style-type: none"> a. Copolymers of vinylidene fluoride having 75% or more beta crystalline structure without stretching; b. Fluorinated polyimides containing 10% by weight or more of combined fluorine; c. Fluorinated phosphazene elastomers containing 30% by weight or more of combined fluorine.
1C010	<p>“Fibrous or filamentary materials”, as follows:</p> <p><u>N.B.</u></p> <p>See also Category Codes 1C210 and 9C110.</p> <p><u>Technical Notes</u></p> <ol style="list-style-type: none"> 1. For the purpose of calculating “specific tensile strength”, “specific modulus” or specific weight of “fibrous or filamentary materials” in Category Code 1C010.a., 1C010.b., 1C010.c. or 1C010.e.1.b., the tensile strength and modulus should be determined by using Method A described in ISO 10618 (2004) or national equivalents. 2. The assessment of the “specific tensile strength”, “specific modulus” or specific weight of non-unidirectional “fibrous or filamentary materials” (e.g. fabrics, random mats or braids) in Category Code 1C010 is to be based on the mechanical properties of the constituent unidirectional monofilaments (e.g. monofilaments, yarns, rovings or tows) prior to processing into the non-unidirectional “fibrous or filamentary materials”. <ol style="list-style-type: none"> a. Organic “fibrous or filamentary materials”, having both of the following: <ol style="list-style-type: none"> 1. “Specific modulus” exceeding 12.7×10^6 m; <u>and</u> 2. “Specific tensile strength” exceeding 23.5×10^4 m; <p><u>Note</u></p> <p>Category Code 1C010.a. does not include polyethylene.</p>

Category Code	Item Description
	<p>b. Carbon “fibrous or filamentary materials”, having both of the following:</p> <ol style="list-style-type: none"> 1. “Specific modulus” exceeding 14.65×10^6 m; <u>and</u> 2. “Specific tensile strength” exceeding 26.82×10^4 m; <p><u>Note</u> <i>Category Code 1C010.b. does not include:</i></p> <ol style="list-style-type: none"> a. “Fibrous or filamentary materials”, for the repair of “civil aircraft” structures or laminates, having all of the following: <ol style="list-style-type: none"> 1. An area not exceeding 1 m^2; 2. A length not exceeding 2.5 m; <u>and</u> 3. A width exceeding 15 mm; b. Mechanically chopped, milled or cut carbon “fibrous or filamentary materials” 25 mm or less in length. <p>c. Inorganic “fibrous or filamentary materials”, having both of the following:</p> <ol style="list-style-type: none"> 1. “Specific modulus” exceeding 2.54×10^6 m; <u>and</u> 2. Melting, softening, decomposition or sublimation point exceeding 1,922 K (1,649°C) in an inert environment; <p><u>Note</u> <i>Category Code 1C010.c. does not include:</i></p> <ol style="list-style-type: none"> a. Discontinuous, multiphase, polycrystalline alumina fibres in chopped fibre or random mat form, containing 3% by weight or more silica, with a “specific modulus” of less than 10×10^6 m; b. Molybdenum and molybdenum alloy fibres; c. Boron fibres; d. Discontinuous ceramic fibres with a melting, softening, decomposition or sublimation point lower than 2,043 K (1,770°C) in an inert environment.

<i>Category Code</i>	<i>Item Description</i>
	<p>d. “Fibrous or filamentary materials”, having any of the following:</p> <ol style="list-style-type: none"> 1. Composed of any of the following: <ol style="list-style-type: none"> a. Polyetherimides specified in Category Code 1C008.a.; <u>or</u> b. Materials specified in Category Codes 1C008.d. to 1C008.f.; <u>or</u> 2. Composed of materials specified in Category Code 1C010.d.1.a. or 1C010.d.1.b. and “commingled” with other fibres specified in Category Code 1C010.a., 1C010.b. or 1C010.c.; <p>e. Fully or partially resin-impregnated or pitch-impregnated “fibrous or filamentary materials” (prepregs), metal or carbon-coated “fibrous or filamentary materials” (preforms) or “carbon fibre preforms”, having all of the following:</p> <ol style="list-style-type: none"> 1. Having any of the following: <ol style="list-style-type: none"> a. Inorganic “fibrous or filamentary materials” specified in Category Code 1C010.c.; <u>or</u> b. Organic or carbon “fibrous or filamentary materials”, having all of the following: <ol style="list-style-type: none"> 1. “Specific modulus” exceeding 10.15×10^6 m; <u>and</u> 2. “Specific tensile strength” exceeding 17.7×10^4 m; <u>and</u> 2. Having any of the following: <ol style="list-style-type: none"> a. Resin or pitch specified in Category Code 1C008 or 1C009.b.; b. ‘Dynamic Mechanical Analysis glass transition temperature (DMA T_g)’ equal to or exceeding 453 K (180°C) and having a phenolic resin; <u>or</u> c. ‘Dynamic Mechanical Analysis glass transition temperature (DMA T_g)’ equal to or exceeding 505 K (232°C) and having a resin or pitch, not specified in Category Code 1C008 or 1C009.b., and not being a phenolic resin.

Category Code	Item Description
	<p><u>Note 1</u></p> <p><i>Metal or carbon-coated “fibrous or filamentary materials” (preforms) or “carbon fibre preforms”, not impregnated with resin or pitch, are specified by “fibrous or filamentary materials” in Category Code 1C010.a., 1C010.b. or 1C010.c.</i></p> <p><u>Note 2</u></p> <p><i>Category Code 1C010.e. does not include:</i></p> <p>a. <i>Epoxy resin “matrix” impregnated carbon “fibrous or filamentary materials” (prepregs) for the repair of “civil aircraft” structures or laminates, having all of the following;</i></p> <ol style="list-style-type: none"> 1. <i>An area not exceeding 1 m²;</i> 2. <i>A length not exceeding 2.5 m; <u>and</u></i> 3. <i>A width exceeding 15 mm.</i> <p>b. <i>Fully or partially resin-impregnated or pitch-impregnated mechanically chopped, milled or cut carbon “fibrous or filamentary materials” 25 mm or less in length when using a resin or pitch other than those specified by Category Code 1C008 or 1C009.b.</i></p> <p><u>Technical Note</u></p> <p><i>The ‘Dynamic Mechanical Analysis glass transition temperature (DMA T_g)’ for materials specified by Category Code 1C010.e. is determined using the method described in ASTM D 7028-07, or equivalent national standard, on a dry test specimen. In the case of thermoset materials, degree of cure of a dry test specimen is a minimum of 90% as defined by ASTM E 2160-04 or equivalent national standard.</i></p>

Category Code	Item Description
1C011	<p>Metals and compounds, as follows:</p> <p><u>N.B.</u></p> <p><i>See also Division 2 of Part 1 of this Schedule and Category Code 1C111.</i></p> <p>a. Metals in particle sizes of less than 60 µm whether spherical, atomised, spheroidal, flaked or ground, manufactured from material consisting of 99% or more of zirconium, magnesium and alloys thereof;</p> <p><u>Technical Note</u></p> <p><i>The natural content of hafnium in the zirconium (typically 2% to 7%) is counted with the zirconium.</i></p> <p><u>Note</u></p> <p><i>Category Code 1C011.a. includes metals or alloys listed therein whether or not they are encapsulated in aluminium, magnesium, zirconium or beryllium.</i></p> <p>b. Boron or boron alloys, with a particle size of 60 µm or less, as follows;</p> <ol style="list-style-type: none"> 1. Boron with a purity of 85% by weight or more; 2. Boron alloys with a boron content of 85% by weight or more; <p><u>Note</u></p> <p><i>Category Code 1C011.b. includes metals or alloys listed therein whether or not they are encapsulated in aluminium, magnesium, zirconium or beryllium.</i></p> <p>c. Guanidine nitrate (506-93-4);</p> <p>d. Nitroguanidine (NQ) (556-88-7).</p> <p><u>N.B.</u></p> <p><i>See also Division 2 of Part 1 of this Schedule for metal powders mixed with other substances to form a mixture formulated for military purposes.</i></p>

<i>Category Code</i>	<i>Item Description</i>
1C012	<p>Materials as follows:</p> <p><u>Technical Note</u> <i>These materials are typically used for nuclear heat sources.</i></p> <p>a. Plutonium in any form with a plutonium isotopic assay of plutonium-238 of more than 50% by weight;</p> <p><u>Note</u> <i>Category Code 1C012.a. does not include:</i></p> <p>a. <i>Shipments with a plutonium content of 1 g or less;</i></p> <p>b. <i>Shipments of 3 “effective grammes” or less when contained in a sensing component in instruments.</i></p> <p>b. “Previously separated” neptunium-237 in any form.</p> <p><u>Note</u> <i>Category Code 1C012.b. does not include shipments with a neptunium-237 content of 1 g or less.</i></p>
1C101	<p>Materials and devices for reduced observables such as radar reflectivity, ultraviolet/infrared signatures and acoustic signatures, other than those specified in Category Code 1C001, usable in ‘missiles’, “missile” sub-systems or unmanned aerial vehicles specified in Category Code 9A012 or 9A112.a.</p> <p><u>Note 1</u> <i>Category Code 1C101 includes:</i></p> <p>a. <i>Structural materials and coatings specially designed for reduced radar reflectivity;</i></p> <p>b. <i>Coatings, including paints, specially designed for reduced or tailored reflectivity or emissivity in the microwave, infrared or ultraviolet regions of the electromagnetic spectrum.</i></p> <p><u>Note 2</u> <i>Category Code 1C101 does not include coatings when specially used for the thermal control of satellites.</i></p>

<i>Category Code</i>	<i>Item Description</i>
	<p><u>Technical Note</u> <i>In Category Code 1C101, 'missile' means complete rocket systems and unmanned aerial vehicle systems capable of a range exceeding 300 km.</i></p>
1C102	<p>Resaturated pyrolysed carbon-carbon materials designed for space launch vehicles specified in Category Code 9A004 or sounding rockets specified in Category Code 9A104.</p>
1C107	<p>Graphite and ceramic materials, other than those specified in Category Code 1C007, as follows:</p> <p>a. Fine grain graphites with a bulk density of 1.72 g/cm³ or greater, measured at 288 K (15°C), and having a grain size of 100 µm or less, usable for rocket nozzles and re-entry vehicle nose tips, which can be machined to any of the following products:</p> <ol style="list-style-type: none"> 1. Cylinders having a diameter of 120 mm or greater and a length of 50 mm or greater; 2. Tubes having an inner diameter of 65 mm or greater and a wall thickness of 25 mm or greater and a length of 50 mm or greater; <u>or</u> 3. Blocks having a size of 120 mm × 120 mm × 50 mm or greater; <p><u>N.B.</u> <i>See also Category Code 0C004.</i></p> <p>b. Pyrolytic or fibrous reinforced graphites, usable for rocket nozzles and re-entry vehicle nose tips usable in "missiles", space launch vehicles specified in Category Code 9A004 or sounding rockets specified in Category Code 9A104;</p> <p><u>N.B.</u> <i>See also Category Code 0C004.</i></p>

<i>Category Code</i>	<i>Item Description</i>
	<ul style="list-style-type: none"> c. Ceramic composite materials (dielectric constant less than 6 at any frequency from 100 MHz to 100 GHz) for use in radomes usable in “missiles”, space launch vehicles specified in Category Code 9A004 or sounding rockets specified in Category Code 9A104; d. Bulk machinable silicon-carbide reinforced unfired ceramic, usable for nose tips usable in “missiles”, space launch vehicles specified in Category Code 9A004 or sounding rockets specified in Category Code 9A104; e. Reinforced silicon-carbide ceramic composites, usable for nose tips, re-entry vehicles and nozzle flaps usable in “missiles”, space launch vehicles specified in Category Code 9A004 or sounding rockets specified in Category Code 9A104.
1C111	<p>Propellants and constituent chemicals for propellants, other than those specified in Category Code 1C011, as follows:</p> <ul style="list-style-type: none"> a. Propulsive substances: <ul style="list-style-type: none"> 1. Spherical or spheroidal aluminium powder, other than that specified in Division 2 of Part 1 of this Schedule, in particle size of less than 200 μm and an aluminium content of 97% by weight or more, if at least 10% of the total weight is made up of particles of less than 63 μm, according to ISO 2591-1:1988 or national equivalents; <p><i>Technical Note</i></p> <p><i>A particle size of 63 μm (ISO R-565) corresponds to 250 mesh (Tyler) or 230 mesh (ASTM standard E-11).</i></p>

<i>Category Code</i>	<i>Item Description</i>
	<p>2. Metal powders, other than that specified in Division 2 of Part 1 of this Schedule, as follows:</p> <p>a. Metal powders of zirconium, beryllium or magnesium, or alloys of these metals, if at least 90% of the total particles by particle volume or weight are made up of particles of less than 60 µm (determined by measurement techniques such as using a sieve, laser diffraction or optical scanning), whether spherical, atomised, spheroidal, flaked or ground, consisting 97% by weight or more of any of the following:</p> <ol style="list-style-type: none"> 1. Zirconium; 2. Beryllium; <u>or</u> 3. Magnesium; <p><i>Technical Note</i></p> <p><i>The natural content of hafnium in the zirconium (typically 2% to 7%) is counted with the zirconium.</i></p> <p>b. Metal powders of either boron or boron alloys with a boron content of 85% or more by weight, if at least 90% of the total particles by particle volume or weight are made up of particles of less than 60 µm (determined by measurement techniques such as using a sieve, laser diffraction or optical scanning), whether spherical, atomised, spheroidal, flaked or ground;</p> <p><i>Note</i></p> <p><i>Category Codes IC111a.2.a. and IC111a.2.b. include any powder mixture with a multimodal particle distribution (e.g. a mixture of different grain sizes) if one or more modes in the powder mixture are specified in Division 2 of Part 2 of this Schedule.</i></p>

<i>Category Code</i>	<i>Item Description</i>
	<p>3. Oxidiser substances usable in liquid propellant rocket engines as follows:</p> <ol style="list-style-type: none"> a. Dinitrogen trioxide (10544-73-7); b. Nitrogen dioxide (10102-44-0)/dinitrogen tetroxide (10544-72-6); c. Dinitrogen pentoxide (10102-03-1); d. Mixed Oxides of Nitrogen (MON); <p><i>Technical Note</i></p> <p><i>Mixed Oxides of Nitrogen (MON) are solutions of Nitric Oxide (NO) in Dinitrogen Tetroxide/ Nitrogen Dioxide (N₂O₄/NO₂) that can be used in missile systems. There are a range of compositions that can be denoted as MON_i or MON_{ij}, where i and j are integers representing the percentage of Nitric Oxide in the mixture (e.g. MON₃ contains 3% Nitric Oxide, MON₂₅ 25% Nitric Oxide. An upper limit is MON₄₀, 40% by weight).</i></p> <ol style="list-style-type: none"> e. See Inhibited Red Fuming Nitric Acid (IRFNA) in Division 2 of Part 1 of this Schedule; f. See compounds composed of fluorine and one or more of other halogens, oxygen or nitrogen in Division 2 of Part 1 of this Schedule and Category Code 1C238; <p>4. Hydrazine derivatives as follows:</p> <p><u>N.B.</u></p> <p><i>See also Division 2 of Part 1 of this Schedule.</i></p> <ol style="list-style-type: none"> a. Trimethylhydrazine (1741-01-1); b. Tetramethylhydrazine (6415-12-9); c. N,N diallylhydrazine (5164-11-4); d. Allylhydrazine (7422-78-8);

<i>Category Code</i>	<i>Item Description</i>
	<ul style="list-style-type: none"> e. Ethylene dihydrazine; f. Monomethylhydrazine dinitrate; g. Unsymmetrical dimethylhydrazine nitrate; h. Hydrazinium azide (14546-44-2); i. Dimethylhydrazinium azide; j. Hydrazinium dinitrate (13464-98-7); k. Diimido oxalic acid dihydrazine (3457-37-2); l. 2-hydroxyethylhydrazine nitrate (HEHN); m. See Hydrazinium perchlorate in Division 2 of Part 1 of this Schedule; n. Hydrazinium diperchlorate (13812-39-0); o. Methylhydrazine nitrate (MHN) (29674-96-2); p. Diethylhydrazine nitrate (DEHN); q. 3,6-dihydrazino tetrazine nitrate (1,4-dihydrazine nitrate) (DHTN); <p>5. High energy density materials, other than that specified in Division 2 of Part 1 of this Schedule, usable in 'missiles' or unmanned aerial vehicles specified in Category Code 9A012 or 9A112.a., as follows:</p> <ul style="list-style-type: none"> a. Mixed fuel that incorporate both solid and liquid fuels, such as boron slurry, having a mass-based energy density of 40×10^6 J/kg or greater; b. Other high energy density fuels and fuel additives (e.g. cubane, ionic solutions, JP-10) having a volume-based energy density of 37.5×10^9 J/m³ or greater, measured at 20°C and one atmosphere (101.325 kPa) pressure;

Category Code	Item Description
	<p data-bbox="561 325 623 357"><u>Note</u></p> <p data-bbox="561 367 1143 601"><i>Category Code 1C111.a.5.b. does not include fossil refined fuels and biofuels produced from vegetables, including fuels for engines certified for use in civil aviation, unless specially formulated for 'missiles' or unmanned aerial vehicles specified in Category Code 9A012 or 9A112.a.</i></p> <p data-bbox="478 620 662 653"><u>Technical Note</u></p> <p data-bbox="478 662 1143 763"><i>In Category Code 1C111.a.5., 'missile' means complete rocket systems and unmanned aerial vehicle systems capable of a range exceeding 300 km.</i></p> <p data-bbox="415 782 958 814">6. Hydrazine replacement fuels as follows:</p> <p data-bbox="499 833 1143 896">a. 2-Dimethylaminoethylazide (DMAZ) (86147-04-8);</p> <p data-bbox="350 915 680 948">b. Polymeric substances:</p> <ol data-bbox="415 967 1143 1334" style="list-style-type: none"> <li data-bbox="415 967 1143 1030">1. Carboxy-terminated polybutadiene (including carboxyl-terminated polybutadiene) (CTPB); <li data-bbox="415 1049 1143 1182">2. Hydroxy-terminated polybutadiene (including hydroxyl-terminated polybutadiene) (HTPB), other than that specified in Division 2 of Part 1 of this Schedule; <li data-bbox="415 1201 911 1233">3. Polybutadiene-acrylic acid (PBAA); <li data-bbox="415 1252 1065 1285">4. Polybutadiene-acrylic acid-acrylonitrile (PBAN); <li data-bbox="415 1304 1069 1334">5. Polytetrahydrofuran polyethylene glycol (TPEG); <p data-bbox="478 1353 662 1386"><u>Technical Note</u></p> <p data-bbox="478 1395 1143 1496"><i>Polytetrahydrofuran polyethylene glycol (TPEG) is a block co-polymer of poly 1,4-Butanediol (110-63-4) and polyethylene glycol (PEG) (25322-68-3).</i></p> <p data-bbox="415 1515 1143 1578">6. Polyglycidyl nitrate (PGN or poly-GLYN) (27814-48-8);</p>

<i>Category Code</i>	<i>Item Description</i>
	<p>c. Other propellant additives and agents:</p> <ol style="list-style-type: none"> 1. See carboranes, decaboranes, pentaboranes and derivatives thereof in Division 2 of Part 1 of this Schedule; 2. Triethylene glycol dinitrate (TEGDN) (111-22-8); 3. 2-Nitrodiphenylamine (119-75-5); 4. Trimethylolethane trinitrate (TMETN) (3032-55-1); 5. Diethylene glycol dinitrate (DEGDN) (693-21-0); 6. Ferrocene derivatives as follows: <ol style="list-style-type: none"> a. See catocene in Division 2 of Part 1 of this Schedule; b. See ethyl ferrocene in Division 2 of Part 1 of this Schedule; c. See propyl ferrocene in Division 2 of Part 1 of this Schedule; d. See n-butyl ferrocene in Division 2 of Part 1 of this Schedule; e. See pentyl ferrocene (1274-00-6) in Division 2 of Part 1 of this Schedule; f. See dicyclopentyl ferrocene in Division 2 of Part 1 of this Schedule; g. See dicyclohexyl ferrocene in Division 2 of Part 1 of this Schedule; h. See diethyl ferrocene in Division 2 of Part 1 of this Schedule; i. See dipropyl ferrocene in Division 2 of Part 1 of this Schedule; j. See dibutyl ferrocene in Division 2 of Part 1 of this Schedule; k. See dihexyl ferrocene in Division 2 of Part 1 of this Schedule;

<i>Category Code</i>	<i>Item Description</i>
	<p>l. See acetyl ferrocene (1271-55-2)/1,1'-diacetyl ferrocene in Division 2 of Part 1 of this Schedule;</p> <p>m. See ferrocene carboxylic acids in Division 2 of Part 1 of this Schedule;</p> <p>n. See butacene in Division 2 of Part 1 of this Schedule;</p> <p>o. Other ferrocene derivatives usable as rocket propellant burning rate modifiers, other than those specified in Division 2 of Part 1 of this Schedule;</p> <p><u>Note</u> <i>Category Code 1C111.c.6.o. does not include ferrocene derivatives that contain a six carbon aromatic functional group attached to the ferrocene molecule.</i></p> <p>7. 4,5 diazidomethyl-2-methyl-1,2,3-triazole (iso-DAMTR), other than that specified in Division 2 of Part 1 of this Schedule.</p> <p><u>Note</u> <i>For propellants and constituent chemicals for propellants not specified in Category Code 1C111, see Division 2 of Part 1 of this Schedule.</i></p>
1C116	<p>Maraging steels, usable in 'missiles', having both of the following:</p> <p><u>N.B.</u> <i>See also Category Code 1C216.</i></p> <p>a. An ultimate tensile strength, measured at 293 K (20°C), equal to or greater than:</p> <ol style="list-style-type: none"> 1. 0.9 GPa in the solution annealed stage; <u>or</u> 2. 1.5 GPa in the precipitation hardened stage; <u>and</u>

<i>Category Code</i>	<i>Item Description</i>
	<p>b. Any of the following forms:</p> <ol style="list-style-type: none"> 1. Sheet, plate or tubing with a wall or plate thickness equal to or less than 5 mm; 2. Tubular forms with a wall thickness equal to or less than 50 mm and having an inner diameter equal to or greater than 270 mm. <p><i>Technical Notes</i></p> <ol style="list-style-type: none"> 1. <i>Maraging steels are iron alloys:</i> <ol style="list-style-type: none"> a. <i>Generally characterised by high nickel, very low carbon content and the use of substitutional elements or precipitates to produce strengthening and age-hardening of the alloy; <u>and</u></i> b. <i>Subjected to heat treatment cycles to facilitate the martensitic transformation process (solution annealed stage) and subsequently age hardened (precipitation hardened stage).</i> 2. <i>In Category Code 1C116, 'missile' means complete rocket systems and unmanned aerial vehicle systems capable of a range exceeding 300 km.</i>
1C117	<p>Materials for the fabrication of 'missiles' components as follows:</p> <ol style="list-style-type: none"> a. Tungsten and alloys in particulate form with a tungsten content of 97% by weight or more and a particle size of 50×10^{-6} m (50 μm) or less; b. Molybdenum and alloys in particulate form with a molybdenum content of 97% by weight or more and a particle size of 50×10^{-6} m (50 μm) or less; c. Tungsten materials in solid form having all of the following: <ol style="list-style-type: none"> 1. Any of the following material compositions: <ol style="list-style-type: none"> a. Tungsten and alloys containing 97% by weight or more of tungsten; b. Copper infiltrated tungsten containing 80% by weight or more of tungsten; <u>or</u>

<i>Category Code</i>	<i>Item Description</i>
1C118	<p data-bbox="502 325 1151 392">c. Silver infiltrated tungsten containing 80% by weight or more of tungsten; <u>and</u></p> <p data-bbox="415 407 1151 439">2. Able to be machined to any of the following products:</p> <p data-bbox="502 458 1151 525">a. Cylinders having a diameter of 120 mm or greater and a length of 50 mm or greater;</p> <p data-bbox="502 544 1151 649">b. Tubes having an inner diameter of 65 mm or greater and a wall thickness of 25 mm or greater and a length of 50 mm or greater; <u>or</u></p> <p data-bbox="502 664 1151 731">c. Blocks having a size of 120 mm by 120 mm by 50 mm or greater.</p> <p data-bbox="350 746 534 778"><u>Technical Note</u></p> <p data-bbox="350 788 1151 892"><i>In Category Code 1C117, 'missile' means complete rocket systems and unmanned aerial vehicle systems capable of a range exceeding 300 km.</i></p> <p data-bbox="350 953 1151 1020">Titanium-stabilised duplex stainless steel (Ti-DSS) having all of the following:</p> <p data-bbox="350 1039 924 1071">a. Having all of the following characteristics:</p> <p data-bbox="417 1090 1151 1157">1. Containing 17-23% by weight chromium and 4.5-7% by weight nickel;</p> <p data-bbox="417 1176 1151 1243">2. Having a titanium content of greater than 0.10% by weight; <u>and</u></p> <p data-bbox="417 1262 1151 1395">3. A ferritic-austenitic microstructure (also referred to as a two-phase microstructure) of which at least 10% is austenite by volume (according to ASTM E-1181-87 or national equivalents); <u>and</u></p> <p data-bbox="350 1414 838 1447">b. Having any of the following forms:</p> <p data-bbox="417 1466 1151 1532">1. Ingots or bars having a size of 100 mm or more in each dimension;</p> <p data-bbox="417 1551 1151 1618">2. Sheets having a width of 600 mm or more and a thickness of 3 mm or less; <u>or</u></p> <p data-bbox="417 1637 1151 1704">3. Tubes having an outer diameter of 600 mm or more and a wall thickness of 3 mm or less.</p>

<i>Category Code</i>	<i>Item Description</i>
1C202	<p>Alloys, other than those specified in Category Code 1C002.b.3. or .b.4., as follows:</p> <p>a. Aluminium alloys having both of the following characteristics:</p> <ol style="list-style-type: none"> 1. ‘Capable of’ an ultimate tensile strength of 460 MPa or more at 293 K (20°C); <u>and</u> 2. In the form of tubes or cylindrical solid forms (including forgings) with an outside diameter of more than 75 mm; <p>b. Titanium alloys having both of the following characteristics:</p> <ol style="list-style-type: none"> 1. ‘Capable of’ an ultimate tensile strength of 900 MPa or more at 293 K (20°C); <u>and</u> 2. In the form of tubes or cylindrical solid forms (including forgings) with an outside diameter of more than 75 mm. <p><u>Technical Note</u> <i>The phrase alloys ‘capable of’ encompasses alloys before or after heat treatment.</i></p>
1C210	<p>‘Fibrous or filamentary materials’ or preregs, other than those specified in Category Code 1C010.a., b. or e., as follows:</p> <p>a. Carbon or aramid ‘fibrous or filamentary materials’ having either of the following characteristics:</p> <ol style="list-style-type: none"> 1. A “specific modulus” of 12.7×10^6 m or greater; <u>or</u> 2. A “specific tensile strength” of 23.5×10^4 m or greater; <p><u>Note</u> <i>Category Code 1C210.a. does not include aramid ‘fibrous or filamentary materials’ having 0.25% by weight or more of an ester based fibre surface modifier;</i></p> <p>b. Glass ‘fibrous or filamentary materials’ having both of the following characteristics:</p> <ol style="list-style-type: none"> 1. A “specific modulus” of 3.18×10^6 m or greater; <u>and</u> 2. A “specific tensile strength” of 7.62×10^4 m or greater;

Category Code	Item Description
	<p>c. Thermoset resin impregnated continuous “yarns”, “rovings”, “tows” or “tapes” with a width of 15 mm or less (prepregs), made from carbon or glass ‘fibrous or filamentary materials’ specified in Category Code 1C210.a. or b.</p> <p><u>Technical Note</u> <i>The resin forms the matrix of the composite.</i></p> <p><u>Note</u> <i>In Category Code 1C210, ‘fibrous or filamentary materials’ is restricted to continuous “monofilaments”, “yarns”, “rovings”, “tows” or “tapes”.</i></p>
1C216	<p>Maraging steel, other than that specified in Category Code 1C116, ‘capable of’ an ultimate tensile strength of 1,950 MPa or more, at 293 K (20°C).</p> <p><u>Note</u> <i>Category Code 1C216 does not include forms in which all linear dimensions are 75 mm or less.</i></p> <p><u>Technical Note</u> <i>The phrase maraging steel ‘capable of’ encompasses maraging steel before or after heat treatment.</i></p>
1C225	<p>Boron enriched in the boron-10 (¹⁰B) isotope to greater than its natural isotopic abundance, as follows: elemental boron, compounds, mixtures containing boron, manufactures thereof, waste or scrap of any of the foregoing.</p> <p><u>Note</u> <i>In Category Code 1C225, mixtures containing boron include boron loaded materials.</i></p> <p><u>Technical Note</u> <i>The natural isotopic abundance of boron-10 is approximately 18.5 weight per cent (20 atom per cent).</i></p>

<i>Category Code</i>	<i>Item Description</i>
1C226	<p>Tungsten, tungsten carbide, and alloys containing more than 90% tungsten by weight, other than that specified by Category Code 1C117, having both of the following characteristics:</p> <ul style="list-style-type: none"> a. In forms with a hollow cylindrical symmetry (including cylinder segments) with an inside diameter between 100 mm and 300 mm; <u>and</u> b. A mass greater than 20 kg. <p><i>Note</i> <i>Category Code 1C226 does not include manufactures specially designed as weights or gamma-ray collimators.</i></p>
1C227	<p>Calcium having both of the following characteristics:</p> <ul style="list-style-type: none"> a. Containing less than 1,000 parts per million by weight of metallic impurities other than magnesium; <u>and</u> b. Containing less than 10 parts per million by weight of boron.
1C228	<p>Magnesium having both of the following characteristics:</p> <ul style="list-style-type: none"> a. Containing less than 200 parts per million by weight of metallic impurities other than calcium; <u>and</u> b. Containing less than 10 parts per million by weight of boron.
1C229	<p>Bismuth having both of the following characteristics:</p> <ul style="list-style-type: none"> a. A purity of 99.99% or greater by weight; <u>and</u> b. Containing less than 10 ppm (parts per million) by weight of silver.

<i>Category Code</i>	<i>Item Description</i>
1C230	<p>Beryllium metal, alloys containing more than 50% beryllium by weight, beryllium compounds, manufactures thereof, and waste or scrap of any of the foregoing, other than that specified in Division 2 of Part 1 of this Schedule.</p> <p><u>N.B.</u> See also Division 2 of Part 1 of this Schedule.</p> <p><u>Note</u> Category Code 1C230 does not include the following:</p> <ol style="list-style-type: none"> a. Metal windows for X-ray machines, or for bore-hole logging devices; b. Oxide shapes in fabricated or semi-fabricated forms specially designed for electronic component parts or as substrates for electronic circuits; c. Beryl (silicate of beryllium and aluminium) in the form of emeralds or aquamarines.
1C231	<p>Hafnium metal, alloys containing more than 60% hafnium by weight, hafnium compounds containing more than 60% hafnium by weight, manufactures thereof, and waste or scrap of any of the foregoing.</p>
1C232	<p>Helium-3 (^3He), mixtures containing helium-3, and products or devices containing any of the foregoing.</p> <p><u>Note</u> Category Code 1C232 does not include a product or device containing less than 1 g of helium-3.</p>

<i>Category Code</i>	<i>Item Description</i>
1C233	<p>Lithium enriched in the lithium-6 (${}^6\text{Li}$) isotope to greater than its natural isotopic abundance, and products or devices containing enriched lithium, as follows: elemental lithium, alloys, compounds, mixtures containing lithium, manufactures thereof, waste or scrap of any of the foregoing.</p> <p><u>Note</u> <i>Category Code 1C233 does not include thermoluminescent dosimeters.</i></p> <p><u>Technical Note</u> <i>The natural isotopic abundance of lithium-6 is approximately 6.5 weight per cent (7.5 atom per cent).</i></p>
1C234	<p>Zirconium with a hafnium content of less than 1 part hafnium to 500 parts zirconium by weight, as follows: metal, alloys containing more than 50% zirconium by weight, compounds, manufactures thereof, waste or scrap of any of the foregoing, other than those specified in Category Code 0A001.f.</p> <p><u>Note</u> <i>Category Code 1C234 does not include zirconium in the form of foil having a thickness of 0.10 mm or less.</i></p>
1C235	<p>Tritium, tritium compounds, mixtures containing tritium in which the ratio of tritium to hydrogen atoms exceeds 1 part in 1,000, and products or devices containing any of the foregoing.</p> <p><u>Note</u> <i>Category Code 1C235 does not include a product or device containing less than 1.48×10^3 GBq (40 Ci) of tritium.</i></p>

<i>Category Code</i>	<i>Item Description</i>
1C236	<p data-bbox="350 325 1143 424">‘Radionuclides’ appropriate for making neutron sources based on alpha-n reaction, other than those specified in Category Codes 0C001 and 1C012.a., in the following forms:</p> <ol data-bbox="350 443 1143 694" style="list-style-type: none"> a. Elemental; b. Compounds having a total activity of 37 GBq/kg (1 Ci/kg) or greater; c. Mixtures having a total activity of 37 GBq/kg (1 Ci/kg) or greater; d. Products or devices containing any of the foregoing. <p data-bbox="350 714 411 744"><u>Note</u></p> <p data-bbox="350 753 1143 820"><i>Category Code 1C236 does not include a product or device containing less than 3.7 GBq (100 millicuries) of activity.</i></p> <p data-bbox="350 839 534 870"><u>Technical Note</u></p> <p data-bbox="350 879 1143 946"><i>In Category Code 1C236, ‘radionuclides’ are any of the following:</i></p> <ul data-bbox="350 965 731 1747" style="list-style-type: none"> – Actinium-225 (Ac-225) – Actinium-227 (Ac-227) – Californium-253 (Cf-253) – Curium-240 (Cm-240) – Curium-241 (Cm-241) – Curium-242 (Cm-242) – Curium-243 (Cm-243) – Curium-244 (Cm-244) – Einsteinium-253 (Es-253) – Einsteinium-254 (Es-254) – Gadolinium-148 (Gd-148) – Plutonium-236 (Pu-236) – Plutonium-238 (Pu-238) – Polonium-208 (Po-208) – Polonium-209 (Po-209) – Polonium-210 (Po-210)

Category Code	Item Description
	<ul style="list-style-type: none"> – Radium-223 (Ra-223) – Thorium-227 (Th-227) – Thorium-228 (Th-228) – Uranium-230 (U-230) – Uranium-232 (U-232)
1C237	<p>Radium-226 (²²⁶Ra), radium-226 alloys, radium-226 compounds, mixtures containing radium-226, manufactures thereof, and products or devices containing any of the foregoing.</p> <p><u>Note</u> Category Code 1C237 does not include the following:</p> <ul style="list-style-type: none"> a. Medical applicators; b. A product or device containing less than 0.37 GBq (10 millicuries) of radium-226.
1C238	Chlorine trifluoride (ClF ₃).
1C239	High explosives, other than those specified in Division 2 of Part 1 of this Schedule, or substances or mixtures containing more than 2% by weight thereof, with a crystal density greater than 1.8 g/cm ³ and having a detonation velocity greater than 8,000 m/s.
1C240	<p>Nickel powder and porous nickel metal, other than those specified in Category Code 0C005, as follows:</p> <ul style="list-style-type: none"> a. Nickel powder having both of the following characteristics: <ul style="list-style-type: none"> 1. A nickel purity content of 99% or greater by weight; <u>and</u> 2. A mean particle size of less than 10 µm measured by American Society for Testing and Materials (ASTM) B330 standard;

<i>Category Code</i>	<i>Item Description</i>
	<p>b. Porous nickel metal produced from materials specified in Category Code 1C240.a.</p> <p><u>Note</u> <i>Category Code 1C240 does not include the following:</i></p> <p>a. <i>Filamentary nickel powders;</i></p> <p>b. <i>Single porous nickel sheets with an area of 1,000 cm² per sheet or less.</i></p> <p><u>Technical Note</u> <i>Category Code 1C240.b. refers to porous metal formed by compacting and sintering the materials in Category Code 1C240.a. to form a metal material with fine pores interconnected throughout the structure.</i></p>
1C241	<p>Rhenium, and alloys containing 90% by weight or more rhenium; and alloys of rhenium and tungsten containing 90% by weight or more of any combination of rhenium and tungsten, other than those specified in Category Code 1C226, having both of the following characteristics:</p> <p>a. In forms with a hollow cylindrical symmetry (including cylinder segments) with an inside diameter between 100 mm and 300 mm; <u>and</u></p> <p>b. A mass greater than 20 kg.</p>
1C350	<p>Chemicals, which may be used as precursors for toxic chemical agents, as follows, and “chemical mixtures” containing one or more thereof:</p> <p><u>N.B.</u> <i>See also Division 2 of Part 1 of this Schedule and Category Code 1C450.</i></p> <ol style="list-style-type: none"> 1. Thiodiglycol (111-48-8); 2. Phosphorus oxychloride (10025-87-3); 3. Dimethyl methylphosphonate (756-79-6); 4. See Methyl phosphonyl difluoride (676-99-3) in Division 2 of Part 1 of this Schedule;

<i>Category Code</i>	<i>Item Description</i>
	5. Methyl phosphonyl dichloride (676-97-1);
	6. Dimethyl phosphite (DMP) (868-85-9);
	7. Phosphorus trichloride (7719-12-2);
	8. Trimethyl phosphite (TMP) (121-45-9);
	9. Thionyl chloride (7719-09-7);
	10. 3-Hydroxy-1-methylpiperidine (3554-74-3);
	11. N,N-Diisopropyl-(beta)-aminoethyl chloride (96-79-7);
	12. N,N-Diisopropyl-(beta)-aminoethane thiol (5842-07-9);
	13. 3-Quinuclidinol (1619-34-7);
	14. Potassium fluoride (7789-23-3);
	15. 2-Chloroethanol (107-07-3);
	16. Dimethylamine (124-40-3);
	17. Diethyl ethylphosphonate (78-38-6);
	18. Diethyl N,N-dimethylphosphoramidate (2404-03-7);
	19. Diethyl phosphite (762-04-9);
	20. Dimethylamine hydrochloride (506-59-2);
	21. Ethyl phosphinyl dichloride (1498-40-4);
	22. Ethyl phosphonyl dichloride (1066-50-8);
	23. See Ethyl phosphonyl difluoride (753-98-0) in Division 2 of Part 1 of this Schedule;
	24. Hydrogen fluoride (7664-39-3);
	25. Methyl benzilate (76-89-1);
	26. Methyl phosphinyl dichloride (676-83-5);
	27. N,N-Diisopropyl-(beta)-amino ethanol (96-80-0);
	28. Pinacolyl alcohol (464-07-3);
	29. See O-Ethyl O-2-diisopropylaminoethyl methyl phosphonite (QL) (57856-11-8) in Division 2 of Part 1 of this Schedule;
	30. Triethyl phosphite (122-52-1);
	31. Arsenic trichloride (7784-34-1);

<i>Category Code</i>	<i>Item Description</i>
	32. Benzilic acid (76-93-7);
	33. Diethyl methylphosphonite (15715-41-0);
	34. Dimethyl ethylphosphonate (6163-75-3);
	35. Ethyl phosphinyl difluoride (430-78-4);
	36. Methyl phosphinyl difluoride (753-59-3);
	37. 3-Quinuclidone (3731-38-2);
	38. Phosphorus pentachloride (10026-13-8);
	39. Pinacolone (75-97-8);
	40. Potassium cyanide (151-50-8);
	41. Potassium bifluoride (7789-29-9);
	42. Ammonium hydrogen fluoride or ammonium bifluoride (1341-49-7);
	43. Sodium fluoride (7681-49-4);
	44. Sodium bifluoride (1333-83-1);
	45. Sodium cyanide (143-33-9);
	46. Triethanolamine (102-71-6);
	47. Phosphorus pentasulphide (1314-80-3);
	48. Di-isopropylamine (108-18-9);
	49. Diethylaminoethanol (100-37-8);
	50. Sodium sulphide (1313-82-2);
	51. Sulphur monochloride (10025-67-9);
	52. Sulphur dichloride (10545-99-0);
	53. Triethanolamine hydrochloride (637-39-8);
	54. N,N-Diisopropyl-(beta)-aminoethyl chloride hydrochloride (4261-68-1);
	55. Methylphosphonic acid (993-13-5);
	56. Diethyl methylphosphonate (683-08-9);
	57. N,N-Dimethylaminophosphoryl dichloride (677-43-0);
	58. Triisopropyl phosphite (116-17-6);

Category Code	Item Description
	<p>59. Ethyldiethanolamine (139-87-7);</p> <p>60. O,O-Diethyl phosphorothioate (2465-65-8);</p> <p>61. O,O-Diethyl phosphorodithioate (298-06-6);</p> <p>62. Sodium hexafluorosilicate (16893-85-9);</p> <p>63. Methylphosphonothioic dichloride (676-98-2).</p> <p><u>Note 1</u> <i>Category Code 1C350 does not include “chemical mixtures” containing one or more of the chemicals specified in Category Codes 1C350.2., .6., .7., .8., .9., .10., .14., .15., .16., .19., .20., .24., .25., .30., .37., .38., .39., .40., .41., .42., .43., .44., .45., .46., .47., .48., .49., .50., .51., .52., .53., .58., .59., .60., .61. and .62. in which no individually specified chemical constitutes more than 30% by the weight of the mixture.</i></p> <p><u>Note 2</u> <i>Category Code 1C350 does not include products identified as consumer goods and packaged for retail sale for personal use or packaged for individual use.</i></p>
1C351	<p>Human and animal pathogens and “toxins”, as follows:</p> <p>a. Viruses, whether natural, enhanced or modified, either in the form of “isolated live cultures” or as material including living material which has been deliberately inoculated or contaminated with such cultures, as follows:</p> <ol style="list-style-type: none"> 1. African horse sickness virus; 2. African swine fever virus; 3. Andes virus; 4. Avian influenza virus, which are <ol style="list-style-type: none"> a. Uncharacterised; <u>or</u> b. Defined in Annex I(2) EC Directive 2005/94/EC (OJ L 10 14.1.2006 p. 16) as having high pathogenicity, as follows: <ol style="list-style-type: none"> 1. Type A viruses with an IVPI (intravenous pathogenicity index) in 6 week old chickens of greater than 1.2; <u>or</u>

<i>Category Code</i>	<i>Item Description</i>
	<ol style="list-style-type: none"> <li data-bbox="565 325 1145 592">2. Type A viruses of the subtypes H5 or H7 with genome sequences codified for multiple basic amino acids at the cleavage site of the haemagglutinin molecule similar to that observed for other HPAI viruses, indicating that the haemagglutinin molecule can be cleaved by a host ubiquitous protease; <li data-bbox="417 614 693 643">5. Bluetongue virus; <li data-bbox="417 664 655 693">6. Chapare virus; <li data-bbox="417 714 716 742">7. Chikungunya virus; <li data-bbox="417 763 642 792">8. Choclo virus; <li data-bbox="417 813 985 841">9. Congo-Crimean haemorrhagic fever virus; <li data-bbox="417 862 716 891">10. Dengue fever virus; <li data-bbox="417 912 774 940">11. Dobrava-Belgrade virus; <li data-bbox="417 961 881 990">12. Eastern equine encephalitis virus; <li data-bbox="417 1011 626 1039">13. Ebola virus; <li data-bbox="417 1060 837 1089">14. Foot and mouth disease virus; <li data-bbox="417 1110 666 1138">15. Goat pox virus; <li data-bbox="417 1159 676 1188">16. Guanarito virus; <li data-bbox="417 1209 655 1237">17. Hantaan virus; <li data-bbox="417 1258 915 1287">18. Hendra virus (Equine morbillivirus); <li data-bbox="417 1308 895 1336">19. Herpes virus (Aujeszky's disease); <li data-bbox="417 1357 932 1386">20. Hog cholera virus (swine fever virus); <li data-bbox="417 1407 810 1435">21. Japanese encephalitis virus; <li data-bbox="417 1456 619 1485">22. Junin virus; <li data-bbox="417 1506 749 1534">23. Kyasanur Forest virus; <li data-bbox="417 1555 724 1584">24. Laguna Negra virus; <li data-bbox="417 1605 693 1633">25. Lassa fever virus; <li data-bbox="417 1654 689 1683">26. Louping ill virus; <li data-bbox="417 1704 612 1732">27. Lujo virus;

<i>Category Code</i>	<i>Item Description</i>
	28. Lumpy skin disease virus;
	29. Lymphocytic choriomeningitis virus;
	30. Machupo virus;
	31. Marburg virus;
	32. Monkey pox virus;
	33. Murray Valley encephalitis virus;
	34. Newcastle disease virus;
	35. Nipah virus;
	36. Omsk haemorrhagic fever virus;
	37. Oropouche virus;
	38. Peste des petits ruminants virus;
	39. Porcine enterovirus type 9 (swine vesicular disease virus);
	40. Powassan virus;
	41. Rabies virus and all other members of the Lyssavirus genus;
	42. Rift Valley fever virus;
	43. Rinderpest virus;
	44. Rocio virus;
	45. Sabia virus;
	46. Seoul virus;
	47. Sheep pox virus;
	48. Sin nombre virus;
	49. St Louis encephalitis virus;
	50. Teschen disease virus;
	51. Tick-borne encephalitis virus (Russian Spring-Summer encephalitis virus);
	52. Variola virus;
	53. Venezuelan equine encephalitis virus;

<i>Category Code</i>	<i>Item Description</i>
	54. Vesicular stomatitis virus; 55. Western equine encephalitis virus; 56. Yellow fever virus;
	b. Not used;
	c. Bacteria, whether natural, enhanced or modified, either in the form of “isolated live cultures” or as material including living material which has been deliberately inoculated or contaminated with such cultures, as follows:
	1. Bacillus anthracis;
	2. Brucella abortus;
	3. Brucella melitensis;
	4. Brucella suis;
	5. Burkholderia mallei (Pseudomonas mallei);
	6. Burkholderia pseudomallei (Pseudomonas pseudomallei);
	7. Chlamydophila psittaci (formerly known as Chlamydia psittaci);
	8. Clostridium argentinense (formerly known as Clostridium botulinum Type G), botulinum neurotoxin producing strains;
	9. Clostridium baratii, botulinum neurotoxin producing strains;
	10. Clostridium botulinum;
	11. Clostridium butyricum, botulinum neurotoxin producing strains;
	12. Clostridium perfringens epsilon toxin producing types;
	13. Coxiella burnetii;
	14. Francisella tularensis;
	15. Mycoplasma capricolum subspecies capripneumoniae (strain F38);
	16. Mycoplasma mycoides subspecies mycoides SC (small colony);

<i>Category Code</i>	<i>Item Description</i>
	<p>17. Rickettsia prowasecki;</p> <p>18. Salmonella typhi;</p> <p>19. Shiga toxin producing Escherichia coli (STEC) of serogroups O26, O45, O103, O104, O111, O121, O145, O157, and other shiga toxin producing serogroups;</p> <p><i>Technical Note</i> <i>Shiga toxin producing Escherichia coli (STEC) is also known as enterohaemorrhagic E. coli (EHEC) or verocytotoxin producing E. coli (VTEC).</i></p> <p>20. Shigella dysenteriae;</p> <p>21. Vibrio cholerae;</p> <p>22. Yersinia pestis;</p> <p>d. “Toxins”, as follows, and “sub-unit of toxins” thereof:</p> <ol style="list-style-type: none"> 1. Botulinum toxins; 2. Clostridium perfringens alpha, beta 1, beta 2, epsilon and iota toxins; 3. Conotoxin; 4. Ricin; 5. Saxitoxin; 6. Shiga toxin; 7. Staphylococcus aureus enterotoxins, hemolysin alpha toxin, and toxic shock syndrome toxin (formerly known as Staphylococcus enterotoxin F); 8. Tetrodotoxin; 9. Verotoxin and shiga-like ribosome inactivating proteins; 10. Microcystin (Cyanginosin); 11. Aflatoxins;

<i>Category Code</i>	<i>Item Description</i>
	<p>12. Abrin;</p> <p>13. Cholera toxin;</p> <p>14. Diacetoxyscirpenol toxin;</p> <p>15. T-2 toxin;</p> <p>16. HT-2 toxin;</p> <p>17. Modeccin;</p> <p>18. Volkensin;</p> <p>19. Viscum album Lectin 1 (Viscumin);</p> <p><u>Note</u> <i>Category Code 1C351.d. does not include botulinum toxins or conotoxins in product form meeting all of the following criteria:</i></p> <ol style="list-style-type: none"> 1. <i>Are pharmaceutical formulations designed for human administration in the treatment of medical conditions;</i> 2. <i>Are pre-packaged for distribution as medical products; and</i> 3. <i>Are authorised by a state authority to be marketed as medical products.</i> <p>e. Fungi, whether natural, enhanced or modified, either in the form of “isolated live cultures” or as material including living material which has been deliberately inoculated or contaminated with such cultures, as follows:</p> <ol style="list-style-type: none"> 1. <i>Coccidioides immitis;</i> 2. <i>Coccidioides posadasii.</i> <p><u>Note</u> <i>Category Code 1C351 does not include “vaccines” or “immunotoxins”.</i></p>

<i>Category Code</i>	<i>Item Description</i>
1C353	<p>Genetic elements and genetically modified organisms, as follows:</p> <ol style="list-style-type: none"> a. Genetically modified organisms or genetic elements that contain nucleic acid sequences associated with pathogenicity of organisms specified in Category Code 1C351.a., 1C351.c., 1C351.e. or 1C354; b. Genetically modified organisms or genetic elements that contain nucleic acid sequences coding for any of the “toxins” specified in Category Code 1C351.d. or “sub-units of toxins” thereof. <p><u>Technical Notes</u></p> <ol style="list-style-type: none"> 1. <i>Genetically modified organisms include organisms in which the genetic material (nucleic acid sequences) has been altered in a way that does not occur naturally by mating and/or natural recombination, and encompasses those produced artificially in whole or in part.</i> 2. <i>Genetic elements include inter alia chromosomes, genomes, plasmids, transposons, and vectors whether genetically modified or unmodified, or chemically synthesised in whole or in part.</i> 3. <i>Nucleic acid sequences associated with the pathogenicity of any of the microorganisms specified in Category Code 1C351.a., 1C351.c., 1C351.e. or 1C354 means any sequence specific to the specified microorganism that:</i> <ol style="list-style-type: none"> a. <i>In itself or through its transcribed or translated products represents a significant hazard to human, animal or plant health; <u>or</u></i> b. <i>Is known to enhance the ability of a specified microorganism, or any other organism into which it may be inserted or otherwise integrated, to cause serious harm to humans, animals or plant health.</i> <p><u>Note</u></p> <p><i>Category Code 1C353 does not extend to nucleic acid sequences associated with the pathogenicity of enterohaemorrhagic Escherichia coli, serotype O157 and other verotoxin producing strains, other than those coding for the verotoxin, or for its sub-units.</i></p>

<i>Category Code</i>	<i>Item Description</i>
1C354	<p>Plant pathogens, as follows:</p> <ul style="list-style-type: none"> a. Viruses, whether natural, enhanced or modified, either in the form of “isolated live cultures” or as material including living material which has been deliberately inoculated or contaminated with such cultures, as follows: <ul style="list-style-type: none"> 1. Andean potato latent virus (Potato Andean latent tymovirus); 2. Potato spindle tuber viroid; b. Bacteria, whether natural, enhanced or modified, either in the form of “isolated live cultures” or as material which has been deliberately inoculated or contaminated with such cultures, as follows: <ul style="list-style-type: none"> 1. Xanthomonas albilineans; 2. Xanthomonas axonopodis pv. citri (Xanthomonas campestris pv. citri A) [Xanthomonas campestris pv. citri]; 3. Xanthomonas oryzae pv. oryzae (Pseudomonas campestris pv. oryzae); 4. Clavibacter michiganensis subsp. sepedonicus (Corynebacterium michiganensis subsp. sepedonicum or Corynebacterium sepedonicum); 5. Ralstonia solanacearum, race 3, biovar 2; c. Fungi, whether natural, enhanced or modified, either in the form of “isolated live cultures” or as material which has been deliberately inoculated or contaminated with such cultures, as follows: <ul style="list-style-type: none"> 1. Colletotrichum kahawae (Colletotrichum coffeanum var. virulans); 2. Cochliobolus miyabeanus (Helminthosporium oryzae); 3. Microcyclus ulei (syn. Dothidella ulei); 4. Puccinia graminis ssp. graminis var. graminis/Puccinia graminis ssp. graminis var. stakmanii (Puccinia graminis [syn. Puccinia graminis f. sp. tritici]); 5. Puccinia striiformis (syn. Puccinia glumarum);

<i>Category Code</i>	<i>Item Description</i>
	<ol style="list-style-type: none"> 6. Magnaporthe oryzae (Pyricularia oryzae); 7. Peronosclerospora philippinensis (Peronosclerospora sacchari); 8. Sclerophthora rayssiae var. zeae; 9. Synchytrium endobioticum; 10. Tilletia indica; 11. Thecaphora solani.
1C450	<p>Toxic chemicals and toxic chemical precursors, as follows, and “chemical mixtures” containing one or more thereof:</p> <p><u>N.B.</u></p> <p><i>See also Category Codes 1C350, 1C351.d. and Division 2 of Part 1 of this Schedule.</i></p> <ol style="list-style-type: none"> a. Toxic chemicals, as follows: <ol style="list-style-type: none"> 1. Amiton: O,O-Diethyl S-[2-(diethylamino)ethyl] phosphorothiolate (78-53-5) and corresponding alkylated or protonated salts; 2. PFIB: 1,1,3,3,3-Pentafluoro-2-(trifluoromethyl)-1-propene (382-21-8); 3. See BZ: 3-Quinuclidinyl benzilate (6581-06-2) in Division 2 of Part 1 of this Schedule; 4. Phosgene: Carbonyl dichloride (75-44-5); 5. Cyanogen chloride (506-77-4); 6. Hydrogen cyanide (74-90-8); 7. Chloropicrin: Trichloronitromethane (76-06-2);

Category Code	Item Description
	<p>b. Toxic chemical precursors, as follows:</p> <ol style="list-style-type: none"> 1. Chemicals, other than those specified in Division 2 of Part 1 of this Schedule or in Category Code 1C350, containing a phosphorus atom to which is bonded one methyl, ethyl or propyl (normal or iso) group but not further carbon atoms; <p style="margin-left: 2em;"><u>Note</u> Category Code 1C450.b.1. does not include Fonofos: O-Ethyl S-phenyl ethylphosphonothiolothionate (944-22-9).</p> 2. N,N-Dialkyl [methyl, ethyl or propyl (normal or iso)] phosphoramidic dihalides, other than N,N-Dimethylaminophosphoryl dichloride; <p style="margin-left: 2em;"><u>N.B.</u> See Category Code 1C350.57. for N,N-Dimethylaminophosphoryl dichloride.</p> 3. Dialkyl [methyl, ethyl or propyl (normal or iso)] N,N-dialkyl [methyl, ethyl or propyl (normal or iso)]-phosphoramidates, other than Diethyl-N,N-dimethylphosphoramidate which is specified in Category Code 1C350; 4. N,N-Dialkyl [methyl, ethyl or propyl (normal or iso)] aminoethyl-2-chlorides and corresponding protonated salts, other than N,N-Diisopropyl-(beta)-aminoethyl chloride or N,N-Diisopropyl-(beta)-aminoethyl chloride hydrochloride which are specified in Category Code 1C350; 5. N,N-Dialkyl [methyl, ethyl or propyl (normal or iso)] aminoethane-2-ols and corresponding protonated salts, other than N,N-Diisopropyl-(beta)-aminoethanol (96-80-0) and N,N-Diethylaminoethanol (100-37-8) which are specified in Category Code 1C350; <p style="margin-left: 2em;"><u>Note</u> Category Code 1C450.b.5. does not include the following:</p> <ol style="list-style-type: none"> a. N,N-Dimethylaminoethanol (108-01-0) and corresponding protonated salts;

Category Code	Item Description
	<p data-bbox="498 316 1146 386"><i>b. Protonated salts of N,N-Diethylaminoethanol (100-37-8).</i></p> <p data-bbox="413 401 1146 538">6. N,N-Dialkyl [methyl, ethyl or propyl (normal or iso)] aminoethane-2-thiols and corresponding protonated salts, other than N,N-Diisopropyl-(beta)-aminoethane thiol which is specified in Category Code 1C350;</p> <p data-bbox="413 554 1146 624">7. See Category Code 1C350 for ethyldiethanolamine (139-87-7);</p> <p data-bbox="413 639 891 674">8. Methyldiethanolamine (105-59-9).</p> <p data-bbox="346 689 431 721"><u>Note 1</u></p> <p data-bbox="346 729 1146 900"><i>Category Code 1C450 does not include “chemical mixtures” containing one or more of the chemicals specified in Category Codes 1C450.a.4., .a.5., .a.6., .a.7. and .b.8. in which no individually specified chemical constitutes more than 30% by weight of the mixture.</i></p> <p data-bbox="346 915 431 948"><u>Note 2</u></p> <p data-bbox="346 955 1146 1062"><i>Category Code 1C450 does not include products identified as consumer goods packaged for retail sale for personal use or packaged for individual use.</i></p>
1D	Software
1D001	“Software” specially designed or modified for the “development”, “production” or “use” of equipment specified in Category Codes 1B001 to 1B003.
1D002	“Software” for the “development” of organic “matrix”, metal “matrix” or carbon “matrix” laminates or “composites”.
1D003	“Software” specially designed or modified to enable equipment to perform the functions of equipment specified in Category Code 1A004.c. or 1A004.d.

<i>Category Code</i>	<i>Item Description</i>
1D101	“Software” specially designed or modified for the operation or maintenance of goods specified in Category Code 1B101, 1B102, 1B115, 1B117, 1B118 or 1B119.
1D103	“Software” specially designed for analysis of reduced observables such as radar reflectivity, ultraviolet/infrared signatures and acoustic signatures.
1D201	“Software” specially designed for the “use” of goods specified in Category Code 1B201.
1E	Technology
1E001	“Technology” (according to the General Technology Note) for the “development” or “production” of equipment or materials specified in Category Code 1A001.b., 1A001.c., 1A002 to 1A005, 1A006.b., 1A007 or Category 1B or 1C.
1E002	<p>Other “technology”, as follows:</p> <ol style="list-style-type: none"> a. “Technology” for the “development” or “production” of polybenzothiazoles or polybenzoxazoles; b. “Technology” for the “development” or “production” of fluoroelastomer compounds containing at least one vinyl ether monomer; c. “Technology” for the design or “production” of the following ceramic powders or non-“composite” ceramic materials: <ol style="list-style-type: none"> 1. Ceramic powders having all of the following: <ol style="list-style-type: none"> a. Any of the following compositions: <ol style="list-style-type: none"> 1. Single or complex oxides of zirconium and complex oxides of silicon or aluminium; 2. Single nitrides of boron (cubic crystalline forms);

<i>Category Code</i>	<i>Item Description</i>
	<p data-bbox="565 325 1143 392">3. Single or complex carbides of silicon or boron; <u>or</u></p> <p data-bbox="565 407 1069 439">4. Single or complex nitrides of silicon;</p> <p data-bbox="501 458 1143 525">b. Any of the following total metallic impurities (excluding intentional additions):</p> <p data-bbox="565 544 1143 611">1. Less than 1,000 ppm for single oxides or carbides; <u>or</u></p> <p data-bbox="565 630 1143 696">2. Less than 5,000 ppm for complex compounds or single nitrides; <u>and</u></p> <p data-bbox="501 715 895 748">c. Being any of the following:</p> <p data-bbox="565 767 1143 900">1. Zirconia (1314-23-4) with an average particle size equal to or less than 1 μm and no more than 10% of the particles larger than 5 μm; <u>or</u></p> <p data-bbox="565 919 1143 1052">2. Other ceramic powders with an average particle size equal to or less than 5 μm and no more than 10% of the particles larger than 10 μm;</p> <p data-bbox="413 1071 1143 1138">2. Non-“composite” ceramic materials composed of the materials specified in Category Code 1E002.c.1.;</p> <p data-bbox="478 1157 538 1190"><u>Note</u></p> <p data-bbox="478 1199 1143 1294"><i>Category Code 1E002.c.2. does not include “technology” for the design or production of abrasives.</i></p> <p data-bbox="350 1313 532 1346">d. Not used;</p> <p data-bbox="350 1365 1143 1431">e. “Technology” for the installation, maintenance or repair of materials specified in Category Code 1C001;</p> <p data-bbox="350 1450 1143 1546">f. “Technology” for the repair of “composite” structures, laminates or materials specified in Category Code 1A002, 1C007.c. or 1C007.d.;</p> <p data-bbox="413 1565 474 1597"><u>Note</u></p> <p data-bbox="413 1606 1143 1740"><i>Category Code 1E002.f. does not include “technology” for the repair of “civil aircraft” structures using carbon “fibrous or filamentary materials” and epoxy resins, contained in aircraft manufacturers’ manuals.</i></p>

<i>Category Code</i>	<i>Item Description</i>
	g. “Libraries” specially designed or modified to enable equipment to perform the functions of equipment specified in Category Code 1A004.c. or 1A004.d.
1E101	“Technology” (according to the General Technology Note) for the “use” of goods specified in Category Code 1A102, 1B001, 1B101, 1B102, 1B115 to 1B119, 1C001, 1C101, 1C107, 1C111, 1C116, 1C117, 1C118, 1D101 or 1D103.
1E102	“Technology” (according to the General Technology Note) for the “development” of “software” specified in Category Code 1D001, 1D101 or 1D103.
1E103	“Technology” for the regulation of temperature, pressure or atmosphere in autoclaves or hydroclaves, when used for the “production” of “composites” or partially processed “composites”.
1E104	“Technology” relating to the “production” of pyrolytically derived materials formed on a mould, mandrel or other substrate from precursor gases which decompose in the 1,573 K (1,300°C) to 3,173 K (2,900°C) temperature range at pressures of 130 Pa to 20 kPa.
	<p data-bbox="350 1252 411 1281"><u>Note</u></p> <p data-bbox="350 1296 1143 1391"><i>Category Code 1E104 includes “technology” for the composition of precursor gases, flow-rates and process control schedules and parameters.</i></p>

<i>Category Code</i>	<i>Item Description</i>
1E201	“Technology” (according to the General Technology Note) for the “use” of goods specified in Category Code 1A002, 1A007, 1A202, 1A225 to 1A227, 1B201, 1B225 to 1B234, 1C002.b.3. or .b.4., 1C010.b., 1C202, 1C210, 1C216, 1C225 to 1C241 or 1D201.
1E202	“Technology” (according to the General Technology Note) for the “development” or “production” of goods specified in Category Code 1A007, 1A202 or 1A225 to 1A227.
1E203	“Technology” (according to the General Technology Note) for the “development” of “software” specified in Category Code 1D201.

<i>Category Code</i>	<i>Item Description</i>
CATEGORY 2 — MATERIALS PROCESSING	
2A	Systems, Equipment and Components
	<p><u>N.B.</u> <i>For quiet running bearings, see Division 2 of Part 1 of this Schedule.</i></p>
2A001	<p>Anti-friction bearings and bearing systems, as follows, and components therefor:</p> <p><u>N.B.</u> <i>See also Category Code 2A101.</i></p> <p><u>Note</u> <i>Category Code 2A001 does not include balls with tolerances specified by the manufacturer in accordance with ISO 3290 as grade 5 or worse.</i></p> <p>a. Ball bearings and solid roller bearings, having all tolerances specified by the manufacturer in accordance with ISO 492 Tolerance Class 4 (or national equivalents), or better, and having both rings and rolling elements (Ref. ISO 5593), made from monel or beryllium;</p> <p><u>Note</u> <i>Category Code 2A001.a. does not include tapered roller bearings.</i></p> <p>b. Not used;</p> <p>c. Active magnetic bearing systems using any of the following:</p> <ol style="list-style-type: none"> 1. Materials with flux densities of 2 T or greater and yield strengths greater than 414 MPa; 2. All-electromagnetic 3D homopolar bias designs for actuators; <u>or</u> 3. High temperature (450 K (177°C) and above) position sensors.

<i>Category Code</i>	<i>Item Description</i>
2A101	<p>Radial ball bearings, other than those specified in Category Code 2A001, having all tolerances specified in accordance with ISO 492 Tolerance Class 2 (or ANSI/ABMA Std 20 Tolerance Class ABEC-9 or other national equivalents), or better and having all of the following characteristics:</p> <ol style="list-style-type: none"> a. An inner ring bore diameter between 12 mm and 50 mm; b. An outer ring outside diameter between 25 mm and 100 mm; <u>and</u> c. A width between 10 mm and 20 mm.
2A225	<p>Crucibles made of materials resistant to liquid actinide metals, as follows:</p> <ol style="list-style-type: none"> a. Crucibles having both of the following characteristics: <ol style="list-style-type: none"> 1. A volume of between 150 cm³ and 8,000 cm³; <u>and</u> 2. Made of or coated with any of the following materials, or combination of the following materials, having an overall impurity level of 2% or less by weight: <ol style="list-style-type: none"> a. Calcium fluoride (CaF₂); b. Calcium zirconate (metazirconate) (CaZrO₃); c. Cerium sulphide (Ce₂S₃); d. Erbium oxide (erbia) (Er₂O₃); e. Hafnium oxide (hafnia) (HfO₂); f. Magnesium oxide (MgO); g. Nitrided niobium-titanium-tungsten alloy (approximately 50% Nb, 30% Ti, 20% W); h. Yttrium oxide (yttria) (Y₂O₃); <u>or</u> i. Zirconium oxide (zirconia) (ZrO₂); b. Crucibles having both of the following characteristics: <ol style="list-style-type: none"> 1. A volume of between 50 cm³ and 2,000 cm³; <u>and</u> 2. Made of or lined with tantalum, having a purity of 99.9% or greater by weight;

<i>Category Code</i>	<i>Item Description</i>
2A226	<p>c. Crucibles having all of the following characteristics:</p> <ol style="list-style-type: none"> 1. A volume of between 50 cm³ and 2,000 cm³; 2. Made of or lined with tantalum, having a purity of 98% or greater by weight; <u>and</u> 3. Coated with tantalum carbide, nitride, boride, or any combination thereof. <p>Valves having all of the following characteristics:</p> <ol style="list-style-type: none"> a. A ‘nominal size’ of 5 mm or greater; b. Having a bellows seal; <u>and</u> c. Wholly made of or lined with aluminium, aluminium alloy, nickel, or nickel alloy containing more than 60% nickel by weight. <p><u>Technical Note</u> <i>For valves with different inlet and outlet diameters, the ‘nominal size’ in Category Code 2A226 refers to the smallest diameter.</i></p>
2B	<p>Test, Inspection and Production Equipment</p> <p><u>Technical Notes</u></p> <ol style="list-style-type: none"> 1. <i>Secondary parallel contouring axes, (e.g. the w-axis on horizontal boring mills or a secondary rotary axis the centre line of which is parallel to the primary rotary axis) are not counted in the total number of contouring axes. Rotary axes need not rotate over 360°. A rotary axis can be driven by a linear device (e.g. a screw or a rack-and-pinion).</i> 2. <i>For the purpose of Category 2B, the number of axes which can be coordinated simultaneously for “contouring control” is the number of axes along or around which, during processing of the workpiece, simultaneous and interrelated motions are performed between the workpiece and a tool. This does not include any additional axes along or around which other relative movement within the machine are performed such as:</i>

Category Code	Item Description
	<p>a. Wheel-dressing systems in grinding machines;</p> <p>b. Parallel rotary axes designed for mounting of separate workpieces;</p> <p>c. Co-linear rotary axes designed for manipulating the same workpiece by holding it in a chuck from different ends.</p> <p>3. Axis nomenclature shall be in accordance with International Standard ISO 841:2001, Industrial automation systems and integration - Numerical control of machines - Coordinate system and motion nomenclature.</p> <p>4. For the purposes of Category Codes 2B001 to 2B009, a “tilting spindle” is counted as a rotary axis.</p> <p>5. Stated “unidirectional positioning repeatability” may be used for each machine tool model as an alternative to individual machine tests and is determined as follows:</p> <p>a. Select five machines of a model to be evaluated;</p> <p>b. Measure the linear axis repeatability (R_{\uparrow}, R_{\downarrow}) according to ISO 230/2:2014 and evaluate “unidirectional positioning repeatability” for each axis of each of the five machines;</p> <p>c. Determine the arithmetic mean value of the “unidirectional positioning repeatability” – values for each axis of all five machines together. These arithmetic mean values of “unidirectional positioning repeatability” (\overline{UPR}) become the stated value of each axis for the model (\overline{UPR}_x, \overline{UPR}_y, ...);</p> <p>d. Since the Category 2 list refers to each linear axis there will be as many stated “unidirectional positioning repeatability” values as there are linear axes;</p>

Category Code	Item Description
2B001	<p data-bbox="417 325 1154 559">e. If any axis of a machine model not included under Category Codes 2B001.a. to 2B001.c. has a stated “unidirectional positioning repeatability” equal to or less than the specified “unidirectional positioning repeatability” of each machine tool model plus 0.7 μm, the builder should be required to reaffirm the accuracy level once every eighteen months.</p> <p data-bbox="350 578 1154 744">6. For the purposes of Category Codes 2B001.a. to 2B001.c., measurement uncertainty for the “unidirectional positioning repeatability” of machine tools, as defined in the International Standard ISO 230/2:2014 or national equivalents, shall not be considered.</p> <p data-bbox="350 763 1154 1201">7. For the purposes of Category Codes 2B001.a. to 2B001.c., the measurement of axes shall be made according to test procedures in 5.3.2. of ISO 230/2:2014. Tests for axes longer than 2 m shall be made over 2 m segments. Axes longer than 4 m require multiple tests (e.g. two tests for axes longer than 4 m and up to 8 m, three tests for axes longer than 8 m and up to 12 m), each over 2 m segments and distributed in equal intervals over the axis length. Test segments are equally spaced along the full axis length, with any excess length equally divided at the beginning, in between, and at the end of the test segments. The smallest “unidirectional positioning repeatability” value of all test segments is to be reported.</p> <p data-bbox="350 1271 1154 1405">Machine tools and any combination thereof, for removing (or cutting) metals, ceramics or “composites”, which, according to the manufacturer’s technical specification, can be equipped with electronic devices for “numerical control”, as follows:</p> <p data-bbox="350 1424 404 1452"><u>N.B.</u></p> <p data-bbox="350 1467 727 1496">See also Category Code 2B201.</p> <p data-bbox="350 1515 431 1544"><u>Note 1</u></p> <p data-bbox="350 1559 1154 1662">Category Code 2B001 does not include special purpose machine tools limited to the manufacture of gears. For such machines, see Category Code 2B003.</p>

Category Code	Item Description
	<p><u>Note 2</u> Category Code 2B001 does not include special purpose machine tools limited to the manufacture of any of the following:</p> <ol style="list-style-type: none"> a. Crankshafts or camshafts; b. Tools or cutters; c. Extruder worms; d. Engraved or faceted jewellery parts;<u>or</u> e. Dental prostheses. <p><u>Note 3</u> A machine tool having at least two of the three turning, milling or grinding capabilities (e.g. a turning machine with milling capability), shall be treated as coming within those entries in Category Codes 2B001.a., .b. and .c. that are applicable to its capabilities.</p> <p><u>N.B.</u> For optical finishing machines, see Category Code 2B002.</p> <ol style="list-style-type: none"> a. Machine tools for turning having all of the following: <ol style="list-style-type: none"> 1. “Unidirectional positioning repeatability” equal to or less (better) than 1.1 µm along one or more linear axis; <u>and</u> 2. Two or more axes which can be coordinated simultaneously for “contouring control”; <p><u>Note</u> Category Code 2B001.a. does not include turning machines specially designed for producing contact lenses, having both of the following:</p> <ol style="list-style-type: none"> a. Machine controller limited to using ophthalmic based “software” for part programming data input; <u>and</u> b. No vacuum chucking.

<i>Category Code</i>	<i>Item Description</i>
	<p>b. Machine tools for milling having any of the following:</p> <ol style="list-style-type: none"> 1. Having all of the following: <ol style="list-style-type: none"> a. “Unidirectional positioning repeatability” equal to or less (better) than 1.1 μm along one or more linear axis; <u>and</u> b. Three linear axes plus one rotary axis which can be coordinated simultaneously for “contouring control”; 2. Five or more axes which can be coordinated simultaneously for “contouring control” having any of the following: <p><u><i>N.B.</i></u></p> <p><i>‘Parallel mechanism machine tools’ are specified in Category Code 2B001.b.2.d.</i></p> <ol style="list-style-type: none"> a. “Unidirectional positioning repeatability” equal to or less (better) than 1.1 μm along one or more linear axis with a travel length less than 1 m; b. “Unidirectional positioning repeatability” equal to or less (better) than 1.4 μm along one or more linear axis with a travel length equal to or greater than 1 m and less than 4 m; c. “Unidirectional positioning repeatability” equal to or less (better) than 6.0 μm along one or more linear axis with a travel length equal to or greater than 4 m; <u>or</u> d. Being a ‘parallel mechanism machine tool’; <p><u><i>Technical Note</i></u></p> <p><i>A ‘parallel mechanism machine tool’ is a machine tool having multiple rods which are linked with a platform and actuators; each of the actuators operates the respective rod simultaneously and independently.</i></p>

<i>Category Code</i>	<i>Item Description</i>
	<ol style="list-style-type: none"> <li data-bbox="413 325 1149 420">3. A “unidirectional positioning repeatability” for jig boring machines, equal to or less (better) than 1.1 μm along one or more linear axis; <u>or</u> <li data-bbox="413 439 1149 677">4. Fly cutting machines having all of the following: <ol style="list-style-type: none"> <li data-bbox="498 491 1149 554">a. Spindle “run-out” and “camming” less (better) than 0.0004 mm TIR; <u>and</u> <li data-bbox="498 573 1149 677">b. Angular deviation of slide movement (yaw, pitch and roll) less (better) than 2 seconds of arc, TIR over 300 mm of travel; <li data-bbox="350 696 1149 1547">c. Machine tools for grinding having any of the following: <ol style="list-style-type: none"> <li data-bbox="413 744 1149 982">1. Having all of the following: <ol style="list-style-type: none"> <li data-bbox="498 795 1149 896">a. “Unidirectional positioning repeatability” equal to or less (better) than 1.1 μm along one or more linear axis; <u>and</u> <li data-bbox="498 915 1149 982">b. Three or more axes which can be coordinated simultaneously for “contouring control”; <u>or</u> <li data-bbox="413 1001 1149 1547">2. Five or more axes which can be coordinated simultaneously for “contouring control” having any of the following: <ol style="list-style-type: none"> <li data-bbox="498 1115 1149 1249">a. “Unidirectional positioning repeatability” equal to or less (better) than 1.1 μm along one or more linear axis with a travel length less than 1 m; <li data-bbox="498 1268 1149 1401">b. “Unidirectional positioning repeatability” equal to or less (better) than 1.4 μm along one or more linear axis with a travel length equal to or greater than 1 m and less than 4 m; <u>or</u> <li data-bbox="498 1420 1149 1547">c. “Unidirectional positioning repeatability” equal to or less (better) than 6.0 μm along one or more linear axis with a travel length equal to or greater than 4 m;

Category Code	Item Description
	<p><u>Note</u> Category Code 2B001.c. does not include grinding machines as follows:</p> <ol style="list-style-type: none"> a. Cylindrical external, internal, and external-internal grinding machines, having all of the following: <ol style="list-style-type: none"> 1. Limited to cylindrical grinding; <u>and</u> 2. Limited to a maximum workpiece capacity of 150 mm outside diameter or length; b. Machines designed specifically as jig grinders that do not have a z-axis or a w-axis, with a “unidirectional positioning repeatability” less (better) than 1.1 μm; c. Surface grinders. d. Electrical discharge machines (EDM) of the non-wire type which have two or more rotary axes which can be coordinated simultaneously for “contouring control”; e. Machine tools for removing metals, ceramics or “composites”, having all of the following: <ol style="list-style-type: none"> 1. Removing material by means of any of the following: <ol style="list-style-type: none"> a. Water or other liquid jets, including those employing abrasive additives; b. Electron beam; <u>or</u> c. “Laser” beam; <u>and</u> 2. At least two rotary axes having all of the following: <ol style="list-style-type: none"> a. Can be coordinated simultaneously for “contouring control”; <u>and</u> b. A positioning “accuracy” of less (better) than 0.003°; f. Deep-hole-drilling machines and turning machines modified for deep-hole-drilling, having a maximum depth-of-bore capability exceeding 5 m.

<i>Category Code</i>	<i>Item Description</i>
2B002	<p>“Numerically controlled” optical finishing machine tools equipped for selective material removal to produce non-spherical optical surfaces having all of the following characteristics:</p> <ol style="list-style-type: none"> a. Finishing the form to less (better) than 1 µm; b. Finishing to a roughness less (better) than 100 nm rms; c. Four or more axes which can be coordinated simultaneously for “contouring control”; <u>and</u> d. Using any of the following processes: <ol style="list-style-type: none"> 1. Magnetorheological finishing (‘MRF’); 2. Electrorheological finishing (‘ERF’); 3. ‘Energetic particle beam finishing’; 4. ‘Inflatable membrane tool finishing’; <u>or</u> 5. ‘Fluid jet finishing’. <p><u>Technical Note</u></p> <p><i>For the purpose of Category Code 2B002:</i></p> <ol style="list-style-type: none"> a. ‘MRF’ is a material removal process using an abrasive magnetic fluid whose viscosity is controlled by a magnetic field. b. ‘ERF’ is a removal process using an abrasive fluid whose viscosity is controlled by an electric field. c. ‘Energetic particle beam finishing’ uses Reactive Atom Plasmas (RAP) or ion-beams to selectively remove material. d. ‘Inflatable membrane tool finishing’ is a process that uses a pressurised membrane that deforms to contact the workpiece over a small area. e. ‘Fluid jet finishing’ makes use of a fluid stream for material removal.

<i>Category Code</i>	<i>Item Description</i>
2B003	<p>“Numerically controlled” or manual machine tools, and specially designed components, controls and accessories therefor, specially designed for the shaving, finishing, grinding or honing of hardened ($R_c = 40$ or more) spur, helical and double-helical gears with a pitch diameter exceeding 1,250 mm and a face width of 15% of pitch diameter or larger finished to a quality of AGMA 14 or better (equivalent to ISO 1328 class 3).</p>
2B004	<p>Hot “isostatic presses” having all of the following, and specially designed components and accessories therefor:</p> <p><u>N.B.</u> <i>See also Category Codes 2B104 and 2B204.</i></p> <ol style="list-style-type: none"> a. A controlled thermal environment within the closed cavity and a chamber cavity with an inside diameter of 406 mm or more; <u>and</u> b. Having any of the following: <ol style="list-style-type: none"> 1. A maximum working pressure exceeding 207 MPa; 2. A controlled thermal environment exceeding 1,773 K (1,500°C); <u>or</u> 3. A facility for hydrocarbon impregnation and removal of resultant gaseous degradation products. <p><u>Technical Note</u> <i>The inside chamber dimension is that of the chamber in which both the working temperature and the working pressure are achieved and does not include fixtures. That dimension will be the smaller of either the inside diameter of the pressure chamber or the inside diameter of the insulated furnace chamber, depending on which of the two chambers is located inside the other.</i></p> <p><u>N.B.</u> <i>For specially designed dies, moulds and tooling, see Category Codes 1B003, 9B009 and Division 2 of Part 1 of this Schedule.</i></p>

<i>Category Code</i>	<i>Item Description</i>
2B005	<p>Equipment specially designed for the deposition, processing and in-process control of inorganic overlays, coatings and surface modifications, as follows, for non-electronic substrates, by processes shown in the Table and associated Notes following Category Code 2E003.f., and specially designed automated handling, positioning, manipulation and control components therefor:</p> <ol style="list-style-type: none"> a. Chemical vapour deposition (CVD) production equipment having both of the following: <ul style="list-style-type: none"> <u><i>N.B.</i></u> <i>See also Category Code 2B105.</i> <ol style="list-style-type: none"> 1. A process modified for one of the following: <ol style="list-style-type: none"> a. Pulsating CVD; b. Controlled nucleation thermal deposition (CNTD); <u>or</u> c. Plasma enhanced or plasma assisted CVD; <u>and</u> 2. Having any of the following: <ol style="list-style-type: none"> a. Incorporating high vacuum (equal to or less than 0.01 Pa) rotating seals; <u>or</u> b. Incorporating <i>in situ</i> coating thickness control; b. Ion implantation production equipment having beam currents of 5 mA or more; c. Electron beam physical vapour deposition (EB-PVD) production equipment incorporating power systems rated for over 80 kW and having any of the following: <ol style="list-style-type: none"> 1. A liquid pool level “laser” control system which regulates precisely the ingots feed rate; <u>or</u> 2. A computer controlled rate monitor operating on the principle of photo-luminescence of the ionised atoms in the evaporant stream to control the deposition rate of a coating containing two or more elements;

<i>Category Code</i>	<i>Item Description</i>
	<p>d. Plasma spraying production equipment having any of the following:</p> <ol style="list-style-type: none"> 1. Operating at reduced pressure controlled atmosphere (equal to or less than 10 kPa measured above and within 300 mm of the gun nozzle exit) in a vacuum chamber capable of evacuation down to 0.01 Pa prior to the spraying process; <u>or</u> 2. Incorporating <i>in situ</i> coating thickness control; <p>e. Sputter deposition production equipment capable of current densities of 0.1 mA/mm² or higher at a deposition rate of 15 µm/h or more;</p> <p>f. Cathodic arc deposition production equipment incorporating a grid of electromagnets for steering control of the arc spot on the cathode;</p> <p>g. Ion plating production equipment capable of the <i>in situ</i> measurement of any of the following:</p> <ol style="list-style-type: none"> 1. Coating thickness on the substrate and rate control; <u>or</u> 2. Optical characteristics. <p><u>Note</u> <i>Category Code 2B005 does not include chemical vapour deposition, cathodic arc, sputter deposition, ion plating or ion implantation equipment, specially designed for cutting or machining tools.</i></p>
2B006	<p>Dimensional inspection or measuring systems, equipment and “electronic assemblies”, as follows:</p> <ol style="list-style-type: none"> a. Computer controlled or “numerically controlled” Coordinate Measuring Machines (CMM), having a three dimensional (volumetric) maximum permissible error of length measurement ($E_{0,MPE}$) at any point within the operating range of the machine (i.e. within the length of axes) equal to or less (better) than $(1.7 + L/1,000)$ µm (L is the measured length in mm), according to ISO 10360-2 (2009);

Category Code	Item Description
	<p><u>Technical Note</u></p> <p>The $E_{0,MPE}$ of the most accurate configuration of the CMM specified by the manufacturer (e.g. best of the following: probe, stylus length, motion parameters, environment) and with “all compensations available” shall be compared to the $1.7 + L/1,000 \mu\text{m}$ threshold.</p> <p><u>N.B.</u></p> <p>See also Category Code 2B206.</p> <p>b. Linear and angular displacement measuring instruments, as follows:</p> <p>1. ‘Linear displacement’ measuring instruments having any of the following:</p> <p><u>Note</u></p> <p>Displacement measuring “laser” interferometers are only included in Category Code 2B006.b.1.c.</p> <p><u>Technical Note</u></p> <p>For the purpose of Category Code 2B006.b.1., ‘linear displacement’ means the change of distance between the measuring probe and the measured object.</p> <p>a. Non-contact type measuring systems with a “resolution” equal to or less (better) than $0.2 \mu\text{m}$ within a measuring range up to 0.2 mm;</p> <p>b. Linear Variable Differential Transformer (LVDT) systems having both of the following:</p> <p>1. Having any of the following:</p> <p>a. “Linearity” equal to or less (better) than 0.1% measured from 0 to the ‘full operating range’, for LVDTs with a ‘full operating range’ up to and including $\pm 5 \text{ mm}$; <u>or</u></p> <p>b. “Linearity” equal to or less (better) than 0.1% measured from 0 to 5 mm for LVDTs with a ‘full operating range’ greater than $\pm 5 \text{ mm}$; <u>and</u></p>

Category Code	Item Description
	<p data-bbox="563 325 1154 424">2. Drift equal to or less (better) than 0.1% per day at a standard ambient test room temperature ± 1 K;</p> <p data-bbox="563 443 747 476"><u>Technical Note</u></p> <p data-bbox="563 485 1154 719"><i>For the purpose of Category Code 2B006.b.1.b., 'full operating range' is half of the total possible linear displacement of the LVDT. For example, LVDTs with a 'full operating range' up to and including ± 5 mm can measure a total possible linear displacement of 10 mm.</i></p> <p data-bbox="501 740 1154 1428">c. Measuring systems having all of the following:</p> <ol style="list-style-type: none"> <li data-bbox="565 790 932 822">1. Containing a "laser"; <u>and</u> <li data-bbox="565 839 1154 1309">2. Maintaining, for at least 12 hours, at a temperature of $20 \pm 1^\circ\text{C}$, all of the following: <ol style="list-style-type: none"> <li data-bbox="624 959 1154 1024">a. A "resolution" over their full scale of $0.1 \mu\text{m}$ or less (better); <u>and</u> <li data-bbox="624 1041 1154 1309">b. Capable of achieving a "measurement uncertainty" equal to or less (better) than $(0.2 + L/2,000) \mu\text{m}$ (L is the measured length in mm) at any point within a measuring range, when compensated for the refractive index of air; <u>or</u> <li data-bbox="501 1328 1154 1428">d. "Electronic assemblies" specially designed to provide feedback capability in systems specified in Category Code 2B006.b.1.c.; <p data-bbox="478 1448 538 1481"><u>Note</u></p> <p data-bbox="478 1490 1154 1690"><i>Category Code 2B006.b.1. does not include measuring interferometer systems, with an automatic control system that is designed to use no feedback techniques, containing a "laser" to measure slide movement errors of machine-tools, dimensional inspection machines or similar equipment.</i></p>

Category Code	Item Description
	<p>2. Angular displacement measuring instruments having an angular position “accuracy” equal to or less (better) than 0.00025°;</p> <p><u>Note</u> Category Code 2B006.b.2. does not include optical instruments, such as autocollimators, using collimated light (e.g. laser light) to detect angular displacement of a mirror.</p> <p>c. Equipment for measuring surface roughness (including surface defects), by measuring optical scatter with a sensitivity of 0.5 nm or less (better).</p> <p><u>Note</u> Category Code 2B006 includes machine tools, other than those specified by Category Code 2B001, that can be used as measuring machines if they meet or exceed the criteria specified for the measuring machine function.</p>
2B007	<p>“Robots” having any of the following characteristics and specially designed controllers and “end-effectors” therefor:</p> <p><u>N.B.</u> See also Category Code 2B207.</p> <p>a. Capable in real-time of full three-dimensional image processing or full three-dimensional ‘scene analysis’ to generate or modify “programmes” or to generate or modify numerical programme data;</p> <p><u>Technical Note</u> The ‘scene analysis’ limitation does not include approximation of the third dimension by viewing at a given angle, or limited grey scale interpretation for the perception of depth or texture for the approved tasks (2½ D).</p> <p>b. Specially designed to comply with national safety standards applicable to potentially explosive munitions environments;</p> <p><u>Note</u> Category Code 2B007.b. does not include “robots” specially designed for paint-spraying booths.</p>

Category Code	Item Description
2B008	<p>c. Specially designed or rated as radiation-hardened to withstand a total radiation dose greater than 5×10^3 Gy (silicon) without operational degradation; <u>or</u></p> <p><u>Technical Note</u> <i>The term Gy (silicon) refers to the energy in Joules per kilogram absorbed by an unshielded silicon sample when exposed to ionising radiation.</i></p> <p>d. Specially designed to operate at altitudes exceeding 30,000 m.</p> <p>Assemblies or units, specially designed for machine tools, or dimensional inspection or measuring systems and equipment, as follows:</p> <p>a. Linear position feedback units having an overall “accuracy” less (better) than $(800 + (600 \times L/1,000))$ nm (L equals the effective length in mm);</p> <p><u>N.B.</u> <i>For “laser” systems, see also Note to Category Codes 2B006.b.1.c. and d.</i></p> <p>b. Rotary position feedback units having an “accuracy” less (better) than 0.00025°;</p> <p><u>N.B.</u> <i>For “laser” systems, see also Note to Category Code 2B006.b.2.</i></p> <p><u>Note</u> <i>Category Codes 2B008.a. and 2B008.b. include units, which are designed to determine the positioning information for feedback control, such as inductive type devices, graduated scales, infrared systems or “laser” systems.</i></p> <p>c. “Compound rotary tables” and “tilting spindles”, capable of upgrading, according to the manufacturer’s specifications, machine tools to or above the levels specified in Category 2B.</p>

<i>Category Code</i>	<i>Item Description</i>
2B009	<p>Spin-forming machines and flow-forming machines, which, according to the manufacturer's technical specification, can be equipped with "numerical control" units or a computer control and having both of the following:</p> <p><u>N.B.</u> <i>See also Category Codes 2B109 and 2B209.</i></p> <p>a. Three or more axes which can be coordinated simultaneously for "contouring control"; <u>and</u></p> <p>b. A roller force more than 60 kN.</p> <p><u>Technical Note</u> <i>For the purpose of Category Code 2B009, machines combining the function of spin-forming and flow-forming are regarded as flow-forming machines.</i></p>
2B104	<p>"Isostatic presses", other than those specified in Category Code 2B004, having all of the following:</p> <p><u>N.B.</u> <i>See also Category Code 2B204.</i></p> <p>a. Maximum working pressure of 69 MPa or greater;</p> <p>b. Designed to achieve and maintain a controlled thermal environment of 873 K (600°C) or greater; <u>and</u></p> <p>c. Possessing a chamber cavity with an inside diameter of 254 mm or greater.</p>
2B105	<p>Chemical Vapour Deposition (CVD) furnaces, other than those specified in Category Code 2B005.a., designed or modified for the densification of carbon-carbon composites.</p>

<i>Category Code</i>	<i>Item Description</i>
2B109	<p>Flow-forming machines, other than those specified in Category Code 2B009, and specially designed components as follows:</p> <p><u><i>N.B.</i></u> <i>See also Category Code 2B209.</i></p> <p>a. Flow-forming machines having both of the following:</p> <ol style="list-style-type: none"> 1. According to the manufacturer's technical specification, can be equipped with "numerical control" units or a computer control, even when not equipped with such units; <u>and</u> 2. With more than two axes which can be coordinated simultaneously for "contouring control"; <p>b. Specially designed components for flow-forming machines specified in Category Code 2B009 or 2B109.a.</p> <p><u><i>Note</i></u> <i>Category Code 2B109 does not include machines that are not usable in the production of propulsion components and equipment (e.g. motor cases) for systems specified in Category Code 9A005, 9A007.a. or 9A105.a.</i></p> <p><u><i>Technical Note</i></u> <i>Machines combining the function of spin-forming and flow-forming are for the purpose of Category Code 2B109 regarded as flow-forming machines.</i></p>
2B116	<p>Vibration test systems, equipment and components therefor, as follows:</p> <p>a. Vibration test systems employing feedback or closed loop techniques and incorporating a digital controller, capable of vibrating a system at an acceleration equal to or greater than 10 g rms between 20 Hz and 2 kHz while imparting forces equal to or greater than 50 kN, measured 'bare table';</p> <p>b. Digital controllers, combined with specially designed vibration test software, with a 'real-time control bandwidth' greater than 5 kHz designed for use with vibration test systems specified in Category Code 2B116.a.;</p>

Category Code	Item Description
	<p><u>Technical Note</u> <i>In Category Code 2B116.b., 'real-time control bandwidth' means the maximum rate at which a controller can execute complete cycles of sampling, processing data and transmitting control signals.</i></p> <p>c. Vibration thrusters (shaker units), with or without associated amplifiers, capable of imparting a force equal to or greater than 50 kN, measured 'bare table', and usable in vibration test systems specified in Category Code 2B116.a.;</p> <p>d. Test piece support structures and electronic units designed to combine multiple shaker units in a system capable of providing an effective combined force equal to or greater than 50 kN, measured 'bare table', and usable in vibration systems specified in Category Code 2B116.a.</p>
	<p><u>Technical Note</u> <i>In Category Code 2B116, 'bare table' means a flat table, or surface, with no fixture or fittings.</i></p>
2B117	<p>Equipment and process controls, other than those specified in Category Code 2B004, 2B005.a., 2B104 or 2B105, designed or modified for densification and pyrolysis of structural composite rocket nozzles and re-entry vehicle nose tips.</p>
2B119	<p>Balancing machines and related equipment, as follows:</p> <p><u>N.B.</u> <i>See also Category Code 2B219.</i></p> <p>a. Balancing machines having all the following characteristics:</p> <ol style="list-style-type: none"> 1. Not capable of balancing rotors/assemblies having a mass greater than 3 kg; 2. Capable of balancing rotors/assemblies at speeds greater than 12,500 rpm; 3. Capable of correcting unbalance in two planes or more; <u>and</u> 4. Capable of balancing to a residual specific unbalance of 0.2 g mm per kg of rotor mass;

<i>Category Code</i>	<i>Item Description</i>
	<p><u>Note</u> <i>Category Code 2B119.a. does not include balancing machines designed or modified for dental or other medical equipment.</i></p> <p>b. Indicator heads designed or modified for use with machines specified in Category Code 2B119.a.</p> <p><u>Technical Note</u> <i>Indicator heads are sometimes known as balancing instrumentation.</i></p>
2B120	<p>Motion simulators or rate tables having all of the following characteristics:</p> <p>a. Two axes or more;</p> <p>b. Designed or modified to incorporate slip rings or integrated non-contact devices capable of transferring electrical power, signal information, or both; <u>and</u></p> <p>c. Having any of the following characteristics:</p> <ol style="list-style-type: none"> 1. For any single axis having all of the following: <ol style="list-style-type: none"> a. Capable of rates of 400 degrees/s or more, or 30 degrees/s or less; <u>and</u> b. A rate resolution equal to or less than 6 degrees/s and an accuracy equal to or less than 0.6 degrees/s; 2. Having a worst-case rate stability equal to or better (less) than plus or minus 0.05% averaged over 10 degrees or more; <u>or</u> 3. A positioning “accuracy” equal to or less (better) than 5 arc second.

Category Code	Item Description
	<p><u>Note 1</u> <i>Category Code 2B120 does not include rotary tables designed or modified for machine tools or for medical equipment. For machine tool rotary tables, see Category Code 2B008.</i></p> <p><u>Note 2</u> <i>Motion simulators or rate tables that satisfy all the characteristics under Category Code 2B120 remain within that Code whether or not slip rings or integrated non-contact devices are fitted on them at time of export.</i></p>
2B121	<p>Positioning tables (equipment capable of precise rotary positioning in any axes), other than those specified in Category Code 2B120, having all of the following characteristics:</p> <ol style="list-style-type: none"> a. Two axes or more; <u>and</u> b. A positioning “accuracy” equal to or less (better) than 5 arc second.
	<p><u>Note</u> <i>Category Code 2B121 does not include rotary tables designed or modified for machine tools or for medical equipment. For machine tool rotary tables, see Category Code 2B008.</i></p>
2B122	<p>Centrifuges capable of imparting accelerations above 100 g and designed or modified to incorporate slip rings or integrated non-contact devices capable of transferring electrical power, signal information, or both.</p> <p><u>Note</u> <i>Centrifuges that come within the description in Category Code 2B122 remain within that Code whether or not slip rings or integrated non-contact devices are fitted on them at time of export.</i></p>

<i>Category Code</i>	<i>Item Description</i>
2B201	<p>Machine tools and any combination thereof, other than those specified in Category Code 2B001, as follows, for removing or cutting metals, ceramics or “composites”, which, according to the manufacturer’s technical specification, can be equipped with electronic devices for simultaneous “contouring control” in two or more axes:</p> <p><u>Technical Note</u></p> <p><i>Stated ‘positioning accuracy’ levels derived under the following procedures from measurements made according to ISO 230/2 (1988) or national equivalents may be used for each machine tool model if provided to, and accepted by, national authorities instead of individual machine tests. Determination of stated ‘positioning accuracy’:</i></p> <ol style="list-style-type: none"> <i>a. Select five machines of a model to be evaluated;</i> <i>b. Measure the linear axis accuracies according to ISO 230/2 (1988);</i> <i>c. Determine the accuracy values (A) for each axis of each machine. The method of calculating the accuracy value is described in the ISO 230/2 (1988) standard;</i> <i>d. Determine the average accuracy value of each axis. This average value becomes the stated ‘positioning accuracy’ of each axis for the model ($\hat{A}_x \hat{A}_y \dots$);</i> <i>e. Since Category Code 2B201 refers to each linear axis, there will be as many stated ‘positioning accuracy’ values as there are linear axes;</i> <i>f. If any axis of a machine tool not included in Category Code 2B201.a., 2B201.b. or 2B201.c. has a stated ‘positioning accuracy’ of 6 μm or better (less) for grinding machines, and 8 μm or better (less) for milling and turning machines, both according to ISO 230/2 (1988), then the builder should be required to reaffirm the accuracy level once every eighteen months.</i>

Category Code	Item Description
	<p>a. Machine tools for milling having any of the following characteristics:</p> <ol style="list-style-type: none"> 1. ‘Positioning accuracies’ with “all compensations available” equal to or less (better) than 6 μm according to ISO 230/2 (1988) or national equivalents along any linear axis; 2. Two or more contouring rotary axes; <u>or</u> 3. Five or more axes which can be coordinated simultaneously for “contouring control”; <p><i>Note</i> <i>Category Code 2B201.a. does not include milling machines having the following characteristics:</i></p> <ol style="list-style-type: none"> a. <i>X-axis travel greater than 2 m; <u>and</u></i> b. <i>Overall ‘positioning accuracy’ on the x-axis more (worse) than 30 μm.</i> <p>b. Machine tools for grinding having any of the following characteristics:</p> <ol style="list-style-type: none"> 1. ‘Positioning accuracies’ with “all compensations available” equal to or less (better) than 4 μm according to ISO 230/2 (1988) or national equivalents along any linear axis; 2. Two or more contouring rotary axes; <u>or</u> 3. Five or more axes which can be coordinated simultaneously for “contouring control”; <p><i>Note</i> <i>Category Code 2B201.b. does not include grinding machines as follows:</i></p> <ol style="list-style-type: none"> a. <i>Cylindrical external, internal, and external-internal grinding machines having both of the following characteristics:</i> <ol style="list-style-type: none"> 1. <i>Limited to a maximum workpiece capacity of 150 mm outside diameter or length; <u>and</u></i> 2. <i>Axes limited to x, z and c;</i>

Category Code	Item Description
	<p data-bbox="413 325 1143 458">b. Jig grinders that do not have a z-axis or a w-axis with an overall 'positioning accuracy' less (better) than $4\ \mu\text{m}$ according to ISO 230/2 (1988) or national equivalents.</p> <p data-bbox="350 477 1143 643">c. Machine tools for turning, that have 'positioning accuracies' with "all compensations available" better (less) than $6\ \mu\text{m}$ according to ISO 230/2 (1988) along any linear axis (overall positioning) for machines capable of machining diameters greater than 35 mm;</p> <p data-bbox="413 662 475 693"><u>Note</u></p> <p data-bbox="413 706 1143 906">Category Code 2B201.c. does not include bar machines (Swissturn), limited to machining only bar feed through, if maximum bar diameter is equal to or less than 42 mm and there is no capability of mounting chucks. Machines may have drilling or milling capabilities, or both for machining parts with diameters less than 42 mm.</p> <p data-bbox="350 925 431 955"><u>Note 1</u></p> <p data-bbox="350 969 1143 1031">Category Code 2B201 does not include special purpose machine tools limited to the manufacture of any of the following parts:</p> <p data-bbox="350 1045 727 1201">a. Gears; b. Crankshafts or camshafts; c. Tools or cutters; <u>or</u> d. Extruder worms.</p> <p data-bbox="350 1220 431 1250"><u>Note 2</u></p> <p data-bbox="350 1264 1143 1429">A machine tool having at least two of the three turning, milling or grinding capabilities (e.g. a turning machine with milling capability) shall be treated as coming within those entries in Category Code 2B201.a., .b. or .c. that are applicable to its capabilities.</p>

<i>Category Code</i>	<i>Item Description</i>
2B204	<p>“Isostatic presses”, other than those specified in Category Code 2B004 or 2B104, and related equipment, as follows:</p> <ol style="list-style-type: none"> a. “Isostatic presses” having both of the following characteristics: <ol style="list-style-type: none"> 1. Capable of achieving a maximum working pressure of 69 MPa or greater; <u>and</u> 2. A chamber cavity with an inside diameter in excess of 152 mm; b. Dies, moulds and controls, specially designed for “isostatic presses” specified in Category Code 2B204.a. <p><i>Technical Note</i></p> <p><i>In Category Code 2B204, the inside chamber dimension is that of the chamber in which both the working temperature and the working pressure are achieved and does not include fixtures. That dimension will be the smaller of either the inside diameter of the pressure chamber or the inside diameter of the insulated furnace chamber, depending on which of the two chambers is located inside the other.</i></p>
2B206	<p>Dimensional inspection machines, instruments or systems, other than those specified in Category Code 2B006, as follows:</p> <ol style="list-style-type: none"> a. Computer controlled or numerically controlled coordinate measuring machines (CMM) having either of the following characteristics: <ol style="list-style-type: none"> 1. Having only two axes and having a maximum permissible error of length measurement along any axis (one dimensional), identified as any combination of $E_{0x,MPE}$, $E_{0y,MPE}$, or $E_{0z,MPE}$, equal to or less (better) than $(1.25 + L/1,000) \mu\text{m}$ (where L is the measured length in mm) at any point within the operating range of the machine (i.e. within the length of the axis), according to ISO 10360-2 (2009); <u>or</u>

Category Code	Item Description
	<p data-bbox="413 325 1153 559">2. Three or more axes and having a three dimensional (volumetric) maximum permissible error of length measurement ($E_{0,MPE}$) equal to or less (better) than $(1.7 + L/800) \mu\text{m}$ (where L is the measured length in mm) at any point within the operating range of the machine (i.e. within the length of the axis), according to ISO 10360-2 (2009);</p> <p data-bbox="413 578 599 607"><u>Technical Note</u></p> <p data-bbox="413 620 1153 820"><i>The $E_{0,MPE}$ of the most accurate configuration of the CMM specified according to ISO 10360-2 (2009) by the manufacturer (e.g. best of the following: probe, stylus, length, motion parameters, environments) and with all compensations available shall be compared to the $1.7 + L/800 \mu\text{m}$ threshold.</i></p> <p data-bbox="350 839 1153 1073">b. Systems for simultaneous linear-angular inspection of hemishells, having both of the following characteristics:</p> <ol data-bbox="413 925 1153 1073" style="list-style-type: none"> <li data-bbox="413 925 1153 991">1. “Measurement uncertainty” along any linear axis equal to or less (better) than $3.5 \mu\text{m}$ per 5 mm; <u>and</u> <li data-bbox="413 1005 1153 1073">2. “Angular position deviation” equal to or less than 0.02°. <p data-bbox="350 1092 434 1121"><u>Note 1</u></p> <p data-bbox="350 1134 1153 1233"><i>Machine tools that can be used as measuring machines are included if they meet or exceed the criteria specified for the machine tool function or the measuring machine function.</i></p> <p data-bbox="350 1252 434 1281"><u>Note 2</u></p> <p data-bbox="350 1294 1153 1393"><i>A machine specified in Category Code 2B206 is included in that Category Code if it exceeds the specifications stated therein anywhere within its operating range.</i></p> <p data-bbox="350 1412 536 1441"><u>Technical Note</u></p> <p data-bbox="350 1454 1153 1521"><i>All parameters of measurement values in Category Code 2B206 represent plus/minus i.e. not total band.</i></p>

<i>Category Code</i>	<i>Item Description</i>
2B207	<p>“Robots”, “end-effectors” and control units, other than those specified in Category Code 2B007, as follows:</p> <ol style="list-style-type: none"> a. “Robots” or “end-effectors” specially designed to comply with national safety standards applicable to handling high explosives (e.g. meeting electrical code ratings for high explosives); b. Control units specially designed for any of the “robots” or “end-effectors” specified in Category Code 2B207.a.
2B209	<p>Flow forming machines, spin forming machines capable of flow forming functions, other than those specified in Category Code 2B009 or 2B109, and mandrels, as follows:</p> <ol style="list-style-type: none"> a. Machines having both of the following characteristics: <ol style="list-style-type: none"> 1. Three or more rollers (active or guiding); <u>and</u> 2. Which, according to the manufacturer’s technical specification, can be equipped with “numerical control” units or a computer control; <p><i>Note</i> <i>Category Code 2B209.a. includes machines which have only a single roller designed to deform metal plus two auxiliary rollers which support the mandrel, but do not participate directly in the deformation process.</i></p> b. Rotor-forming mandrels designed to form cylindrical rotors of inside diameter between 75 mm and 400 mm.
2B219	<p>Centrifugal multiplane balancing machines, fixed or portable, horizontal or vertical, as follows:</p> <ol style="list-style-type: none"> a. Centrifugal balancing machines designed for balancing flexible rotors having a length of 600 mm or more and having all of the following characteristics: <ol style="list-style-type: none"> 1. Swing or journal diameter greater than 75 mm; 2. Mass capability of from 0.9 kg to 23 kg; <u>and</u> 3. Capable of balancing speed of revolution greater than 5,000 rpm;

<i>Category Code</i>	<i>Item Description</i>
2B225	<p>b. Centrifugal balancing machines designed for balancing hollow cylindrical rotor components and having all of the following characteristics:</p> <ol style="list-style-type: none"> 1. Journal diameter greater than 75 mm; 2. Mass capability of from 0.9 kg to 23 kg; 3. Capable of balancing to a residual imbalance equal to or less than 0.01 kg × mm/kg per plane; <u>and</u> 4. Belt drive type. <p>Remote manipulators that can be used to provide remote actions in radiochemical separation operations or hot cells, having either of the following characteristics:</p> <ol style="list-style-type: none"> a. A capability of penetrating 0.6 m or more of hot cell wall (through-the-wall operation); <u>or</u> b. A capability of bridging over the top of a hot cell wall with a thickness of 0.6 m or more (over-the-wall operation). <p><u>Technical Note</u> <i>Remote manipulators provide translation of human operator actions to a remote operating arm and terminal fixture. They may be of 'master/slave' type or operated by joystick or keypad.</i></p>
2B226	<p>Controlled atmosphere (vacuum or inert gas) induction furnaces, and power supplies therefor, as follows:</p> <p><u>N.B.</u> <i>See also Category 3B.</i></p> <ol style="list-style-type: none"> a. Furnaces having all of the following characteristics: <ol style="list-style-type: none"> 1. Capable of operation above 1,123 K (850°C); 2. Induction coils 600 mm or less in diameter; <u>and</u> 3. Designed for power inputs of 5 kW or more;

<i>Category Code</i>	<i>Item Description</i>
	<p>b. Power supplies, with a specified power output of 5 kW or more, specially designed for furnaces specified in Category Code 2B226.a.</p> <p><i>Note</i> <i>Category Code 2B226.a. does not include furnaces designed for the processing of semiconductor wafers.</i></p>
2B227	<p>Vacuum or other controlled atmosphere metallurgical melting and casting furnaces and related equipment as follows:</p> <p>a. Arc remelt and casting furnaces having both of the following characteristics:</p> <ol style="list-style-type: none"> 1. Consumable electrode capacities between 1,000 cm³ and 20,000 cm³; <u>and</u> 2. Capable of operating with melting temperatures above 1,973 K (1,700°C); <p>b. Electron beam melting furnaces and plasma atomisation and melting furnaces, having both of the following characteristics:</p> <ol style="list-style-type: none"> 1. A power of 50 kW or greater; <u>and</u> 2. Capable of operating with melting temperatures above 1,473 K (1,200°C); <p>c. Computer control and monitoring systems specially configured for any of the furnaces specified in Category Code 2B227.a. or 2B227.b.</p>

<i>Category Code</i>	<i>Item Description</i>
2B228	<p>Rotor fabrication or assembly equipment, rotor straightening equipment, bellows-forming mandrels and dies, as follows:</p> <p>a. Rotor assembly equipment for assembly of gas centrifuge rotor tube sections, baffles, and end caps;</p> <p><i>Note</i> <i>Category Code 2B228.a. includes precision mandrels, clamps, and shrink fit machines.</i></p> <p>b. Rotor straightening equipment for alignment of gas centrifuge rotor tube sections to a common axis;</p> <p><i>Technical Note</i> <i>Equipment specified in Category Code 2B228.b. normally consists of precision measuring probes linked to a computer that subsequently controls the action of, e.g. pneumatic rams used for aligning the rotor tube sections.</i></p> <p>c. Bellows-forming mandrels and dies for producing single-convolution bellows.</p> <p><i>Technical Note</i> <i>In Category Code 2B228.c., the bellows have all of the following characteristics:</i></p> <p>a. <i>Inside diameter between 75 mm and 400 mm;</i></p> <p>b. <i>Length equal to or greater than 12.7 mm;</i></p> <p>c. <i>Single convolution depth greater than 2 mm; <u>and</u></i></p> <p>d. <i>Made of high-strength aluminium alloys, maraging steel or high strength “fibrous or filamentary materials”.</i></p>

<i>Category Code</i>	<i>Item Description</i>
2B230	<p>All types of ‘pressure transducers’ capable of measuring absolute pressures and having all of the following:</p> <ol style="list-style-type: none"> a. Pressure sensing elements made of or protected by aluminium, aluminium alloy, aluminium oxide (alumina or sapphire), nickel, nickel alloy with more than 60% nickel by weight, or fully fluorinated hydrocarbon polymers; b. Seals, if any, essential for sealing the pressure sensing element, and in direct contact with the process medium, made of or protected by aluminium, aluminium alloy, aluminium oxide (alumina or sapphire), nickel, nickel alloy with more than 60% nickel by weight, or fully fluorinated hydrocarbon polymers; <u>and</u> c. Having either of the following characteristics: <ol style="list-style-type: none"> 1. A full scale of less than 13 kPa and an ‘accuracy’ of better than $\pm 1\%$ of full-scale; <u>or</u> 2. A full scale of 13 kPa or greater and an ‘accuracy’ of better than ± 130 Pa when measured at 13 kPa. <p><i>Technical Notes</i></p> <ol style="list-style-type: none"> 1. In Category Code 2B230, ‘pressure transducer’ means a device that converts a pressure measurement into a signal. 2. For the purpose of Category Code 2B230, ‘accuracy’ includes non-linearity, hysteresis and repeatability at ambient temperature.
2B231	<p>Vacuum pumps having all of the following characteristics:</p> <ol style="list-style-type: none"> a. Input throat size equal to or greater than 380 mm; b. Pumping speed equal to or greater than 15 m³/s; <u>and</u> c. Capable of producing an ultimate vacuum better than 13 mPa. <p><i>Technical Notes</i></p> <ol style="list-style-type: none"> 1. The pumping speed is determined at the measurement point with nitrogen gas or air. 2. The ultimate vacuum is determined at the input of the pump with the input of the pump blocked off.

<i>Category Code</i>	<i>Item Description</i>
2B232	<p>High-velocity gun systems (propellant, gas, coil, electromagnetic, and electrothermal types, and other advanced systems) capable of accelerating projectiles to 1.5 km/s or greater.</p> <p><u>N.B.</u> See also Division 2 of Part 1 of this Schedule.</p>
2B233	<p>Bellows-sealed scroll-type compressors and bellows-sealed scroll-type vacuum pumps having all of the following:</p> <p><u>N.B.</u> See also Category Code 2B350.i.</p> <ol style="list-style-type: none"> a. Capable of an inlet volume flow rate of 50 m³/h or greater; b. Capable of a pressure ratio of 2:1 or greater; <u>and</u> c. Having all surfaces that come in contact with the process gas made from any of the following materials: <ol style="list-style-type: none"> 1. Aluminium or aluminium alloy; 2. Aluminium oxide; 3. Stainless steel; 4. Nickel or nickel alloy; 5. Phosphor bronze; <u>or</u> 6. Fluoropolymers.
2B350	<p>Chemical manufacturing facilities, equipment and components, as follows:</p> <ol style="list-style-type: none"> a. Reaction vessels or reactors, with or without agitators, with total internal (geometric) volume greater than 0.1 m³ (100 litres) and less than 20 m³ (20,000 litres), where all surfaces that come in direct contact with the chemical(s) being processed or contained are made from any of the following materials: <ol style="list-style-type: none"> 1. ‘Alloys’ with more than 25% nickel and 20% chromium by weight; 2. Fluoropolymers (polymeric or elastomeric materials with more than 35% fluorine by weight);

<i>Category Code</i>	<i>Item Description</i>
	<ol style="list-style-type: none"> 3. Glass (including vitrified or enamelled coating or glass lining); 4. Nickel or ‘alloys’ with more than 40% nickel by weight; 5. Tantalum or tantalum ‘alloys’; 6. Titanium or titanium ‘alloys’; 7. Zirconium or zirconium ‘alloys’; <u>or</u> 8. Niobium (columbium) or niobium ‘alloys’; <p>b. Agitators designed for use in reaction vessels or reactors specified in Category Code 2B350.a.; and impellers, blades or shafts designed for such agitators, where all surfaces of the agitator that come in direct contact with the chemical(s) being processed or contained are made from any of the following materials:</p> <ol style="list-style-type: none"> 1. ‘Alloys’ with more than 25% nickel and 20% chromium by weight; 2. Fluoropolymers (polymeric or elastomeric materials with more than 35% fluorine by weight); 3. Glass (including vitrified or enamelled coatings or glass lining); 4. Nickel or ‘alloys’ with more than 40% nickel by weight; 5. Tantalum or tantalum ‘alloys’; 6. Titanium or titanium ‘alloys’; 7. Zirconium or zirconium ‘alloys’; <u>or</u> 8. Niobium (columbium) or niobium ‘alloys’;

<i>Category Code</i>	<i>Item Description</i>
	<p>c. Storage tanks, containers or receivers with a total internal (geometric) volume greater than 0.1 m³ (100 litres) where all surfaces that come in direct contact with the chemical(s) being processed or contained are made from any of the following materials:</p> <ol style="list-style-type: none"> 1. 'Alloys' with more than 25% nickel and 20% chromium by weight; 2. Fluoropolymers (polymeric or elastomeric materials with more than 35% fluorine by weight); 3. Glass (including vitrified or enamelled coatings or glass lining); 4. Nickel or 'alloys' with more than 40% nickel by weight; 5. Tantalum or tantalum 'alloys'; 6. Titanium or titanium 'alloys'; 7. Zirconium or zirconium 'alloys'; <u>or</u> 8. Niobium (columbium) or niobium 'alloys'; <p>d. Heat exchangers or condensers with a heat transfer surface area greater than 0.15 m², and less than 20 m²; and tubes, plates, coils or blocks (cores) designed for such heat exchangers or condensers, where all surfaces that come in direct contact with the chemical(s) being processed are made from any of the following materials:</p> <ol style="list-style-type: none"> 1. 'Alloys' with more than 25% nickel and 20% chromium by weight; 2. Fluoropolymers (polymeric or elastomeric materials with more than 35% fluorine by weight); 3. Glass (including vitrified or enamelled coatings or glass lining); 4. Graphite or 'carbon graphite'; 5. Nickel or 'alloys' with more than 40% nickel by weight; 6. Tantalum or tantalum 'alloys'; 7. Titanium or titanium 'alloys';

<i>Category Code</i>	<i>Item Description</i>
	<ol style="list-style-type: none"> 8. Zirconium or zirconium ‘alloys’; 9. Silicon carbide; 10. Titanium carbide; <u>or</u> 11. Niobium (columbium) or niobium ‘alloys’; <p>e. Distillation or absorption columns of internal diameter greater than 0.1 m; and liquid distributors, vapour distributors or liquid collectors designed for such distillation or absorption columns, where all surfaces that come in direct contact with the chemical(s) being processed are made from any of the following materials:</p> <ol style="list-style-type: none"> 1. ‘Alloys’ with more than 25% nickel and 20% chromium by weight; 2. Fluoropolymers (polymeric or elastomeric materials with more than 35% fluorine by weight); 3. Glass (including vitrified or enamelled coatings or glass lining); 4. Graphite or ‘carbon graphite’; 5. Nickel or ‘alloys’ with more than 40% nickel by weight; 6. Tantalum or tantalum ‘alloys’; 7. Titanium or titanium ‘alloys’; 8. Zirconium or zirconium ‘alloys’; <u>or</u> 9. Niobium (columbium) or niobium ‘alloys’; <p>f. Remotely operated filling equipment in which all surfaces that come in direct contact with the chemical(s) being processed are made from any of the following materials:</p> <ol style="list-style-type: none"> 1. ‘Alloys’ with more than 25% nickel and 20% chromium by weight; <u>or</u> 2. Nickel or ‘alloys’ with more than 40% nickel by weight;

<i>Category Code</i>	<i>Item Description</i>
	<p>g. Valves and components, as follows:</p> <ol style="list-style-type: none"> 1. Valves having both of the following: <ol style="list-style-type: none"> a. A 'nominal size' greater than 10 mm (3/8"); <u>and</u> b. All surfaces that come in direct contact with the chemical(s) being produced, processed, or contained are made from 'corrosion resistant materials'; 2. Valves, other than those specified in Category Code 2B350.g.1., having all of the following: <ol style="list-style-type: none"> a. A 'nominal size' equal to or greater than 25.4 mm (1") and equal to or less than 101.6 mm (4"); b. Casings (valve bodies) or preformed casing liners; c. A closure element designed to be interchangeable; <u>and</u> d. All surfaces of the casing (valve body) or preformed case liner that come in direct contact with the chemical(s) being produced, processed, or contained are made from 'corrosion resistant materials'; 3. Components, designed for valves specified in Category Code 2B350.g.1. or 2B350.g.2., in which all surfaces that come in direct contact with the chemical(s) being produced, processed, or contained are made from 'corrosion resistant materials', as follows: <ol style="list-style-type: none"> a. Casings (valve bodies); b. Preformed casing liners;

Category Code	Item Description
	<p data-bbox="413 325 608 354"><u>Technical Notes</u></p> <ol style="list-style-type: none"> <li data-bbox="413 367 1145 462">1. For the purpose of Category Code 2B350.g., 'corrosion resistant materials' means any of the following materials: <ol style="list-style-type: none"> <li data-bbox="498 483 1145 550">a. Nickel or alloys with more than 40% nickel by weight; <li data-bbox="498 567 1145 634">b. Alloys with more than 25% nickel and 20% chromium by weight; <li data-bbox="498 651 1145 746">c. Fluoropolymers (polymeric or elastomeric materials with more than 35% fluorine by weight); <li data-bbox="498 763 1145 830">d. Glass or glass-lined (including vitrified or enamelled coatings); <li data-bbox="498 847 911 875">e. Tantalum or tantalum alloys; <li data-bbox="498 894 897 923">f. Titanium or titanium alloys; <li data-bbox="498 942 934 971">g. Zirconium or zirconium alloys; <li data-bbox="498 990 1089 1018">h. Niobium (columbium) or niobium alloys; <u>or</u> <li data-bbox="498 1037 1145 1304">i. Ceramic materials as follows: <ol style="list-style-type: none"> <li data-bbox="565 1094 1145 1161">1. Silicon carbide with a purity of 80% or more by weight; <li data-bbox="565 1180 1145 1247">2. Aluminium oxide (alumina) with a purity of 99.9% or more by weight; <li data-bbox="565 1266 955 1294">3. Zirconium oxide (zirconia). <li data-bbox="413 1323 1145 1380">2. The 'nominal size' is defined as the smaller of the inlet and outlet diameters.

<i>Category Code</i>	<i>Item Description</i>
	<p>h. Multi-walled piping incorporating a leak detection port, in which all surfaces that come in direct contact with the chemical(s) being processed or contained are made from any of the following materials:</p> <ol style="list-style-type: none"> 1. 'Alloys' with more than 25% nickel and 20% chromium by weight; 2. Fluoropolymers (polymeric or elastomeric materials with more than 35% fluorine by weight); 3. Glass (including vitrified or enamelled coatings or glass lining); 4. Graphite or 'carbon graphite'; 5. Nickel or 'alloys' with more than 40% nickel by weight; 6. Tantalum or tantalum 'alloys'; 7. Titanium or titanium 'alloys'; 8. Zirconium or zirconium 'alloys'; <u>or</u> 9. Niobium (columbium) or niobium 'alloys'; <p>i. Multiple-seal and seal-less pumps, with manufacturer's specified maximum flow-rate greater than 0.6 m³/hour, or vacuum pumps with manufacturer's specified maximum flow-rate greater than 5 m³/hour (under standard temperature (273 K (0°C)) and pressure (101.3 kPa) conditions), other than those specified in Category Code 2B233; and casings (pump bodies), preformed casing liners, impellers, rotors or jet pump nozzles designed for such pumps, in which all surfaces that come in direct contact with the chemical(s) being processed are made from any of the following materials:</p> <ol style="list-style-type: none"> 1. 'Alloys' with more than 25% nickel and 20% chromium by weight; 2. Ceramics; 3. Ferrosilicon (high silicon iron alloys); 4. Fluoropolymers (polymeric or elastomeric materials with more than 35% fluorine by weight);

<i>Category Code</i>	<i>Item Description</i>
	<ol style="list-style-type: none"> 5. Glass (including vitrified or enamelled coatings or glass lining); 6. Graphite or ‘carbon graphite’; 7. Nickel or ‘alloys’ with more than 40% nickel by weight; 8. Tantalum or tantalum ‘alloys’; 9. Titanium or titanium ‘alloys’; 10. Zirconium or zirconium ‘alloys’; <u>or</u> 11. Niobium (columbium) or niobium ‘alloys’; <p><i><u>Technical Note</u></i> <i>In Category Code 2B350.i., the term seal refers to only those seals that come into direct contact with the chemical(s) being processed (or are designed to), and provide a sealing function where a rotary or reciprocating drive shaft passes through a pump body.</i></p> <p>j. Incinerators designed to destroy chemicals specified in Category Code 1C350, having specially designed waste supply systems, special handling facilities and an average combustion chamber temperature greater than 1,273 K (1,000°C), in which all surfaces in the waste supply system that come into direct contact with the waste products are made from or lined with any of the following materials:</p> <ol style="list-style-type: none"> 1. ‘Alloys’ with more than 25% nickel and 20% chromium by weight; 2. Ceramics; <u>or</u> 3. Nickel or ‘alloys’ with more than 40% nickel by weight. <p><i><u>Note</u></i> <i>For the purpose of Category Code 2B350, the materials used for gaskets, packing, seals, screws, washers or other materials performing a sealing function do not determine the control status, provided that such components are designed to be interchangeable.</i></p>

<i>Category Code</i>	<i>Item Description</i>
	<p><u>Technical Notes</u></p> <ol style="list-style-type: none"> 1. 'Carbon graphite' is a composition consisting of amorphous carbon and graphite, in which the graphite content is 8% or more by weight. 2. For the listed materials in the above entries, the term 'alloy' when not accompanied by a specific elemental concentration is understood as identifying those alloys where the identified metal is present in a higher percentage by weight than any other element.
2B351	<p>Toxic gas monitoring systems and their dedicated detecting components, other than those specified in Category Code 1A004, as follows; and detectors; sensor devices; and replaceable sensor cartridges therefor:</p> <ol style="list-style-type: none"> a. Designed for continuous operation and usable for the detection of chemical warfare agents or chemicals specified in Category Code 1C350, at concentrations of less than 0.3 mg/m³; <u>or</u> b. Designed for the detection of cholinesterase-inhibiting activity.
2B352	<p>Equipment capable of use in handling biological materials as follows:</p> <ol style="list-style-type: none"> a. Complete biological containment facilities at P3, P4 containment level; <p><u>Technical Note</u> <i>P3 or P4 (BL3, BL4, L3, L4) containment levels are as specified in the WHO Laboratory Biosafety manual (3rd edition, Geneva 2004).</i></p>

<i>Category Code</i>	<i>Item Description</i>
	<p>b. Fermenters and components as follows:</p> <ol style="list-style-type: none"> 1. Fermenters capable of cultivation of pathogenic “microorganisms” or of live cells, for the production of pathogenic viruses or toxins, without the propagation of aerosols, having a total capacity of 20 litres or more; 2. Components designed for fermenters in Category Code 2B352.b.1. as follows: <ol style="list-style-type: none"> a. Cultivation chambers designed to be sterilised or disinfected <i>in situ</i>; b. Cultivation chamber holding devices; c. Process control units capable of simultaneously monitoring and controlling two or more fermentation system parameters (e.g. temperature, pH, nutrients, agitation, dissolved oxygen, air flow, foam control); <p><u>Technical Note</u> <i>For the purpose of Category Code 2B352.b., fermenters include bioreactors, single-use (disposable) bioreactors, chemostats and continuous-flow systems.</i></p> <p>c. Centrifugal separators, capable of continuous separation without the propagation of aerosols, having all of the following characteristics:</p> <ol style="list-style-type: none"> 1. Flow-rate exceeding 100 litres per hour; 2. Components of polished stainless steel or titanium; 3. One or more sealing joints within the steam containment area; <u>and</u> 4. Capable of <i>in situ</i> steam sterilisation in a closed state; <p><u>Technical Note</u> <i>Centrifugal separators include decanters.</i></p>

<i>Category Code</i>	<i>Item Description</i>
	<p>d. Cross (tangential) flow filtration equipment and components as follows:</p> <ol style="list-style-type: none"> 1. Cross (tangential) flow filtration equipment capable of separation of pathogenic microorganisms, viruses, toxins or cell cultures having all of the following characteristics: <ol style="list-style-type: none"> a. A total filtration area equal to or greater than 1 m²; <u>and</u> b. Having any of the following characteristics: <ol style="list-style-type: none"> 1. Capable of being sterilised or disinfected <i>in situ</i>; <u>or</u> 2. Using disposable or single-use filtration components; <p><u>Technical Note</u> <i>In Category Code 2B352.d.1.b., sterilised denotes the elimination of all viable microbes from the equipment through the use of either physical (e.g. steam) or chemical agents. Disinfected denotes the destruction of potential microbial infectivity in the equipment through the use of chemical agents with a germicidal effect. Disinfection and sterilisation are distinct from sanitisation, the latter referring to cleaning procedures designed to lower the microbial content of equipment without necessarily achieving elimination of all microbial infectivity or viability.</i></p> <p><u>Note</u> <i>Category Code 2B352.d. does not include reverse osmosis equipment, as specified by the manufacturer.</i></p> <ol style="list-style-type: none"> 2. Cross (tangential) flow filtration components (e.g. modules, elements, cassettes, cartridges, units or plates) with filtration area equal to or greater than 0.2 m² for each component and designed for use in cross (tangential) flow filtration equipment specified in Category Code 2B352.d.;

Category Code	Item Description
	<p>e. Steam sterilisable freeze drying equipment with a condenser capacity exceeding 10 kg of ice in 24 hours and less than 1,000 kg of ice in 24 hours;</p> <p>f. Protective and containment equipment, as follows:</p> <ol style="list-style-type: none"> 1. Protective full or half suits, or hoods dependent upon a tethered external air supply and operating under positive pressure; <p><i>Note</i> <i>Category Code 2B352.f.1. does not include suits designed to be worn with self-contained breathing apparatus.</i></p> <ol style="list-style-type: none"> 2. Class III biological safety cabinets or isolators with similar performance standards; <p><i>Note</i> <i>In Category Code 2B352.f.2., isolators include flexible isolators, dry boxes, anaerobic chambers, glove boxes and laminar flow hoods (closed with vertical flow).</i></p> <p>g. Chambers designed for aerosol challenge testing with “microorganisms”, viruses or “toxins” and having a capacity of 1 m³ or greater.</p> <p>h. Spray drying equipment capable of drying toxins or pathogenic microorganisms having all of the following:</p> <ol style="list-style-type: none"> 1. A water evaporation capacity of ≥ 0.4 kg/h and ≤ 400 kg/h; 2. The ability to generate a typical mean product particle size of ≤ 10 μm with existing fittings or by minimal modification of the spray-dryer with atomisation nozzles enabling generation of the required particle size; <u>and</u> 3. Capable of being sterilised or disinfected <i>in situ</i>.
2C	<p>Materials</p> <p>None.</p>

<i>Category Code</i>	<i>Item Description</i>
2D	Software
2D001	<p>“Software”, other than that specified in Category Code 2D002, as follows:</p> <ol style="list-style-type: none"> a. “Software” specially designed or modified for the “development” or “production” of equipment specified in Category Code 2A001 or 2B001; b. “Software” specially designed or modified for the “use” of equipment specified in Category Code 2A001.c., 2B001 or 2B003 to 2B009. <p><u>Note</u> <i>Category Code 2D001 does not include part programming “software” that generates “numerical control” codes for machining various parts.</i></p>
2D002	<p>“Software” for electronic devices, even when residing in an electronic device or system, enabling such devices or systems to function as a “numerical control” unit, capable of coordinating simultaneously more than four axes for “contouring control”.</p> <p><u>Note 1</u> <i>Category Code 2D002 does not include “software” specially designed or modified for the operation of items not specified in Category 2.</i></p> <p><u>Note 2</u> <i>Category Code 2D002 does not include “software” for items specified in Category Code 2B002. See Category Codes 2D001 and 2D003 for “software” for items specified in Category Code 2B002.</i></p> <p><u>Note 3</u> <i>Category Code 2D002 does not include “software” that is exported with, and the minimum necessary for the operation of, items not specified in Category 2.</i></p>

<i>Category Code</i>	<i>Item Description</i>
2D003	“Software”, designed or modified for the operation of equipment specified in Category Code 2B002, that converts optical design, workpiece measurements and material removal functions into “numerical control” commands to achieve the desired workpiece form.
2D101	“Software” specially designed or modified for the “use” of equipment specified in Category Code 2B104, 2B105, 2B109, 2B116, 2B117 or 2B119 to 2B122. <i><u>N.B.</u></i> <i>See also Category Code 9D004.</i>
2D201	“Software” specially designed for the “use” of equipment specified in Category Code 2B204, 2B206, 2B207, 2B209, 2B219 or 2B227.
2D202	“Software” specially designed or modified for the “development”, “production” or “use” of equipment specified in Category Code 2B201. <i><u>Note</u></i> <i>Category Code 2D202 does not include part programming “software” that generates “numerical control” command codes but does not allow direct use of equipment for machining various parts.</i>
2D351	“Software”, other than that specified in Category Code 1D003, specially designed for the “use” of equipment specified in Category Code 2B351.

<i>Category Code</i>	<i>Item Description</i>
2E	Technology
2E001	<p>“Technology” (according to the General Technology Note) for the “development” of equipment or “software” specified in Category 2A, 2B or 2D.</p> <p><i>Note</i> <i>Category Code 2E001 includes “technology” for the integration of probe systems into coordinate measurement machines specified in Category Code 2B006.a.</i></p>
2E002	<p>“Technology” (according to the General Technology Note) for the “production” of equipment specified in Category 2A or 2B.</p>
2E003	<p>Other “technology” as follows:</p> <ol style="list-style-type: none"> a. “Technology” for the “development” of interactive graphics as an integrated part in “numerical control” units for preparation or modification of part programmes; b. “Technology” for metal-working manufacturing processes as follows: <ol style="list-style-type: none"> 1. “Technology” for the design of tools, dies or fixtures specially designed for any of the following processes: <ol style="list-style-type: none"> a. “Superplastic forming”; b. “Diffusion bonding”; <u>or</u> c. “Direct-acting hydraulic pressing”; 2. Technical data consisting of process methods or parameters as listed below used to control: <ol style="list-style-type: none"> a. “Superplastic forming” of aluminium alloys, titanium alloys or “superalloys”: <ol style="list-style-type: none"> 1. Surface preparation; 2. Strain rate; 3. Temperature; 4. Pressure;

<i>Category Code</i>	<i>Item Description</i>
	<p>b. “Diffusion bonding” of “superalloys” or titanium alloys:</p> <ol style="list-style-type: none"> 1. Surface preparation; 2. Temperature; 3. Pressure; <p>c. “Direct-acting hydraulic pressing” of aluminium alloys or titanium alloys:</p> <ol style="list-style-type: none"> 1. Pressure; 2. Cycle time; <p>d. “Hot isostatic densification” of titanium alloys, aluminium alloys or “superalloys”:</p> <ol style="list-style-type: none"> 1. Temperature; 2. Pressure; 3. Cycle time; <p>c. “Technology” for the “development” or “production” of hydraulic stretch-forming machines and dies therefor, for the manufacture of airframe structures;</p> <p>d. “Technology” for the “development” of generators of machine tool instructions (e.g. part programmes) from design data residing inside “numerical control” units;</p> <p>e. “Technology” for the “development” of integration “software” for incorporation of expert systems for advanced decision support of shop floor operations into “numerical control” units;</p> <p>f. “Technology” for the application of inorganic overlay coatings or inorganic surface modification coatings (specified in column 3 of the Table entitled Deposition Techniques) to non-electronic substrates (specified in column 2 of that Table), by processes specified in column 1 of that Table and defined in the Technical Note.</p> <p><u>Note</u> <i>The Table entitled Deposition Techniques and Technical Note appear after Category Code 2E301.</i></p>

Category Code	Item Description
	<p><u>N.B.</u></p> <p><i>This table should be read to specify the technology of a particular Coating Process only when the Resultant Coating in column 3 is in a paragraph directly across from the relevant Substrate under column 2. For example, Chemical Vapour Deposition (CVD) coating process technical data are included for the application of silicides to carbon-carbon, ceramic and metal “matrix” “composites” substrates, but are not included for the application of silicides to ‘cemented tungsten carbide’ (16), ‘silicon carbide’ (18) substrates. In the second case, the resultant coating is not listed in the paragraph under column 3 directly across from the paragraph under column 2 listing ‘cemented tungsten carbide’ (16), ‘silicon carbide’ (18).</i></p>
2E101	<p>“Technology” (according to the General Technology Note) for the “use” of equipment or “software” specified in Category Code 2B004, 2B009, 2B104, 2B109, 2B116, 2B119 to 2B122 or 2D101.</p>
2E201	<p>“Technology” (according to the General Technology Note) for the “use” of equipment or “software” specified in Category Code 2A225, 2A226, 2B001, 2B006, 2B007.b., 2B007.c., 2B008, 2B009, 2B201, 2B204, 2B206, 2B207, 2B209, 2B225 to 2B233, 2D201 or 2D202.</p>
2E301	<p>“Technology” (according to the General Technology Note) for the “use” of goods specified in Category Codes 2B350 to 2B352.</p>

TABLE – DEPOSITION TECHNIQUES

Notes

1. Bracketed numbers are explained in the Notes that appear after the table.
2. The coating processes under column 1 are further explained in the Technical Notes below.

1. Coating Process (1)	2. Substrate	3. Resultant Coating
A. Chemical Vapour Deposition (CVD)	<p>“Superalloys”</p> <p>Ceramics (19) and Low-expansion glasses (14)</p> <p>Carbon-carbon, Ceramic and Metal “matrix” “composites”</p> <p>Cemented tungsten carbide (16), Silicon carbide (18)</p> <p>Molybdenum and Molybdenum alloys</p> <p>Beryllium and Beryllium alloys</p>	<p>Aluminides for internal passages</p> <p>Silicides</p> <p>Carbides</p> <p>Dielectric layers (15)</p> <p>Diamond</p> <p>Diamond-like carbon (17)</p> <p>Silicides</p> <p>Carbides</p> <p>Refractory metals</p> <p>Mixtures thereof (4)</p> <p>Dielectric layers (15)</p> <p>Aluminides</p> <p>Alloyed aluminides (2)</p> <p>Boron nitride</p> <p>Carbides</p> <p>Tungsten</p> <p>Mixtures thereof (4)</p> <p>Dielectric layers (15)</p> <p>Dielectric layers (15)</p> <p>Dielectric layers (15)</p> <p>Diamond</p> <p>Diamond-like carbon (17)</p>

1. Coating Process (1)	2. Substrate	3. Resultant Coating
	Sensor window materials (9)	Dielectric layers (15) Diamond Diamond-like carbon (17)
<p>B. Thermal-Evaporation Physical Vapour Deposition (TE-PVD)</p> <p>B.1 Physical Vapour Deposition (PVD): Electron-Beam (EB-PVD)</p>	<p>“Superalloys”</p> <p>Ceramics (19) and Low-expansion glasses (14)</p> <p>Corrosion resistant steel (7)</p> <p>Carbon-carbon, Ceramic and Metal “matrix” “composites”</p> <p>Cemented tungsten carbide (16), Silicon carbide (18)</p>	<p>Alloyed silicides Alloyed aluminides (2) MCrAlX (5) Modified zirconia (12) Silicides Aluminides Mixtures thereof (4)</p> <p>Dielectric layers (15)</p> <p>MCrAlX (5) Modified zirconia (12) Mixtures thereof (4)</p> <p>Silicides Carbides Refractory metals Mixtures thereof (4) Dielectric layers (15) Boron nitride</p> <p>Carbides Tungsten Mixtures thereof (4) Dielectric layers (15)</p>

1. Coating Process (1)	2. Substrate	3. Resultant Coating
B.2 Ion assisted resistive heating Physical Vapour Deposition (PVD) (Ion Plating)	Molybdenum and Molybdenum alloys	Dielectric layers (15)
	Beryllium and Beryllium alloys	Dielectric layers (15) Borides Beryllium
	Sensor window materials (9)	Dielectric layers (15)
	Titanium alloys (13)	Borides Nitrides
	Ceramics (19) and Low- expansion glasses (14)	Dielectric layers (15) Diamond-like carbon (17)
	Carbon-carbon, Ceramic and Metal “matrix” “composites”	Dielectric layers (15)
	Cemented tungsten carbide (16), Silicon carbide	Dielectric layers (15)
	Molybdenum and Molybdenum alloys	Dielectric layers (15)
	Beryllium and Beryllium alloys	Dielectric layers (15)
Sensor window materials (9)	Dielectric layers (15) Diamond-like carbon (17)	

1. Coating Process (1)	2. Substrate	3. Resultant Coating
B.3 Physical Vapour Deposition (PVD): “Laser” Vaporisation	Ceramics (19) and Low-expansion glasses (14) Carbon-carbon, Ceramic and Metal “matrix” “composites” Cemented tungsten carbide (16), Silicon carbide Molybdenum and Molybdenum alloys Beryllium and Beryllium alloys Sensor window materials (9)	Silicides Dielectric layers (15) Diamond-like carbon (17) Dielectric layers (15) Dielectric layers (15) Dielectric layers (15) Dielectric layers (15) Diamond-like carbon (17)
B.4 Physical Vapour Deposition (PVD): Cathodic Arc Discharge	“Superalloys” Polymers (11) and Organic “matrix” “composites”	Alloyed silicides Alloyed aluminides (2) MCrAlX (5) Borides Carbides Nitrides Diamond-like carbon (17)

1. Coating Process (1)	2. Substrate	3. Resultant Coating
C. Pack cementation (See A above for out-of-pack cementation) (10)	Carbon-carbon, Ceramic and Metal “matrix” “composites” Titanium alloys (13) Refractory metals and alloys (8)	Silicides Carbides Mixtures thereof (4) Silicides Aluminides Alloyed aluminides (2) Silicides Oxides
D. Plasma spraying	“Superalloys” Aluminium alloys (6) Refractory metals and alloys (8) Corrosion resistant steel (7)	MCrAlX (5) Modified zirconia (12) Mixtures thereof (4) Abradable Nickel- Graphite Abradable materials containing Ni-Cr-Al Abradable Al-Si- Polyester Alloyed aluminides (2) MCrAlX (5) Modified zirconia (12) Silicides Mixtures thereof (4) Aluminides Silicides Carbides MCrAlX (5) Modified zirconia (12) Mixtures thereof (4)

1. Coating Process (1)	2. Substrate	3. Resultant Coating
	Titanium alloys (13)	Carbides Aluminides Silicides Alloyed aluminides (2) Abradable Nickel-Graphite Abradable materials containing Ni-Cr-Al Abradable Al-Si-Polyester
E. Slurry Deposition	Refractory metals and alloys (8) Carbon-carbon, Ceramic and Metal “matrix” “composites”	Fused silicides Fused aluminides except for resistance heating elements Silicides Carbides Mixtures thereof (4)
F. Sputter Deposition	“Superalloys” Ceramics and Low-expansion glasses (14)	Alloyed silicides Alloyed aluminides (2) Noble metal modified aluminides (3) MCrAlX (5) Modified zirconia (12) Platinum Mixtures thereof (4) Silicides Platinum Mixtures thereof (4) Dielectric layers (15) Diamond-like carbon (17)

1. Coating Process (1)	2. Substrate	3. Resultant Coating
	Titanium alloys (13)	Borides Nitrides Oxides Silicides Aluminides Alloyed aluminides (2) Carbides
	Carbon-carbon, Ceramic and Metal “matrix” “composites”	Silicides Carbides Refractory metals Mixtures thereof (4) Dielectric layers (15) Boron nitride
	Cemented tungsten carbide (16), Silicon carbide (18)	Carbides Tungsten Mixtures thereof (4) Dielectric layers (15) Boron nitride
	Molybdenum and Molybdenum alloys	Dielectric layers (15)
	Beryllium and Beryllium alloys	Borides Dielectric layers (15) Beryllium
	Sensor window materials (9)	Dielectric layers (15) Diamond-like carbon (17)
	Refractory metals and alloys (8)	Aluminides Silicides Oxides Carbides

1. Coating Process (1)	2. Substrate	3. Resultant Coating
G. Ion Implantation	High temperature bearing steels	Additions of Chromium Tantalum or Niobium (Columbium)
	Titanium alloys (13)	Borides Nitrides
	Beryllium and Beryllium alloys	Borides
	Cemented tungsten carbide (16)	Carbides Nitrides

TABLE — DEPOSITION TECHNIQUES — NOTES

1. The term ‘coating process’ includes coating repair and refurbishing as well as original coating.
2. The term ‘alloyed aluminide coating’ includes single or multiple-step coatings in which an element or elements are deposited prior to or during application of the aluminide coating, even if these elements are deposited by another coating process. It does not, however, include the multiple use of single-step pack cementation processes to achieve alloyed aluminides.
3. The term ‘noble metal modified aluminide’ coating includes multiple-step coatings in which the noble metal or noble metals are laid down by some other coating process prior to application of the aluminide coating.
4. The term ‘mixtures thereof’ includes infiltrated material, graded compositions, co-deposits and multilayer deposits and are obtained by one or more of the coating processes specified in the Table.
5. ‘MCrAlX’ refers to a coating alloy where M equals cobalt, iron, nickel or combinations thereof and X equals hafnium, yttrium, silicon, tantalum in any amount or other intentional additions over 0.01% by weight in various proportions and combinations, except:
 - a. CoCrAlY coatings which contain less than 22% by weight of chromium, less than 7% by weight of aluminium and less than 2% by weight of yttrium;
 - b. CoCrAlY coatings which contain 22% to 24% by weight of chromium, 10% to 12% by weight of aluminium and 0.5% to 0.7% by weight of yttrium; or

-
- c. NiCrAlY coatings which contain 21% to 23% by weight of chromium, 10% to 12% by weight of aluminium and 0.9% to 1.1% by weight of yttrium.
 6. The term ‘aluminium alloys’ refers to alloys having an ultimate tensile strength of 190 MPa or more measured at 293 K (20°C).
 7. The term ‘corrosion resistant steel’ refers to AISI (American Iron and Steel Institute) 300 series or equivalent national standard steels.
 8. ‘Refractory metals and alloys’ include the following metals and their alloys: niobium (columbium), molybdenum, tungsten and tantalum.
 9. ‘Sensor window materials’ as follows: alumina, silicon, germanium, zinc sulphide, zinc selenide, gallium arsenide, diamond, gallium phosphide, sapphire and the following metal halides: sensor window materials of more than 40 mm diameter for zirconium fluoride and hafnium fluoride.
 10. “Technology” for single-step pack cementation of solid airfoils is not included in Category 2.
 11. ‘Polymers’ as follows: polyimide, polyester, polysulphide, polycarbonates and polyurethanes.
 12. ‘Modified zirconia’ refers to additions of other metal oxides (e.g. calcia, magnesia, yttria, hafnia, rare earth oxides) to zirconia in order to stabilise certain crystallographic phases and phase compositions. Thermal barrier coatings made of zirconia, modified with calcia or magnesia by mixing or fusion, are not included.
 13. ‘Titanium alloys’ refers only to aerospace alloys having an ultimate tensile strength of 900 MPa or more measured at 293 K (20°C).
 14. ‘Low-expansion glasses’ refers to glasses which have a coefficient of thermal expansion of $1 \times 10^{-7} \text{ K}^{-1}$ or less measured at 293 K (20°C).
 15. ‘Dielectric layers’ are coatings constructed of multi-layers of insulator materials in which the interference properties of a design composed of materials of various refractive indices are used to reflect, transmit or absorb various wavelength bands. Dielectric layers refer to more than four dielectric layers or dielectric/metal “composite” layers.
 16. ‘Cemented tungsten carbide’ does not include cutting and forming tool materials consisting of tungsten carbide/(cobalt, nickel), titanium carbide/(cobalt, nickel), chromium carbide/nickel-chromium and chromium carbide/nickel.

-
-
17. “Technology” specially designed to deposit diamond-like carbon on any of the following is not included in Category 2:
magnetic disk drives and heads, equipment for the manufacture of disposables, valves for faucets, acoustic diaphragms for speakers, engine parts for automobiles, cutting tools, punching-pressing dies, office automation equipment, microphones or medical devices or moulds, for casting or moulding of plastics, manufactured from alloys containing less than 5% beryllium.
 18. ‘Silicon carbide’ does not include cutting and forming tool materials.
 19. Ceramic substrates, as used in this Table, does not include ceramic materials containing 5% by weight, or greater, clay or cement content, either as separate constituents or in combination.

TABLE — DEPOSITION TECHNIQUES — TECHNICAL NOTE

Processes specified in Column 1 of the Table are defined as follows:

- a. Chemical Vapour Deposition (CVD) is an overlay coating or surface modification coating process wherein a metal, alloy, “composite”, dielectric or ceramic is deposited upon a heated substrate. Gaseous reactants are decomposed or combined in the vicinity of a substrate resulting in the deposition of the desired elemental, alloy or compound material on the substrate. Energy for this decomposition or chemical reaction process may be provided by the heat of the substrate, a glow discharge plasma, or “laser” irradiation.

Note 1

CVD includes the following processes: directed gas flow out-of-pack deposition, pulsating CVD, controlled nucleation thermal deposition (CNTD), plasma enhanced or plasma assisted CVD processes.

Note 2

Pack denotes a substrate immersed in a powder mixture.

Note 3

The gaseous reactants used in the out-of-pack process are produced using the same basic reactions and parameters as the pack cementation process, except that the substrate to be coated is not in contact with the powder mixture.

- b. Thermal Evaporation-Physical Vapour Deposition (TE-PVD) is an overlay coating process conducted in a vacuum with a pressure less than 0.1 Pa wherein a source of thermal energy is used to vaporise the coating material. This process results in the condensation, or deposition, of the evaporated species onto appropriately positioned substrates.

The addition of gases to the vacuum chamber during the coating process to synthesise compound coatings is an ordinary modification of the process.

The use of ion or electron beams, or plasma, to activate or assist the coating's deposition is also a common modification in this technique. The use of monitors to provide in-process measurement of optical characteristics and thickness of coatings can be a feature of these processes.

Specific TE-PVD processes are as follows:

1. Electron Beam PVD uses an electron beam to heat and evaporate the material which forms the coating;
2. Ion Assisted Resistive Heating PVD employs electrically resistive heating sources in combination with impinging ion beam(s) to produce a controlled and uniform flux of evaporated coating species;
3. "Laser" Vaporisation uses either pulsed or continuous wave "laser" beams to vaporise the material which forms the coating;
4. Cathodic Arc Deposition employs a consumable cathode of the material which forms the coating and has an arc discharge established on the surface by a momentary contact of a ground trigger. Controlled motion of arcing erodes the cathode surface creating a highly ionised plasma. The anode can be either a cone attached to the periphery of the cathode, through an insulator, or the chamber. Substrate biasing is used for non-line-of-sight deposition.

Note

This definition does not include random cathodic arc deposition with non-biased substrates.

5. Ion Plating is a special modification of a general TE-PVD process in which a plasma or an ion source is used to ionise the species to be deposited, and a negative bias is applied to the substrate in order to facilitate the extraction of the species from the plasma. The introduction of reactive species, evaporation of solids within the process chamber, and the use of monitors to provide in-process measurement of optical characteristics and thicknesses of coatings are ordinary modifications of the process.

-
-
- c. Pack Cementation is a surface modification coating or overlay coating process wherein a substrate is immersed in a powder mixture (a pack), that consists of:
1. The metallic powders that are to be deposited (usually aluminium, chromium, silicon or combinations thereof);
 2. An activator (normally a halide salt); and
 3. An inert powder, most frequently alumina.

The substrate and powder mixture is contained within a retort which is heated to between 1,030 K (757°C) and 1,375 K (1,102°C) for sufficient time to deposit the coating.

- d. Plasma Spraying is an overlay coating process wherein a gun (spray torch) which produces and controls a plasma accepts powder or wire coating materials, melts them and propels them towards a substrate, whereon an integrally bonded coating is formed. Plasma spraying constitutes either low pressure plasma spraying or high velocity plasma spraying.

Note 1

Low pressure means less than ambient atmospheric pressure.

Note 2

High velocity refers to nozzle-exit gas velocity exceeding 750 m/s calculated at 293 K (20°C) at 0.1 MPa.

- e. Slurry Deposition is a surface modification coating or overlay coating process wherein a metallic or ceramic powder with an organic binder is suspended in a liquid and is applied to a substrate by either spraying, dipping or painting, subsequent air or oven drying, and heat treatment to obtain the desired coating.
- f. Sputter Deposition is an overlay coating process based on a momentum transfer phenomenon, wherein positive ions are accelerated by an electric field towards the surface of a target (coating material). The kinetic energy of the impacting ions is sufficient to cause target surface atoms to be released and deposited on an appropriately positioned substrate.

Note 1

The Table refers only to triode, magnetron or reactive sputter deposition which is used to increase adhesion of the coating and rate of deposition and to radio frequency (RF) augmented sputter deposition used to permit vaporisation of non-metallic coating materials.

Note 2

Low-energy ion beams (less than 5 keV) can be used to activate the deposition.

- g. Ion Implantation is a surface modification coating process in which the element to be alloyed is ionised, accelerated through a potential gradient and implanted into the surface region of the substrate. This includes processes in which ion implantation is performed simultaneously with electron beam physical vapour deposition or sputter deposition.

Category Code	Item Description
CATEGORY 3 — ELECTRONICS	
3A	<p>Systems, Equipment and Components</p> <p><u>Note 1</u> <i>Equipment and components described in Category Code 3A001 or 3A002, other than those described in Category Code 3A001.a.3. to 3A001.a.10., 3A001.a.12. or 3A001.a.13., which are specially designed for or which have the same functional characteristics as other equipment shall only be treated as coming within that description if that other equipment is included in Division 2 of this Part.</i></p> <p><u>Note 2</u> <i>Integrated circuits described in Category Code 3A001.a.3. to 3A001.a.9., 3A001.a.12. or 3A001.a.13., which are unalterably programmed or designed for a specific function for another equipment shall only be treated as coming within that description if that other equipment is included in Division 2 of this Part.</i></p> <p><u>N.B.</u> <i>Where it is unclear if the other equipment is included in Division 2 of this Part, then the integrated circuit is treated as falling within Category Code 3A001.a.3. to 3A001.a.9., 3A001.a.12. and 3A001.a.13. if it comes within the relevant description therein.</i></p>
3A001	<p>Electronic components and specially designed components therefor, as follows:</p> <p>a. General purpose integrated circuits, as follows:</p> <p><u>Note 1</u> <i>Category Code 3A001.a. includes wafers (finished or unfinished), in which the function has been determined, if it comes within the parameters set out therein.</i></p> <p><u>Note 2</u> <i>Integrated circuits include the following types:</i></p> <ul style="list-style-type: none"> – “Monolithic integrated circuits”; – “Hybrid integrated circuits”; – “Multichip integrated circuits”;

Category Code	Item Description
	<ul style="list-style-type: none"> – “Film type integrated circuits”, including silicon-on-sapphire integrated circuits; – “Optical integrated circuits”; – “Three dimensional integrated circuits”. <p>1. Integrated circuits designed or rated as radiation hardened to withstand any of the following:</p> <ul style="list-style-type: none"> a. A total dose of 5×10^3 Gy (silicon) or higher; b. A dose rate upset of 5×10^6 Gy (silicon)/s or higher; <u>or</u> c. A fluence (integrated flux) of neutrons (1 MeV equivalent) of 5×10^{13} n/cm² or higher on silicon, or its equivalent for other materials; <p style="text-align: center;"><u>Note</u> Category Code 3A001.a.1.c. does not include Metal Insulator Semiconductors (MIS).</p> <p>2. “Microprocessor microcircuits”, “microcomputer microcircuits”, microcontroller microcircuits, storage integrated circuits manufactured from a compound semiconductor, analogue-to-digital converters, digital-to-analogue converters, electro-optical or “optical integrated circuits” designed for “signal processing”, field programmable logic devices, custom integrated circuits for which either the function is unknown or the control status of the equipment in which the integrated circuit will be used is unknown, Fast Fourier Transform (FFT) processors, electrical erasable programmable read-only memories (EEPROMs), flash memories or static random-access memories (SRAMs), having any of the following:</p> <ul style="list-style-type: none"> a. Rated for operation at an ambient temperature above 398 K (125°C); b. Rated for operation at an ambient temperature below 218 K (-55°C); <u>or</u> c. Rated for operation over the entire ambient temperature range from 218 K (-55°C) to 398 K (125°C);

Category Code	Item Description
	<p data-bbox="481 325 538 354"><u>Note</u></p> <p data-bbox="481 367 1137 464"><i>Category Code 3A001.a.2. does not include integrated circuits for civil automobiles or railway train applications.</i></p> <p data-bbox="417 483 1137 616">3. “Microprocessor microcircuits”, “microcomputer microcircuits” and microcontroller microcircuits, manufactured from a compound semiconductor and operating at a clock frequency exceeding 40 MHz;</p> <p data-bbox="481 635 538 664"><u>Note</u></p> <p data-bbox="481 677 1137 774"><i>Category Code 3A001.a.3. includes digital signal processors, digital array processors and digital coprocessors.</i></p> <p data-bbox="417 793 596 822">4. Not used;</p> <p data-bbox="417 841 1137 938">5. Analogue-to-Digital Converter (ADC) and Digital-to-Analogue Converter (DAC) integrated circuits, as follows:</p> <p data-bbox="502 957 985 986">a. ADCs having any of the following:</p> <p data-bbox="565 1011 623 1039"><u>N.B.</u></p> <p data-bbox="565 1052 942 1081"><i>See also Category Code 3A101.</i></p> <ol data-bbox="565 1100 1137 1709" style="list-style-type: none"> <li data-bbox="565 1100 1137 1205">1. A resolution of 8 bit or more, but less than 10 bit, with an output rate greater than 1,000 million words per second; <li data-bbox="565 1224 1137 1328">2. A resolution of 10 bit or more, but less than 12 bit, with an output rate greater than 300 million words per second; <li data-bbox="565 1348 1137 1452">3. A resolution of 12 bit with an output rate greater than 200 million words per second; <li data-bbox="565 1471 1137 1595">4. A resolution of more than 12 bit, but equal to or less than 14 bit, with an output rate greater than 125 million words per second; <u>or</u> <li data-bbox="565 1614 1137 1709">5. A resolution of more than 14 bit with an output rate greater than 20 million words per second;

Category Code	Item Description
	<p data-bbox="565 325 760 357"><u>Technical Notes</u></p> <ol data-bbox="565 369 1139 1717" style="list-style-type: none"> <li data-bbox="565 369 1139 434">1. A resolution of n bit corresponds to a quantisation of 2^n levels. <li data-bbox="565 453 1139 517">2. The number of bits in the output word is equal to the resolution of the ADC. <li data-bbox="565 536 1139 635">3. The output rate is the maximum output rate of the converter, regardless of the architecture or oversampling. <li data-bbox="565 654 1139 784">4. For 'multiple channel ADCs', the outputs are not aggregated and the output rate is the maximum output rate of any single channel. <li data-bbox="565 803 1139 1005">5. For 'interleaved ADCs' or for 'multiple channel ADCs' that are specified to have an interleaved mode of operation, the outputs are aggregated and the output rate is the maximum combined total output rate of all of the outputs. <li data-bbox="565 1024 1139 1191">6. Vendors may also refer to the output rate as sampling rate, conversion rate or throughput rate. It is often specified in megahertz (MHz) or mega samples per second (MSPS). <li data-bbox="565 1210 1139 1309">7. For the purpose of measuring output rate, one output word per second is equivalent to one Hertz or one sample per second. <li data-bbox="565 1328 1139 1458">8. 'Multiple channel ADCs' are defined as devices which integrate more than one ADC, designed so that each ADC has a separate analogue input. <li data-bbox="565 1477 1139 1717">9. 'Interleaved ADCs' are defined as devices which have multiple ADC units that sample the same analogue input at different times such that when the outputs are aggregated, the analogue input has been effectively sampled and converted at a higher sampling rate.

<i>Category Code</i>	<i>Item Description</i>
	<p>b. Digital-to-Analogue Converters (DAC) having any of the following:</p> <ol style="list-style-type: none"> 1. A resolution of 10 bit or more with an ‘adjusted update rate’ of greater than 3,500 MSPS; <u>or</u> 2. A resolution of 12 bit or more with an ‘adjusted update rate’ of greater than 1,250 MSPS and having any of the following: <ol style="list-style-type: none"> a. A “settling time” less than 9 ns to 0.024% of full scale from a full scale step; <u>or</u> b. A ‘Spurious Free Dynamic Range’ (SFDR) greater than 68 dBc (carrier) when synthesising a full scale analogue signal of 100 MHz or the highest full scale analogue signal frequency specified below 100 MHz; <p><u>Technical Notes</u></p> <ol style="list-style-type: none"> 1. ‘Spurious Free Dynamic Range’ (SFDR) is defined as the ratio of the RMS value of the carrier frequency (maximum signal component) at the input of the DAC to the RMS value of the next largest noise or harmonic distortion component at its output. 2. SFDR is determined directly from the specification table or from the characterisation plots of SFDR versus frequency. 3. A signal is defined to be full scale when its amplitude is greater than -3 dBfs (full scale).

Category Code	Item Description
	<p data-bbox="568 325 1029 357">4. <i>'Adjusted update rate' for DACs:</i></p> <p data-bbox="633 376 1139 776">a. <i>For conventional (non-interpolating) DACs, the 'adjusted update rate' is the rate at which the digital signal is converted to an analogue signal and the output analogue values are changed by the DAC. For DACs where the interpolation mode may be bypassed (interpolation factor of one), the DAC should be considered as a conventional (non-interpolating) DAC.</i></p> <p data-bbox="633 795 1139 1068">b. <i>For interpolating DACs (oversampling DACs), the 'adjusted update rate' is defined as the DAC update rate divided by the smallest interpolating factor. For interpolating DACs, the 'adjusted update rate' may be referred to by different terms including:</i></p> <ul style="list-style-type: none"> <li data-bbox="696 1087 935 1119">– <i>input data rate</i> <li data-bbox="696 1138 942 1170">– <i>input word rate</i> <li data-bbox="696 1190 964 1222">– <i>input sample rate</i> <li data-bbox="696 1241 1110 1273">– <i>maximum total input bus rate</i> <li data-bbox="696 1292 1139 1353">– <i>maximum DAC clock rate for DAC clock input.</i> <p data-bbox="417 1372 1139 1467">6. <i>Electro-optical and "optical integrated circuits", designed for "signal processing" and having all of the following:</i></p> <ul style="list-style-type: none"> <li data-bbox="505 1487 1096 1519">a. <i>One or more than one internal "laser" diode;</i> <li data-bbox="505 1538 1139 1601">b. <i>One or more than one internal light detecting element; <u>and</u></i> <li data-bbox="505 1620 811 1652">c. <i>Optical waveguides;</i>

<i>Category Code</i>	<i>Item Description</i>
	<p>7. ‘Field programmable logic devices’ having any of the following:</p> <ol style="list-style-type: none"> a. A maximum number of single-ended digital inputs/outputs of greater than 700; <u>or</u> b. An ‘aggregate one-way peak serial transceiver data rate’ of 500 Gb/s or greater; <p><u>Note</u> <i>Category Code 3A001.a.7. includes:</i></p> <ul style="list-style-type: none"> – <i>Simple Programmable Logic Devices (SPLDs)</i> – <i>Complex Programmable Logic Devices (CPLDs)</i> – <i>Field Programmable Gate Arrays (FPGAs)</i> – <i>Field Programmable Logic Arrays (FPLAs)</i> – <i>Field Programmable Interconnects (FPICs)</i> <p><u>Technical Notes</u></p> <ol style="list-style-type: none"> 1. <i>Maximum number of digital inputs/outputs in Category Code 3A001.a.7.a. is also referred to as the maximum user inputs/outputs or maximum available inputs/outputs, whether the integrated circuit is packaged or bare die.</i> 2. <i>‘Aggregate one-way peak serial transceiver data rate’ is the product of the peak serial one-way transceiver data rate times the number of transceivers on the FPGA.</i> <p>8. Not used;</p> <p>9. Neural network integrated circuits;</p>

<i>Category Code</i>	<i>Item Description</i>
	<p>10. Custom integrated circuits for which the function is unknown, or the control status of the equipment in which the integrated circuits will be used is unknown to the manufacturer, having any of the following:</p> <ul style="list-style-type: none"> a. More than 1,500 terminals; b. A typical “basic gate propagation delay time” of less than 0.02 ns; <u>or</u> c. An operating frequency exceeding 3 GHz; <p>11. Digital integrated circuits, other than those described in Category Codes 3A001.a.3. to 3A001.a.10. and 3A001.a.12., based upon any compound semiconductor and having either of the following:</p> <ul style="list-style-type: none"> a. An equivalent gate count of more than 3,000 (2 input gates); <u>or</u> b. A toggle frequency exceeding 1.2 GHz; <p>12. Fast Fourier Transform (FFT) processors having a rated execution time for an N-point complex FFT of less than $(N \log_2 N)/20,480$ ms, where N is the number of points;</p> <p><i>Technical Note</i> <i>When N is equal to 1,024 points, the formula in Category Code 3A001.a.12. gives an execution time of 500 μs.</i></p> <p>13. Direct Digital Synthesizer (DDS) integrated circuits having any of the following:</p> <ul style="list-style-type: none"> a. A Digital-to-Analogue Converter (DAC) clock frequency of 3.5 GHz or more and a DAC resolution of 10 bit or more, but less than 12 bit; <u>or</u> b. A DAC clock frequency of 1.25 GHz or more and a DAC resolution of 12 bit or more; <p><i>Technical Note</i> <i>The DAC clock frequency may be specified as the master clock frequency or the input clock frequency.</i></p>

Category Code	Item Description
	<p>b. Microwave or millimetre wave components, as follows:</p> <p><u>Technical Note</u> <i>For the purpose of Category Code 3A001.b., the parameter peak saturated power output may also be referred to on product data sheets as output power, saturated power output, maximum power output, peak power output, or peak envelope power output.</i></p> <p>1. Electronic vacuum tubes and cathodes, as follows:</p> <p><u>Note 1</u> <i>Category Code 3A001.b.1. does not include tubes designed or rated for operation in any frequency band and having both of the following:</i></p> <p>a. <i>Does not exceed 31.8 GHz; <u>and</u></i></p> <p>b. <i>Is “allocated by the ITU” for radio-communications services, but not for radio-determination.</i></p> <p><u>Note 2</u> <i>Category Code 3A001.b.1. does not include non-“space-qualified” tubes having all of the following:</i></p> <p>a. <i>An average output power equal to or less than 50 W; <u>and</u></i></p> <p>b. <i>Designed or rated for operation in any frequency band and having all of the following:</i></p> <p>1. <i>Exceeds 31.8 GHz but does not exceed 43.5 GHz; <u>and</u></i></p> <p>2. <i>Is “allocated by the ITU” for radio-communications services, but not for radio-determination.</i></p> <p>a. Travelling wave tubes, pulsed or continuous wave, as follows:</p> <p>1. Tubes operating at frequencies exceeding 31.8 GHz;</p> <p>2. Tubes having a cathode heater element with a turn on time to rated RF power of less than 3 seconds;</p>

<i>Category Code</i>	<i>Item Description</i>
	<ol style="list-style-type: none"> <li data-bbox="565 325 1139 458">3. Coupled cavity tubes, or derivatives thereof, with a “fractional bandwidth” of more than 7% or a peak power exceeding 2.5 kW; <li data-bbox="565 477 1139 1201">4. Helix tubes, or derivatives thereof, having any of the following: <ol style="list-style-type: none"> <li data-bbox="626 563 1139 725">a. An “instantaneous bandwidth” of more than one octave, and average power (expressed in kW) times frequency (expressed in GHz) of more than 0.5; <li data-bbox="626 744 1139 915">b. An “instantaneous bandwidth” of one octave or less, and average power (expressed in kW) times frequency (expressed in GHz) of more than 1; <u>or</u> <li data-bbox="626 934 989 963">c. Being “space-qualified”; <li data-bbox="502 982 1139 1049">b. Crossed-field amplifier tubes with a gain of more than 17 dB; <li data-bbox="502 1068 1139 1201">c. Impregnated cathodes designed for electronic tubes producing a continuous emission current density at rated operating conditions exceeding 5 A/cm²; <ol style="list-style-type: none"> <li data-bbox="417 1220 1139 1742">2. Microwave “Monolithic Integrated Circuits” (MMIC) power amplifiers having any of the following: <ol style="list-style-type: none"> <li data-bbox="502 1306 1139 1439">a. Rated for operation at frequencies exceeding 2.7 GHz up to and including 6.8 GHz with a “fractional bandwidth” greater than 15%, and having any of the following: <ol style="list-style-type: none"> <li data-bbox="565 1458 1139 1591">1. A peak saturated power output greater than 75 W (48.75 dBm) at any frequency exceeding 2.7 GHz up to and including 2.9 GHz; <li data-bbox="565 1610 1139 1742">2. A peak saturated power output greater than 55 W (47.4 dBm) at any frequency exceeding 2.9 GHz up to and including 3.2 GHz;

<i>Category Code</i>	<i>Item Description</i>
	<ol style="list-style-type: none"> <li data-bbox="565 325 1137 458">3. A peak saturated power output greater than 40 W (46 dBm) at any frequency exceeding 3.2 GHz up to and including 3.7 GHz; <u>or</u> <li data-bbox="565 477 1137 611">4. A peak saturated power output greater than 20 W (43 dBm) at any frequency exceeding 3.7 GHz up to and including 6.8 GHz; <ol style="list-style-type: none"> <li data-bbox="502 630 1137 763">b. Rated for operation at frequencies exceeding 6.8 GHz up to and including 16 GHz with a “fractional bandwidth” greater than 10%, and having any of the following: <ol style="list-style-type: none"> <li data-bbox="565 782 1137 915">1. A peak saturated power output greater than 10 W (40 dBm) at any frequency exceeding 6.8 GHz up to and including 8.5 GHz; <u>or</u> <li data-bbox="565 934 1137 1068">2. A peak saturated power output greater than 5 W (37 dBm) at any frequency exceeding 8.5 GHz up to and including 16 GHz; <li data-bbox="502 1087 1137 1249">c. Rated for operation with a peak saturated power output greater than 3 W (34.77 dBm) at any frequency exceeding 16 GHz up to and including 31.8 GHz, and with a “fractional bandwidth” of greater than 10%; <li data-bbox="502 1268 1137 1410">d. Rated for operation with a peak saturated power output greater than 0.1 nW (-70 dBm) at any frequency exceeding 31.8 GHz up to and including 37 GHz; <li data-bbox="502 1429 1137 1591">e. Rated for operation with a peak saturated power output greater than 1 W (30 dBm) at any frequency exceeding 37 GHz up to and including 43.5 GHz, and with a “fractional bandwidth” of greater than 10%;

Category Code	Item Description
	<p>f. Rated for operation with a peak saturated power output greater than 31.62 mW (15 dBm) at any frequency exceeding 43.5 GHz up to and including 75 GHz, and with a “fractional bandwidth” of greater than 10%;</p> <p>g. Rated for operation with a peak saturated power output greater than 10 mW (10 dBm) at any frequency exceeding 75 GHz up to and including 90 GHz, and with a “fractional bandwidth” of greater than 5%; <u>or</u></p> <p>h. Rated for operation with a peak saturated power output greater than 0.1 nW (-70 dBm) at any frequency exceeding 90 GHz;</p> <p><u>Note 1</u> Not used.</p> <p><u>Note 2</u> <i>Whether any MMIC whose rated operating frequency includes frequencies listed in more than one frequency range, as defined by Category Codes 3A001.b.2.a. to 3A001.b.2.h., is included in that Category is determined by the lowest peak saturated power output threshold.</i></p> <p><u>Note 3</u> <i>Notes 1 and 2 in Category 3A mean that Category Code 3A001.b.2. does not include MMICs if they are specially designed for other applications, e.g. telecommunications, radar, automobiles.</i></p> <p>3. Discrete microwave transistors having any of the following:</p> <p>a. Rated for operation at frequencies exceeding 2.7 GHz up to and including 6.8 GHz and having any of the following:</p> <p>1. A peak saturated power output greater than 400 W (56 dBm) at any frequency exceeding 2.7 GHz up to and including 2.9 GHz;</p>

<i>Category Code</i>	<i>Item Description</i>
	<ol style="list-style-type: none"> <li data-bbox="565 325 1137 453">2. A peak saturated power output greater than 205 W (53.12 dBm) at any frequency exceeding 2.9 GHz up to and including 3.2 GHz; <li data-bbox="565 477 1137 605">3. A peak saturated power output greater than 115 W (50.61 dBm) at any frequency exceeding 3.2 GHz up to and including 3.7 GHz; <u>or</u> <li data-bbox="565 630 1137 757">4. A peak saturated power output greater than 60 W (47.78 dBm) at any frequency exceeding 3.7 GHz up to and including 6.8 GHz; <p data-bbox="502 782 1137 877">b. Rated for operation at frequencies exceeding 6.8 GHz up to and including 31.8 GHz and having any of the following:</p> <ol style="list-style-type: none"> <li data-bbox="565 902 1137 1030">1. A peak saturated power output greater than 50 W (47 dBm) at any frequency exceeding 6.8 GHz up to and including 8.5 GHz; <li data-bbox="565 1054 1137 1182">2. A peak saturated power output greater than 15 W (41.76 dBm) at any frequency exceeding 8.5 GHz up to and including 12 GHz; <li data-bbox="565 1207 1137 1334">3. A peak saturated power output greater than 40 W (46 dBm) at any frequency exceeding 12 GHz up to and including 16 GHz; <u>or</u> <li data-bbox="565 1359 1137 1487">4. A peak saturated power output greater than 7 W (38.45 dBm) at any frequency exceeding 16 GHz up to and including 31.8 GHz; <p data-bbox="502 1511 1137 1639">c. Rated for operation with a peak saturated power output greater than 0.5 W (27 dBm) at any frequency exceeding 31.8 GHz up to and including 37 GHz;</p>

Category Code	Item Description
	<p>d. Rated for operation with a peak saturated power output greater than 1 W (30 dBm) at any frequency exceeding 37 GHz up to and including 43.5 GHz; <u>or</u></p> <p>e. Rated for operation with a peak saturated power output greater than 0.1 nW (-70 dBm) at any frequency exceeding 43.5 GHz;</p> <p><u>Note 1</u> <i>Whether a transistor whose rated operating frequency includes frequencies listed in more than one frequency range, as defined by Category Codes 3A001.b.3.a. to 3A001.b.3.e., is included under that Category is determined by the lowest peak saturated power output threshold.</i></p> <p><u>Note 2</u> <i>Category Code 3A001.b.3. includes bare dice, dice mounted on carriers, or dice mounted in packages. Some discrete transistors may also be referred to as power amplifiers, but the status of these discrete transistors is determined by Category Code 3A001.b.3.</i></p> <p>4. Microwave solid state amplifiers and microwave assemblies/modules containing microwave solid state amplifiers, that are any of the following:</p> <p>a. Rated for operation at frequencies exceeding 2.7 GHz up to and including 6.8 GHz with a “fractional bandwidth” greater than 15%, and having any of the following:</p> <ol style="list-style-type: none"> 1. A peak saturated power output greater than 500 W (57 dBm) at any frequency exceeding 2.7 GHz up to and including 2.9 GHz; 2. A peak saturated power output greater than 270 W (54.3 dBm) at any frequency exceeding 2.9 GHz up to and including 3.2 GHz;

<i>Category Code</i>	<i>Item Description</i>
	<ol style="list-style-type: none"> <li data-bbox="565 325 1137 458">3. A peak saturated power output greater than 200 W (53 dBm) at any frequency exceeding 3.2 GHz up to and including 3.7 GHz; <u>or</u> <li data-bbox="565 477 1137 611">4. A peak saturated power output greater than 90 W (49.54 dBm) at any frequency exceeding 3.7 GHz up to and including 6.8 GHz; <p data-bbox="502 630 1137 763">b. Rated for operation at frequencies exceeding 6.8 GHz up to and including 31.8 GHz with a “fractional bandwidth” greater than 10%, and having any of the following:</p> <ol style="list-style-type: none"> <li data-bbox="565 782 1137 915">1. A peak saturated power output greater than 70 W (48.54 dBm) at any frequency exceeding 6.8 GHz up to and including 8.5 GHz; <li data-bbox="565 934 1137 1068">2. A peak saturated power output greater than 50 W (47 dBm) at any frequency exceeding 8.5 GHz up to and including 12 GHz; <li data-bbox="565 1087 1137 1220">3. A peak saturated power output greater than 30 W (44.77 dBm) at any frequency exceeding 12 GHz up to and including 16 GHz; <u>or</u> <li data-bbox="565 1239 1137 1372">4. A peak saturated power output greater than 20 W (43 dBm) at any frequency exceeding 16 GHz up to and including 31.8 GHz; <p data-bbox="502 1391 1137 1525">c. Rated for operation with a peak saturated power output greater than 0.5 W (27 dBm) at any frequency exceeding 31.8 GHz up to and including 37 GHz;</p> <p data-bbox="502 1544 1137 1709">d. Rated for operation with a peak saturated power output greater than 2 W (33 dBm) at any frequency exceeding 37 GHz up to and including 43.5 GHz, and with a “fractional bandwidth” of greater than 10%;</p>

Category Code	Item Description
	<p>e. Rated for operation at frequencies exceeding 43.5 GHz and having any of the following:</p> <ol style="list-style-type: none"> 1. A peak saturated power output greater than 0.2 W (23 dBm) at any frequency exceeding 43.5 GHz up to and including 75 GHz, and with a “fractional bandwidth” of greater than 10%; 2. A peak saturated power output greater than 20 mW (13 dBm) at any frequency exceeding 75 GHz up to and including 90 GHz, and with a “fractional bandwidth” of greater than 5%; <u>or</u> 3. A peak saturated power output greater than 0.1 nW (-70 dBm) at any frequency exceeding 90 GHz; <u>or</u> <p>f. Rated for operation at frequencies above 2.7 GHz and having all of the following:</p> <ol style="list-style-type: none"> 1. A peak saturation power (in watts), P_{sat}, greater than 400 divided by the maximum operating frequency (in GHz) squared [$P_{\text{sat}} > 400 \text{ W} \cdot \text{GHz}^2 / f_{\text{GHz}}^2$]; 2. A “fractional bandwidth” of 5% or greater; <u>and</u> 3. Any two sides perpendicular to one another with either length d (in cm) equal to or less than 15 divided by the lowest operating frequency in GHz [$d \leq 15 \text{ cm} \cdot \text{GHz} / f_{\text{GHz}}$]; <p><i>Technical Note</i></p> <p><i>2.7 GHz should be used as the lowest operating frequency (f_{GHz}) in the formula in Category Code 3A001.b.4.f.3., for amplifiers that have a rated operating range extending downward to 2.7 GHz and below [$d \leq 15 \text{ cm} \cdot \text{GHz} / 2.7 \text{ GHz}$].</i></p>

Category Code	Item Description
	<p data-bbox="481 325 534 354"><u>N.B.</u></p> <p data-bbox="481 367 1137 430"><i>MMIC power amplifiers should be evaluated against the criteria in Category Code 3A001.b.2.</i></p> <p data-bbox="481 453 561 481"><u>Note 1</u></p> <p data-bbox="481 495 592 523"><i>Not used.</i></p> <p data-bbox="481 546 561 575"><u>Note 2</u></p> <p data-bbox="481 588 1137 782"><i>Whether an item whose rated operating frequency includes frequencies listed in more than one frequency range, as defined by Category Codes 3A001.b.4.a. to 3A001.b.4.e., is included in that Category is determined by the lowest peak saturation output threshold.</i></p> <p data-bbox="481 805 561 833"><u>Note 3</u></p> <p data-bbox="481 847 1137 910"><i>Category Code 3A001.b.4. includes transmit/receive modules and transmit modules.</i></p> <p data-bbox="417 932 1137 1096">5. Electronically or magnetically tunable band-pass or band-stop filters, having more than 5 tunable resonators capable of tuning across 1.5:1 frequency band (f_{\max}/f_{\min}) in less than 10 μs and having any of the following:</p> <ul style="list-style-type: none"> <li data-bbox="502 1119 1137 1182">a. A band-pass bandwidth of more than 0.5% of centre frequency; <u>or</u> <li data-bbox="502 1205 1137 1268">b. A band-stop bandwidth of less than 0.5% of centre frequency; <p data-bbox="417 1290 592 1319">6. Not used;</p> <p data-bbox="417 1342 1137 1405">7. Converters and harmonic mixers that are any of the following:</p> <ul style="list-style-type: none"> <li data-bbox="502 1428 1137 1490">a. Designed to extend the frequency range of “signal analysers” beyond 90 GHz;

<i>Category Code</i>	<i>Item Description</i>
	<p>b. Designed to extend the operating range of signal generators as follows:</p> <ol style="list-style-type: none"> 1. Beyond 90 GHz; 2. To an output power greater than 100 mW (20 dBm) anywhere within the frequency range exceeding 43.5 GHz but not exceeding 90 GHz; <p>c. Designed to extend the operating range of network analysers as follows:</p> <ol style="list-style-type: none"> 1. Beyond 110 GHz; 2. To an output power greater than 31.62 mW (15 dBm) anywhere within the frequency range exceeding 43.5 GHz but not exceeding 90 GHz; 3. To an output power greater than 1 mW (0 dBm) anywhere within the frequency range exceeding 90 GHz but not exceeding 110 GHz; <u>or</u> <p>d. Designed to extend the frequency range of microwave test receivers beyond 110 GHz;</p> <p>8. Microwave power amplifiers containing tubes specified in Category Code 3A001.b.1. and having all of the following:</p> <ol style="list-style-type: none"> a. Operating frequencies above 3 GHz; b. An average output power to mass ratio exceeding 80 W/kg; <u>and</u> c. A volume of less than 400 cm³; <p><u>Note</u> <i>Category Code 3A001.b.8. does not include equipment designed or rated for operation in any frequency band which is "allocated by the ITU" for radio-communications services, but not for radio-determination.</i></p>

<i>Category Code</i>	<i>Item Description</i>
	<p>9. Microwave power modules (MPM), consisting of, at least, a travelling wave tube, a microwave “monolithic integrated circuit” and an integrated electronic power conditioner and having all of the following:</p> <ol style="list-style-type: none"> a. A ‘turn-on time’ from off to fully operational in less than 10 seconds; b. A volume less than the maximum rated power in watts multiplied by 10 cm³/W; <u>and</u> c. An “instantaneous bandwidth” greater than 1 octave ($f_{\max} > 2f_{\min}$) and having any of the following: <ol style="list-style-type: none"> 1. For frequencies equal to or less than 18 GHz, an RF output power greater than 100 W; <u>or</u> 2. A frequency greater than 18 GHz; <p><u>Technical Notes</u></p> <ol style="list-style-type: none"> 1. To calculate the volume in Category Code 3A001.b.9.b., the following example is provided: for a maximum rated power of 20 W, the volume would be: $20\text{ W} \times 10\text{ cm}^3/\text{W} = 200\text{ cm}^3$. 2. The ‘turn-on time’ in Category Code 3A001.b.9.a. refers to the time from fully-off to fully operational, i.e. it includes the warm-up time of the MPM. <p>10. Oscillators or oscillator assemblies, specified to operate with a single sideband (SSB) phase noise, in dBc/Hz, less (better) than $-(126 + 20\log_{10}F - 20\log_{10}f)$ anywhere within the range of $10\text{ Hz} \leq F \leq 10\text{ kHz}$;</p> <p><u>Technical Note</u></p> <p>In Category Code 3A001.b.10., F is the offset from the operating frequency in Hz and f is the operating frequency in MHz.</p>

<i>Category Code</i>	<i>Item Description</i>
	<p>11. “Frequency synthesiser” “electronic assemblies” having a “frequency switching time” as specified by any of the following:</p> <ol style="list-style-type: none"> a. Less than 156 ps; b. Less than 100 μs for any frequency change exceeding 1.6 GHz within the synthesised frequency range exceeding 4.8 GHz but not exceeding 10.6 GHz; c. Less than 250 μs for any frequency change exceeding 550 MHz within the synthesised frequency range exceeding 10.6 GHz but not exceeding 31.8 GHz; d. Less than 500 μs for any frequency change exceeding 550 MHz within the synthesised frequency range exceeding 31.8 GHz but not exceeding 43.5 GHz; e. Less than 1 ms for any frequency change exceeding 550 MHz within the synthesised frequency range exceeding 43.5 GHz but not exceeding 56 GHz; f. Less than 1 ms for any frequency change exceeding 2.2 GHz within the synthesised frequency range exceeding 56 GHz but not exceeding 90 GHz; <u>or</u> g. Less than 1 ms within the synthesised frequency range exceeding 90 GHz; <p><u>N.B.</u> <i>For general purpose “signal analysers”, signal generators, network analysers and microwave test receivers, see Category Codes 3A002.c., 3A002.d., 3A002.e. and 3A002.f., respectively.</i></p>

<i>Category Code</i>	<i>Item Description</i>
	<p>c. Acoustic wave devices as follows and specially designed components therefor:</p> <ol style="list-style-type: none"> 1. Surface acoustic wave and surface skimming (shallow bulk) acoustic wave devices, having any of the following: <ol style="list-style-type: none"> a. A carrier frequency exceeding 6 GHz; b. A carrier frequency exceeding 1 GHz, but not exceeding 6 GHz, and having any of the following: <ol style="list-style-type: none"> 1. A ‘frequency side-lobe rejection’ exceeding 65 dB; 2. A product of the maximum delay time and the bandwidth (time in μs and bandwidth in MHz) of more than 100; 3. A bandwidth greater than 250 MHz; <u>or</u> 4. A dispersive delay of more than 10 μs; <u>or</u> c. A carrier frequency of 1 GHz or less and having any of the following: <ol style="list-style-type: none"> 1. A product of the maximum delay time and the bandwidth (time in μs and bandwidth in MHz) of more than 100; 2. A dispersive delay of more than 10 μs; <u>or</u> 3. A ‘frequency side-lobe rejection’ exceeding 65 dB and a bandwidth greater than 100 MHz; <p><i>Technical Note</i> ‘Frequency side-lobe rejection’ is the maximum rejection value specified in data sheet.</p> <ol style="list-style-type: none"> 2. Bulk (volume) acoustic wave devices which permit the direct processing of signals at frequencies exceeding 6 GHz;

<i>Category Code</i>	<i>Item Description</i>
	<p data-bbox="417 325 1139 491">3. Acoustic-optic “signal processing” devices employing interaction between acoustic waves (bulk wave or surface wave) and light waves which permit the direct processing of signals or images, including spectral analysis, correlation or convolution;</p> <p data-bbox="417 510 478 538"><u>Note</u></p> <p data-bbox="417 554 1139 649"><i>Category Code 3A001.c. does not include acoustic wave devices that are limited to a single band pass, low pass, high pass or notch filtering, or resonating function.</i></p> <p data-bbox="354 668 1139 833">d. Electronic devices and circuits containing components, manufactured from “superconductive” materials, specially designed for operation at temperatures below the “critical temperature” of at least one of the “superconductive” constituents and having any of the following:</p> <ol data-bbox="417 852 1139 1071" style="list-style-type: none"> 1. Current switching for digital circuits using “superconductive” gates with a product of delay time per gate (in seconds) and power dissipation per gate (in watts) of less than 10^{-14} J; <u>or</u> 2. Frequency selection at all frequencies using resonant circuits with Q-values exceeding 10,000; <p data-bbox="354 1090 807 1119">e. High energy devices, as follows:</p> <ol data-bbox="417 1138 1139 1338" style="list-style-type: none"> 1. ‘Cells’, as follows: <ol data-bbox="502 1186 1139 1338" style="list-style-type: none"> a. ‘Primary cells’ having an ‘energy density’ exceeding 550 Wh/kg at 20°C; b. ‘Secondary cells’ having an ‘energy density’ exceeding 300 Wh/kg at 20°C; <p data-bbox="481 1357 676 1386"><u>Technical Notes</u></p> <ol data-bbox="502 1405 1139 1734" style="list-style-type: none"> 1. <i>For the purpose of Category Code 3A001.e.1., ‘energy density’ (Wh/kg) is calculated from the nominal voltage multiplied by the nominal capacity in ampere-hours (Ah) divided by the mass in kilograms. If the nominal capacity is not stated, energy density is calculated from the nominal voltage squared then multiplied by the discharge duration in hours divided by the discharge load in ohms and the mass in kilograms.</i>

Category Code	Item Description
	<p data-bbox="502 325 1137 491">2. For the purpose of Category Code 3A001.e.1., a 'cell' is defined as an electrochemical device, which has positive and negative electrodes, an electrolyte, and is a source of electrical energy. It is the basic building block of a battery.</p> <p data-bbox="502 510 1137 639">3. For the purpose of Category Code 3A001.e.1.a., a 'primary cell' is a 'cell' that is not designed to be charged by any other source.</p> <p data-bbox="502 658 1137 788">4. For the purpose of Category Code 3A001.e.1.b., a 'secondary cell' is a 'cell' that is designed to be charged by an external electrical source.</p> <p data-bbox="481 814 538 843"><u>Note</u></p> <p data-bbox="481 852 1137 919">Category Code 3A001.e.1. does not include batteries, including single-cell batteries.</p> <p data-bbox="417 938 993 967">2. High energy storage capacitors, as follows:</p> <p data-bbox="481 991 534 1020"><u>N.B.</u></p> <p data-bbox="481 1030 1137 1096">See also Category Code 3A201.a. and Division 2 of Part 1 of this Schedule.</p> <p data-bbox="502 1115 1137 1210">a. Capacitors with a repetition rate of less than 10 Hz (single shot capacitors) and having all of the following:</p> <ol data-bbox="565 1229 1137 1467" style="list-style-type: none"> <li data-bbox="565 1229 1137 1296">1. A voltage rating equal to or more than 5 kV; <li data-bbox="565 1315 1137 1382">2. An energy density equal to or more than 250 J/kg; <u>and</u> <li data-bbox="565 1401 1137 1467">3. A total energy equal to or more than 25 kJ; <p data-bbox="502 1487 1137 1582">b. Capacitors with a repetition rate of 10 Hz or more (repetition rated capacitors) and having all of the following:</p> <ol data-bbox="565 1601 1137 1744" style="list-style-type: none"> <li data-bbox="565 1601 1137 1667">1. A voltage rating equal to or more than 5 kV; <li data-bbox="565 1686 1137 1744">2. An energy density equal to or more than 50 J/kg;

Category Code	Item Description
	<p data-bbox="565 325 1139 392">3. A total energy equal to or more than 100 J; <u>and</u></p> <p data-bbox="565 407 1139 474">4. A charge/discharge cycle life equal to or more than 10,000;</p> <p data-bbox="417 489 1139 592">3. “Superconductive” electromagnets and solenoids, specially designed to be fully charged or discharged in less than one second and having all of the following:</p> <p data-bbox="481 609 538 639"><u>N.B.</u></p> <p data-bbox="481 653 881 683">See also Category Code 3A201.b.</p> <p data-bbox="481 700 542 731"><u>Note</u></p> <p data-bbox="481 744 1139 877">Category Code 3A001.e.3. does not include “superconductive” electromagnets or solenoids specially designed for Magnetic Resonance Imaging (MRI) medical equipment.</p> <p data-bbox="502 894 1139 961">a. Energy delivered during the discharge exceeding 10 kJ in the first second;</p> <p data-bbox="502 978 1139 1045">b. Inner diameter of the current carrying windings of more than 250 mm; <u>and</u></p> <p data-bbox="502 1062 1139 1165">c. Rated for a magnetic induction of more than 8 T or “overall current density” in the winding of more than 300 A/mm²;</p> <p data-bbox="417 1182 1139 1420">4. Solar cells, cell-interconnect-coverglass (CIC) assemblies, solar panels, and solar arrays, which are “space-qualified”, having a minimum average efficiency exceeding 20% at an operating temperature of 301 K (28°C) under simulated ‘AM0’ illumination with an irradiance of 1,367 watts per square metre (W/m²);</p> <p data-bbox="481 1437 666 1467"><u>Technical Note</u></p> <p data-bbox="481 1481 1139 1614">‘AM0’, or ‘Air Mass Zero’, refers to the spectral irradiance of sun light in the earth's outer atmosphere when the distance between the earth and sun is one astronomical unit (AU).</p> <p data-bbox="354 1631 1139 1698">f. Rotary input type absolute position encoders having an accuracy equal to or less (better) than ±1 second of arc;</p>

<i>Category Code</i>	<i>Item Description</i>
	<p data-bbox="350 325 1137 458">g. Solid-state pulsed power switching thyristor devices and ‘thyristor modules’, using either electrically, optically, or electron radiation controlled switch methods and having any of the following:</p> <ol data-bbox="417 477 1137 830" style="list-style-type: none"> <li data-bbox="417 477 1137 582">1. A maximum turn-on current rate of rise (di/dt) greater than 30,000 A/μs and off-state voltage greater than 1,100 V; <u>or</u> <li data-bbox="417 592 1137 830">2. A maximum turn-on current rate of rise (di/dt) greater than 2,000 A/μs and having both of the following: <ol data-bbox="498 677 1137 830" style="list-style-type: none"> <li data-bbox="498 677 1137 753">a. An off-state peak voltage equal to or greater than 3,000 V; <u>and</u> <li data-bbox="498 763 1137 830">b. A peak (surge) current equal to or greater than 3,000 A; <p data-bbox="417 849 498 877"><u>Note 1</u></p> <p data-bbox="417 887 827 915"><i>Category Code 3A001.g. includes:</i></p> <ul data-bbox="417 934 1063 1268" style="list-style-type: none"> <li data-bbox="417 934 908 963">– <i>Silicon Controlled Rectifiers (SCRs)</i> <li data-bbox="417 982 948 1011">– <i>Electrical Triggering Thyristors (ETTs)</i> <li data-bbox="417 1030 895 1058">– <i>Light Triggering Thyristors (LTTs)</i> <li data-bbox="417 1077 1063 1106">– <i>Integrated Gate Commutated Thyristors (IGCTs)</i> <li data-bbox="417 1125 868 1153">– <i>Gate Turn-off Thyristors (GTOs)</i> <li data-bbox="417 1172 908 1201">– <i>MOS Controlled Thyristors (MCTs)</i> <li data-bbox="417 1220 599 1249">– <i>Solidtrons</i> <p data-bbox="417 1287 498 1315"><u>Note 2</u></p> <p data-bbox="417 1325 1137 1429"><i>Category Code 3A001.g. does not include thyristor devices and ‘thyristor modules’ incorporated into equipment designed for civil railway or “civil aircraft” applications.</i></p> <p data-bbox="417 1448 599 1477"><u>Technical Note</u></p> <p data-bbox="417 1487 1137 1557"><i>For the purpose of Category Code 3A001.g., a ‘thyristor module’ contains one or more thyristor devices.</i></p>

Category Code	Item Description
	<p data-bbox="353 325 1139 392">h. Solid-state power semiconductor switches, diodes, or ‘modules’, having all of the following:</p> <ol data-bbox="417 407 1139 611" style="list-style-type: none"> <li data-bbox="417 407 1139 477">1. Rated for a maximum operating junction temperature greater than 488 K (215°C); <li data-bbox="417 493 1139 563">2. Repetitive peak off-state voltage (blocking voltage) exceeding 300 V; <u>and</u> <li data-bbox="417 578 919 611">3. Continuous current greater than 1 A. <p data-bbox="417 628 498 660"><u>Note 1</u></p> <p data-bbox="417 670 1139 805"><i>Repetitive peak off-state voltage in Category Code 3A001.h. includes drain to source voltage, collector to emitter voltage, repetitive peak reverse voltage and peak repetitive off-state blocking voltage.</i></p> <p data-bbox="417 822 498 854"><u>Note 2</u></p> <p data-bbox="417 864 830 896"><i>Category Code 3A001.h. includes:</i></p> <ul data-bbox="417 913 1139 1566" style="list-style-type: none"> <li data-bbox="417 913 978 946">– <i>Junction Field Effect Transistors (JFETs)</i> <li data-bbox="417 963 1099 995">– <i>Vertical Junction Field Effect Transistors (VJFETs)</i> <li data-bbox="417 1012 1139 1083">– <i>Metal Oxide Semiconductor Field Effect Transistors (MOSFETs)</i> <li data-bbox="417 1100 1139 1170">– <i>Double Diffused Metal Oxide Semiconductor Field Effect Transistor (DMOSFET)</i> <li data-bbox="417 1188 978 1220">– <i>Insulated Gate Bipolar Transistor (IGBT)</i> <li data-bbox="417 1237 1022 1269">– <i>High Electron Mobility Transistors (HEMTs)</i> <li data-bbox="417 1287 911 1319">– <i>Bipolar Junction Transistors (BJTs)</i> <li data-bbox="417 1336 1095 1368">– <i>Thyristors and Silicon Controlled Rectifiers (SCRs)</i> <li data-bbox="417 1386 878 1418">– <i>Gate Turn-Off Thyristors (GTOs)</i> <li data-bbox="417 1435 908 1467">– <i>Emitter Turn-Off Thyristors (ETOs)</i> <li data-bbox="417 1485 619 1517">– <i>PiN Diodes</i> <li data-bbox="417 1534 676 1566">– <i>Schottky Diodes</i>

<i>Category Code</i>	<i>Item Description</i>
3A002	<p data-bbox="417 325 1137 500"><u>Note 3</u> <i>Category Code 3A001.h. does not include switches, diodes, or ‘modules’, incorporated into equipment designed for civil automobile, civil railway or “civil aircraft” applications.</i></p> <p data-bbox="417 519 1137 658"><u>Technical Note</u> <i>For the purpose of Category Code 3A001.h., ‘modules’ contain one or more solid-state power semiconductor switches or diodes.</i></p> <p data-bbox="354 729 942 757">General purpose electronic equipment as follows:</p> <p data-bbox="354 782 1033 811">a. Recording equipment and oscilloscopes, as follows:</p> <ol data-bbox="417 830 1137 1382" style="list-style-type: none"> <li data-bbox="417 830 596 858">1. Not used; <li data-bbox="417 877 596 906">2. Not used; <li data-bbox="417 925 596 953">3. Not used; <li data-bbox="417 972 596 1001">4. Not used; <li data-bbox="417 1030 1137 1382">5. Waveform digitisers and transient recorders, having all of the following: <ol data-bbox="502 1115 1137 1382" style="list-style-type: none"> <li data-bbox="502 1115 1137 1210">a. Digitising rate equal to or more than 200 million samples per second and a resolution of 10 bit or more; <li data-bbox="502 1229 1137 1296">b. A ‘continuous throughput’ of 2 Gbit/s or more; <u>and</u> <li data-bbox="502 1315 1137 1382">c. Triggered acquisition of transients or aperiodic signals; <p data-bbox="481 1401 673 1429"><u>Technical Notes</u></p> <ol data-bbox="502 1439 1137 1578" style="list-style-type: none"> <li data-bbox="502 1439 1137 1578">1. <i>For those instruments with a parallel bus architecture, the ‘continuous throughput’ rate is the highest word rate multiplied by the number of bits in a word.</i>

Category Code	Item Description
	<p data-bbox="502 325 1139 491">2. <i>'Continuous throughput' is the fastest data rate the instrument can output to mass storage without the loss of any information whilst sustaining the sampling rate and analogue-to-digital conversion.</i></p> <p data-bbox="502 510 1139 611">3. <i>For the purpose of Category Code 3A002.a.5.c., acquisition can be triggered internally or externally.</i></p> <p data-bbox="417 630 1139 761">6. Digital instrumentation data recorder systems using magnetic disk storage technique and having both of the following, and specially designed digital recorders therefor:</p> <p data-bbox="502 780 1139 881">a. Digitised instrumentation data rate equal to or more than 100 million samples per second at a resolution of 8 bit or more; <u>and</u></p> <p data-bbox="502 900 1139 931">b. A 'continuous throughput' of 1 Gbit/s or more;</p> <p data-bbox="481 950 666 980"><u>Technical Note</u></p> <p data-bbox="481 991 1139 1092"><i>Digital instrumentation data recorder systems can be configured either with a digitiser integrated within or outside the digital recorder.</i></p> <p data-bbox="417 1111 1139 1277">7. Real-time oscilloscopes having a vertical root-mean-square (rms) noise voltage of less than 2% of full-scale at the vertical scale setting that provides the lowest noise value for any input 3 dB bandwidth of 60 GHz or greater per channel;</p> <p data-bbox="481 1296 542 1327"><u>Note</u></p> <p data-bbox="481 1338 1139 1403"><i>Category Code 3A002.a.7. does not include equivalent-time sampling oscilloscopes.</i></p> <p data-bbox="353 1422 534 1452">b. Not used;</p>

<i>Category Code</i>	<i>Item Description</i>
	<p>c. “Signal analysers”, as follows:</p> <ol style="list-style-type: none"> 1. “Signal analysers” having a 3 dB resolution bandwidth (RBW) exceeding 10 MHz anywhere within the frequency range exceeding 31.8 GHz but not exceeding 37 GHz; 2. “Signal analysers” having Displayed Average Noise Level (DANL) less (better) than -150 dBm/Hz anywhere within the frequency range exceeding 43.5 GHz but not exceeding 90 GHz; 3. “Signal analysers” having a frequency exceeding 90 GHz; 4. “Signal analysers” having all of the following: <ol style="list-style-type: none"> a. “Real-time bandwidth” exceeding 170 MHz; <u>and</u> b. 100% probability of discovery with less than a 3 dB reduction from full amplitude due to gaps or windowing effects of signals having a duration of 15 µs or less; <p><u>Technical Notes</u></p> <ol style="list-style-type: none"> 1. <i>Probability of discovery in Category Code 3A002.c.4.b. is also referred to as probability of intercept or probability of capture.</i> 2. <i>For the purpose of Category Code 3A002.c.4.b., the duration for 100% probability of discovery is equivalent to the minimum signal duration necessary for the specified level measurement uncertainty.</i> <p><u>Note</u></p> <p><i>Category Code 3A002.c.4. does not include those “signal analysers” using only constant percentage bandwidth filters (also known as octave or fractional octave filters).</i></p>

<i>Category Code</i>	<i>Item Description</i>
	<p data-bbox="417 325 1139 420">5. “Signal analysers” having a “frequency mask trigger” function with 100% probability of trigger (capture) for signals having a duration of 15 μs or less;</p> <p data-bbox="354 439 969 477">d. Signal generators having any of the following:</p> <ol style="list-style-type: none"> <li data-bbox="417 496 1139 592">1. Specified to generate pulse-modulated signals having all of the following, anywhere within the frequency range exceeding 31.8 GHz but not exceeding 37 GHz: <ol style="list-style-type: none"> <li data-bbox="502 611 1032 643">a. ‘Pulse duration’ of less than 25 ns; <u>and</u> <li data-bbox="502 662 1059 694">b. On/off ratio equal to or exceeding 65 dB; <li data-bbox="417 714 1139 809">2. An output power exceeding 100 mW (20 dBm) anywhere within the frequency range exceeding 43.5 GHz but not exceeding 90 GHz; <li data-bbox="417 828 1139 923">3. A “frequency switching time” as specified by any of the following: <ol style="list-style-type: none"> <li data-bbox="502 923 682 955">a. Not used; <li data-bbox="502 974 1139 1094">b. Less than 100 μs for any frequency change exceeding 2.2 GHz within the frequency range exceeding 4.8 GHz but not exceeding 31.8 GHz; <li data-bbox="502 1113 682 1146">c. Not used; <li data-bbox="502 1165 1139 1304">d. Less than 500 μs for any frequency change exceeding 550 MHz within the frequency range exceeding 31.8 GHz but not exceeding 37 GHz; <u>or</u> <li data-bbox="502 1323 1139 1418">e. Less than 100 μs for any frequency change exceeding 2.2 GHz within the frequency range exceeding 37 GHz but not exceeding 90 GHz; <li data-bbox="502 1437 682 1469">f. Not used; <li data-bbox="417 1488 1139 1551">4. Single sideband (SSB) phase noise, in dBc/Hz, specified as being any of the following: <ol style="list-style-type: none"> <li data-bbox="502 1570 1139 1740">a. Less (better) than $-(126 + 20\log_{10}F - 20\log_{10}f)$ anywhere within the range of $10 \text{ Hz} < F < 10 \text{ kHz}$ anywhere within the frequency range exceeding 3.2 GHz but not exceeding 90 GHz; <u>or</u>

Category Code	Item Description
	<p>b. Less (better) than $-(206 - 20\log_{10}f)$ anywhere within the range of $10 \text{ kHz} < F \leq 100 \text{ kHz}$ anywhere within the frequency range exceeding 3.2 GHz but not exceeding 90 GHz; <u>or</u></p> <p><u>Technical Note</u> <i>In Category Code 3A002.b.4., F is the offset from the operating frequency in Hz and f is the operating frequency in MHz.</i></p> <p>5. A maximum frequency exceeding 90 GHz;</p> <p><u>Note 1</u> <i>For the purpose of Category Code 3A002.d., the term signal generators includes arbitrary waveform and function generators.</i></p> <p><u>Note 2</u> <i>Category Code 3A002.d. does not include equipment in which the output frequency is either produced by the addition or subtraction of two or more crystal oscillator frequencies, or by an addition or subtraction followed by a multiplication of the result.</i></p> <p><u>Technical Notes</u></p> <ol style="list-style-type: none"> 1. <i>The maximum frequency of an arbitrary waveform or function generator is calculated by dividing the sample rate, in samples/second, by a factor of 2.5.</i> 2. <i>For the purpose of Category Code 3A002.d.1.a., 'pulse duration' is defined as the time interval from the point on the leading edge that is 50% of the pulse amplitude to the point on the trailing edge that is 50% of the pulse amplitude.</i> <p>e. Network analysers having any of the following:</p> <ol style="list-style-type: none"> 1. An output power exceeding 31.62 mW (15 dBm) anywhere within the operating frequency range exceeding 43.5 GHz but not exceeding 90 GHz; 2. An output power exceeding 1 mW (0 dBm) anywhere within the operating frequency range exceeding 90 GHz but not exceeding 110 GHz;

Category Code	Item Description
	<p>3. ‘Non-linear vector measurement functionality’ at frequencies exceeding 50 GHz but not exceeding 110 GHz; <u>or</u></p> <p><i>Technical Note</i> ‘Non-linear vector measurement functionality’ is an instrument’s ability to analyse the test results of devices driven into the large-signal domain or the non-linear distortion range.</p> <p>4. A maximum operating frequency exceeding 110 GHz;</p> <p>f. Microwave test receivers having both of the following:</p> <ol style="list-style-type: none"> 1. A maximum operating frequency exceeding 110 GHz; <u>and</u> 2. Being capable of measuring amplitude and phase simultaneously; <p>g. Atomic frequency standards being any of the following:</p> <ol style="list-style-type: none"> 1. “Space-qualified”; 2. Non-rubidium and having a long-term stability less (better) than 1×10^{-11}/month; <u>or</u> 3. Non-“space-qualified” and having all of the following: <ol style="list-style-type: none"> a. Being a rubidium standard; b. Long-term stability less (better) than 1×10^{-11}/month; <u>and</u> c. Total power consumption of less than 1 W.
3A003	<p>Spray cooling thermal management systems employing closed loop fluid handling and reconditioning equipment in a sealed enclosure where a dielectric fluid is sprayed onto electronic components using specially designed spray nozzles that are designed to maintain electronic components within their operating temperature range, and specially designed components therefor.</p>

<i>Category Code</i>	<i>Item Description</i>
3A101	<p>Electronic equipment, devices and components, other than those specified in Category Code 3A001, as follows:</p> <ol style="list-style-type: none"> a. Analogue-to-digital converters, usable in “missiles”, designed to meet military specifications for ruggedised equipment; b. Accelerators capable of delivering electromagnetic radiation produced by bremsstrahlung from accelerated electrons of 2 MeV or greater, and systems containing those accelerators. <p><i>Note</i> <i>Category Code 3A101.b. does not include equipment specially designed for medical purposes.</i></p>
3A102	<p>‘Thermal batteries’ designed or modified for ‘missiles’.</p> <p><i>Technical Notes</i></p> <ol style="list-style-type: none"> 1. <i>In Category Code 3A102, ‘thermal batteries’ are single use batteries that contain a solid non-conducting inorganic salt as the electrolyte. These batteries incorporate a pyrolytic material that, when ignited, melts the electrolyte and activates the battery.</i> 2. <i>In Category Code 3A102, ‘missile’ means complete rocket systems and unmanned aerial vehicle systems capable of a range exceeding 300 km.</i>
3A201	<p>Electronic components, other than those specified in Category Code 3A001, as follows:</p> <ol style="list-style-type: none"> a. Capacitors having either of the following sets of characteristics: <ol style="list-style-type: none"> 1. a. Voltage rating greater than 1.4 kV; b. Energy storage greater than 10 J; c. Capacitance greater than 0.5 μF; <u>and</u> d. Series inductance less than 50 nH; <u>or</u>

Category Code	Item Description
	<p data-bbox="422 325 991 453">2. a. Voltage rating greater than 750 V; b. Capacitance greater than 0.25 μF; <u>and</u> c. Series inductance less than 10 nH;</p> <p data-bbox="354 477 1139 773">b. Superconducting solenoidal electromagnets having all of the following characteristics: 1. Capable of creating magnetic fields greater than 2 T; 2. A ratio of length to inner diameter greater than 2; 3. Inner diameter greater than 300 mm; <u>and</u> 4. Magnetic field uniform to better than 1% over the central 50% of the inner volume;</p> <p data-bbox="417 795 478 824"><u>Note</u></p> <p data-bbox="417 839 1139 1106"><i>Category Code 3A201.b. does not include magnets specially designed for and exported 'as parts of' medical nuclear magnetic resonance (NMR) imaging systems. For this purpose, the magnets and NMR imaging systems may be part of the same shipment or in separate shipments from different sources, provided the related export documents clearly specify that the separate shipments are dispatched 'as part of' the imaging systems.</i></p> <p data-bbox="354 1129 1139 1458">c. Flash X-ray generators or pulsed electron accelerators having either of the following sets of characteristics: 1. a. An accelerator peak electron energy of 500 keV or greater but less than 25 MeV; <u>and</u> b. With a 'figure of merit' (K) of 0.25 or greater; <u>or</u> 2. a. An accelerator peak electron energy of 25 MeV or greater; <u>and</u> b. A 'peak power' greater than 50 MW.</p> <p data-bbox="417 1481 478 1509"><u>Note</u></p> <p data-bbox="417 1525 1139 1652"><i>Category Code 3A201.c. does not include accelerators that are component parts of devices designed for purposes other than electron beam or X-ray radiation (e.g. electron microscopy) nor those designed for medical purposes.</i></p>

Category Code	Item Description
	<p><u>Technical Notes</u></p> <ol style="list-style-type: none"> <li data-bbox="417 367 915 439">1. The 'figure of merit' K is defined as: $K = 1.7 \times 10^3 V^{2.65} Q$ <p>V is the peak electron energy in million electron volts. If the accelerator beam pulse duration is less than or equal to $1 \mu\text{s}$, then Q is the total accelerated charge in Coulombs. If the accelerator beam pulse duration is greater than $1 \mu\text{s}$, then Q is the maximum accelerated charge in $1 \mu\text{s}$. Q equals the integral of i with respect to t, over the lesser of $1 \mu\text{s}$ or the time duration of the beam pulse ($Q = \int idt$), where i is beam current in amperes and t is time in seconds.</p> <li data-bbox="417 824 1137 887">2. 'Peak power' = (peak potential in volts) \times (peak beam current in amperes). <li data-bbox="417 910 1137 1039">3. In machines based on microwave accelerating cavities, the time duration of the beam pulse is the lesser of $1 \mu\text{s}$ or the duration of the bunched beam packet resulting from one microwave modulator pulse. <li data-bbox="417 1062 1137 1157">4. In machines based on microwave accelerating cavities, the peak beam current is the average current in the time duration of a bunched beam packet.
3A225	<p>Frequency changers or generators, other than those specified in Category Code 0B001.b.13., usable as a variable or fixed frequency motor drive, having all of the following characteristics:</p> <p><u>N.B.</u></p> <ol style="list-style-type: none"> <li data-bbox="353 1391 1137 1521">1. "Software" specially designed to enhance or release the performance of a frequency changer or generator to meet the characteristics of Category Code 3A225 is specified in Category Code 3D225. <li data-bbox="353 1544 1137 1673">2. "Technology" in the form of codes or keys to enhance or release the performance of a frequency changer or generator to meet the characteristics of Category Code 3A225 is specified in Category Code 3E225.

Category Code	Item Description
	<p>a. Multiphase output providing a power of 40 VA or greater;</p> <p>b. Operating at a frequency of 600 Hz or more; <u>and</u></p> <p>c. Frequency control better (less) than 0.2%.</p> <p><u>Note</u></p> <p><i>Category Code 3A225 does not include frequency changers or generators if they have hardware, “software” or “technology” constraints that limit the performance to less than that specified above, provided they meet any of the following:</i></p> <ol style="list-style-type: none"> 1. <i>They need to be returned to the original manufacturer to make the enhancements or release the constraints;</i> 2. <i>They require “software” as specified in Category Code 3D225 to enhance or release the performance to meet the characteristics of Category Code 3A225; <u>or</u></i> 3. <i>They require “technology” in the form of keys or codes as specified in Category Code 3E225 to enhance or release the performance to meet the characteristics of Category Code 3A225.</i> <p><u>Technical Notes</u></p> <ol style="list-style-type: none"> 1. <i>Frequency changers in Category Code 3A225 are also known as converters or inverters.</i> 2. <i>Frequency changers in Category Code 3A225 may be marketed as Generators, Electronic Test Equipment, AC Power Supplies, Variable Speed Motors Drives, Variable Speed Drives (VSDs), Variable Frequency Drives (VFDs), Adjustable Frequency Drives (AFDs), or Adjustable Speed Drives (ASDs).</i>

<i>Category Code</i>	<i>Item Description</i>
3A226	<p>High-power direct current power supplies, other than those specified in Category Code 0B001.j.6., having both of the following characteristics:</p> <ol style="list-style-type: none"> a. Capable of continuously producing, over a time period of 8 hours, 100 V or greater with current output of 500 A or greater; <u>and</u> b. Current or voltage stability better than 0.1% over a time period of 8 hours.
3A227	<p>High-voltage direct current power supplies, other than those specified in Category Code 0B001.j.5., having both of the following characteristics:</p> <ol style="list-style-type: none"> a. Capable of continuously producing, over a time period of 8 hours, 20 kV or greater with current output of 1 A or greater; <u>and</u> b. Current or voltage stability better than 0.1% over a time period of 8 hours.
3A228	<p>Switching devices, as follows:</p> <ol style="list-style-type: none"> a. Cold-cathode tubes, whether gas filled or not, operating similarly to a spark gap, having all of the following characteristics: <ol style="list-style-type: none"> 1. Containing three or more electrodes; 2. Anode peak voltage rating of 2.5 kV or more; 3. Anode peak current rating of 100 A or more; <u>and</u> 4. Anode delay time of 10 μs or less; <p><u>Note</u> <i>Category Code 3A228 includes gas krytron tubes and vacuum sprytron tubes.</i></p>

Category Code	Item Description
	<ul style="list-style-type: none"> b. Triggered spark-gaps having both of the following characteristics: <ul style="list-style-type: none"> 1. An anode delay time of 15 μs or less; <u>and</u> 2. Rated for a peak current of 500 A or more; c. Modules or assemblies with a fast switching function, other than those specified in Category Code 3A001.g. or 3A001.h., having all of the following characteristics: <ul style="list-style-type: none"> 1. Anode peak voltage rating greater than 2 kV; 2. Anode peak current rating of 500 A or more; <u>and</u> 3. Turn-on time of 1 μs or less.
3A229	<p>High-current pulse generators as follows:</p> <p><u>N.B.</u> <i>See also Division 2 of Part 1 of this Schedule.</i></p> <ul style="list-style-type: none"> a. Detonator firing sets (initiator systems, firesets), including electronically-charged, explosively-driven and optically-driven firing sets, other than those specified in Category Code 1A007.a., designed to drive multiple controlled detonators specified in Category Code 1A007.b.; b. Modular electrical pulse generators (pulsers) having all of the following characteristics: <ul style="list-style-type: none"> 1. Designed for portable, mobile, or ruggedised-use; 2. Capable of delivering their energy in less than 15 μs into loads of less than 40 ohms; 3. Having an output greater than 100 A; 4. No dimension greater than 30 cm; 5. Weight less than 30 kg; <u>and</u> 6. Specified for use over an extended temperature range 223 K (-50°C) to 373 K (100°C) or specified as suitable for aerospace applications; <p><u>Note</u> <i>Category Code 3A229.b. includes xenon flash-lamp drivers.</i></p>

<i>Category Code</i>	<i>Item Description</i>
3A230	<p>c. Micro-firing units having all of the following characteristics:</p> <ol style="list-style-type: none"> 1. No dimension greater than 35 mm; 2. Voltage rating of equal to or greater than 1 kV; <u>and</u> 3. Capacitance of equal to or greater than 100 nF. <p>High-speed pulse generators, and ‘pulse heads’ therefor, having both of the following characteristics:</p> <ol style="list-style-type: none"> a. Output voltage greater than 6 V into a resistive load of less than 55 ohms; <u>and</u> b. ‘Pulse transition time’ less than 500 ps. <p><i><u>Technical Notes</u></i></p> <ol style="list-style-type: none"> 1. <i>In Category Code 3A230, ‘pulse transition time’ is defined as the time interval between 10% and 90% voltage amplitude.</i> 2. <i>‘Pulse heads’ are impulse forming networks designed to accept a voltage step function and shape it into a variety of pulse forms that can include rectangular, triangular, step, impulse, exponential, or monocycle types. ‘Pulse heads’ can be an integral part of the pulse generator, they can be a plug-in module to the device or they can be an externally connected device.</i>
3A231	<p>Neutron generator systems, including tubes, having both of the following characteristics:</p> <ol style="list-style-type: none"> a. Designed for operation without an external vacuum system; <u>and</u> b. Utilising any of the following: <ol style="list-style-type: none"> 1. Electrostatic acceleration to induce a tritium-deuterium nuclear reaction; <u>or</u> 2. Electrostatic acceleration to induce a deuterium-deuterium nuclear reaction and capable of an output of 3×10^9 neutrons/s or greater.

Category Code	Item Description
3A232	<p>Multipoint initiation systems, other than those specified in Category Code 1A007, as follows:</p> <p><u>N.B.</u></p> <p><i>See also Division 2 of Part 1 of this Schedule.</i></p> <p><i>See Category Code 1A007.b. for detonators.</i></p> <p>a. Not used;</p> <p>b. Arrangements using single or multiple detonators designed to nearly simultaneously initiate an explosive surface over greater than 5,000 mm² from a single firing signal with an initiation timing spread over the surface of less than 2.5 µs.</p> <p><u>Note</u></p> <p><i>Category Code 3A232 does not include detonators using only primary explosives, such as lead azide.</i></p>
3A233	<p>Mass spectrometers, other than those specified in Category Code 0B002.g., capable of measuring ions of 230 atomic mass units or greater and having a resolution of better than 2 parts in 230, as follows, and ion sources therefor:</p> <p>a. Inductively coupled plasma mass spectrometers (ICP/MS);</p> <p>b. Glow discharge mass spectrometers (GDMS);</p> <p>c. Thermal ionisation mass spectrometers (TIMS);</p> <p>d. Electron bombardment mass spectrometers having both of the following features:</p> <ol style="list-style-type: none"> 1. A molecular beam inlet system that injects a collimated beam of analyte molecules into a region of the ion source where the molecules are ionised by an electron beam; <u>and</u> 2. One or more ‘cold traps’ that can be cooled to a temperature of 193 K (-80°C); <p>e. Not used;</p> <p>f. Mass spectrometers equipped with a microfluorination ion source designed for actinides or actinide fluorides.</p>

Category Code	Item Description
	<p><u>Technical Notes</u></p> <ol style="list-style-type: none"> 1. <i>Electron bombardment mass spectrometers in Category Code 3A233.d. are also known as electron impact mass spectrometers or electron ionisation mass spectrometers.</i> 2. <i>In Category Code 3A233.d.2., a 'cold trap' is a device that traps gas molecules by condensing or freezing them on cold surfaces. For the purpose of Category Code 3A233.d.2., a closed-loop gaseous helium cryogenic vacuum pump is not a 'cold trap'.</i>
3A234	<p>Striplines to provide low inductance path to detonators with the following characteristics:</p> <ol style="list-style-type: none"> a. Voltage rating greater than 2 kV; <u>and</u> b. Inductance of less than 20 nH.
3B	Test, Inspection and Production Equipment
3B001	<p>Equipment for the manufacturing of semiconductor devices or materials, as follows and specially designed components and accessories therefor:</p> <ol style="list-style-type: none"> a. Equipment designed for epitaxial growth, as follows: <ol style="list-style-type: none"> 1. Equipment capable of producing a layer of any material other than silicon with a thickness uniform to less than $\pm 2.5\%$ across a distance of 75 mm or more; <p><u>Note</u> <i>Category Code 3B001.a.1. includes Atomic Layer Epitaxy (ALE) equipment.</i></p> <ol style="list-style-type: none"> 2. Metal Organic Chemical Vapour Deposition (MOCVD) reactors designed for compound semiconductor epitaxial growth of material having two or more of the following elements: aluminium, gallium, indium, arsenic, phosphorus, antimony, or nitrogen; 3. Molecular beam epitaxial growth equipment using gas or solid sources;

<i>Category Code</i>	<i>Item Description</i>
	<p>b. Equipment designed for ion implantation and having any of the following:</p> <ol style="list-style-type: none"> 1. Not used; 2. Being designed and optimised to operate at a beam energy of 20 keV or more and a beam current of 10 mA or more for hydrogen, deuterium or helium implant; 3. Direct write capability; 4. A beam energy of 65 keV or more and a beam current of 45 mA or more for high energy oxygen implant into a heated semiconductor material “substrate”; <u>or</u> 5. Being designed and optimised to operate at a beam energy of 20 keV or more and a beam current of 10 mA or more for silicon implant into a semiconductor material “substrate” heated to 600°C or greater; <p>c. Anisotropic plasma dry etching equipment having both of the following:</p> <ol style="list-style-type: none"> 1. Designed or optimised to produce critical dimensions of 65 nm or less; <u>and</u> 2. Within-wafer non-uniformity equal to or less than 10% 3σ measured with an edge exclusion of 2 mm or less; <p>d. Not used;</p> <p>e. Automatic loading multi-chamber central wafer handling systems, having both of the following:</p> <ol style="list-style-type: none"> 1. Interfaces for wafer input and output, to which more than two functionally different ‘semiconductor process tools’ specified in Category Code 3B001.a., 3B001.b. or 3B001.c. are designed to be connected; <u>and</u> 2. Designed to form an integrated system in a vacuum environment for ‘sequential multiple wafer processing’;

Category Code	Item Description
	<p><u>Note</u></p> <p>Category Code 3B001.e. does not include automatic robotic wafer handling systems specially designed for parallel wafer processing.</p> <p><u>Technical Notes</u></p> <ol style="list-style-type: none"> 1. For the purpose of Category Code 3B001.e., 'semiconductor process tools' refers to modular tools that provide physical processes for semiconductor production that are functionally different, such as deposition, etch, implant or thermal processing. 2. For the purpose of Category Code 3B001.e., 'sequential multiple wafer processing' means the capability to process each wafer in different 'semiconductor process tools', such as by transferring each wafer from one tool to a second tool and on to a third tool with the automatic loading multi-chamber central wafer handling systems. <p>f. Lithography equipment as follows:</p> <ol style="list-style-type: none"> 1. Align and expose step and repeat (direct step on wafer) or step and scan (scanner) equipment for wafer processing using photo-optical or X-ray methods and having any of the following: <ol style="list-style-type: none"> a. A light source wavelength shorter than 193 nm; <u>or</u> b. Capable of producing a pattern with a 'Minimum Resolvable Feature size' (MRF) of 45 nm or less; <p><u>Technical Note</u></p> <p>The 'Minimum Resolvable Feature size' (MRF) is calculated by the following formula:</p> $MRF = \frac{\left[\begin{array}{c} \text{an exposure light source} \\ \text{wavelength in nm} \end{array} \right] \times [K \text{ factor}]}{\text{numerical aperture}}$ <p>where the K factor = 0.35</p>

Category Code	Item Description
	<p>2. Imprint lithography equipment capable of producing features of 45 nm or less;</p> <p><u>Note</u> Category Code 3B001.f.2. includes:</p> <ul style="list-style-type: none"> – Micro contact printing tools – Hot embossing tools – Nano-imprint lithography tools – Step and flash imprint lithography (S-FIL) tools <p>3. Equipment specially designed for mask making or semiconductor device processing using direct writing methods and having all of the following:</p> <ul style="list-style-type: none"> a. Using deflected focused electron beam, ion beam or “laser” beam; <u>and</u> b. Having any of the following: <ul style="list-style-type: none"> 1. A spot size smaller than 0.2 μm; 2. Being capable of producing a pattern with a feature size of less than 1 μm; <u>or</u> 3. An overlay accuracy of better than $\pm 0.20 \mu\text{m}$ (3 sigma); <p>g. Masks and reticles, designed for integrated circuits specified in Category Code 3A001;</p> <p>h. Multi-layer masks with a phase shift layer not specified by Category Code 3B001.g. and having any of the following:</p> <ul style="list-style-type: none"> 1. Made on a mask “substrate blank” from glass specified as having less than 7 nm/cm birefringence; <u>or</u> 2. Designed to be used by lithography equipment having a light source wavelength less than 245 nm;

<i>Category Code</i>	<i>Item Description</i>
	<p><u>Note</u> <i>Category Code 3B001.h. does not include multi-layer masks with a phase shift layer designed for the fabrication of memory devices not specified in Category Code 3A001.</i></p> <p>i. Imprint lithography templates designed for integrated circuits specified in Category Code 3A001.</p>
3B002	<p>Test equipment specially designed for testing finished or unfinished semiconductor devices as follows and specially designed components and accessories therefor:</p>
	<p>a. For testing S-parameters of transistor devices at frequencies exceeding 31.8 GHz;</p>
	<p>b. Not used;</p>
	<p>c. For testing microwave integrated circuits specified in Category Code 3A001.b.2.</p>
3C	Materials
3C001	<p>Hetero-epitaxial materials consisting of a “substrate” having stacked epitaxially grown multiple layers of any of the following:</p>
	<p>a. Silicon (Si);</p>
	<p>b. Germanium (Ge);</p>
	<p>c. Silicon carbide (SiC); <u>or</u></p>
	<p>d. “III/V compounds” of gallium or indium.</p>
	<p><u>Note</u> <i>Category Code 3C001.d. does not apply to a “substrate” having one or more P-type epitaxial layers of GaN, InGaN, AlGaN, InAlN, InAlGaN, GaP, InGaP, AlInP or InGaAlP, independent of the sequence of the elements, except if the P-type epitaxial layer is between N-type layers.</i></p>

<i>Category Code</i>	<i>Item Description</i>
3C002	<p>Resist materials as follows and “substrates” coated with the following resists:</p> <ol style="list-style-type: none"> a. Resists designed for semiconductor lithography as follows: <ol style="list-style-type: none"> 1. Positive resists adjusted (optimised) for use at wavelengths less than 245 nm but equal to or greater than 15 nm; 2. Resists adjusted (optimised) for use at wavelengths less than 15 nm but greater than 1 nm; b. All resists designed for use with electron beams or ion beams, with a sensitivity of 0.01 $\mu\text{coulomb}/\text{mm}^2$ or better; c. Not used; d. All resists optimised for surface imaging technologies; e. All resists designed or optimised for use with imprint lithography equipment specified in Category Code 3B001.f.2. that use either a thermal or photo-curable process.
3C003	<p>Organo-inorganic compounds as follows:</p> <ol style="list-style-type: none"> a. Organo-metallic compounds of aluminium, gallium or indium having a purity (metal basis) better than 99.999%; b. Organo-arsenic, organo-antimony and organo-phosphorus compounds, having a purity (inorganic element basis) better than 99.999%. <p><u>Note</u> <i>Category Code 3C003 only includes compounds whose metallic, partly metallic or non-metallic element is directly linked to carbon in the organic part of the molecule.</i></p>
3C004	<p>Hydrides of phosphorus, arsenic or antimony, having a purity better than 99.999%, even diluted in inert gases or hydrogen.</p> <p><u>Note</u> <i>Category Code 3C004 does not include hydrides containing 20% molar or more of inert gases or hydrogen.</i></p>

<i>Category Code</i>	<i>Item Description</i>
3C005	Silicon carbide (SiC), gallium nitride (GaN), aluminium nitride (AlN) or aluminium gallium nitride (AlGaN) semiconductor “substrates”, or ingots, boules, or other preforms of those materials, having resistivities greater than 10,000 ohm-cm at 20°C.
3C006	“Substrates” specified in Category Code 3C005 with at least one epitaxial layer of silicon carbide, gallium nitride, aluminium nitride or aluminium gallium nitride.
3D	Software
3D001	“Software” specially designed for the “development” or “production” of equipment specified in Category Codes 3A001.b. to 3A002.g. or Category 3B.
3D002	“Software” specially designed for the “use” of equipment specified in Category Code 3A225, 3B001.a. to f. or 3B002.
3D003	‘Physics-based’ simulation “software” specially designed for the “development” of lithographic, etching or deposition processes for translating masking patterns into specific topographical patterns in conductors, dielectrics or semiconductor materials.
	<p><u>Technical Note</u></p> <p><i>‘Physics-based’ in Category Code 3D003 means using computations to determine a sequence of physical cause and effect events based on physical properties (e.g. temperature, pressure, diffusion constants and semiconductor materials properties).</i></p>
	<p><u>Note</u></p> <p><i>Libraries, design attributes or associated data for the design of semiconductor devices or integrated circuits are considered as “technology”.</i></p>

<i>Category Code</i>	<i>Item Description</i>
3D004	“Software” specially designed for the “development” of the equipment specified in Category Code 3A003.
3D101	“Software” specially designed or modified for the “use” of equipment specified in Category Code 3A101.b.
3D225	“Software” specially designed to enhance or release the performance of frequency changers or generators to meet the characteristics of Category Code 3A225.
3E	Technology
3E001	“Technology” (according to the General Technology Note) for the “development” or “production” of equipment or materials specified in Category 3A, 3B or 3C.
	<u>Note 1</u>
	<i>Category Code 3E001 does not include “technology” for the “production” of equipment or components specified in Category Code 3A003.</i>
	<u>Note 2</u>
	<i>Category Code 3E001 does not include “technology” for the “development” or “production” of integrated circuits specified in Category Codes 3A001.a.3. to 3A001.a.12., having all of the following:</i>
	<i>a. Using “technology” at or above 0.130 μm; <u>and</u></i>
	<i>b. Incorporating multi-layer structures with three or fewer metal layers.</i>

<i>Category Code</i>	<i>Item Description</i>
3E002	<p>“Technology” (according to the General Technology Note) other than that specified in Category Code 3E001, for the “development” or “production” of a “microprocessor microcircuit”, “microcomputer microcircuit” or microcontroller microcircuit core, having an arithmetic logic unit with an access width of 32 bits or more and any of the following features or characteristics:</p> <p>a. A ‘vector processor unit’ designed to perform more than two calculations on floating-point vectors (one-dimensional arrays of 32-bit or larger numbers) simultaneously;</p> <p><i>Technical Note</i> <i>A ‘vector processing unit’ is a processor element with built-in instructions that perform multiple calculations on floating-point vectors (one-dimensional arrays of 32-bit or larger numbers) simultaneously, having at least one vector arithmetic logic unit.</i></p> <p>b. Designed to perform more than four 64-bit or larger floating-point operation results per cycle; <u>or</u></p> <p>c. Designed to perform more than four 16-bit fixed-point multiply-accumulate results per cycle (e.g. digital manipulation of analogue information that has been previously converted into digital form, also known as digital “signal processing”).</p> <p><i>Note</i> <i>Category Code 3E002.c. does not include “technology” for multimedia extensions.</i></p> <p><i>Note 1</i> <i>Category Code 3E002 does not include “technology” for the “development” or “production” of micro-processor cores, having all of the following:</i></p> <p>a. <i>Using “technology” at or above 0.130 μm; <u>and</u></i></p> <p>b. <i>Incorporating multi-layer structures with five or fewer metal layers.</i></p> <p><i>Note 2</i> <i>Category Code 3E002 includes “technology” for digital signal processors and digital array processors.</i></p>

<i>Category Code</i>	<i>Item Description</i>
3E003	<p>Other “technology” for the “development” or “production” of the following:</p> <ul style="list-style-type: none"> a. Vacuum microelectronic devices; b. Hetero-structure semiconductor electronic devices such as high electron mobility transistors (HEMT), hetero-bipolar transistors (HBT), quantum well and super lattice devices; <p><i>Note</i> <i>Category Code 3E003.b. does not include “technology” for high electron mobility transistors (HEMT) operating at frequencies lower than 31.8 GHz and hetero-junction bipolar transistors (HBT) operating at frequencies lower than 31.8 GHz.</i></p> <ul style="list-style-type: none"> c. “Superconductive” electronic devices; d. Substrates of films of diamond for electronic components; e. Substrates of silicon-on-insulator (SOI) for integrated circuits in which the insulator is silicon dioxide; f. Substrates of silicon carbide for electronic components; g. Electronic vacuum tubes operating at frequencies of 31.8 GHz or higher.
3E101	<p>“Technology” (according to the General Technology Note) for the “use” of equipment or “software” specified in Category Code 3A001.a.1. or 2., 3A101, 3A102 or 3D101.</p>
3E102	<p>“Technology” (according to the General Technology Note) for the “development” of “software” specified in Category Code 3D101.</p>

<i>Category Code</i>	<i>Item Description</i>
3E201	“Technology” (according to the General Technology Note) for the “use” of equipment specified in Category Codes 3A001.e.2., 3A001.e.3., 3A001.g., 3A201, 3A225 to 3A234.
3E225	“Technology”, in the form of codes or keys, to enhance or release the performance of frequency changers or generators to meet the characteristics of Category Code 3A225.

Category Code	Item Description
---------------	------------------

CATEGORY 4 — COMPUTERS

Note 1

Computers, related equipment and “software” performing telecommunications or “local area network” functions with the performance characteristics in Category 5 – Part 1 (Telecommunications) shall also be treated as coming within that Category.

Note 2

Control units which directly interconnect the buses or channels of central processing units, “main storage” or disk controllers are not regarded as telecommunications equipment described in Category 5 – Part 1 (Telecommunications).

N.B.

For “software” specially designed for packet switching, see Category Code 5D001.

Note 3

Computers, related equipment and “software” performing cryptographic, cryptanalytic, certifiable multi-level security or certifiable user isolation functions, or which limit electromagnetic compatibility (EMC), with the performance characteristics in Category 5 – Part 2 (“Information Security”) shall also be treated as coming within that Category.

4A	Systems, Equipment and Components
4A001	<p>Electronic computers and related equipment, having any of the following, and “electronic assemblies” and specially designed components therefor:</p> <p><u>N.B.</u></p> <p>See also Category Code 4A101.</p> <p>a. Specially designed to have any of the following:</p> <ol style="list-style-type: none"> 1. Rated for operation at an ambient temperature below 228 K (-45°C) or above 358 K (85°C); <u>or</u> <p><u>Note</u></p> <p>Category Code 4A001.a.1. does not apply to computers specially designed for civil automobile, railway train or “civil aircraft” applications.</p>

<i>Category Code</i>	<i>Item Description</i>
	<p>2. Radiation hardened to exceed any of the following specifications:</p> <p>a. Total Dose 5×10^3 Gy (silicon);</p> <p>b. Dose Rate Upset 5×10^6 Gy (silicon)/s; <u>or</u></p> <p>c. Single Event Upset 1×10^{-8} Error/bit/day;</p> <p><u>Note</u> <i>Category Code 4A001.a.2. does not include computers specially designed for “civil aircraft” applications.</i></p> <p>b. Not used.</p>
4A003	<p>“Digital computers”, “electronic assemblies”, and related equipment therefor, as follows, and specially designed components therefor:</p> <p><u>Note 1</u> <i>Category Code 4A003 includes the following:</i></p> <ul style="list-style-type: none"> – ‘Vector processors’; – Array processors; – Digital signal processors; – Logic processors; – Equipment designed for “image enhancement”; – Equipment designed for “signal processing”. <p><u>Technical Note</u> <i>A ‘vector processor’ is defined as a processor with built-in instructions that perform multiple calculations on floating-point vectors (one-dimensional arrays of 64-bit or larger numbers) simultaneously, having at least 2 vector functional units and at least 8 vector registers of at least 64 elements each.</i></p> <p><u>Note 2</u> <i>The control status of the “digital computers” and related equipment described in Category Code 4A003 is determined by the control status of other equipment or systems provided:</i></p>

Category Code	Item Description
	<p>a. The “digital computers” or related equipment are essential for the operation of the other equipment or systems;</p> <p>b. The “digital computers” or related equipment are not a “principal element” of the other equipment or systems; <u>and</u></p> <p><u>N.B. 1</u></p> <p>The control status of “signal processing” or “image enhancement” equipment specially designed for other equipment with functions limited to those required for the other equipment is determined by the control status of the other equipment even if it exceeds the “principal element” criterion.</p> <p><u>N.B. 2</u></p> <p>For the control status of “digital computers” or related equipment for telecommunications equipment, see Category 5 – Part 1 (Telecommunications).</p> <p>c. The “technology” for the “digital computers” and related equipment is determined by Category 4E.</p> <p>a. Not used;</p> <p>b. “Digital computers” having an “Adjusted Peak Performance” (“APP”) exceeding 8 Weighted TeraFLOPS (WT);</p> <p>c. “Electronic assemblies” specially designed or modified for enhancing performance by aggregation of processors so that the “APP” of the aggregation exceeds the limit specified in Category Code 4A003.b.;</p> <p><u>Note 1</u></p> <p>Category Code 4A003.c. includes only “electronic assemblies” and programmable interconnections not exceeding the limit specified in Category Code 4A003.b. when shipped as unintegrated “electronic assemblies”. It does not include “electronic assemblies” inherently limited by nature of their design for use as related equipment specified in Category Code 4A003.e.</p> <p><u>Note 2</u></p> <p>Category Code 4A003.c. does not include “electronic assemblies” specially designed for a product or family of products whose maximum configuration does not exceed the limit specified in Category Code 4A003.b.</p>

<i>Category Code</i>	<i>Item Description</i>
	<p>d. Not used;</p> <p>e. Equipment performing analogue-to-digital conversions exceeding the limits specified in Category Code 3A001.a.5.;</p> <p>f. Not used;</p> <p>g. Equipment specially designed for aggregating the performance of “digital computers” by providing external interconnections which allows communications at unidirectional data rates exceeding 2 Gbyte/s per link.</p> <p><i>Note</i> <i>Category Code 4A003.g. does not include internal interconnection equipment (e.g. backplanes and buses), passive interconnection equipment, “network access controllers” or “communications channel controllers”.</i></p>
4A004	<p>Computers as follows and specially designed related equipment, “electronic assemblies” and components therefor:</p> <p>a. “Systolic array computers”;</p> <p>b. “Neural computers”;</p> <p>c. “Optical computers”.</p>
4A005	<p>Systems, equipment, and components therefor, specially designed or modified for the generation, operation or delivery of, or communication with, “intrusion software”.</p>

<i>Category Code</i>	<i>Item Description</i>
4A101	Analogue computers, “digital computers” or digital differential analysers, other than those specified in Category Code 4A001.a.1., which are ruggedised and designed or modified for use in space launch vehicles specified in Category Code 9A004 or sounding rockets specified in Category Code 9A104.
4A102	“Hybrid computers” specially designed for modelling, simulation or design integration of space launch vehicles specified in Category Code 9A004 or sounding rockets specified in Category Code 9A104.
	<p><i>Note</i></p> <p><i>Category Code 4A102 only extends to equipment supplied with “software” specified in Category Code 7D103 or 9D103.</i></p>
4B	<p>Test, Inspection and Production Equipment</p> <p>None.</p>
4C	<p>Materials</p> <p>None.</p>
4D	<p>Software</p> <p><i>Note</i></p> <p><i>For “software” for equipment described in other Categories, please see the appropriate Category.</i></p>

<i>Category Code</i>	<i>Item Description</i>
4D001	<p>“Software” as follows:</p> <ol style="list-style-type: none"> a. “Software” specially designed or modified for the “development” or “production” of equipment or “software” specified in Category Codes 4A001 to 4A004, or Category 4D; b. “Software”, other than that specified in Category Code 4D001.a., specially designed or modified for the “development” or “production” of equipment, as follows: <ol style="list-style-type: none"> 1. “Digital computers” having an “Adjusted Peak Performance” (“APP”) exceeding 1.0 Weighted TeraFLOPS (WT); 2. “Electronic assemblies” specially designed or modified for enhancing performance by aggregation of processors so that the “APP” of the aggregation exceeds the limit in Category Code 4D001.b.1. <p><i>Note</i> Please see Technical Note on calculation of “APP” immediately after Category Code 4E001.</p>
4D002	Not used.
4D003	Not used.
4D004	“Software” specially designed or modified for the generation, operation or delivery of, or communication with, “intrusion software”.

<i>Category Code</i>	<i>Item Description</i>
4E	Technology
4E001	<p>a. “Technology” (according to the General Technology Note) for the “development”, “production” or “use” of equipment or “software” specified in Category 4A or 4D;</p> <p>b. “Technology”, other than that specified in Category Code 4E001.a., specially designed or modified for the “development” or “production” of equipment as follows:</p> <ol style="list-style-type: none"> 1. “Digital computers” having an “Adjusted Peak Performance” (“APP”) exceeding 1.0 Weighted TeraFLOPS (WT); 2. “Electronic assemblies” specially designed or modified for enhancing performance by aggregation of processors so that the “APP” of the aggregation exceeds the limit in Category Code 4E001.b.1.; <p>c. “Technology” for the “development” of “intrusion software”.</p> <p><u>Note</u> Please see Technical Note on calculation of “APP” immediately after Category Code 4E001.</p>

TECHNICAL NOTE ON “ADJUSTED PEAK PERFORMANCE” (“APP”)

“APP” is an adjusted peak rate at which “digital computers” perform 64-bit or larger floating-point additions and multiplications.

“APP” is expressed in Weighted TeraFLOPS (WT), in units of 10^{12} adjusted floating-point operations per second.

Abbreviations used in this Technical Note

n	number of processors in the “digital computer”
i	processor number ($i = 1, \dots, n$)
t_i	processor cycle time ($t_i = 1/F_i$)
F_i	processor frequency
R_i	peak floating-point calculating rate
W_i	architecture adjustment factor

Outline of “APP” calculation method

1. For each processor i , determine the peak number of 64-bit or larger floating-point operations, FPO_i , performed per cycle for each processor in the “digital computer”.

Note

In determining FPO, include only 64-bit or larger floating-point additions and/or multiplications. All floating-point operations must be expressed in operations per processor cycle; operations requiring multiple cycles may be expressed in fractional results per cycle. For processors not capable of performing calculations on floating-point operands of 64-bit or more, the effective calculating rate R is zero.

2. Calculate the floating-point rate R for each processor $R_i = FPO_i/t_i$.
3. Calculate “APP” as “APP” = $W_1 \times R_1 + W_2 \times R_2 + \dots + W_n \times R_n$.
4. For ‘vector processors’, $W_i = 0.9$. For non-‘vector processors’, $W_i = 0.3$.

Note 1

For processors that perform compound operations in a cycle, such as addition and multiplication, each operation is counted.

Note 2

For a pipelined processor the effective calculating rate R is the faster of the pipelined rate, once the pipeline is full, or the non-pipelined rate.

Note 3

The calculating rate R of each contributing processor is to be calculated at its maximum value theoretically possible before the “APP” of the combination is derived. Simultaneous operations are assumed to exist when the computer manufacturer claims concurrent, parallel, or simultaneous operation or execution in a manual or brochure for the computer.

Note 4

Do not include processors that are limited to input/output and peripheral functions (e.g. disk drive, communication and video display) when calculating “APP”.

Note 5

“APP” values are not to be calculated for processor combinations (inter)connected by “Local Area Networks”, Wide Area Networks, I/O shared connections/devices, I/O controllers and any communication interconnection implemented by “software”.

Note 6

“APP” values must be calculated for processor combinations containing processors specially designed to enhance performance by aggregation, operating simultaneously and sharing memory.

Technical Notes

- 1. Aggregate all processors and accelerators operating simultaneously and located on the same die.*
- 2. Processor combinations share memory when any processor is capable of accessing any memory location in the system through the hardware transmission of cache lines or memory words, without the involvement of any software mechanism, which may be achieved using “electronic assemblies” specified in Category Code 4A003.c.*

Note 7

A ‘vector processor’ is defined as a processor with built-in instructions that perform multiple calculations on floating-point vectors (one-dimensional arrays of 64-bit or larger numbers) simultaneously, having at least 2 vector functional units and at least 8 vector registers of at least 64 elements each.

Category Code	Item Description
---------------	------------------

CATEGORY 5 — TELECOMMUNICATIONS AND “INFORMATION SECURITY”

Part 1 — TELECOMMUNICATIONS

Note 1

Category 5 – Part 1 concerns components, “lasers”, test and “production” equipment and “software”, therefor which are specially designed for telecommunications equipment or systems.

N.B. 1

For “lasers” specially designed for telecommunications equipment or systems, see Category Code 6A005.

N.B. 2

See also Category 5 – Part 2 for equipment, components, and “software”, performing or incorporating “information security” functions.

Note 2

“Digital computers”, related equipment or “software”, when essential for the operation and support of telecommunications equipment described in this Category, are regarded as specially designed components for the purposes of this Category, provided they are the standard models customarily supplied by the manufacturer. This includes operation, administration, maintenance, engineering or billing computer systems.

5A1	Systems, Equipment and Components
5A001	<p>Telecommunications systems, equipment, components and accessories, as follows:</p> <p>a. Any type of telecommunications equipment having any of the following characteristics, functions or features:</p> <ol style="list-style-type: none"> 1. Specially designed to withstand transitory electronic effects or electromagnetic pulse effects, both arising from a nuclear explosion; 2. Specially hardened to withstand gamma, neutron or ion radiation; <u>or</u>

Category Code	Item Description
	<p data-bbox="417 325 1153 392">3. Specially designed to operate outside the temperature range from 218 K (-55°C) to 397 K (124°C);</p> <p data-bbox="481 411 542 439"><u>Note</u></p> <p data-bbox="481 453 1153 519"><i>Category Code 5A001.a.3. applies only to electronic equipment.</i></p> <p data-bbox="417 538 479 567"><u>Note</u></p> <p data-bbox="417 580 1153 647"><i>Category Codes 5A001.a.2. and 5A001.a.3. do not include equipment designed or modified for use on board satellites.</i></p> <p data-bbox="354 662 1153 763">b. Telecommunications systems and equipment, and specially designed components and accessories therefor, having any of the following characteristics, functions or features:</p> <ol data-bbox="417 782 1153 1742" style="list-style-type: none"> <li data-bbox="417 782 1153 849">1. Being underwater untethered communications systems having any of the following: <ol data-bbox="502 868 1153 1182" style="list-style-type: none"> <li data-bbox="502 868 1153 934">a. An acoustic carrier frequency outside the range from 20 kHz to 60 kHz; <li data-bbox="502 953 1153 1020">b. Using an electromagnetic carrier frequency below 30 kHz; <li data-bbox="502 1039 1153 1068">c. Using electronic beam steering techniques; <u>or</u> <li data-bbox="502 1087 1153 1182">d. Using “lasers” or light-emitting diodes (LEDs) with an output wavelength greater than 400 nm and less than 700 nm, in a “local area network”; <li data-bbox="417 1201 1153 1268">2. Being radio equipment operating in the 1.5 MHz to 87.5 MHz band and having all of the following: <ol data-bbox="502 1287 1153 1742" style="list-style-type: none"> <li data-bbox="502 1287 1153 1391">a. Automatically predicting and selecting frequencies and “total digital transfer rates” per channel to optimise the transmission; <u>and</u> <li data-bbox="502 1410 1153 1742">b. Incorporating a linear power amplifier configuration having a capability to support multiple signals simultaneously at an output power of 1 kW or more in the frequency range of 1.5 MHz or more but less than 30 MHz, or 250 W or more in the frequency range of 30 MHz or more but not exceeding 87.5 MHz, over an “instantaneous bandwidth” of one octave or more and with an output harmonic and distortion content of better than -80 dB;

<i>Category Code</i>	<i>Item Description</i>
	<p>3. Being radio equipment employing “spread spectrum” techniques, including “frequency hopping” techniques, other than those specified in Category Code 5A001.b.4. and having any of the following:</p> <ul style="list-style-type: none"> a. User programmable spreading codes; <u>or</u> b. A total transmitted bandwidth which is 100 or more times the bandwidth of any one information channel and in excess of 50 kHz; <p><i>Note</i> <i>Category Code 5A001.b.3.b. does not apply to radio equipment specially designed for use with any of the following:</i></p> <ul style="list-style-type: none"> a. <i>Civil cellular radio-communications systems; <u>or</u></i> b. <i>Fixed or mobile satellite earth stations for commercial civil telecommunications.</i> <p><i>Note</i> <i>Category Code 5A001.b.3. does not include equipment designed to operate at an output power of 1 W or less.</i></p> <p>4. Being radio equipment employing ultra-wideband modulation techniques, having user programmable channelising codes, scrambling codes or network identification codes and having any of the following:</p> <ul style="list-style-type: none"> a. A bandwidth exceeding 500 MHz; <u>or</u> b. A “fractional bandwidth” of 20% or more; <p>5. Being digitally controlled radio receivers having all of the following:</p> <ul style="list-style-type: none"> a. More than 1,000 channels; b. A ‘channel switching time’ of less than 1 ms; c. Automatic searching or scanning of a part of the electromagnetic spectrum; <u>and</u> d. Identification of the received signals or the type of transmitter; <u>or</u>

Category Code	Item Description
	<p data-bbox="481 329 542 357"><u>Note</u></p> <p data-bbox="481 371 1143 468">Category Code 5A001.b.5. does not include radio equipment specially designed for use with civil cellular radio-communications systems.</p> <p data-bbox="481 487 666 515"><u>Technical Note</u></p> <p data-bbox="481 529 1143 763">'Channel switching time' means the time (i.e. delay) to change from one receiving frequency to another, to arrive at or within $\pm 0.05\%$ of the final specified receiving frequency. Items having a specified frequency range of less than $\pm 0.05\%$ around their centre frequency are defined to be incapable of channel frequency switching.</p> <p data-bbox="417 782 1143 879">6. Employing functions of digital "signal processing" to provide 'voice coding' output at rates of less than 2,400 bit/s.</p> <p data-bbox="481 898 677 927"><u>Technical Notes</u></p> <ol data-bbox="505 940 1143 1258" style="list-style-type: none"> <li data-bbox="505 940 1143 1037">1. For variable rate 'voice coding', Category Code 5A001.b.6. applies to the 'voice coding' output of continuous speech. <li data-bbox="505 1056 1143 1258">2. For the purpose of Category Code 5A001.b.6., 'voice coding' is defined as the technique to take samples of human voice and then convert these samples into a digital signal, taking into account specific characteristics of human speech. <p data-bbox="354 1277 1143 1374">c. Optical fibres of more than 500 m in length and specified by the manufacturer as being capable of withstanding a 'proof test' tensile stress of 2×10^9 N/m² or more;</p> <p data-bbox="417 1393 475 1422"><u>N.B.</u></p> <p data-bbox="417 1435 1143 1502">For underwater umbilical cables, see Category Code 8A002.a.3.</p>

Category Code	Item Description
	<p data-bbox="417 321 602 354"><u>Technical Note</u></p> <p data-bbox="417 363 1146 601"><i>‘Proof Test’: on-line or off-line production screen testing that dynamically applies a prescribed tensile stress over a 0.5 m to 3 m length of fibre at a running rate of 2 m/s to 5 m/s while passing between capstans approximately 150 mm in diameter. The ambient temperature is a nominal 293 K (20°C) and relative humidity 40%. Equivalent national standards may be used for executing the proof test.</i></p> <p data-bbox="350 616 1146 683">d. “Electronically steerable phased array antennae” operating above 31.8 GHz;</p> <p data-bbox="417 700 478 733"><u>Note</u></p> <p data-bbox="417 742 1146 877"><i>Category Code 5A001.d. does not include “electronically steerable phased array antennae” for landing systems with instruments meeting ICAO standards covering Microwave Landing Systems (MLS).</i></p> <p data-bbox="350 894 1146 997">e. Radio direction finding equipment operating at frequencies above 30 MHz and having all of the following, and specially designed components therefor:</p> <ol data-bbox="417 1014 1146 1163" style="list-style-type: none"> <li data-bbox="417 1014 1146 1047">1. “Instantaneous bandwidth” of 10 MHz or more; <u>and</u> <li data-bbox="417 1064 1146 1163">2. Capable of finding a Line Of Bearing (LOB) to non-cooperating radio transmitters with a signal duration of less than 1 ms; <p data-bbox="350 1180 1146 1283">f. Mobile telecommunications interception or jamming equipment, and monitoring equipment therefor, as follows, and specially designed components therefor:</p> <ol data-bbox="417 1300 1146 1555" style="list-style-type: none"> <li data-bbox="417 1300 1146 1367">1. Interception equipment designed for the extraction of voice or data, transmitted over the air interface; <li data-bbox="417 1384 1146 1555">2. Interception equipment not specified in Category Code 5A001.f.1., designed for the extraction of client device or subscriber identifiers (e.g. IMSI, TIMSI or IMEI), signalling, or other metadata transmitted over the air interface;

<i>Category Code</i>	<i>Item Description</i>
	<p>3. Jamming equipment specially designed or modified to intentionally and selectively interfere with, deny, inhibit, degrade or seduce mobile telecommunication services and performing any of the following:</p> <ul style="list-style-type: none"> a. Simulate the functions of Radio Access Network (RAN) equipment; b. Detect and exploit specific characteristics of the mobile telecommunications protocol employed (e.g. GSM); <u>or</u> c. Exploit specific characteristics of the mobile telecommunications protocol employed (e.g. GSM); <p>4. RF monitoring equipment designed or modified to identify the operation of items specified in Category Code 5A001.f.1., 5A001.f.2. or 5A001.f.3.;</p> <p><u>Note</u> <i>Category Codes 5A001.f.1. and 5A001.f.2. do not include any of the following:</i></p> <ul style="list-style-type: none"> a. <i>Equipment specially designed for the interception of analogue Private Mobile Radio (PMR), IEEE 802.11 WLAN;</i> b. <i>Equipment designed for mobile telecommunications network operators; <u>or</u></i> c. <i>Equipment designed for the “development” or “production” of mobile telecommunications equipment or systems.</i> <p><u>N.B. 1</u> <i>See also Division 2 of Part 1 of this Schedule.</i></p> <p><u>N.B. 2</u> <i>For radio receivers, see Category Code 5A001.b.5.</i></p>

<i>Category Code</i>	<i>Item Description</i>
	<p data-bbox="350 325 1146 458">g. Passive Coherent Location (PCL) systems or equipment, specially designed for detecting and tracking moving objects by measuring reflections of ambient radio frequency emissions, supplied by non-radar transmitters;</p> <p data-bbox="417 477 602 506"><u>Technical Note</u></p> <p data-bbox="417 519 1139 582"><i>Non-radar transmitters may include commercial radio, television or cellular telecommunications base stations.</i></p> <p data-bbox="417 601 478 630"><u>Note</u></p> <p data-bbox="413 643 1146 706"><i>Category Code 5A001.g. does not include any of the following:</i></p> <p data-bbox="417 725 1146 843"> <i>a. Radio-astronomical equipment; <u>or</u></i> <i>b. Systems or equipment, that require any radio transmission from the target.</i> </p> <p data-bbox="350 862 1146 925">h. Counter Improvised Explosive Device (IED) equipment and related equipment, as follows:</p> <p data-bbox="417 944 1146 1229"> 1. Radio Frequency (RF) transmitting equipment, not specified in Category Code 5A001.f., designed or modified for prematurely activating or preventing the initiation of Improvised Explosive Devices; 2. Equipment using techniques designed to enable radio communications in the same frequency channels on which co-located equipment specified in Category Code 5A001.h.1. is transmitting; </p> <p data-bbox="417 1249 478 1277"><u>N.B.</u></p> <p data-bbox="417 1290 962 1319"><i>See also Division 2 of Part 1 of this Schedule.</i></p> <p data-bbox="350 1338 534 1367">i. Not used;</p> <p data-bbox="350 1386 1146 1490">j. Internet Protocol (IP) network communications surveillance systems or equipment, and specially designed components therefor, having all of the following:</p> <p data-bbox="417 1509 1146 1730"> 1. Performing all of the following on a carrier class Internet Protocol (IP) network (e.g. national grade IP backbone): <ul style="list-style-type: none"> <li data-bbox="498 1624 1146 1730">a. Analysis at the application layer (e.g. Layer 7 of Open Systems Interconnection (OSI) model (ISO/IEC 7498-1)); </p>

<i>Category Code</i>	<i>Item Description</i>
	<ul style="list-style-type: none"> b. Extraction of selected metadata and application content (e.g. voice, video, messages, attachments); <u>and</u> c. Indexing of extracted data; <u>and</u> <p>2. Being specially designed to carry out all of the following:</p> <ul style="list-style-type: none"> a. Execution of searches on the basis of ‘hard selectors’; <u>and</u> <p><u>Technical Note</u> ‘Hard selectors’ means data or set of data, related to an individual (e.g. family name, given name, e-mail, street address, phone number or group affiliations).</p> <ul style="list-style-type: none"> b. Mapping of the relational network of an individual or of a group of people. <p><u>Note</u> Category Code 5A001.j. does not include systems or equipment, specially designed for any of the following:</p> <ul style="list-style-type: none"> a. Marketing purposes; b. Network Quality of Service (QoS); <u>or</u> c. Quality of Experience (QoE).
5A101	<p>Telemetry and telecontrol equipment, including ground equipment, designed or modified for ‘missiles’.</p> <p><u>Technical Note</u> In Category Code 5A101, ‘missile’ means complete rocket systems and unmanned aerial vehicle systems capable of a range exceeding 300 km.</p> <p><u>Note</u> Category Code 5A101 does not include:</p> <ul style="list-style-type: none"> a. Equipment designed or modified for manned aircraft or satellites;

Category Code	Item Description
	<p>b. <i>Ground based equipment designed or modified for terrestrial or marine applications;</i></p> <p>c. <i>Equipment designed for commercial, civil or ‘Safety of Life’ (e.g. data integrity, flight safety) GNSS services.</i></p>
<p>5B1</p>	<p>Test, Inspection and Production Equipment</p>
<p>5B001</p>	<p>Telecommunications test, inspection and production equipment, components and accessories, as follows:</p> <p>a. Equipment and specially designed components or accessories therefor, specially designed for the “development” or “production” of equipment, functions or features, specified in Category Code 5A001;</p> <p><i>Note</i> <i>Category Code 5B001.a. does not include optical fibre characterisation equipment.</i></p> <p>b. Equipment and specially designed components or accessories therefor, specially designed for the “development” of any of the following telecommunication transmission or switching equipment:</p> <ol style="list-style-type: none"> 1. Not used; 2. Equipment employing a “laser” and having any of the following: <ol style="list-style-type: none"> a. A transmission wavelength exceeding 1,750 nm; b. Performing “optical amplification” using praseodymium-doped fluoride fibre amplifiers (PDFFA); c. Employing coherent optical transmission or coherent optical detection techniques; <u>or</u> <p><i>Note</i> <i>Category Code 5B001.b.2.c. includes equipment specially designed for the “development” of systems using an optical local oscillator in the receiving side to synchronise with a carrier “laser”.</i></p>

Category Code	Item Description
	<p data-bbox="568 325 749 357"><u>Technical Note</u></p> <p data-bbox="568 369 1143 502"><i>For the purpose of Category Code 5B001.b.2.c., these techniques include optical heterodyne, homodyne or intradyne techniques.</i></p> <p data-bbox="505 521 1143 586">d. Employing analogue techniques and having a bandwidth exceeding 2.5 GHz; <u>or</u></p> <p data-bbox="568 605 628 637"><u>Note</u></p> <p data-bbox="568 649 1143 744"><i>Category Code 5B001.b.2.d. does not include equipment specially designed for the “development” of commercial TV systems.</i></p> <p data-bbox="420 763 599 795">3. Not used;</p> <p data-bbox="420 814 1143 879">4. Radio equipment employing Quadrature-Amplitude-Modulation (QAM) techniques above level 256;</p> <p data-bbox="420 898 599 931">5. Not used.</p>
5C1	<p data-bbox="357 997 478 1030">Materials</p> <p data-bbox="357 1049 427 1081">None.</p>
5D1 5D001	<p data-bbox="357 1150 471 1182">Software</p> <p data-bbox="357 1201 626 1233">“Software” as follows:</p> <p data-bbox="357 1252 1143 1353">a. “Software” specially designed or modified for the “development”, “production” or “use” of equipment, functions or features, specified in Category Code 5A001;</p> <p data-bbox="357 1372 534 1405">b. Not used;</p> <p data-bbox="357 1424 1143 1519">c. Specific “software” specially designed or modified to provide characteristics, functions or features of equipment, specified in Category Code 5A001 or 5B001;</p>

<i>Category Code</i>	<i>Item Description</i>
	<p>d. “Software” specially designed or modified for the “development” of any of the following telecommunication transmission or switching equipment:</p> <ol style="list-style-type: none"> 1. Not used; 2. Equipment employing a “laser” and having any of the following: <ol style="list-style-type: none"> a. A transmission wavelength exceeding 1,750 nm; <u>or</u> b. Employing analogue techniques and having a bandwidth exceeding 2.5 GHz; <u>or</u> <p style="text-align: center;"><i>Note</i> <i>Category Code 5D001.d.2.b. does not include “software” specially designed or modified for the “development” of commercial TV systems.</i></p> 3. Not used; 4. Radio equipment employing Quadrature-Amplitude-Modulation (QAM) techniques above level 256.
5D101	“Software” specially designed or modified for the “use” of equipment specified in Category Code 5A101.
5E1	Technology
5E001	<p>“Technology”, as follows:</p> <ol style="list-style-type: none"> a. “Technology” (according to the General Technology Note) for the “development”, “production” or “use” (excluding operation) of equipment, functions or features specified in Category Code 5A001 or “software” specified in Category Code 5D001.a.; b. Specific “technology” as follows: <ol style="list-style-type: none"> 1. “Required” “technology” for the “development” or “production” of telecommunications equipment specially designed to be used on board satellites;

<i>Category Code</i>	<i>Item Description</i>
	<p data-bbox="417 325 1145 491">2. “Technology” for the “development” or “use” of “laser” communication techniques with the capability of automatically acquiring and tracking signals and maintaining communications through exoatmosphere or sub-surface (water) media;</p> <p data-bbox="417 510 1145 710">3. “Technology” for the “development” of digital cellular radio base station receiving equipment whose reception capabilities that allow multi-band, multi-channel, multi-mode, multi-coding algorithm or multi-protocol operation can be modified by changes in “software”;</p> <p data-bbox="417 729 1145 830">4. “Technology” for the “development” of “spread spectrum” techniques, including “frequency hopping” techniques;</p> <p data-bbox="481 849 542 877"><u>Note</u></p> <p data-bbox="481 891 1145 991"><i>Category Code 5E001.b.4. does not apply to “technology” for the “development” of any of the following:</i></p> <p data-bbox="502 1011 1145 1073">a. <i>Civil cellular radio-communications systems;</i> <i>or</i></p> <p data-bbox="502 1092 1145 1155">b. <i>Fixed or mobile satellite earth stations for commercial civil telecommunications.</i></p> <p data-bbox="354 1174 1145 1275">c. “Technology” (according to the General Technology Note) for the “development” or “production” of any of the following:</p> <p data-bbox="417 1294 1145 1395">1. Equipment employing digital techniques designed to operate at a “total digital transfer rate” exceeding 560 Gbit/s;</p> <p data-bbox="481 1414 666 1443"><u>Technical Note</u></p> <p data-bbox="481 1456 1145 1586"><i>For telecommunication switching equipment the “total digital transfer rate” is the unidirectional speed of a single interface, measured at the highest speed port or line.</i></p>

<i>Category Code</i>	<i>Item Description</i>
	<p>2. Equipment employing a “laser” and having any of the following:</p> <ol style="list-style-type: none"> a. A transmission wavelength exceeding 1,750 nm; b. Performing “optical amplification” using Praseodymium-Doped Fluoride Fibre Amplifiers (PDFFA); c. Employing coherent optical transmission or coherent optical detection techniques; <p><i>Note</i> <i>Category Code 5E001.c.2.c. includes “technology” for the “development” or “production” of systems using an optical local oscillator in the receiving side to synchronise with a carrier “laser”.</i></p> <p><i>Technical Note</i> <i>For the purpose of Category Code 5E001.c.2.c., these techniques include optical heterodyne, homodyne or intradyne techniques.</i></p> <ol style="list-style-type: none"> d. Employing wavelength division multiplexing techniques of optical carriers at less than 100 GHz spacing; <u>or</u> e. Employing analogue techniques and having a bandwidth exceeding 2.5 GHz; <p><i>Note</i> <i>Category Code 5E001.c.2.e. does not include “technology” for the “development” or “production” of commercial TV systems.</i></p> <p><i>N.B.</i> <i>For “technology” for the “development” or “production” of non-telecommunications equipment employing a laser, see Category 6E.</i></p> <p>3. Equipment employing “optical switching” and having a switching time less than 1 ms;</p>

Category Code	Item Description
	<p data-bbox="417 325 1032 357">4. Radio equipment having any of the following:</p> <p data-bbox="502 376 1142 439">a. Quadrature-Amplitude-Modulation (QAM) techniques above level 256;</p> <p data-bbox="502 458 1142 521">b. Operating at input or output frequencies exceeding 31.8 GHz; <u>or</u></p> <p data-bbox="565 544 628 576"><i>Note</i></p> <p data-bbox="565 586 1142 820"><i>Category Code 5E001.c.4.b. does not include “technology” for the “development” or “production” of equipment designed or modified for operation in any frequency band which is “allocated by the ITU” for radio-communications services, but not for radio-determination.</i></p> <p data-bbox="502 839 1142 972">c. Operating in the 1.5 MHz to 87.5 MHz band and incorporating adaptive techniques providing more than 15 dB suppression of an interfering signal; <u>or</u></p> <p data-bbox="417 991 599 1024">5. Not used;</p> <p data-bbox="417 1043 1032 1075">6. Mobile equipment having all of the following:</p> <p data-bbox="502 1094 1142 1195">a. Operating at an optical wavelength greater than or equal to 200 nm and less than or equal to 400 nm; <u>and</u></p> <p data-bbox="502 1214 1002 1247">b. Operating as a “local area network”;</p> <p data-bbox="354 1266 1142 1429">d. “Technology” (according to the General Technology Note) for the “development” or “production” of Microwave Monolithic Integrated Circuit (MMIC) power amplifiers specially designed for telecommunications and that are any of the following:</p> <p data-bbox="417 1448 602 1481"><i>Technical Note</i></p> <p data-bbox="417 1490 1142 1658"><i>For the purpose of Category Code 5E001.d., the parameter peak saturated power output may also be referred to on product data sheets as output power, saturated power output, maximum power output, peak power output, or peak envelope power output.</i></p>

<i>Category Code</i>	<i>Item Description</i>
	<ol style="list-style-type: none"> <li data-bbox="417 325 1153 929">1. Rated for operation at frequencies exceeding 2.7 GHz up to and including 6.8 GHz with a “fractional bandwidth” greater than 15%, and having any of the following: <ol style="list-style-type: none"> <li data-bbox="502 477 1153 573">a. A peak saturated power output greater than 75 W (48.75 dBm) at any frequency exceeding 2.7 GHz up to and including 2.9 GHz; <li data-bbox="502 592 1153 687">b. A peak saturated power output greater than 55 W (47.4 dBm) at any frequency exceeding 2.9 GHz up to and including 3.2 GHz; <li data-bbox="502 706 1153 801">c. A peak saturated power output greater than 40 W (46 dBm) at any frequency exceeding 3.2 GHz up to and including 3.7 GHz; <u>or</u> <li data-bbox="502 820 1153 915">d. A peak saturated power output greater than 20 W (43 dBm) at any frequency exceeding 3.7 GHz up to and including 6.8 GHz; <li data-bbox="417 948 1153 1315">2. Rated for operation at frequencies exceeding 6.8 GHz up to and including 16 GHz with a “fractional bandwidth” greater than 10%, and having any of the following: <ol style="list-style-type: none"> <li data-bbox="502 1100 1153 1195">a. A peak saturated power output greater than 10 W (40 dBm) at any frequency exceeding 6.8 GHz up to and including 8.5 GHz; <u>or</u> <li data-bbox="502 1214 1153 1309">b. A peak saturated power output greater than 5 W (37 dBm) at any frequency exceeding 8.5 GHz up to and including 16 GHz; <li data-bbox="417 1334 1153 1467">3. Rated for operation with a peak saturated power output greater than 3 W (34.77 dBm) at any frequency exceeding 16 GHz up to and including 31.8 GHz, and with a “fractional bandwidth” of greater than 10%; <li data-bbox="417 1487 1153 1582">4. Rated for operation with a peak saturated power output greater than 0.1 nW (-70 dBm) at any frequency exceeding 31.8 GHz up to and including 37 GHz; <li data-bbox="417 1601 1153 1734">5. Rated for operation with a peak saturated power output greater than 1 W (30 dBm) at any frequency exceeding 37 GHz up to and including 43.5 GHz, and with a “fractional bandwidth” of greater than 10%;

<i>Category Code</i>	<i>Item Description</i>
5E101	<p>6. Rated for operation with a peak saturated power output greater than 31.62 mW (15 dBm) at any frequency exceeding 43.5 GHz up to and including 75 GHz, and with a “fractional bandwidth” of greater than 10%;</p> <p>7. Rated for operation with a peak saturated power output greater than 10 mW (10 dBm) at any frequency exceeding 75 GHz up to and including 90 GHz, and with a “fractional bandwidth” of greater than 5%; <u>or</u></p> <p>8. Rated for operation with a peak saturated power output greater than 0.1 nW (-70 dBm) at any frequency exceeding 90 GHz;</p> <p>e. “Technology” (according to the General Technology Note) for the “development” or “production” of electronic devices and circuits, specially designed for telecommunications and containing components manufactured from “superconductive” materials, specially designed for operation at temperatures below the “critical temperature” of at least one of the “superconductive” constituents and having any of the following:</p> <ol style="list-style-type: none"> 1. Current switching for digital circuits using “superconductive” gates with a product of delay time per gate (in seconds) and power dissipation per gate (in watts) of less than 10^{-14} J; <u>or</u> 2. Frequency selection at all frequencies using resonant circuits with Q-values exceeding 10,000.
	<p>“Technology” (according to the General Technology Note) for the “development”, “production” or “use” of equipment specified in Category Code 5A101.</p>

Category Code	Item Description
---------------	------------------

Part 2 — “INFORMATION SECURITY”

Note 1

Category 5 – Part 2 concerns “information security” items or functions whether or not they are components, “software” or functions of other systems or equipment.

Note 2

Category 5 – Part 2 does not include products when accompanying their user for the user’s personal use.

Note 3

Cryptography Note

Category Codes 5A002 and 5D002 do not include goods as follows:

- a. *Goods that meet all of the following:*
 1. *Generally available to the public by being sold, without restriction, from stock at retail selling points by means of any of the following:*
 - a. *Over-the-counter transactions;*
 - b. *Mail order transactions;*
 - c. *Electronic transactions; or*
 - d. *Telephone call transactions;*
 2. *The cryptographic functionality cannot easily be changed by the user; and*
 3. *Designed for installation by the user without further substantial support by the supplier;*
- b. *Hardware components or ‘executable software’, of existing goods described in paragraph a. of this Note, that have been designed for these existing items, meeting all of the following:*
 1. *“Information security” is not the primary function or set of functions of the component or ‘executable software’;*
 2. *The component or ‘executable software’ does not change any cryptographic functionality of the existing items, or add new cryptographic functionality to the existing items; and*
 3. *The feature set of the component or ‘executable software’ is fixed and is not designed or modified to customer specification.*

Category Code	Item Description
---------------	------------------

Technical Note

For the purpose of the Cryptography Note, ‘executable software’ means “software” in executable form, from an existing hardware component excluded from Category Code 5A002 by the Cryptography Note.

Note

‘Executable software’ does not include complete binary images of the “software” running on an end-item.

Note to the Cryptography Note

1. *To meet paragraph a. of Note 3, all of the following must apply:*
 - a. *The item is of potential interest to a wide range of individuals and businesses; and*
 - b. *The price and information about the main functionality of the item are available before purchase without the need to consult the vendor or supplier.*
2. *In determining eligibility of paragraph a. of Note 3, factors such as quantity, price, required technical skill, existing sales channels, typical customers, typical use or any exclusionary practices of the supplier may be taken into account.*

Note 4

Category 5 – Part 2 does not include goods incorporating or using “cryptography” and meeting all of the following:

- a. *The primary function or set of functions is not any of the following:*
 1. *“Information security”;*
 2. *A computer, including operating systems, parts and components therefor;*
 3. *Sending, receiving or storing information (except in support of entertainment, mass commercial broadcasts, digital rights management or medical records management); or*
 4. *Networking (includes operation, administration, management and provisioning); and*
- b. *The cryptographic functionality is limited to supporting their primary function or set of functions.*

<i>Category Code</i>	<i>Item Description</i>
<p>5A2</p> <p>5A002</p>	<p>Systems, Equipment and Components</p> <p>“Information security” systems, equipment and components therefor, as follows:</p> <p>a. Systems, equipment and components for “information security”, as follows:</p> <p><u><i>N.B.</i></u></p> <p><i>For Global Navigation Satellite Systems (GNSS) receiving equipment containing or employing decryption, see Category Code 7A005 and for related decryption “software” and “technology”, see Category Codes 7D005 and 7E001.</i></p> <p>1. Designed or modified to use “cryptography” employing digital techniques performing any cryptographic function other than authentication, digital signature or the execution of copy-protected “software”, and having any of the following:</p> <p><u><i>Technical Notes</i></u></p> <p>1. <i>Functions for authentication, digital signature and the execution of copy-protected “software” include their associated key management function.</i></p> <p>2. <i>Authentication includes all aspects of access control where there is no encryption of files or text except as directly related to the protection of passwords, Personal Identification Numbers (PINs) or similar data to prevent unauthorised access.</i></p> <p>a. A “symmetric algorithm” employing a key length in excess of 56 bits; <u>or</u></p> <p><u><i>Technical Note</i></u></p> <p><i>In Category 5 – Part 2, parity bits are not included in the key length.</i></p>

<i>Category Code</i>	<i>Item Description</i>
	<p>b. An “asymmetric algorithm” where the security of the algorithm is based on any of the following:</p> <ol style="list-style-type: none"> 1. Factorisation of integers in excess of 512 bits (e.g. RSA); 2. Computation of discrete logarithms in a multiplicative group of a finite field of size greater than 512 bits (e.g. Diffie-Hellman over Z/pZ); <u>or</u> 3. Discrete logarithms in a group other than mentioned in Category Code 5A002.a.1.b.2. in excess of 112 bits (e.g. Diffie-Hellman over an elliptic curve); <p>2. Designed or modified to perform ‘cryptanalytic functions’;</p> <p><u>Note</u> <i>Category Code 5A002.a.2. includes systems or equipment, designed or modified to perform ‘cryptanalytic functions’ by means of reverse engineering.</i></p> <p><u>Technical Note</u> <i>‘Cryptanalytic functions’ are functions designed to defeat cryptographic mechanisms in order to derive confidential variables or sensitive data, including clear text, passwords or cryptographic keys.</i></p> <ol style="list-style-type: none"> 3. Not used; 4. Specially designed or modified to reduce the compromising emanations of information-bearing signals beyond what is necessary for health, safety or electromagnetic interference standards; 5. Designed or modified to use cryptographic techniques to generate the spreading code for “spread spectrum” systems, other than those specified in Category Code 5A002.a.6., including the hopping code for “frequency hopping” systems;

<i>Category Code</i>	<i>Item Description</i>
	<p>6. Designed or modified to use cryptographic techniques to generate channelising codes, scrambling codes or network identification codes, for systems using ultra-wideband modulation techniques and having any of the following:</p> <ul style="list-style-type: none"> a. A bandwidth exceeding 500 MHz; <u>or</u> b. A “fractional bandwidth” of 20% or more; <p>7. Non-cryptographic Information and Communications Technology (ICT) security systems and devices that have been evaluated and certified by a national authority to exceed class EAL-6 (evaluation assurance level) of the Common Criteria (CC) or equivalent;</p> <p>8. Communications cable systems designed or modified using mechanical, electrical or electronic means to detect surreptitious intrusion;</p> <p><i>Note</i> <i>Category Code 5A002.a.8. applies only to physical layer security.</i></p> <p>9. Designed or modified to use or perform “quantum cryptography”;</p> <p><i>Technical Note</i> <i>“Quantum cryptography” is also known as Quantum Key Distribution (QKD).</i></p> <p>b. Systems, equipment and components, designed or modified to enable, by means of “cryptographic activation” an item to achieve or exceed the controlled performance levels for functionality specified by Category Code 5A002.a. that would not otherwise be enabled.</p>

Category Code	Item Description
	<p data-bbox="354 329 413 357"><u>Note</u></p> <p data-bbox="354 369 1075 401">Category Code 5A002 does not include any of the following:</p> <p data-bbox="354 420 1099 453">a. Smart cards and smart card ‘readers/writers’ as follows:</p> <p data-bbox="419 472 1143 573">1. A smart card or an electronically readable personal document (e.g. token coin, e-passport) that meets any of the following:</p> <p data-bbox="502 592 1143 788">a. The cryptographic capability is restricted for use in equipment or systems excluded from Category Code 5A002 by Note 4 in Category 5 – Part 2 or entries d. to i. of this Note, and cannot be reprogrammed for any other use; <u>or</u></p> <p data-bbox="502 807 897 839">b. Having all of the following:</p> <p data-bbox="569 858 1143 959">1. It is specially designed and limited to allow protection of ‘personal data’ stored within;</p> <p data-bbox="569 978 1143 1079">2. Has been, or can only be, personalised for public or commercial transactions or individual identification; <u>and</u></p> <p data-bbox="569 1098 1143 1163">3. Where the cryptographic capability is not user accessible;</p> <p data-bbox="569 1182 749 1214"><u>Technical Note</u></p> <p data-bbox="569 1226 1143 1353">‘Personal data’ includes any data specific to a particular person or entity, such as the amount of money stored and data necessary for authentication.</p> <p data-bbox="419 1372 1143 1437">2. ‘Readers/writers’ specially designed or modified, and limited, for items specified in a.1. of this Note;</p> <p data-bbox="481 1456 663 1488"><u>Technical Note</u></p> <p data-bbox="481 1500 1143 1601">‘Readers/writers’ include equipment that communicates with smart cards or electronically readable documents through a network.</p> <p data-bbox="354 1620 534 1652">b. Not used;</p> <p data-bbox="354 1671 534 1704">c. Not used;</p>

Category Code	Item Description
	<p>d. <i>Cryptographic equipment specially designed and limited for banking use or 'money transactions';</i></p> <p><u>Technical Note</u> <i>'Money transactions' in Category Code 5A002 Note d. includes the collection and settlement of fares or credit functions.</i></p> <p>e. <i>Portable or mobile radiotelephones for civil use (e.g. for use with commercial civil cellular radio communication systems) that are not capable of transmitting encrypted data directly to another radiotelephone or equipment (other than Radio Access Network (RAN) equipment), nor of passing encrypted data through RAN equipment (e.g. Radio Network Controller (RNC) or Base Station Controller (BSC));</i></p> <p>f. <i>Cordless telephone equipment not capable of end-to-end encryption where the maximum effective range of unboosted cordless operation (i.e. a single, unrelayed hop between terminal and home base station) is less than 400 metres according to the manufacturer's specifications;</i></p> <p>g. <i>Portable or mobile radiotelephones and similar client wireless devices for civil use, that implement only published or commercial cryptographic standards (except for anti-piracy functions, which may be non-published) and also meet the provisions of paragraphs a.2. and a.3. of the Cryptography Note (Note 3 in Category 5 – Part 2), that have been customised for a specific civil industry application with features that do not affect the cryptographic functionality of these original non-customised devices;</i></p> <p>h. <i>Not used;</i></p> <p>i. <i>Wireless "personal area network" equipment that implement only published or commercial cryptographic standards and where the cryptographic capability is limited to a nominal operating range not exceeding 30 metres according to the manufacturer's specifications, or not exceeding 100 metres according to the manufacturer's specifications for equipment that cannot interconnect with more than seven devices;</i></p>

Category Code	Item Description
	<p>j. <i>Equipment, having no functionality specified by Category Code 5A002.a.2., 5A002.a.4., 5A002.a.7., 5A002.a.8. or 5A002.b., where all cryptographic capability specified by Category Code 5A002.a. meets any of the following:</i></p> <ol style="list-style-type: none"> 1. <i>It cannot be used; <u>or</u></i> 2. <i>It can only be made useable by means of “cryptographic activation”;</i> <p><u>N.B.1</u> <i>See Category Code 5A002.a. for equipment that has undergone “cryptographic activation”.</i></p> <p><u>N.B.2</u> <i>See also Category Codes 5A002.b., 5D002.d. and 5E002.b.</i></p> <p>k. <i>Mobile telecommunications Radio Access Network (RAN) equipment designed for civil use, which also meet the provisions of paragraphs a.2. and a.3. of the Cryptography Note (Note 3 to Category 5 – Part 2), having an RF output power limited to 0.1 W (20 dBm) or less, and supporting 16 or fewer concurrent users;</i></p> <ol style="list-style-type: none"> l. <i>Routers, switches or relays, where the “information security” functionality is limited to the tasks of “Operations, Administration or Maintenance” (“OAM”) implementing only published or commercial cryptographic standards; <u>or</u></i> <p>m. <i>General purpose computing equipment or servers, where the “information security” functionality meets all of the following:</i></p> <ol style="list-style-type: none"> 1. <i>Uses only published or commercial cryptographic standards; <u>and</u></i> 2. <i>Is any of the following:</i> <ol style="list-style-type: none"> a. <i>Integral to a CPU that meets the provisions of Note 3 to Category 5 – Part 2;</i> b. <i>Integral to an operating system that is not specified by Category Code 5D002; <u>or</u></i> c. <i>Limited to “OAM” of the equipment.</i>

<i>Category Code</i>	<i>Item Description</i>
5B2	Test, Inspection and Production Equipment
5B002	<p>“Information security” test, inspection and “production” equipment, as follows:</p> <ol style="list-style-type: none"> a. Equipment specially designed for the “development” or “production” of equipment specified in Category Code 5A002 or 5B002.b.; b. Measuring equipment specially designed to evaluate and validate the “information security” functions of the equipment specified in Category Code 5A002 or “software” specified in Category Code 5D002.a. or 5D002.c.
5C2	<p>Materials</p> <p>None.</p>
5D2	Software
5D002	<p>“Software” as follows:</p> <ol style="list-style-type: none"> a. “Software” specially designed or modified for the “development”, “production” or “use” of equipment specified in Category Code 5A002 or “software” specified in Category Code 5D002.c.; b. “Software” specially designed or modified to support “technology” specified in Category Code 5E002; c. Specific “software”, as follows: <ol style="list-style-type: none"> 1. “Software” having the characteristics, or performing or simulating the functions of the equipment specified in Category Code 5A002; 2. “Software” to certify “software” specified in Category Code 5D002.c.1.; <p><i>Note</i></p> <p><i>Category Code 5D002.c. does not apply to “software” limited to the tasks of “OAM” implementing only published or commercial cryptographic standards.</i></p>

<i>Category Code</i>	<i>Item Description</i>
<p>5E2 5E002</p>	<p>d. “Software” designed or modified to enable, by means of “cryptographic activation”, an item to achieve or exceed the controlled performance levels for functionality specified by Category Code 5A002.a. that would not otherwise be enabled.</p> <p>Technology</p> <p>“Technology” as follows:</p> <p>a. “Technology” (according to the General Technology Note) for the “development”, “production” or “use” of equipment specified in Category Code 5A002, 5B002 or “software” specified in Category Code 5D002.a. or 5D002.c.;</p> <p>b. “Technology” to enable, by means of “cryptographic activation”, an item to achieve or exceed the controlled performance levels for functionality specified by Category Code 5A002.a. that would not otherwise be enabled.</p> <p><u>Note</u></p> <p><i>Category Code 5E002 includes “information security” technical data resulting from procedures carried out to evaluate or determine the implementation of functions, features or techniques specified in Category 5 – Part 2.</i></p>

<i>Category Code</i>	<i>Item Description</i>
CATEGORY 6 — SENSORS AND LASERS	
6A	Systems, Equipment and Components
6A001	<p>Acoustic systems, equipment and components, as follows:</p> <ol style="list-style-type: none"> a. Marine acoustic systems, equipment and specially designed components therefor, as follows: <ol style="list-style-type: none"> 1. Active (transmitting or transmitting-and-receiving) systems, equipment and specially designed components therefor, as follows: <p><i>Note</i> Category Code 6A001.a.1. does not include equipment as follows:</p> <ol style="list-style-type: none"> a. <i>Depth sounders operating vertically below the apparatus, not including a scanning function exceeding $\pm 20^\circ$, and limited to measuring the depth of water, the distance of submerged or buried objects or fish finding;</i> b. <i>Acoustic beacons, as follows:</i> <ol style="list-style-type: none"> 1. <i>Acoustic emergency beacons;</i> 2. <i>Pingers specially designed for relocating or returning to an underwater position.</i> a. Acoustic seabed survey equipment as follows: <ol style="list-style-type: none"> 1. Surface vessel survey equipment designed for seabed topographic mapping and having all of the following: <ol style="list-style-type: none"> a. Designed to take measurements at an angle exceeding 20° from the vertical; b. Designed to measure seabed topography at seabed depths exceeding 600 m;

<i>Category Code</i>	<i>Item Description</i>
	<p data-bbox="633 325 1139 388">c. 'Sounding resolution' less than 2; <u>and</u></p> <p data-bbox="633 407 1139 506">d. 'Enhancement' of the depth accuracy through compensation for all of the following:</p> <ol data-bbox="696 525 1139 725" style="list-style-type: none"> <li data-bbox="696 525 1139 557">1. Motion of the acoustic sensor; <li data-bbox="696 576 1139 675">2. In-water propagation from sensor to the seabed and back; <u>and</u> <li data-bbox="696 694 1139 725">3. Sound speed at the sensor; <p data-bbox="633 744 827 776"><u>Technical Notes</u></p> <ol data-bbox="633 795 1139 1011" style="list-style-type: none"> <li data-bbox="633 795 1139 925">1. 'Sounding resolution' is the swath width (degrees) divided by the maximum number of soundings per swath. <li data-bbox="633 944 1139 1011">2. 'Enhancement' includes the ability to compensate by external means. <p data-bbox="569 1030 1139 1129">2. Underwater survey equipment designed for seabed topographic mapping and having any of the following:</p> <p data-bbox="633 1148 817 1180"><u>Technical Note</u></p> <p data-bbox="633 1190 1139 1319"><i>The acoustic sensor pressure rating determines the depth rating of the equipment specified in Category Code 6A001.a.1.a.2.</i></p> <ol data-bbox="633 1338 1139 1572" style="list-style-type: none"> <li data-bbox="633 1338 1139 1370">a. Having all of the following: <ol data-bbox="696 1389 1139 1572" style="list-style-type: none"> <li data-bbox="696 1389 1139 1488">1. Designed or modified to operate at depths exceeding 300 m; <u>and</u> <li data-bbox="696 1507 1139 1572">2. 'Sounding rate' greater than 3,800 m/s; <u>or</u>

Category Code	Item Description
	<p data-bbox="758 325 942 357"><u>Technical Note</u></p> <p data-bbox="758 369 1145 738"><i>'Sounding rate' is the product of the maximum speed (m/s) at which the sensor can operate and the maximum number of soundings per swath assuming 100% coverage. For systems that produce soundings in two directions (3D sonars), the maximum of the 'sounding rate' in either direction should be used.</i></p> <p data-bbox="628 757 1145 1652"> b. Survey equipment, not specified in Category Code 6A001.a.1.a.2.a., having all of the following: <ol style="list-style-type: none"> <li data-bbox="696 877 1145 972">1. Designed or modified to operate at depths exceeding 100 m; <li data-bbox="696 997 1145 1092">2. Designed to take measurements at an angle exceeding 20° from the vertical; <li data-bbox="696 1117 1145 1416">3. Having any of the following: <ol style="list-style-type: none"> <li data-bbox="763 1169 1145 1233">a. Operating frequency below 350 kHz; <u>or</u> <li data-bbox="763 1252 1145 1416">b. Designed to measure seabed topography at a range exceeding 200 m from the acoustic sensor; <u>and</u> <li data-bbox="696 1435 1145 1652">4. 'Enhancement' of the depth accuracy through compensation of all of the following: <ol style="list-style-type: none"> <li data-bbox="763 1595 1145 1652">a. Motion of the acoustic sensor; </p>

<i>Category Code</i>	<i>Item Description</i>
	<p style="margin-left: 40px;">b. In-water propagation from sensor to the seabed and back; <u>and</u></p> <p style="margin-left: 40px;">c. Sound speed at the sensor;</p> <p>3. Side Scan Sonar (SSS) or Synthetic Aperture Sonar (SAS), designed for seabed imaging and having all of the following, and specially designed transmitting and receiving acoustic arrays therefor:</p> <p style="margin-left: 20px;">a. Designed or modified to operate at depths exceeding 500 m;</p> <p style="margin-left: 20px;">b. An ‘area coverage rate’ of greater than 570 m²/s while operating at the maximum range that it can operate with an ‘along track resolution’ of less than 15 cm; <u>and</u></p> <p style="margin-left: 20px;">c. An ‘across track resolution’ of less than 15 cm;</p> <p><u>Technical Notes</u></p> <p>1. ‘Area coverage rate’ (m²/s) is twice the product of the sonar range (m) and the maximum speed (m/s) at which the sensor can operate at that range.</p> <p>2. ‘Along track resolution’ (cm), for SSS only, is the product of azimuth (horizontal) beamwidth (degrees) and sonar range (m) and 0.873.</p> <p>3. ‘Across track resolution’ (cm) is 75 divided by the signal bandwidth (kHz).</p>

<i>Category Code</i>	<i>Item Description</i>
	<p>b. Systems or transmitting and receiving arrays, designed for object detection or location, having any of the following:</p> <ol style="list-style-type: none"> 1. A transmitting frequency below 10 kHz; 2. Sound pressure level exceeding 224 dB (reference 1 μPa at 1 m) for equipment with an operating frequency in the band from 10 kHz to 24 kHz inclusive; 3. Sound pressure level exceeding 235 dB (reference 1 μPa at 1 m) for equipment with an operating frequency in the band between 24 kHz and 30 kHz; 4. Forming beams of less than 1° on any axis and having an operating frequency of less than 100 kHz; 5. Designed to operate with an unambiguous display range exceeding 5,120 m; <u>or</u> 6. Designed to withstand pressure during normal operation at depths exceeding 1,000 m and having transducers with any of the following: <ol style="list-style-type: none"> a. Dynamic compensation for pressure; <u>or</u> b. Incorporating other than lead zirconate titanate as the transduction element;

Category Code	Item Description
	<p>c. Acoustic projectors (including transducers), incorporating piezoelectric, magnetostrictive, electrostrictive, electrodynamic or hydraulic elements operating individually or in a designed combination, and having any of the following:</p> <p><u>Note 1</u> <i>Whether acoustic projectors (including transducers), which are not specified by Category Code 6A001 and which are specially designed for other equipment, is included in Category Code 6A001.c. is determined by whether the other equipment is specified in Division 2 of Part 2 of this Schedule.</i></p> <p><u>Note 2</u> <i>Category Code 6A001.a.1.c. does not include electronic sources which direct the sound vertically only, or mechanical (e.g. air gun or vapour-shock gun) or chemical (e.g. explosive) sources.</i></p> <p><u>Note 3</u> <i>Piezoelectric elements specified in Category Code 6A001.a.1.c. include those made from lead-magnesium-niobate/lead-titanate ($Pb(Mg_{1/3}Nb_{2/3})O_3$-$PbTiO_3$, or PMN-PT) single crystals grown from solid solution or lead-indium-niobate/lead-magnesium-niobate/lead-titanate ($Pb(In_{1/2}Nb_{1/2})O_3$-$Pb(Mg_{1/3}Nb_{2/3})O_3$-$PbTiO_3$, or PIN-PMN-PT) single crystals grown from solid solution.</i></p>

<i>Category Code</i>	<i>Item Description</i>
	<p>1. Operating at frequencies below 10 kHz and having any of the following:</p> <ol style="list-style-type: none"> a. Not designed for continuous operation at 100% duty cycle and having a radiated ‘free-field Source Level (SL_{RMS})’ exceeding $(10\log(f) + 169.77)$ dB (reference 1 μPa at 1 m) where f is the frequency in Hertz of maximum Transmitting Voltage Response (TVR) below 10 kHz; <u>or</u> b. Designed for continuous operation at 100% duty cycle and having a continuously radiated ‘free-field Source Level (SL_{RMS})’ at 100% duty cycle exceeding $(10\log(f) + 159.77)$ dB (reference 1 μPa at 1 m) where f is the frequency in Hertz of maximum Transmitting Voltage Response (TVR) below 10 kHz; <u>or</u> <p><i>Technical Note</i> <i>The ‘free-field Source Level (SL_{RMS})’ is defined along the maximum response axis and in the far field of the acoustic projector. It can be obtained from the Transmitting Voltage Response using the following equation: $SL_{RMS} = (TVR + 20\log V_{RMS})$ dB (reference 1 μPa at 1 m), where SL_{RMS} is the source level, TVR is the Transmitting Voltage Response and V_{RMS} is the Driving Voltage of the Projector.</i></p> <ol style="list-style-type: none"> 2. Not used; 3. Side-lobe suppression exceeding 22 dB;

Category Code	Item Description
	<p>d. Acoustic systems and equipment, designed to determine the position of surface vessels or underwater vehicles and having all of the following, and specially designed components therefor:</p> <ol style="list-style-type: none"> 1. Detection range exceeding 1,000 m; <u>and</u> 2. Positioning accuracy of less than 10 m rms (root mean square) when measured at a range of 1,000 m; <p><u>Note</u> <i>Category Code 6A001.a.1.d. includes:</i></p> <ol style="list-style-type: none"> a. <i>Equipment using coherent “signal processing” between two or more beacons and the hydrophone unit carried by the surface vessel or underwater vehicle;</i> b. <i>Equipment capable of automatically correcting speed-of-sound propagation errors for calculation of a point.</i> <p>e. Active individual sonars, specially designed or modified to detect, locate and automatically classify swimmers or divers, having all of the following, and specially designed transmitting and receiving acoustic arrays therefor:</p> <ol style="list-style-type: none"> 1. Detection range exceeding 530 m; 2. Positioning accuracy of less than 15 m rms (root mean square) when measured at a range of 530 m; <u>and</u> 3. Transmitted pulse signal bandwidth exceeding 3 kHz; <p><u>N.B.</u> <i>For diver detection systems specially designed or modified for military use, see Division 2 of Part 1 of this Schedule.</i></p>

Category Code	Item Description
	<p data-bbox="565 325 626 354"><u>Note</u></p> <p data-bbox="565 367 1139 500"><i>For Category Code 6A001.a.1.e., where multiple detection ranges are specified for various environments, the greatest detection range is used.</i></p> <p data-bbox="417 519 1139 582">2. Passive systems, equipment and specially designed components therefor, as follows:</p> <p data-bbox="502 601 1072 634">a. Hydrophones having any of the following:</p> <p data-bbox="565 653 626 681"><u>Note</u></p> <p data-bbox="565 694 1139 862"><i>Whether hydrophones specially designed for other equipment is included in Category Code 6A001.a.2.a. is determined by whether the other equipment is included in that Category Code.</i></p> <p data-bbox="565 881 749 910"><u>Technical Note</u></p> <p data-bbox="565 923 1139 1056"><i>Hydrophones consist of one or more sensing elements producing a single acoustic output channel. Those that contain multiple elements can be referred to as a hydrophone group.</i></p> <ol data-bbox="565 1075 1139 1666" style="list-style-type: none"> <li data-bbox="565 1075 1139 1138">1. Incorporating continuous flexible sensing elements; <li data-bbox="565 1157 1139 1325">2. Incorporating flexible assemblies of discrete sensing elements with either a diameter or length less than 20 mm and with a separation between elements of less than 20 mm; <li data-bbox="565 1344 1139 1666">3. Having any of the following sensing elements: <ol data-bbox="626 1429 1139 1666" style="list-style-type: none"> <li data-bbox="626 1429 865 1462">a. Optical fibres; <li data-bbox="626 1481 1139 1614">b. ‘Piezoelectric polymer films’ other than polyvinylidene-fluoride (PVDF) and its co-polymers {P(VDF-TrFE) and P(VDF-TFE)}; <li data-bbox="626 1633 1120 1666">c. ‘Flexible piezoelectric composites’;

<i>Category Code</i>	<i>Item Description</i>
	<p>d. Lead-magnesium-niobate/lead-titanate (i.e. $\text{Pb}(\text{Mg}_{1/3}\text{Nb}_{2/3})\text{O}_3$-$\text{PbTiO}_3$, or PMN-PT) piezoelectric single crystals grown from solid solution; <u>or</u></p> <p>e. Lead-indium-niobate/lead-magnesium-niobate/lead-titanate (i.e. $\text{Pb}(\text{In}_{1/2}\text{Nb}_{1/2})\text{O}_3$-$\text{Pb}(\text{Mg}_{1/3}\text{Nb}_{2/3})\text{O}_3$-$\text{PbTiO}_3$, or PIN-PMN-PT) piezoelectric single crystals grown from solid solution;</p> <p>4. A ‘hydrophone sensitivity’ better than -180 dB at any depth with no acceleration compensation;</p> <p>5. Designed to operate at depths exceeding 35 m with acceleration compensation; <u>or</u></p> <p>6. Designed for operation at depths exceeding 1,000 m;</p> <p><i><u>Technical Notes</u></i></p> <p>1. ‘Piezoelectric polymer film’ sensing elements consist of polarised polymer film that is stretched over and attached to a supporting frame or spool (mandrel).</p> <p>2. ‘Flexible piezoelectric composite’ sensing elements consist of piezoelectric ceramic particles or fibres combined with an electrically insulating, acoustically transparent rubber, polymer or epoxy compound, where the compound is an integral part of the sensing elements.</p>

Category Code	Item Description
	<p data-bbox="569 325 1145 763">3. 'Hydrophone sensitivity' is defined as twenty times the logarithm to the base 10 of the ratio of rms output voltage to a 1 V rms reference, when the hydrophone sensor, without a pre-amplifier, is placed in a plane wave acoustic field with an rms pressure of 1 μPa. For example, a hydrophone of -160 dB (reference 1 V per μPa) would yield an output voltage of 10^{-8} V in such a field, while one of -180 dB sensitivity would yield only 10^{-9} V output. Thus, -160 dB is better than -180 dB.</p> <p data-bbox="505 782 1145 845">b. Towed acoustic hydrophone arrays having any of the following:</p> <p data-bbox="569 864 753 896"><u>Technical Note</u></p> <p data-bbox="569 906 1145 1005"><i>Hydrophone arrays consist of a number of hydrophones providing multiple acoustic output channels.</i></p> <ol data-bbox="569 1024 1145 1245" style="list-style-type: none"> 1. Hydrophone group spacing of less than 12.5 m or 'able to be modified' to have hydrophone group spacing of less than 12.5 m; 2. Designed or 'able to be modified' to operate at depths exceeding 35 m; <p data-bbox="569 1264 753 1296"><u>Technical Note</u></p> <p data-bbox="569 1306 1145 1643"><i>'Able to be modified' in Category Codes 6A001.a.2.b.1. and 2. means having provisions to allow a change of the wiring or interconnections to alter hydrophone group spacing or operating depth limits. These provisions are: spare wiring exceeding 10% of the number of wires, hydrophone group spacing adjustment blocks or internal depth limiting devices that are adjustable or that control more than one hydrophone group.</i></p>

<i>Category Code</i>	<i>Item Description</i>
	<ol style="list-style-type: none"> 3. Heading sensors specified in Category Code 6A001.a.2.d.; 4. Longitudinally reinforced array hoses; 5. An assembled array of less than 40 mm in diameter; 6. Not used; 7. Hydrophone characteristics specified in Category Code 6A001.a.2.a.; <u>or</u> 8. Accelerometer-based hydro-acoustic sensors specified in Category Code 6A001.a.2.g.; <p>c. Processing equipment, specially designed for towed acoustic hydrophone arrays, having “user accessible programmability” and time or frequency domain processing and correlation, including spectral analysis, digital filtering and beamforming using Fast Fourier or other transforms or processes;</p> <p>d. Heading sensors having all of the following:</p> <ol style="list-style-type: none"> 1. An accuracy of better than $\pm 0.5^\circ$; <u>and</u> 2. Designed to operate at depths exceeding 35 m or having an adjustable or removable depth sensing device in order to operate at depths exceeding 35 m; <p>e. Bottom or bay-cable hydrophone arrays, having any of the following:</p> <ol style="list-style-type: none"> 1. Incorporating hydrophones specified in Category Code 6A001.a.2.a.;

<i>Category Code</i>	<i>Item Description</i>
	<p>2. Incorporating multiplexed hydrophone group signal modules having all of the following characteristics:</p> <ul style="list-style-type: none"> a. Designed to operate at depths exceeding 35 m or having an adjustable or removable depth sensing device in order to operate at depths exceeding 35 m; <u>and</u> b. Capable of being operationally interchanged with towed acoustic hydrophone array modules; <u>or</u> <p>3. Incorporating accelerometer-based hydro-acoustic sensors specified in Category Code 6A001.a.2.g.;</p> <p>f. Processing equipment, specially designed for bottom or bay cable systems, having “user accessible programmability” and time or frequency domain processing and correlation, including spectral analysis, digital filtering and beamforming using Fast Fourier or other transforms or processes;</p> <p>g. Accelerometer-based hydro-acoustic sensors having all of the following:</p> <ul style="list-style-type: none"> 1. Composed of three accelerometers arranged along three distinct axes; 2. Having an overall ‘acceleration sensitivity’ better than 48 dB (reference 1,000 mV rms per 1 g); 3. Designed to operate at depths greater than 35 m; <u>and</u> 4. Operating frequency below 20 kHz; <p><u>Note</u> <i>Category Code 6A001.a.2.g. does not include particle velocity sensors or geophones.</i></p>

Category Code	Item Description
	<p data-bbox="569 325 763 357"><u>Technical Notes</u></p> <ol data-bbox="569 369 1139 687" style="list-style-type: none"> <li data-bbox="569 369 1139 434">1. Accelerometer-based hydro-acoustic sensors are also known as vector sensors. <li data-bbox="569 453 1139 687">2. 'Acceleration sensitivity' is defined as twenty times the logarithm to the base 10 of the ratio of rms output voltage to a 1 V rms reference, when the hydro-acoustic sensor, without a preamplifier, is placed in a plane wave acoustic field with an rms acceleration of 1 g (i.e. 9.81 m/s²). <p data-bbox="420 706 478 738"><u>Note</u></p> <p data-bbox="420 750 1139 877">Category Code 6A001.a.2. also includes receiving equipment, whether or not related in normal application to separate active equipment, and specially designed components therefor.</p> <ol data-bbox="357 902 1139 1334" style="list-style-type: none"> <li data-bbox="357 902 1139 997">b. Correlation-velocity and Doppler-velocity sonar log equipment, designed to measure the horizontal speed of the equipment carrier relative to the seabed, as follows: <ol data-bbox="420 1016 1139 1334" style="list-style-type: none"> <li data-bbox="420 1016 1139 1169">1. Correlation-velocity sonar log equipment having any of the following characteristics: <ol data-bbox="505 1106 1139 1252" style="list-style-type: none"> <li data-bbox="505 1106 1139 1169">a. Designed to operate at distances between the carrier and the seabed exceeding 500 m; <u>or</u> <li data-bbox="505 1188 1139 1252">b. Having speed accuracy better than 1% of speed; <li data-bbox="420 1271 1139 1334">2. Doppler-velocity sonar log equipment having speed accuracy better than 1% of speed; <p data-bbox="420 1353 501 1386"><u>Note 1</u></p> <p data-bbox="420 1397 1139 1462">Category Code 6A001.b. does not include depth sounders limited to any of the following:</p> <ol data-bbox="420 1481 1139 1646" style="list-style-type: none"> <li data-bbox="420 1481 844 1513">a. Measuring the depth of water; <li data-bbox="420 1532 1139 1597">b. Measuring the distance of submerged or buried objects; <u>or</u> <li data-bbox="420 1616 635 1646">c. Fish finding.

Category Code	Item Description
6A002	<p data-bbox="417 325 498 354"><u>Note 2</u></p> <p data-bbox="417 367 1139 434"><i>Category Code 6A001.b. does not include equipment specially designed for installation on surface vessels.</i></p> <p data-bbox="354 453 534 481">c. Not used.</p> <p data-bbox="354 554 1139 620">Optical sensors or equipment and components therefor, as follows:</p> <p data-bbox="354 639 408 668"><u>N.B.</u></p> <p data-bbox="354 681 731 710"><i>See also Category Code 6A102.</i></p> <p data-bbox="354 729 758 757">a. Optical detectors as follows:</p> <p data-bbox="417 776 1076 805">1. “Space-qualified” solid-state detectors as follows:</p> <p data-bbox="481 830 542 858"><u>Note</u></p> <p data-bbox="481 872 1139 938"><i>For the purpose of Category Code 6A002.a.1., solid-state detectors include “focal plane arrays”.</i></p> <p data-bbox="502 957 1139 1024">a. “Space-qualified” solid-state detectors having all of the following:</p> <ol data-bbox="569 1043 1139 1252" style="list-style-type: none"> <li data-bbox="569 1043 1139 1138">1. A peak response in the wavelength range exceeding 10 nm but not exceeding 300 nm; <u>and</u> <li data-bbox="569 1157 1139 1252">2. A response of less than 0.1% relative to the peak response at a wavelength exceeding 400 nm; <p data-bbox="502 1271 1139 1338">b. “Space-qualified” solid-state detectors having all of the following:</p> <ol data-bbox="569 1357 1139 1547" style="list-style-type: none"> <li data-bbox="569 1357 1139 1452">1. A peak response in the wavelength range exceeding 900 nm but not exceeding 1,200 nm; <u>and</u> <li data-bbox="569 1471 1139 1547">2. A response “time constant” of 95 ns or less; <p data-bbox="502 1566 1139 1690">c. “Space-qualified” solid-state detectors having a peak response in the wavelength range exceeding 1,200 nm but not exceeding 30,000 nm;</p>

Category Code	Item Description
	<p data-bbox="508 325 1145 458">d. “Space-qualified” “focal plane arrays” having more than 2,048 elements per array and having a peak response in the wavelength range exceeding 300 nm but not exceeding 900 nm;</p> <p data-bbox="419 477 1145 544">2. Image intensifier tubes and specially designed components therefor, as follows:</p> <p data-bbox="481 563 545 592"><u>Note</u></p> <p data-bbox="481 601 1145 734"><i>Category Code 6A002.a.2. does not include non-imaging photomultiplier tubes having an electron sensing device in the vacuum space limited solely to any of the following:</i></p> <p data-bbox="508 753 868 782">a. <i>A single metal anode; <u>or</u></i></p> <p data-bbox="508 801 1145 868">b. <i>Metal anodes with a centre-to-centre spacing greater than 500 μm.</i></p> <p data-bbox="481 887 669 915"><u>Technical Note</u></p> <p data-bbox="481 925 1145 1134"><i>‘Charge multiplication’ is a form of electronic image amplification and is defined as the generation of charge carriers as a result of an impact ionisation gain process. ‘Charge multiplication’ sensors may take the form of an image intensifier tube, solid state detector or “focal plane array”.</i></p> <p data-bbox="508 1153 1145 1220">a. Image intensifier tubes having all of the following:</p> <p data-bbox="572 1239 1145 1334">1. A peak response in the wavelength range exceeding 400 nm but not exceeding 1,050 nm;</p> <p data-bbox="572 1353 1145 1420">2. Electron image amplification using any of the following:</p> <p data-bbox="637 1439 1145 1534">a. A microchannel plate with a hole pitch (centre-to-centre spacing) of 12 μm or less; <u>or</u></p> <p data-bbox="637 1553 1145 1753">b. An electron sensing device with a non-binned pixel pitch of 500 μm or less, specially designed or modified to achieve ‘charge multiplication’ other than by a microchannel plate; <u>and</u></p>

<i>Category Code</i>	<i>Item Description</i>
	<ol style="list-style-type: none"> <li data-bbox="569 325 1069 357">3. Any of the following photocathodes: <ol style="list-style-type: none"> <li data-bbox="633 376 1137 477">a. Multialkali photocathodes (e.g. S-20 and S-25) having a luminous sensitivity exceeding 350 $\mu\text{A}/\text{lm}$; <li data-bbox="633 496 1116 529">b. GaAs or GaInAs photocathodes; <u>or</u> <li data-bbox="633 548 1137 677">c. Other “III/V compound” semiconductor photocathodes having a maximum “radiant sensitivity” exceeding 10 mA/W; <li data-bbox="502 696 1137 763">b. Image intensifier tubes having all of the following: <ol style="list-style-type: none"> <li data-bbox="569 782 1137 883">1. A peak response in the wavelength range exceeding 1,050 nm but not exceeding 1,800 nm; <li data-bbox="569 902 1137 969">2. Electron image amplification using any of the following: <ol style="list-style-type: none"> <li data-bbox="633 988 1137 1089">a. A microchannel plate with a hole pitch (centre-to-centre spacing) of 12 μm or less; <u>or</u> <li data-bbox="633 1108 1137 1304">b. An electron sensing device with a non-binned pixel pitch of 500 μm or less, specially designed or modified to achieve ‘charge multiplication’ other than by a microchannel plate; <u>and</u> <li data-bbox="569 1323 1137 1490">3. “III/V compound” semiconductor (e.g. GaAs or GaInAs) photocathodes and transferred electron photocathodes, having a maximum “radiant sensitivity” exceeding 15 mA/W;

Category Code	Item Description
	<p>c. Specially designed components as follows:</p> <ol style="list-style-type: none"> 1. Microchannel plates having a hole pitch (centre-to-centre spacing) of 12 μm or less; 2. An electron sensing device with a non-binned pixel pitch of 500 μm or less, specially designed or modified to achieve ‘charge multiplication’ other than by a microchannel plate; 3. “III/V compound” semiconductor (e.g. GaAs or GaInAs) photocathodes and transferred electron photocathodes; <p><u>Note</u> Category Code 6A002.a.2.c.3. does not include compound semiconductor photocathodes designed to achieve a maximum “radiant sensitivity” of any of the following:</p> <ol style="list-style-type: none"> a. 10 mA/W or less at the peak response in the wavelength range exceeding 400 nm but not exceeding 1,050 nm; <u>or</u> b. 15 mA/W or less at the peak response in the wavelength range exceeding 1,050 nm but not exceeding 1,800 nm. <p>3. Non-“space-qualified” “focal plane arrays” as follows:</p> <p><u>N.B.</u> ‘Microbolometer’ non-“space-qualified” “focal plane arrays” are only specified in Category Code 6A002.a.3.f.</p> <p><u>Technical Note</u> Linear or two-dimensional multi-element detector arrays are referred to as “focal plane arrays”.</p>

Category Code	Item Description
	<p><u>Note 1</u> Category Code 6A002.a.3. includes photoconductive arrays and photovoltaic arrays.</p> <p><u>Note 2</u> Category Code 6A002.a.3. does not include:</p> <ol style="list-style-type: none"> a. Multi-element (not to exceed 16 elements) encapsulated photoconductive cells using either lead sulphide or lead selenide; b. Pyroelectric detectors using any of the following: <ol style="list-style-type: none"> 1. Triglycine sulphate and variants; 2. Lead-lanthanum-zirconium titanate and variants; 3. Lithium tantalate; 4. Polyvinylidene fluoride and variants; <u>or</u> 5. Strontium barium niobate and variants; c. "Focal plane arrays" specially designed or modified to achieve 'charge multiplication' and limited by design to have a maximum "radiant sensitivity" of 10 mA/W or less for wavelengths exceeding 760 nm, having all of the following: <ol style="list-style-type: none"> 1. Incorporating a response limiting mechanism designed not to be removed or modified; <u>and</u> 2. Any of the following: <ol style="list-style-type: none"> a. The response limiting mechanism is integral to or combined with the detector element; <u>or</u> b. The "focal plane array" is only operable with the response limiting mechanism in place.

Category Code	Item Description
	<p data-bbox="633 325 817 357"><u>Technical Note</u></p> <p data-bbox="633 369 1141 502"><i>A response limiting mechanism integral to the detector element is designed not to be removed or modified without rendering the detector inoperable.</i></p> <p data-bbox="569 519 753 552"><u>Technical Note</u></p> <p data-bbox="569 563 1141 801"><i>‘Charge multiplication’ is a form of electronic image amplification and is defined as the generation of charge carriers as a result of an impact ionisation gain process. ‘Charge multiplication’ sensors may take the form of an image intensifier tube, solid state detector or “focal plane array”.</i></p> <p data-bbox="505 814 1141 881">a. Non-“space-qualified” “focal plane arrays” having all of the following:</p> <ol data-bbox="569 900 1141 1287" style="list-style-type: none"> <li data-bbox="569 900 1141 1001">1. Individual elements with a peak response within the wavelength range exceeding 900 nm but not exceeding 1,050 nm; <u>and</u> <li data-bbox="569 1020 1141 1287">2. Any of the following: <ol data-bbox="628 1068 1141 1287" style="list-style-type: none"> <li data-bbox="628 1068 1141 1134">a. A response “time constant” of less than 0.5 ns; <u>or</u> <li data-bbox="628 1153 1141 1287">b. Specially designed or modified to achieve ‘charge multiplication’ and having a maximum “radiant sensitivity” exceeding 10 mA/W; <p data-bbox="505 1306 1141 1372">b. Non-“space-qualified” “focal plane arrays” having all of the following:</p> <ol data-bbox="569 1391 1141 1658" style="list-style-type: none"> <li data-bbox="569 1391 1141 1525">1. Individual elements with a peak response in the wavelength range exceeding 1,050 nm but not exceeding 1,200 nm; <u>and</u> <li data-bbox="569 1544 1141 1658">2. Any of the following: <ol data-bbox="628 1591 1141 1658" style="list-style-type: none"> <li data-bbox="628 1591 1141 1658">a. A response “time constant” of 95 ns or less; <u>or</u>

Category Code	Item Description
	<p>b. Specially designed or modified to achieve ‘charge multiplication’ and having a maximum “radiant sensitivity” exceeding 10 mA/W;</p> <p>c. Non-“space-qualified” non-linear (2-dimensional) “focal plane arrays” having individual elements with a peak response in the wavelength range exceeding 1,200 nm but not exceeding 30,000 nm;</p> <p><u>N.B.</u> <i>Silicon and other material based ‘microbolometer’ non-“space-qualified” “focal plane arrays” are only specified in Category Code 6A002.a.3.f.</i></p> <p>d. Non-“space-qualified” linear (1-dimensional) “focal plane arrays” having all of the following:</p> <ol style="list-style-type: none"> 1. Individual elements with a peak response in the wavelength range exceeding 1,200 nm but not exceeding 3,000 nm; <u>and</u> 2. Any of the following: <ol style="list-style-type: none"> a. A ratio of ‘scan direction’ dimension of the detector element to the ‘cross-scan direction’ dimension of the detector element of less than 3.8; <u>or</u> b. Signal processing in the detector elements; <p><u>Note</u> <i>Category Code 6A002.a.3.d. does not include “focal plane arrays” (not to exceed 32 elements) having detector elements limited solely to germanium material.</i></p>

Category Code	Item Description
	<p data-bbox="569 325 753 357"><u>Technical Note</u></p> <p data-bbox="569 369 1145 573"><i>For the purpose of Category Code 6A002.a.3.d., ‘cross-scan direction’ is defined as the axis parallel to the linear array of detector elements and the ‘scan direction’ is defined as the axis perpendicular to the linear array of detector elements.</i></p> <p data-bbox="505 586 1145 757">e. Non-“space-qualified” linear (1-dimensional) “focal plane arrays” having individual elements with a peak response in the wavelength range exceeding 3,000 nm but not exceeding 30,000 nm;</p> <p data-bbox="505 771 1145 974">f. Non-“space-qualified” non-linear (2-dimensional) infrared “focal plane arrays” based on ‘microbolometer’ material, having individual elements with an unfiltered response in the wavelength range equal to or exceeding 8,000 nm but not exceeding 14,000 nm;</p> <p data-bbox="569 991 753 1024"><u>Technical Note</u></p> <p data-bbox="569 1035 1145 1239"><i>For the purpose of Category Code 6A002.a.3.f., ‘microbolometer’ is defined as a thermal imaging detector that, as a result of a temperature change in the detector caused by the absorption of infrared radiation, is used to generate any usable signal.</i></p> <p data-bbox="505 1252 1145 1321">g. Non-“space-qualified” “focal plane arrays” having all of the following:</p> <ol data-bbox="569 1334 1145 1709" style="list-style-type: none"> <li data-bbox="569 1334 1145 1473">1. Individual detector elements with a peak response in the wavelength range exceeding 400 nm but not exceeding 900 nm; <li data-bbox="569 1487 1145 1658">2. Specially designed or modified to achieve ‘charge multiplication’ and having a maximum “radiant sensitivity” exceeding 10 mA/W for wavelengths exceeding 760 nm; <u>and</u> <li data-bbox="569 1671 1145 1709">3. Greater than 32 elements;

<i>Category Code</i>	<i>Item Description</i>
	<p>b. “Monospectral imaging sensors” and “multispectral imaging sensors”, designed for remote sensing applications and having any of the following:</p> <ol style="list-style-type: none"> 1. An Instantaneous-Field-Of-View (IFOV) of less than 200 μrad (microradians); <u>or</u> 2. Specified for operation in the wavelength range exceeding 400 nm but not exceeding 30,000 nm and having all the following: <ol style="list-style-type: none"> a. Providing output imaging data in digital format; <u>and</u> b. Having any of the following characteristics: <ol style="list-style-type: none"> 1. “Space-qualified”; <u>or</u> 2. Designed for airborne operation, using other than silicon detectors, and having an IFOV of less than 2.5 mrad (milliradians); <p><i>Note</i></p> <p><i>Category Code 6A002.b.1. does not include “monospectral imaging sensors” with a peak response in the wavelength range exceeding 300 nm but not exceeding 900 nm and only incorporating any of the following non-“space-qualified” detectors or non-“space-qualified” “focal plane arrays”:</i></p> <ol style="list-style-type: none"> a. <i>Charged Coupled Devices (CCD) not designed or modified to achieve ‘charge multiplication’; <u>or</u></i> b. <i>Complementary Metal Oxide Semiconductor (CMOS) devices not designed or modified to achieve ‘charge multiplication’.</i> <p>c. ‘Direct view’ imaging equipment incorporating any of the following:</p> <ol style="list-style-type: none"> 1. Image intensifier tubes specified in Category Code 6A002.a.2.a. or 6A002.a.2.b.; 2. “Focal plane arrays” specified in Category Code 6A002.a.3.; <u>or</u> 3. Solid state detectors specified in Category Code 6A002.a.1.;

Category Code	Item Description
	<p data-bbox="419 325 603 357"><u>Technical Note</u></p> <p data-bbox="419 369 1141 535"><i>'Direct view' refers to imaging equipment that presents a visual image to a human observer without converting the image into an electronic signal for television display, and that cannot record or store the image photographically, electronically or by any other means.</i></p> <p data-bbox="419 554 478 586"><u>Note</u></p> <p data-bbox="419 597 1141 696"><i>Category Code 6A002.c. does not include equipment as follows, when incorporating other than GaAs or GaInAs photocathodes:</i></p> <ol style="list-style-type: none"> <li data-bbox="419 715 1141 782">a. <i>Industrial or civilian intrusion alarm, traffic or industrial movement control or counting systems;</i> <li data-bbox="419 801 723 833">b. <i>Medical equipment;</i> <li data-bbox="419 852 1141 919">c. <i>Industrial equipment used for inspection, sorting or analysis of the properties of materials;</i> <li data-bbox="419 938 962 971">d. <i>Flame detectors for industrial furnaces;</i> <li data-bbox="419 990 1069 1022">e. <i>Equipment specially designed for laboratory use.</i> <p data-bbox="357 1041 1126 1073">d. Special support components for optical sensors, as follows:</p> <ol style="list-style-type: none"> <li data-bbox="419 1092 852 1125">1. "Space-qualified" cryocoolers; <li data-bbox="419 1144 1141 1210">2. Non-"space-qualified" cryocoolers having a cooling source temperature below 218 K (-55°C), as follows: <ol style="list-style-type: none"> <li data-bbox="505 1229 1141 1328">a. Closed cycle type with a specified Mean-Time-To-Failure (MTTF) or Mean-Time-Between-Failures (MTBF), exceeding 2,500 hours; <li data-bbox="505 1348 1141 1437">b. Joule-Thomson (JT) self-regulating minicoolers having bore (outside) diameters of less than 8 mm;

Category Code	Item Description
6A003	<p data-bbox="417 325 1139 458">3. Optical sensing fibres specially fabricated either compositionally or structurally, or modified by coating, to be acoustically, thermally, inertially, electromagnetically or nuclear radiation sensitive;</p> <p data-bbox="481 477 542 510"><u>Note</u></p> <p data-bbox="481 519 1139 620"><i>Category Code 6A002.d.3. does not include encapsulated optical sensing fibres specially designed for bore hole sensing applications.</i></p> <p data-bbox="354 639 532 672">e. Not used.</p> <p data-bbox="354 738 1139 801">Cameras, systems or equipment, and components therefor, as follows:</p> <p data-bbox="354 820 411 852"><u>N.B.</u></p> <p data-bbox="354 862 733 894"><i>See also Category Code 6A203.</i></p> <p data-bbox="354 913 411 946"><u>N.B.</u></p> <p data-bbox="354 955 1139 1056"><i>For television and film-based photographic still cameras specially designed or modified for underwater use, see Category Codes 8A002.d.1. and 8A002.e.</i></p> <p data-bbox="354 1075 1139 1138">a. Instrumentation cameras and specially designed components therefor, as follows:</p> <p data-bbox="417 1157 479 1190"><u>Note</u></p> <p data-bbox="417 1199 1139 1367"><i>Instrumentation cameras, specified in Category Codes 6A003.a.3. to 6A003.a.5., with modular structures should be evaluated by their maximum capability, using plug-ins available according to the camera manufacturer's specifications.</i></p> <p data-bbox="417 1386 1139 1553">1. High-speed cinema recording cameras using any film format from 8 mm to 16 mm inclusive, in which the film is continuously advanced throughout the recording period, and that are capable of recording at framing rates exceeding 13,150 frames/s;</p> <p data-bbox="481 1572 542 1605"><u>Note</u></p> <p data-bbox="481 1614 1139 1677"><i>Category Code 6A003.a.1. does not include cinema recording cameras designed for civil purposes.</i></p>

<i>Category Code</i>	<i>Item Description</i>
	<p>2. Mechanical high speed cameras, in which the film does not move, capable of recording at rates exceeding 1,000,000 frames/s for the full framing height of 35 mm film, or at proportionately higher rates for lesser frame heights, or at proportionately lower rates for greater frame heights;</p> <p>3. Mechanical or electronic streak cameras, as follows:</p> <ul style="list-style-type: none"> a. Mechanical streak cameras having writing speeds exceeding 10 mm/μs; b. Electronic streak cameras having temporal resolution better than 50 ns; <p>4. Electronic framing cameras having a speed exceeding 1,000,000 frames/s;</p> <p>5. Electronic cameras having all of the following:</p> <ul style="list-style-type: none"> a. An electronic shutter speed (gating capability) of less than 1 μs per full frame; <u>and</u> b. A read out time allowing a framing rate of more than 125 full frames per second; <p>6. Plug-ins having all of the following characteristics:</p> <ul style="list-style-type: none"> a. Specially designed for instrumentation cameras which have modular structures and which are specified in Category Code 6A003.a.; <u>and</u> b. Enabling these cameras to meet the characteristics specified in Category Code 6A003.a.3., 6A003.a.4. or 6A003.a.5., according to the manufacturer's specifications; <p>b. Imaging cameras as follows:</p> <p><u>Note</u> <i>Category Code 6A003.b. does not include television or video cameras, specially designed for television broadcasting.</i></p>

<i>Category Code</i>	<i>Item Description</i>
	<p>1. Video cameras incorporating solid state sensors, having a peak response in the wavelength range exceeding 10 nm, but not exceeding 30,000 nm and having all of the following:</p> <p>a. Having any of the following:</p> <ol style="list-style-type: none"> 1. More than 4×10^6 “active pixels” per solid state array for monochrome (black and white) cameras; 2. More than 4×10^6 “active pixels” per solid state array for colour cameras incorporating three solid state arrays; <u>or</u> 3. More than 12×10^6 “active pixels” for solid state array colour cameras incorporating one solid state array; <u>and</u> <p>b. Having any of the following:</p> <ol style="list-style-type: none"> 1. Optical mirrors specified in Category Code 6A004.a.; 2. Optical control equipment specified in Category Code 6A004.d.; <u>or</u> 3. The capability for annotating internally generated ‘camera tracking data’; <p><u>Technical Notes</u></p> <ol style="list-style-type: none"> 1. <i>For the purpose of this entry, digital video cameras should be evaluated by the maximum number of “active pixels” used for capturing moving images.</i> 2. <i>For the purpose of this entry, ‘camera tracking data’ is the information necessary to define camera line of sight orientation with respect to the earth. This includes: 1) the horizontal angle the camera line of sight makes with respect to the earth’s magnetic field direction; and 2) the vertical angle between the camera line of sight and the earth’s horizon.</i>

<i>Category Code</i>	<i>Item Description</i>
	<p data-bbox="422 325 1139 392">2. Scanning cameras and scanning camera systems, having all of the following:</p> <ul style="list-style-type: none"> <li data-bbox="505 411 1139 510">a. A peak response in the wavelength range exceeding 10 nm, but not exceeding 30,000 nm; <li data-bbox="505 529 1139 595">b. Linear detector arrays with more than 8,192 elements per array; <u>and</u> <li data-bbox="505 614 1022 643">c. Mechanical scanning in one direction; <p data-bbox="482 662 542 691"><u>Note</u></p> <p data-bbox="482 706 1139 805"><i>Category Code 6A003.b.2. does not include scanning cameras and scanning camera systems, specially designed for any of the following:</i></p> <ul style="list-style-type: none"> <li data-bbox="505 824 989 852"><i>a. Industrial or civilian photocopiers;</i> <li data-bbox="505 872 1139 1043"><i>b. Image scanners specially designed for civil, stationary, close proximity scanning applications (e.g. reproduction of images or print contained in documents, artwork or photographs); <u>or</u></i> <li data-bbox="505 1062 803 1090"><i>c. Medical equipment.</i> <p data-bbox="422 1110 1139 1209">3. Imaging cameras incorporating image intensifier tubes specified in Category Code 6A002.a.2.a. or 6A002.a.2.b.;</p> <p data-bbox="422 1228 1139 1294">4. Imaging cameras incorporating “focal plane arrays” having any of the following:</p> <ul style="list-style-type: none"> <li data-bbox="505 1313 1139 1380">a. Incorporating “focal plane arrays” specified in Category Codes 6A002.a.3.a. to 6A002.a.3.e.; <li data-bbox="505 1399 1139 1466">b. Incorporating “focal plane arrays” specified in Category Code 6A002.a.3.f.; <u>or</u> <li data-bbox="505 1485 1139 1551">c. Incorporating “focal plane arrays” specified in Category Code 6A002.a.3.g.;

Category Code	Item Description
	<p data-bbox="481 325 561 357"><u>Note 1</u></p> <p data-bbox="481 367 1139 571"><i>Imaging cameras specified in Category Code 6A003.b.4. include “focal plane arrays” combined with sufficient “signal processing” electronics, beyond the read out integrated circuit, to enable as a minimum the output of an analogue or digital signal once power is supplied.</i></p> <p data-bbox="481 586 561 618"><u>Note 2</u></p> <p data-bbox="481 628 1139 795"><i>Category Code 6A003.b.4.a. does not include imaging cameras incorporating linear “focal plane arrays” with 12 elements or fewer, not employing time-delay-and-integration within the element and designed for any of the following:</i></p> <ul style="list-style-type: none"> <li data-bbox="502 814 1139 913"><i>a. Industrial or civilian intrusion alarm, traffic or industrial movement control or counting systems;</i> <li data-bbox="502 932 1139 1031"><i>b. Industrial equipment used for inspection or monitoring of heat flows in buildings, equipment or industrial processes;</i> <li data-bbox="502 1051 1139 1150"><i>c. Industrial equipment used for inspection, sorting or analysis of the properties of materials;</i> <li data-bbox="502 1169 1139 1233"><i>d. Equipment specially designed for laboratory use; <u>or</u></i> <li data-bbox="502 1252 803 1285"><i>e. Medical equipment.</i> <p data-bbox="481 1304 561 1336"><u>Note 3</u></p> <p data-bbox="481 1346 1139 1410"><i>Category Code 6A003.b.4.b. does not include imaging cameras having any of the following:</i></p> <ul style="list-style-type: none"> <li data-bbox="502 1429 1139 1494"><i>a. A maximum frame rate equal to or less than 9 Hz;</i> <li data-bbox="502 1513 1139 1698"><i>b. Having all of the following:</i> <ul style="list-style-type: none"> <li data-bbox="569 1563 1139 1698"><i>1. Having a minimum horizontal or vertical ‘Instantaneous-Field-of-View (IFOV)’ of at least 10 mrad/pixel (milliradians/pixel);</i>

Category Code	Item Description
	<ol style="list-style-type: none"> <li data-bbox="569 325 1139 392">2. <i>Incorporating a fixed focal-length lens that is not designed to be removed;</i> <li data-bbox="569 407 1139 474">3. <i>Not incorporating a 'direct view' display; <u>and</u></i> <li data-bbox="569 489 1139 525">4. <i>Having any of the following:</i> <ol style="list-style-type: none"> <li data-bbox="628 540 1139 643">a. <i>No facility to obtain a viewable image of the detected field-of-view; <u>or</u></i> <li data-bbox="628 658 1139 761">b. <i>The camera is designed for a single kind of application and designed not to be user modified; <u>or</u></i> <li data-bbox="505 776 1139 879">c. <i>The camera is specially designed for installation into a civilian passenger land vehicle and having all of the following:</i> <ol style="list-style-type: none"> <li data-bbox="569 894 1139 1030">1. <i>The placement and configuration of the camera within the vehicle are solely to assist the driver in the safe operation of the vehicle;</i> <li data-bbox="569 1045 1139 1111">2. <i>Is only operable when installed in any of the following:</i> <ol style="list-style-type: none"> <li data-bbox="628 1127 1139 1262">a. <i>The civilian passenger land vehicle for which it was intended and the vehicle weighs less than 4,500 kg (gross vehicle weight); <u>or</u></i> <li data-bbox="628 1277 1139 1344">b. <i>A specially designed, authorised maintenance test facility; <u>and</u></i> <li data-bbox="569 1359 1139 1494">3. <i>Incorporates an active mechanism that forces the camera not to function when it is removed from the vehicle for which it was intended.</i>

Category Code	Item Description
	<p data-bbox="569 325 763 354"><u>Technical Notes</u></p> <ol data-bbox="569 376 1139 1030" style="list-style-type: none"> <li data-bbox="569 376 1139 540">1. <i>'Instantaneous-Field-of-View (IFOV)' specified in Category Code 6A003.b.4. Note 3.b. is the lesser figure of the 'Horizontal IFOV' or the 'Vertical IFOV'.</i> <i>'Horizontal IFOV' = horizontal Field of View (FOV) / number of horizontal detector elements</i> <i>'Vertical IFOV' = vertical Field of View (FOV) / number of vertical detector elements</i> <li data-bbox="569 801 1139 1030">2. <i>'Direct view' in Category Code 6A003.b.4. Note 3.b. refers to an imaging camera operating in the infrared spectrum that presents a visual image to a human observer using a near-to-eye micro display incorporating any light-security mechanism.</i> <p data-bbox="482 1052 565 1081"><u>Note 4</u></p> <p data-bbox="482 1096 1139 1157"><i>Category Code 6A003.b.4.c. does not include imaging cameras having any of the following:</i></p> <ol data-bbox="505 1182 1139 1683" style="list-style-type: none"> <li data-bbox="505 1182 897 1210">a. <i>Having all of the following:</i> <ol data-bbox="569 1229 1139 1683" style="list-style-type: none"> <li data-bbox="569 1229 1139 1429">1. <i>Where the camera is specially designed for installation as an integrated component into indoor and wall-plug-operated systems or equipment, limited by design for a single kind of application, as follows:</i> <ol data-bbox="628 1448 1139 1683" style="list-style-type: none"> <li data-bbox="628 1448 1139 1553">a. <i>Industrial process monitoring, quality control, or analysis of the properties of materials;</i> <li data-bbox="628 1572 1139 1629">b. <i>Laboratory equipment specially designed for scientific research;</i> <li data-bbox="628 1648 1139 1683">c. <i>Medical equipment;</i>

Category Code	Item Description
	<p data-bbox="628 325 1139 392">d. Financial fraud detection equipment; <u>and</u></p> <p data-bbox="569 411 1145 477">2. Is only operable when installed in any of the following:</p> <p data-bbox="628 496 1139 563">a. The system(s) or equipment for which it was intended; <u>or</u></p> <p data-bbox="628 582 1139 649">b. A specially designed, authorised maintenance facility; <u>and</u></p> <p data-bbox="569 668 1145 792">3. Incorporates an active mechanism that forces the camera not to function when it is removed from the system(s) or equipment for which it was intended;</p> <p data-bbox="508 811 1145 944">b. Where the camera is specially designed for installation into a civilian passenger land vehicle or passenger and vehicle ferries, and having all of the following:</p> <p data-bbox="569 963 1145 1096">1. The placement and configuration of the camera within the vehicle or ferry is solely to assist the driver or operator in the safe operation of the vehicle or ferry;</p> <p data-bbox="569 1115 1145 1182">2. Is only operable when installed in any of the following:</p> <p data-bbox="628 1201 1139 1334">a. The civilian passenger land vehicle for which it was intended and the vehicle weighs less than 4,500 kg (gross vehicle weight);</p> <p data-bbox="628 1353 1139 1487">b. The passenger and vehicle ferry for which it was intended and having a length overall (LOA) 65 m or greater; <u>or</u></p> <p data-bbox="628 1506 1139 1572">c. A specially designed, authorised maintenance test facility; <u>and</u></p> <p data-bbox="569 1591 1145 1715">3. Incorporates an active mechanism that forces the camera not to function when it is removed from the vehicle for which it was intended;</p>

Category Code	Item Description
	<p data-bbox="502 325 1139 424">c. Limited by design to have a maximum “radiant sensitivity” of 10 mA/W or less for wavelengths exceeding 760 nm, having all of the following:</p> <ol data-bbox="569 443 1139 776" style="list-style-type: none"> <li data-bbox="569 443 1139 542">1. Incorporating a response limiting mechanism designed not to be removed or modified; <li data-bbox="569 561 1139 691">2. Incorporates an active mechanism that forces the camera not to function when the response limiting mechanism is removed; <u>and</u> <li data-bbox="569 710 1139 776">3. Not specially designed or modified for underwater use; <u>or</u> <p data-bbox="502 795 897 830">d. Having all of the following:</p> <ol data-bbox="569 849 1139 1296" style="list-style-type: none"> <li data-bbox="569 849 1139 910">1. Not incorporating a ‘direct view’ or electronic image display; <li data-bbox="569 929 1139 995">2. Has no facility to output a viewable image of the detected field of view; <li data-bbox="569 1014 1139 1113">3. The “focal plane array” is only operable when installed in the camera for which it was intended; <u>and</u> <li data-bbox="569 1132 1139 1296">4. The “focal plane array” incorporates an active mechanism that forces it to be permanently inoperable when removed from the camera for which it was intended. <p data-bbox="422 1315 1139 1382">5. Imaging cameras incorporating solid-state detectors specified by Category Code 6A002.a.1.</p>

Category Code	Item Description
6A004	<p>Optical equipment and components, as follows:</p> <p>a. Optical mirrors (reflectors) as follows:</p> <p><i>Technical Note</i> <i>For the purpose of Category Code 6A004.a., Laser Induced Damage Threshold (LIDT) is measured according to ISO 21254-1:2011.</i></p> <p><i>N.B.</i> <i>For optical mirrors specially designed for lithography equipment, see Category Code 3B001.</i></p> <ol style="list-style-type: none"> 1. “Deformable mirrors” having an active optical aperture greater than 10 mm and having any of the following, and specially designed components therefor: <ol style="list-style-type: none"> a. Having all the following: <ol style="list-style-type: none"> 1. A mechanical resonant frequency of 750 Hz or more; <u>and</u> 2. More than 200 actuators; <u>or</u> b. A Laser Induced Damage Threshold (LIDT) being any of the following: <ol style="list-style-type: none"> 1. Greater than 1 kW/cm² using a “CW laser”; <u>or</u> 2. Greater than 2 J/cm² using 20 ns “laser” pulses at 20 Hz repetition rate; 2. Lightweight monolithic mirrors having an average “equivalent density” of less than 30 kg/m² and a total mass exceeding 10 kg; 3. Lightweight “composite” or foam mirror structures having an average “equivalent density” of less than 30 kg/m² and a total mass exceeding 2 kg; 4. Mirrors specially designed for beam steering mirror stages specified in Category Code 6A004.d.2.a. with a flatness of $\lambda/10$ or better (λ is equal to 633 nm) and having any of the following: <ol style="list-style-type: none"> a. Diameter or major axis length greater than or equal to 100 mm; <u>or</u>

<i>Category Code</i>	<i>Item Description</i>
	<ul style="list-style-type: none"> b. Having all of the following: <ul style="list-style-type: none"> 1. Diameter or major axis length greater than 50 mm but less than 100 mm; <u>and</u> 2. A Laser Induced Damage Threshold (LIDT) being any of the following: <ul style="list-style-type: none"> a. Greater than 10 kW/cm² using a “CW laser”; <u>or</u> b. Greater than 20 J/cm² using 20 ns “laser” pulses at 20 Hz repetition rate; b. Optical components made from zinc selenide (ZnSe) or zinc sulphide (ZnS) with transmission in the wavelength range exceeding 3,000 nm but not exceeding 25,000 nm and having any of the following: <ul style="list-style-type: none"> 1. Exceeding 100 cm³ in volume; <u>or</u> 2. Exceeding 80 mm in diameter or length of major axis and 20 mm in thickness (depth); c. “Space-qualified” components for optical systems, as follows: <ul style="list-style-type: none"> 1. Components lightweighted to less than 20% “equivalent density” compared with a solid blank of the same aperture and thickness; 2. Raw substrates, processed substrates having surface coatings (single-layer or multi-layer, metallic or dielectric, conducting, semiconducting or insulating) or having protective films; 3. Segments or assemblies of mirrors designed to be assembled in space into an optical system with a collecting aperture equivalent to or larger than a single optic 1 m in diameter; 4. Components manufactured from “composite” materials having a coefficient of linear thermal expansion equal to or less than 5×10^{-6} in any coordinate direction;

<i>Category Code</i>	<i>Item Description</i>
	<p>d. Optical control equipment as follows:</p> <ol style="list-style-type: none"> 1. Equipment specially designed to maintain the surface figure or orientation of the “space-qualified” components specified in Category Code 6A004.c.1. or 6A004.c.3.; 2. Steering, tracking, stabilisation and resonator alignment equipment as follows: <ol style="list-style-type: none"> a. Beam steering mirror stages designed to carry mirrors having diameter or major axis length greater than 50 mm and having all of the following, and specially designed electronic control equipment therefor: <ol style="list-style-type: none"> 1. A maximum angular travel of ± 26 mrad or more; 2. A mechanical resonant frequency of 500 Hz or more; <u>and</u> 3. An angular accuracy of 10 μrad (microradians) or less; b. Resonator alignment equipment having bandwidths equal to or more than 100 Hz and an accuracy of 10 μrad or less; 3. Gimbals having all of the following: <ol style="list-style-type: none"> a. A maximum slew exceeding 5°; b. A bandwidth of 100 Hz or more; c. Angular pointing errors of 200 μrad (microradians) or less; <u>and</u> d. Having any of the following: <ol style="list-style-type: none"> 1. Exceeding 0.15 m but not exceeding 1 m in diameter or major axis length and capable of angular accelerations exceeding 2 rad (radians)/s²; <u>or</u> 2. Exceeding 1 m in diameter or major axis length and capable of angular accelerations exceeding 0.5 rad (radians)/s²;

Category Code	Item Description
	<p>4. Not used;</p> <p>e. ‘Aspheric optical elements’ having all of the following:</p> <ol style="list-style-type: none"> 1. Largest dimension of the optical-aperture greater than 400 mm; 2. Surface roughness less than 1 nm (rms) for sampling lengths equal to or greater than 1 mm; <u>and</u> 3. Coefficient of linear thermal expansion’s absolute magnitude less than $3 \times 10^{-6}/\text{K}$ at 25°C. <p><u>Technical Notes</u></p> <ol style="list-style-type: none"> 1. An ‘aspheric optical element’ is any element used in an optical system whose imaging surface or surfaces are designed to depart from the shape of an ideal sphere. 2. It is not necessary to evaluate the surface roughness of the optical element against the criteria in Category Code 6A004.e.2. unless the optical element was designed or manufactured with the intent to meet, or exceed the control parameter. <p><u>Note</u></p> <p>Category Code 6A004.e. does not include ‘aspheric optical elements’ having any of the following:</p> <ol style="list-style-type: none"> a. Largest optical-aperture dimension less than 1 m and focal length to aperture ratio equal to or greater than 4.5:1; b. Largest optical-aperture dimension equal to or greater than 1 m and focal length to aperture ratio equal to or greater than 7:1; c. Designed as Fresnel, flyeye, stripe, prism or diffractive optical elements; d. Fabricated from borosilicate glass having a coefficient of linear thermal expansion greater than $2.5 \times 10^{-6}/\text{K}$ at 25°C; <u>or</u> e. An X-ray optical element having inner mirror capabilities (e.g. tube-type mirrors).

Category Code	Item Description
6A005	<p><u>N.B.</u> For 'aspheric optical elements' specially designed for lithography equipment, see Category Code 3B001.</p> <p>"Lasers", other than those specified in Category Code 0B001.g.5. or 0B001.h.6., components and optical equipment, as follows:</p> <p><u>N.B.</u> See also Category Code 6A205.</p> <p><u>Note 1</u> Pulsed "lasers" include those that run in a continuous wave (CW) mode with pulses superimposed.</p> <p><u>Note 2</u> Excimer, semiconductor, chemical, CO, CO₂, and 'non-repetitive pulsed' Nd:glass "lasers" are only specified in Category Code 6A005.d.</p> <p><u>Technical Note</u> 'Non-repetitive pulsed' refers to "lasers" that produce either a single output pulse or that have a time interval between pulses exceeding one minute.</p> <p><u>Note 3</u> Category Code 6A005 includes fibre "lasers".</p> <p><u>Note 4</u> The control status of "lasers" incorporating frequency conversion (i.e. wavelength change) by means other than one "laser" pumping another "laser" is determined by applying the control parameters for both the output of the source "laser" and the frequency-converted optical output.</p> <p><u>Note 5</u> Category Code 6A005 does not include "lasers" as follows:</p> <ol style="list-style-type: none"> a. Ruby with output energy below 20 J; b. Nitrogen; c. Krypton.

Category Code	Item Description
	<p data-bbox="354 325 538 357"><u>Technical Note</u></p> <p data-bbox="354 367 1139 535"><i>In Category Code 6A005, 'Wall-plug efficiency' is defined as the ratio of "laser" output power (or "average output power") to total electrical input power required to operate the "laser", including the power supply/conditioning and thermal conditioning/heat exchanger.</i></p> <p data-bbox="354 554 1139 616">a. Non-"tunable" continuous wave "(CW) lasers" having any of the following:</p> <ol data-bbox="422 635 1139 788" style="list-style-type: none"> <li data-bbox="422 635 1139 698">1. Output wavelength less than 150 nm and output power exceeding 1 W; <li data-bbox="422 717 1139 788">2. Output wavelength of 150 nm or more but not exceeding 510 nm and output power exceeding 30 W; <p data-bbox="481 807 542 839"><u>Note</u></p> <p data-bbox="481 849 1139 944"><i>Category Code 6A005.a.2. does not include Argon "lasers" having an output power equal to or less than 50 W.</i></p> <ol data-bbox="422 963 1139 1536" style="list-style-type: none"> <li data-bbox="422 963 1139 1201">3. Output wavelength exceeding 510 nm but not exceeding 540 nm and any of the following: <ol data-bbox="502 1049 1139 1201" style="list-style-type: none"> <li data-bbox="502 1049 1139 1111">a. Single transverse mode output and output power exceeding 50 W; <u>or</u> <li data-bbox="502 1130 1139 1201">b. Multiple transverse mode output and output power exceeding 150 W; <li data-bbox="422 1220 1139 1283">4. Output wavelength exceeding 540 nm but not exceeding 800 nm and output power exceeding 30 W; <li data-bbox="422 1302 1139 1536">5. Output wavelength exceeding 800 nm but not exceeding 975 nm and any of the following: <ol data-bbox="502 1378 1139 1536" style="list-style-type: none"> <li data-bbox="502 1378 1139 1441">a. Single transverse mode output and output power exceeding 50 W; <u>or</u> <li data-bbox="502 1460 1139 1536">b. Multiple transverse mode output and output power exceeding 80 W;

Category Code	Item Description
	<p data-bbox="422 325 1145 392">6. Output wavelength exceeding 975 nm but not exceeding 1,150 nm and any of the following:</p> <ul style="list-style-type: none"> <li data-bbox="505 411 1145 477">a. Single transverse mode output and output power exceeding 200 W; <u>or</u> <li data-bbox="505 496 1145 696">b. Multiple transverse mode output and any of the following: <ul style="list-style-type: none"> <li data-bbox="569 582 1145 649">1. ‘Wall-plug efficiency’ exceeding 18% and output power exceeding 500 W; <u>or</u> <li data-bbox="569 668 1009 696">2. Output power exceeding 2 kW; <p data-bbox="569 715 650 744"><u>Note 1</u></p> <p data-bbox="569 753 1145 1058"><i>Category Code 6A005.a.6.b. does not include multiple transverse mode, industrial “lasers” with output power exceeding 2 kW and not exceeding 6 kW with a total mass greater than 1,200 kg. For the purpose of this Note, total mass includes all components required to operate the “laser”, e.g. “laser”, power supply, heat exchanger, but excludes external optics for beam conditioning and/or delivery.</i></p> <p data-bbox="569 1077 650 1106"><u>Note 2</u></p> <p data-bbox="569 1115 1145 1220"><i>Category Code 6A005.a.6.b. does not include multiple transverse mode, industrial “lasers” having any of the following:</i></p> <ul style="list-style-type: none"> <li data-bbox="569 1239 1145 1334">a. <i>Output power exceeding 500 W but not exceeding 1 kW and having all of the following:</i> <ul style="list-style-type: none"> <li data-bbox="634 1353 1145 1420">1. <i>Beam Parameter Product (BPP) exceeding 0.7 mm•mrad; <u>and</u></i> <li data-bbox="634 1439 1145 1506">2. <i>‘Brightness’ not exceeding 1,024 W/(mm•mrad)²;</i> <li data-bbox="569 1525 1145 1620">b. <i>Output power exceeding 1 kW but not exceeding 1.6 kW and having a BPP exceeding 1.25 mm•mrad;</i> <li data-bbox="569 1639 1145 1734">c. <i>Output power exceeding 1.6 kW but not exceeding 2.5 kW and having a BPP exceeding 1.7 mm•mrad;</i>

Category Code	Item Description
	<p>d. Output power exceeding 2.5 kW but not exceeding 3.3 kW and having a BPP exceeding 2.5 mm•mrad;</p> <p>e. Output power exceeding 3.3 kW but not exceeding 4 kW and having a BPP exceeding 3.5 mm•mrad;</p> <p>f. Output power exceeding 4 kW but not exceeding 5 kW and having a BPP exceeding 5 mm•mrad;</p> <p>g. Output power exceeding 5 kW but not exceeding 6 kW and having a BPP exceeding 7.2 mm•mrad;</p> <p>h. Output power exceeding 6 kW but not exceeding 8 kW and having a BPP exceeding 12 mm•mrad; <u>or</u></p> <p>i. Output power exceeding 8 kW but not exceeding 10 kW and having a BPP exceeding 24 mm•mrad.</p> <p><u>Technical Note</u> For the purpose of Category Code 6A005.a.6.b., Note 2.a., 'brightness' is defined as the output power of the "laser" divided by the squared Beam Parameter Product (BPP), i.e. (output power)/BPP².</p> <p>7. Output wavelength exceeding 1,150 nm but not exceeding 1,555 nm and any of the following:</p> <p>a. Single transverse mode and output power exceeding 50 W; <u>or</u></p> <p>b. Multiple transverse mode and output power exceeding 80 W; <u>or</u></p> <p>8. Output wavelength exceeding 1,555 nm and output power exceeding 1 W;</p>

Category Code	Item Description
	<p>b. Non-“tunable” “pulsed lasers” having any of the following:</p> <ol style="list-style-type: none"> 1. Output wavelength less than 150 nm and any of the following: <ol style="list-style-type: none"> a. Output energy exceeding 50 mJ per pulse and “peak power” exceeding 1 W; <u>or</u> b. “Average output power” exceeding 1 W; 2. Output wavelength of 150 nm or more but not exceeding 510 nm and having any of the following: <ol style="list-style-type: none"> a. Output power exceeding 1.5 J per pulse and “peak power” exceeding 30 W; <u>or</u> b. “Average output power” exceeding 30 W; <p><i>Note</i> <i>Category Code 6A005.b.2.b. does not include Argon “lasers” having an “average output power” equal to or less than 50 W.</i></p> <ol style="list-style-type: none"> 3. Output wavelength exceeding 510 nm but not exceeding 540 nm and any of the following: <ol style="list-style-type: none"> a. Single transverse mode output and any of the following: <ol style="list-style-type: none"> 1. Output energy exceeding 1.5 J per pulse and “peak power” exceeding 50 W; <u>or</u> 2. “Average output power” exceeding 50 W; <u>or</u> b. Multiple transverse mode output and any of the following: <ol style="list-style-type: none"> 1. Output energy exceeding 1.5 J per pulse and “peak power” exceeding 150 W; <u>or</u> 2. “Average output power” exceeding 150 W;

<i>Category Code</i>	<i>Item Description</i>
	<p>4. Output wavelength exceeding 540 nm but not exceeding 800 nm and any of the following:</p> <ul style="list-style-type: none"> a. “Pulse duration” less than 1 ps and any of the following: <ul style="list-style-type: none"> 1. Output energy exceeding 0.005 J per pulse and “peak power” exceeding 5 GW; <u>or</u> 2. “Average output power” exceeding 20 W; <u>or</u> b. “Pulse duration” equal to or exceeding 1 ps and any of the following: <ul style="list-style-type: none"> 1. Output energy exceeding 1.5 J per pulse and “peak power” exceeding 30 W; <u>or</u> 2. “Average output power” exceeding 30 W; <p>5. Output wavelength exceeding 800 nm but not exceeding 975 nm and any of the following:</p> <ul style="list-style-type: none"> a. “Pulse duration” less than 1 ps and any of the following: <ul style="list-style-type: none"> 1. Output energy exceeding 0.005 J per pulse and “peak power” exceeding 5 GW; <u>or</u> 2. Single transverse mode output and “average output power” exceeding 20 W; b. “Pulse duration” equal to or exceeding 1 ps and not exceeding 1 μs and any of the following: <ul style="list-style-type: none"> 1. Output energy exceeding 0.5 J per pulse and “peak power” exceeding 50 W; 2. Single transverse mode output and “average output power” exceeding 20 W; <u>or</u> 3. Multiple transverse mode output and “average output power” exceeding 50 W; <u>or</u>

<i>Category Code</i>	<i>Item Description</i>
	<ul style="list-style-type: none"> c. “Pulse duration” exceeding 1 μs and any of the following: <ul style="list-style-type: none"> 1. Output energy exceeding 2 J per pulse and “peak power” exceeding 50 W; 2. Single transverse mode output and “average output power” exceeding 50 W; <u>or</u> 3. Multiple transverse mode output and “average output power” exceeding 80 W; 6. Output wavelength exceeding 975 nm but not exceeding 1,150 nm and any of the following: <ul style="list-style-type: none"> a. “Pulse duration” of less than 1 ps and any of the following: <ul style="list-style-type: none"> 1. Output “peak power” exceeding 2 GW per pulse; 2. “Average output power” exceeding 10 W; <u>or</u> 3. Output energy exceeding 0.002 J per pulse; b. “Pulse duration” equal to or exceeding 1 ps and less than 1 ns and any of the following: <ul style="list-style-type: none"> 1. Output “peak power” exceeding 5 GW per pulse; 2. “Average output power” exceeding 10 W; <u>or</u> 3. Output energy exceeding 0.1 J per pulse; c. “Pulse duration” equal to or exceeding 1 ns but not exceeding 1 μs, and any of the following: <ul style="list-style-type: none"> 1. Single transverse mode output and any of the following: <ul style="list-style-type: none"> a. “Peak power” exceeding 100 MW;

<i>Category Code</i>	<i>Item Description</i>
	<ul style="list-style-type: none"> b. “Average output power” exceeding 20 W limited by design to a maximum pulse repetition frequency less than or equal to 1 kHz; c. ‘Wall-plug efficiency’ exceeding 12%, “average output power” exceeding 100 W and capable of operating at a pulse repetition frequency greater than 1 kHz; d. “Average output power” exceeding 150 W and capable of operating at a pulse repetition frequency greater than 1 kHz; <u>or</u> e. Output energy exceeding 2 J per pulse; <u>or</u> <p>2. Multiple transverse mode output and any of the following:</p> <ul style="list-style-type: none"> a. “Peak power” exceeding 400 MW; b. ‘Wall-plug efficiency’ exceeding 18% and “average output power” exceeding 500 W; c. “Average output power” exceeding 2 kW; <u>or</u> d. Output energy exceeding 4 J per pulse; <u>or</u> <p>d. “Pulse duration” exceeding 1 μs and any of the following:</p> <ul style="list-style-type: none"> 1. Single transverse mode output and any of the following: <ul style="list-style-type: none"> a. “Peak power” exceeding 500 kW; b. ‘Wall-plug efficiency’ exceeding 12% and “average output power” exceeding 100 W; <u>or</u> c. “Average output power” exceeding 150 W; <u>or</u>

<i>Category Code</i>	<i>Item Description</i>
	<p data-bbox="569 325 1151 392">2. Multiple transverse mode output and any of the following:</p> <ul style="list-style-type: none"> <li data-bbox="628 407 1083 439">a. “Peak power” exceeding 1 MW; <li data-bbox="628 458 1151 559">b. ‘Wall-plug efficiency’ exceeding 18% and “average output power” exceeding 500 W; <u>or</u> <li data-bbox="628 578 1151 645">c. “Average output power” exceeding 2 kW; <p data-bbox="422 664 1151 731">7. Output wavelength exceeding 1,150 nm but not exceeding 1,555 nm, and any of the following:</p> <ul style="list-style-type: none"> <li data-bbox="508 750 1151 816">a. “Pulse duration” not exceeding 1 μs and any of the following: <ul style="list-style-type: none"> <li data-bbox="569 835 1151 902">1. Output energy exceeding 0.5 J per pulse and “peak power” exceeding 50 W; <li data-bbox="569 921 1151 1022">2. Single transverse mode output and “average output power” exceeding 20 W; <u>or</u> <li data-bbox="569 1041 1151 1142">3. Multiple transverse mode output and “average output power” exceeding 50 W; <u>or</u> <li data-bbox="508 1159 1151 1226">b. “Pulse duration” exceeding 1 μs and any of the following: <ul style="list-style-type: none"> <li data-bbox="569 1245 1151 1311">1. Output energy exceeding 2 J per pulse and “peak power” exceeding 50 W; <li data-bbox="569 1330 1151 1431">2. Single transverse mode output and “average output power” exceeding 50 W; <u>or</u> <li data-bbox="569 1450 1151 1551">3. Multiple transverse mode output and “average output power” exceeding 80 W; <u>or</u> <p data-bbox="422 1570 1151 1637">8. Output wavelength exceeding 1,555 nm and any of the following:</p> <ul style="list-style-type: none"> <li data-bbox="508 1656 1151 1723">a. Output energy exceeding 100 mJ per pulse and “peak power” exceeding 1 W; <u>or</u> <li data-bbox="508 1742 1056 1774">b. “Average output power” exceeding 1 W;

Category Code	Item Description
	<p>c. “Tunable” “lasers” having any of the following:</p> <ol style="list-style-type: none"> 1. Output wavelength less than 600 nm and any of the following: <ol style="list-style-type: none"> a. Output energy exceeding 50 mJ per pulse and “peak power” exceeding 1 W; <u>or</u> b. Average or CW output power exceeding 1 W; <p><u>Note</u> <i>Category Code 6A005.c.1. does not include dye lasers or other liquid lasers, having a multimode output and a wavelength of 150 nm or more but not exceeding 600 nm and all of the following:</i></p> <ol style="list-style-type: none"> 1. <i>Output energy less than 1.5 J per pulse or a “peak power” less than 20 W; <u>and</u></i> 2. <i>Average or CW output power less than 20 W.</i> 2. Output wavelength of 600 nm or more but not exceeding 1,400 nm, and any of the following: <ol style="list-style-type: none"> a. Output energy exceeding 1 J per pulse and “peak power” exceeding 20 W; <u>or</u> b. Average or CW output power exceeding 20 W; <u>or</u> 3. Output wavelength exceeding 1,400 nm and any of the following: <ol style="list-style-type: none"> a. Output energy exceeding 50 mJ per pulse and “peak power” exceeding 1 W; <u>or</u> b. Average or CW output power exceeding 1 W; <p>d. Other “lasers”, not specified in Category Code 6A005.a., 6A005.b. or 6A005.c. as follows:</p> <ol style="list-style-type: none"> 1. Semiconductor “lasers” as follows: <p><u>Note 1</u> <i>Category Code 6A005.d.1. includes semiconductor “lasers” having optical output connectors (e.g. fibre optic pigtails).</i></p>

Category Code	Item Description
	<p data-bbox="481 325 565 357"><u>Note 2</u></p> <p data-bbox="481 367 1142 468"><i>The control status of semiconductor “lasers” specially designed for other equipment is determined by the control status of the other equipment.</i></p> <ol style="list-style-type: none"> <li data-bbox="505 487 1142 588">a. Individual single-transverse mode semiconductor “lasers” having any of the following: <ol style="list-style-type: none"> <li data-bbox="569 605 1142 706">1. Wavelength equal or less than 1,510 nm and average or CW output power, exceeding 1.5 W; <u>or</u> <li data-bbox="569 723 1142 824">2. Wavelength greater than 1,510 nm and average or CW output power, exceeding 500 mW; <li data-bbox="505 841 1142 942">b. Individual, multiple-transverse mode semiconductor “lasers” having any of the following: <ol style="list-style-type: none"> <li data-bbox="569 959 1142 1060">1. Wavelength of less than 1,400 nm and average or CW output power, exceeding 15 W; <li data-bbox="569 1077 1142 1210">2. Wavelength equal to or greater than 1,400 nm and less than 1,900 nm and average or CW output power, exceeding 2.5 W; <u>or</u> <li data-bbox="569 1228 1142 1328">3. Wavelength equal to or greater than 1,900 nm and average or CW output power, exceeding 1 W; <li data-bbox="505 1346 1142 1447">c. Individual semiconductor “laser” ‘bars’, having any of the following: <ol style="list-style-type: none"> <li data-bbox="569 1429 1142 1530">1. Wavelength of less than 1,400 nm and average or CW output power, exceeding 100 W; <li data-bbox="569 1547 1142 1681">2. Wavelength equal to or greater than 1,400 nm and less than 1,900 nm and average or CW output power, exceeding 25 W; <u>or</u>

<i>Category Code</i>	<i>Item Description</i>
	<p data-bbox="569 325 1139 424">3. Wavelength equal to or greater than 1,900 nm and average or CW output power, exceeding 10 W;</p> <p data-bbox="505 443 1139 542">d. Semiconductor “laser” ‘stacked arrays’ (two-dimensional arrays) having any of the following:</p> <p data-bbox="569 561 1139 624">1. Wavelength less than 1,400 nm and having any of the following:</p> <p data-bbox="628 643 1139 776">a. Average or CW total output power less than 3 kW and having average or CW output ‘power density’ greater than 500 W/cm²;</p> <p data-bbox="628 795 1139 967">b. Average or CW total output power equal to or exceeding 3 kW but less than or equal to 5 kW, and having average or CW output ‘power density’ greater than 350 W/cm²;</p> <p data-bbox="628 986 1139 1049">c. Average or CW total output power exceeding 5 kW;</p> <p data-bbox="628 1068 1139 1130">d. Peak pulsed ‘power density’ exceeding 2,500 W/cm²; <u>or</u></p> <p data-bbox="628 1150 1139 1249">e. Spatially coherent average or CW total output power, greater than 150 W;</p> <p data-bbox="569 1268 1139 1367">2. Wavelength greater than or equal to 1,400 nm but less than 1,900 nm, and having any of the following:</p> <p data-bbox="628 1386 1139 1519">a. Average or CW total output power less than 250 W and average or CW output ‘power density’ greater than 150 W/cm²;</p> <p data-bbox="628 1538 1139 1709">b. Average or CW total output power equal to or exceeding 250 W but less than or equal to 500 W, and having average or CW output ‘power density’ greater than 50 W/cm²;</p>

<i>Category Code</i>	<i>Item Description</i>
	<p>c. Average or CW total output power exceeding 500 W;</p> <p>d. Peak pulsed ‘power density’ exceeding 500 W/cm²; <u>or</u></p> <p>e. Spatially coherent average or CW total output power, exceeding 15 W;</p> <p>3. Wavelength greater than or equal to 1,900 nm and having any of the following:</p> <p>a. Average or CW output ‘power density’ greater than 50 W/cm²;</p> <p>b. Average or CW output power greater than 10 W; <u>or</u></p> <p>c. Spatially coherent average or CW total output power, exceeding 1.5 W; <u>or</u></p> <p>4. At least one “laser” ‘bar’ specified in Category Code 6A005.d.1.c.;</p> <p><i><u>Technical Note</u></i></p> <p><i>For the purpose of Category Code 6A005.d.1.d., ‘power density’ means the total “laser” output power divided by the emitter surface area of the ‘stacked array’.</i></p> <p>e. Semiconductor “laser” ‘stacked arrays’, other than those specified in Category Code 6A005.d.1.d., having all of the following:</p> <p>1. Specially designed or modified to be combined with other ‘stacked arrays’ to form a larger ‘stacked array’; <u>and</u></p> <p>2. Integrated connections, common for both electronics and cooling;</p>

Category Code	Item Description
	<p data-bbox="567 325 646 354"><u>Note 1</u></p> <p data-bbox="567 367 1139 567"><i>'Stacked arrays', formed by combining semiconductor "laser" 'stacked arrays' specified by Category Code 6A005.d.1.e., that are not designed to be further combined or modified are specified by Category Code 6A005.d.1.d.</i></p> <p data-bbox="567 586 646 614"><u>Note 2</u></p> <p data-bbox="567 628 1139 828"><i>'Stacked arrays', formed by combining semiconductor "laser" 'stacked arrays' specified by Category Code 6A005.d.1.e., that are designed to be further combined or modified are specified by Category Code 6A005.d.1.e.</i></p> <p data-bbox="567 847 646 875"><u>Note 3</u></p> <p data-bbox="567 889 1139 1022"><i>Category Code 6A005.d.1.e. does not include modular assemblies of single 'bars' designed to be fabricated into end-to-end stacked linear arrays.</i></p> <p data-bbox="482 1041 677 1070"><u>Technical Notes</u></p> <ol data-bbox="417 1083 1139 1641" style="list-style-type: none"> <li data-bbox="505 1083 1139 1150">1. Semiconductor "lasers" are commonly called "laser" diodes. <li data-bbox="505 1169 1139 1302">2. A 'bar' (also called a semiconductor "laser" 'bar', a "laser" diode 'bar' or diode 'bar') consists of multiple semiconductor "lasers" in a one-dimensional array. <li data-bbox="505 1321 1139 1416">3. A 'stacked array' consists of multiple 'bars' forming a two-dimensional array of semiconductor "lasers". <ol data-bbox="417 1435 1139 1641" style="list-style-type: none"> <li data-bbox="417 1435 1139 1511">2. Carbon monoxide (CO) "lasers" having any of the following: <ol data-bbox="505 1530 1139 1641" style="list-style-type: none"> <li data-bbox="505 1530 1139 1597">a. Output energy exceeding 2 J per pulse and "peak power" exceeding 5 kW; <u>or</u> <li data-bbox="505 1616 1139 1641">b. Average or CW output power exceeding 5 kW;

<i>Category Code</i>	<i>Item Description</i>
	<p>3. Carbon dioxide (CO₂) “lasers” having any of the following:</p> <ul style="list-style-type: none"> a. CW output power exceeding 15 kW; b. Pulsed output with a “pulse duration” exceeding 10 μs and any of the following: <ul style="list-style-type: none"> 1. “Average output power” exceeding 10 kW; <u>or</u> 2. “Peak power” exceeding 100 kW; <u>or</u> c. Pulsed output with a “pulse duration” equal to or less than 10 μs and any of the following: <ul style="list-style-type: none"> 1. Pulse energy exceeding 5 J per pulse; <u>or</u> 2. “Average output power” exceeding 2.5 kW; <p>4. Excimer “lasers” having any of the following:</p> <ul style="list-style-type: none"> a. Output wavelength not exceeding 150 nm and any of the following: <ul style="list-style-type: none"> 1. Output energy exceeding 50 mJ per pulse; <u>or</u> 2. “Average output power” exceeding 1 W; b. Output wavelength exceeding 150 nm but not exceeding 190 nm and any of the following: <ul style="list-style-type: none"> 1. Output energy exceeding 1.5 J per pulse; <u>or</u> 2. “Average output power” exceeding 120 W; c. Output wavelength exceeding 190 nm but not exceeding 360 nm and any of the following: <ul style="list-style-type: none"> 1. Output energy exceeding 10 J per pulse; <u>or</u> 2. “Average output power” exceeding 500 W; <u>or</u>

<i>Category Code</i>	<i>Item Description</i>
	<p>d. Output wavelength exceeding 360 nm and any of the following:</p> <ol style="list-style-type: none"> 1. Output energy exceeding 1.5 J per pulse; <u>or</u> 2. “Average output power” exceeding 30 W; <p><u>N.B.</u> <i>For excimer “lasers” specially designed for lithography equipment, see Category Code 3B001.</i></p> <p>5. “Chemical lasers” as follows:</p> <ol style="list-style-type: none"> a. Hydrogen Fluoride (HF) “lasers”; b. Deuterium Fluoride (DF) “lasers”; c. “Transfer lasers”, as follows: <ol style="list-style-type: none"> 1. Oxygen Iodine (O₂-I) “lasers”; 2. Deuterium Fluoride-Carbon dioxide (DF-CO₂) “lasers”; <p>6. ‘Non-repetitive pulsed’ Nd: glass “lasers” having any of the following:</p> <ol style="list-style-type: none"> a. “Pulse duration” not exceeding 1 μs and output energy exceeding 50 J per pulse; <u>or</u> b. “Pulse duration” exceeding 1 μs and output energy exceeding 100 J per pulse; <p><u>Note</u> <i>‘Non-repetitive pulsed’ refers to “lasers” that produce either a single output pulse or that have a time interval between pulses exceeding one minute.</i></p>

Category Code	Item Description
	<p>e. Components as follows:</p> <ol style="list-style-type: none"> 1. Mirrors cooled either by ‘active cooling’ or by heat pipe cooling; <p><i><u>Technical Note</u></i> ‘Active cooling’ is a cooling technique for optical components using flowing fluids within the subsurface (nominally less than 1 mm below the optical surface) of the optical component to remove heat from the optic.</p> 2. Optical mirrors or transmissive or partially transmissive optical or electro-optical components, other than fused tapered fibre combiners and Multi-Layer Dielectric gratings (MLDs), specially designed for use with specified “lasers”; <p><i><u>Note</u></i> Fibre combiners and MLDs are specified in Category Code 6A005.e.3.</p> 3. Fibre laser components as follows: <ol style="list-style-type: none"> a. Multimode to multimode fused tapered fibre combiners having all of the following: <ol style="list-style-type: none"> 1. An insertion loss better (less) than or equal to 0.3 dB maintained at a rated total average or CW output power (excluding output power transmitted through the single mode core if present) exceeding 1,000 W; <u>and</u> 2. Number of input fibres equal to or greater than 3; b. Single mode to multimode fused tapered fibre combiners having all of the following: <ol style="list-style-type: none"> 1. An insertion loss better (less) than 0.5 dB maintained at a rated total average or CW output power exceeding 4,600 W; 2. Number of input fibres equal to or greater than 3; <u>and</u>

<i>Category Code</i>	<i>Item Description</i>
	<p>3. Having any of the following:</p> <ol style="list-style-type: none"> a. A Beam Parameter Product (BPP) measured at the output not exceeding 1.5 mm•mrad for a number of input fibres less than or equal to 5; <u>or</u> b. A BPP measured at the output not exceeding 2.5 mm•mrad for a number of input fibres greater than 5; c. MLDs having all of the following: <ol style="list-style-type: none"> 1. Designed for spectral or coherent beam combination of 5 or more fibre lasers; <u>and</u> 2. CW Laser Induced Damage Threshold (LIDT) greater than or equal to 10 kW/cm²; <p>f. Optical equipment as follows:</p> <p><u>N.B.</u> <i>For shared aperture optical elements, capable of operating in “Super-High Power Laser” (“SHPL”) applications, see Division 2 of Part 1 of this Schedule.</i></p> <ol style="list-style-type: none"> 1. Dynamic wavefront (phase) measuring equipment capable of mapping at least 50 positions on a beam wavefront and any of the following: <ol style="list-style-type: none"> a. Frame rates equal to or more than 100 Hz and phase discrimination of at least 5% of the beam’s wavelength; <u>or</u> b. Frame rates equal to or more than 1,000 Hz and phase discrimination of at least 20% of the beam’s wavelength; 2. “Laser” diagnostic equipment capable of measuring “SHPL” system angular beam steering errors of equal to or less than 10 µrad;

<i>Category Code</i>	<i>Item Description</i>
	<p>3. Optical equipment and components, specially designed for a phased-array “SHPL” system for coherent beam combination to an accuracy of $\lambda/10$ at the designed wavelength, or 0.1 μm, whichever is the smaller;</p> <p>4. Projection telescopes specially designed for use with “SHPL” systems;</p> <p>g. ‘Laser acoustic detection equipment’ having all of the following:</p> <ol style="list-style-type: none"> 1. CW laser output power equal to or exceeding 20 mW; 2. Laser frequency stability equal to or better (less) than 10 MHz; 3. Laser wavelengths equal to or exceeding 1,000 nm but not exceeding 2,000 nm; 4. Optical system resolution better (less) than 1 nm; <u>and</u> 5. Optical Signal to Noise ratio equal to or exceeding 10^3. <p><u>Technical Note</u> ‘Laser acoustic detection equipment’ is sometimes referred to as a Laser Microphone or Particle Flow Detection Microphone.</p>
6A006	<p>“Magnetometers”, “magnetic gradiometers”, “intrinsic magnetic gradiometers”, underwater electric field sensors, “compensation systems”, and specially designed components therefor, as follows:</p> <p><u>N.B.</u> See also Category Code 7A103.d.</p> <p><u>Note</u> Category Code 6A006 does not include instruments specially designed for fishery applications or biomagnetic measurements for medical diagnostics.</p>

<i>Category Code</i>	<i>Item Description</i>
	<p>a. “Magnetometers” and sub-systems, as follows:</p> <ol style="list-style-type: none"> 1. “Magnetometers” using “superconductive” (SQUID) “technology” and having any of the following: <ol style="list-style-type: none"> a. SQUID systems designed for stationary operation, without specially designed sub-systems designed to reduce in-motion noise, and having a ‘sensitivity’ equal to or lower (better) than 50 fT (rms) per square root Hz at a frequency of 1 Hz; <u>or</u> b. SQUID systems having an in-motion-magnetometer ‘sensitivity’ lower (better) than 20 pT (rms) per square root Hz at a frequency of 1 Hz and specially designed to reduce in-motion noise; 2. “Magnetometers” using optically pumped or nuclear precession (proton/Overhauser) “technology” having a ‘sensitivity’ lower (better) than 20 pT (rms) per square root Hz at a frequency of 1 Hz; 3. “Magnetometers” using fluxgate “technology” having a ‘sensitivity’ equal to or lower (better) than 10 pT (rms) per square root Hz at a frequency of 1 Hz; 4. Induction coil “magnetometers” having a ‘sensitivity’ lower (better) than any of the following: <ol style="list-style-type: none"> a. 0.05 nT (rms) per square root Hz at frequencies of less than 1 Hz; b. 1×10^{-3} nT (rms) per square root Hz at frequencies of 1 Hz or more but not exceeding 10 Hz; <u>or</u> c. 1×10^{-4} nT (rms) per square root Hz at frequencies exceeding 10 Hz; 5. Fibre optic “magnetometers” having a ‘sensitivity’ lower (better) than 1 nT (rms) per square root Hz; <p>b. Underwater electric field sensors having a ‘sensitivity’ lower (better) than 8 nanovolt per metre per square root Hz when measured at 1 Hz;</p>

<i>Category Code</i>	<i>Item Description</i>
	<p>c. “Magnetic gradiometers” as follows:</p> <ol style="list-style-type: none"> 1. “Magnetic gradiometers” using multiple “magnetometers” specified in Category Code 6A006.a.; 2. Fibre optic “intrinsic magnetic gradiometers” having a magnetic gradient field ‘sensitivity’ lower (better) than 0.3 nT/m (rms) per square root Hz; 3. “Intrinsic magnetic gradiometers”, using “technology” other than fibre-optic “technology”, having a magnetic gradient field ‘sensitivity’ lower (better) than 0.015 nT/m (rms) per square root Hz; <p>d. “Compensation systems” for magnetic or underwater electric field sensors resulting in a performance equal to or better than the specified parameters of Category Code 6A006.a., 6A006.b. or 6A006.c.;</p> <p>e. Underwater electromagnetic receivers incorporating magnetic field sensors specified by Category Code 6A006.a. or underwater electric field sensors specified by Category Code 6A006.b.</p> <p><i>Technical Note</i> <i>For the purpose of Category Code 6A006, ‘sensitivity’ (noise level) is the root mean square of the device-limited noise floor which is the lowest signal that can be measured.</i></p>
6A007	<p>Gravity meters (gravimeters) and gravity gradiometers, as follows:</p> <p><i>N.B.</i> <i>See also Category Code 6A107.</i></p> <p>a. Gravity meters designed or modified for ground use and having a static accuracy of less (better) than 10 μGal;</p> <p><i>Note</i> <i>Category Code 6A007.a. does not include ground gravity meters of the quartz element (Worden) type.</i></p>

<i>Category Code</i>	<i>Item Description</i>
	<p>b. Gravity meters designed for mobile platforms and having all of the following:</p> <ol style="list-style-type: none"> 1. A static accuracy of less (better) than 0.7 mGal; <u>and</u> 2. An in-service (operational) accuracy of less (better) than 0.7 mGal having a 'time-to-steady-state registration' of less than 2 minutes under any combination of attendant corrective compensations and motional influences; <p><i>Technical Note</i> <i>For the purpose of Category Code 6A007.b., 'time-to-steady-state registration' (also referred to as the gravimeter's response time) is the time over which the disturbing effects of platform induced accelerations (high frequency noise) are reduced.</i></p> <p>c. Gravity gradiometers.</p>
6A008	<p>Radar systems, equipment and assemblies having any of the following, and specially designed components therefor:</p> <p><u>N.B.</u> <i>See also Category Code 6A108.</i></p> <p><u>Note</u> <i>Category Code 6A008 does not include:</i></p> <ul style="list-style-type: none"> – <i>Secondary surveillance radar (SSR);</i> – <i>Civil Automotive Radar;</i> – <i>Displays or monitors used for air traffic control (ATC);</i> – <i>Meteorological (weather) radar;</i> – <i>Precision approach radar (PAR) equipment conforming to ICAO standards and employing electronically steerable linear (1-dimensional) arrays or mechanically positioned passive antennae.</i>

<i>Category Code</i>	<i>Item Description</i>
	<p>a. Operating at frequencies from 40 GHz to 230 GHz and having any of the following:</p> <ol style="list-style-type: none"> 1. An average output power exceeding 100 mW; <u>or</u> 2. Locating accuracy of 1 m or less (better) in range and 0.2 degree or less (better) in azimuth; <p>b. A tunable bandwidth exceeding $\pm 6.25\%$ of the ‘centre operating frequency’;</p> <p><i>Technical Note</i> <i>The ‘centre operating frequency’ equals one half of the sum of the highest plus the lowest specified operating frequencies.</i></p> <p>c. Capable of operating simultaneously on more than two carrier frequencies;</p> <p>d. Capable of operating in synthetic aperture (SAR), inverse synthetic aperture (ISAR) radar mode, or sidelooking airborne (SLAR) radar mode;</p> <p>e. Incorporating electronically steerable array antennae;</p> <p>f. Capable of heightfinding non-cooperative targets;</p> <p>g. Specially designed for airborne (balloon or airframe mounted) operation and having Doppler “signal processing” for the detection of moving targets;</p> <p>h. Employing processing of radar signals and using any of the following:</p> <ol style="list-style-type: none"> 1. “Radar spread spectrum” techniques; <u>or</u> 2. “Radar frequency agility” techniques; <p>i. Providing ground-based operation with a maximum “instrumented range” exceeding 185 km;</p>

Category Code	Item Description
	<p><u>Note</u></p> <p>Category Code 6A008.i. does not include:</p> <ol style="list-style-type: none"> a. Fishing ground surveillance radar; b. Ground radar equipment specially designed for enroute air traffic control and having all of the following: <ol style="list-style-type: none"> 1. A maximum “instrumented range” of 500 km or less; 2. Configured so that radar target data can be transmitted only one way from the radar site to one or more civil ATC centres; 3. Contains no provisions for remote control of the radar scan rate from the enroute ATC centre; <u>and</u> 4. Permanently installed; c. Weather balloon tracking radars. j. Being “laser” radar or Light Detection and Ranging (LIDAR) equipment and having any of the following: <ol style="list-style-type: none"> 1. “Space-qualified”; 2. Employing coherent heterodyne or homodyne detection techniques and having an angular resolution of less (better) than 20 μrad (microradians); <u>or</u> 3. Designed for carrying out airborne bathymetric littoral surveys to International Hydrographic Organisation (IHO) Order 1a Standard (5th Edition February 2008) for Hydrographic Surveys or better, and using one or more lasers with a wavelength exceeding 400 nm but not exceeding 600 nm; <p><u>Note 1</u></p> <p>LIDAR equipment specially designed for surveying is only specified in Category Code 6A008.j.3.</p> <p><u>Note 2</u></p> <p>Category Code 6A008.j. does not include LIDAR equipment specially designed for meteorological observation.</p>

Category Code	Item Description
	<p><u>Note 3</u> <i>Parameters in the IHO Order 1a Standard 5th Edition February 2008 are summarised as follows:</i></p> <ul style="list-style-type: none"> – <i>Horizontal Accuracy (95% Confidence Level) = 5 m + 5% of depth</i> – <i>Depth Accuracy for Reduced Depths (95% confidence level) = $\pm\sqrt{(a^2 + (b*d)^2)}$, where:</i> <ul style="list-style-type: none"> <i>a = 0.5 m = constant depth error, i.e. the sum of all constant depth errors</i> <i>b = 0.013 = factor of depth dependent error</i> <i>b*d = depth dependent error, i.e. the sum of all depth dependent errors</i> <i>d = depth</i> – <i>Feature Detection = Cubic features > 2 m in depths up to 40 m; 10% of depth beyond 40 m.</i> <p>k. Having “signal processing” sub-systems using “pulse compression” and having any of the following:</p> <ol style="list-style-type: none"> 1. A “pulse compression” ratio exceeding 150; <u>or</u> 2. A compressed pulse width of less than 200 ns; <u>or</u> <p><u>Note</u> <i>Category Code 6A008.k.2. does not include two dimensional ‘marine radar’ or ‘vessel traffic service’ radar, having all of the following:</i></p> <ol style="list-style-type: none"> a. <i>“Pulse compression” ratio not exceeding 150;</i> b. <i>Compressed pulse width of greater than 30 ns;</i> c. <i>Single and rotating mechanically scanned antenna;</i> d. <i>Peak output power not exceeding 250 W; <u>and</u></i> e. <i>Not capable of “frequency hopping”.</i>

<i>Category Code</i>	<i>Item Description</i>
	<p>1. Having data processing sub-systems and having any of the following:</p> <ol style="list-style-type: none"> 1. “Automatic target tracking” providing, at any antenna rotation, the predicted target position beyond the time of the next antenna beam passage; <u>or</u> <p><u>Note</u> <i>Category Code 6A008.l.1. does not include conflict alert capability in ATC systems, or ‘marine radar’.</i></p> <ol style="list-style-type: none"> 2. Not used; 3. Not used; 4. Configured to provide superposition and correlation, or fusion, of target data within six seconds from two or more “geographically dispersed” radar sensors to improve the aggregate performance beyond that of any single sensor specified in Category Code 6A008.f. or 6A008.i. <p><u>N.B.</u> <i>See also Division 2 of Part 1 of this Schedule.</i></p> <p><u>Note</u> <i>Category Code 6A008.l.4. does not include systems, equipment and assemblies used for ‘vessel traffic service’.</i></p> <p><u>Technical Notes</u></p> <ol style="list-style-type: none"> 1. <i>For the purpose of Category Code 6A008, ‘marine radar’ is a radar that is used to navigate safely at sea, inland waterways or near-shore environments.</i> 2. <i>For the purpose of Category Code 6A008, ‘vessel traffic service’ is a vessel traffic monitoring and control service similar to air traffic control for aircraft.</i>

<i>Category Code</i>	<i>Item Description</i>
6A102	<p>Radiation hardened ‘detectors’, other than those specified in Category Code 6A002, specially designed or modified for protecting against nuclear effects (e.g. electromagnetic pulse (EMP), X-rays, combined blast and thermal effects) and usable for “missiles”, designed or rated to withstand radiation levels which meet or exceed a total irradiation dose of 5×10^5 rads (silicon).</p> <p><u>Technical Note</u> <i>In Category Code 6A102, a ‘detector’ is defined as a mechanical, electrical, optical or chemical device that automatically identifies and records, or registers a stimulus such as an environmental change in pressure or temperature, an electrical or electromagnetic signal or radiation from a radioactive material. This includes devices that sense by one time operation or failure.</i></p>
6A107	<p>Gravity meters (gravimeters) and components for gravity meters and gravity gradiometers, as follows:</p> <ol style="list-style-type: none"> a. Gravity meters, other than those specified in Category Code 6A007.b., designed or modified for airborne or marine use, and having a static or operational accuracy equal to or less (better) than 0.7 milligal (mgal), and having a time-to-steady-state registration of two minutes or less; b. Specially designed components for gravity meters specified in Category Code 6A007.b. or 6A107.a. and gravity gradiometers specified in Category Code 6A007.c.
6A108	<p>Radar systems and tracking systems, other than those specified in Category Code 6A008, as follows:</p> <ol style="list-style-type: none"> a. Radar and laser radar systems designed or modified for use in space launch vehicles specified in Category Code 9A004 or sounding rockets specified in Category Code 9A104; <p><u>Note</u> <i>Category Code 6A108.a. includes the following:</i></p> <ol style="list-style-type: none"> a. <i>Terrain contour mapping equipment;</i> b. <i>Imaging sensor equipment;</i>

<i>Category Code</i>	<i>Item Description</i>
	<p>c. <i>Scene mapping and correlation (both digital and analogue) equipment;</i></p> <p>d. <i>Doppler navigation radar equipment.</i></p> <p>b. Precision tracking systems, usable for ‘missiles’, as follows:</p> <ol style="list-style-type: none"> 1. Tracking systems which use a code translator in conjunction with either surface or airborne references or navigation satellite systems to provide real-time measurements of in-flight position and velocity; 2. Range instrumentation radars including associated optical/infrared trackers with all of the following capabilities: <ol style="list-style-type: none"> a. Angular resolution better than 1.5 milliradians; b. Range of 30 km or greater with a range resolution better than 10 m rms; <u>and</u> c. Velocity resolution better than 3 m/s. <p><u><i>Technical Note</i></u> <i>In Category Code 6A108.b., ‘missile’ means complete rocket systems and unmanned aerial vehicle systems capable of a range exceeding 300 km.</i></p>
6A202	<p>Photomultiplier tubes having both of the following characteristics:</p> <ol style="list-style-type: none"> a. Photocathode area of greater than 20 cm²; <u>and</u> b. Anode pulse rise time of less than 1 ns.

Category Code	Item Description
6A203	<p>Cameras and components, other than those specified in Category Code 6A003, as follows:</p> <p><u>N.B. 1</u> <i>“Software” specially designed to enhance or release the performance of a camera or imaging device to meet the characteristics of Category Code 6A203.a., 6A203.b. or 6A203.c. is specified in Category Code 6D203.</i></p> <p><u>N.B. 2</u> <i>“Technology” in the form of codes or keys to enhance or release the performance of a camera or imaging device to meet the characteristics of Category Code 6A203.a., 6A203.b. or 6A203.c. is specified in Category Code 6E203.</i></p> <p><u>Note</u> <i>Category Codes 6A203.a. to 6A203.c. do not include cameras or imaging devices if they have hardware, “software” or “technology” constraints that limit the performance to less than that specified above, provided they meet any of the following:</i></p> <p>a. <i>They need to be returned to the original manufacturer to make the enhancements or release the constraints;</i></p> <p>b. <i>They require “software” as specified in Category Code 6D203 to enhance or release the performance to meet the characteristics of Category Code 6A203; <u>or</u></i></p> <p>c. <i>They require “technology” in the form of keys or codes as specified in Category Code 6E203 to enhance or release the performance to meet the characteristics of Category Code 6A203.</i></p> <p>a. Streak cameras, and specially designed components therefor, as follows:</p> <ol style="list-style-type: none"> 1. Streak cameras with writing speeds greater than 0.5 mm/μs; 2. Electronic streak cameras capable of 50 ns or less time resolution; 3. Streak tubes for cameras specified in Category Code 6A203.a.2.;

<i>Category Code</i>	<i>Item Description</i>
	<ol style="list-style-type: none"> 4. Plug-ins specially designed for use with streak cameras which have modular structures and that enable the performance specifications in Category Code 6A203.a.1. or 6A203.a.2.; 5. Synchronising electronics units, rotor assemblies consisting of turbines, mirrors and bearings specially designed for cameras specified in Category Code 6A203.a.1.; <p>b. Framing cameras, and specially designed components therefor, as follows:</p> <ol style="list-style-type: none"> 1. Framing cameras with recording rates greater than 225,000 frames per second; 2. Framing cameras capable of 50 ns or less frame exposure time; 3. Framing tubes and solid-state imaging devices having a fast image gating (shutter) time of 50 ns or less specially designed for cameras specified in Category Code 6A203.b.1. or 6A203.b.2.; 4. Plug-ins specially designed for use with framing cameras which have modular structures and that enable the performance specifications in Category Code 6A203.b.1. or 6A203.b.2.; 5. Synchronising electronics units, rotor assemblies consisting of turbines, mirrors and bearings specially designed for cameras specified in Category Code 6A203.b.1. or 6A203.b.2.; <p><u>Technical Note</u></p> <p><i>In Category Code 6A203.b., high speed single frame cameras can be used alone to produce a single image of a dynamic event, or several such cameras can be combined in a sequentially triggered system to produce multiple images of an event.</i></p>

<i>Category Code</i>	<i>Item Description</i>
	<p>c. Solid state or electron tube cameras, and specially designed components therefor, as follows:</p> <ol style="list-style-type: none"> 1. Solid-state cameras or electron tube cameras with a fast image gating (shutter) time of 50 ns or less; 2. Solid-state imaging devices and image intensifier tubes having a fast image gating (shutter) time of 50 ns or less specially designed for cameras specified in Category Code 6A203.c.1.; 3. Electro-optical shuttering devices (Kerr or Pockels cells) with a fast image gating (shutter) time of 50 ns or less; 4. Plug-ins specially designed for use with cameras which have modular structures and that enable the performance specifications in Category Code 6A203.c.1.; <p>d. Radiation-hardened TV cameras, or lenses therefor, specially designed or rated as radiation hardened to withstand a total radiation dose greater than 50×10^3 Gy (silicon) (5×10^6 rad (silicon)) without operational degradation.</p> <p><u>Technical Note</u> <i>The term Gy (silicon) refers to the energy in Joules per kilogram absorbed by an unshielded silicon sample when exposed to ionising radiation.</i></p>
6A205	<p>“Lasers”, “laser” amplifiers and oscillators, other than those specified in Category Codes 0B001.g.5., 0B001.h.6. and 6A005; as follows:</p> <p><u>N.B.</u> <i>For copper vapour lasers, see Category Code 6A005.b.</i></p> <p>a. Argon ion “lasers” having both of the following characteristics:</p> <ol style="list-style-type: none"> 1. Operating at wavelengths between 400 nm and 515 nm; <u>and</u> 2. An average output power greater than 40 W;

<i>Category Code</i>	<i>Item Description</i>
	<p>b. Tunable pulsed single-mode dye laser oscillators having all of the following characteristics:</p> <ol style="list-style-type: none"> 1. Operating at wavelengths between 300 nm and 800 nm; 2. An average output power greater than 1 W; 3. A repetition rate greater than 1 kHz; <u>and</u> 4. Pulse width less than 100 ns; <p>c. Tunable pulsed dye laser amplifiers and oscillators, having all of the following characteristics:</p> <ol style="list-style-type: none"> 1. Operating at wavelengths between 300 nm and 800 nm; 2. An average output power greater than 30 W; 3. A repetition rate greater than 1 kHz; <u>and</u> 4. Pulse width less than 100 ns; <p><i>Note</i> <i>Category Code 6A205.c. does not include single mode oscillators.</i></p> <p>d. Pulsed carbon dioxide “lasers” having all of the following characteristics:</p> <ol style="list-style-type: none"> 1. Operating at wavelengths between 9,000 nm and 11,000 nm; 2. A repetition rate greater than 250 Hz; 3. An average output power greater than 500 W; <u>and</u> 4. Pulse width of less than 200 ns; <p>e. Para-hydrogen Raman shifters designed to operate at 16 μm output wavelength and at a repetition rate greater than 250 Hz;</p>

<i>Category Code</i>	<i>Item Description</i>
	<p>f. Neodymium-doped (other than glass) “lasers” with an output wavelength between 1,000 nm and 1,100 nm having either of the following:</p> <ol style="list-style-type: none"> 1. Pulse-excited and Q-switched with a pulse duration equal to or more than 1 ns, and having either of the following: <ol style="list-style-type: none"> a. A single-transverse mode output with an average output power greater than 40 W; <u>or</u> b. A multiple-transverse mode output having an average output power greater than 50 W; <u>or</u> 2. Incorporating frequency doubling to give an output wavelength between 500 nm and 550 nm with an average output power of more than 40 W; <p>g. Pulsed carbon monoxide lasers, other than those specified in Category Code 6A005.d.2., having all of the following:</p> <ol style="list-style-type: none"> 1. Operating at wavelengths between 5,000 nm and 6,000 nm; 2. A repetition rate greater than 250 Hz; 3. An average output power greater than 200 W; <u>and</u> 4. Pulse width of less than 200 ns.
6A225	<p>Velocity interferometers for measuring velocities exceeding 1 km/s during time intervals of less than 10 microseconds.</p> <p><u>Note</u></p> <p><i>Category Code 6A225 includes velocity interferometers such as VISARs (Velocity Interferometer Systems for Any Reflector), DLIs (Doppler Laser Interferometers) and PDV (Photonic Doppler Velocimeters) also known as Het-V (Heterodyne Velocimeters).</i></p>

<i>Category Code</i>	<i>Item Description</i>
6A226	Pressure sensors, as follows: <ol style="list-style-type: none"> a. Shock pressure gauges capable of measuring pressures greater than 10 GPa, including gauges made with manganin, ytterbium, and polyvinylidene bifluoride (PVBF, PVF₂); b. Quartz pressure transducers for pressures greater than 10 GPa.
6B	Test, Inspection and Production Equipment
6B004	Optical equipment as follows: <ol style="list-style-type: none"> a. Equipment for measuring absolute reflectance to an accuracy of $\pm 0.1\%$ of the reflectance value; b. Equipment other than optical surface scattering measurement equipment, having an unobscured aperture of more than 10 cm, specially designed for the non-contact optical measurement of a non-planar optical surface figure (profile) to an “accuracy” of 2 nm or less (better) against the required profile.
	<u>Note</u>
	<i>Category Code 6B004 does not include microscopes.</i>
6B007	Equipment to produce, align and calibrate land-based gravity meters with a static accuracy of better than 0.1 mGal.
6B008	Pulse radar cross-section measurement systems having transmit pulse widths of 100 ns or less, and specially designed components therefor.
	<u>N.B.</u>
	<i>See also Category Code 6B108.</i>

Category Code	Item Description
6B108	<p>Systems, other than those specified in Category Code 6B008, specially designed for radar cross-section measurement usable for ‘missiles’ and their sub-systems.</p> <p><i>Technical Note</i> <i>In Category Code 6B108, ‘missile’ means complete rocket systems and unmanned aerial vehicle systems capable of a range exceeding 300 km.</i></p>
<p>6C</p> <p>6C002</p>	<p>Materials</p> <p>Optical sensor materials as follows:</p> <ol style="list-style-type: none"> a. Elemental tellurium (Te) of purity levels of 99.9995% or more; b. Single crystals (including epitaxial wafers) of any of the following: <ol style="list-style-type: none"> 1. Cadmium zinc telluride (CdZnTe), with zinc content of less than 6% by ‘mole fraction’; 2. Cadmium telluride (CdTe) of any purity level; <u>or</u> 3. Mercury cadmium telluride (HgCdTe) of any purity level. <p><i>Technical Note</i> ‘Mole fraction’ is defined as the ratio of moles of ZnTe to the sum of moles of CdTe and ZnTe present in the crystal.</p>
6C004	<p>Optical materials as follows:</p> <ol style="list-style-type: none"> a. Zinc selenide (ZnSe) and zinc sulphide (ZnS) “substrate blanks”, produced by the chemical vapour deposition process and having any of the following: <ol style="list-style-type: none"> 1. A volume greater than 100 cm³; <u>or</u> 2. A diameter greater than 80 mm and a thickness of 20 mm or more;

<i>Category Code</i>	<i>Item Description</i>
	<p>b. Electro-optic materials and non-linear optical materials, as follows:</p> <ol style="list-style-type: none"> 1. Potassium titanyl arsenate (KTA) (59400-80-5); 2. Silver gallium selenide (AgGaSe₂, also known as AGSE) (12002-67-4); 3. Thallium arsenic selenide (Tl₃AsSe₃, also known as TAS) (16142-89-5); 4. Zinc germanium phosphide (ZnGeP₂, also known as ZGP, zinc germanium biphosphide or zinc germanium diphosphide); <u>or</u> 5. Gallium selenide (GaSe) (12024-11-2); <p>c. Non-linear optical materials, other than those specified in Category Code 6C004.b., having any of the following:</p> <ol style="list-style-type: none"> 1. Having all of the following: <ol style="list-style-type: none"> a. Dynamic (also known as non-stationary) third order non-linear susceptibility ($\chi^{(3)}$, chi 3) of 10^{-6} m²/V² or more; <u>and</u> b. Response time of less than 1 ms; <u>or</u> 2. Second order non-linear susceptibility ($\chi^{(2)}$, chi 2) of 3.3×10^{-11} m/V or more; <p>d. "Substrate blanks" of silicon carbide or beryllium beryllium (Be/Be) deposited materials, exceeding 300 mm in diameter or major axis length;</p> <p>e. Glass, including fused silica, phosphate glass, fluorophosphate glass, zirconium fluoride (ZrF₄) (7783-64-4) and hafnium fluoride (HfF₄) (13709-52-9) and having all of the following:</p> <ol style="list-style-type: none"> 1. A hydroxyl ion (OH-) concentration of less than 5 ppm; 2. Integrated metallic purity levels of less than 1 ppm; <u>and</u> 3. High homogeneity (index of refraction variance) less than 5×10^{-6};

<i>Category Code</i>	<i>Item Description</i>
6C005	<p>f. Synthetically produced diamond material with an absorption of less than 10^{-5} cm^{-1} for wavelengths exceeding 200 nm but not exceeding 14,000 nm.</p> <p>“Laser” materials as follows:</p> <p>a. Synthetic crystalline “laser” host material in unfinished form as follows:</p> <ol style="list-style-type: none"> 1. Titanium doped sapphire; 2. Not used; <p>b. Rare-earth-metal doped double-clad fibres having any of the following:</p> <ol style="list-style-type: none"> 1. Nominal laser wavelength of 975 nm to 1,150 nm and having all of the following: <ol style="list-style-type: none"> a. Average core diameter equal to or greater than 25 μm; <u>and</u> b. Core ‘Numerical Aperture’ (‘NA’) less than 0.065; <u>or</u> <p><u>Note</u> <i>Category Code 6C005.b.1. does not include double-clad fibres having an inner glass cladding diameter exceeding 150 μm and not exceeding 300 μm.</i></p> 2. Nominal laser wavelength exceeding 1,530 nm and having all of the following: <ol style="list-style-type: none"> a. Average core diameter equal to or greater than 20 μm; <u>and</u> b. Core ‘NA’ less than 0.1. <p><u>Technical Notes</u></p> <ol style="list-style-type: none"> 1. <i>For the purpose of Category Code 6C005, the core ‘Numerical Aperture’ (‘NA’) is measured at the emission wavelengths of the fibre.</i> 2. <i>Category Code 6C005.b. includes fibres assembled with end caps.</i>

<i>Category Code</i>	<i>Item Description</i>
6D	Software
6D001	“Software” specially designed for the “development” or “production” of equipment specified in Category Code 6A004, 6A005, 6A008 or 6B008.
6D002	“Software” specially designed for the “use” of equipment specified in Category Code 6A002.b., 6A008 or 6B008.
6D003	<p>Other “software” as follows:</p> <p>a. “Software” as follows:</p> <ol style="list-style-type: none"> 1. “Software” specially designed for acoustic beam forming for the “real-time processing” of acoustic data for passive reception using towed hydrophone arrays; 2. “Source code” for the “real-time processing” of acoustic data for passive reception using towed hydrophone arrays; 3. “Software” specially designed for acoustic beam forming for “real-time processing” of acoustic data for passive reception using bottom or bay cable systems; 4. “Source code” for “real-time processing” of acoustic data for passive reception using bottom or bay cable systems; 5. “Software” or “source code”, specially designed for all of the following: <ol style="list-style-type: none"> a. “Real-time processing” of acoustic data from sonar systems specified by Category Code 6A001.a.1.e.; <u>and</u> b. Automatically detecting, classifying and determining the location of divers or swimmers; <p><u>N.B.</u> For diver detection “software” or “source code”, specially designed or modified for military use, see Division 2 of Part 1 of this Schedule.</p>

<i>Category Code</i>	<i>Item Description</i>
	<ul style="list-style-type: none"> b. Not used; c. “Software” designed or modified for cameras incorporating “focal plane arrays” specified in Category Code 6A002.a.3.f. and designed or modified to remove a frame rate restriction and allow the camera to exceed the frame rate specified in Category Code 6A003.b.4. Note 3.a.; d. “Software” specially designed to maintain the alignment and phasing of segmented mirror systems consisting of mirror segments having a diameter or major axis length equal to or larger than 1 m; e. Not used; f. “Software” as follows: <ul style="list-style-type: none"> 1. “Software” specially designed for magnetic and electric field “compensation systems” for magnetic sensors designed to operate on mobile platforms; 2. “Software” specially designed for magnetic and electric field anomaly detection on mobile platforms; 3. “Software” specially designed for “real-time processing” of electromagnetic data using underwater electromagnetic receivers specified in Category Code 6A006.e.; 4. “Source code” for “real-time processing” of electromagnetic data using underwater electromagnetic receivers specified in Category Code 6A006.e.; g. “Software” specially designed to correct motional influences of gravity meters or gravity gradiometers; h. “Software” as follows: <ul style="list-style-type: none"> 1. Air Traffic Control (ATC) “software” application “programmes” designed to be hosted on general purpose computers located at Air Traffic Control centres and capable of accepting radar target data from more than four primary radars; 2. “Software” for the design or “production” of radomes and having all of the following:

<i>Category Code</i>	<i>Item Description</i>
	<p>a. Specially designed to protect the “electronically steerable phased array antennae” specified in Category Code 6A008.e.; <u>and</u></p> <p>b. Resulting in an antenna pattern having an ‘average side lobe level’ more than 40 dB below the peak of the main beam level.</p> <p><i>Technical Note</i> ‘Average side lobe level’ in Category Code 6D003.h.2.b. is measured over the entire array excluding the angular extent of the main beam and the first two side lobes on either side of the main beam.</p>
6D102	“Software” specially designed or modified for the “use” of goods specified in Category Code 6A108.
6D103	“Software” which processes post-flight, recorded data, enabling determination of vehicle position throughout its flight path, specially designed or modified for ‘missiles’. <i>Technical Note</i> In Category Code 6D103, ‘missile’ means complete rocket systems and unmanned aerial vehicle systems capable of a range exceeding 300 km.
6D203	“Software” specially designed to enhance or release the performance of cameras or imaging devices to meet the characteristics of Category Codes 6A203.a. to 6A203.c.

Category Code	Item Description
6E	Technology
6E001	“Technology” (according to the General Technology Note) for the “development” of equipment, materials or “software” specified in Category 6A, 6B, 6C or 6D.
6E002	“Technology” (according to the General Technology Note) for the “production” of equipment or materials specified in Category 6A, 6B or 6C.
6E003	<p>Other “technology”, as follows:</p> <p>a. “Technology” as follows:</p> <ol style="list-style-type: none"> 1. Optical surface coating and treatment “technology”, “required” to achieve an ‘optical thickness’ uniformity of 99.5% or better for optical coatings 500 mm or more in diameter or major axis length and with a total loss (absorption and scatter) of less than 5×10^{-3}; <p><i>N.B.</i> <i>See also Category Code 2E003.f.</i></p> <p><i>Technical Note</i> <i>‘Optical thickness’ is the mathematical product of the index of refraction and the physical thickness of the coating.</i></p> <ol style="list-style-type: none"> 2. Optical fabrication “technology” using single point diamond turning techniques to produce surface finish accuracies of better than 10 nm rms on non-planar surfaces exceeding 0.5 m²; <p>b. “Technology” “required” for the “development”, “production” or “use” of specially designed diagnostic instruments or targets in test facilities for “SHPL” testing or testing or evaluation of materials irradiated by “SHPL” beams.</p>

<i>Category Code</i>	<i>Item Description</i>
6E101	<p>“Technology” (according to the General Technology Note) for the “use” of equipment or “software” specified in Category Code 6A002, 6A007.b. and .c., 6A008, 6A102, 6A107, 6A108, 6B108, 6D102 or 6D103.</p> <p><u>Note</u> <i>Category Code 6E101 only specifies “technology” for equipment specified in Category Code 6A008 when it is designed for airborne applications and is usable in “missiles”.</i></p>
6E201	<p>“Technology” (according to the General Technology Note) for the “use” of equipment specified in Category Code 6A003, 6A005.a.2., 6A005.b.2., 6A005.b.3., 6A005.b.4., 6A005.b.6., 6A005.c.2., 6A005.d.3.c., 6A005.d.4.c., 6A202, 6A203, 6A205, 6A225 or 6A226.</p>
6E203	<p>“Technology”, in the form of codes or keys, to enhance or release the performance of cameras or imaging devices to meet the characteristics of Category Codes 6A203.a. to 6A203.c.</p>

<i>Category Code</i>	<i>Item Description</i>
CATEGORY 7 — NAVIGATION AND AVIONICS	
7A	Systems, Equipment and Components
	<p><u>N.B.</u> <i>For automatic pilots for underwater vehicles, see Category 8. For radar, see Category 6.</i></p>
7A001	<p>Accelerometers as follows and specially designed components therefor:</p> <p><u>N.B.</u> <i>See also Category Code 7A101.</i> <i>For angular or rotational accelerometers, see Category Code 7A001.b.</i></p> <ol style="list-style-type: none"> a. Linear accelerometers having any of the following: <ol style="list-style-type: none"> 1. Specified to function at linear acceleration levels less than or equal to 15 g and having any of the following: <ol style="list-style-type: none"> a. A “bias” “stability” of less (better) than 130 micro g with respect to a fixed calibration value over a period of one year; <u>or</u> b. A “scale factor” “stability” of less (better) than 130 ppm with respect to a fixed calibration value over a period of one year; 2. Specified to function at linear acceleration levels exceeding 15 g but less than or equal to 100 g and having all of the following: <ol style="list-style-type: none"> a. A “bias” “repeatability” of less (better) than 1,250 micro g over a period of one year; <u>and</u> b. A “scale factor” “repeatability” of less (better) than 1,250 ppm over a period of one year; <u>or</u> 3. Designed for use in inertial navigation or guidance systems and specified to function at linear acceleration levels exceeding 100 g;

<i>Category Code</i>	<i>Item Description</i>
7A002	<p data-bbox="413 325 475 354"><u>Note</u></p> <p data-bbox="413 367 1143 462"><i>Category Codes 7A001.a.1. and 7A001.a.2. do not include accelerometers limited to measurement of only vibration or shock.</i></p> <p data-bbox="350 487 1143 550">b. Angular or rotational accelerometers, specified to function at linear acceleration levels exceeding 100 g.</p> <p data-bbox="350 620 1143 683">Gyros or angular rate sensors, having any of the following and specially designed components therefor:</p> <p data-bbox="350 706 404 734"><u>N.B.</u></p> <p data-bbox="350 748 727 776"><i>See also Category Code 7A102.</i></p> <p data-bbox="350 797 1143 860"><i>For angular or rotational accelerometers, see Category Code 7A001.b.</i></p> <p data-bbox="350 883 1143 946">a. Specified to function at linear acceleration levels less than or equal to 100 g and having any of the following:</p> <ol data-bbox="417 969 1143 1268" style="list-style-type: none"> <li data-bbox="417 969 1143 1031">1. A rate range of less than 500 degrees per second and having any of the following: <ol data-bbox="498 1054 1143 1268" style="list-style-type: none"> <li data-bbox="498 1054 1143 1182">a. A “bias” “stability” of less (better) than 0.5 degree per hour, when measured in a 1 g environment over a period of one month, and with respect to a fixed calibration value; <u>or</u> <li data-bbox="498 1205 1143 1268">b. An “angle random walk” of less (better) than or equal to 0.0035 degree per square root hour; <u>or</u> <p data-bbox="565 1290 619 1319"><u>Note</u></p> <p data-bbox="565 1330 1143 1393"><i>Category Code 7A002.a.1.b. does not include “spinning mass gyros”.</i></p>

<i>Category Code</i>	<i>Item Description</i>
7A003	<p data-bbox="417 329 1153 392">2. A rate range greater than or equal to 500 degrees per second and having any of the following:</p> <p data-bbox="502 411 1153 544">a. A “bias” “stability” of less (better) than 4 degrees per hour, when measured in a 1 g environment over a period of three minutes, and with respect to a fixed calibration value; <u>or</u></p> <p data-bbox="502 563 1153 626">b. An “angle random walk” of less (better) than or equal to 0.1 degree per square root hour; <u>or</u></p> <p data-bbox="565 649 1153 753"><u>Note</u> Category Code 7A002.a.2.b. does not include “spinning mass gyros”.</p> <p data-bbox="350 773 1153 835">b. Specified to function at linear acceleration levels exceeding 100 g.</p> <p data-bbox="350 906 1153 969">‘Inertial measurement equipment or systems’, having any of the following:</p> <p data-bbox="350 991 408 1020"><u>N.B.</u></p> <p data-bbox="350 1033 731 1062">See also Category Code 7A103.</p> <p data-bbox="350 1081 435 1110"><u>Note 1</u></p> <p data-bbox="350 1129 1153 1290">‘Inertial measurement equipment or systems’ incorporate accelerometers or gyroscopes to measure changes in velocity and orientation in order to determine or maintain heading or position without requiring an external reference once aligned. ‘Inertial measurement equipment or systems’ include:</p> <ul data-bbox="350 1309 1018 1593" style="list-style-type: none"> – Attitude and Heading Reference Systems (AHRSs); – Gyrocompasses; – Inertial Measurement Units (IMUs); – Inertial Navigation Systems (INSs); – Inertial Reference Systems (IRSs); – Inertial Reference Units (IRUs).

Category Code	Item Description
	<p data-bbox="350 325 431 354"><u>Note 2</u></p> <p data-bbox="350 367 1145 496"><i>Category Code 7A003 does not include ‘inertial measurement equipment or systems’ which are certified for use on “civil aircraft” by civil authorities of one or more “participating states”.</i></p> <p data-bbox="350 519 545 548"><u>Technical Notes</u></p> <ol data-bbox="350 561 1145 1281" style="list-style-type: none"> <li data-bbox="350 561 1145 725">1. <i>‘Positional aiding references’ independently provide position, and include:</i> <ol data-bbox="417 643 1145 725" style="list-style-type: none"> <li data-bbox="417 643 1013 672">a. <i>Global Navigation Satellite Systems (GNSS);</i> <li data-bbox="417 691 1076 719">b. <i>“Data-Based Referenced Navigation” (“DBRN”).</i> <li data-bbox="350 744 1145 908">2. <i>‘Circular Error Probable’ (‘CEP’) - In a circular normal distribution, the radius of the circle containing 50% of the individual measurements being made, or the radius of the circle within which there is a 50% probability of being located.</i> <ol data-bbox="350 929 1145 1281" style="list-style-type: none"> <li data-bbox="350 929 1145 1281">a. <i>Designed for “aircraft”, land vehicles or vessels, providing position without the use of ‘positional aiding references’, and having any of the following accuracies subsequent to normal alignment:</i> <ol data-bbox="417 1081 1145 1281" style="list-style-type: none"> <li data-bbox="417 1081 1145 1148">1. <i>0.8 nautical miles per hour (nm/hr) ‘Circular Error Probable’ (‘CEP’) rate or less (better);</i> <li data-bbox="417 1167 1076 1195">2. <i>0.5% distanced travelled ‘CEP’ or less (better); or</i> <li data-bbox="417 1214 1145 1281">3. <i>Total drift of 1 nautical mile ‘CEP’ or less (better) in a 24-hour period;</i> <p data-bbox="417 1300 599 1328"><u>Technical Note</u></p> <p data-bbox="417 1342 1145 1709"><i>The performance parameters in Category Codes 7A003.a.1., 7A003.a.2. and 7A003.a.3. typically apply to ‘inertial measurement equipment or systems’ designed for “aircraft”, vehicles and vessels, respectively. These parameters result from the utilisation of specialised non-positional aiding references (e.g. altimeter, odometer, velocity log). As a consequence, the specified performance values cannot be readily converted between these parameters. Equipment designed for multiple platforms are evaluated against each applicable Category Code 7A003.a.1., 7A003.a.2. or 7A003.a.3.</i></p>

Category Code	Item Description
	<p>b. Designed for “aircraft”, land vehicles or vessels, with an embedded ‘positional aiding reference’ and providing position after loss of all ‘positional aiding references’ for a period of up to 4 minutes, having an accuracy of less (better) than 10 meters ‘CEP’;</p> <p><i>Technical Note</i> <i>Category Code 7A003.b. refers to systems in which ‘inertial measurement equipment or systems’ and other independent ‘positional aiding references’ are built into a single unit (i.e. embedded) in order to achieve improved performance.</i></p> <p>c. Designed for “aircraft”, land vehicles or vessels, providing heading or True North determination and having any of the following:</p> <ol style="list-style-type: none"> 1. A maximum operating angular rate less (lower) than 500 deg/s and a heading accuracy without the use of ‘positional aiding references’ equal to or less (better) than 0.07 deg sec(Lat) (equivalent to 6 arc minutes rms at 45 degrees latitude); <u>or</u> 2. A maximum operating angular rate equal to or greater (higher) than 500 deg/s and a heading accuracy without the use of ‘positional aiding references’ equal to or less (better) than 0.2 deg sec(Lat) (equivalent to 17 arc minutes rms at 45 degrees latitude); <u>or</u> <p>d. Providing acceleration measurements or angular rate measurements, in more than one dimension, and having any of the following:</p> <ol style="list-style-type: none"> 1. Performance specified by Category Code 7A001 or 7A002 along any axis, without the use of any aiding references; <u>or</u> 2. Being “space-qualified” and providing angular rate measurements having an “angle random walk” along any axis of less (better) than or equal to 0.1 degree per square root hour. <p><i>Note</i> <i>Category Code 7A003.d.2. does not include ‘inertial measurement equipment or systems’ that contain “spinning mass gyros” as the only type of gyro.</i></p>

<i>Category Code</i>	<i>Item Description</i>
7A004	<p>‘Star trackers’ and components therefor, as follows:</p> <p><u>N.B.</u></p> <p><i>See also Category Code 7A104.</i></p> <ol style="list-style-type: none"> a. ‘Star trackers’ with a specified azimuth accuracy of equal to or less (better) than 20 seconds of arc throughout the specified lifetime of the equipment; b. Components specially designed for equipment specified in Category Code 7A004.a. as follows: <ol style="list-style-type: none"> 1. Optical heads or baffles; 2. Data processing units. <p><u>Technical Note</u></p> <p><i>‘Star trackers’ are also referred to as stellar attitude sensors or gyro-astro compasses.</i></p>
7A005	<p>Global Navigation Satellite Systems (GNSS) receiving equipment having any of the following and specially designed components therefor:</p> <p><u>N.B.</u></p> <p><i>See also Category Code 7A105.</i></p> <p><i>For equipment specially designed for military use, see Division 2 of Part 1 of this Schedule.</i></p> <ol style="list-style-type: none"> a. Employing a decryption algorithm specially designed or modified for government use to access the ranging code for position and time; <u>or</u> b. Employing ‘adaptive antenna systems’. <p><u>Note</u></p> <p><i>Category Code 7A005.b. does not include GNSS receiving equipment that only uses components designed to filter, switch or combine signals from multiple omni-directional antennae that do not implement adaptive antenna techniques.</i></p>

Category Code	Item Description
	<p data-bbox="417 325 599 357"><u>Technical Note</u></p> <p data-bbox="417 369 1143 502"><i>For the purpose of Category Code 7A005.b., ‘adaptive antenna systems’ dynamically generate one or more spatial nulls in an antenna array pattern by signal processing in the time domain or frequency domain.</i></p>
7A006	<p data-bbox="353 567 1143 635">Airborne altimeters operating at frequencies other than 4.2 GHz to 4.4 GHz inclusive and having any of the following:</p> <p data-bbox="353 654 407 687"><u>N.B.</u></p> <p data-bbox="353 696 729 729"><i>See also Category Code 7A106.</i></p> <p data-bbox="353 748 823 830">a. “Power management”; <u>or</u> b. Using phase shift key modulation.</p>
7A008	<p data-bbox="353 896 1143 1062">Underwater sonar navigation systems using doppler velocity or correlation velocity logs integrated with a heading source and having a positioning accuracy of equal to or less (better) than 3% of distance travelled ‘Circular Error Probable’ (‘CEP’) and specially designed components therefor.</p> <p data-bbox="353 1081 411 1113"><u>Note</u></p> <p data-bbox="353 1125 1143 1224"><i>Category Code 7A008 does not include systems specially designed for installation on surface vessels or systems requiring acoustic beacons or buoys to provide positioning data.</i></p> <p data-bbox="353 1243 407 1275"><u>N.B.</u></p> <p data-bbox="353 1287 1143 1386"><i>See Category Code 6A001.a. for acoustic systems, and Category Code 6A001.b. for correlation-velocity and Doppler-velocity sonar log equipment.</i></p> <p data-bbox="353 1395 975 1428"><i>See Category Code 8A002 for other marine systems.</i></p>

<i>Category Code</i>	<i>Item Description</i>
7A101	<p>Linear accelerometers, other than those specified in Category Code 7A001, designed for use in inertial navigation systems or in guidance systems of all types, usable in ‘missiles’, having all the following characteristics, and specially designed components therefor:</p> <ol style="list-style-type: none"> <li data-bbox="350 510 1150 578">a. A “bias” “repeatability” of less (better) than 1,250 micro g; <u>and</u> <li data-bbox="350 592 1150 660">b. A “scale factor” “repeatability” of less (better) than 1,250 ppm. <p><u>Note</u> <i>Category Code 7A101 does not include accelerometers specially designed and developed as Measurement While Drilling (MWD) Sensors for use in downhole well service operations.</i></p> <p><u>Technical Notes</u></p> <ol style="list-style-type: none"> <li data-bbox="350 881 1150 978">1. <i>In Category Code 7A101, ‘missile’ means complete rocket systems and unmanned aerial vehicle systems capable of a range exceeding 300 km.</i> <li data-bbox="350 991 1150 1089">2. <i>In Category Code 7A101, the measurement of “bias” and “scale factor” refers to a one sigma standard deviation with respect to a fixed calibration over a period of one year.</i>
7A102	<p>All types of gyros, other than those specified in Category Code 7A002, usable in ‘missiles’, with a rated “drift rate” ‘stability’ of less than 0.5° (1 sigma or rms) per hour in a 1 g environment and specially designed components therefor.</p> <p><u>Technical Notes</u></p> <ol style="list-style-type: none"> <li data-bbox="350 1353 1150 1450">1. <i>In Category Code 7A102, ‘missile’ means complete rocket systems and unmanned aerial vehicle systems capable of a range exceeding 300 km.</i> <li data-bbox="350 1464 1150 1629">2. <i>In Category Code 7A102, ‘stability’ is defined as a measure of the ability of a specific mechanism or performance coefficient to remain invariant when continuously exposed to a fixed operating condition (IEEE STD 528-2001 paragraph 2.247).</i>

<i>Category Code</i>	<i>Item Description</i>
7A103	<p data-bbox="350 325 1145 426">Instrumentation, navigation equipment and systems, other than those specified in Category Code 7A003, as follows; and specially designed components therefor:</p> <p data-bbox="350 445 1145 776"> a. Inertial or other equipment, using accelerometers or gyros as follows, and systems incorporating such equipment: <ol data-bbox="417 529 1145 776" style="list-style-type: none"> <li data-bbox="417 529 1145 630">1. Accelerometers specified in Category Code 7A001.a.3., 7A001.b. or 7A101 or gyros specified in Category Code 7A002 or 7A102; <u>or</u> <li data-bbox="417 649 1145 776">2. Accelerometers specified in Category Code 7A001.a.1. or 7A001.a.2., designed for use in inertial navigation systems or in guidance systems of all types, and usable in ‘missiles’; </p> <p data-bbox="417 801 1145 1005"> <u>Note</u> <i>Category Code 7A103.a. does not include equipment containing accelerometers specified in Category Code 7A001 where such accelerometers are specially designed and developed as MWD (Measurement While Drilling) sensors for use in down-hole well services operations.</i> </p> <p data-bbox="350 1030 1145 1245"> b. Integrated flight instrument systems which include gyrostabilisers or automatic pilots, designed or modified for use in ‘missiles’; c. ‘Integrated navigation systems’, designed or modified for ‘missiles’ and capable of providing a navigational accuracy of 200 m Circle of Equal Probability (CEP) or less; </p> <p data-bbox="417 1264 1145 1700"> <u>Technical Note</u> <i>An ‘integrated navigation system’ typically incorporates the following components:</i> <ol data-bbox="417 1386 1145 1700" style="list-style-type: none"> <li data-bbox="417 1386 1145 1481">a. <i>An inertial measurement device (e.g. an attitude and heading reference system, inertial reference unit, or inertial navigation system);</i> <li data-bbox="417 1500 1145 1658">b. <i>One or more external sensors used to update the position and/or velocity, either periodically or continuously throughout the flight (e.g. satellite navigation receiver, radar altimeter, and/or Doppler radar); <u>and</u></i> <li data-bbox="417 1677 1145 1700">c. <i>Integration hardware and software.</i> </p>

<i>Category Code</i>	<i>Item Description</i>
	<p>d. Three axis magnetic heading sensors, designed or modified to be integrated with flight control and navigation systems, other than those specified in Category Code 6A006, having all the following characteristics, and specially designed components therefor:</p> <ol style="list-style-type: none"> 1. Internal tilt compensation in pitch (± 90 degrees) and roll (± 180 degrees) axes; <u>and</u> 2. Capable of providing azimuthal accuracy better (less) than 0.5 degrees rms at latitude of ± 80 degrees, reference to local magnetic field. <p><u>Note</u> <i>Flight control and navigation systems in Category Code 7A103.d. include gyrostabilisers, automatic pilots and inertial navigation systems.</i></p> <p><u>Technical Note</u> <i>In Category Code 7A103, 'missile' means complete rocket systems and unmanned aerial vehicle systems capable of a range exceeding 300 km.</i></p>
7A104	Gyro-astro compasses and other devices, other than those specified in Category Code 7A004, which derive position or orientation by means of automatically tracking celestial bodies or satellites and specially designed components therefor.
7A105	<p>Receiving equipment for Global Navigation Satellite Systems (GNSS; e.g. GPS, GLONASS, or Galileo), other than those specified in Category Code 7A005, having any of the following characteristics, and specially designed components therefor:</p> <ol style="list-style-type: none"> a. Designed or modified for use in space launch vehicles specified in Category Code 9A004, sounding rockets specified in Category Code 9A104 or unmanned aerial vehicles specified in Category Code 9A012 or 9A112.a.; <u>or</u> b. Designed or modified for airborne applications and having any of the following: <ol style="list-style-type: none"> 1. Capable of providing navigation information at speeds in excess of 600 m/s;

<i>Category Code</i>	<i>Item Description</i>
	<p>2. Employing decryption, designed or modified for military or governmental services, to gain access to GNSS secured signal/data; <u>or</u></p> <p>3. Being specially designed to employ anti-jam features (e.g. null steering antenna or electronically steerable antenna) to function in an environment of active or passive countermeasures.</p> <p><u>Note</u> <i>Category Codes 7A105.b.2. and 7A105.b.3. do not include equipment designed for commercial, civil or ‘Safety of Life’ (e.g. data integrity, flight safety) GNSS services.</i></p>
7A106	<p>Altimeters, other than those specified in Category Code 7A006, of radar or laser radar type, designed or modified for use in space launch vehicles specified in Category Code 9A004 or sounding rockets specified in Category Code 9A104.</p>
7A115	<p>Passive sensors for determining bearing to specific electromagnetic source (direction finding equipment) or terrain characteristics, designed or modified for use in space launch vehicles specified in Category Code 9A004 or sounding rockets specified in Category Code 9A104.</p> <p><u>Note</u> <i>Category Code 7A115 includes sensors for the following equipment:</i></p> <p>a. <i>Terrain contour mapping equipment;</i></p> <p>b. <i>Imaging sensor equipment (both active and passive);</i></p> <p>c. <i>Passive interferometer equipment.</i></p>

<i>Category Code</i>	<i>Item Description</i>
7A116	<p>Flight control systems and servo valves, as follows; designed or modified for use in space launch vehicles specified in Category Code 9A004 or sounding rockets specified in Category Code 9A104:</p> <ul style="list-style-type: none"> a. Hydraulic, mechanical, electro-optical, or electro-mechanical flight control systems (including fly-by-wire types); b. Attitude control equipment; c. Flight control servo valves designed or modified for the systems specified in Category Code 7A116.a. or 7A116.b., and designed or modified to operate in a vibration environment greater than 10 g rms between 20 Hz and 2 kHz.
7A117	<p>“Guidance sets”, usable in “missiles” capable of achieving system accuracy of 3.33% or less of the range (e.g. a “CEP” of 10 km or less at a range of 300 km).</p>
7B	Test, Inspection and Production Equipment
7B001	<p>Test, calibration or alignment equipment, specially designed for equipment specified in Category 7A.</p>
	<p><u>Note</u></p>
	<p><i>Category Code 7B001 does not include test, calibration or alignment equipment for ‘Maintenance Level I’ or ‘Maintenance Level II’.</i></p>
	<p><u>Technical Notes</u></p>
	<p>1. <u>‘Maintenance Level I’</u></p> <p><i>The failure of an inertial navigation unit is detected on the aircraft by indications from the Control and Display Unit (CDU) or by the status message from the corresponding sub-system. By following the manufacturer’s manual, the cause of the failure may be localised at the level of the malfunctioning Line Replaceable Unit (LRU). The operator then removes the LRU and replaces it with a spare.</i></p>

Category Code	Item Description
	<p>2. <u>'Maintenance Level II'</u> <i>The defective LRU is sent to the maintenance workshop (the manufacturer's or that of the operator responsible for level II maintenance). At the maintenance workshop, the malfunctioning LRU is tested by various appropriate means to verify and localise the defective Shop Replaceable Assembly (SRA) module responsible for the failure. This SRA is removed and replaced by an operative spare. The defective SRA (or possibly the complete LRU) is then shipped to the manufacturer. 'Maintenance Level II' does not include the disassembly or repair of controlled accelerometers or gyro sensors.</i></p>
7B002	<p>Equipment specially designed to characterise mirrors for ring "laser" gyros, as follows:</p> <p><u>N.B.</u> <i>See also Category Code 7B102.</i></p> <p>a. Scatterometers having a measurement accuracy of 10 ppm or less (better);</p> <p>b. Profilometers having a measurement accuracy of 0.5 nm (5 angstrom) or less (better).</p>
7B003	<p>Equipment specially designed for the "production" of equipment specified in Category 7A.</p> <p><u>Note</u> <i>Category Code 7B003 includes:</i></p> <ul style="list-style-type: none"> – Gyro tuning test stations; – Gyro dynamic balance stations; – Gyro run-in/motor test stations; – Gyro evacuation and fill stations;

<i>Category Code</i>	<i>Item Description</i>
	<ul style="list-style-type: none"> – <i>Centrifuge fixtures for gyro bearings;</i> – <i>Accelerometer axis align stations;</i> – <i>Fibre optic gyro coil winding machines.</i>
7B102	Reflectometers specially designed to characterise mirrors, for “laser” gyros, having a measurement accuracy of 50 ppm or less (better).
7B103	<p>“Production facilities” and “production equipment” as follows:</p> <ul style="list-style-type: none"> a. “Production facilities” specially designed for equipment specified in Category Code 7A117; b. “Production equipment”, and other test, calibration and alignment equipment, other than that specified in Category Codes 7B001 to 7B003, designed or modified to be used with equipment specified in Category 7A.
7C	<p>Materials</p> <p>None.</p>
7D	<p>Software</p>
7D001	“Software” specially designed or modified for the “development” or “production” of equipment specified in Category 7A or 7B.

<i>Category Code</i>	<i>Item Description</i>
7D002	<p>“Source code” for the operation or maintenance of any inertial navigation equipment, including inertial equipment not specified in Category Code 7A003 or 7A004, or Attitude and Heading Reference Systems (‘AHRS’).</p> <p><u>Note</u></p> <p><i>Category Code 7D002 does not include “source code” for the “use” of gimballed ‘AHRS’.</i></p> <p><u>Technical Note</u></p> <p><i>‘AHRS’ generally differ from Inertial Navigation Systems (INS) in that an ‘AHRS’ provides attitude and heading information and normally does not provide the acceleration, velocity and position information associated with an INS.</i></p>
7D003	<p>Other “software” as follows:</p> <ol style="list-style-type: none"> a. “Software” specially designed or modified to improve the operational performance or reduce the navigational error of systems to the levels specified in Category Code 7A003, 7A004 or 7A008; b. “Source code” for hybrid integrated systems which improves the operational performance or reduces the navigational error of systems to the level specified in Category Code 7A003 or 7A008 by continuously combining heading data with any of the following: <ol style="list-style-type: none"> 1. Doppler radar or sonar velocity data; 2. Global Navigation Satellite Systems (GNSS) reference data; <u>or</u> 3. Data from “Data-Based Referenced Navigation” (“DBRN”) systems; c. Not used; d. Not used;

<i>Category Code</i>	<i>Item Description</i>
7D004	<p>e. Computer-Aided-Design (CAD) “software” specially designed for the “development” of “active flight control systems”, helicopter multi-axis fly-by-wire or fly-by-light controllers or helicopter “circulation-controlled anti-torque or circulation-controlled direction control systems”, whose “technology” is specified in Category Code 7E004.b., 7E004.c.1. or 7E004.c.2.</p> <p>“Source code” incorporating “development” “technology” specified in Category Code 7E004.a.2., 7E004.a.3., 7E004.a.5., 7E004.a.6. or 7E004.b., for any of the following:</p> <p>a. Digital flight management systems for “total control of flight”;</p> <p>b. Integrated propulsion and flight control systems;</p> <p>c. “Fly-by-wire systems” or “fly-by-light systems”;</p> <p>d. Fault-tolerant or self-reconfiguring “active flight control systems”;</p> <p>e. Not used;</p> <p>f. Air data systems based on surface static data; <u>or</u></p> <p>g. Three dimensional displays.</p> <p><u>Note</u> <i>Category Code 7D004 does not include “source code” associated with common computer elements and utilities (e.g. input signal acquisition, output signal transmission, computer programme and data loading, built-in test, task scheduling mechanisms) not providing a specific flight control system function.</i></p>
7D005	<p>“Software” specially designed to decrypt Global Navigation Satellite Systems (GNSS) ranging code designed for government use.</p>

<i>Category Code</i>	<i>Item Description</i>
7D101	<p>“Software” specially designed or modified for the “use” of equipment specified in Category Code 7A001 to 7A006, 7A101 to 7A106, 7A115, 7A116.a., 7A116.b., 7B001, 7B002, 7B003, 7B102 or 7B103.</p>
7D102	<p>Integration “software” as follows:</p> <ol style="list-style-type: none"> a. Integration “software” for the equipment specified in Category Code 7A103.b.; b. Integration “software” specially designed for the equipment specified in Category Code 7A003 or 7A103.a.; c. Integration “software” designed or modified for the equipment specified in Category Code 7A103.c. <p><u>Note</u> <i>A common form of integration “software” employs Kalman filtering.</i></p>
7D103	<p>“Software” specially designed for modelling or simulation of the “guidance sets” specified in Category Code 7A117 or for their design integration with the space launch vehicles specified in Category Code 9A004 or sounding rockets specified in Category Code 9A104.</p> <p><u>Note</u> <i>“Software” specified in Category Code 7D103 remains within the description in that Category when combined with specially designed hardware specified in Category Code 4A102.</i></p>

<i>Category Code</i>	<i>Item Description</i>
7E	Technology
7E001	<p>“Technology” (according to the General Technology Note) for the “development” of equipment or “software”, specified in Category 7A, 7B or Category Codes 7D001, 7D002, 7D003, 7D005 and 7D101 to 7D103.</p> <p><u>Note</u> <i>Category Code 7E001 includes key management “technology” exclusively for equipment specified in Category Code 7A005.a.</i></p>
7E002	<p>“Technology” (according to the General Technology Note) for the “production” of equipment specified in Category 7A or 7B.</p>
7E003	<p>“Technology” (according to the General Technology Note) for the repair, refurbishing or overhaul of equipment specified in Category Codes 7A001 to 7A004.</p> <p><u>Note</u> <i>Category Code 7E003 does not include maintenance “technology” directly associated with calibration, removal or replacement of damaged or unserviceable LRUs and SRAs of a “civil aircraft” as described in ‘Maintenance Level I’ or ‘Maintenance Level II’.</i></p>
7E004	<p><u>N.B.</u> <i>See Technical Notes to Category Code 7B001.</i></p>
7E004	<p>Other “technology” as follows:</p> <ol style="list-style-type: none"> a. “Technology” for the “development” or “production” of any of the following: <ol style="list-style-type: none"> 1. Not used; 2. Air data systems based on surface static data only, i.e. which dispense with conventional air data probes; 3. Three dimensional displays for “aircraft”; 4. Not used;

<i>Category Code</i>	<i>Item Description</i>
	<ol style="list-style-type: none"> 5. Electric actuators (i.e. electromechanical, electrohydrostatic and integrated actuator package) specially designed for “primary flight control”; 6. “Flight control optical sensor array” specially designed for implementing “active flight control systems”; <u>or</u> 7. “DBRN” systems designed to navigate underwater, using sonar or gravity databases, that provide a positioning accuracy equal to or less (better) than 0.4 nautical miles; <p>b. “Development” “technology”, as follows, for “active flight control systems” (including “fly-by-wire systems” or “fly-by-light systems”):</p> <ol style="list-style-type: none"> 1. Photonic-based “technology” for sensing aircraft or flight control component state, transferring flight control data, or commanding actuator movement, “required” for “fly-by-light systems” “active flight control systems”; 2. Not used; 3. Real-time algorithms to analyse component sensor information to predict and preemptively mitigate impending degradation and failures of components within an “active flight control system”; <p><i>Note</i> <i>Category Code 7E004.b.3. does not include algorithms for purpose of off-line maintenance.</i></p> <ol style="list-style-type: none"> 4. Real-time algorithms to identify component failures and reconfigure force and moment controls to mitigate “active flight control system” degradations and failures; <p><i>Note</i> <i>Category Code 7E004.b.4. does not include algorithms for the elimination of fault effects through comparison of redundant data sources, or off-line pre-planned responses to anticipated failures.</i></p> <ol style="list-style-type: none"> 5. Integration of digital flight control, navigation and propulsion control data, into a digital flight management system for “total control of flight”;

Category Code	Item Description
	<p data-bbox="478 325 538 354"><u>Note</u></p> <p data-bbox="478 367 1009 396"><i>Category Code 7E004.b.5. does not include:</i></p> <ol style="list-style-type: none"> <li data-bbox="501 415 1143 548">a. <i>“Development” “technology” for integration of digital flight control, navigation and propulsion control data, into a digital flight management system for “flight path optimisation”;</i> <li data-bbox="501 567 1143 700">b. <i>“Development” “technology” for “aircraft” flight instrument systems integrated solely for VOR, DME, ILS or MLS navigation or approaches.</i> <p data-bbox="415 719 595 748">6. Not used;</p> <p data-bbox="415 767 1143 872">7. “Technology” “required” for deriving the functional requirements for “fly-by-wire systems” having all of the following:</p> <ol style="list-style-type: none"> <li data-bbox="501 891 1143 986">a. ‘Inner-loop’ airframe stability controls requiring loop closure rates of 40 Hz or greater; <u>and</u> <p data-bbox="565 1005 747 1033"><u>Technical Note</u></p> <p data-bbox="565 1052 1143 1148"><i>‘Inner-loop’ refers to functions of “active flight control systems” that automate airframe stability controls.</i></p> <ol style="list-style-type: none"> <li data-bbox="501 1167 1143 1500">b. Having any of the following: <ol style="list-style-type: none"> <li data-bbox="565 1224 1143 1376">1. Corrects an aerodynamically unstable airframe, measured at any point in the design flight envelope, that would lose recoverable control if not corrected within 0.5 seconds; <li data-bbox="565 1405 1143 1500">2. Couples controls in two or more axes while compensating for ‘abnormal changes in aircraft state’; <p data-bbox="633 1519 814 1547"><u>Technical Note</u></p> <p data-bbox="633 1566 1143 1698"><i>‘Abnormal changes in aircraft state’ include in-flight structural damage, loss of engine thrust, disabled control surface, or destabilising shifts in cargo load.</i></p>

<i>Category Code</i>	<i>Item Description</i>
	<p data-bbox="565 325 1153 392">3. Performs the functions specified in Category Code 7E004.b.5.; <u>or</u></p> <p data-bbox="628 411 690 439"><i>Note</i></p> <p data-bbox="628 453 1153 519"><i>Category Code 7E004.b.7.b.3. does not include autopilots.</i></p> <p data-bbox="565 538 1153 738">4. Enables aircraft to have a stable controlled flight, other than during take-off or landing, at greater than 18 degrees angle of attack, 15 degrees side slip, 15 degrees/second pitch or yaw rate, or 90 degrees/second roll rate;</p> <p data-bbox="417 757 1153 858">8. “Technology” “required” for deriving the functional requirements for “fly-by-wire systems” to achieve all of the following:</p> <p data-bbox="502 877 1153 978">a. No loss of control of the aircraft in the event of a consecutive sequence of any two individual faults within the “fly-by-wire system”; <u>and</u></p> <p data-bbox="502 997 1153 1098">b. Probability of loss of control of the aircraft being less (better) than 1×10^{-9} failures per flight hour;</p> <p data-bbox="417 1117 479 1146"><i>Note</i></p> <p data-bbox="417 1159 1153 1359"><i>Category Code 7E004.b. does not include technology associated with common computer elements and utilities (e.g. input signal acquisition, output signal transmission, computer programme and data loading, built-in test, task scheduling mechanisms) not providing a specific flight control system function.</i></p> <p data-bbox="354 1378 1153 1445">c. “Technology” for the “development” of helicopter systems, as follows:</p> <p data-bbox="417 1464 1153 1565">1. Multi-axis fly-by-wire or fly-by-light controllers, which combine the functions of at least two of the following into one controlling element:</p> <p data-bbox="502 1584 801 1612">a. Collective controls;</p> <p data-bbox="502 1631 753 1660">b. Cyclic controls;</p> <p data-bbox="502 1679 733 1707">c. Yaw controls;</p>

<i>Category Code</i>	<i>Item Description</i>
	<ol style="list-style-type: none"> <li data-bbox="413 325 1137 392">2. “Circulation-controlled anti-torque or circulation-controlled directional control systems”; <li data-bbox="413 411 1137 506">3. Rotor blades incorporating “variable geometry airfoils”, for use in systems using individual blade control.
7E101	<p data-bbox="350 576 1137 710">“Technology” (according to the General Technology Note) for the “use” of equipment specified in Category Codes 7A001 to 7A006, 7A101 to 7A106, 7A115 to 7A117, 7B001, 7B002, 7B003, 7B102, 7B103, 7D101 to 7D103.</p>
7E102	<p data-bbox="350 776 1137 910">“Technology” for protection of avionics and electrical sub-systems against electromagnetic pulse (EMP) and electromagnetic interference (EMI) hazards, from external sources, as follows:</p> <ol style="list-style-type: none"> <li data-bbox="350 929 935 963">a. Design “technology” for shielding systems; <li data-bbox="350 982 1137 1039">b. Design “technology” for the configuration of hardened electrical circuits and sub-systems; <li data-bbox="350 1058 1137 1125">c. Design “technology” for the determination of hardening criteria of Category Codes 7E102.a. and 7E102.b.
7E104	<p data-bbox="350 1205 1137 1294">“Technology” for the integration of the flight control, guidance, and propulsion data into a flight management system for optimisation of rocket system trajectory.</p>

Category Code	Item Description
CATEGORY 8 — MARINE	
8A	Systems, Equipment and Components
8A001	<p>Submersible vehicles and surface vessels, as follows:</p> <p><u>N.B.</u></p> <p><i>For equipment for submersible vehicles, see:</i></p> <ul style="list-style-type: none"> – <i>Category 5 – Part 2 “Information Security” for encrypted communication equipment;</i> – <i>Category 6 for sensors;</i> – <i>Categories 7 and 8 for navigation equipment;</i> – <i>Category 8A for underwater equipment.</i> <p>a. Manned, tethered submersible vehicles designed to operate at depths exceeding 1,000 m;</p> <p>b. Manned, untethered submersible vehicles having any of the following:</p> <ol style="list-style-type: none"> 1. Designed to ‘operate autonomously’ and having a lifting capacity of all the following: <ol style="list-style-type: none"> a. 10% or more of their weight in air; <u>and</u> b. 15 kN or more; 2. Designed to operate at depths exceeding 1,000 m; <u>or</u> 3. Having all of the following: <ol style="list-style-type: none"> a. Designed to continuously ‘operate autonomously’ for 10 hours or more; <u>and</u> b. ‘Range’ of 25 nautical miles or more; <p><u>Technical Notes</u></p> <ol style="list-style-type: none"> 1. <i>For the purpose of Category Code 8A001.b., ‘operate autonomously’ means fully submerged, without snorkel, all systems working and cruising at minimum speed at which the submersible can safely control its depth dynamically by using its depth planes only, with no need for a support vessel or support base on the surface, sea-bed or shore, and containing a propulsion system for submerged or surface use.</i>

<i>Category Code</i>	<i>Item Description</i>
	<p data-bbox="417 325 1146 424">2. For the purpose of Category Code 8A001.b., ‘range’ means half the maximum distance a submersible vehicle can ‘operate autonomously’.</p> <p data-bbox="350 443 1146 542">c. Unmanned, tethered submersible vehicles designed to operate at depths exceeding 1,000 m and having any of the following:</p> <ol data-bbox="417 561 1146 710" style="list-style-type: none"> <li data-bbox="417 561 1146 660">1. Designed for self-propelled manoeuvre using propulsion motors or thrusters specified in Category Code 8A002.a.2.; <u>or</u> <li data-bbox="417 679 729 710">2. Fibre optic data link; <p data-bbox="350 729 1146 793">d. Unmanned, untethered submersible vehicles having any of the following:</p> <ol data-bbox="417 813 1146 1014" style="list-style-type: none"> <li data-bbox="417 813 1146 912">1. Designed for deciding a course relative to any geographical reference without real-time human assistance; <li data-bbox="417 931 896 961">2. Acoustic data or command link; <u>or</u> <li data-bbox="417 980 1076 1014">3. Optical data or command link exceeding 1,000 m; <p data-bbox="350 1033 1146 1132">e. Ocean salvage systems with a lifting capacity exceeding 5 MN for salvaging objects from depths exceeding 250 m and having any of the following:</p> <ol data-bbox="417 1151 1146 1403" style="list-style-type: none"> <li data-bbox="417 1151 1146 1250">1. Dynamic positioning systems capable of position keeping within 20 m of a given point provided by the navigation system; <u>or</u> <li data-bbox="417 1269 1146 1403">2. Seafloor navigation and navigation integration systems, for depths exceeding 1,000 m and with positioning accuracies to within 10 m of a predetermined point; <p data-bbox="350 1422 533 1452">f. Not used;</p> <p data-bbox="350 1471 533 1502">g. Not used;</p> <p data-bbox="350 1521 533 1551">h. Not used;</p> <p data-bbox="350 1570 533 1601">i. Not used;</p>

<i>Category Code</i>	<i>Item Description</i>
8A002	<p>Marine systems, equipment and components, as follows:</p> <p><u><i>N.B.</i></u> <i>For underwater communications systems, see Category 5 – Part 1 – Telecommunications.</i></p> <p>a. Systems, equipment and components, specially designed or modified for submersible vehicles and designed to operate at depths exceeding 1,000 m, as follows:</p> <ol style="list-style-type: none"> 1. Pressure housings or pressure hulls with a maximum inside chamber diameter exceeding 1.5 m; 2. Direct current propulsion motors or thrusters; 3. Umbilical cables, and connectors therefor, using optical fibre and having synthetic strength members; 4. Components manufactured from material specified in Category Code 8C001; <p><u><i>Technical Note</i></u> <i>Category Code 8A002.a.4. includes ‘syntactic foam’ specified in Category Code 8C001 when an intermediate stage of manufacture has been performed and it is not yet in the final component form.</i></p> <p>b. Systems specially designed or modified for the automated control of the motion of submersible vehicles specified in Category Code 8A001, using navigation data, having closed loop servo-controls and having any of the following:</p> <ol style="list-style-type: none"> 1. Enabling a vehicle to move within 10 m of a predetermined point in the water column; 2. Maintaining the position of the vehicle within 10 m of a predetermined point in the water column; <u>or</u> 3. Maintaining the position of the vehicle within 10 m while following a cable on or under the seabed; <p>c. Fibre optic pressure hull penetrators;</p>

<i>Category Code</i>	<i>Item Description</i>
	<p>d. Underwater vision systems as follows:</p> <ol style="list-style-type: none"> 1. Television systems and television cameras, as follows: <ol style="list-style-type: none"> a. Television systems (comprising camera, monitoring and signal transmission equipment) having a 'limiting resolution' when measured in air of more than 800 lines and specially designed or modified for remote operation with a submersible vehicle; b. Underwater television cameras having a 'limiting resolution' when measured in air of more than 1,100 lines; c. Low light level television cameras specially designed or modified for underwater use and having all of the following: <ol style="list-style-type: none"> 1. Image intensifier tubes specified in Category Code 6A002.a.2.a.; <u>and</u> 2. More than 150,000 "active pixels" per solid state area array; <p><i><u>Technical Note</u></i> <i>'Limiting resolution' is a measure of horizontal resolution usually expressed in terms of the maximum number of lines per picture height discriminated on a test chart, using IEEE Standard 208/1960 or any equivalent standard.</i></p> <ol style="list-style-type: none"> 2. Systems specially designed or modified for remote operation with an underwater vehicle, employing techniques to minimise the effects of back scatter and including range-gated illuminators or "laser" systems;

<i>Category Code</i>	<i>Item Description</i>
	<p>e. Photographic still cameras specially designed or modified for underwater use below 150 m, with a film format of 35 mm or larger and having any of the following:</p> <ol style="list-style-type: none"> 1. Annotation of the film with data provided by a source external to the camera; 2. Automatic back focal distance correction; <u>or</u> 3. Automatic compensation control specially designed to permit an underwater camera housing to be usable at depths exceeding 1,000 m; <p>f. Not used;</p> <p>g. Light systems specially designed or modified for underwater use, as follows:</p> <ol style="list-style-type: none"> 1. Stroboscopic light systems capable of a light output energy of more than 300 J per flash and a flash rate of more than 5 flashes per second; 2. Argon arc light systems specially designed for use below 1,000 m; <p>h. “Robots” specially designed for underwater use, controlled by using a dedicated computer and having any of the following:</p> <ol style="list-style-type: none"> 1. Systems that control the “robot” using information from sensors which measure force or torque applied to an external object, distance to an external object, or tactile sense between the “robot” and an external object; <u>or</u> 2. The ability to exert a force of 250 N or more or a torque of 250 Nm or more and using titanium based alloys or “composite” “fibrous or filamentary materials” in their structural members;

<i>Category Code</i>	<i>Item Description</i>
	<p>i. Remotely controlled articulated manipulators specially designed or modified for use with submersible vehicles and having any of the following:</p> <ol style="list-style-type: none"> 1. Systems which control the manipulator using information from sensors which measure any of the following: <ol style="list-style-type: none"> a. Torque or force applied to an external object; <u>or</u> b. Tactile sense between the manipulator and an external object; <u>or</u> 2. Controlled by proportional master-slave techniques and having 5 degrees of ‘freedom of movement’ or more; <p><i>Technical Note</i> <i>Only functions having proportionally related motion control using positional feedback are counted when determining the number of degrees of ‘freedom of movement’.</i></p> <p>j. Air independent power systems specially designed for underwater use, as follows:</p> <ol style="list-style-type: none"> 1. Brayton or Rankine cycle engine air independent power systems having any of the following: <ol style="list-style-type: none"> a. Chemical scrubber or absorber systems, specially designed to remove carbon dioxide, carbon monoxide and particulates from recirculated engine exhaust; b. Systems specially designed to use a monoatomic gas; c. Devices or enclosures, specially designed for underwater noise reduction in frequencies below 10 kHz, or special mounting devices for shock mitigation; <u>or</u>

<i>Category Code</i>	<i>Item Description</i>
	<ul style="list-style-type: none"> d. Systems having all of the following: <ul style="list-style-type: none"> 1. Specially designed to pressurise the products of reaction or for fuel reformation; 2. Specially designed to store the products of the reaction; <u>and</u> 3. Specially designed to discharge the products of the reaction against a pressure of 100 kPa or more; 2. Diesel cycle engine air independent systems having all of the following: <ul style="list-style-type: none"> a. Chemical scrubber or absorber systems, specially designed to remove carbon dioxide, carbon monoxide and particulates from recirculated engine exhaust; b. Systems specially designed to use a monoatomic gas; c. Devices or enclosures, specially designed for underwater noise reduction in frequencies below 10 kHz, or special mounting devices for shock mitigation; <u>and</u> d. Specially designed exhaust systems that do not exhaust continuously the products of combustion; 3. “Fuel cell” air independent power systems with an output exceeding 2 kW and having any of the following: <ul style="list-style-type: none"> a. Devices or enclosures, specially designed for underwater noise reduction in frequencies below 10 kHz, or special mounting devices for shock mitigation; <u>or</u>

<i>Category Code</i>	<i>Item Description</i>
	<ul style="list-style-type: none"> b. Systems having all of the following: <ul style="list-style-type: none"> 1. Specially designed to pressurise the products of reaction or for fuel reformation; 2. Specially designed to store the products of the reaction; <u>and</u> 3. Specially designed to discharge the products of the reaction against a pressure of 100 kPa or more; 4. Stirling cycle engine air independent power systems having all of the following: <ul style="list-style-type: none"> a. Devices or enclosures, specially designed for underwater noise reduction in frequencies below 10 kHz, or special mounting devices for shock mitigation; <u>and</u> b. Specially designed exhaust systems which discharge the products of combustion against a pressure of 100 kPa or more; k. Not used; l. Not used; m. Not used; n. Not used; o. Propellers, power transmission systems, power generation systems and noise reduction systems, as follows: <ul style="list-style-type: none"> 1. Not used; 2. Water-screw propeller, power generation systems or transmission systems, designed for use on vessels, as follows: <ul style="list-style-type: none"> a. Controllable-pitch propellers and hub assemblies, rated at more than 30 MW; b. Internally liquid-cooled electric propulsion engines with a power output exceeding 2.5 MW;

<i>Category Code</i>	<i>Item Description</i>
	<p>c. “Superconductive” propulsion engines or permanent magnet electric propulsion engines, with a power output exceeding 0.1 MW;</p> <p>d. Power transmission shaft systems incorporating “composite” material components and capable of transmitting more than 2 MW;</p> <p>e. Ventilated or base-ventilated propeller systems, rated at more than 2.5 MW;</p> <p>3. Noise reduction systems designed for use on vessels of 1,000 tonnes displacement or more, as follows:</p> <p>a. Systems that attenuate underwater noise at frequencies below 500 Hz and consist of compound acoustic mounts for the acoustic isolation of diesel engines, diesel generator sets, gas turbines, gas turbine generator sets, propulsion motors or propulsion reduction gears, specially designed for sound or vibration isolation and having an intermediate mass exceeding 30% of the equipment to be mounted;</p> <p>b. ‘Active noise reduction or cancellation systems’ or magnetic bearings, specially designed for power transmission systems;</p> <p><i>Technical Note</i> <i>‘Active noise reduction or cancellation systems’ incorporate electronic control systems capable of actively reducing equipment vibration by the generation of anti-noise or anti-vibration signals directly to the source.</i></p> <p>p. Pumpjet propulsion systems having all of the following:</p> <ol style="list-style-type: none"> 1. Power output exceeding 2.5 MW; <u>and</u> 2. Using divergent nozzle and flow conditioning vane techniques to improve propulsive efficiency or reduce propulsion-generated underwater-radiated noise;

<i>Category Code</i>	<i>Item Description</i>
	<p>q. Underwater swimming and diving equipment as follows:</p> <ol style="list-style-type: none"> 1. Closed circuit rebreathers; 2. Semi-closed circuit rebreathers; <p><u>Note</u> <i>Category Code 8A002.q. does not include individual rebreathers for personal use when accompanying their users.</i></p> <p><u>N.B.</u> <i>For equipment and devices specially designed for military use, see Division 2 of Part 1 of this Schedule.</i></p> <p>r. Diver deterrent acoustic systems specially designed or modified to disrupt divers and having a sound pressure level equal to or exceeding 190 dB (reference 1 μPa at 1 m) at frequencies of 200 Hz and below.</p> <p><u>Note 1</u> <i>Category Code 8A002.r. does not include diver deterrent systems based on underwater explosive devices, air guns or combustible sources.</i></p> <p><u>Note 2</u> <i>Category Code 8A002.r. includes diver deterrent acoustic systems that use spark gap sources, also known as plasma sound sources.</i></p>
8B	Test, Inspection and Production Equipment
8B001	Water tunnels having a background noise of less than 100 dB (reference 1 μ Pa, 1 Hz), in the frequency range from 0 Hz to 500 Hz and designed for measuring acoustic fields generated by a hydro-flow around propulsion system models.

<i>Category Code</i>	<i>Item Description</i>
8C	Materials
8C001	<p>‘Syntactic foam’ designed for underwater use and having all of the following:</p> <p><u>N.B.</u></p> <p><i>See also Category Code 8A002.a.4.</i></p> <p>a. Designed for marine depths exceeding 1,000 m; <u>and</u></p> <p>b. A density less than 561 kg/m³.</p> <p><u>Technical Note</u></p> <p><i>‘Syntactic foam’ consists of hollow spheres of plastic or glass embedded in a resin matrix.</i></p>
8D	Software
8D001	“Software” specially designed or modified for the “development”, “production” or “use” of equipment or materials, specified in Category 8A, 8B or 8C.
8D002	Specific “software” specially designed or modified for the “development”, “production”, repair, overhaul or refurbishing (re-machining) of propellers specially designed for underwater noise reduction.
8E	Technology
8E001	“Technology” (according to the General Technology Note) for the “development” or “production” of equipment or materials specified in Category 8A, 8B or 8C.

<i>Category Code</i>	<i>Item Description</i>
8E002	<p>Other “technology”, as follows:</p> <ol style="list-style-type: none"> a. “Technology” for the “development”, “production”, repair, overhaul or refurbishing (re-machining) of propellers specially designed for underwater noise reduction; b. “Technology” for the overhaul or refurbishing of equipment specified in Category Code 8A001, 8A002.b., 8A002.j., 8A002.o. or 8A002.p. c. “Technology” (according to the General Technology Note) for the “development” or “production” of any of the following: <ol style="list-style-type: none"> 1. Surface-effect vehicles (fully skirted variety) having all of the following: <ol style="list-style-type: none"> a. Maximum design speed, fully loaded, exceeding 30 knots in a significant wave height of 1.25 m or more; b. Cushion pressure exceeding 3,830 Pa; <u>and</u> c. Light-ship-to-full-load displacement ratio of less than 0.70; 2. Surface-effect vehicles (rigid sidewalls) with a maximum design speed, fully loaded, exceeding 40 knots in a significant wave height of 3.25 m or more; 3. Hydrofoil vessels with active systems for automatically controlling foil systems, with a maximum design speed, fully loaded, of 40 knots or more in a significant wave height of 3.25 m or more; <u>or</u>

<i>Category Code</i>	<i>Item Description</i>
	<p data-bbox="417 325 1145 392">4. 'Small waterplane area vessels' having any of the following:</p> <ul style="list-style-type: none"><li data-bbox="502 411 1145 544">a. Full load displacement exceeding 500 tonnes with a maximum design speed, fully loaded, exceeding 35 knots in a significant wave height of 3.25 m or more; <u>or</u><li data-bbox="502 563 1145 696">b. Full load displacement exceeding 1,500 tonnes with a maximum design speed, fully loaded, exceeding 25 knots in a significant wave height of 4 m or more. <p data-bbox="478 715 663 744"><i><u>Technical Note</u></i></p> <p data-bbox="478 753 1145 887"><i>A 'small waterplane area vessel' is defined by the following formula: waterplane area at an operational design draft less than 2 x (displaced volume at the operational design draft)^{2/3}.</i></p>

Category Code	Item Description
CATEGORY 9 — AEROSPACE AND PROPULSION	
9A	Systems, Equipment and Components
	<p><u>N.B.</u> <i>For propulsion systems designed or rated against neutron or transient ionising radiation, see Division 2 of Part 1 of this Schedule.</i></p>
9A001	<p>Aero gas turbine engines having any of the following:</p> <p><u>N.B.</u> <i>See also Category Code 9A101.</i></p> <p>a. Incorporating any of the “technologies” specified in Category Code 9E003.a., 9E003.h. or 9E003.i.; <u>or</u></p> <p><u>Note 1</u> <i>Category Code 9A001.a. does not include aero gas turbine engines which meet all of the following:</i></p> <p>a. <i>Certified by the civil aviation authority of a “participating state”; <u>and</u></i></p> <p>b. <i>Intended to power non-military manned aircraft for which any of the following has been issued by civil aviation authority of a “participating state” for the aircraft with this specific engine type:</i></p> <ol style="list-style-type: none"> 1. <i>A civil type certificate; <u>or</u></i> 2. <i>An equivalent document recognised by the International Civil Aviation Organisation (ICAO).</i> <p><u>Note 2</u> <i>Category Code 9A001.a. does not include aero gas turbine engines designed for Auxiliary Power Units (APUs) approved by the civil aviation authority of a “participating state”.</i></p> <p>b. Designed to power an aircraft to cruise at Mach 1 or higher, for more than 30 minutes.</p>

<i>Category Code</i>	<i>Item Description</i>
9A002	<p>‘Marine gas turbine engines’ with an ISO standard continuous power rating of 24,245 kW or more and a specific fuel consumption not exceeding 0.219 kg/kWh in the power range from 35% to 100%, and specially designed assemblies and components therefor.</p> <p><u>Note</u> <i>The term ‘marine gas turbine engines’ includes those industrial, or aero-derivative, gas turbine engines adapted for a ship’s electric power generation or propulsion.</i></p>
9A003	<p>Specially designed assemblies or components, incorporating any of the “technologies” specified in Category Code 9E003.a., 9E003.h. or 9E003.i., for any of the following aero gas turbine engines:</p> <ol style="list-style-type: none"> a. Specified in Category Code 9A001; <u>or</u> b. Whose design or production origins are either non-“participating state” or unknown to the manufacturer.
9A004	<p>Space launch vehicles, “spacecraft”, “spacecraft buses”, “spacecraft payloads”, “spacecraft” on-board systems or equipment, and terrestrial equipment, as follows:</p> <p><u>N.B.</u> <i>See also Category Code 9A104.</i></p> <ol style="list-style-type: none"> a. Space launch vehicles; b. “Spacecraft”; c. “Spacecraft buses”; d. “Spacecraft payloads” incorporating items specified in Category Code 3A001.b.1.a.4., 3A002.g., 5A001.a.1., 5A001.b.3., 5A002.a.5., 5A002.a.9., 6A002.a.1., 6A002.a.2., 6A002.b., 6A002.d., 6A003.b., 6A004.c., 6A004.e., 6A008.d., 6A008.e., 6A008.k., 6A008.l. or 9A010.c.;

<i>Category Code</i>	<i>Item Description</i>
	<p>e. On-board systems or equipment, specially designed for “spacecraft” and having any of the following functions:</p> <ol style="list-style-type: none"> 1. ‘Command and telemetry data handling’; <p><u>Note</u> <i>For the purpose of Category Code 9A004.e.1., ‘command and telemetry data handling’ includes bus data management, storage, and processing.</i></p> <ol style="list-style-type: none"> 2. ‘Payload data handling’; <u>or</u> <p><u>Note</u> <i>For the purpose of Category Code 9A004.e.2., ‘payload data handling’ includes payload data management, storage, and processing.</i></p> <ol style="list-style-type: none"> 3. ‘Attitude and orbit control’; <p><u>Note</u> <i>For the purpose of Category Code 9A004.e.3., ‘attitude and orbit control’ includes sensing and actuation to determine and control the position and orientation of a “spacecraft”.</i></p> <p><u>N.B.</u> <i>For equipment specially designed for military use, see Division 2 of Part 1 of this Schedule.</i></p> <p>f. Terrestrial equipment, specially designed for “spacecraft” as follows:</p> <ol style="list-style-type: none"> 1. Telemetry and telecommand equipment; 2. Simulators.
9A005	<p>Liquid rocket propulsion systems containing any of the systems or components, specified in Category Code 9A006.</p> <p><u>N.B.</u> <i>See also Category Codes 9A105 and 9A119.</i></p>

Category Code	Item Description
9A006	<p>Systems and components, specially designed for liquid rocket propulsion systems, as follows:</p> <p><u>N.B.</u></p> <p>See also Category Codes 9A106, 9A108 and 9A120.</p> <ol style="list-style-type: none"> a. Cryogenic refrigerators, flightweight dewars, cryogenic heat pipes or cryogenic systems, specially designed for use in space vehicles and capable of restricting cryogenic fluid losses to less than 30% per year; b. Cryogenic containers or closed-cycle refrigeration systems, capable of providing temperatures of 100 K (-173°C) or less for “aircraft” capable of sustained flight at speeds exceeding Mach 3, launch vehicles or “spacecraft”; c. Slush hydrogen storage or transfer systems; d. High pressure (exceeding 17.5 MPa) turbo pumps, pump components or their associated gas generator or expander cycle turbine drive systems; e. High-pressure (exceeding 10.6 MPa) thrust chambers and nozzles therefor; f. Propellant storage systems using the principle of capillary containment or positive expulsion (i.e. with flexible bladders); g. Liquid propellant injectors with individual orifices of 0.381 mm or smaller in diameter (an area of $1.14 \times 10^{-3} \text{ cm}^2$ or smaller for non-circular orifices) and specially designed for liquid rocket engines; h. One-piece carbon-carbon thrust chambers or one-piece carbon-carbon exit cones, with densities exceeding 1.4 g/cm^3 and tensile strengths exceeding 48 MPa.

<i>Category Code</i>	<i>Item Description</i>
9A007	<p>Solid rocket propulsion systems having any of the following:</p> <p><u>N.B.</u> <i>See also Category Codes 9A107 and 9A119.</i></p> <ol style="list-style-type: none"> a. Total impulse capacity exceeding 1.1 MNs; b. Specific impulse of 2.4 kNs/kg or more, when the nozzle flow is expanded to ambient sea level conditions for an adjusted chamber pressure of 7 MPa; c. Stage mass fractions exceeding 88% and propellant solid loadings exceeding 86%; d. Components specified in Category Code 9A008; <u>or</u> e. Insulation and propellant bonding systems, using direct-bonded motor designs to provide a ‘strong mechanical bond’ or a barrier to chemical migration between the solid propellant and case insulation material. <p><u>Technical Note</u> <i>‘Strong mechanical bond’ means bond strength equal to or more than propellant strength.</i></p>
9A008	<p>Components specially designed for solid rocket propulsion systems, as follows:</p> <p><u>N.B.</u> <i>See also Category Code 9A108.</i></p> <ol style="list-style-type: none"> a. Insulation and propellant bonding systems, using liners to provide a ‘strong mechanical bond’ or a barrier to chemical migration between the solid propellant and case insulation material; <p><u>Technical Note</u> <i>‘Strong mechanical bond’ means bond strength equal to or more than propellant strength.</i></p>

Category Code	Item Description
	<p>b. Filament-wound “composite” motor cases exceeding 0.61 m in diameter or having ‘structural efficiency ratios (PV/W)’ exceeding 25 km;</p> <p><i>Technical Note</i> ‘Structural efficiency ratio (PV/W)’ is the burst pressure (P) multiplied by the vessel volume (V) divided by the total pressure vessel weight (W).</p> <p>c. Nozzles with thrust levels exceeding 45 kN or nozzle throat erosion rates of less than 0.075 mm/s;</p> <p>d. Movable nozzle or secondary fluid injection thrust vector control systems, capable of any of the following:</p> <ol style="list-style-type: none"> 1. Omni-axial movement exceeding $\pm 5^\circ$; 2. Angular vector rotations of $20^\circ/\text{s}$ or more; <u>or</u> 3. Angular vector accelerations of $40^\circ/\text{s}^2$ or more.
9A009	<p>Hybrid rocket propulsion systems having any of the following:</p> <p><i>N.B.</i> See also Category Codes 9A109 and 9A119.</p> <ol style="list-style-type: none"> a. Total impulse capacity exceeding 1.1 MNs; <u>or</u> b. Thrust levels exceeding 220 kN in vacuum exit conditions.
9A010	<p>Specially designed components, systems and structures, for launch vehicles, launch vehicle propulsion systems or “spacecraft”, as follows:</p> <p><i>N.B.</i> See also Category Codes 1A002 and 9A110.</p> <ol style="list-style-type: none"> a. Components and structures, each exceeding 10 kg and specially designed for launch vehicles manufactured using any of the following: <ol style="list-style-type: none"> 1. “Composite” materials consisting of “fibrous or filamentary materials” specified in Category Code 1C010.e. and resins specified in Category Code 1C008 or 1C009.b.;

<i>Category Code</i>	<i>Item Description</i>
	<ol style="list-style-type: none"> <li data-bbox="417 325 1137 605">2. Metal “matrix” “composites” reinforced by any of the following: <ol style="list-style-type: none"> <li data-bbox="502 411 1096 439">a. Material specified in Category Code 1C007; <li data-bbox="502 458 1137 525">b. “Fibrous or filamentary materials” specified in Category Code 1C010; <u>or</u> <li data-bbox="502 544 1137 605">c. Aluminides specified in Category Code 1C002.a.; <u>or</u> <li data-bbox="417 624 1137 691">3. Ceramic “matrix” “composite” materials specified in Category Code 1C007; <p data-bbox="417 710 478 738"><i>Note</i></p> <p data-bbox="417 757 995 786"><i>The weight cut-off is not relevant for nose cones.</i></p> <ol style="list-style-type: none"> <li data-bbox="354 805 1137 1405">b. Components and structures, specially designed for launch vehicle propulsion systems specified in Category Codes 9A005 to 9A009 manufactured using any of the following: <ol style="list-style-type: none"> <li data-bbox="417 919 1137 1024">1. “Fibrous or filamentary materials” specified in Category Code 1C010.e. and resins specified in Category Code 1C008 or 1C009.b.; <li data-bbox="417 1043 1137 1323">2. Metal “matrix” “composites” reinforced by any of the following: <ol style="list-style-type: none"> <li data-bbox="502 1123 1107 1151">a. Materials specified in Category Code 1C007; <li data-bbox="502 1170 1137 1237">b. “Fibrous or filamentary materials” specified in Category Code 1C010; <u>or</u> <li data-bbox="502 1256 1137 1323">c. Aluminides specified in Category Code 1C002.a.; <u>or</u> <li data-bbox="417 1342 1137 1405">3. Ceramic “matrix” “composite” materials specified in Category Code 1C007; <li data-bbox="354 1424 1137 1528">c. Structural components and isolation systems, specially designed to control actively the dynamic response or distortion of “spacecraft” structures; <li data-bbox="354 1547 1137 1671">d. Pulsed liquid rocket engines with thrust-to-weight ratios equal to or more than 1 kN/kg and a response time (the time required to achieve 90% of total rated thrust from start-up) of less than 30 ms.

<i>Category Code</i>	<i>Item Description</i>
9A011	<p>Ramjet, scramjet or combined cycle engines, and specially designed components therefor.</p> <p><u>N.B.</u> See also Category Codes 9A111 and 9A118.</p>
9A012	<p>“Unmanned aerial vehicles” (“UAVs”), unmanned “airships”, related equipment and components, as follows:</p> <p><u>N.B.</u> See also Category Code 9A112.</p> <p>a. “UAVs” or unmanned “airships”, designed to have controlled flight out of the direct ‘natural vision’ of the ‘operator’ and having any of the following:</p> <ol style="list-style-type: none"> 1. Having all of the following: <ol style="list-style-type: none"> a. A maximum ‘endurance’ greater than or equal to 30 minutes but less than 1 hour; <u>and</u> b. Designed to take-off and have stable controlled flight in wind gusts equal to or exceeding 46.3 km/h (25 knots); <u>or</u> 2. A maximum ‘endurance’ of 1 hour or greater; <p><u>Technical Notes</u></p> <ol style="list-style-type: none"> 1. For the purpose of Category Code 9A012.a., ‘operator’ is a person who initiates or commands the “UAV” or unmanned “airship” flight. 2. For the purpose of Category Code 9A012.a., ‘endurance’ is to be calculated for ISA conditions (ISO 2533:1975) at sea level in zero wind. 3. For the purpose of Category Code 9A012.a., ‘natural vision’ means unaided human sight, with or without corrective lenses.

<i>Category Code</i>	<i>Item Description</i>
	<p>b. Related equipment and components, as follows:</p> <ol style="list-style-type: none"> 1. Not used; 2. Not used; 3. Equipment or components, specially designed to convert a manned “aircraft” or manned “airship”, to a “UAV” or unmanned “airship”, specified in Category Code 9A012.a.; 4. Air breathing reciprocating or rotary internal combustion type engines, specially designed or modified to propel “UAVs” or unmanned “airships”, at altitudes above 15,240 metres (50,000 feet).
9A101	<p>Turbojet and turbofan engines, other than those specified in Category Code 9A001, as follows:</p> <p>a. Engines having both of the following characteristics:</p> <ol style="list-style-type: none"> 1. ‘Maximum thrust value’ greater than 400 N (achieved un-installed) excluding civil certified engines with a ‘maximum thrust value’ greater than 8,890 N (achieved un-installed); <u>and</u> 2. Specific fuel consumption of 0.15 kg/N/hr or less (at maximum continuous power at sea level static conditions using the ICAO standard atmosphere); <p><i><u>Technical Note</u></i></p> <p><i>For the purpose of Category Code 9A101.a.1., ‘maximum thrust value’ is the manufacturer’s demonstrated maximum thrust for the engine type un-installed. The civil type certified thrust value will be equal to or less than the manufacturer’s demonstrated maximum thrust for the engine type.</i></p> <p>b. Engines designed or modified for use in “missiles” or unmanned aerial vehicles specified in Category Code 9A012 or 9A112.a.</p>

Category Code	Item Description
9A102	<p>‘Turboprop engine systems’ specially designed for unmanned aerial vehicles specified in Category Code 9A012 or 9A112.a., and specially designed components therefor, having a ‘maximum power’ greater than 10 kW.</p> <p><u>Note</u> Category Code 9A102 does not include civil certified engines.</p> <p><u>Technical Notes</u></p> <ol style="list-style-type: none"> 1. For the purpose of Category Code 9A102, a ‘turboprop engine system’ incorporates all of the following: <ol style="list-style-type: none"> a. Turboshaft engine; <u>and</u> b. Power transmission system to transfer the power to a propeller. 2. For the purpose of Category Code 9A102, the ‘maximum power’ is achieved uninstalled at sea level static conditions using the ICAO standard atmosphere.
9A104	<p>Sounding rockets, capable of a range of at least 300 km.</p> <p><u>N.B.</u> See also Category Code 9A004.</p>
9A105	<p>Liquid propellant rocket engines, as follows:</p> <p><u>N.B.</u> See also Category Code 9A119.</p> <ol style="list-style-type: none"> a. Liquid propellant rocket engines usable in “missiles”, other than those specified in Category Code 9A005, integrated, or designed or modified to be integrated, into a liquid propellant propulsion system which has a total impulse capacity equal to or greater than 1.1 MNs; b. Liquid propellant rocket engines, usable in complete rocket systems or unmanned aerial vehicles, capable of a range of 300 km, other than those specified in Category Code 9A005 or 9A105.a., integrated, or designed or modified to be integrated, into a liquid propellant propulsion system which has a total impulse capacity equal to or greater than 0.841 MNs.

<i>Category Code</i>	<i>Item Description</i>
9A106	<p>Systems or components, other than those specified in Category Code 9A006 as follows, specially designed for liquid rocket propulsion systems:</p> <ol style="list-style-type: none"> a. Ablative liners for thrust or combustion chambers, usable in “missiles”, space launch vehicles specified in Category Code 9A004 or sounding rockets specified in Category Code 9A104; b. Rocket nozzles, usable in “missiles”, space launch vehicles specified in Category Code 9A004 or sounding rockets specified in Category Code 9A104; c. Thrust vector control sub-systems, usable in “missiles”; <p><u>Technical Note</u> <i>Examples of methods of achieving thrust vector control specified in Category Code 9A106.c. are:</i></p> <ol style="list-style-type: none"> a. <i>Flexible nozzle;</i> b. <i>Fluid or secondary gas injection;</i> c. <i>Movable engine or nozzle;</i> d. <i>Deflection of exhaust gas stream (jet vanes or probes);<u>or</u></i> e. <i>Thrust tabs.</i> <ol style="list-style-type: none"> d. Liquid, slurry and gel propellant (including oxidisers) control systems, and specially designed components therefor, usable in “missiles”, designed or modified to operate in vibration environments greater than 10 g rms between 20 Hz and 2 kHz. <p><u>Note</u> <i>The only servo valves, pumps and gas turbines specified in Category Code 9A106.d., are the following:</i></p> <ol style="list-style-type: none"> a. <i>Servo valves designed for flow rates equal to or greater than 24 litres per minute, at an absolute pressure equal to or greater than 7 MPa, that have an actuator response time of less than 100 ms;</i>

Category Code	Item Description
	<ul style="list-style-type: none"> b. <i>Pumps, for liquid propellants, with shaft speeds equal to or greater than 8,000 rpm at a maximum operating mode or with discharge pressures equal to or greater than 7 MPa.</i> c. <i>Gas turbines, for liquid propellant turbopumps, with shaft speeds equal to or greater than 8,000 rpm at the maximum operating mode.</i> e. <i>Combustion chambers and nozzles, usable in “missiles”, space launch vehicles specified in Category Code 9A004 or sounding rockets specified in Category Code 9A104.</i>
9A107	<p>Solid propellant rocket engines, usable in complete rocket systems or unmanned aerial vehicles, capable of a range of 300 km, other than those specified in Category Code 9A007, having total impulse capacity equal to or greater than 0.841 MNs.</p> <p><u>N.B.</u> See also Category Code 9A119.</p>
9A108	<p>Components, other than those specified in Category Code 9A008, as follows, specially designed for solid rocket propulsion systems:</p> <ul style="list-style-type: none"> a. <i>Rocket motor cases and “insulation” components therefor, usable in “missiles”, space launch vehicles specified in Category Code 9A004 or sounding rockets specified in Category Code 9A104;</i> b. <i>Rocket nozzles, usable in “missiles”, space launch vehicles specified in Category Code 9A004 or sounding rockets specified in Category Code 9A104;</i> c. <i>Thrust vector control sub-systems, usable in “missiles”.</i> <p><u>Technical Note</u> <i>Examples of methods of achieving thrust vector control specified in Category Code 9A108.c. are:</i></p> <ul style="list-style-type: none"> a. <i>Flexible nozzle;</i> b. <i>Fluid or secondary gas injection;</i> c. <i>Movable engine or nozzle;</i>

<i>Category Code</i>	<i>Item Description</i>
	<p>d. <i>Deflection of exhaust gas stream (jet vanes or probes);</i> <i>or</i></p> <p>e. <i>Thrust tabs.</i></p>
9A109	<p>Hybrid rocket motors and specially designed components, as follows:</p> <p>a. Hybrid rocket motors usable in complete rocket systems or unmanned aerial vehicles, capable of 300 km, other than those specified in Category Code 9A009, having a total impulse capacity equal to or greater than 0.841 MNs, and specially designed components therefor;</p> <p>b. Specially designed components for hybrid rocket motors specified in Category Code 9A009 that are usable in “missiles”.</p> <p><u>N.B.</u> <i>See also Category Codes 9A009 and 9A119.</i></p>
9A110	<p>Composite structures, laminates and manufactures thereof, other than those specified in Category Code 9A010, specially designed for use in ‘missiles’ or the sub-systems specified in Category Code 9A005, 9A007, 9A105, 9A106.c., 9A107, 9A108.c., 9A116 or 9A119.</p> <p><u>N.B.</u> <i>See also Category Code 1A002.</i></p> <p><u>Technical Note</u> <i>In Category Code 9A110, ‘missile’ means complete rocket systems and unmanned aerial vehicle systems capable of a range exceeding 300 km.</i></p>

<i>Category Code</i>	<i>Item Description</i>
9A111	<p>Pulse jet engines, usable in “missiles” or unmanned aerial vehicles specified in Category Code 9A012 or 9A112.a., and specially designed components therefor.</p> <p><u><i>N.B.</i></u> <i>See also Category Codes 9A011 and 9A118.</i></p>
9A112	<p>“Unmanned aerial vehicles” (“UAVs”), other than those specified in Category Code 9A012, as follows:</p> <ol style="list-style-type: none"> a. “Unmanned aerial vehicles” (“UAVs”) capable of a range of 300 km; b. “Unmanned aerial vehicles” (“UAVs”) having all of the following: <ol style="list-style-type: none"> 1. Having any of the following: <ol style="list-style-type: none"> a. An autonomous flight control and navigation capability; <u>or</u> b. Capability of controlled flight out of direct vision range involving a human operator; <u>and</u> 2. Having any of the following: <ol style="list-style-type: none"> a. Incorporating an aerosol dispensing system or mechanism with a capacity greater than 20 litres; <u>or</u> b. Designed or modified to incorporate an aerosol dispensing system or mechanism with a capacity greater than 20 litres. <p><u><i>Technical Notes</i></u></p> <ol style="list-style-type: none"> 1. <i>An aerosol consists of particulate or liquids other than fuel components, by products or additives, as part of the “payload” to be dispersed in the atmosphere. Examples of aerosols include pesticides for crop dusting and dry chemicals for cloud seeding.</i>

Category Code	Item Description
	<p>2. <i>An aerosol dispensing system or mechanism contains all those devices (mechanical, electrical, hydraulic, etc.), which are necessary for storage and dispersion of an aerosol into the atmosphere. This includes the possibility of aerosol injection into the combustion exhaust vapour and into the propeller slip stream.</i></p>
9A115	<p>Launch support equipment as follows:</p> <ol style="list-style-type: none"> a. Apparatus and devices for handling, control, activation or launching, designed or modified for space launch vehicles specified in Category Code 9A004, sounding rockets specified in Category Code 9A104 or unmanned aerial vehicles specified in Category Code 9A012 or 9A112.a.; b. Vehicles for transport, handling, control, activation or launching, designed or modified for space launch vehicles specified in Category Code 9A004 or sounding rockets specified in Category Code 9A104.
9A116	<p>Re-entry vehicles, usable in “missiles”, and equipment designed or modified therefor, as follows:</p> <ol style="list-style-type: none"> a. Re-entry vehicles; b. Heat shields and components therefor, fabricated of ceramic or ablative materials; c. Heat sinks and components therefor, fabricated of light-weight, high heat capacity materials; d. Electronic equipment specially designed for re-entry vehicles.
9A117	<p>Staging mechanisms, separation mechanisms, and interstages, usable in “missiles”.</p> <p><u>N.B.</u> See also Category Code 9A121.</p>

<i>Category Code</i>	<i>Item Description</i>
9A118	Devices to regulate combustion usable in engines, which are usable in “missiles” or unmanned aerial vehicles specified in Category Code 9A012 or 9A112.a., specified in Category Code 9A011 or 9A111.
9A119	Individual rocket stages, usable in complete rocket systems or unmanned aerial vehicles, capable of a range of 300 km, other than those specified in Category Codes 9A005, 9A007, 9A009, 9A105, 9A107 and 9A109.
9A120	<p>Liquid propellant tanks, other than those specified in Category Code 9A006, specially designed for propellants specified in Category Code 1C111 or ‘other liquid propellants’, used in rocket systems capable of delivering at least a 500 kg payload to a range of at least 300 km.</p> <p><u>Note</u> <i>In Category Code 9A120, ‘other liquid propellants’ includes, but is not limited to, propellants specified in Division 2 of Part 1 of this Schedule.</i></p>
9A121	<p>Umbilical and interstage electrical connectors specially designed for “missiles”, space launch vehicles specified in Category Code 9A004 or sounding rockets specified in Category Code 9A104.</p> <p><u>Technical Note</u> <i>Interstage connectors referred to in Category Code 9A121 also include electrical connectors installed between the “missile”, space launch vehicle or sounding rocket and their payload.</i></p>

<i>Category Code</i>	<i>Item Description</i>
9A350	<p data-bbox="354 325 1135 420">Spraying or fogging systems, specially designed or modified for fitting to aircraft, “lighter-than-air vehicles” or unmanned aerial vehicles, and specially designed components therefor, as follows:</p> <ol data-bbox="354 443 1135 811" style="list-style-type: none"> <li data-bbox="354 443 1135 573">a. Complete spraying or fogging systems capable of delivering, from a liquid suspension, an initial droplet ‘VMD’ of less than 50 μm at a flow rate of greater than two litres per minute; <li data-bbox="354 595 1135 725">b. Spray booms or arrays of aerosol generating units capable of delivering, from a liquid suspension, an initial droplet ‘VMD’ of less than 50 μm at a flow rate of greater than two litres per minute; <li data-bbox="354 748 1135 811">c. Aerosol generating units specially designed for fitting to systems specified in Category Codes 9A350.a. and .b. <p data-bbox="417 833 478 858"><u>Note</u></p> <p data-bbox="417 872 1135 967"><i>Aerosol generating units are devices specially designed or modified for fitting to aircraft such as nozzles, rotary drum atomisers and similar devices.</i></p> <p data-bbox="354 991 415 1016"><u>Note</u></p> <p data-bbox="354 1030 1135 1125"><i>Category Code 9A350 does not include spraying or fogging systems and components that are demonstrated not to be capable of delivering biological agents in the form of infectious aerosols.</i></p> <p data-bbox="354 1150 549 1174"><u>Technical Notes</u></p> <ol data-bbox="354 1188 1135 1538" style="list-style-type: none"> <li data-bbox="354 1188 1135 1317">1. <i>Droplet size for spray equipment or nozzles specially designed for use on aircraft, “lighter-than-air vehicles” or unmanned aerial vehicles should be measured using either of the following:</i> <ol data-bbox="417 1340 888 1424" style="list-style-type: none"> <li data-bbox="417 1340 753 1372">a. <i>Doppler laser method;</i> <li data-bbox="417 1395 888 1424">b. <i>Forward laser diffraction method.</i> <li data-bbox="354 1443 1135 1538">2. <i>In Category Code 9A350, ‘VMD’ means Volume Median Diameter and for water-based systems this equates to Mass Median Diameter (MMD).</i>

<i>Category Code</i>	<i>Item Description</i>
9B	Test, Inspection and Production Equipment
9B001	<p>Equipment, tooling and fixtures, specially designed for manufacturing gas turbine blades, vanes or “tip shroud” castings, as follows:</p> <ol style="list-style-type: none"> a. Directional solidification or single crystal casting equipment; b. Cores or shells (moulds), specially designed for casting, manufactured from refractory metals or ceramics; c. Directional-solidification or single-crystal additive-manufacturing equipment.
9B002	<p>On-line (real-time) control systems, instrumentation (including sensors) or automated data acquisition and processing equipment, having all of the following:</p> <ol style="list-style-type: none"> a. Specially designed for the “development” of gas turbine engines, assemblies or components; <u>and</u> b. Incorporating “technology” specified in Category Code 9E003.h. or 9E003.i.
9B003	<p>Equipment specially designed for the “production” or test of gas turbine brush seals designed to operate at tip speeds exceeding 335 m/s and temperatures in excess of 773 K (500°C), and specially designed components or accessories therefor.</p>
9B004	<p>Tools, dies or fixtures, for the solid state joining of “superalloy”, titanium or intermetallic airfoil-to-disk combinations described in Category Code 9E003.a.3. or 9E003.a.6. for gas turbines.</p>

Category Code	Item Description
9B005	<p>On-line (real-time) control systems, instrumentation (including sensors) or automated data acquisition and processing equipment, specially designed for use with any of the following:</p> <p><u>N.B.</u> See also Category Code 9B105.</p> <p>a. Wind tunnels designed for speeds of Mach 1.2 or more;</p> <p><u>Note</u> Category Code 9B005.a. does not include wind tunnels specially designed for educational purposes and having a 'test section size' (measured laterally) of less than 250 mm.</p> <p><u>Technical Note</u> 'Test section size' means the diameter of the circle, or the side of the square, or the longest side of the rectangle, at the largest test section location.</p> <p>b. Devices for simulating flow-environments at speeds exceeding Mach 5, including hot-shot tunnels, plasma arc tunnels, shock tubes, shock tunnels, gas tunnels and light gas guns; <u>or</u></p> <p>c. Wind tunnels or devices, other than two-dimensional sections, capable of simulating Reynolds number flows exceeding 25×10^6.</p>
9B006	<p>Acoustic vibration test equipment capable of producing sound pressure levels of 160 dB or more (referenced to 20 μPa) with a rated output of 4 kW or more at a test cell temperature exceeding 1,273 K (1,000°C), and specially designed quartz heaters therefor.</p> <p><u>N.B.</u> See also Category Code 9B106.</p>
9B007	<p>Equipment specially designed for inspecting the integrity of rocket motors and using Non-Destructive Test (NDT) techniques other than planar X-ray or basic physical or chemical analysis.</p>

<i>Category Code</i>	<i>Item Description</i>
9B008	Direct measurement wall skin friction transducers specially designed to operate at a test flow total (stagnation) temperature exceeding 833 K (560°C).
9B009	Tooling specially designed for producing turbine engine powder metallurgy rotor components capable of operating at stress levels of 60% of Ultimate Tensile Strength (UTS) or more and metal temperatures of 873 K (600°C) or more.
9B010	Equipment specially designed for the production of items specified in Category Code 9A012.
9B105	<p data-bbox="354 830 1137 896">'Aerodynamic test facilities' for speeds of Mach 0.9 or more, usable for 'missiles' and their sub-systems.</p> <p data-bbox="354 915 411 944"><u>N.B.</u></p> <p data-bbox="354 957 731 986"><i>See also Category Code 9B005.</i></p> <p data-bbox="354 1005 413 1033"><u>Note</u></p> <p data-bbox="354 1049 1137 1148"><i>Category Code 9B105 does not include wind tunnels for speeds of Mach 3 or less with dimension of the 'test cross section size' equal to or less than 250 mm.</i></p> <p data-bbox="354 1167 548 1195"><u>Technical Notes</u></p> <ol data-bbox="354 1210 1137 1643" style="list-style-type: none"> <li data-bbox="354 1210 1137 1309"><i>1. In Category Code 9B105, 'aerodynamics test facilities' includes wind tunnels and shock tunnels for the study of airflow over objects.</i> <li data-bbox="354 1328 1137 1528"><i>2. In Note to Category Code 9B105, 'test cross section size' means the diameter of the circle, or the side of the square, or the longest side of the rectangle, or the major axis of the ellipse at the largest 'test cross section' location. 'Test cross section' is the section perpendicular to the flow direction.</i> <li data-bbox="354 1547 1137 1643"><i>3. In Category Code 9B105, 'missile' means complete rocket systems and unmanned aerial vehicle systems capable of a range exceeding 300 km.</i>

<i>Category Code</i>	<i>Item Description</i>
9B106	<p>Environmental chambers and anechoic chambers, as follows:</p> <ol style="list-style-type: none"> a. Environmental chambers capable of simulating all of the following flight conditions: <ol style="list-style-type: none"> 1. Having any of the following: <ol style="list-style-type: none"> a. Altitude equal to or greater than 15 km; <u>or</u> b. Temperature range from below 223 K (-50°C) to above 398 K (+125°C); <u>and</u> 2. Incorporating, or ‘designed or modified’ to incorporate, a shaker unit or other vibration test equipment to produce vibration environments equal to or greater than 10 g rms, measured ‘bare table’, between 20 Hz and 2 kHz while imparting forces equal to or greater than 5 kN; <p><i>Technical Notes</i></p> <ol style="list-style-type: none"> 1. <i>Category Code 9B106.a.2. describes systems that are capable of generating a vibration environment with a single wave (e.g. a sine wave) and systems capable of generating a broad band random vibration (i.e. power spectrum).</i> 2. <i>In Category Code 9B106.a.2., ‘designed or modified’ means the environmental chamber provides appropriate interfaces (e.g. sealing devices) to incorporate a shaker unit or other vibration test equipment as specified in Category Code 2B116.</i> 3. <i>In Category Code 9B106.a.2., ‘bare table’ means a flat table, or surface, with no fixture or fittings.</i> b. Environmental chambers capable of simulating all of the following flight conditions: <ol style="list-style-type: none"> 1. Acoustic environments at an overall sound pressure level of 140 dB or greater (referenced to 20 µPa) or with a total rated acoustic power output of 4 kW or greater; <u>and</u>

<i>Category Code</i>	<i>Item Description</i>
	2. Having any of the following: <ol style="list-style-type: none"> a. Altitude equal to greater than 15 km; <u>or</u> b. Temperature range from below 223 K (-50°C) to above 398 K (+125°C).
9B115	Specially designed “production equipment” for the systems, sub-systems and components specified in Category Codes 9A005 to 9A009, 9A011, 9A101, 9A102, 9A105 to 9A109, 9A111, 9A116 to 9A120.
9B116	Specially designed “production facilities” for the space launch vehicles specified in Category Code 9A004, or systems, sub-systems, and components specified in Category Codes 9A005 to 9A009, 9A011, 9A101, 9A102, 9A104 to 9A109, 9A111, 9A116 to 9A120 or ‘missiles’. <u>Technical Note</u> <i>In Category Code 9B116, ‘missile’ means complete rocket systems and unmanned aerial vehicle systems capable of a range exceeding 300 km.</i>
9B117	Test benches and test stands for solid or liquid propellant rockets or rocket motors, having either of the following characteristics: <ol style="list-style-type: none"> a. The capacity to handle more than 68 kN of thrust; <u>or</u> b. Capable of simultaneously measuring the three axial thrust components.

Category Code	Item Description
9C	Materials
9C108	<p>“Insulation” material in bulk form and “interior lining”, other than those specified in Category Code 9A008, for rocket motor cases usable in “missiles” or specially designed for ‘missiles’.</p> <p><u>Technical Note</u> <i>In Category Code 9C108, ‘missile’ means complete rocket systems and unmanned aerial vehicle systems capable of a range exceeding 300 km.</i></p>
9C110	<p>Resin impregnated fibre prepregs and metal coated fibre preforms therefor, for composite structures, laminates and manufactures specified in Category Code 9A110, made either with organic matrix or metal matrix utilising fibrous or filamentary reinforcements having a “specific tensile strength” greater than 7.62×10^4 m and a “specific modulus” greater than 3.18×10^6 m.</p> <p><u>N.B.</u> <i>See also Category Codes 1C010 and 1C210.</i></p> <p><u>Note</u> <i>The only resin impregnated fibre prepregs specified in Category Code 9C110 are those using resins with a glass transition temperature (T_g), after cure, exceeding 418 K (145°C) as determined by ASTM D4065 or equivalent.</i></p>
9D	Software
9D001	<p>“Software” specially designed or modified for the “development” of equipment or “technology”, specified in Category Codes 9A001 to 9A119, Category 9B or Category Code 9E003.</p>
9D002	<p>“Software” specially designed or modified for the “production” of equipment specified in Category Codes 9A001 to 9A119 or Category 9B.</p>

<i>Category Code</i>	<i>Item Description</i>
9D003	“Software” incorporating “technology” specified in Category Code 9E003.h. and used in “FADEC Systems” for systems specified in Category 9A or equipment specified in Category 9B.
9D004	<p>Other “software” as follows:</p> <ol style="list-style-type: none"> a. 2D or 3D viscous “software”, validated with wind tunnel or flight test data required for detailed engine flow modelling; b. “Software” for testing aero gas turbine engines, assemblies or components, specially designed to collect, reduce and analyse data in real time and capable of feedback control, including the dynamic adjustment of test articles or test conditions, as the test is in progress; c. “Software” specially designed to control directional solidification or single crystal material growth in equipment specified in Category Code 9B001.a. or 9B001.c.; d. Not used; e. “Software” specially designed or modified for the operation of items specified in Category Code 9A012; f. “Software” specially designed to design the internal cooling passages of aero gas turbine blades, vanes and “tip shrouds”; g. “Software” having all of the following: <ol style="list-style-type: none"> 1. Specially designed to predict aero thermal, aeromechanical and combustion conditions in aero gas turbine engines; <u>and</u> 2. Theoretical modelling predictions of the aero thermal, aeromechanical and combustion conditions, which have been validated with actual aero gas turbine engine (experimental or production) performance data.

<i>Category Code</i>	<i>Item Description</i>
9D005	“Software” specially designed or modified for the operation of items specified in Category Code 9A004.e. or 9A004.f.
9D101	“Software” specially designed or modified for the “use” of goods specified in Category Code 9B105, 9B106, 9B116 or 9B117.
9D103	<p>“Software” specially designed for modelling, simulation or design integration of the space launch vehicles specified in Category Code 9A004 or sounding rockets specified in Category Code 9A104, or “missiles” or the sub-systems specified in Category Code 9A005, 9A007, 9A105, 9A106.c., 9A107, 9A108.c., 9A116 or 9A119.</p> <p><u>Note</u></p> <p><i>“Software” specified in Category Code 9D103 remains within the description of that Category when combined with specially designed hardware specified in Category Code 4A102.</i></p>
9D104	<p>“Software” specially designed or modified for the “use” of goods specified in Category Code 9A001, 9A005, 9A006.d., 9A006.g., 9A007.a., 9A008.d., 9A009.a., 9A010.d., 9A011, 9A101, 9A102, 9A105, 9A106.c., 9A106.d., 9A107, 9A108.c., 9A109, 9A111, 9A115.a., 9A116.d., 9A117 or 9A118.</p>
9D105	<p>“Software” which coordinates the function of more than one sub-system, other than that specified in Category Code 9D004.e. specially designed or modified for “use” in space launch vehicles specified in Category Code 9A004 or sounding rockets specified in Category Code 9A104 or ‘missiles’.</p> <p><u>Technical Note</u></p> <p><i>In Category Code 9D105, ‘missile’ means complete rocket systems and unmanned aerial vehicle systems capable of a range exceeding 300 km.</i></p>

Category Code	Item Description
9E	<p data-bbox="354 325 502 357">Technology</p> <p data-bbox="354 376 413 409"><u>Note</u></p> <p data-bbox="354 420 1145 687">“Development” or “production” “technology” specified in Category Codes 9E001 to 9E003 for gas turbine engines remains within the description of that Category when used for repair or overhaul. Excluded from that Category are: technical data, drawings or documentation for maintenance activities directly associated with calibration, removal or replacement of damaged or unserviceable line replaceable units, including replacement of whole engines or engine modules.</p> <p data-bbox="229 757 306 790">9E001</p> <p data-bbox="354 757 1145 891">“Technology” (according to the General Technology Note) for the “development” of equipment or “software”, specified in Category Code 9A001.b., 9A004 to 9A012, 9A350, Category 9B or 9D.</p> <p data-bbox="229 961 306 993">9E002</p> <p data-bbox="354 961 1145 1056">“Technology” (according to the General Technology Note) for the “production” of equipment specified in Category Code 9A001.b., 9A004 to 9A011, 9A350 or Category 9B.</p> <p data-bbox="354 1075 413 1108"><u>N.B.</u></p> <p data-bbox="354 1119 1145 1182">For “technology” for the repair of structures, laminates or materials, see Category Code 1E002.f.</p> <p data-bbox="229 1252 306 1285">9E003</p> <p data-bbox="354 1252 727 1285">Other “technology” as follows:</p> <p data-bbox="354 1304 1145 1622"> a. “Technology” “required” for the “development” or “production” of any of the following gas turbine engine components or systems: <ol style="list-style-type: none"> <li data-bbox="422 1424 1145 1622">1. Gas turbine blades, vanes or “tip shrouds”, made from directionally solidified (DS) or single crystal (SC) alloys and having (in the 001 Miller Index Direction) a stress-rupture life exceeding 400 hours at 1,273 K (1,000°C) at a stress of 200 MPa, based on the average property values; </p>

Category Code	Item Description
	<p data-bbox="417 325 971 357">2. Combustors having any of the following:</p> <ul style="list-style-type: none"> <li data-bbox="504 376 1137 477">a. Thermally decoupled liners designed to operate at ‘combustor exit temperature’ exceeding 1,883 K (1,610°C); <li data-bbox="504 496 807 529">b. Non-metallic liners; <li data-bbox="504 548 841 580">c. Non-metallic shells; <u>or</u> <li data-bbox="504 599 1137 725">d. Liners designed to operate at ‘combustor exit temperature’ exceeding 1,883 K (1,610°C) and having holes that meet the parameters specified by Category Code 9E003.c.; <p data-bbox="481 748 541 776"><u>Note</u></p> <p data-bbox="481 788 1137 889"><i>The “required” “technology” for holes in Category Code 9E003.a.2. is limited to the derivation of the geometry and location of the holes.</i></p> <p data-bbox="481 908 666 936"><u>Technical Note</u></p> <p data-bbox="481 948 1137 1214"><i>‘Combustor exit temperature’ is the bulk average gas path total (stagnation) temperature between the combustor exit plane and the leading edge of the turbine inlet guide vane (i.e. measured at engine station T40 as defined in SAE ARP 755A) when the engine is running in a ‘steady state mode’ of operation at the certificated maximum continuous operating temperature.</i></p> <p data-bbox="417 1233 474 1262"><u>N.B.</u></p> <p data-bbox="417 1273 1137 1344"><i>See Category Code 9E003.c. for “technology” “required” for manufacturing cooling holes.</i></p> <p data-bbox="417 1363 985 1395">3. Components that are any of the following:</p> <ul style="list-style-type: none"> <li data-bbox="504 1414 1137 1515">a. Manufactured from organic “composite” materials designed to operate above 588 K (315°C); <li data-bbox="504 1534 1056 1566">b. Manufactured from any of the following: <ul style="list-style-type: none"> <li data-bbox="568 1586 1137 1654">1. Metal “matrix” “composites” reinforced by any of the following: <ul style="list-style-type: none"> <li data-bbox="628 1673 1137 1730">a. Materials specified in Category Code 1C007;

Category Code	Item Description
	<p>b. “Fibrous or filamentary materials” specified in Category Code 1C010; <u>or</u></p> <p>c. Aluminides specified in Category Code 1C002.a.; <u>or</u></p> <p>2. Ceramic “matrix” “composites” specified in Category Code 1C007; <u>or</u></p> <p>c. Stators, vanes, blades, tip seals (shrouds), rotating blings, rotating blisks, or ‘splitter ducts’, that are all of the following:</p> <ol style="list-style-type: none"> 1. Not specified in Category Code 9E003.a.3.a.; 2. Designed for compressors or fans; <u>and</u> 3. Manufactured from material specified in Category Code 1C010.e. with resins specified in Category Code 1C008; <p><u>Technical Note</u> <i>A ‘splitter duct’ performs the initial separation of the air-mass flow between the bypass and core sections of the engine.</i></p> <p>4. Uncooled turbine blades, vanes or “tip-shrouds”, designed to operate at a ‘gas path temperature’ of 1,373 K (1,100°C) or more;</p> <p><u>Technical Note</u> <i>‘Gas path temperature’ is the bulk average gas path total (stagnation) temperature at the leading edge plane of the turbine component when the engine is running in a ‘steady state mode’ of operation at the certificated or specified maximum continuous operating temperature.</i></p> <p>5. Cooled turbine blades, vanes, “tip-shrouds” other than those described in Category Code 9E003.a.1., designed to operate at a ‘gas path temperature’ of 1,693 K (1,420°C) or more;</p>

Category Code	Item Description
	<p data-bbox="481 325 676 354"><u>Technical Notes</u></p> <ol data-bbox="504 367 1139 820" style="list-style-type: none"> <li data-bbox="504 367 1139 601">1. 'Gas path temperature' is the bulk average gas path total (stagnation) temperature at the leading edge plane of the turbine component when the engine is running in a 'steady state mode' of operation at the certificated or specified maximum continuous operating temperature. <li data-bbox="504 620 1139 820">2. The term 'steady state mode' defines engine operation conditions, where the engine parameters, such as thrust/power, rpm and others, have no appreciable fluctuations, when the ambient air temperature and pressure at the engine inlet are constant. <ol data-bbox="417 839 1139 1144" style="list-style-type: none"> <li data-bbox="417 839 1139 906">6. Airfoil-to-disk blade combinations using solid state joining; <li data-bbox="417 925 1139 1020">7. Gas turbine engine components using "diffusion bonding" "technology" specified in Category Code 2E003.b.; <li data-bbox="417 1039 1139 1144">8. 'Damage tolerant' gas turbine engine rotor components using powder metallurgy materials specified in Category Code 1C002.b.; <u>or</u> <p data-bbox="481 1163 666 1191"><u>Technical Note</u></p> <p data-bbox="481 1205 1139 1300">'Damage tolerant' components are designed using methodology and substantiation to predict and limit crack growth.</p> <ol data-bbox="417 1319 709 1452" style="list-style-type: none"> <li data-bbox="417 1319 709 1357">9. Not used; <li data-bbox="417 1376 709 1414">10. Not used; <li data-bbox="417 1433 709 1452">11. Hollow fan blades; <p data-bbox="353 1471 1139 1538">b. "Technology" "required" for the "development" or "production" of any of the following:</p> <ol data-bbox="417 1557 1139 1652" style="list-style-type: none"> <li data-bbox="417 1557 1139 1652">1. Wind tunnel aero-models equipped with non-intrusive sensors capable of transmitting data from the sensors to the data acquisition system; <u>or</u>

Category Code	Item Description
	<p data-bbox="417 325 1145 426">2. “Composite” propeller blades or propfans, capable of absorbing more than 2,000 kW at flight speeds exceeding Mach 0.55;</p> <p data-bbox="354 443 1145 576">c. “Technology” “required” for manufacturing cooling holes, in gas turbine engine components incorporating any of the “technologies” specified by Category Code 9E003.a.1., 9E003.a.2. or 9E003.a.5., and having any of the following:</p> <p data-bbox="417 594 817 630">1. Having all of the following:</p> <p data-bbox="502 647 1145 712">a. Minimum ‘cross-sectional area’ less than 0.45 mm²;</p> <p data-bbox="502 729 1053 765">b. ‘Hole shape ratio’ greater than 4.52; <u>and</u></p> <p data-bbox="502 782 1112 818">c. ‘Incidence angle’ equal to or less than 25°; <u>or</u></p> <p data-bbox="417 835 817 872">2. Having all of the following:</p> <p data-bbox="502 889 1145 953">a. Minimum ‘cross-sectional area’ less than 0.12 mm²;</p> <p data-bbox="502 971 1053 1007">b. ‘Hole shape ratio’ greater than 5.65; <u>and</u></p> <p data-bbox="502 1024 959 1060">c. ‘Incidence angle’ more than 25°;</p> <p data-bbox="417 1077 481 1113"><u>Note</u></p> <p data-bbox="417 1111 1145 1245"><i>Category Code 9E003.c. does not include “technology” for manufacturing constant radius cylindrical holes that are straight through and enter and exit on the external surfaces of the component.</i></p> <p data-bbox="417 1262 615 1298"><u>Technical Notes</u></p> <p data-bbox="417 1296 1145 1397">1. <i>For the purpose of Category Code 9E003.c., the ‘cross-sectional area’ is the area of the hole in the plane perpendicular to the hole axis.</i></p> <p data-bbox="417 1414 1145 1547">2. <i>For the purpose of Category Code 9E003.c., ‘hole shape ratio’ is the nominal length of the axis of the hole divided by the square root of its minimum ‘cross-sectional area’.</i></p> <p data-bbox="417 1565 1145 1738">3. <i>For the purpose of Category Code 9E003.c., ‘incidence angle’ is the acute angle measured between the plane tangential to the aerofoil surface and the hole axis at the point where the hole axis enters the aerofoil surface.</i></p>

Category Code	Item Description
	<p data-bbox="417 325 1137 458">4. <i>Techniques for manufacturing holes in Category Code 9E003.c. include “laser”, water jet, Electro-Chemical Machining (ECM) or Electrical Discharge Machining (EDM) methods.</i></p> <p data-bbox="354 477 1137 576">d. <i>“Technology” “required” for the “development” or “production” of helicopter power transfer systems or tilt rotor or tilt wing “aircraft” power transfer systems;</i></p> <p data-bbox="354 595 1137 694">e. <i>“Technology” for the “development” or “production” of reciprocating diesel engine ground vehicle propulsion systems having all of the following:</i></p> <ol data-bbox="417 714 1137 948" style="list-style-type: none"> <li data-bbox="417 714 857 744">1. <i>‘Box volume’ of 1.2 m³ or less;</i> <li data-bbox="417 763 1137 862">2. <i>An overall power output of more than 750 kW based on 80/1269/EEC, ISO 2534 or national equivalents; <u>and</u></i> <li data-bbox="417 881 1137 948">3. <i>Power density of more than 700 kW/m³ of ‘box volume’;</i> <p data-bbox="417 967 602 997"><u><i>Technical Note</i></u></p> <p data-bbox="417 1016 1137 1115"><i>‘Box volume’ in Category Code 9E003.e. is the product of three perpendicular dimensions measured in the following way:</i></p> <p data-bbox="417 1134 512 1165"><u><i>Length:</i></u></p> <p data-bbox="417 1165 1137 1231"><i>The length of the crankshaft from front flange to flywheel face;</i></p> <p data-bbox="417 1250 502 1281"><u><i>Width:</i></u></p> <p data-bbox="417 1281 830 1330"><i>The widest of any of the following:</i></p> <ol data-bbox="417 1349 1137 1544" style="list-style-type: none"> <li data-bbox="417 1349 1137 1416">a. <i>The outside dimension from valve cover to valve cover;</i> <li data-bbox="417 1435 1137 1502">b. <i>The dimensions of the outside edges of the cylinder heads; <u>or</u></i> <li data-bbox="417 1521 928 1544">c. <i>The diameter of the flywheel housing;</i> <p data-bbox="417 1563 512 1593"><u><i>Height:</i></u></p> <p data-bbox="417 1612 834 1643"><i>The largest of any of the following:</i></p> <ol data-bbox="417 1662 1137 1761" style="list-style-type: none"> <li data-bbox="417 1662 1137 1761">a. <i>The dimension of the crankshaft centre-line to the top plane of the valve cover (or cylinder head) plus twice the stroke; <u>or</u></i>

<i>Category Code</i>	<i>Item Description</i>
	<p data-bbox="417 325 928 357"><i>b. The diameter of the flywheel housing.</i></p> <p data-bbox="354 376 1139 477">f. “Technology” “required” for the “production” of specially designed components for high output diesel engines, as follows:</p> <ol style="list-style-type: none"> <li data-bbox="417 496 1139 630">1. “Technology” “required” for the “production” of engine systems having all of the following components employing ceramics materials specified in Category Code 1C007: <ol style="list-style-type: none"> <li data-bbox="505 649 753 681">a. Cylinder liners; <li data-bbox="505 700 659 733">b. Pistons; <li data-bbox="505 752 807 784">c. Cylinder heads; <u>and</u> <li data-bbox="505 803 1139 904">d. One or more other components (including exhaust ports, turbochargers, valve guides, valve assemblies or insulated fuel injectors); <li data-bbox="417 923 1139 1024">2. “Technology” “required” for the “production” of turbocharger systems with single-stage compressors and having all of the following: <ol style="list-style-type: none"> <li data-bbox="505 1043 1096 1075">a. Operating at pressure ratios of 4:1 or higher; <li data-bbox="505 1094 1139 1157">b. Mass flow in the range from 30 kg to 130 kg per minute; <u>and</u> <li data-bbox="505 1176 1139 1239">c. Variable flow area capability within the compressor or turbine sections; <li data-bbox="417 1258 1139 1454">3. “Technology” “required” for the “production” of fuel injection systems with a specially designed multifuel (e.g. diesel or jet fuel) capability covering a viscosity range from diesel fuel (2.5 cSt at 310.8 K (37.8°C)) down to gasoline fuel (0.5 cSt at 310.8 K (37.8°C)) and having all of the following: <ol style="list-style-type: none"> <li data-bbox="505 1473 1139 1536">a. Injection amount in excess of 230 mm³ per injection per cylinder; <u>and</u> <li data-bbox="505 1555 1139 1725">b. Electronic control features specially designed for switching governor characteristics automatically depending on fuel property to provide the same torque characteristics by using the appropriate sensors;

Category Code	Item Description
	<p data-bbox="354 325 1137 525">g. “Technology” “required” for the “development” or “production” of ‘high output diesel engines’ for solid, gas phase or liquid film (or combinations thereof) cylinder wall lubrication and permitting operation to temperatures exceeding 723 K (450°C), measured on the cylinder wall at the top limit of travel of the top ring of the piston;</p> <p data-bbox="417 544 602 573"><u>Technical Note</u></p> <p data-bbox="417 586 1137 719"><i>‘High output diesel engines’ are diesel engines with a specified brake mean effective pressure of 1.8 MPa or more at a speed of 2,300 rpm, provided the rated speed is 2,300 rpm or more.</i></p> <p data-bbox="354 738 1137 801">h. “Technology” for gas turbine engine “FADEC systems” as follows:</p> <ol data-bbox="417 820 1137 1290" style="list-style-type: none"> <li data-bbox="417 820 1137 986">1. “Development” “technology” for deriving the functional requirements for the components necessary for the “FADEC system” to regulate engine thrust or shaft power (e.g. feedback sensor time constants and accuracies, fuel valve slew rate); <li data-bbox="417 1005 1137 1138">2. “Development” or “production” “technology” for control and diagnostic components unique to the “FADEC system” and used to regulate engine thrust or shaft power; <li data-bbox="417 1157 1137 1290">3. “Development” “technology” for the control law algorithms, including “source code”, unique to the “FADEC system” and used to regulate engine thrust or shaft power; <p data-bbox="417 1309 478 1338"><u>Note</u></p> <p data-bbox="417 1353 1137 1624"><i>Category Code 9E003.h. does not include technical data related to engine-aircraft integration required by the relevant civil aviation certification authorities of a “participating state” to be published for general airline use (e.g. installation manuals, operating instructions, instructions for continued airworthiness) or interface functions (e.g. input/output processing, airframe thrust or shaft power demand).</i></p>

<i>Category Code</i>	<i>Item Description</i>
	<p>i. “Technology” for adjustable flow path systems designed to maintain engine stability for gas generator turbines, fan or power turbines, or propelling nozzles, as follows:</p> <ol style="list-style-type: none"> 1. “Development” “technology” for deriving the functional requirements for the components that maintain engine stability; 2. “Development” or “production” “technology” for components unique to the adjustable flow path system and that maintain engine stability; 3. “Development” “technology” for the control law algorithms, including “source code”, unique to the adjustable flow path system and that maintain engine stability; <p><u>Note</u> <i>Category Code 9E003.i. does not include “development” or “production” “technology” for any of the following:</i></p> <ol style="list-style-type: none"> a. <i>Inlet guide vanes;</i> b. <i>Variable pitch fans or prop-fans;</i> c. <i>Variable compressor vanes;</i> d. <i>Compressor bleed valves; <u>or</u></i> e. <i>Adjustable flow path geometry for reverse thrust.</i> <p>j. “Technology” “required” for the “development” of wing-folding systems designed for fixed-wing aircraft powered by gas turbine engines.</p> <p><u>N.B.</u> <i>For “technology” “required” for the “development” of wing-folding systems designed for fixed-wing aircraft, see also Division 2 of Part 1 of this Schedule.</i></p>

<i>Category Code</i>	<i>Item Description</i>
9E101	<p>a. “Technology” (according to the General Technology Note) for the “development” of goods specified in Category Code 9A101, 9A102, 9A104 to 9A111, 9A112.a. or 9A115 to 9A121.</p> <p>b. “Technology” (according to the General Technology Note) for the “production” of ‘UAVs’ specified in Category Code 9A012 or goods specified in Category Code 9A101, 9A102, 9A104 to 9A111, 9A112.a. or 9A115 to 9A121.</p> <p><u>Technical Note</u> <i>In Category Code 9E101.b., ‘UAV’ means unmanned aerial vehicle systems capable of a range exceeding 300 km.</i></p>
9E102	<p>“Technology” (according to the General Technology Note) for the “use” of space launch vehicles specified in Category Code 9A004, goods specified in Category Codes 9A005 to 9A011, ‘UAVs’ specified in Category Code 9A012 or goods specified in Category Code 9A101, 9A102, 9A104 to 9A111, 9A112.a., 9A115 to 9A121, 9B105, 9B106, 9B115, 9B116, 9B117, 9D101 or 9D103.</p> <p><u>Technical Note</u> <i>In Category Code 9E102, ‘UAV’ means unmanned aerial vehicle systems capable of a range exceeding 300 km.</i></p>

Made on 6 September 2016.

LOH KHUM YEAN
*Permanent Secretary,
 Ministry of Trade and Industry,
 Singapore.*

[Customs (Conf.) 0117/2003/PTA; MTI 66/1-2-24 PT1 VOL3; AG/LEGIS/SL/300/2015/1 Vol. 9]