

---

First published in the *Government Gazette*, Electronic Edition, on 4th September 2015 at 5.00 pm.

**No. S 542**

STRATEGIC GOODS (CONTROL) ACT  
(CHAPTER 300)

STRATEGIC GOODS (CONTROL)  
ORDER 2015

ARRANGEMENT OF PARAGRAPHS

Paragraph

1. Citation and commencement
2. Strategic goods and strategic goods technology
3. Revocation

The Schedule

---

In exercise of the powers conferred by section 4A(1) of the Strategic Goods (Control) Act, the Minister for Trade and Industry makes the following Order:

**Citation and commencement**

1. This Order may be cited as the Strategic Goods (Control) Order 2015 and comes into operation on 2 November 2015.

**Strategic goods and strategic goods technology**

2. The goods and technology specified in the Schedule are strategic goods and strategic goods technology, respectively, for the purposes of the Act.

**Revocation**

3. The Strategic Goods (Control) Order 2013 (G.N. No. S 10/2013) is revoked.

---

---

## THE SCHEDULE

Paragraph 2

### PART I

#### MILITARY GOODS THE EXPORT, TRANSHIPMENT OR BRINGING IN TRANSIT OF WHICH, AND TECHNOLOGY THE EXPORT OR TRANSMISSION OF WHICH, REQUIRE A PERMIT

##### *Division 1 — Preliminary Provisions*

##### *Subdivision 1 — General Notes*

1. Non-controlled goods (including plant) containing one or more controlled components set out in Division 2 shall be considered as being controlled goods within Division 2 if the controlled components are the principal element of the non-controlled goods and can feasibly be removed or used for other purposes.
2. In determining whether goods are to be considered the principal element of other goods for the purposes of paragraph 1, factors such as the quantity, value and technological know-how involved and other special circumstances which might establish the goods as the principal element of those other goods must be weighed.
3. Goods specified in Division 2 include both new and used goods.
4. Chemicals in Division 2 are listed by name and CAS number. Chemicals of the same structural formula (including hydrates) as chemicals listed in Division 2 are to be considered as coming within the descriptions of the second-mentioned chemicals regardless of name or CAS number. CAS numbers are shown in order to assist in identifying whether a particular chemical or mixture is a chemical within Division 2, irrespective of nomenclature. CAS numbers are not intended to be used as unique identifiers because some forms of the listed chemical have different CAS numbers, and mixtures containing a listed chemical may also have different CAS numbers.
5. Specially formulated pharmaceutical products that contain any item under Category Code ML8 in Division 2 shall not be treated as coming under that Division.
6. An aircraft shall not be treated as coming under Category Code ML10 in Division 2 if it has no item listed in that Division and it is not configured for military use.

---

---

*Subdivision 2 — Definitions of Words and  
Expressions in this Part*

7. In this Part, words and expressions in quotation marks (“ ”) take the definitions set out against them in this paragraph:

“adapted for use in war” (ML7) means any modification or selection (such as altering purity, shelf life, virulence, dissemination characteristics, or resistance to UV radiation) designed to increase the effectiveness in producing casualties in humans or animals, degrading equipment or damaging crops or the environment;

“additives” (ML8) means substances used in explosive formulations to improve their properties;

“aircraft” (ML10, ML14) means a fixed wing, swivel wing, rotary wing (helicopter), tilt rotor or tilt-wing airborne vehicle;

“automated command and control systems” (ML11) means electronic systems, through which information essential to the effective operation of the grouping, major formation, tactical formation, unit, ship, subunit or weapons under command is entered, processed and transmitted. This is achieved by the use of computer and other specialised hardware designed to support the functions of a military command and control organisation. The main functions of an automated command and control system are: the efficient automated collection, accumulation, storage and processing of information; the display of the situation and the circumstances affecting the preparation and conduct of combat operations; operational and tactical calculations for the allocation of resources among force groupings or elements of the operational order of battle or battle deployment according to the mission or stage of the operation; the preparation of data for appreciation of the situation and decision-making at any point during operation or battle and computer simulation of operations;

“biocatalysts” (ML7, ML22) means ‘enzymes’ for specific chemical or biochemical reactions or other biological compounds which bind to and accelerate the degradation of CW agents;

Technical Note

*‘Enzymes’ means “biocatalysts” for specific chemical or biochemical reactions.*

“biopolymers” (ML7) means the following biological macromolecules:

- a. Enzymes for specific chemical or biochemical reactions;
- b. ‘Anti-idiotypic’, ‘monoclonal’ or ‘polyclonal’ ‘antibodies’;
- c. Specially designed or specially processed ‘receptors’;

---

---

Technical Notes

1. *'Anti-idiotypic antibodies' means antibodies which bind to the specific antigen binding sites of other antibodies.*
2. *'Monoclonal antibodies' means proteins which bind to one antigenic site and are produced by a single clone of cells.*
3. *'Polyclonal antibodies' means a mixture of proteins which bind to the specific antigen and are produced by more than one clone of cells.*
4. *'Receptors' means biological macromolecular structures capable of binding ligands, the binding of which affects physiological functions.*

“civil aircraft” (ML4, ML10) means an “aircraft” listed by designation in published airworthiness certification lists by civil aviation authorities of one or more “participating states” to fly commercial civil internal and external routes or for legitimate civil, private or business use;

“deactivated firearm” (ML1) means a firearm that has been made incapable of firing any projectile by processes. These processes permanently modify the essential elements of the firearm. Deactivation of the firearm may be attested by a certificate delivered by a competent authority of the country in which the firearm is deactivated and may be marked on the firearm by a stamp on an essential part;

“development” (All Categories) has the same meaning as in the Act;

“end-effectors” (ML17) means grippers, ‘active tooling units’ and any other tooling that is attached to the baseplate on the end of a “robot” manipulator arm;

Technical Note

*'Active tooling units' means devices for applying motive power, process energy or sensing to a workpiece.*

“energetic materials” (ML8) means substances or mixtures that react chemically to release energy required for their intended application. “Explosives”, “pyrotechnics” and “propellants” are subclasses of energetic materials;

“explosives” (ML8) means solid, liquid or gaseous substances or mixtures of substances which, in their application as primary, booster, or main charges in warheads, demolition and other applications, are required to detonate;

“expression vectors” (ML7) means carriers (e.g. plasmid and virus) used to introduce genetic material into host cells;

---

“fibrous or filamentary materials” (ML13) includes:

- a. Continuous monofilaments;
- b. Continuous yarns and rovings;
- c. Tapes, fabrics, random mats and braids;
- d. Chopped fibres, staple fibres and coherent fibre blankets;
- e. Whiskers, either monocrystalline or polycrystalline, of any length;  
and
- f. Aromatic polyamide pulp;

“first generation image intensifier tubes” (ML15) means electrostatically focused tubes, employing input and output fibre optic or glass face plates, multi-alkali photocathodes (S-20 or S-25), but not microchannel plate amplifiers;

“fuel cell” (ML17) means an electrochemical device that converts chemical energy directly into Direct Current (DC) electricity by consuming fuel from an external source;

“laser” (ML9, ML19) means an assembly of components which produce both spatially and temporally coherent light that is amplified by stimulated emission of radiation;

“library” (parametric technical database) (ML17) means a collection of technical information, reference to which may enhance the performance of relevant systems, equipment or components;

“lighter-than-air vehicles” (ML10) means balloons and airships that rely on hot air or on lighter-than-air gases such as helium or hydrogen for their lift;

“nuclear reactor” (ML17) includes the items within or attached directly to the reactor vessel, the equipment which controls the level of power in the core, and the components which normally contain or come into direct contact with or control the primary coolant of the reactor core;

“participating state” (ML4, ML10) means a state participating in the Wassenaar Arrangement (details of which are set out in <http://www.wassenaar.org/participants/index.html>);

“precursors” (ML8) means speciality chemicals used in the manufacture of “explosives”;

“production” (All Categories) has the same meaning as in the Act;

“propellants” (ML8) means substances or mixtures that react chemically to produce large volumes of hot gases at controlled rates to perform mechanical work;

---

“pyrotechnic(s)” (ML4, ML8) means mixtures of solid or liquid fuels and oxidisers which, when ignited, undergo an energetic chemical reaction at a controlled rate intended to produce specific time delays, or quantities of heat, noise, smoke, visible light or infrared radiation. Pyrophorics are a subclass of “pyrotechnics”, which contain no oxidisers but ignite spontaneously on contact with air;

“required” (ML22), in relation to “technology”, means only that portion of “technology” which is peculiarly responsible for achieving or exceeding the controlled performance levels, characteristics or functions. Such “required” “technology” may be shared by different products;

“riot control agents” (ML7) means substances which, under the expected conditions of use for riot control purposes, produce rapidly in humans sensory irritation or disabling physical effects which disappear within a short time following termination of exposure. (Tear gases are a subset of “riot control agents”);

“robot” (ML17) means a manipulation mechanism of the continuous path or the point-to-point variety, may use sensors, and has all the following characteristics:

- a. it is multifunctional;
- b. it is capable of positioning or orienting material, parts, tools or special devices through variable movements in three dimensional space;
- c. it incorporates three or more closed or open loop servo-devices which may include stepping motors; and
- d. it has “user-accessible programmability” by means of the teach/playback method or by means of an electronic computer which may be a programmable logic controller, i.e. without mechanical intervention;

Note

*“Robot” does not include the following devices:*

- a. *Manipulation mechanisms which are only manually or teleoperator controllable;*
- b. *Fixed sequence manipulation mechanisms which are automated moving devices, operating according to mechanically fixed programmed motions. The program is mechanically limited by fixed stops, such as pins or cams. The sequence of motions and the selection of paths or angles are not variable or changeable by mechanical, electronic or electrical means;*

- 
- 
- c. *Mechanically controlled variable sequence manipulation mechanisms which are automated moving devices, operating according to mechanically fixed programmed motions. The program is mechanically limited by fixed, but adjustable stops such as pins or cams. The sequence of motions and the selection of paths or angles are variable within the fixed program pattern. Variations or modifications of the program pattern (e.g. changes of pins or exchanges of cams) in one or more motion axes are accomplished only through mechanical operations;*
- d. *Non-servo-controlled variable sequence manipulation mechanisms which are automated moving devices, operating according to mechanically fixed programmed motions, where the program is variable but the sequence proceeds only by the binary signal from mechanically fixed electrical binary devices or adjustable stops;*
- e. *Stacker cranes defined as Cartesian coordinate manipulator systems manufactured as an integral part of a vertical array of storage bins and designed to access the contents of those bins for storage or retrieval.*

“software” (All Categories) means a collection of one or more ‘programs’ or ‘microprogrammes’ recorded, stored or embodied in any device;

Technical Note 1

*‘Program’ means a sequence of instructions to carry out a process in, or convertible into, a form executable by an electronic computer;*

Technical Note 2

*‘Microprogramme’ means a sequence of elementary instructions, maintained in a special storage, the execution of which is initiated by the introduction of its reference instruction into an instruction register.*

“spacecraft” (ML11) means active and passive satellites and space probes;

“space-qualified” (ML19) means designed, manufactured, or qualified through successful testing, for operation at altitudes greater than 100 km above the surface of the Earth;

---

---

Note

*A determination that a specific item is “space-qualified” by virtue of testing does not mean that other items in the same production run or model series are “space-qualified” if not individually tested.*

“superconductive” (ML20), in relation to any equipment, means the equipment is made of any material (such as a metal, alloy or compound) which can lose all electrical resistance (i.e. it can attain infinite electrical conductivity and carry very large electrical currents without Joule heating);

Technical Note

*The “superconductive” state of a material is individually characterised by a ‘critical temperature’, a critical magnetic field, which is a function of temperature, and a critical current density which is, however, a function of both magnetic field and temperature.*

Note

*‘Critical temperature’ (sometimes referred to as the transition temperature) of a specific “superconductive” material is the temperature at which the material loses all resistance to the flow of direct electrical current.*

“technology” (All Categories) means information (including information comprised in such documents as specifications, blueprints, plans, manuals, models, diagrams, formulae, tables and designs) that is necessary for the “development”, “production” or ‘use’ of any goods;

Technical Note

*‘Use’ has the same meaning as in the Act.*

“unmanned aerial vehicle” (“UAV”) (ML10) means any “aircraft” capable of initiating flight and sustaining controlled flight and navigation without any human presence on board.

8. In paragraph 7, a reference to a Category Code (prefixed with the abbreviation “ML”) in brackets is a reference to that Category Code in Division 2 in which the defined word or expression appears.
9. In this Part, a word or expression enclosed with single quotation marks (‘’) takes the definition set out against it in the Technical Note that follows immediately after the definition in which the word or expression appears.



---



---

 Division 2 — List of Military Goods
 

---

<i>Category Code</i>	<i>Item Description</i>
ML1	<p>Smooth-bore weapons with a calibre of less than 20 mm, other arms and automatic weapons with a calibre of 12.7 mm (calibre 0.50 inches) or less and accessories, as follows, and specially designed components therefor:</p> <p><u>Note</u>  <i>Category Code ML1 does not apply to the following:</i></p> <ul style="list-style-type: none"> <li>a. <i>Firearms specially designed for dummy ammunition and which are incapable of discharging a projectile;</i></li> <li>b. <i>Firearms specially designed to launch tethered projectiles having no high explosive charge or communications link, to a range of less than or equal to 500 m;</i></li> <li>c. <i>Weapons using non-centre fire cased ammunition and which are not of the fully automatic firing type;</i></li> <li>d. <i>“Deactivated firearms”.</i></li> </ul> <ul style="list-style-type: none"> <li>a. Rifles and combination guns, handguns, machine, sub-machine and volley guns;</li> </ul> <p><u>Note</u>  <i>Category Code ML1.a. does not apply to the following:</i></p> <ul style="list-style-type: none"> <li>a. <i>Rifles and combination guns, manufactured earlier than 1938;</i></li> <li>b. <i>Reproductions of rifles and combination guns, the originals of which were manufactured earlier than 1890;</i></li> <li>c. <i>Handguns, volley guns and machine guns, manufactured earlier than 1890, and their reproductions;</i></li> <li>d. <i>Rifles or handguns, specially designed to discharge an inert projectile by compressed air or CO<sub>2</sub>.</i></li> </ul> <ul style="list-style-type: none"> <li>b. Smooth-bore weapons as follows:           <ul style="list-style-type: none"> <li>1. Smooth-bore weapons specially designed for military use;</li> <li>2. Other smooth-bore weapons as follows:               <ul style="list-style-type: none"> <li>a. Fully automatic type weapons;</li> </ul> </li> </ul> </li> </ul>

<i>Category Code</i>	<i>Item Description</i>
	<p>b. Semi-automatic or pump-action type weapons;</p> <p><u>Note</u>  <i>Category Code ML1.b.2. does not apply to weapons specially designed to discharge an inert projectile by compressed air or CO<sub>2</sub>.</i></p> <p><u>Note</u>  <i>Category Code ML1.b. does not apply to the following:</i></p> <p>a. <i>Smooth-bore weapons manufactured earlier than 1938;</i></p> <p>b. <i>Reproductions of smooth-bore weapons, the originals of which were manufactured earlier than 1890;</i></p> <p>c. <i>Smooth-bore weapons used for hunting or sporting purposes. These weapons must not be specially designed for military use or of the fully automatic firing type;</i></p> <p>d. <i>Smooth-bore weapons specially designed for any of the following:</i></p> <ol style="list-style-type: none"> <li>1. <i>Slaughtering of domestic animals;</i></li> <li>2. <i>Tranquilizing of animals;</i></li> <li>3. <i>Seismic testing;</i></li> <li>4. <i>Firing of industrial projectiles; <u>or</u></i></li> <li>5. <i>Disrupting Improvised Explosive Devices (IEDs).</i></li> </ol> <p><u>N.B.</u>  <i>For disruptors, see Category Code ML4 and Category Code 1A006 in Division 2 of Part II of this Schedule.</i></p> <p>c. Weapons using caseless ammunition;</p> <p>d. Detachable cartridge magazines, sound suppressors or moderators, special gun-mountings, optical weapons sights and flash suppressors, for arms specified in Category Code ML1.a., ML1.b. or ML1.c.</p>

<i>Category Code</i>	<i>Item Description</i>
ML2	<p data-bbox="564 454 624 483"><u>Note</u></p> <p data-bbox="564 495 1265 689"><i>Category Code ML1.d. does not apply to optical weapon sights without electronic image processing, with a magnification of 9 times or less, provided they are not specially designed or modified for military use, or incorporate any reticles specially designed for military use.</i></p> <p data-bbox="501 763 1265 891">Smooth-bore weapons with a calibre of 20 mm or more, other weapons or armament with a calibre greater than 12.7 mm (calibre 0.50 inches), projectors and accessories, as follows, and specially designed components therefor:</p> <p data-bbox="501 913 1265 1041">a. Guns, howitzers, cannon, mortars, anti-tank weapons, projectile launchers, military flame throwers, rifles, recoilless rifles, smooth-bore weapons and signature reduction devices therefor;</p> <p data-bbox="564 1064 647 1093"><u>Note 1</u></p> <p data-bbox="564 1104 1265 1232"><i>Category Code ML2.a. includes injectors, metering devices, storage tanks and other specially designed components for use with liquid propelling charges for any of the equipment specified in Category Code ML2.a.</i></p> <p data-bbox="564 1254 647 1283"><u>Note 2</u></p> <p data-bbox="564 1294 1265 1357"><i>Category Code ML2.a. does not apply to weapons as follows:</i></p> <p data-bbox="564 1379 1265 1442">a. <i>Rifles, smooth-bore weapons and combination guns, manufactured earlier than 1938;</i></p> <p data-bbox="564 1464 1265 1559">b. <i>Reproductions of rifles, smooth-bore weapons and combination guns, the originals of which were manufactured earlier than 1890;</i></p> <p data-bbox="564 1581 1265 1644">c. <i>Guns, howitzers, cannons and mortars, manufactured earlier than 1890;</i></p> <p data-bbox="564 1666 1265 1794">d. <i>Smooth-bore weapons used for hunting or sporting purposes. These weapons must not be specially designed for military use or of the fully automatic firing type;</i></p> <p data-bbox="564 1816 1265 1879">e. <i>Smooth-bore weapons specially designed for any of the following:</i></p>

<i>Category Code</i>	<i>Item Description</i>
	<ol style="list-style-type: none"> <li>1. <i>Slaughtering of domestic animals;</i></li> <li>2. <i>Tranquilizing of animals;</i></li> <li>3. <i>Seismic testing;</i></li> <li>4. <i>Firing of industrial projectiles; <u>or</u></i></li> <li>5. <i>Disrupting Improvised Explosive Devices (IEDs);</i></li> </ol> <p style="text-align: center;"><u><i>N.B.</i></u> <i>For disruptors, see Category Code ML4 and Category Code 1A006 in Division 2 of Part II of this Schedule.</i></p> <p>f. <i>Hand-held projectile launchers specially designed to launch tethered projectiles having no high explosive charge or communications link, to a range of less than or equal to 500 m.</i></p> <p>b. <i>Smoke, gas and pyrotechnic projectors or generators, specially designed or modified for military use;</i></p> <p style="text-align: center;"><u><i>Note</i></u> <i>Category Code ML2.b. does not apply to signal pistols.</i></p> <p>c. <i>Weapons sights and weapon sight mounts, having all of the following:</i></p> <ol style="list-style-type: none"> <li>1. <i>Specially designed for military use; <u>and</u></i></li> <li>2. <i>Specially designed for weapons specified in Category Code ML2.a.;</i></li> </ol> <p>d. <i>Mountings and detachable cartridge magazines, specially designed for the weapons specified in Category Code ML2.a.</i></p>
ML3	<p><i>Ammunition and fuse setting devices, as follows, and specially designed components therefor:</i></p> <ol style="list-style-type: none"> <li>a. <i>Ammunition for weapons specified in Category Code ML1, ML2 or ML12;</i></li> <li>b. <i>Fuse setting devices specially designed for ammunition specified in Category Code ML3.a.</i></li> </ol>

Category Code	Item Description
	<p><u>Note 1</u> Specially designed components specified in Category Code ML3 include:</p> <ul style="list-style-type: none"> <li>a. Metal or plastic fabrications such as primer anvils, bullet cups, cartridge links, rotating bands and munitions metal parts;</li> <li>b. Safing and arming devices, fuses, sensors and initiation devices;</li> <li>c. Power supplies with high one-time operational output;</li> <li>d. Combustible cases for charges;</li> <li>e. Submunitions including bomblets, minelets and terminally guided projectiles.</li> </ul> <p><u>Note 2</u> Category Code ML3.a. does not apply to any of the following:</p> <ul style="list-style-type: none"> <li>a. Ammunition crimped without a projectile (blank star);</li> <li>b. Dummy ammunition with a pierced powder chamber;</li> <li>c. Other blank and dummy ammunition, not incorporating components designed for live ammunition; <u>or</u></li> <li>d. Components specially designed for blank or dummy ammunition, specified in this Note 2.a., b., or c.</li> </ul> <p><u>Note 3</u> Category Code ML3.a. does not apply to cartridges specially designed for any of the following purposes:</p> <ul style="list-style-type: none"> <li>a. Signalling;</li> <li>b. Bird scaring; <u>or</u></li> <li>c. Lighting of gas flares at oil wells.</li> </ul>
ML4	<p>Bombs, torpedoes, rockets, missiles, other explosive devices and charges and related equipment and accessories, as follows, and specially designed components therefor:</p> <p><u>N.B. 1</u> For guidance and navigation equipment, see Category Code ML11.</p>

<i>Category Code</i>	<i>Item Description</i>
	<p><u>N.B. 2</u>  <i>For Aircraft Missile Protection Systems (AMPS), see Category Code ML4.c.</i></p> <p>a. Bombs, torpedoes, grenades, smoke canisters, rockets, mines, missiles, depth charges, demolition-charges, demolition-devices, demolition-kits, “pyrotechnic” devices, cartridges and simulators (i.e. equipment simulating the characteristics of any of these items), specially designed for military use;</p> <p><u>Note</u>  <i>Category Code ML4.a. includes:</i></p> <p>a. <i>Smoke grenades, fire bombs, incendiary bombs and explosive devices;</i></p> <p>b. <i>Missile rocket nozzles and re-entry vehicle nosetips.</i></p> <p>b. Equipment having all of the following:</p> <p>1. Specially designed for military use; <u>and</u></p> <p>2. Specially designed for ‘activities’ relating to any of the following:</p> <p>a. Items specified in Category Code ML4.a.; <u>or</u></p> <p>b. Improvised Explosive Devices (IEDs);</p> <p><u>Technical Note</u>  <i>For the purpose of Category Code ML4.b.2., ‘activities’ applies to handling, launching, laying, controlling, discharging, detonating, activating, powering with one-time operational output, decoying, jamming, sweeping, detecting, disrupting or disposing.</i></p> <p><u>Note 1</u>  <i>Category Code ML4.b. includes:</i></p> <p>a. <i>Mobile gas liquefying equipment capable of producing 1,000 kg or more per day of gas in liquid form;</i></p> <p>b. <i>Buoyant electric conducting cable suitable for sweeping magnetic mines.</i></p>

<i>Category Code</i>	<i>Item Description</i>
	<p data-bbox="564 456 647 488"><u>Note 2</u></p> <p data-bbox="564 499 1267 629"><i>Category Code ML4.b. does not apply to hand-held devices limited by design solely to the detection of metal objects and incapable of distinguishing between mines and other metal objects.</i></p> <p data-bbox="501 647 1102 678">c. <i>Aircraft Missile Protection Systems (AMPS).</i></p> <p data-bbox="564 696 627 728"><u>Note</u></p> <p data-bbox="564 739 1267 804"><i>Category Code ML4.c. does not apply to AMPS having all of the following:</i></p> <p data-bbox="564 822 1171 853">a. <i>Any of the following missile warning sensors:</i></p> <ol data-bbox="651 871 1267 1019" style="list-style-type: none"> <li data-bbox="651 871 1267 943">1. <i>Passive sensors having peak response between 100 nm - 400 nm; <u>or</u></i></li> <li data-bbox="651 954 1267 1019">2. <i>Active pulsed Doppler missile warning sensors;</i></li> </ol> <p data-bbox="564 1037 1078 1068">b. <i>Countermeasures dispensing systems;</i></p> <p data-bbox="564 1086 1267 1189">c. <i>Flares, which exhibit both a visible signature and an infrared signature, for decoying surface-to-air missiles; <u>and</u></i></p> <p data-bbox="564 1207 1267 1272">d. <i>Installed on “civil aircraft” and having all of the following:</i></p> <ol data-bbox="651 1290 1267 1738" style="list-style-type: none"> <li data-bbox="651 1290 1267 1420">1. <i>The AMPS is only operable in a specific “civil aircraft” in which the specific AMPS is installed and for which any of the following has been issued:</i> <ol data-bbox="715 1438 1267 1653" style="list-style-type: none"> <li data-bbox="715 1438 1267 1541">a. <i>A civil Type Certificate issued by civil aviation authorities of one or more “participating states”; <u>or</u></i></li> <li data-bbox="715 1552 1267 1653">b. <i>An equivalent document recognised by the International Civil Aviation Organisation (ICAO);</i></li> </ol> </li> <li data-bbox="651 1671 1267 1738">2. <i>The AMPS employs protection to prevent unauthorised access to “software”; <u>and</u></i></li> </ol>

<i>Category Code</i>	<i>Item Description</i>
ML5	<p data-bbox="651 456 1272 584">3. <i>The AMPS incorporates an active mechanism that forces the system not to function when it is removed from the “civil aircraft” in which it was installed.</i></p> <p data-bbox="501 658 1272 786">Fire control, and related alerting and warning equipment, and related systems, test and alignment and countermeasure equipment, as follows, specially designed for military use, and specially designed components and accessories therefor:</p> <p data-bbox="501 808 1272 869">a. <i>Weapon sights, bombing computers, gun laying equipment and weapon control systems;</i></p> <p data-bbox="501 891 1272 1019">b. <i>Target acquisition, designation, range-finding, surveillance or tracking systems; detection, data fusion, recognition or identification equipment; and sensor integration equipment;</i></p> <p data-bbox="501 1041 1272 1102">c. <i>Countermeasure equipment for items specified in Category Code ML5.a. or ML5.b.;</i></p> <p data-bbox="564 1124 628 1153"><u><i>Note</i></u></p> <p data-bbox="564 1167 1272 1227"><i>For the purpose of Category Code ML5.c., countermeasure equipment includes detection equipment.</i></p> <p data-bbox="501 1249 1272 1346">d. <i>Field test or alignment equipment, specially designed for items specified in Category Code ML5.a., ML5.b. or ML5.c.</i></p>
ML6	<p data-bbox="501 1420 1043 1449">Ground vehicles and components, as follows:</p> <p data-bbox="501 1464 564 1494"><u><i>N.B.</i></u></p> <p data-bbox="501 1507 1272 1568"><i>For guidance and navigation equipment, see Category Code ML11.</i></p> <p data-bbox="501 1590 1272 1650">a. <i>Ground vehicles and components therefor, specially designed or modified for military use;</i></p> <p data-bbox="564 1673 756 1702"><u><i>Technical Note</i></u></p> <p data-bbox="564 1715 1272 1776"><i>For the purpose of Category Code ML6.a., the term ground vehicles includes trailers.</i></p> <p data-bbox="501 1798 1176 1827">b. <i>Other ground vehicles and components, as follows:</i></p> <p data-bbox="564 1850 1064 1879">1. <i>Vehicles having all of the following:</i></p>



<i>Category Code</i>	<i>Item Description</i>
	<ul style="list-style-type: none"> <li>a. Manufactured or fitted with materials or components to provide ballistic protection to level III (NIJ 0108.01, September 1985, or comparable national standard) or better;</li> <li>b. A transmission to provide drive to both front and rear wheels simultaneously, including those vehicles having additional wheels for load bearing purposes whether driven or not;</li> <li>c. Gross Vehicle Weight Rating (GVWR) greater than 4,500 kg; <u>and</u></li> <li>d. Designed or modified for off-road use;</li> </ul> <p>2. Components having all of the following:</p> <ul style="list-style-type: none"> <li>a. Specially designed for vehicles specified in Category Code ML6.b.1.; <u>and</u></li> <li>b. Providing ballistic protection to level III (NIJ 0108.01, September 1985, or comparable national standard) or better.</li> </ul> <p><u>N.B.</u> See also Category Code ML13.a.</p> <p><u>Note 1</u> Category Code ML6.a. includes:</p> <ul style="list-style-type: none"> <li>a. Tanks and other military armed vehicles and military vehicles fitted with mountings for arms or equipment for mine laying or the launching of munitions specified in Category Code ML4;</li> <li>b. Armoured vehicles;</li> <li>c. Amphibious and deep water fording vehicles;</li> <li>d. Recovery vehicles and vehicles for towing or transporting ammunition or weapon systems and associated load handling equipment.</li> </ul> <p><u>Note 2</u> Under Category Code ML6.a., modification of a ground vehicle for military use entails a structural, electrical or mechanical change involving one or more components that are specially designed for military use. Such components include:</p>

<i>Category Code</i>	<i>Item Description</i>
	<p>a. <i>Pneumatic tyre casings of a kind specially designed to be bullet-proof;</i></p> <p>b. <i>Armoured protection of vital parts (e.g. fuel tanks or vehicle cabs);</i></p> <p>c. <i>Special reinforcements or mountings for weapons;</i></p> <p>d. <i>Black-out lighting.</i></p> <p><u>Note 3</u>  <i>Category Code ML6 does not apply to civil vehicles designed or modified for transporting money or valuables.</i></p> <p><u>Note 4</u>  <i>Category Code ML6 does not apply to vehicles that meet all of the following:</i></p> <p>a. <i>Were manufactured before 1946;</i></p> <p>b. <i>Do not have items specified in any part of this Division and manufactured after 1945, except for reproductions of original components or accessories for the vehicle; <u>and</u></i></p> <p>c. <i>Do not incorporate weapons specified in Category Code ML1, ML2 or ML4 unless they are inoperable and incapable of discharging a projectile.</i></p>
ML7	<p>Chemical or biological toxic agents, “riot control agents”, radioactive materials, related equipment, components and materials, as follows:</p> <p>a. Biological agents or radioactive materials, “adapted for use in war” to produce casualties in humans or animals, degrade equipment or damage crops or the environment;</p> <p>b. Chemical warfare (CW) agents, including:</p> <ol style="list-style-type: none"> <li>1. CW nerve agents: <ol style="list-style-type: none"> <li>a. O-Alkyl (equal to or less than C<sub>10</sub>, including cycloalkyl) alkyl (Methyl, Ethyl, n-Propyl or Isopropyl)-phosphonofluoridates, such as:  Sarin (GB):O-Isopropyl methylphosphonofluoridate (107-44-8); <u>and</u></li> </ol> </li> </ol>

<i>Category Code</i>	<i>Item Description</i>
	<p>Soman (GD):O-Pinacolyl methylphosphonofluoridate (96-64-0);</p> <p>b. O-Alkyl (equal to or less than C<sub>10</sub>, including cycloalkyl) N,N-dialkyl (Methyl, Ethyl, n-Propyl or Isopropyl) phosphoramidocyanidates, such as:</p> <p>Tabun (GA):O-Ethyl N,N-dimethylphosphoramidocyanidate (77-81-6);</p> <p>c. O-Alkyl (H or equal to or less than C<sub>10</sub>, including cycloalkyl) S-2-dialkyl (Methyl, Ethyl, n-Propyl or Isopropyl)-aminoethyl alkyl (Methyl, Ethyl, n-Propyl or Isopropyl) phosphonothiolates and corresponding alkylated and protonated salts, such as:</p> <p>VX: O-Ethyl S-2-diisopropylaminoethyl methyl phosphonothiolate (50782-69-9);</p> <p>2. CW vesicant agents:</p> <p>a. Sulphur mustards, such as:</p> <ol style="list-style-type: none"> <li>1. 2-Chloroethylchloromethylsulphide (2625-76-5);</li> <li>2. Bis(2-chloroethyl) sulphide (505-60-2);</li> <li>3. Bis(2-chloroethylthio) methane (63869-13-6);</li> <li>4. 1,2-bis (2-chloroethylthio) ethane (3563-36-8);</li> <li>5. 1,3-bis (2-chloroethylthio) -n-propane (63905-10-2);</li> <li>6. 1,4-bis (2-chloroethylthio) -n-butane (142868-93-7);</li> <li>7. 1,5-bis (2-chloroethylthio) -n-pentane (142868-94-8);</li> <li>8. Bis (2-chloroethylthiomethyl) ether (63918-90-1);</li> <li>9. Bis (2-chloroethylthioethyl) ether (63918-89-8);</li> </ol>

<i>Category Code</i>	<i>Item Description</i>
	<ul style="list-style-type: none"> <li>b. Lewisites, such as:               <ul style="list-style-type: none"> <li>1. 2-chlorovinyl dichloroarsine (541-25-3);</li> <li>2. Tris (2-chlorovinyl) arsine (40334-70-1);</li> <li>3. Bis (2-chlorovinyl) chloroarsine (40334-69-8);</li> </ul> </li> <li>c. Nitrogen mustards, such as:               <ul style="list-style-type: none"> <li>1. HN1: bis (2-chloroethyl) ethylamine (538-07-8);</li> <li>2. HN2: bis (2-chloroethyl) methylamine (51-75-2);</li> <li>3. HN3: tris (2-chloroethyl) amine (555-77-1);</li> </ul> </li> <li>3. CW incapacitating agents, such as:               <ul style="list-style-type: none"> <li>a. 3-Quinuclidinyl benzilate (BZ) (6581-06-2);</li> </ul> </li> <li>4. CW defoliants, such as               <ul style="list-style-type: none"> <li>a. Butyl 2-chloro-4-fluorophenoxyacetate (LNF);</li> <li>b. 2,4,5-trichlorophenoxyacetic acid (93-76-5) mixed with 2,4-dichlorophenoxyacetic acid (94-75-7) (Agent Orange (39277-47-9));</li> </ul> </li> <li>c. CW binary precursors and key precursors, as follows:               <ul style="list-style-type: none"> <li>1. Alkyl (Methyl, Ethyl, n-Propyl or Isopropyl) Phosphonyl Difluorides, such as:                   <ul style="list-style-type: none"> <li>DF: Methyl Phosphonyldifluoride (676-99-3);</li> </ul> </li> <li>2. O-Alkyl (H or equal to or less than C<sub>10</sub>, including cycloalkyl) O-2-dialkyl (Methyl, Ethyl, n-Propyl or Isopropyl)-aminoethyl alkyl (Methyl, Ethyl, n-Propyl or Isopropyl) phosphonites and corresponding alkylated and protonated salts, such as:                   <ul style="list-style-type: none"> <li>QL: O-Ethyl O-2-di-isopropylaminoethyl methylphosphonite (57856-11-8);</li> </ul> </li> <li>3. Chlorosarin: O-Isopropyl methylphosphonochloridate (1445-76-7);</li> </ul> </li> </ul>

<i>Category Code</i>	<i>Item Description</i>
	<p>4. Chlorosoman: O-Pinacolyl methylphosphonochloridate (7040-57-5);</p> <p>d. “Riot control agents”, active constituent chemicals and combinations thereof, including:</p> <ol style="list-style-type: none"> <li>1. <math>\alpha</math>-Bromobenzeneacetonitrile, (Bromobenzyl cyanide) (CA) (5798-79-8);</li> <li>2. [(2-chlorophenyl) methylene] propanedinitrile, (o-Chlorobenzylidenemalononitrile) (CS) (2698-41-1);</li> <li>3. 2-Chloro-1-phenylethanone, Phenylacetyl chloride (<math>\omega</math>-chloroacetophenone) (CN) (532-27-4);</li> <li>4. Dibenz-(b,f)-1,4-oxazephine, (CR) (257-07-8);</li> <li>5. 10-Chloro-5,10-dihydrophenarsazine, (Phenarsazine chloride), (Adamsite), (DM) (578-94-9);</li> <li>6. N-Nonanoylmorpholine, (MPA) (5299-64-9);</li> </ol> <p><u>Note 1</u>  <i>Category Code ML7.d. does not apply to “riot control agents” individually packaged for personal self-defence purposes.</i></p> <p><u>Note 2</u>  <i>Category Code ML7.d. does not apply to active constituent chemicals, and combinations thereof, identified and packaged for food production or medical purposes.</i></p> <p>e. Equipment, specially designed or modified for military use, designed or modified for the dissemination of any of the following, and specially designed components therefor:</p> <ol style="list-style-type: none"> <li>1. Materials or agents specified in Category Code ML7.a., ML7.b. or ML7.d.; <u>or</u></li> <li>2. CW agents made up of precursors specified in Category Code ML7.c.;</li> </ol> <p>f. Protective and decontamination equipment, specially designed or modified for military use, components and chemical mixtures, as follows:</p>

<i>Category Code</i>	<i>Item Description</i>
	<p>1. Equipment designed or modified for defence against materials specified in Category Code ML7.a., ML7.b. or ML7.d., and specially designed components therefor;</p> <p>2. Equipment designed or modified for decontamination of objects contaminated with materials specified in Category Code ML7.a. or ML7.b., and specially designed components therefor;</p> <p>3. Chemical mixtures specially developed or formulated for the decontamination of objects contaminated with materials specified in Category Code ML7.a. or ML7.b.;</p> <p><i>Note</i>  <i>Category Code ML7.f.1. includes:</i></p> <p>a. <i>Air conditioning units specially designed or modified for nuclear, biological or chemical filtration;</i></p> <p>b. <i>Protective clothing.</i></p> <p><i>N.B.</i>  <i>For civil gas masks, protective and decontamination equipment, see also Category Code IA004 in Division 2 of Part II of this Schedule.</i></p> <p>g. Equipment, specially designed or modified for military use designed or modified for the detection or identification of materials specified in Category Code ML7.a., ML7.b. or ML7.d., and specially designed components therefor;</p> <p><i>Note</i>  <i>Category Code ML7.g. does not apply to personal radiation monitoring dosimeters.</i></p> <p><i>N.B.</i>  <i>See also Category Code IA004 in Division 2 of Part II of this Schedule.</i></p> <p>h. “Biopolymers” specially designed or processed for the detection or identification of CW agents specified in Category Code ML7.b., and the cultures of specific cells used to produce them;</p>

<i>Category Code</i>	<i>Item Description</i>
	<p>i. “Biocatalysts” for the decontamination or degradation of CW agents, and biological systems therefor, as follows:</p> <ol style="list-style-type: none"> <li>1. “Biocatalysts” specially designed for the decontamination or degradation of CW agents specified in Category Code ML7.b., and resulting from directed laboratory selection or genetic manipulation of biological systems;</li> <li>2. Biological systems containing the genetic information specific to the production of “biocatalysts” specified in Category Code ML7.i.1., as follows: <ol style="list-style-type: none"> <li>a. “Expression vectors”;</li> <li>b. Viruses;</li> <li>c. Cultures of cells.</li> </ol> </li> </ol> <p><i>Note 1</i></p> <p><i>Category Codes ML7.b. and ML7.d. do not apply to the following:</i></p> <ol style="list-style-type: none"> <li>a. Cyanogen chloride (506-77-4);</li> <li>b. Hydrocyanic acid (74-90-8);</li> <li>c. Chlorine (7782-50-5);</li> <li>d. Carbonyl chloride (phosgene) (75-44-5);</li> <li>e. Diphosgene (trichloromethyl-chloroformate) (503-38-8);</li> <li>f. Not used;</li> <li>g. Xylyl bromide, ortho: (89-92-9), meta: (620-13-3), para: (104-81-4);</li> <li>h. Benzyl bromide (100-39-0);</li> <li>i. Benzyl iodide (620-05-3);</li> <li>j. Bromo acetone (598-31-2);</li> <li>k. Cyanogen bromide (506-68-3);</li> <li>l. Bromo methylethylketone (816-40-0);</li> <li>m. Chloro acetone (78-95-5);</li> <li>n. Ethyl iodoacetate (623-48-3);</li> </ol>

<i>Category Code</i>	<i>Item Description</i>
ML8	<p data-bbox="501 454 879 488"><i>o. Iodo acetone (3019-04-3);</i></p> <p data-bbox="501 501 847 535"><i>p. Chloropicrin (76-06-2).</i></p> <p data-bbox="501 551 584 584"><u>Note 2</u></p> <p data-bbox="501 593 1262 792"><i>The cultures of cells and biological systems specified in Category Codes ML7.h. and ML7.i.2. are exclusive and these sub-items do not apply to cells or biological systems for civil purposes, such as agricultural, pharmaceutical, medical, veterinary, environmental, waste management, or in the food industry.</i></p> <p data-bbox="501 862 1171 896">“Energetic materials” and related substances, as follows:</p> <p data-bbox="501 911 579 945"><u>N.B. 1</u></p> <p data-bbox="501 954 1262 1019"><i>See also Category Code 1C011 in Division 2 of Part II of this Schedule.</i></p> <p data-bbox="501 1034 579 1068"><u>N.B. 2</u></p> <p data-bbox="501 1077 1262 1142"><i>For charges and devices, see Category Code ML4 and Category Code 1A008 in Division 2 of Part II of this Schedule.</i></p> <p data-bbox="501 1158 695 1191"><u>Technical Notes</u></p> <ol data-bbox="501 1200 1262 1704" style="list-style-type: none"> <li data-bbox="501 1200 1262 1332"><i>1. For the purpose of Category Code ML8, ‘mixture’ refers to a composition of two or more substances with at least one substance being listed in the sub-items under this Category Code.</i></li> <li data-bbox="501 1348 1262 1547"><i>2. Any substance listed in the sub-items under Category Code ML8 is treated as coming within the description of that substance even when utilised in an application other than that indicated. (e.g. TAGN is predominantly used as an explosive but can also be used either as a fuel or an oxidiser.)</i></li> <li data-bbox="501 1563 1262 1704"><i>3. For the purpose of Category Code ML8, particle size is the mean particle diameter on a weight or volume basis. International or equivalent national standards will be used in sampling and determining particle size.</i></li> </ol> <p data-bbox="501 1720 1134 1753"><i>a. “Explosives” as follows, and ‘mixtures’ thereof:</i></p> <ol data-bbox="564 1762 1262 1839" style="list-style-type: none"> <li data-bbox="564 1762 1262 1839"><i>1. ADNBF (aminodinitrobenzofuroxan or 7-amino-4,6-dinitrobenzofurazane-1-oxide) (97096-78-1);</i></li> </ol>



<i>Category Code</i>	<i>Item Description</i>
	2. BNCP (cis-bis (5-nitrotetrazolato) tetra amine-cobalt (III) perchlorate) (117412-28-9);
	3. CL-14 (diamino dinitrobenzofuroxan or 5,7-diamino-4,6-dinitrobenzofurazane-1-oxide) (117907-74-1);
	4. CL-20 (HNIW or Hexanitrohexaazaisowurtzitane) (135285-90-4); chlathrates of CL-20 (see also Category Codes ML8.g.3. and g.4. for its “precursors”);
	5. CP (2-(5-cyanotetrazolato) penta amine-cobalt (III) perchlorate) (70247-32-4);
	6. DADE (1,1-diamino-2,2-dinitroethylene, FOX7) (145250-81-3);
	7. DATB (diaminotrinitrobenzene) (1630-08-6);
	8. DDFP (1,4-dinitrodifurazanopiperazine);
	9. DDPO (2,6-diamino-3,5-dinitropyrazine-1-oxide, PZO) (194486-77-6);
	10. DIPAM (3,3'-diamino-2,2',4,4',6,6'-hexanitrobiphenyl or dipicramide) (17215-44-0);
	11. DNGU (DINGU or dinitroglycoluril) (55510-04-8);
	12. Furazans as follows: <ul style="list-style-type: none"> <li>a. DAAOF (DAAF, DAAFox, or diaminoazoxyfurazan);</li> <li>b. DAAzF (diaminoazofurazan) (78644-90-3);</li> </ul>
	13. HMX and derivatives (see also Category Code ML8.g.5. for its “precursors”), as follows: <ul style="list-style-type: none"> <li>a. HMX (Cyclotetramethylenetetranitramine, octahydro-1,3,5,7-tetranitro-1,3,5,7-tetrazine, 1,3,5,7-tetranitro-1,3,5,7-tetraza-cyclooctane, octogen or octogene) (2691-41-0);</li> <li>b. Difluoroaminated analogs of HMX;</li> <li>c. K-55 (2,4,6,8-tetranitro-2,4,6,8-tetraazabicyclo [3,3,0]-octanone-3, tetranitrosemiglycouril or keto-bicyclic HMX) (130256-72-3);</li> </ul>

<i>Category Code</i>	<i>Item Description</i>
	14. HNAD (hexanitroadamantane) (143850-71-9);
	15. HNS (hexanitrostilbene) (20062-22-0);
	16. Imidazoles as follows:
	a. BNNII (Octahydro-2,5-bis(nitroimino)imidazo [4,5-d]imidazole);
	b. DNI (2,4-dinitroimidazole) (5213-49-0);
	c. FDIA (1-fluoro-2,4-dinitroimidazole);
	d. NTDNIA (N-(2-nitrotriazolo)-2,4-dinitroimidazole);
	e. PTIA (1-picryl-2,4,5-trinitroimidazole);
	17. NTNMH (1-(2-nitrotriazolo)-2-dinitromethylene hydrazine);
	18. NTO (ONTA or 3-nitro-1,2,4-triazol-5-one) (932-64-9);
	19. Polynitrocubanes with more than four nitro groups;
	20. PYX (2,6-Bis(picrylamino)-3,5-dinitropyridine) (38082-89-2);
	21. RDX and derivatives, as follows:
	a. RDX (cyclotrimethylenetrinitramine, cyclonite, T4, hexahydro-1,3,5-trinitro-1,3,5-triazine, 1,3,5-trinitro-1,3,5-triazacyclohexane, hexogen or hexogene) (121-82-4);
	b. Keto-RDX (K-6 or 2,4,6-trinitro-2,4,6-triazacyclohexanone) (115029-35-1);
	22. TAGN (triaminoguanidinenitrate) (4000-16-2);
	23. TATB (triaminotrinitrobenzene) (3058-38-6) (see also Category Code ML8.g.7. for its “precursors”);
	24. TEDDZ (3,3,7,7-tetrabis(difluoroamine) octahydro-1,5-dinitro-1,5-diazocine);
	25. Tetrazoles as follows:
	a. NTAT (nitrotriazol aminotetrazole);

<i>Category Code</i>	<i>Item Description</i>
	<ul style="list-style-type: none"> <li>b. NTNT (1-N-(2-nitrotriazolo)-4-nitrotetrazole);</li> </ul>
	26. Tetryl (trinitrophenylmethylnitramine) (479-45-8);
	27. TNAD (1,4,5,8-tetranitro-1,4,5,8-tetraazadecalin) (135877-16-6) (see also Category Code ML8.g.6. for its “precursors”);
	28. TNAZ (1,3,3-trinitroazetidine) (97645-24-4) (see also Category Code ML8.g.2. for its “precursors”);
	29. TNGU (SORGUYL or tetranitroglycoluril) (55510-03-7);
	30. TNP (1,4,5,8-tetranitro-pyridazino[4,5-d]pyridazine) (229176-04-9);
	31. Triazines as follows: <ul style="list-style-type: none"> <li>a. DNAM (2-oxy-4,6-dinitroamino-s-triazine) (19899-80-0);</li> <li>b. NNHT (2-nitroimino-5-nitro-hexahydro-1,3,5-triazine) (130400-13-4);</li> </ul>
	32. Triazoles as follows: <ul style="list-style-type: none"> <li>a. 5-azido-2-nitrotriazole;</li> <li>b. ADHTDN (4-amino-3,5-dihydrazino-1,2,4-triazole dinitramide) (1614-08-0);</li> <li>c. ADNT (1-amino-3,5-dinitro-1,2,4-triazole);</li> <li>d. BDNTA ((bis-dinitrotriazole)amine);</li> <li>e. DBT (3,3'-dinitro-5,5-bi-1,2,4-triazole) (30003-46-4);</li> <li>f. DNBT (dinitrobistriazole) (70890-46-9);</li> <li>g. Not used;</li> <li>h. NTDNT (1-N-(2-nitrotriazolo) 3,5-dinitrotriazole);</li> <li>i. PDNT (1-picryl-3,5-dinitrotriazole);</li> <li>j. TACOT (tetranitrobenzotriazolobenzotriazole) (25243-36-1);</li> </ul>

<i>Category Code</i>	<i>Item Description</i>
	<p>33. Explosives not listed elsewhere in Category Code ML8.a. and having any of the following:</p> <ol style="list-style-type: none"> <li>a. Detonation velocity exceeding 8,700 m/s, at maximum density; <u>or</u></li> <li>b. Detonation pressure exceeding 34 GPa (340 kbar);</li> </ol> <p>34. Not used;</p> <p>35. DNAN (2,4-dinitroanisole) (119-27-7);</p> <p>36. TEX (4,10-Dinitro-2,6,8,12-tetraoxa-4,10-diazaisowurtzitane);</p> <p>37. GUDN (Guanylurea dinitramide) FOX-12 (217464-38-5);</p> <p>38. Tetrazines as follows:</p> <ol style="list-style-type: none"> <li>a. BTAT (Bis(2,2,2-trinitroethyl)-3,6-diaminotetrazine);</li> <li>b. LAX-112 (3,6-diamino-1,2,4,5-tetrazine-1,4-dioxide);</li> </ol> <p>39. Energetic ionic materials melting between 343 K (70°C) and 373 K (100°C) and with detonation velocity exceeding 6,800 m/s or detonation pressure exceeding 18 GPa (180 kbar);</p> <p>b. "Propellants" as follows:</p> <ol style="list-style-type: none"> <li>1. Any solid "propellant" with a theoretical specific impulse (under standard conditions) of more than: <ol style="list-style-type: none"> <li>a. 240 seconds for non-metallised, non-halogenised "propellant";</li> <li>b. 250 seconds for non-metallised, halogenised "propellant"; <u>or</u></li> <li>c. 260 seconds for metallised "propellant";</li> </ol> </li> <li>2. Not used;</li> <li>3. "Propellants" having a force constant of more than 1,200 kJ/kg;</li> </ol>

<i>Category Code</i>	<i>Item Description</i>
	<p>4. “Propellants” that can sustain a steady-state linear burning rate of more than 38 mm/s under standard conditions (as measured in the form of an inhibited single strand) of 6.89 MPa (68.9 bar) pressure and 294 K (21°C);</p> <p>5. Elastomer Modified Cast Double Base (EMCDB) “propellants” with extensibility at maximum stress of more than 5% at 233 K (-40°C);</p> <p>6. Any “propellant” containing substances specified in Category Code ML8.a.;</p> <p>7. “Propellants”, not specified elsewhere in any part of this Division, specially designed for military use;</p> <p>c. “Pyrotechnics”, fuels and related substances, as follows, and ‘mixtures’ thereof:</p> <p>1. Aircraft fuels specially formulated for military purposes;</p> <p><i>Note</i> <i>Aircraft fuels specified in Category Code ML8.c.1. are finished products, not their constituents.</i></p> <p>2. Alane (aluminium hydride) (7784-21-6);</p> <p>3. Carboranes; decaborane (17702-41-9); pentaboranes (19624-22-7 and 18433-84-6) and their derivatives;</p> <p>4. Hydrazine and derivatives, as follows (see also Category Codes ML8.d.8. and d.9. for oxidising hydrazine derivatives):</p> <p>a. Hydrazine (302-01-2) in concentrations of 70% or more;</p> <p>b. Monomethyl hydrazine (60-34-4);</p> <p>c. Symmetrical dimethyl hydrazine (540-73-8);</p> <p>d. Unsymmetrical dimethyl hydrazine (57-14-7);</p> <p><i>Note</i> <i>Category Code ML8.c.4.a. does not apply to hydrazine ‘mixtures’ specially formulated for corrosion control.</i></p>

<i>Category Code</i>	<i>Item Description</i>
	<p>5. Metal fuels, fuels mixtures or “pyrotechnic” mixtures, in particle form whether spherical, atomised, spheroidal, flaked or ground, manufactured from material consisting of 99% or more of any of the following:</p> <p>a. Metals as follows and mixtures thereof:</p> <ol style="list-style-type: none"> <li>1. Beryllium (7440-41-7) in particle sizes of less than 60 µm;</li> <li>2. Iron powder (7439-89-6) with particle size of 3 µm or less produced by reduction of iron oxide with hydrogen;</li> </ol> <p>b. ‘Mixtures’ containing any of the following:</p> <ol style="list-style-type: none"> <li>1. Zirconium (7440-67-7), magnesium (7439-95-4) or alloys of these in particle sizes of less than 60 µm; <u>or</u></li> <li>2. Boron (7440-42-8) or boron carbide (12069-32-8) fuels of 85% purity or higher and particle sizes of less than 60 µm;</li> </ol> <p><u>Note 1</u>  <i>Category Code ML8.c.5. applies to explosives and fuels, whether or not the metals or alloys are encapsulated in aluminium, magnesium, zirconium, or beryllium.</i></p> <p><u>Note 2</u>  <i>Category Code ML8.c.5.b. only applies to metal fuels in particle form when they are mixed with other substances to form a mixture formulated for military purposes such as liquid propellant slurries, solid propellants, or pyrotechnic mixtures.</i></p> <p><u>Note 3</u>  <i>Category Code ML8.c.5.b.2. does not apply to boron and boron carbide enriched with boron-10 (20% or more of total boron-10 content).</i></p>

<i>Category Code</i>	<i>Item Description</i>
	<p>6. Military materials, containing thickeners for hydrocarbon fuels, specially formulated for use in flame throwers or incendiary munitions, such as metal stearates (e.g. octal (637-12-7)) or palmitates;</p> <p>7. Perchlorates, chlorates and chromates, composited with powdered metal or other high energy fuel components;</p> <p>8. Spherical or spheroidal aluminium powder (7429-90-5) with a particle size of 60 <math>\mu\text{m}</math> or less and manufactured from material with an aluminium content of 99% or more;</p> <p>9. Titanium subhydride (<math>\text{TiH}_n</math>) of stoichiometry equivalent to <math>n = 0.65-1.68</math>;</p> <p>10. Liquid high energy density fuels not specified in Category Code ML8.c.1., as follows:</p> <p style="padding-left: 20px;">a. Mixed fuels, that incorporate both solid and liquid fuels (e.g. boron slurry), having a mass-based energy density of 40 MJ/kg or greater;</p> <p style="padding-left: 20px;">b. Other high energy density fuels and fuel additives (e.g. cubane, ionic solutions, JP-7, JP-10), having a volume-based energy density of 37.5 GJ per cubic metre or greater, measured at 293 K (20°C) and one atmosphere (101.325 kPa) pressure;</p> <p style="padding-left: 40px;"><i>Note</i> <i>Category Code ML8.c.10.b. does not apply to JP-4, JP-8, fossil refined fuels or biofuels, or fuels for engines certified for used in civil aviation.</i></p> <p>11. “Pyrotechnic” and pyrophoric materials as follows:</p> <p style="padding-left: 20px;">a. “Pyrotechnic” and pyrophoric materials specifically formulated to enhance or control the production of radiated energy in any part of the IR spectrum;</p>

<i>Category Code</i>	<i>Item Description</i>
	<p>b. Mixtures of magnesium, polytetrafluoroethylene (PTFE) and a vinylidene difluoride-hexafluoropropylene copolymer (e.g. MTV);</p> <p>12. Fuel mixtures, “pyrotechnic” mixtures or “energetic materials”, not specified elsewhere in Category Code ML8, having all of the following:</p> <p>a. Containing greater than 0.5% of particles of any of the following:</p> <ol style="list-style-type: none"> <li>1. Aluminium;</li> <li>2. Beryllium;</li> <li>3. Boron;</li> <li>4. Zirconium;</li> <li>5. Magnesium; <u>or</u></li> <li>6. Titanium;</li> </ol> <p>b. Particles specified in Category Code ML8.c.12.a. with a size less than 200 nm in any direction; <u>and</u></p> <p>c. Particles specified in Category Code ML8.c.12.a. with a metal content of 60% or greater;</p> <p>d. Oxidisers as follows, and mixtures thereof:</p> <ol style="list-style-type: none"> <li>1. ADN (ammonium dinitramide or SR 12) (140456-78-6);</li> <li>2. AP (ammonium perchlorate) (7790-98-9);</li> <li>3. Compounds composed of fluorine and any of the following: <ol style="list-style-type: none"> <li>a. Other halogens;</li> <li>b. Oxygen; <u>or</u></li> <li>c. Nitrogen;</li> </ol> </li> </ol> <p><i>Note 1</i>  Category Code ML8.d.3. does not apply to chlorine trifluoride (7790-91-2).</p>



<i>Category Code</i>	<i>Item Description</i>
	<p><i>Note 2</i>  <i>Category Code ML8.d.3. does not apply to nitrogen trifluoride (7783-54-2) in its gaseous state.</i></p> <ol style="list-style-type: none"> <li>4. DNAD (1,3-dinitro-1,3-diazetidine) (78246-06-7);</li> <li>5. HAN (hydroxylammonium nitrate) (13465-08-2);</li> <li>6. HAP (hydroxylammonium perchlorate) (15588-62-2);</li> <li>7. HNF (hydrazinium nitroformate) (20773-28-8);</li> <li>8. Hydrazine nitrate (37836-27-4);</li> <li>9. Hydrazine perchlorate (27978-54-7);</li> <li>10. Liquid oxidisers comprised of or containing inhibited red fuming nitric acid (IRFNA) (8007-58-7);</li> </ol> <p><i>Note</i>  <i>Category Code ML8.d.10. does not apply to non-inhibited fuming nitric acid.</i></p> <p>e. Binders, plasticisers, monomers and polymers, as follows:</p> <ol style="list-style-type: none"> <li>1. AMMO (azidomethylmethyloxetane and its polymers) (90683-29-7) (see also Category Code ML8.g.1. for its “precursors”);</li> <li>2. BAMO (3,3-bis(azidomethyl)oxetane and its polymers) (17607-20-4) (see also Category Code ML8.g.1. for its “precursors”);</li> <li>3. BDNPA (bis (2,2-dinitropropyl)acetal) (5108-69-0);</li> <li>4. BDNPF (bis (2,2-dinitropropyl)formal) (5917-61-3);</li> <li>5. BTTN (butanetrioltrinitrate) (6659-60-5) (see also Category Code ML8.g.8. for its “precursors”);</li> <li>6. Energetic monomers, plasticisers or polymers, specially formulated for military use and containing any of the following: <ol style="list-style-type: none"> <li>a. Nitro groups;</li> <li>b. Azido groups;</li> <li>c. Nitrate groups;</li> <li>d. Nitraza groups; <u>or</u></li> </ol> </li> </ol>

<i>Category Code</i>	<i>Item Description</i>
	<p>e. Difluoroamino groups;</p> <p>7. FAMA0 (3-difluoroaminomethyl-3-azidomethyl oxetane) and its polymers;</p> <p>8. FEFO (bis-(2-fluoro-2,2-dinitroethyl) formal) (17003-79-1);</p> <p>9. FPF-1 (poly-2,2,3,3,4,4-hexafluoropentane-1,5-diol formal) (376-90-9);</p> <p>10. FPF-3 (poly-2,4,4,5,5,6,6-heptafluoro-2-trifluoromethyl-3-oxaheptane-1,7-diol formal);</p> <p>11. GAP (glycidylazide polymer) (143178-24-9) and its derivatives;</p> <p>12. HTPB (hydroxyl terminated polybutadiene) with a hydroxyl functionality equal to or greater than 2.2 and less than or equal to 2.4, a hydroxyl value of less than 0.77 meq/g, and a viscosity at 30°C of less than 47 poise (69102-90-5);</p> <p>13. Alcohol functionalised poly(epichlorohydrin) with a molecular weight of less than 10,000, as follows:</p> <p style="padding-left: 20px;">a. Poly(epichlorohydrindiol);</p> <p style="padding-left: 20px;">b. Poly(epichlorohydrintriol);</p> <p>14. NENAs (nitrate ethylnitramine compounds) (17096-47-8, 85068-73-1, 82486-83-7, 82486-82-6 and 85954-06-9);</p> <p>15. PGN (poly-GLYN, polyglycidyl nitrate or poly(nitratomethyl oxirane)) (27814-48-8);</p> <p>16. Poly-NIMMO (poly nitratomethylmethyloxetane), poly-NMMO or (poly(3-Nitratomethyl-3-methyloxetane)) (84051-81-0);</p> <p>17. Polynitroorthocarbonates;</p> <p>18. TVOPA (1,2,3-tris[1,2-bis(difluoroamino)ethoxy] propane or tris vinoxyl propane adduct) (53159-39-0);</p> <p>19. 4,5 diazidomethyl-2-methyl-1,2,3-triazole (iso-DAMTR);</p> <p>20. PNO (Poly(3-nitrate oxetane));</p>

<i>Category Code</i>	<i>Item Description</i>
	<p>f. "Additives" as follows:</p> <ol style="list-style-type: none"> <li>1. Basic copper salicylate (62320-94-9);</li> <li>2. BHEGA (bis-(2-hydroxyethyl) glycolamide) (17409-41-5);</li> <li>3. BNO (butadienenitrileoxide);</li> <li>4. Ferrocene derivatives, as follows: <ol style="list-style-type: none"> <li>a. Butacene (125856-62-4);</li> <li>b. Catocene (2,2-bis-ethylferrocenyl propane) (37206-42-1);</li> <li>c. Ferrocene carboxylic acids and ferrocene carboxylic acid esters;</li> <li>d. n-butyl ferrocene (31904-29-7);</li> <li>e. Other adducted polymer ferrocene derivatives not specified elsewhere in Category Code ML8.f.4.;</li> <li>f. Ethyl ferrocene (1273-89-8);</li> <li>g. Propyl ferrocene;</li> <li>h. Pentyl ferrocene (1274-00-6);</li> <li>i. Dicyclopentyl ferrocene;</li> <li>j. Dicyclohexyl ferrocene;</li> <li>k. Diethyl ferrocene (1273-97-8);</li> <li>l. Dipropyl ferrocene;</li> <li>m. Dibutyl ferrocene (1274-08-4);</li> <li>n. Dihexyl ferrocene (93894-59-8);</li> <li>o. Acetyl ferrocene (1271-55-2)/1,1'-diacetyl ferrocene (1273-94-5);</li> </ol> </li> <li>5. Lead beta-resorcyate (20936-32-7);</li> <li>6. Lead citrate (14450-60-3);</li> <li>7. Lead-copper chelates of beta-resorcyate or salicylates (68411-07-4);</li> <li>8. Lead maleate (19136-34-6);</li> </ol>

<i>Category Code</i>	<i>Item Description</i>
	<p>9. Lead salicylate (15748-73-9);</p> <p>10. Lead stannate (12036-31-6);</p> <p>11. MAPO (tris-1-(2-methyl)aziridiny phosphine oxide) (57-39-6); BOBBA 8 (bis(2-methyl aziridiny) 2-(2-hydroxypropanoxy) propylamino phosphine oxide); and other MAPO derivatives;</p> <p>12. Methyl BAPO (bis(2-methyl aziridiny) methylamino phosphine oxide) (85068-72-0);</p> <p>13. N-methyl-p-nitroaniline (100-15-2);</p> <p>14. 3-Nitrazo-1,5-pentane diisocyanate (7406-61-9);</p> <p>15. Organo-metallic coupling agents as follows:</p> <ul style="list-style-type: none"> <li>a. Neopentyl[diallyl]oxy, tri[diethyl]phosphato-titanate (103850-22-2); also known as titanium IV, 2,2[bis 2-propenolato-methyl, butanolato, tris (diethyl) phosphato] (110438-25-0); or LICA 12 (103850-22-2);</li> <li>b. Titanium IV, [(2-propenolato-1) methyl, n-propanolatomethyl] butanolato-1, tris[diethyl] pyrophosphate or KR3538;</li> <li>c. Titanium IV, [(2-propenolato-1)methyl, n-propanolatomethyl] butanolato-1, tris(diethyl)phosphate;</li> </ul> <p>16. Polycyanodifluoroaminoethyleneoxide;</p> <p>17. Bonding agents as follows:</p> <ul style="list-style-type: none"> <li>a. 1,1R,1S-trimesoyl-tris(2-ethylaziridine) (HX-868, BITA) (7722-73-8);</li> <li>b. Polyfunctional aziridine amides with isophthalic, trimesic, isocyanuric or trimethyladipic backbone also having a 2-methyl or 2-ethyl aziridine group;</li> </ul> <p><i>Note</i></p> <p><i>Category Code ML8.f.17.b. includes:</i></p> <ul style="list-style-type: none"> <li>a. 1,1 H-Isophthaloyl-bis(2-methylaziridine) (HX-752) (7652-64-4);</li> </ul>

Category Code	Item Description
	<p>b. 2,4,6-tris(2-ethyl-1-aziridinyl)-1,3,5-triazine (HX-874) (18924-91-9);</p> <p>c. 1,1'-trimethyladipoyl-bis(2-ethylaziridine) (HX-877) (71463-62-2).</p>
	18. Propyleneimine (2-methylaziridine) (75-55-8);
	19. Superfine iron oxide (Fe <sub>2</sub> O <sub>3</sub> ) (1317-60-8) with a specific surface area more than 250 m <sup>2</sup> /g and an average particle size of 3 nm or less;
	20. TEPAN (tetraethylenepentaamineacrylonitrile) (68412-45-3); cyanoethylated polyamines and their salts;
	21. TEPANOL (tetraethylenepentaamineacrylonitrileglycidol) (68412-46-4); cyanoethylated polyamines adducted with glycidol and their salts;
	22. TPB (triphenyl bismuth) (603-33-8);
	23. TEPB (Tris (ethoxyphenyl) bismuth) (90591-48-3);
	g. "Precursors" as follows:
	<u>N.B.</u>
	<i>The references in Category Code ML8.g. are specified "energetic materials" manufactured from these substances.</i>
	1. BCMO (3,3-bis(chloromethyl)oxetane) (78-71-7) (see also Category Codes ML8.e.1. and e.2.);
	2. Dinitroazetidine-t-butyl salt (125735-38-8) (see also Category Code ML8.a.28.);
	3. Hexaazaisowurtzitane derivatives including HBIW (hexabenzylhexaazaisowurtzitane) (124782-15-6) (see also Category Code ML8.a.4.) and TAIW (tetraacetyldibenzylhexaazaisowurtzitane) (182763-60-6) (see also Category Code ML8.a.4.);
	4. Not used;
	5. TAT (1,3,5,7 tetraacetyl-1,3,5,7,-tetraaza cyclo-octane) (41378-98-7) (see also Category Code ML8.a.13.);

<i>Category Code</i>	<i>Item Description</i>
	<p>6. 1,4,5,8-tetraazadecalin (5409-42-7) (see also Category Code ML8.a.27.);</p> <p>7. 1,3,5-trichlorobenzene (108-70-3) (see also Category Code ML8.a.23.);</p> <p>8. 1,2,4-trihydroxybutane (1,2,4-butanetriol) (3068-00-6) (see also Category Code ML8.e.5.);</p> <p>9. DADN (1,5-diacetyl-3,7-dinitro-1, 3, 5, 7-tetraazacyclooctane) (see also Category Code ML8.a.13.).</p>
	<p><u>Note 1</u></p> <p><i>Category Code ML8 does not apply to the following substances unless they are compounded or mixed with the “energetic material” specified in Category Code ML8.a. or powdered metals specified in Category Code ML8.c.:</i></p> <p>a. <i>Ammonium picrate (131-74-8);</i></p> <p>b. <i>Black powder;</i></p> <p>c. <i>Hexanitrodiphenylamine (131-73-7);</i></p> <p>d. <i>Difluoroamine (10405-27-3);</i></p> <p>e. <i>Nitrostarch (9056-38-6);</i></p> <p>f. <i>Potassium nitrate (7757-79-1);</i></p> <p>g. <i>Tetranitronaphthalene;</i></p> <p>h. <i>Trinitroanisol;</i></p> <p>i. <i>Trinitronaphthalene;</i></p> <p>j. <i>Trinitroxylene;</i></p> <p>k. <i>N-pyrrolidinone; 1-methyl-2-pyrrolidinone (872-50-4);</i></p> <p>l. <i>Diocylmaleate (142-16-5);</i></p> <p>m. <i>Ethylhexylacrylate (103-11-7);</i></p> <p>n. <i>Triethylaluminium (TEA) (97-93-8), trimethylaluminium (TMA) (75-24-1), and other pyrophoric metal alkyls and aryls of lithium, sodium, magnesium, zinc or boron;</i></p> <p>o. <i>Nitrocellulose (9004-70-0);</i></p> <p>p. <i>Nitroglycerin (or glyceroltrinitrate, trinitroglycerine) (NG) (55-63-0);</i></p>

Category Code	Item Description
q.	2,4,6-trinitrotoluene (TNT) (118-96-7);
r.	Ethylenediaminedinitrate (EDDN) (20829-66-7);
s.	Pentaerythritoltetranitrate (PETN) (78-11-5);
t.	Lead azide (13424-46-9), normal lead styphnate (15245-44-0) and basic lead styphnate (12403-82-6), and primary explosives or priming compositions containing azides or azide complexes;
u.	Triethyleneglycoldinitrate (TEGDN) (111-22-8);
v.	2,4,6-trinitroresorcinol (styphnic acid) (82-71-3);
w.	Diethyldiphenylurea (85-98-3); dimethyldiphenylurea (611-92-7); methylethyldiphenylurea; [Centralites];
x.	N,N-diphenylurea (unsymmetrical diphenylurea) (603-54-3);
y.	Methyl-N,N-diphenylurea (methyl unsymmetrical diphenylurea) (13114-72-2);
z.	Ethyl-N,N-diphenylurea (ethyl unsymmetrical diphenylurea) (64544-71-4);
aa.	2-Nitrodiphenylamine (2-NDPA) (119-75-5);
bb.	4-Nitrodiphenylamine (4-NDPA) (836-30-6);
cc.	2,2-dinitropropanol (918-52-5);
dd.	Nitroguanidine (556-88-7) (see Category Code 1C011.d. in Division 2 of Part II of this Schedule).
<u>Note 2</u>	
Category Code ML8. does not apply to ammonium perchlorate (Category Code ML8.d.2.), NTO (Category Code ML8.a.18.) or catocene (Category Code ML8.f.4.b.), and meeting all of the following:	
a.	Specially shaped and formulated for civil-use gas generation devices;
b.	Compounded or mixed, with non-active thermoset binders or plasticisers, and having a mass of less than 250 g;
c.	Having a maximum of 80% ammonium perchlorate (Category Code ML8.d.2.) in mass of active material;

<i>Category Code</i>	<i>Item Description</i>
ML9	<p>d. <i>Having less than or equal to 4 g of NTO (Category Code ML8.a.18.); <u>and</u></i></p> <p>e. <i>Having less than or equal to 1 g of catocene (Category Code ML8.f.4.b.).</i></p> <p>Vessels of war (surface or underwater), special naval equipment, accessories, components and other surface vessels, as follows:</p> <p><u>N.B.</u> <i>For guidance and navigation equipment, see Category Code ML11.</i></p> <p>a. Vessels and components, as follows:</p> <ol style="list-style-type: none"> <li>1. Vessels (surface or underwater) specially designed or modified for military use, regardless of current state of repair or operating condition, and whether or not they contain weapon delivery systems or armour, and hulls or parts of hulls for such vessels, and components therefor specially designed for military use;</li> <li>2. Surface vessels, other than those specified in Category Code ML9.a.1., having any of the following, fixed or integrated into the vessel: <ol style="list-style-type: none"> <li>a. Automatic weapons specified in Category Code ML1, or weapons specified in Category Code ML2, ML4, ML12 or ML19, or 'mountings' or hard points for weapons having a calibre of 12.7 mm or greater; <p><u>Technical Note</u> <i>'Mountings' refers to weapon mounts or structural strengthening for the purpose of installing weapons.</i></p> </li> <li>b. Fire control systems specified in Category Code ML5;</li> <li>c. Having all of the following: <ol style="list-style-type: none"> <li>1. 'Chemical, Biological, Radiological and Nuclear (CBRN) protection'; <u>and</u></li> </ol> </li> </ol> </li> </ol>



<i>Category Code</i>	<i>Item Description</i>
	<p data-bbox="715 454 1265 555">2. 'Pre-wet or wash down system' designed for decontamination purposes; <u>or</u></p> <p data-bbox="778 566 975 600"><i>Technical Notes</i></p> <p data-bbox="778 611 1265 880">1. 'CBRN protection' is a self-contained interior space containing features such as over-pressurisation, isolation of ventilation systems, limited ventilation openings with CBRN filters and limited personnel access points incorporating air-locks.</p> <p data-bbox="778 902 1265 1059">2. 'Pre-wet or wash down system' is a seawater spray system capable of simultaneously wetting the exterior superstructure and decks of a vessel.</p> <p data-bbox="651 1081 1265 1182">d. Active weapon countermeasure systems specified in Category Code ML4.b., ML5.c. or ML11.a. and having any of the following:</p> <p data-bbox="715 1193 1018 1227">1. 'CBRN protection';</p> <p data-bbox="715 1249 1265 1350">2. Hull and superstructure, specially designed to reduce the radar cross section;</p> <p data-bbox="715 1373 1265 1563">3. Thermal signature reduction devices, (e.g. an exhaust gas cooling system), excluding those specially designed to increase overall power plant efficiency or to reduce the environmental impact; <u>or</u></p> <p data-bbox="715 1585 1265 1686">4. A degaussing system designed to reduce the magnetic signature of the whole vessel;</p>

<i>Category Code</i>	<i>Item Description</i>
	<p data-bbox="778 454 962 488"><i>Technical Note</i></p> <p data-bbox="778 495 1268 725"><i>'CBRN protection' is a self-contained interior space containing features such as over-pressurisation, isolation of ventilation systems, limited ventilation openings with CBRN filters and limited personnel access points incorporating air-locks.</i></p> <p data-bbox="501 748 1268 846">b. Engines and propulsion systems, as follows, specially designed for military use and components therefor specially designed for military use:</p> <ol data-bbox="564 864 1268 1711" style="list-style-type: none"> <li data-bbox="564 864 1268 931">1. Diesel engines specially designed for submarines and having all of the following: <ol data-bbox="651 949 1268 1061" style="list-style-type: none"> <li data-bbox="651 949 1268 1016">a. Power output of 1.12 MW (1,500 hp) or more; <u>and</u></li> <li data-bbox="651 1034 1268 1061">b. Rotary speed of 700 rpm or more;</li> </ol> </li> <li data-bbox="564 1079 1268 1146">2. Electric motors specially designed for submarines and having all of the following: <ol data-bbox="651 1164 1268 1375" style="list-style-type: none"> <li data-bbox="651 1164 1268 1232">a. Power output of more than 0.75 MW (1,000 hp);</li> <li data-bbox="651 1249 1268 1276">b. Quick reversing;</li> <li data-bbox="651 1294 1268 1321">c. Liquid cooled; <u>and</u></li> <li data-bbox="651 1339 1268 1375">d. Totally enclosed;</li> </ol> </li> <li data-bbox="564 1393 1268 1460">3. Non-magnetic diesel engines having all of the following: <ol data-bbox="651 1478 1268 1621" style="list-style-type: none"> <li data-bbox="651 1478 1268 1545">a. Power output of 37.3 kW (50 hp) or more; <u>and</u></li> <li data-bbox="651 1563 1268 1621">b. Non-magnetic content in excess of 75% of total mass;</li> </ol> </li> <li data-bbox="564 1639 1268 1706">4. 'Air Independent Propulsion' (AIP) systems specially designed for submarines;</li> </ol>

<i>Category Code</i>	<i>Item Description</i>
	<p data-bbox="630 454 810 488"><u>Technical Note</u></p> <p data-bbox="630 499 1265 696"><i>'Air Independent Propulsion' (AIP) allows a submerged submarine to operate its propulsion system, without access to atmospheric oxygen, for a longer time than the batteries would have otherwise allowed. For the purpose of Category Code ML9.b.4., AIP does not include nuclear power.</i></p> <p data-bbox="502 719 1265 1093"> c. Underwater detection devices, specially designed for military use, controls therefor and components therefor specially designed for military use;  d. Anti-submarine nets and anti-torpedo nets, specially designed for military use;  e. Not used;  f. Hull penetrators and connectors, specially designed for military use, that enable interaction with equipment external to a vessel, and components therefor specially designed for military use; </p> <p data-bbox="566 1115 625 1149"><u>Note</u></p> <p data-bbox="566 1160 1265 1525"><i>Category Code ML9.f. includes connectors for vessels which are of the single-conductor, multi-conductor, coaxial or waveguide type, and hull penetrators for vessels, both of which are capable of remaining impervious to leakage from without and of retaining required characteristics at marine depths exceeding 100 m; and fibre-optic connectors and optical hull penetrators, specially designed for "laser" beam transmission, regardless of depth. Category Code ML9.f. does not apply to ordinary propulsive shaft and hydrodynamic control-rod hull penetrators.</i></p> <p data-bbox="502 1547 1265 1794"> g. Silent bearings having any of the following, components therefor and equipment containing those bearings, specially designed for military use: <ol data-bbox="566 1659 1002 1794" style="list-style-type: none"> <li>1. Gas or magnetic suspension;</li> <li>2. Active signature controls; <u>or</u></li> <li>3. Vibration suppression controls.</li> </ol> </p>

<i>Category Code</i>	<i>Item Description</i>
ML10	<p>“Aircraft”, “lighter-than-air vehicles”, “Unmanned Aerial Vehicles” (“UAVs”), aero-engines and “aircraft” equipment, related equipment and components, as follows, specially designed or modified for military use:</p> <p><i>N.B.</i></p> <p><i>For guidance and navigation equipment, see Category Code ML11.</i></p> <ol style="list-style-type: none"> <li>a. Manned “aircraft” and “lighter-than-air vehicles”, and specially designed components therefor;</li> <li>b. Not used;</li> <li>c. Unmanned aircraft and related equipment, as follows, and specially designed components therefor: <ol style="list-style-type: none"> <li>1. “UAVs”, Remotely Piloted Air Vehicles (RPVs), autonomous programmable vehicles and unmanned “lighter-than-air vehicles”;</li> <li>2. Launchers, recovery equipment and ground support equipment;</li> <li>3. Equipment designed for command and control;</li> </ol> </li> <li>d. Propulsion aero-engines and specially designed components therefor;</li> <li>e. Airborne refuelling equipment specially designed or modified for any of the following, and specially designed components therefor: <ol style="list-style-type: none"> <li>1. “Aircraft” specified in Category Code ML10.a.; <u>or</u></li> <li>2. Unmanned aircraft specified in Category Code ML10.c.;</li> </ol> </li> <li>f. ‘Ground equipment’ specially designed for aircraft specified in Category Code ML10.a. or aero-engines specified in Category Code ML10.d.;</li> </ol> <p><i>Technical Note</i></p> <p><i>‘Ground equipment’ includes pressure refuelling equipment and equipment designed to facilitate operations in confined areas.</i></p>

<i>Category Code</i>	<i>Item Description</i>
	<p data-bbox="499 454 1267 589">g. Aircrew life support equipment, aircrew safety equipment and other devices for emergency escape, not specified in Category Code ML10.a., designed for “aircraft” specified in Category Code ML10.a.;</p> <p data-bbox="563 607 627 636"><u>Note</u></p> <p data-bbox="563 647 1267 745"><i>Category Code ML10.g. does not include aircrew helmets that do not incorporate, or have mountings or fittings for, equipment specified in any part of this Division.</i></p> <p data-bbox="563 763 627 792"><u>N.B.</u></p> <p data-bbox="563 804 1107 833"><i>For helmets, see also Category Code ML13.c.</i></p> <p data-bbox="499 853 1267 920">h. Parachutes, paragliders and related equipment, as follows, and specially designed components therefor:</p> <ol data-bbox="563 938 1267 1171" style="list-style-type: none"> <li data-bbox="563 938 1267 1005">1. Parachutes not specified elsewhere in any part of this Division;</li> <li data-bbox="563 1023 772 1052">2. Paragliders;</li> <li data-bbox="563 1070 1267 1171">3. Equipment specially designed for high altitude parachutists (e.g. suits, special helmets, breathing systems, navigation equipment);</li> </ol> <p data-bbox="499 1189 1267 1256">i. Controlled opening equipment or automatic piloting systems, designed for parachuted loads.</p> <p data-bbox="499 1274 584 1303"><u>Note 1</u></p> <p data-bbox="499 1314 1267 1449"><i>Category Code ML10.a. does not apply to “aircraft” or “lighter-than-air vehicles” or variants of those “aircraft”, specially designed for military use and which are all of the following:</i></p> <ol data-bbox="499 1467 1267 1700" style="list-style-type: none"> <li data-bbox="499 1467 836 1496">a. <i>Not a combat aircraft;</i></li> <li data-bbox="499 1514 1267 1612">b. <i>Not configured for military use and not fitted with equipment or attachments specially designed or modified for military use; <u>and</u></i></li> <li data-bbox="499 1630 1267 1700">c. <i>Certified for civil use by civil aviation authorities of one or more “participating states”.</i></li> </ol> <p data-bbox="499 1718 584 1747"><u>Note 2</u></p> <p data-bbox="499 1758 1011 1787"><i>Category Code ML10.d. does not apply to:</i></p>

<i>Category Code</i>	<i>Item Description</i>
	<p>a. <i>Aero-engines designed or modified for military use which have been certified for civil use by civil aviation authorities of one or more “participating states” or specially designed components therefor;</i></p> <p>b. <i>Reciprocating engines or specially designed components therefor, except those specially designed for “UAVs”.</i></p> <p><u>Note 3</u>  <i>For the purposes of Category Codes ML10.a. and ML10.d., specially designed components and related equipment for non-military “aircraft” or aero-engines modified for military use applies only to those military components and to military related equipment required for the modification to military use.</i></p> <p><u>Note 4</u>  <i>For the purpose of Category Code ML10.a., military use includes: combat, military reconnaissance, assault, military training, logistics support, and transporting and airdropping troops or military equipment.</i></p> <p><u>Note 5</u>  <i>Category Code ML10.a. does not apply to “aircraft” that meet all of the following:</i></p> <p>a. <i>Were first manufactured before 1946;</i></p> <p>b. <i>Do not incorporate items specified in any part of this Division, unless the items are required to meet safety or airworthiness standards of civil aviation authorities of one or more “participating states”; and</i></p> <p>c. <i>Do not incorporate weapons specified in any part of this Division, unless inoperable and incapable of being returned to operation.</i></p>
ML11	<p>Electronic equipment, “spacecraft” and components, not specified elsewhere in any part of this Division, as follows:</p> <p>a. <i>Electronic equipment specially designed for military use and specially designed components therefor;</i></p> <p><u>Note</u>  <i>Category Code ML11.a. includes:</i></p>

<i>Category Code</i>	<i>Item Description</i>
	<p>a. <i>Electronic countermeasure and electronic counter-countermeasure equipment (i.e. equipment designed to introduce extraneous or erroneous signals into radar or radio communication receivers or otherwise hinder the reception, operation or effectiveness of adversary electronic receivers including their countermeasure equipment), including jamming and counter-jamming equipment;</i></p> <p>b. <i>Frequency agile tubes;</i></p> <p>c. <i>Electronic systems or equipment, designed either for surveillance and monitoring of the electromagnetic spectrum for military intelligence or security purposes or for counteracting such surveillance and monitoring;</i></p> <p>d. <i>Underwater countermeasures, including acoustic and magnetic jamming and decoy, equipment designed to introduce extraneous or erroneous signals into sonar receivers;</i></p> <p>e. <i>Data processing security equipment, data security equipment and transmission and signalling line security equipment, using ciphering processes;</i></p> <p>f. <i>Identification, authentication and keyloader equipment and key management, manufacturing and distribution equipment;</i></p> <p>g. <i>Guidance and navigation equipment;</i></p> <p>h. <i>Digital troposcatter-radio communications transmission equipment;</i></p> <p>i. <i>Digital demodulators specially designed for signals intelligence;</i></p> <p>j. <i>“Automated Command and Control Systems”.</i></p> <p><u><i>N.B.</i></u>  <i>For “software” associated with military “Software” Defined Radio (SDR), see Category Code ML21.</i></p> <p>b. <i>Global Navigation Satellite Systems (GNSS) jamming equipment and specially designed components therefor;</i></p>

<i>Category Code</i>	<i>Item Description</i>
ML12	<p>c. “Spacecraft” specially designed or modified for military use, and “spacecraft” components specially designed for military use.</p> <p>High velocity kinetic energy weapon systems and related equipment, as follows, and specially designed components therefor:</p> <p>a. Kinetic energy weapon systems specially designed for destruction or effecting mission-abort of a target;</p> <p>b. Specially designed test and evaluation facilities and test models, including diagnostic instrumentation and targets, for dynamic testing of kinetic energy projectiles and systems.</p> <p><u>N.B.</u>  <i>For weapon systems using sub-calibre ammunition or employing solely chemical propulsion, and ammunition therefor, see Category Codes ML1 to ML4.</i></p> <p><u>Note 1</u>  <i>Category Code ML12 includes the following when specially designed for kinetic energy weapon systems:</i></p> <p>a. <i>Launch propulsion systems capable of accelerating masses larger than 0.1 g to velocities in excess of 1.6 km/s, in single or rapid fire modes;</i></p> <p>b. <i>Prime power generation, electric armour, energy storage (e.g. high energy storage capacitors), thermal management, conditioning, switching or fuel-handling equipment; and electrical interfaces between power supply, gun and other turret electric drive functions;</i></p> <p><u>N.B.</u>  <i>See also Category Code 3A001.e.2. in Division 2 of Part II of this Schedule for high energy storage capacitors.</i></p> <p>c. <i>Target acquisition, tracking, fire control or damage assessment systems;</i></p> <p>d. <i>Homing seeker, guidance or divert propulsion (lateral acceleration) systems for projectiles.</i></p>



<i>Category Code</i>	<i>Item Description</i>
	<p><u>Note 2</u>  <i>Category Code ML12 applies to weapon systems using any of the following methods of propulsion:</i></p> <ul style="list-style-type: none"> <li><i>a. Electromagnetic;</i></li> <li><i>b. Electrothermal;</i></li> <li><i>c. Plasma;</i></li> <li><i>d. Light gas; <u>or</u></i></li> <li><i>e. Chemical (when used in combination with any of the above).</i></li> </ul>
ML13	<p>Armoured or protective equipment, constructions and components, as follows:</p> <ul style="list-style-type: none"> <li>a. Metallic or non-metallic armoured plate, having any of the following: <ul style="list-style-type: none"> <li>1. Manufactured to comply with a military standard or specification; <u>or</u></li> <li>2. Suitable for military use;</li> </ul> <p><u>N.B.</u>  <i>For body armour plate, see Category Code ML13.d.2.</i></p> </li> <li>b. Constructions of metallic or non-metallic materials, or combinations thereof, specially designed to provide ballistic protection for military systems, and specially designed components therefor;</li> <li>c. Helmets manufactured according to military standards or specifications, or comparable national standards, and specially designed components therefor (i.e. helmet shell, liner and comfort pads);</li> <li>d. Body armour or protective garments, and components therefor, as follows: <ul style="list-style-type: none"> <li>1. Soft body armour or protective garments, manufactured to military standards or specifications, or to their equivalents, and specially designed components therefor;</li> </ul> </li> </ul>

<i>Category Code</i>	<i>Item Description</i>
	<p><u>Note</u> For the purpose of Category Code ML13.d.1., military standards or specifications include, at a minimum, specifications for fragmentation protection.</p> <p>2. Hard body armour plates providing ballistic protection equal to or greater than level III (NIJ 0101.06, July 2008) or national equivalents.</p> <p><u>Note 1</u> Category Code ML13.b. includes materials specially designed to form explosive reactive armour or to construct military shelters.</p> <p><u>Note 2</u> Category Code ML13.c. does not apply to conventional steel helmets, neither modified or designed to accept, nor equipped with any type of accessory device.</p> <p><u>Note 3</u> Category Codes ML13.c. and ML13.d. do not apply to helmets, body armour or protective garments, when accompanying their user for the user's own personal protection.</p> <p><u>Note 4</u> The only helmets specially designed for bomb disposal personnel that are specified in Category Code ML13 are those specially designed for military use.</p> <p><u>N.B. 1</u> See also Category Code 1A005 in Division 2 of Part II of this Schedule.</p> <p><u>N.B. 2</u> For "fibrous or filamentary materials" used in the manufacture of body armour and helmets, see Category Code 1C010 in Division 2 of Part II of this Schedule.</p>
ML14	'Specialised equipment for military training' or for simulating military scenarios, simulators specially designed for training in the use of any firearm or weapon specified in Category Code ML1 or ML2, and specially designed components and accessories therefor.

<i>Category Code</i>	<i>Item Description</i>
ML15	<p><u>Technical Note</u></p> <p><i>The term ‘specialised equipment for military training’ includes military types of attack trainers, operational flight trainers, radar target trainers, radar target generators, gunnery training devices, anti-submarine warfare trainers, flight simulators (including human-rated centrifuges for pilot/astronaut training), radar trainers, instrument flight trainers, navigation trainers, missile launch trainers, target equipment, drone “aircraft”, armament trainers, pilotless “aircraft” trainers, mobile training units and training equipment for ground military operations.</i></p> <p><u>Note 1</u></p> <p><i>Category Code ML14 includes image generating and interactive environment systems for simulators, when specially designed or modified for military use.</i></p> <p><u>Note 2</u></p> <p><i>Category Code ML14 does not apply to equipment specially designed for training in the use of hunting or sporting weapons.</i></p> <p>Imaging or countermeasure equipment, as follows, specially designed for military use, and specially designed components and accessories therefor:</p> <ol style="list-style-type: none"> <li>a. Recorders and image processing equipment;</li> <li>b. Cameras, photographic equipment and film processing equipment;</li> <li>c. Image intensifier equipment;</li> <li>d. Infrared or thermal imaging equipment;</li> <li>e. Imaging radar sensor equipment;</li> <li>f. Countermeasure or counter-countermeasure equipment, for the equipment specified in Category Codes ML15.a. to ML15.e.</li> </ol> <p><u>Note</u></p> <p><i>Category Code ML15.f. includes equipment designed to degrade the operation or effectiveness of military imaging systems or to minimise such degrading effects.</i></p>

<i>Category Code</i>	<i>Item Description</i>
	<p><u>Note 1</u>  <i>In Category Code ML15, the term specially designed components includes the following, when specially designed for military use:</i></p> <ul style="list-style-type: none"> <li><i>a. Infrared image converter tubes;</i></li> <li><i>b. Image intensifier tubes (other than first generation);</i></li> <li><i>c. Microchannel plates;</i></li> <li><i>d. Low-light-level television camera tubes;</i></li> <li><i>e. Detector arrays (including electronic interconnection or read out systems);</i></li> <li><i>f. Pyroelectric television camera tubes;</i></li> <li><i>g. Cooling systems for imaging systems;</i></li> <li><i>h. Electrically triggered shutters of the photochromic or electro-optical type having a shutter speed of less than 100 <math>\mu</math>s, except in the case of shutters which are an essential part of a high speed camera;</i></li> <li><i>i. Fibre optic image inverters;</i></li> <li><i>j. Compound semiconductor photocathodes.</i></li> </ul> <p><u>Note 2</u>  <i>Category Code ML15 does not apply to “first generation image intensifier tubes” or equipment specially designed to incorporate “first generation image intensifier tubes”.</i></p> <p><u>N.B.</u>  <i>For the classification of weapons sights incorporating “first generation image intensifier tubes” see Category Codes ML1, ML2 and ML5.a.</i></p> <p><u>N.B.</u>  <i>See also Category Codes 6A002.a.2. and 6A002.b. in Division 2 of Part II of this Schedule.</i></p>
ML16	<p>Forgings, castings and other unfinished products, specially designed for items specified in Category Code ML1 to ML4, ML6, ML9, ML10, ML12 or ML19.</p>

<i>Category Code</i>	<i>Item Description</i>
ML17	<p data-bbox="499 454 1268 566"><u>Note</u> <i>Category Code ML16 applies to unfinished products when they are identifiable by material composition, geometry or function.</i></p> <p data-bbox="499 629 1268 696">Miscellaneous equipment, materials and “libraries”, as follows, and specially designed components therefor:</p> <p data-bbox="499 712 1268 981">a. Diving and underwater swimming apparatus, specially designed or modified for military use, as follows:</p> <ol data-bbox="563 790 1268 981" style="list-style-type: none"> <li data-bbox="563 790 1268 857">1. Self-contained diving rebreathers, closed or semi-closed circuit;</li> <li data-bbox="563 880 1268 981">2. Underwater swimming apparatus specially designed for use with the diving apparatus specified in Category Code ML17.a.1.;</li> </ol> <p data-bbox="563 992 1268 1104"><u>N.B.</u> <i>See also Category Code 8A002.q. in Division 2 of Part II of this Schedule.</i></p> <p data-bbox="499 1122 1268 1189">b. Construction equipment specially designed for military use;</p> <p data-bbox="499 1205 1268 1272">c. Fittings, coatings and treatments, for signature suppression, specially designed for military use;</p> <p data-bbox="499 1288 1268 1355">d. Field engineer equipment specially designed for use in a combat zone;</p> <p data-bbox="499 1370 1268 1438">e. “Robots”, “robot” controllers and “robot” “end-effectors”, having any of the following characteristics:</p> <ol data-bbox="563 1453 1268 1753" style="list-style-type: none"> <li data-bbox="563 1453 1268 1498">1. Specially designed for military use;</li> <li data-bbox="563 1514 1268 1671">2. Incorporating means of protecting hydraulic lines against externally induced punctures caused by ballistic fragments (e.g. incorporating self-sealing lines) and designed to use hydraulic fluids with flash points higher than 839 K (566°C); <u>or</u></li> <li data-bbox="563 1686 1268 1753">3. Specially designed or rated for operating in an electromagnetic pulse (EMP) environment;</li> </ol>

<i>Category Code</i>	<i>Item Description</i>
	<p data-bbox="630 454 810 488"><u>Technical Note</u></p> <p data-bbox="630 499 1262 629"><i>Electromagnetic pulse does not refer to unintentional interference caused by electromagnetic radiation from nearby equipment (e.g. machinery, appliances or electronics) or lightning.</i></p> <p data-bbox="502 645 1262 741">f. “Libraries” specially designed or modified for military use with systems, equipment or components, specified in this Division;</p> <p data-bbox="502 763 1262 898">g. Nuclear power generating equipment or propulsion equipment, including “nuclear reactors”, specially designed for military use and components therefor specially designed or ‘modified’ for military use;</p> <p data-bbox="502 920 1262 1010">h. Equipment and material, coated or treated for signature suppression, specially designed for military use, other than those specified elsewhere in this Division;</p> <p data-bbox="502 1032 1262 1099">i. Simulators specially designed for military “nuclear reactors”;</p> <p data-bbox="502 1122 1262 1189">j. Mobile repair shops specially designed or ‘modified’ to service military equipment;</p> <p data-bbox="502 1211 1262 1279">k. Field generators specially designed or ‘modified’ for military use;</p> <p data-bbox="502 1301 1262 1368">l. Containers specially designed or ‘modified’ for military use;</p> <p data-bbox="502 1391 1262 1458">m. Ferries, other than those specified elsewhere in this Division, bridges and pontoons, specially designed for military use;</p> <p data-bbox="502 1480 1262 1570">n. Test models specially designed for the “development” of items specified in Category Code ML4, ML6, ML9 or ML10;</p> <p data-bbox="502 1592 1262 1659">o. Laser protection equipment (e.g. eye and sensor protection) specially designed for military use;</p> <p data-bbox="502 1682 1262 1771">p. “Fuel cells”, other than those specified elsewhere in any part of this Division, specially designed or ‘modified’ for military use.</p> <p data-bbox="502 1794 699 1827"><u>Technical Notes</u></p> <p data-bbox="502 1839 683 1872">1. <i>Not used.</i></p>

<i>Category Code</i>	<i>Item Description</i>
ML18	<p data-bbox="499 454 1260 622">2. For the purpose of Category Code ML17, ‘modified’ means any structural, electrical, mechanical, or other change that provides a non-military item with military capabilities equivalent to an item which is specially designed for military use.</p> <p data-bbox="499 689 1129 723">‘Production’ equipment and components, as follows:</p> <p data-bbox="499 741 1260 987">a. Specially designed or modified ‘production’ equipment for the ‘production’ of products specified in this Division, and specially designed components therefor;</p> <p data-bbox="499 857 1260 987">b. Specially designed environmental test facilities and specially designed equipment therefor, for the certification, qualification or testing of products specified in this Division.</p> <p data-bbox="499 1010 687 1043"><u>Technical Note</u></p> <p data-bbox="499 1055 1260 1144">For the purpose of Category Code ML18, the term ‘production’ includes design, examination, manufacture, testing and checking.</p> <p data-bbox="499 1167 560 1200"><u>Note</u></p> <p data-bbox="499 1211 1260 1279">Category Codes ML18.a. and ML18.b. include the following equipment:</p> <p data-bbox="499 1290 1260 1886">a. Continuous nitrators;</p> <p data-bbox="499 1339 1260 1626">b. Centrifugal testing apparatus or equipment, having any of the following:</p> <ol data-bbox="563 1424 1260 1626" style="list-style-type: none"> <li>1. Driven by a motor or motors having a total rated horsepower of more than 298 kW (400 hp);</li> <li>2. Capable of carrying a payload of 113 kg or more; <u>or</u></li> <li>3. Capable of exerting a centrifugal acceleration of 8 g or more on a payload of 91 kg or more;</li> </ol> <p data-bbox="499 1637 823 1671">c. Dehydration presses;</p> <p data-bbox="499 1693 1260 1760">d. Screw extruders specially designed or modified for military explosive extrusion;</p> <p data-bbox="499 1771 1230 1805">e. Cutting machines for the sizing of extruded propellants;</p> <p data-bbox="499 1816 1260 1886">f. Sweetie barrels (tumblers) 1.85 m or more in diameter and having over 227 kg product capacity;</p>

<i>Category Code</i>	<i>Item Description</i>
	<ul style="list-style-type: none"> <li><i>g. Continuous mixers for solid propellants;</i></li> <li><i>h. Fluid energy mills for grinding or milling the ingredients of military explosives;</i></li> <li><i>i. Equipment to achieve both sphericity and uniform particle size in metal powder listed in Category Code ML8.c.8.;</i></li> <li><i>j. Convection current converters for the conversion of materials listed in Category Code ML8.c.3.</i></li> </ul>
ML19	<p>Directed Energy Weapon (DEW) systems, related or countermeasure equipment and test models, as follows, and specially designed components therefor:</p> <ul style="list-style-type: none"> <li>a. “Laser” systems specially designed for destruction or effecting mission-abort of a target;</li> <li>b. Particle beam systems capable of destruction or effecting mission-abort of a target;</li> <li>c. High power Radio-Frequency (RF) systems capable of destruction or effecting mission-abort of a target;</li> <li>d. Equipment specially designed for the detection or identification of, or defence against, systems specified in Category Codes ML19.a. to ML19.c.;</li> <li>e. Physical test models for the systems, equipment and components, specified in Category Code ML19;</li> <li>f. “Laser” systems specially designed to cause permanent blindness to unenhanced vision, i.e. to the naked eye or to the eye with corrective eyesight devices.</li> </ul> <p><u>Note 1</u></p> <p><i>DEW systems specified in Category Code ML19 include systems whose capability is derived from the controlled application of:</i></p> <ul style="list-style-type: none"> <li><i>a. “Lasers” of sufficient power to effect destruction similar to the manner of conventional ammunition;</i></li> <li><i>b. Particle accelerators which project a charged or neutral particle beam with destructive power;</i></li> </ul>



<i>Category Code</i>	<i>Item Description</i>
	<p data-bbox="501 454 1262 584">c. <i>High pulsed power or high average power radio frequency beam transmitters, which produce fields sufficiently intense to disable electronic circuitry at a distant target.</i></p> <p data-bbox="501 607 584 636"><i>Note 2</i></p> <p data-bbox="501 647 1262 712"><i>Category Code ML19 includes the following when specially designed for DEW systems:</i></p> <p data-bbox="501 730 1262 795">a. <i>Prime power generation, energy storage, switching, power conditioning or fuel-handling equipment;</i></p> <p data-bbox="501 813 1027 842">b. <i>Target acquisition or tracking systems;</i></p> <p data-bbox="501 860 1262 925">c. <i>Systems capable of assessing target damage, destruction or mission-abort;</i></p> <p data-bbox="501 943 1187 972">d. <i>Beam-handling, propagation or pointing equipment;</i></p> <p data-bbox="501 990 1262 1055">e. <i>Equipment with rapid beam slew capability for rapid multiple target operations;</i></p> <p data-bbox="501 1072 1034 1102">f. <i>Adaptive optics and phase conjugators;</i></p> <p data-bbox="501 1120 1174 1149">g. <i>Current injectors for negative hydrogen ion beams;</i></p> <p data-bbox="501 1167 1086 1196">h. <i>“Space-qualified” accelerator components;</i></p> <p data-bbox="501 1214 1054 1243">i. <i>Negative ion beam funnelling equipment;</i></p> <p data-bbox="501 1261 1262 1326">j. <i>Equipment for controlling and slewing a high energy ion beam;</i></p> <p data-bbox="501 1344 1262 1408">k. <i>“Space-qualified” foils for neutralising negative hydrogen isotope beams.</i></p>
ML20	<p data-bbox="501 1496 1262 1561">Cryogenic and “superconductive” equipment, as follows, and specially designed components and accessories therefor:</p> <p data-bbox="501 1579 1262 1736">a. <i>Equipment specially designed or configured to be installed in a vehicle for military ground, marine, airborne or space applications, capable of operating while in motion and of producing or maintaining temperatures below 103 K (-170°C);</i></p>

<i>Category Code</i>	<i>Item Description</i>
ML21	<p data-bbox="564 456 624 488"><u>Note</u></p> <p data-bbox="564 499 1262 663"><i>Category Code ML20.a. includes mobile systems incorporating or employing accessories or components manufactured from non-metallic or non-electrical conductive materials, such as plastics or epoxy-impregnated materials.</i></p> <p data-bbox="501 680 1262 844">b. “Superconductive” electrical equipment (rotating machinery and transformers) specially designed or configured to be installed in a vehicle for military ground, marine, airborne or space applications and capable of operating while in motion.</p> <p data-bbox="564 864 624 896"><u>Note</u></p> <p data-bbox="564 907 1262 1106"><i>Category Code ML20.b. does not apply to direct-current hybrid homopolar generators that have single-pole normal metal armatures which rotate in a magnetic field produced by superconducting windings, provided those windings are the only superconducting components in the generator.</i></p> <p data-bbox="501 1173 770 1205">“Software” as follows:</p> <p data-bbox="501 1225 1262 1285">a. “Software” specially designed or modified for any of the following:</p> <ol data-bbox="564 1305 1262 1541" style="list-style-type: none"> <li data-bbox="564 1305 1262 1366">1. “Development”, “production”, operation or maintenance of equipment specified in this Division;</li> <li data-bbox="564 1388 1262 1449">2. “Development” or “production” of materials specified in this Division; <u>or</u></li> <li data-bbox="564 1471 1262 1532">3. “Development”, “production”, operation or maintenance of “software” specified in this Division;</li> </ol> <p data-bbox="501 1554 1262 1615">b. Specific “software”, other than that specified in Category Code ML21.a., as follows:</p> <ol data-bbox="564 1635 1262 1850" style="list-style-type: none"> <li data-bbox="564 1635 1262 1733">1. “Software” specially designed for military use and specially designed for modelling, simulating or evaluating military weapon systems;</li> <li data-bbox="564 1756 1262 1850">2. “Software” specially designed for military use and specially designed for modelling or simulating military operational scenarios;</li> </ol>

<i>Category Code</i>	<i>Item Description</i>
ML22	<p>3. “Software” for determining the effects of conventional, nuclear, chemical or biological weapons;</p> <p>4. “Software” specially designed for military use and specially designed for Command, Communications, Control and Intelligence (C<sup>3</sup>I) or Command, Communications, Control, Computer and Intelligence (C<sup>4</sup>I) applications;</p> <p>c. “Software”, not specified in Category Code ML21.a. or ML21.b., specially designed or modified to enable equipment not specified in this Division to perform the military functions of equipment specified in this Division.</p> <p>“Technology” as follows:</p> <p>a. “Technology”, other than specified in Category Code ML22.b., which is “required” for the “development”, “production”, operation, installation, maintenance (checking), repair, overhaul or refurbishing of items specified in this Division;</p> <p>b. “Technology” as follows:</p> <ol style="list-style-type: none"> <li>1. “Technology” “required” for the design of, the assembly of components into, and the operation, maintenance and repair of, complete production installations for items specified in this Division, even if the components of such production installations are not specified;</li> <li>2. “Technology” “required” for the “development” and “production” of small arms, even if used to produce reproductions of antique small arms;</li> <li>3. Not used;</li> </ol> <p><u>N.B.</u> See Category Code ML22.a. for “technology” previously specified by Category Code ML22.b.3.</p> <ol style="list-style-type: none"> <li>4. Not used;</li> </ol>

<i>Category Code</i>	<i>Item Description</i>
	<p><u><i>N.B.</i></u>  <i>See Category Code ML22.a. for “technology” previously specified by Category Code ML22.b.4.</i></p> <p>5. “Technology” “required” exclusively for the incorporation of “biocatalysts”, specified in Category Code ML7.i.1., into military carrier substances or military material.</p> <p><u><i>Note 1</i></u>  <i>“Technology” “required” for the “development”, “production”, operation, installation, maintenance (checking), repair, overhaul or refurbishing of items specified in this Division is considered to fall within Category Code ML22 even when applicable to any goods which are not specified in this Division.</i></p> <p><u><i>Note 2</i></u>  <i>Category Code ML22 does not include “technology” for magnetic induction for continuous propulsion of civil transport devices.</i></p>

## PART II

DUAL-USE GOODS THE EXPORT, TRANSHIPMENT OR BRINGING IN TRANSIT OF WHICH, AND TECHNOLOGY THE EXPORT OR TRANSMISSION OF WHICH, REQUIRE A PERMIT

*Division 1 — Preliminary Provisions*

*Subdivision 1 — General Notes*

1. Non-controlled goods (including plant) containing one or more controlled components set out in Division 2 shall be considered as being controlled goods within Division 2 if the controlled components are the principal element of the non-controlled goods and can feasibly be removed or used for other purposes.
2. In determining whether goods are to be considered the principal element of other goods for the purposes of paragraph 1, factors such as the quantity, value and technological know-how involved and other special circumstances which might establish the goods as the principal element of the other goods must be weighed.
3. Goods specified in Division 2 include both new and used goods.

- 
- 
4. Chemicals in Division 2 are listed by name and CAS number. Chemicals of the same structural formula (including hydrates) as chemicals listed in Division 2 are to be considered as coming within the descriptions of the second-mentioned chemicals regardless of name or CAS number. CAS numbers are shown in order to assist in identifying whether a particular chemical or mixture is a chemical within Division 2, irrespective of nomenclature. CAS numbers are not intended to be used as unique identifiers because some forms of the listed chemical have different CAS numbers, and mixtures containing a listed chemical may also have different CAS numbers.

*Subdivision 2 — Nuclear Technology Note (NTN)*

*(To be read in conjunction with section E of Category 0.)*

5. “Technology” for the “development”, “production” or “use” of goods specified in Category 0 are considered to be “technology” under section E of that Category even when applicable to goods not so specified.

*Subdivision 3 — General Technology Note (GTN)*

*(To be read in conjunction with section E of Categories 1 to 9.)*

6. “Technology” under section E of Categories 1 to 9 is “technology” which is “required” for the “development”, “production” or “use” of goods specified in those Categories.

“Technology” for the “development”, “production” or “use” of goods specified in Categories 1 to 9 are considered to be “technology” under section E of those Categories even when applicable to goods not so specified.

*Subdivision 4 — General Software Note (GSN)*

7. Categories 0 to 9 of Division 2 do not include “software” which is any of the following:
- a. Generally available to the public by being:
    1. Sold from stock at retail selling points, without restriction, by means of:
      - a. Over-the-counter transactions;
      - b. Mail order transactions;
      - c. Electronic transactions; or
      - d. Telephone order transactions; and
    2. Designed for installation by the user without further substantial support by the supplier; or

- b. The minimum necessary “object code” for the installation, operation, maintenance (checking) or repair of those items whose export has been authorised.

*Note*

*Paragraph 7 does not extend to “software” specified in Category 5 — Part 2 (“Information Security”).*

*Subdivision 5 — Definitions of Words and Expressions in this Part*

8. In this Part, words and expressions in quotation marks (“ ”) take the definitions set out against them in this paragraph:

“accuracy” (Categories 2, 6), usually measured in terms of inaccuracy, means the maximum deviation, positive or negative, of an indicated value from an accepted standard or true value;

“active flight control systems” (Category 7) means systems that function to prevent undesirable “aircraft” and missile motions or structural loads by autonomously processing outputs from multiple sensors and then providing the necessary preventive commands to effect automatic control;

“active pixel” (Categories 6, 8) means a minimum (single) element of the solid state array which has a photoelectric transfer function when exposed to light (electromagnetic) radiation;

“adapted for use in war” (Category 1) means any modification or selection (such as altering purity, shelf life, virulence, dissemination characteristics, or resistance to UV radiation) designed to increase the effectiveness in producing casualties in humans or animals, degrading equipment or damaging crops or the environment;

“adjusted peak performance” (Category 4) means an adjusted peak rate at which “digital computers” perform 64-bit or larger floating point additions and multiplications, and is expressed in Weighted TeraFLOPS (WT) with units of  $10^{12}$  adjusted floating point operations per second;

*N.B.*

*See Category 4, Technical Note.*

“aircraft” (Categories 1, 7, 9) means a fixed wing, swivel wing, rotary wing (helicopter), tilt rotor or tilt-wing airborne vehicle;

*N.B.*

*See also “civil aircraft”.*

“airship” (Category 9) means a power-driven airborne vehicle that is kept buoyant by a body of gas (usually helium, formerly hydrogen) which is lighter than air;

---

“all compensations available” (Category 2) means after all feasible measures available to the manufacturer to minimise all systematic positioning errors for the particular machine-tool model or measuring errors for the particular coordinate measuring machine are considered;

“allocated by the ITU” (Categories 3, 5) means the allocation of frequency bands according to the current edition of the ITU Radio Regulations for primary, permitted and secondary services;

*Note*

*Additional and alternative allocations are not included.*

“angle random walk” (Category 7) means the angular error build-up with time that is due to white noise in angular rate (IEEE STD 528-2001);

“angular position deviation” (Category 2) means the maximum difference between angular position and the actual, very accurately measured angular position after the workpiece mount of the table has been turned out of its initial position;

“APP” (Category 4) is equivalent to “Adjusted Peak Performance”;

“asymmetric algorithm” (Category 5) means a cryptographic algorithm using different, mathematically-related keys for encryption and decryption;

*Note*

*A common use of “asymmetric algorithms” is key management.*

“automatic target tracking” (Category 6) means a processing technique that automatically determines and provides as output an extrapolated value of the most probable position of the target in real time;

“average output power” (Category 6) means the total “laser” output energy, in joules, divided by the period over which a series of consecutive pulses is emitted, in seconds. For a series of uniformly spaced pulses it is equal to the total “laser” output energy in a single pulse, in joules, multiplied by the pulse frequency of the “laser”, in Hertz;

“basic gate propagation delay time” (Category 3) means the propagation delay time value corresponding to the basic gate used in a “monolithic integrated circuit”. For a ‘family’ of “monolithic integrated circuits”, this may be specified either as the propagation delay time per typical gate within the given ‘family’ or as the typical propagation delay time per gate within the given ‘family’;

*Note 1*

*“Basic gate propagation delay time” is not to be confused with the input or output delay time of a complex “monolithic integrated circuit”.*

---

---

*Note 2*

*'Family' consists of all integrated circuits to which all of the following are applied as their manufacturing methodology and specifications except their respective functions:*

- a. The common hardware and software architecture;*
- b. The common design and process technology; and*
- c. The common basic characteristics.*

“bias” (accelerometer) (Category 7) means the average over a specified time of accelerometer output, measured at specified operating conditions, that has no correlation with input acceleration or rotation. “Bias” is expressed in grams or in metres per second squared (g or m/s<sup>2</sup>). (Ref. IEEE Std 528-2001) (Micro g equals  $1 \times 10^{-6}$  g);

“bias” (gyro) (Category 7) means the average over a specified time of gyro output measured at specified operating conditions that has no correlation with input rotation or acceleration. “Bias” is typically expressed in degrees per hour (deg/hr). (Ref. IEEE Std 528-2001);

“camming” (Category 2) means axial displacement in one revolution of the main spindle measured in a plane perpendicular to the spindle faceplate, at a point next to the circumference of the spindle faceplate (Ref. ISO 230/1 1986, paragraph 5.63);

“carbon fibre preforms” (Category 1) means an ordered arrangement of uncoated or coated fibres intended to constitute a framework of a part before the “matrix” is introduced to form a “composite”;

“CEP” (circle of equal probability) (Category 7) means a measure of accuracy; the radius of the circle centred at the target, at a specific range, in which 50% of the payloads impact;

“chemical laser” (Category 6) means a “laser” in which the excited species is produced by the output energy from a chemical reaction;

“chemical mixture” (Category 1) means a solid, liquid or gaseous product made up of two or more components which do not react together under the conditions under which the mixture is stored;

“circulation-controlled anti-torque or circulation-controlled direction control systems” (Category 7) means systems that use air blown over aerodynamic surfaces to increase or control the forces generated by the surfaces;

“civil aircraft” (Categories 1, 3, 4, 7) means an “aircraft” listed by designation in published airworthiness certification lists by the civil aviation authorities to fly commercial civil internal and external routes or for legitimate civil, private or business use;



---

---

N.B.

*See also "aircraft".*

“commingled” (Category 1) means filament to filament blending of thermoplastic fibres and reinforcement fibres in order to produce a fibre reinforcement “matrix” mix in total fibre form;

“comminution” (Category 1) means a process to reduce a material to particles by crushing or grinding;

“communications channel controller” (Category 4) means the physical interface which controls the flow of synchronous or asynchronous digital information. It is an assembly that can be integrated into computer or telecommunications equipment to provide communications access;

“compensation systems” (Category 6) means systems which consist of the primary scalar sensor, one or more reference sensors (e.g. vector magnetometers) together with software that permit reduction of rigid body rotation noise of the platform;

“composite” (Categories 1, 2, 6, 8, 9) means a “matrix” and an additional phase or additional phases consisting of particles, whiskers, fibres or any combination thereof, present for a specific purpose or purposes;

“compound rotary table” (Category 2) means a table allowing the workpiece to rotate and tilt about two non-parallel axes, which can be coordinated simultaneously for “contouring control”;

“III/V compounds” (Categories 3, 6) means polycrystalline or binary or complex monocrystalline products consisting of elements of groups IIIA and VA of Mendeleev’s periodic classification table (e.g. gallium arsenide, gallium-aluminium arsenide, indium phosphide);

“contouring control” (Category 2) means two or more “numerically controlled” motions operating in accordance with instructions that specify the next required position and the required feed rates to that position. These feed rates are varied in relation to each other so that a desired contour is generated (Ref. ISO/DIS 2806-1980);

“critical temperature” (Categories 1, 3, 5) (sometimes referred to as the transition temperature) of a specific “superconductive” material means the temperature at which the material loses all resistance to the flow of direct electrical current;

“cryptographic activation” (Category 5) means any technique that activates or enables cryptographic capability, via a secure mechanism that is implemented by the manufacturer of the item and is uniquely bound to the item or customer for which the cryptographic capability is being activated or enabled (e.g. a serial number-based licence key or an authentication instrument such as a digitally signed certificate);

---

---

Technical Note

*“cryptographic activation” techniques and mechanisms may be implemented as hardware, “software” or “technology”.*

“cryptography” (Category 5) means the discipline which embodies principles, means and methods for the transformation of data in order to hide its information content, prevent its undetected modification or prevent its unauthorised use. “Cryptography” is limited to the transformation of information using one or more ‘secret parameters’ (e.g. crypto variables) or associated key management;

Note

*“Cryptography” does not include “fixed” data compression or coding techniques.*

Technical Note

*‘Secret parameter’ means a constant or key kept from the knowledge of others or shared only within a group.*

“CW laser” (Category 6) means a “laser” that produces a nominally constant output energy for greater than 0.25 seconds;

“Data-Based Referenced Navigation” (“DBRN”) (Category 7) Systems means systems which use various sources of previously measured geo-mapping data integrated to provide accurate navigation information under dynamic conditions. Data sources include bathymetric maps, stellar maps, gravity maps, magnetic maps or 3-D digital terrain maps;

“deformable mirrors” (Category 6) (also known as adaptive optic mirrors) means mirrors having:

- a. A single continuous optical reflecting surface which is dynamically deformed by the application of individual torques or forces to compensate for distortions in the optical waveform incident upon the mirror; or
- b. Multiple optical reflecting elements that can be individually and dynamically repositioned by the application of torques or forces to compensate for distortions in the optical waveform incident upon the mirror;

“depleted uranium” (Category 0) means uranium depleted in the isotope 235 below that occurring in nature;

“development” (GTN, NTN, All Categories) has the same meaning as in the Act;

---

“diffusion bonding” (Categories 1, 2, 9) means a solid state joining of at least two separate pieces of metals into a single piece with a joint strength equivalent to that of the weakest material, wherein the principal mechanism is interdiffusion of atoms across the interface;

“digital computer” (Categories 4, 5) means equipment which can, in the form of one or more discrete variables, perform all of the following:

- a. Accept data;
- b. Store data or instructions in fixed or alterable (writable) storage devices;
- c. Process data by means of a stored sequence of instructions which is modifiable; and
- d. Provide output of data;

*Note*

*Modifications of a stored sequence of instructions include replacement of fixed storage devices, but not a physical change in wiring or inter-connections.*

“digital transfer rate” (Category 5) means the total bit rate of the information that is directly transferred on any type of medium;

*N.B.*

*See also “total digital transfer rate”.*

“direct-acting hydraulic pressing” (Category 2) means a deformation process which uses a fluid-filled flexible bladder in direct contact with the workpiece;

“drift rate” (gyro) (Category 7) means the component of gyro output that is functionally independent of input rotation. It is expressed as an angular rate. (IEEE STD 528-2001);

“effective gramme” (Categories 0, 1) of “special fissile material” means:

- a. For plutonium isotopes and uranium-233, the isotope weight in grammes;
- b. For uranium enriched 1 per cent or greater in the isotope uranium-235, the element weight in grammes multiplied by the square of its enrichment expressed as a decimal weight fraction;
- c. For uranium enriched below 1 per cent in the isotope uranium-235, the element weight in grammes multiplied by 0.0001;

---

“electronic assembly” (Categories 2, 3, 4, 5) means a number of electronic components (i.e. ‘circuit elements’, ‘discrete components’, integrated circuits, etc.) connected together to perform one or more specific functions, replaceable as an entity and normally capable of being disassembled;

Note 1

*‘Circuit element’ means a single active or passive functional part of an electronic circuit, such as one diode, one transistor, one resistor, one capacitor, etc.*

Note 2

*‘Discrete component’ means a separately packaged ‘circuit element’ with its own external connections.*

“electronically steerable phased array antenna” (Categories 5, 6) means an antenna which forms a beam by means of phase coupling, i.e. the beam direction is controlled by the complex excitation coefficients of the radiating elements and the direction of that beam can be varied in azimuth or in elevation, or both, by application, both in transmission and reception, of an electrical signal;

“energetic materials” (Category 1) means substances or mixtures that react chemically to release energy required for their intended application. “Explosives”, ‘pyrotechnics’ and ‘propellants’ are subclasses of energetic materials;

Technical Note 1

*‘Pyrotechnics’ means mixtures of solid or liquid fuels and oxidisers which, when ignited, undergo an energetic chemical reaction at a controlled rate intended to produce specific time delays, or quantities of heat, noise, smoke, visible light or infrared radiation. Pyrophorics are a subclass of ‘pyrotechnics’, which contain no oxidisers but ignite spontaneously on contact with air.*

Technical Note 2

*‘Propellants’ means substances or mixtures that react chemically to produce large volumes of hot gases at controlled rates to perform mechanical work.*

“end-effectors” (Category 2) means grippers, ‘active tooling units’ and any other tooling that is attached to the baseplate on the end of a “robot” manipulator arm;

Note

*‘Active tooling unit’ means a device for applying motive power, process energy or sensing to the workpiece.*

---

“equivalent density” (Category 6) means the mass of an optic per unit optical area projected onto the optical surface;

“explosives” (Category 1) means solid, liquid or gaseous substances or mixtures of substances which, in their application as primary, booster, or main charges in warheads, demolition and other applications, are required to detonate;

“FADEC Systems” (Categories 7, 9) means Full Authority Digital Engine Control Systems – A digital electronic control system for a gas turbine engine that is able to autonomously control the engine throughout its whole operating range from demanded engine start until demanded engine shut-down, in both normal and fault conditions;

“fibrous or filamentary materials” (Categories 0, 1, 8) includes:

- a. Continuous “monofilaments”;
- b. Continuous “yarns” and “rovings”;
- c. “Tapes”, fabrics, random mats and braids;
- d. Chopped fibres, staple fibres and coherent fibre blankets;
- e. Whiskers, either monocrystalline or polycrystalline, of any length;
- f. Aromatic polyamide pulp;

“film type integrated circuit” (Category 3) means an array of ‘circuit elements’ and metallic interconnections formed by deposition of a thick or thin film on an insulating “substrate”;

*Note*

*‘Circuit element’ means a single active or passive functional part of an electronic circuit, such as one diode, one transistor, one resistor, one capacitor, etc.*

“fixed” (Category 5) means the coding or compression algorithm cannot accept externally supplied parameters (e.g. cryptographic or key variables) and cannot be modified by the user;

“flight control optical sensor array” (Category 7) means a network of distributed optical sensors, using “laser” beams, to provide real-time flight control data for on-board processing;

“flight path optimisation” (Category 7) means a procedure that minimises deviations from a four-dimensional (space and time) desired trajectory based on maximising performance or effectiveness for mission tasks;

“focal plane array” (Category 6) means a linear or two-dimensional planar layer, or combination of planar layers, of individual detector elements, with or without readout electronics, which work in the focal plane;

---

---

*Note*

*“Focal plane array” does not include a stack of single detector elements or any two, three or four element detectors provided time delay and integration is not performed within the element.*

“fractional bandwidth” (Categories 3, 5) means the “instantaneous bandwidth” divided by the centre frequency, expressed as a percentage;

“frequency hopping” (Category 5) means a form of “spread spectrum” in which the transmission frequency of a single communication channel is made to change by a random or pseudo-random sequence of discrete steps;

“frequency mask trigger” (Category 3) for “signal analysers” means a mechanism where the trigger function is able to select a frequency range to be triggered on as a subset of the acquisition bandwidth while ignoring other signals that may also be present within the same acquisition bandwidth. A “frequency mask trigger” may contain more than one independent set of limits;

“frequency switching time” (Category 3) means the time (i.e. delay) taken by a signal when switched from an initial specified output frequency, to arrive at or within  $\pm 0.05\%$  of a final specified output frequency. Items having a specified frequency range of less than  $\pm 0.05\%$  around their centre frequency are defined to be incapable of frequency switching;

“frequency synthesiser” (Category 3) means any kind of frequency source, regardless of the actual technique used, providing a multiplicity of simultaneous or alternative output frequencies, from one or more outputs, controlled by, derived from or disciplined by a lesser number of standard (or master) frequencies;

“fuel cell” (Category 8) means an electrochemical device that converts chemical energy directly into Direct Current (DC) electricity by consuming fuel from an external source;

“fusible” (Category 1) means capable of being cross-linked or polymerised further (cured) by the use of heat, radiation, catalysts, etc., or that can be melted without pyrolysis (charring);

“gas atomisation” (Category 1) means a process to reduce a molten stream of metal alloy to droplets of 500 micrometre diameter or less by a high pressure gas stream;

“geographically dispersed” (Category 6) means a state where each location is distant from any other more than 1,500 m in any direction. Mobile sensors are always considered “geographically dispersed”;

---

“guidance set” (Category 7) means systems that integrate the process of measuring and computing a vehicle’s position and velocity (i.e. navigation) with that of computing and sending commands to the vehicle’s flight control systems to correct the trajectory;

“hot isostatic densification” (Category 2) means the process of pressurising a casting at temperatures exceeding 375 K (102°C) in a closed cavity through various media (gas, liquid, solid particles, etc.) to create equal force in all directions to reduce or eliminate internal voids in the casting;

“hybrid integrated circuit” (Category 3) means any combination of integrated circuit or circuits, or integrated circuit with ‘circuit elements’ or ‘discrete components’ connected together to perform one or more specific functions, and having all of the following characteristics:

- a. Containing at least one unencapsulated device;
- b. Connected together using typical IC production methods;
- c. Replaceable as an entity; and
- d. Not normally capable of being disassembled;

Note 1

*‘Circuit element’ means a single active or passive functional part of an electronic circuit, such as one diode, one transistor, one resistor, one capacitor, etc.*

Note 2

*‘Discrete component’ means a separately packaged ‘circuit element’ with its own external connections.*

“image enhancement” (Category 4) means the processing of externally derived information-bearing images by algorithms such as time compression, filtering, extraction, selection, correlation, convolution or transformations between domains (e.g. fast Fourier transform or Walsh transform). This does not include algorithms using only linear or rotational transformation of a single image, such as translation, feature extraction, registration or false coloration;

“immunotoxin” (Category 1) means a conjugate of one cell specific monoclonal antibody and a “toxin” or “sub-unit of toxin”, that selectively affects diseased cells;

“information security” (Categories 4, 5) means all the means and functions ensuring the accessibility, confidentiality or integrity of information or communications, excluding the means and functions intended to safeguard against malfunctions. “Information security” includes “cryptography”, “cryptographic activation”, ‘cryptanalysis’, protection against compromising emanations and computer security;

*Note*

*‘Cryptanalysis’ means analysis of a cryptographic system or its inputs and outputs to derive confidential variables or sensitive data, including clear text.*

“instantaneous bandwidth” (Categories 3, 5) means the bandwidth over which output power remains constant within 3 dB without adjustment of other operating parameters;

“instrumented range” (Category 6) means the specified unambiguous display range of a radar;

“insulation” (Category 9) means insulation that is applied to the components of a rocket motor, i.e. the case, nozzle, inlets, case closures, and includes cured or semi-cured compounded rubber sheet stock containing an insulating or refractory material. It may also be incorporated as stress relief boots or flaps;

“interior lining” (Category 9) means interior lining that is suited for the bond interface between the solid propellant and the case or insulating liner, and is usually a liquid polymer based dispersion of refractory or insulating materials, e.g. carbon filled hydroxyl terminated polybutadiene (HTPB) or other polymer with added curing agents sprayed or screeded over a case interior;

“intrinsic magnetic gradiometer” (Category 6) means a single magnetic field gradient sensing element and associated electronics the output of which is a measure of magnetic field gradient;

*N.B.*

*See also “magnetic gradiometer”.*

“intrusion software” (Category 4) means “software” specially designed or modified to avoid detection by ‘monitoring tools’, or to defeat ‘protective countermeasures’, of a computer or network-capable device, and performing any of the following:

- a. The extraction of data or information, from a computer or network-capable device, or the modification of system or user data; or
- b. The modification of the standard execution path of a program or process in order to allow the execution of externally provided instructions;



Note 1

*“Intrusion software” does not include any of the following:*

- a. *Hypervisors, debuggers or Software Reverse Engineering (SRE) tools;*
- b. *Digital Rights Management (DRM) “software”; or*
- c. *“Software” designed to be installed by manufacturers, administrators or users, for the purposes of asset tracking or recovery.*

Note 2

*Network-capable devices include mobile devices and smart meters.*

Technical Notes

1. *‘Monitoring tools’ means “software” or hardware devices, that monitor system behaviours or processes running on a device. This includes antivirus (AV) products, end point security products, Personal Security Products (PSP), Intrusion Detection Systems (IDS), Intrusion Prevention Systems (IPS) or firewalls.*
2. *‘Protective countermeasures’ means techniques designed to ensure the safe execution of code, such as Data Execution Prevention (DEP), Address Space Layout Randomisation (ASLR) or sandboxing.*

*“isolated live cultures” (Category 1) includes live cultures in dormant form and in dried preparations;*

*“isostatic presses” (Category 2) means equipment capable of pressurising a closed cavity through various media (e.g. gas, liquid, solid particles, etc.) to create equal pressure in all directions within the cavity upon a workpiece or material;*

*“laser” (Categories 0, 2, 3, 5, 6, 7, 8, 9) means an assembly of components which produce both spatially and temporally coherent light that is amplified by stimulated emission of radiation;*

N.B.

*See also:*

*“Chemical laser”;*

*“Super High Power Laser”;*

*“Transfer laser”.*

“lighter-than-air vehicles” (Category 9) means balloons and airships that rely on hot air or other lighter-than-air gases such as helium or hydrogen for their lift;

“linearity” (Category 2) (usually measured in terms of non-linearity) means the maximum deviation of the actual characteristic (average of upscale and downscale readings), positive or negative, from a straight line so positioned as to equalise and minimise the maximum deviations;

“local area network” (Categories 4, 5) means a data communication system having all of the following characteristics:

- a. Allows an arbitrary number of independent ‘data devices’ to communicate directly with each other; and
- b. Is confined to a geographical area of moderate size (e.g. office building, plant, campus, warehouse);

Note

*‘Data device’ means equipment capable of transmitting or receiving sequences of digital information.*

“magnetic gradiometers” (Category 6) means instruments designed to detect the spatial variation of magnetic fields from sources external to the instrument. They consist of multiple “magnetometers” and associated electronics the output of which is a measure of magnetic field gradient;

N.B.

*See also “intrinsic magnetic gradiometer”.*

“magnetometers” (Category 6) means instruments designed to detect magnetic fields from sources external to the instrument. They consist of a single magnetic field sensing element and associated electronics the output of which is a measure of the magnetic field;

“main storage” (Category 4) means the primary storage for data or instructions for rapid access by a central processing unit. It consists of the internal storage of a “digital computer” and any hierarchical extension thereto, such as cache storage or non-sequentially accessed extended storage;

“materials resistant to corrosion by UF<sub>6</sub>” (Category 0) means copper, copper alloys, stainless steel, aluminium, aluminium oxide, aluminium alloys, nickel or alloys containing 60% or more nickel by weight and fluorinated hydrocarbon polymers;

“matrix” (Categories 1, 2, 8, 9) means a substantially continuous phase that fills the space between particles, whiskers or fibres;

---

“measurement uncertainty” (Category 2) means the characteristic parameter which specifies in what range around the output value the correct value of the measurable variable lies with a confidence level of 95%. It includes the uncorrected systematic deviations, the uncorrected backlash and the random deviations (Ref. ISO 10360-2);

“mechanical alloying” (Category 1) means an alloying process resulting from the bonding, fracturing and rebonding of elemental and master alloy powders by mechanical impact. Non-metallic particles may be incorporated in the alloy by addition of the appropriate powders;

“melt extraction” (Category 1) means a process to ‘solidify rapidly’ and extract a ribbon-like alloy product by the insertion of a short segment of a rotating chilled block into a bath of a molten metal alloy;

Note

*‘Solidify rapidly’ means solidification of molten material at cooling rates exceeding 1,000 K/s.*

“melt spinning” (Category 1) means a process to ‘solidify rapidly’ a molten metal stream impinging upon a rotating chilled block, forming a flake, ribbon or rod-like product;

Note

*‘Solidify rapidly’ means solidification of molten material at cooling rates exceeding 1,000 K/s.*

“microcomputer microcircuit” (Category 3) means a “monolithic integrated circuit” or “multichip integrated circuit” containing an arithmetic logic unit (ALU) capable of executing general purpose instructions from an internal storage, on data contained in the internal storage;

Note

*The internal storage may be augmented by an external storage.*

“microprocessor microcircuit” (Category 3) means a “monolithic integrated circuit” or “multichip integrated circuit” containing an arithmetic logic unit (ALU) capable of executing a series of general purpose instructions from an external storage;

Note 1

*“Microprocessor microcircuit” normally does not contain integral user-accessible storage, although storage present on-the-chip may be used in performing its logic function.*

---

---

Note 2

*“Microprocessor microcircuit” includes chip sets which are designed to operate together to provide the function of a “microprocessor microcircuit”.*

“microorganisms” (Categories 1, 2) means bacteria, viruses, mycoplasmas, rickettsiae, chlamydiae or fungi, whether natural, enhanced or modified, either in the form of “isolated live cultures” or as material including living material which has been deliberately inoculated or contaminated with such cultures;

“missiles” (Categories 1, 3, 6, 7, 9) means complete rocket systems and unmanned aerial vehicle systems, capable of delivering at least 500 kg payload to a range of at least 300 km;

“monofilament” (Category 1) or filament means the smallest increment of fibre, usually several micrometres in diameter;

“monolithic integrated circuit” (Category 3) means a combination of passive or active ‘circuit elements’ or both which:

- a. Are formed by means of diffusion processes, implantation processes or deposition processes in or on a single semiconducting piece of material, a so-called ‘chip’;
- b. Can be considered as indivisibly associated; and
- c. Perform the function or functions of a circuit;

Note

*‘Circuit element’ means a single active or passive functional part of an electronic circuit, such as one diode, one transistor, one resistor or one capacitor, etc.*

“monospectral imaging sensors” (Category 6) means sensors capable of acquisition of imaging data from one discrete spectral band;

“multichip integrated circuit” (Category 3) means two or more “monolithic integrated circuits” bonded to a common “substrate”;

“multispectral imaging sensors” (Category 6) means sensors capable of simultaneous or serial acquisition of imaging data from two or more discrete spectral bands. Sensors having more than twenty discrete spectral bands are sometimes referred to as hyperspectral imaging sensors;

“natural uranium” (Category 0) means uranium containing the mixtures of isotopes occurring in nature;

---

“network access controller” (Category 4) means a physical interface to a distributed switching network. It uses a common medium which operates throughout at the same “digital transfer rate” using arbitration (e.g. token or carrier sense) for transmission. Independently from any other, it selects data packets or data groups (e.g. Ref. IEEE 802) addressed to it. It is an assembly that can be integrated into computer or telecommunications equipment to provide communications access;

“neural computer” (Category 4) means a computational device designed or modified to mimic the behaviour of a neuron or a collection of neurons, i.e. a computational device which is distinguished by its hardware capability to modulate the weights and numbers of the interconnections of a multiplicity of computational components based on previous data;

“nuclear reactor” (Category 0) means a complete reactor capable of operation so as to maintain a controlled self-sustaining fission chain reaction. A “nuclear reactor” includes all the items within or attached directly to the reactor vessel, the equipment which controls the level of power in the core, and the components which normally contain, come into direct contact with or control the primary coolant of the reactor core;

“numerical control” (Category 2) means the automatic control of a process performed by a device that makes use of numeric data usually introduced as the operation is in progress (Ref. ISO 2382);

“object code” (GSN) means an equipment executable form of a convenient expression of one or more processes (“source code” or source language) which has been compiled by programming system;

“Operations, Administration or Maintenance” (“OAM”) (Category 5) means performing one or more of the following tasks:

- a. Establishing or managing any of the following:
  1. Accounts or privileges of users or administrators;
  2. Settings of an item; or
  3. Authentication data in support of the tasks described in paragraphs a.1. or a.2.;
- b. Monitoring or managing the operating condition or performance of an item; or
- c. Managing logs or audit data in support of any of the tasks described in paragraphs a. or b.;

*Note*

*“OAM” does not include any of the following tasks or their associated key management functions:*

- 
- 
- a. *Provisioning or upgrading any cryptographic functionality that is not directly related to establishing or managing authentication data in support of the tasks described in paragraphs a.1. or a.2. above; or*
  - b. *Performing any cryptographic functionality on the forwarding or data plane of an item.*

“optical amplification” (Category 5) in optical communications, means an amplification technique that introduces a gain of optical signals that have been generated by a separate optical source, without conversion to electrical signals, i.e. using semiconductor optical amplifiers, optical fibre luminescent amplifiers;

“optical computer” (Category 4) means a computer designed or modified to use light to represent data and whose computational logic elements are based on directly coupled optical devices;

“optical integrated circuit” (Category 3) means a “monolithic integrated circuit” or a “hybrid integrated circuit”, containing one or more parts designed to function as a photosensor or photoemitter or to perform an optical or an electro-optical function or functions;

“optical switching” (Category 5) means the routing of or switching of signals in optical form without conversion to electrical signals;

“overall current density” (Category 3) means the total number of ampere-turns in the coil (i.e. the sum of the number of turns multiplied by the maximum current carried by each turn) divided by the total cross-section of the coil (comprising the superconducting filaments, the metallic matrix in which the superconducting filaments are embedded, the encapsulating material, any cooling channels, etc.);

“participating state” (Categories 7, 9) means a state participating in the Wassenaar Arrangement (details of which are set out in <http://www.wassenaar.org/participants/index.html>);

“peak power” (Category 6) means the highest power attained in the “pulse duration”;

“personal area network” (Category 5) means a data communication system having all of the following characteristics:

- a. Allows an arbitrary number of independent or interconnected ‘data devices’ to communicate directly with each other; and
- b. Is confined to the communication between devices within the immediate vicinity of an individual person or device controller (e.g. single room, office, or automobile and their nearby surrounding spaces);

---

---

Technical Note

*'Data device' means equipment capable of transmitting or receiving sequences of digital information.*

“power management” (Category 7) means changing the transmitted power of the altimeter signal so that received power at the “aircraft” altitude is always at the minimum necessary to determine the altitude;

“previously separated” (Category 1) means the application of any process intended to increase the concentration of the controlled isotope;

“primary flight control” (Category 7) means an “aircraft” stability or manoeuvring control using force or moment generators, i.e. aerodynamic control surfaces or propulsive thrust vectoring;

“principal element” (Category 4), as it applies in Category 4, is a “principal element” when its replacement value is more than 35% of the total value of the system of which it is an element. Element value is the price paid for the element by the manufacturer of the system, or by the system integrator. Total value is the normal international selling price to unrelated parties at the point of manufacture or consolidation of shipment;

“production” (GTN, NTN, All Categories) has the same meaning as in the Act;

“production equipment” (Categories 1, 7, 9) means tooling, templates, jigs, mandrels, moulds, dies, fixtures, alignment mechanisms, test equipment, other machinery and components therefor, limited to those specially designed or modified for “development” or for one or more phases of “production”;

“production facilities” (Categories 7, 9) means “production equipment” and specially designed software therefor integrated into installations for “development” or for one or more phases of “production”;

“program” (Categories 2, 6) means a sequence of instructions to carry out a process in, or convertible into, a form executable by an electronic computer;

“pulse compression” (Category 6) means the coding and processing of a radar signal pulse of long time duration to one of short time duration, while maintaining the benefits of high pulse energy;

“pulse duration” (Category 6) means the duration of a “laser” pulse and means the time between the half-power points on the leading edge and trailing edge of an individual pulse;

“pulsed laser” (Category 6) means a “laser” having a “pulse duration” that is less than or equal to 0.25 seconds;

“quantum cryptography” (Category 5) means a family of techniques for the establishment of shared key for “cryptography” by measuring the quantum-mechanical properties of a physical system (including those physical properties explicitly governed by quantum optics, quantum field theory or quantum electrodynamics);

“radar frequency agility” (Category 6) means any technique which changes, in a pseudo-random sequence, the carrier frequency of a pulsed radar transmitter between pulses or between groups of pulses by an amount equal to or larger than the pulse bandwidth;

“radar spread spectrum” (Category 6) means any modulation technique for spreading energy originating from a signal with a relatively narrow frequency band, over a much wider band of frequencies, by using random or pseudo-random coding;

“radiant sensitivity” (Category 6) means Radiant sensitivity (mA/W) =  $0.807 \times (\text{wavelength in nm}) \times \text{Quantum Efficiency (QE)}$ ;

*Technical Note*

*QE is usually expressed as a percentage; however, for the purposes of this formula QE is expressed as a decimal number less than one, e.g. 78% is 0.78.*

“real-time bandwidth” (Category 3) for “signal analysers” means the widest frequency range for which the analyser can continuously transform time-domain data entirely into frequency-domain results, using a Fourier or other discrete time transformation that processes every incoming time point without gaps or windowing effects that causes a reduction of measured amplitude of more than 3 dB below the actual signal amplitude, while outputting or displaying the transformed data;

“real-time processing” (Categories 2, 6, 7) means the processing of data by a computer system providing a required level of service, as a function of available resources, within a guaranteed response time, regardless of the load of the system, when stimulated by an external event;

“repeatability” (Category 7) means the closeness of agreement among repeated measurements of the same variable under the same operating conditions when changes in conditions or non-operating periods occur between measurements (Ref. IEEE STD 528-2001 (one sigma standard deviation));

“required” (GTN, Categories 1-9), as applied to “technology”, refers to only that portion of “technology” which is peculiarly responsible for achieving or extending the controlled performance levels, characteristics or functions. Such “required” “technology” may be shared by different goods;



---

“resolution” (Category 2) means the least increment of a measuring device; on digital instruments, the least significant bit. (Ref. ANSI B-89.1.12);

“riot control agent” (Category 1) means substances which, under the expected conditions of use for riot control purposes, produce rapidly in human sensory irritation or disabling physical effects which disappear within a short time following termination of exposure;

*Technical Note*

*Tear gases are a subset of “riot control agents”.*

“robot” (Categories 2, 8) means a manipulation mechanism, which may be of the continuous path or of the point-to-point variety, may use sensors, and has all the following characteristics:

- a. Is multifunctional;
- b. Is capable of positioning or orienting material, parts, tools or special devices through variable movements in three dimensional space;
- c. Incorporates three or more closed or open loop servo-devices which may include stepping motors; and
- d. Has “user-accessible programmability” by means of teach or playback method or by means of an electronic computer which may be a programmable logic controller, i.e. without mechanical intervention;

*Note*

*“Robot” does not include the following devices:*

- a. *Manipulation mechanisms which are only manually or teleoperator controllable;*
- b. *Fixed sequence manipulation mechanisms which are automated moving devices, operating according to mechanically fixed programmed motions. The program is mechanically limited by fixed stops, such as pins or cams. The sequence of motions and the selection of paths or angles are not variable or changeable by mechanical, electronic or electrical means;*

- 
- 
- c. *Mechanically controlled variable sequence manipulation mechanisms which are automated moving devices, operating according to mechanically fixed programmed motions. The program is mechanically limited by fixed, but adjustable stops, such as pins or cams. The sequence of motions and the selection of paths or angles are variable within the fixed program pattern. Variations or modifications of the program pattern (e.g. changes of pins or exchanges of cams) in one or more motion axes are accomplished only through mechanical operations;*
  - d. *Non-servo-controlled variable sequence manipulation mechanisms which are automated moving devices, operating according to mechanically fixed programmed motions. The program is variable but the sequence proceeds only by the binary signal from mechanically fixed electrical binary devices or adjustable stops;*
  - e. *Stacker cranes defined as Cartesian coordinate manipulator systems manufactured as an integral part of a vertical array of storage bins and designed to access the contents of those bins for storage or retrieval.*

“rotary atomisation” (Category 1) means a process to reduce a stream or pool of molten metal to droplets to a diameter of 500 micrometre or less by centrifugal force;

“roving” (Category 1) means a bundle (typically 12-120) of approximately parallel ‘strands’;

*Note*

*‘Strand’ means a bundle of “monofilaments” (typically over 200) arranged approximately parallel to each other.*

“run-out” (Category 2) (out-of-true running) means radial displacement in one revolution of the main spindle measured in a plane perpendicular to the spindle axis at a point on the external or internal revolving surface to be tested. (Ref. ISO 230/1 1986, paragraph 5.61);

“scale factor” (gyro or accelerometer) (Category 7) means the ratio of change in output to a change in the input intended to be measured. “Scale factor” is generally evaluated as the slope of the straight line that can be fitted by the method of least squares to input-output data obtained by varying the input cyclically over the input range;

“settling time” (Category 3) means the time required for the output to come within one-half bit of the final value when switching between any two levels of the converter;

“SHPL” is equivalent to “super high power laser”;

“signal analysers” (Category 3) means apparatus capable of measuring and displaying basic properties of the single-frequency components of multi-frequency signals;

“signal processing” (Categories 3, 4, 5, 6) means the processing of externally derived information-bearing signals by algorithms such as time compression, filtering, extraction, selection, correlation, convolution or transformations between domains (e.g. fast Fourier transform or Walsh transform);

“software” (GSN, All Categories) means a collection of one or more “programs” or ‘microprogrammes’ recorded, stored or embodied in any device;

*Technical Note*

*‘Microprogramme’ means a sequence of elementary instructions, maintained in a special storage, the execution of which is initiated by the introduction of its reference instruction into an instruction register.*

“source code” (or source language) (Categories 6, 7, 9) means a convenient expression of one or more processes which may be turned by a programming system into equipment executable form (“object code” (or object language));

“spacecraft” (Category 9) means active and passive satellites and space probes;

“space-qualified” (Categories 3, 6, 7) means designed, manufactured or qualified through successful testing, for operation at altitudes greater than 100 km above the surface of the Earth;

*Note*

*A determination that a specific item is “space-qualified” by virtue of testing does not mean that other items in the same production run or model series are “space-qualified” if not individually tested.*

“special fissile material” (Category 0) means plutonium-239, uranium-233, “uranium enriched in the isotopes 235 or 233”, and any material containing the foregoing;

“specific modulus” (Categories 0, 1, 9) means Young’s modulus in pascals, equivalent to  $N/m^2$  divided by specific weight in  $N/m^3$ , measured at a temperature of  $(296 \pm 2)$  K ( $(23 \pm 2)^\circ\text{C}$ ) and a relative humidity of  $(50 \pm 5)\%$ ;

“specific tensile strength” (Categories 0, 1, 9) means ultimate tensile strength in pascals, equivalent to  $\text{N/m}^2$  divided by specific weight in  $\text{N/m}^3$ , measured at a temperature of  $(296 \pm 2)$  K ( $(23 \pm 2)^\circ\text{C}$ ) and a relative humidity of  $(50 \pm 5)\%$ ;

“spinning mass gyros” (Category 7) means gyros which use a continually rotating mass to sense angular motion;

“splat quenching” (Category 1) means a process to ‘solidify rapidly’ a molten metal stream impinging upon a chilled block, forming a flake-like product;

*Note*

*‘Solidify rapidly’ means solidification of molten material at cooling rates exceeding 1,000 K/s.*

“spread spectrum” (Category 5) means the technique whereby energy in a relatively narrow-band communication channel is spread over a much wider energy spectrum;

“spread spectrum” radar (Category 6) – see “radar spread spectrum”;

“stability” (Category 7) means the standard deviation (1 sigma) of the variation of a particular parameter from its calibrated value measured under stable temperature conditions. It can be expressed as a function of time;

“substrate” (Category 3) means a sheet of base material with or without an interconnection pattern and on which or within which ‘discrete components’ or integrated circuits or both can be located;

*Note 1*

*‘Discrete component’ means a separately packaged ‘circuit element’ with its own external connections.*

*Note 2*

*‘Circuit element’ means a single active or passive functional part of an electronic circuit, such as one diode, one transistor, one resistor or one capacitor, etc.*

“substrate blanks” (Categories 3, 6) means monolithic compounds with dimensions suitable for the production of optical elements such as mirrors or optical windows;

“sub-unit of toxin” (Category 1) means a structurally and functionally discrete component of a whole “toxin”;

---

“superalloys” (Categories 2, 9) means nickel-, cobalt- or iron-base alloys having strengths superior to any alloys in the AISI 300 series at temperatures over 922 K (649 °C) under severe environmental and operating conditions;

“superconductive” (Categories 1, 3, 5, 6, 8) means materials, i.e. metals, alloys or compounds, which can lose all electrical resistance, i.e. which can attain infinite electrical conductivity and carry very large electrical currents without Joule heating;

*Note*

*The “superconductive” state of a material is individually characterised by a “critical temperature”, a critical magnetic field, which is a function of temperature, and a critical current density which is, however, a function of both magnetic field and temperature.*

“Super High Power Laser” (“SHPL”) (Category 6) means a “laser” capable of delivering (the total or any portion of) the output energy exceeding 1 kJ within 50 ms or having an average or CW power exceeding 20 kW;

“superplastic forming” (Categories 1, 2) means a deformation process using heat for metals that are normally characterised by low values of elongation (less than 20%) at the breaking point as determined at room temperature by conventional tensile strength testing, in order to achieve elongations during processing which are at least 2 times those values;

“symmetric algorithm” (Category 5) means a cryptographic algorithm using an identical key for both encryption and decryption;

*Note*

*A common use of “symmetric algorithms” is to safeguard confidentiality of data.*

“system tracks” (Category 6) means processed, correlated (fusion of radar target data to flight plan position) and updated aircraft flight position report available to Air Traffic Control centre controllers;

“systolic array computer” (Category 4) means a computer where the flow and modification of the data is dynamically controllable at the logic gate level by the user;

“tape” (Category 1) means a material constructed of interlaced or unidirectional “monofilaments”, ‘strands’, “rovings”, “tows”, “yarns”, etc., usually pre-impregnated with resin;

---

---

Note

*'Strand' is a bundle of "monofilaments" (typically over 200) arranged approximately parallel to each other.*

"technology" (GTN, NTN, All Categories) means information (including information comprised in such documents as specifications, blueprints, plans, manuals, models, diagrams, formulae, tables and designs) that is necessary for the "development", "production" or "use" of any goods;

"three dimensional integrated circuit" (Category 3) means a collection of semiconductor die, integrated together, and having vias passing completely through at least one die to establish interconnections between die;

"tilting spindle" (Category 2) means a tool-holding spindle which alters, during the machining process, the angular position of its centre line with respect to any other axis;

"time constant" (Category 6) means the time taken from the application of a light stimulus for the current increment to reach a value of  $1-1/e$  times the final value (i.e. 63% of the final value);

"tip shroud" (Category 9) means a stationary ring component (solid or segmented) attached to the inner surface of the engine turbine casing or a feature at the outer tip of the turbine blade, which primarily provides a gas seal between the stationary and rotating components;

"total control of flight" (Category 7) means an automated control of "aircraft" state variables and flight path to meet mission objectives responding to real-time changes in data regarding objectives, hazards or other "aircraft";

"total digital transfer rate" (Category 5) means the number of bits, including line coding, overhead and so forth per unit time passing between corresponding equipment in a digital transmission system;

N.B.

*See also "digital transfer rate".*

"tow" (Category 1) means a bundle of "monofilaments", usually approximately parallel to each other;

"toxins" (Categories 1, 2) means toxins in the form of deliberately isolated preparations or mixtures, no matter how produced, other than toxins present as contaminants of other materials such as pathological specimens, crops, foodstuffs or seed stocks of "microorganisms";

"transfer laser" (Category 6) means a "laser" in which the lasing species is excited through the transfer of energy by collision of a non-lasing atom or molecule with a lasing atom or molecule species;

“tunable” (Category 6) means the ability of a “laser” to produce a continuous output at all wavelengths over a range of several “laser” transitions. A line selectable “laser” produces discrete wavelengths within one “laser” transition and is not considered “tunable”;

“Unmanned Aerial Vehicle” (“UAV”) (Category 9) means any aircraft capable of initiating flight and sustaining controlled flight and navigation without any human presence on board;

“uranium enriched in the isotopes 235 or 233” (Category 0) means uranium containing the isotopes 235 or 233, or both, in an amount such that the abundance ratio of the sum of these isotopes to the isotope 238 is more than the ratio of the isotope 235 to the isotope 238 occurring in nature (isotopic ratio 0.71 per cent);

“use” (GTN, NTN, All Categories) has the same meaning as in the Act;

“user accessible programmability” (Category 6) means the facility allowing a user to insert, modify or replace “programs” by means other than:

- a. A physical change in wiring or interconnections; or
- b. The setting of function controls including entry of parameters;

“vaccine” (Category 1) means a medicinal product in a pharmaceutical formulation licensed by, or having marketing or clinical trial authorisation from, the regulatory authorities of either the country of manufacture or of use, which is intended to stimulate a protective immunological response in humans or animals in order to prevent disease in those to whom or to which it is administered;

“vacuum atomisation” (Category 1) means a process to reduce a molten stream of metal to droplets of a diameter of 500 micrometre or less by the rapid evolution of a dissolved gas upon exposure to a vacuum;

“variable geometry airfoils” (Category 7) means the use of trailing edge flaps or tabs, or leading edge slats or pivoted nose droop, the position of which can be controlled in flight;

“yarn” (Category 1) means a bundle of twisted ‘strands’.

Note

*‘Strand’ means a bundle of “monofilaments” (typically over 200) arranged approximately parallel to each other.*

9. In this Part, a word or expression enclosed with single quotation marks (‘’) takes the definition set out against it in the Technical Note that follows immediately after the provision in which the word or expression appears.

---



---

*Subdivision 6 — Acronyms and Abbreviations used in this Part*

The acronyms and abbreviations used in this Part and set out in the first column have the meanings set out against them in the second column.

<i>Acronym or Abbreviation</i>	<i>Meaning</i>
ABEC	Annular Bearing Engineers Committee
AGMA	American Gear Manufacturers' Association
AHRS	attitude and heading reference systems
AISI	American Iron and Steel Institute
ALU	arithmetic logic unit
ANSI	American National Standards Institute
ASTM	the American Society for Testing and Materials
ATC	air traffic control
AVLIS	atomic vapour laser isotope separation
CAD	computer-aided design
CAS	Chemical Abstract Service
CDU	control and display unit
CEP	circular error probable
CNTD	controlled nucleation thermal disposition
CRISLA	chemical reaction by isotope selective laser activation
CVD	chemical vapour deposition
CW	chemical warfare
CW (for lasers)	continuous wave
DME	distance measuring equipment
DS	directionally solidified
EB-PVD	electron beam physical vapour deposition
EBU	European Broadcasting Union
ECM	electro-chemical machining
ECR	electron cyclotron resonance
EDM	electrical discharge machines
EEPROMS	electrically erasable programmable read only memory
EIA	Electronic Industries Association



---



---

EMC	electromagnetic compatibility
ETSI	European Telecommunications Standards Institute
FFT	Fast Fourier Transform
GLONASS	global navigation satellite system
GPS	global positioning system
HBT	hetero-bipolar transistors
HDDR	high density digital recording
HEMT	high electron mobility transistors
ICAO	International Civil Aviation Organisation
IEC	International Electro-technical Commission
IEEE	Institute of Electrical and Electronic Engineers
IFOV	instantaneous-field-of-view
ILS	instrument landing system
IRIG	inter-range instrumentation group
ISA	international standard atmosphere
ISAR	inverse synthetic aperture radar
ISO	International Organisation for Standardisation
ITU	International Telecommunication Union
JIS	Japanese Industrial Standard
JT	Joule-Thomson
LIDAR	light detection and ranging
LRU	line replaceable unit
MAC	message authentication code
Mach	ratio of speed of an object to speed of sound (after Ernst Mach)
MLIS	molecular laser isotopic separation
MLS	microwave landing systems
MOCVD	metal organic chemical vapour deposition
MRI	magnetic resonance imaging
MTBF	mean-time-between-failures
Mtops	million theoretical operations per second

---

---

MTTF	mean-time-to-failure
NBC	Nuclear, Biological and Chemical
NDT	non-destructive test
PAR	precision approach radar
PIN	personal identification number
ppm	parts per million
PSD	power spectral density
QAM	quadrature-amplitude-modulation
RF	radio frequency
SACMA	Suppliers of Advanced Composite Materials Association
SAR	synthetic aperture radar
SC	single crystal
SLAR	sidelooking airborne radar
SMPTE	Society of Motion Picture and Television Engineers
SRA	shoe replaceable assembly
SRAM	static random access memory
SRM	SACMA Recommended Methods
SSB	single sideband
SSR	secondary surveillance radar
TCSEC	trusted computer system evaluation criteria
TIR	total indicated reading
UV	ultraviolet
UTS	ultimate tensile strength
VOR	very high frequency omni-directional range
YAG	yttrium/aluminium garnet

---



---

*Division 2 — List of Dual-Use Goods*


---

<i>Category Code</i>	<i>Item Description</i>
<b>CATEGORY 0 — NUCLEAR MATERIALS, FACILITIES, AND EQUIPMENT</b>	
<b>0A</b>	<b>Systems, Equipment and Components</b>
0A001	<p>“Nuclear reactors” and specially designed or prepared equipment and components therefor, as follows:</p> <ol style="list-style-type: none"> <li>a. “Nuclear reactors”;</li> <li>b. Metal vessels, or major shop-fabricated parts therefor, including the reactor vessel head for a reactor pressure vessel, specially designed or prepared to contain the core of a “nuclear reactor”;</li> <li>c. Manipulative equipment specially designed or prepared for inserting or removing fuel in a “nuclear reactor”;</li> <li>d. Control rods specially designed or prepared for the control of the fission process in a “nuclear reactor”, support or suspension structures therefor, rod drive mechanisms and rod guide tubes;</li> <li>e. Pressure tubes specially designed or prepared to contain both fuel elements and the primary coolant in a “nuclear reactor”;</li> <li>f. Zirconium metal tubes or zirconium alloy tubes (or assemblies of tubes) specially designed or prepared for use as fuel cladding in a “nuclear reactor”, and in quantities exceeding 10 kg;</li> </ol> <p><u><i>N.B.</i></u>  <i>For zirconium pressure tubes, see Category Code 0A001.e. and for calandria tubes, see Category Code 0A001.h.</i></p> <ol style="list-style-type: none"> <li>g. Coolant pumps or circulators specially designed or prepared for circulating the primary coolant of “nuclear reactors”;</li> <li>h. ‘Nuclear reactor internals’ specially designed or prepared for use in a “nuclear reactor”, including support columns for the core, fuel channels, calandria tubes, thermal shields, baffles, core grid plates, and diffuser plates;</li> </ol>

<i>Category Code</i>	<i>Item Description</i>
	<p><u>Technical Note</u>  <i>In Category Code 0A001.h., ‘nuclear reactor internals’ means any major structure within a reactor vessel which has one or more functions such as supporting the core, maintaining fuel alignment, directing primary coolant flow, providing radiation shields for the reactor vessel, and guiding in-core instrumentation.</i></p> <p>i. Heat exchangers as follows:</p> <ol style="list-style-type: none"> <li>1. Steam generators specially designed or prepared for the primary, or intermediate, coolant circuit of a “nuclear reactor”;</li> <li>2. Other heat exchangers specially designed or prepared for use in the primary coolant circuit of a “nuclear reactor”;</li> </ol> <p><u>Note</u>  <i>Category Code 0A001.i. does not include heat exchangers for the supporting systems of the reactor, e.g. the emergency cooling system or the decay heat cooling system.</i></p> <p>j. Neutron detectors specially designed or prepared for determining neutron flux levels within the core of a “nuclear reactor”;</p> <p>k. ‘External thermal shields’ specially designed or prepared for use in a “nuclear reactor” for the reduction of heat loss and also for the containment vessel protection.</p> <p><u>Technical Note</u>  <i>In Category Code 0A001.k., ‘external thermal shields’ means major structures placed over the reactor vessel which reduce heat loss from the reactor and reduce temperature within the containment vessel.</i></p>
<b>0B</b>	<b>Test, Inspection and Production Equipment</b>
0B001	Plant for the separation of isotopes of “natural uranium”, “depleted uranium” and “special fissile materials”, and specially designed or prepared equipment and components therefor, as follows:

<i>Category Code</i>	<i>Item Description</i>
	<p>a. Plant specially designed for separating isotopes of “natural uranium”, “depleted uranium”, and “special fissile materials”, as follows:</p> <ol style="list-style-type: none"> <li>1. Gas centrifuge separation plant;</li> <li>2. Gaseous diffusion separation plant;</li> <li>3. Aerodynamic separation plant;</li> <li>4. Chemical exchange separation plant;</li> <li>5. Ion-exchange separation plant;</li> <li>6. Atomic vapour “laser” isotope separation (AVLIS) plant;</li> <li>7. Molecular “laser” isotope separation (MLIS) plant;</li> <li>8. Plasma separation plant;</li> <li>9. Electromagnetic separation plant;</li> </ol> <p>b. Gas centrifuges and assemblies and components, specially designed or prepared for gas centrifuge separation process, as follows:</p> <p><u>Technical Note</u>  <i>In Category Code 0B001.b., ‘high strength-to-density ratio material’ means any of the following:</i></p> <ol style="list-style-type: none"> <li>a. <i>Maraging steel capable of an ultimate tensile strength of 1.95 GPa or more;</i></li> <li>b. <i>Aluminium alloys capable of an ultimate tensile strength of 0.46 GPa or more; or</i></li> <li>c. <i>“Fibrous or filamentary materials” with a “specific modulus” of more than <math>3.18 \times 10^6</math> m and a “specific tensile strength” greater than <math>7.62 \times 10^4</math> m.</i></li> </ol> <ol style="list-style-type: none"> <li>1. Gas centrifuges;</li> <li>2. Complete rotor assemblies;</li> <li>3. Rotor tube cylinders with a wall thickness of 12 mm or less, a diameter of between 75 mm and 650 mm, made from ‘high strength-to-density ratio materials’;</li> </ol>

<i>Category Code</i>	<i>Item Description</i>
	<ol style="list-style-type: none"> <li>4. Rings or bellows with a wall thickness of 3 mm or less and a diameter of between 75 mm and 650 mm and designed to give local support to a rotor tube or to join a number together, made from 'high strength-to-density ratio materials';</li> <li>5. Baffles of between 75 mm and 650 mm diameter for mounting inside a rotor tube, made from 'high strength-to-density ratio materials';</li> <li>6. Top or bottom caps of between 75 mm and 650 mm diameter to fit the ends of a rotor tube, made from 'high strength-to-density ratio materials';</li> <li>7. Magnetic suspension bearings as follows: <ol style="list-style-type: none"> <li>a. Bearing assemblies consisting of an annular magnet suspended within a housing made of or protected by "materials resistant to corrosion by UF<sub>6</sub>" containing a damping medium and having the magnet coupling with a pole piece or second magnet fitted to the top cap of the rotor;</li> <li>b. Active magnetic bearings specially designed or prepared for use with gas centrifuges;</li> </ol> </li> <li>8. Specially prepared bearings comprising a pivot-cup assembly mounted on a damper;</li> <li>9. Molecular pumps comprised of cylinders having internally machined or extruded helical grooves and internally machined bores;</li> <li>10. Ring-shaped motor stators for multiphase AC hysteresis (or reluctance) motors for synchronous operation within a vacuum at a frequency of 600 Hz or more and a power of 40 VA or more;</li> <li>11. Centrifuge housing/recipients to contain the rotor tube assembly of a gas centrifuge, consisting of a rigid cylinder of wall thickness up to 30 mm with precision machined ends that are parallel to each other and perpendicular to the cylinder's longitudinal axis to within 0.05 degrees or less;</li> </ol>

<i>Category Code</i>	<i>Item Description</i>
	<ol style="list-style-type: none"> <li data-bbox="539 454 1264 589">12. Scoops consisting of specially designed or prepared tubes for the extraction of UF<sub>6</sub> gas from within the rotor tube by a Pitot tube action and capable of being fixed to the central gas extraction system;</li> <li data-bbox="539 607 1264 936">13. Frequency changers (converters or inverters) specially designed or prepared to supply motor stators for gas centrifuge enrichment, having all of the following characteristics, and specially designed components therefor: <ol style="list-style-type: none"> <li data-bbox="624 790 1264 857">a. A multiphase frequency output of 600 Hz or greater; <u>and</u></li> <li data-bbox="624 875 1264 936">b. High stability (with frequency control better than 0.2%);</li> </ol> </li> <li data-bbox="539 954 1264 1323">14. Shut-off and control valves as follows: <ol style="list-style-type: none"> <li data-bbox="624 1010 1264 1099">a. Shut-off valves specially designed or prepared to act on the feed, product or tails UF<sub>6</sub> gaseous streams of an individual gas centrifuge;</li> <li data-bbox="624 1122 1264 1323">b. Bellows-sealed valves, shut-off or control, made of or protected by “materials resistant to corrosion by UF<sub>6</sub>”, with an inside diameter of 10 mm to 160 mm, specially designed or prepared for use in main or auxiliary systems of gas centrifuge enrichment plants;</li> </ol> </li> <li data-bbox="475 1346 1264 1856">c. Equipment and components, specially designed or prepared for gaseous diffusion separation process, as follows: <ol style="list-style-type: none"> <li data-bbox="539 1424 1264 1581">1. Gaseous diffusion barriers made of porous metallic, polymer or ceramic “materials resistant to corrosion by UF<sub>6</sub>” with a pore size of 10 nm to 100 nm, a thickness of 5 mm or less, and, for tubular forms, a diameter of 25 mm or less;</li> <li data-bbox="539 1603 1264 1671">2. Gaseous diffuser housings made of or protected by “materials resistant to corrosion by UF<sub>6</sub>”;</li> <li data-bbox="539 1693 1264 1856">3. Compressors or gas blowers with a suction volume capacity of 1 m<sup>3</sup>/min or more of UF<sub>6</sub>, discharge pressure up to 500 kPa and having a pressure ratio of 10:1 or less, and made of or protected by “materials resistant to corrosion by UF<sub>6</sub>”;</li> </ol> </li> </ol>

<i>Category Code</i>	<i>Item Description</i>
	<ol style="list-style-type: none"> <li>4. Rotary shaft seals for compressors or blowers specified in Category Code 0B001.c.3. and designed for a buffer gas in-leakage rate of less than 1,000 cm<sup>3</sup>/min;</li> <li>5. Heat exchangers made of or protected by “materials resistant to corrosion by UF<sub>6</sub>”, and designed for a leakage pressure rate of less than 10 Pa per hour under a pressure differential of 100 kPa;</li> <li>6. Bellows-sealed valves, manual or automated, shut-off or control, made of or protected by “materials resistant to corrosion by UF<sub>6</sub>”;</li> </ol> <p>d. Equipment and components, specially designed or prepared for aerodynamic separation process, as follows:</p> <ol style="list-style-type: none"> <li>1. Separation nozzles consisting of slit-shaped, curved channels having a radius of curvature less than 1 mm, resistant to corrosion by UF<sub>6</sub>, and having a knife-edge contained within the nozzle which separates the gas flowing through the nozzle into two streams;</li> <li>2. Cylindrical or conical tubes, (vortex tubes), made of or protected by “materials resistant to corrosion by UF<sub>6</sub>” and with one or more tangential inlets;</li> <li>3. Compressors or gas blowers made of or protected by “materials resistant to corrosion by UF<sub>6</sub>”, and rotary shaft seals therefor;</li> <li>4. Heat exchangers made of or protected by “materials resistant to corrosion by UF<sub>6</sub>”;</li> <li>5. Separation element housings, made of or protected by “materials resistant to corrosion by UF<sub>6</sub>” to contain vortex tubes or separation nozzles;</li> <li>6. Bellows-sealed valves, manual or automated, shut-off or control, made of or protected by “materials resistant to corrosion by UF<sub>6</sub>”, with a diameter of 40 mm or more;</li> <li>7. Process systems for separating UF<sub>6</sub> from carrier gas (hydrogen or helium) to 1 ppm UF<sub>6</sub> content or less, including:</li> </ol>



<i>Category Code</i>	<i>Item Description</i>
	<ul style="list-style-type: none"> <li>a. Cryogenic heat exchangers and cryoseparators capable of temperatures of 153 K (-120°C) or less;</li> <li>b. Cryogenic refrigeration units capable of temperatures of 153 K (-120°C) or less;</li> <li>c. Separation nozzle or vortex tube units for the separation of UF<sub>6</sub> from carrier gas;</li> <li>d. UF<sub>6</sub> cold traps capable of freezing out UF<sub>6</sub>;</li> <li>e. Equipment and components, specially designed or prepared for chemical exchange separation process, as follows: <ul style="list-style-type: none"> <li>1. Fast-exchange liquid-liquid pulse columns with stage residence time of 30 seconds or less and resistant to concentrated hydrochloric acid (e.g. made of or protected by suitable plastic materials such as fluorinated hydrocarbon polymers or glass);</li> <li>2. Fast-exchange liquid-liquid centrifugal contactors with stage residence time of 30 seconds or less and resistant to concentrated hydrochloric acid (e.g. made of or protected by suitable plastic materials such as fluorinated hydrocarbon polymers or glass);</li> <li>3. Electrochemical reduction cells resistant to concentrated hydrochloric acid solutions, for reduction of uranium from one valence state to another;</li> <li>4. Electrochemical reduction cells feed equipment to take U<sup>+4</sup> from the organic stream and, for those parts in contact with the process stream, made of or protected by suitable materials (e.g. glass, fluorocarbon polymers, polyphenyl sulphate, polyether sulfone and resin-impregnated graphite);</li> <li>5. Feed preparation systems for producing high purity uranium chloride solution consisting of dissolution, solvent extraction and/or ion exchange equipment for purification and electrolytic cells for reducing the uranium U<sup>+6</sup> or U<sup>+4</sup> to U<sup>+3</sup>;</li> <li>6. Uranium oxidation systems for oxidation of U<sup>+3</sup> to U<sup>+4</sup>;</li> </ul> </li> <li>f. Equipment and components, specially designed or prepared for ion-exchange separation process, as follows:</li> </ul>

<i>Category Code</i>	<i>Item Description</i>
	<ol style="list-style-type: none"> <li>1. Fast reacting ion-exchange resins, pellicular or porous macro-reticulated resins in which the active chemical exchange groups are limited to a coating on the surface of an inactive porous support structure, and other composite structures in any suitable form, including particles or fibres, with diameters of 0.2 mm or less, resistant to concentrated hydrochloric acid and designed to have an exchange rate half-time of less than 10 seconds and capable of operating at temperatures in the range of 373 K (100°C) to 473 K (200°C);</li> <li>2. Ion exchange columns (cylindrical) with a diameter greater than 1,000 mm, made of or protected by materials resistant to concentrated hydrochloric acid (e.g. titanium or fluorocarbon plastics) and capable of operating at temperatures in the range of 373 K (100°C) to 473 K (200°C) and pressures above 0.7 MPa;</li> <li>3. Ion exchange reflux systems (chemical or electrochemical oxidation or reduction systems) for regeneration of the chemical reducing or oxidising agents used in ion exchange enrichment cascades;</li> </ol> <p>g. Equipment and components, specially designed or prepared for atomic vapour based methods, as follows:</p> <ol style="list-style-type: none"> <li>1. Uranium metal vaporisation systems designed to achieve a delivered power of 1 kW or more on the target for use in laser enrichment;</li> <li>2. Liquid or vapour uranium metal handling systems specially designed or prepared for handling molten uranium, molten uranium alloys or uranium metal vapour for use in laser enrichment, and specially designed components therefor;</li> </ol> <p><u><i>N.B.</i></u> <i>See also Category Code 2A225.</i></p> <ol style="list-style-type: none"> <li>3. Product and tails collector assemblies for uranium metal in liquid or solid form, made of or protected by materials resistant to the heat and corrosion of uranium metal vapour or liquid, such as yttria-coated graphite or tantalum;</li> </ol>

<i>Category Code</i>	<i>Item Description</i>
	<p>4. Separator module housings (cylindrical or rectangular vessels) for containing the uranium metal vapour source, the electron beam gun and the product and tails collectors;</p> <p>5. “Lasers” or “laser” systems specially designed or prepared for the separation of uranium isotopes with a spectrum frequency stabilisation for operation over extended periods of time;</p> <p><u>N.B.</u> See also Category Codes 6A005 and 6A205.</p> <p>h. Equipment and components, specially designed or prepared for molecular based methods or laser systems, as follows:</p> <ol style="list-style-type: none"> <li>1. Supersonic expansion nozzles for cooling mixtures of UF<sub>6</sub> and carrier gas to 150 K (-123°C) or less and made from “materials resistant to corrosion by UF<sub>6</sub>”;</li> <li>2. Product or tails collector components or devices specially designed or prepared for collecting uranium material or uranium tails material following illumination with laser light, made of “materials resistant to corrosion by UF<sub>6</sub>”;</li> <li>3. Compressors made of or protected by “materials resistant to corrosion by UF<sub>6</sub>”, and rotary shaft seals therefor;</li> <li>4. Equipment for fluorinating UF<sub>5</sub> (solid) to UF<sub>6</sub> (gas);</li> <li>5. Process systems for separating UF<sub>6</sub> from carrier gas (e.g. nitrogen, argon or other gas) including: <ol style="list-style-type: none"> <li>a. Cryogenic heat exchangers and cryoseparators capable of temperatures of 153 K (-120°C) or less;</li> <li>b. Cryogenic refrigeration units capable of temperatures of 153 K (-120°C) or less;</li> <li>c. UF<sub>6</sub> cold traps capable of freezing out UF<sub>6</sub>;</li> </ol> </li> <li>6. “Lasers” or “laser” systems specially designed or prepared for the separation of uranium isotopes with a spectrum frequency stabilisation for operation over extended periods of time;</li> </ol>

<i>Category Code</i>	<i>Item Description</i>
	<p data-bbox="603 456 655 486"><u><i>N.B.</i></u></p> <p data-bbox="603 497 1126 526"><i>See also Category Codes 6A005 and 6A205.</i></p> <p data-bbox="475 546 1262 611">i. Equipment and components, specially designed or prepared for plasma separation process, as follows:</p> <ol data-bbox="544 629 1262 1279" style="list-style-type: none"> <li data-bbox="544 629 1262 757">1. Microwave power sources and antennae for producing or accelerating ions, with an output frequency greater than 30 GHz and mean power output greater than 50 kW;</li> <li data-bbox="544 779 1262 884">2. Radio frequency ion excitation coils for frequencies of more than 100 kHz and capable of handling more than 40 kW mean power;</li> <li data-bbox="544 898 1038 927">3. Uranium plasma generation systems;</li> <li data-bbox="544 949 719 978">4. Not used;</li> <li data-bbox="544 1001 1262 1128">5. Product and tails collector assemblies for uranium metal in solid form, made of or protected by materials resistant to the heat and corrosion of uranium vapour such as yttria-coated graphite or tantalum;</li> <li data-bbox="544 1151 1262 1279">6. Separator module housings (cylindrical) for containing the uranium plasma source, radio-frequency drive coil and the product and tails collectors and made of a suitable non-magnetic material (e.g. stainless steel);</li> </ol> <p data-bbox="475 1301 1262 1366">j. Equipment and components, specially designed or prepared for electromagnetic separation process, as follows:</p> <ol data-bbox="544 1384 1262 1848" style="list-style-type: none"> <li data-bbox="544 1384 1262 1547">1. Ion sources, single or multiple, consisting of a vapour source, ioniser, and beam accelerator made of suitable non-magnetic materials (e.g. graphite, stainless steel, or copper) and capable of providing a total ion beam current of 50 mA or greater;</li> <li data-bbox="544 1570 1262 1697">2. Ion collector plates for collection of enriched or depleted uranium ion beams, consisting of two or more slits and pockets and made of suitable non-magnetic materials (e.g. graphite or stainless steel);</li> <li data-bbox="544 1720 1262 1848">3. Vacuum housings for uranium electromagnetic separators made of non-magnetic materials (e.g. stainless steel) and designed to operate at pressures of 0.1 Pa or lower;</li> </ol>

<i>Category Code</i>	<i>Item Description</i>
	<p>4. Magnet pole pieces with a diameter greater than 2 m;</p> <p>5. High voltage power supplies for ion sources, having all of the following characteristics:</p> <ul style="list-style-type: none"> <li>a. Capable of continuous operation;</li> <li>b. Output voltage of 20,000 V or greater;</li> <li>c. Output current of 1 A or greater; <u>and</u></li> <li>d. Voltage regulation of better than 0.01% over a period of 8 hours;</li> </ul> <p><u>N.B.</u> See also Category Code 3A227.</p> <p>6. Magnet power supplies (high power, direct current) having all of the following characteristics:</p> <ul style="list-style-type: none"> <li>a. Capable of continuous operation with a current output of 500 A or greater at a voltage of 100 V or greater; <u>and</u></li> <li>b. Current or voltage regulation better than 0.01% over a period of 8 hours.</li> </ul> <p><u>N.B.</u> See also Category Code 3A226.</p>
0B002	<p>Specially designed or prepared auxiliary systems, equipment and components, as follows, for isotope separation plant specified in Category Code 0B001, made of or protected by “materials resistant to corrosion by UF<sub>6</sub>”:</p> <ul style="list-style-type: none"> <li>a. Feed autoclaves, ovens or systems used for passing UF<sub>6</sub> to the enrichment process;</li> <li>b. Desublimers or cold traps, used to remove UF<sub>6</sub> from the enrichment process for subsequent transfer upon heating;</li> <li>c. Product and tails stations for transferring UF<sub>6</sub> into containers;</li> <li>d. Liquefaction or solidification stations used to remove UF<sub>6</sub> from the enrichment process by compressing, cooling and converting UF<sub>6</sub> to a liquid or solid form;</li> </ul>

<i>Category Code</i>	<i>Item Description</i>
	<ul style="list-style-type: none"> <li>e. Piping systems and header systems specially designed or prepared for handling UF<sub>6</sub> within gaseous diffusion, centrifuge or aerodynamic cascades;</li> <li>f. Vacuum systems and pumps as follows:               <ul style="list-style-type: none"> <li>1. Vacuum manifolds, vacuum headers or vacuum pumps having a suction capacity of 5 m<sup>3</sup>/minute or more;</li> <li>2. Vacuum pumps specially designed for use in UF<sub>6</sub> bearing atmospheres made of, or protected by “materials resistant to corrosion by UF<sub>6</sub>”; <u>or</u></li> <li>3. Vacuum systems consisting of vacuum manifolds, vacuum headers and vacuum pumps, and designed for service in UF<sub>6</sub>-bearing atmospheres;</li> </ul> </li> <li>g. UF<sub>6</sub> mass spectrometers/ion sources capable of taking on-line samples from UF<sub>6</sub> gas streams and having all of the following:               <ul style="list-style-type: none"> <li>1. Capable of measuring ions of 320 atomic mass units or greater and having a resolution of better than 1 part in 320;</li> <li>2. Ion sources constructed of or protected by nickel, nickel-copper alloys with a nickel content of 60% or more by weight, or nickel-chrome alloys;</li> <li>3. Electron bombardment ionisation sources; <u>and</u></li> <li>4. Having a collector system suitable for isotopic analysis.</li> </ul> </li> </ul>
0B003	<p>Plant for the conversion of uranium and equipment specially designed or prepared therefor, as follows:</p> <ul style="list-style-type: none"> <li>a. Systems for the conversion of uranium ore concentrates to UO<sub>3</sub>;</li> <li>b. Systems for the conversion of UO<sub>3</sub> to UF<sub>6</sub>;</li> <li>c. Systems for the conversion of UO<sub>3</sub> to UO<sub>2</sub>;</li> <li>d. Systems for the conversion of UO<sub>2</sub> to UF<sub>4</sub>;</li> <li>e. Systems for the conversion of UF<sub>4</sub> to UF<sub>6</sub>;</li> <li>f. Systems for the conversion of UF<sub>4</sub> to uranium metal;</li> </ul>

<i>Category Code</i>	<i>Item Description</i>
OB004	<p>g. Systems for the conversion of UF<sub>6</sub> to UO<sub>2</sub>;</p> <p>h. Systems for the conversion of UF<sub>6</sub> to UF<sub>4</sub>;</p> <p>i. Systems for the conversion of UO<sub>2</sub> to UCl<sub>4</sub>.</p> <p>Plant for the production or concentration of heavy water, deuterium and deuterium compounds and specially designed or prepared equipment and components therefor, as follows:</p> <p>a. Plant for the production of heavy water, deuterium or deuterium compounds, as follows:</p> <ol style="list-style-type: none"> <li>1. Water-hydrogen sulphide exchange plants;</li> <li>2. Ammonia-hydrogen exchange plants;</li> </ol> <p>b. Equipment and components, as follows:</p> <ol style="list-style-type: none"> <li>1. Water-hydrogen sulphide exchange towers with diameters of 1.5 m or more, capable of operating at pressures greater than or equal to 2 MPa;</li> <li>2. Single stage, low head (i.e. 0.2 MPa) centrifugal blowers or compressors for hydrogen sulphide gas circulation (i.e. gas containing more than 70% H<sub>2</sub>S) with a throughput capacity greater than or equal to 56 m<sup>3</sup>/second when operating at pressures greater than or equal to 1.8 MPa suction and having seals designed for wet H<sub>2</sub>S service;</li> <li>3. Ammonia-hydrogen exchange towers greater than or equal to 35 m in height with diameters of 1.5 m to 2.5 m capable of operating at pressures greater than 15 MPa;</li> <li>4. Tower internals, including stage contactors, and stage pumps, including those which are submersible, for heavy water production utilising the ammonia-hydrogen exchange process;</li> <li>5. Ammonia crackers with operating pressures greater than or equal to 3 MPa for heavy water production utilising the ammonia-hydrogen exchange process;</li> <li>6. Infrared absorption analysers capable of on-line hydrogen/deuterium ratio analysis where deuterium concentrations are equal to or greater than 90%;</li> </ol>

<i>Category Code</i>	<i>Item Description</i>
0B005	<p>7. Catalytic burners for the conversion of enriched deuterium gas into heavy water utilising the ammonia-hydrogen exchange process;</p> <p>8. Complete heavy water upgrade systems, or columns therefor, for the upgrade of heavy water to reactor-grade deuterium concentration;</p> <p>9. Ammonia synthesis converters or synthesis units specially designed or prepared for heavy water production utilising the ammonia-hydrogen exchange process.</p> <p>Plant specially designed for the fabrication of “nuclear reactor” fuel elements and specially designed or prepared equipment therefor.</p> <p><i>Technical Note</i>  <i>A plant for the fabrication of “nuclear reactor” fuel elements includes equipment which:</i></p> <p><i>a. Normally comes into direct contact with or directly processes or controls the production flow of nuclear materials;</i></p> <p><i>b. Seals the nuclear materials within the cladding;</i></p> <p><i>c. Checks the integrity of the cladding or the seal;</i></p> <p><i>d. Checks the finish treatment of the sealed fuel; <u>or</u></i></p> <p><i>e. Is used for assembling reactor elements.</i></p>
0B006	<p>Plant for the reprocessing of irradiated “nuclear reactor” fuel elements, and specially designed or prepared equipment and components therefor.</p> <p><i>Note</i>  <i>Category Code 0B006 includes:</i></p> <p><i>a. Plant for the reprocessing of irradiated “nuclear reactor” fuel elements including equipment and components which normally come into direct contact with and directly control the irradiated fuel and the major nuclear material and fission product processing streams;</i></p>



<i>Category Code</i>	<i>Item Description</i>
	<p>b. <i>Fuel element chopping or shredding machines, i.e. remotely operated equipment to cut, chop or shear irradiated “nuclear reactor” fuel assemblies, bundles or rods;</i></p> <p>c. <i>Dissolvers, critically safe tanks (e.g. small diameter, annular or slab tanks) specially designed or prepared for the dissolution of irradiated “nuclear reactor” fuel, which are capable of withstanding hot, highly corrosive liquids, and which can be remotely loaded and maintained;</i></p> <p>d. <i>Solvent extractors, such as packed or pulsed columns, mixer settlers or centrifugal contactors, resistant to the corrosive effects of nitric acid and specially designed or prepared for use in a plant for the reprocessing of irradiated “natural uranium”, “depleted uranium” or “special fissile materials”;</i></p> <p>e. <i>Holding or storage vessels specially designed to be critically safe and resistant to the corrosive effects of nitric acid;</i></p> <p><u><i>Technical Note</i></u>  <i>Holding or storage vessels may have the following features:</i></p> <ol style="list-style-type: none"> <li>1. <i>Walls or internal structures with a boron equivalent (calculated for all constituent elements as defined in the note to Category Code 0C004) of at least two per cent;</i></li> <li>2. <i>A maximum diameter of 175 mm for cylindrical vessels; <u>or</u></i></li> <li>3. <i>A maximum width of 75 mm for either a slab or annular vessel.</i></li> </ol> <p>f. <i>Neutron measurement systems specially designed or prepared for integration and use with automated process control systems in a plant for the reprocessing of irradiated “natural uranium”, “depleted uranium” or “special fissile materials”.</i></p>

<i>Category Code</i>	<i>Item Description</i>
0B007	Plant for the conversion of plutonium and equipment specially designed or prepared therefor, as follows: <ol style="list-style-type: none"> <li>a. Systems for the conversion of plutonium nitrate to oxide;</li> <li>b. Systems for plutonium metal production.</li> </ol>
<b>0C</b>	<b>Materials</b>
0C001	<p>“Natural uranium” or “depleted uranium” or thorium in the form of metal, alloy, chemical compound or concentrate and any other material containing one or more of the foregoing.</p> <p><u>Note</u>  <i>Category Code 0C001 does not include the following:</i></p> <ol style="list-style-type: none"> <li>a. <i>Four grammes or less of “natural uranium” or “depleted uranium” when contained in a sensing component in instruments;</i></li> <li>b. <i>“Depleted uranium” specially fabricated for the following civil non-nuclear applications:</i> <ol style="list-style-type: none"> <li>1. <i>Shielding;</i></li> <li>2. <i>Packaging;</i></li> <li>3. <i>Ballasts having a mass not greater than 100 kg;</i></li> <li>4. <i>Counter-weights having a mass not greater than 100 kg;</i></li> </ol> </li> <li>c. <i>Alloys containing less than 5% thorium;</i></li> <li>d. <i>Ceramic products containing thorium, which have been manufactured for non-nuclear use.</i></li> </ol>
0C002	<p>“Special fissile materials”.</p> <p><u>Note</u>  <i>Category Code 0C002 does not include four “effective grammes” or less when contained in a sensing component in instruments.</i></p>

<i>Category Code</i>	<i>Item Description</i>
0C003	Deuterium, heavy water (deuterium oxide) and other compounds of deuterium, and mixtures and solutions containing deuterium, in which the isotopic ratio of deuterium to hydrogen exceeds 1:5,000.
0C004	Graphite having a purity level of less than 5 parts per million 'boron equivalent' and with a density greater than 1.5 g/cm <sup>3</sup> for use in a "nuclear reactor", in quantities exceeding 1 kg.
	<p><u>N.B.</u> See also Category Code 1C107.</p>
	<p><u>Note 1</u> For the purpose of Category Code 0C004, whether or not the exports of graphite meeting the above specifications are for "nuclear reactor" use is determined, at or before the time of export, by the competent authorities of the country in which the exporter is established.</p>
	<p><u>Note 2</u> In Category Code 0C004, 'boron equivalent' (BE) means the sum of BE<sub>Z</sub> for impurities (excluding BE<sub>carbon</sub> since carbon is not considered an impurity) including boron, where:</p> $BE_z \text{ (ppm)} = CF \times \text{concentration of element Z in ppm};$ <p>where CF is the conversion factor = <math>\frac{\sigma_z \times A_B}{\sigma_B \times A_z}</math></p> <p>and <math>\sigma_B</math> and <math>\sigma_z</math> are the thermal neutron capture cross sections (in barns) for naturally occurring boron and element Z respectively; and <math>A_B</math> and <math>A_z</math> are the atomic masses of naturally occurring boron and element Z, respectively.</p>
0C005	Specially prepared compounds or powders for the manufacture of gaseous diffusion barriers, resistant to corrosion by UF <sub>6</sub> (e.g. nickel or alloy containing 60% or more nickel by weight, aluminium oxide and fully fluorinated hydrocarbon polymers), having a purity of 99.9% by weight or more and a particle size less than 10 µm measured by American Society for Testing and Materials (ASTM) B330 standard and a high degree of particle size uniformity.

<i>Category Code</i>	<i>Item Description</i>
<b>0D</b>	<b>Software</b>
0D001	“Software” specially designed or modified for the “development”, “production” or “use” of goods specified in this Category.
<b>0E</b>	<b>Technology</b>
0E001	“Technology” according to the Nuclear Technology Note for the “development”, “production” or “use” of goods specified in this Category.

<i>Category Code</i>	<i>Item Description</i>
<b>CATEGORY 1 — SPECIAL MATERIALS AND RELATED EQUIPMENT</b>	
<b>1A</b>	<b>Systems, Equipment and Components</b>
1A001	<p>Components made from fluorinated compounds, as follows:</p> <ol style="list-style-type: none"> <li>a. Seals, gaskets, sealants or fuel bladders, specially designed for “aircraft” or aerospace use, made from more than 50% by weight of any of the materials specified in Category Code 1C009.b. or 1C009.c.;</li> <li>b. Piezoelectric polymers and copolymers, made from vinylidene fluoride (75-38-7) materials, specified in Category Code 1C009.a., having all of the following: <ol style="list-style-type: none"> <li>1. In sheet or film form; <u>and</u></li> <li>2. With a thickness exceeding 200 µm;</li> </ol> </li> <li>c. Seals, gaskets, valve seats, bladders or diaphragms, having all of the following: <ol style="list-style-type: none"> <li>1. Made from fluoroelastomers containing at least one vinylether group as a constitutional unit; <u>and</u></li> <li>2. Specially designed for “aircraft”, aerospace or ‘missile’ use.</li> </ol> </li> </ol> <p><i>Note</i>  <i>In Category Code 1A001.c., ‘missile’ means complete rocket systems and unmanned aerial vehicle systems.</i></p>
1A002	<p>“Composite” structures or laminates, having any of the following:</p> <p><u>N.B.</u>  <i>See also Category Codes 1A202, 9A010 and 9A110.</i></p> <ol style="list-style-type: none"> <li>a. Consisting of an organic “matrix” and materials specified in Category Code 1C010.c., 1C010.d. or 1C010.e.; <u>or</u></li> <li>b. Consisting of a metal or carbon “matrix”, and any of the following: <ol style="list-style-type: none"> <li>1. Carbon “fibrous or filamentary materials” having all of the following: <ol style="list-style-type: none"> <li>a. A “specific modulus” exceeding <math>10.15 \times 10^6</math> m; <u>and</u></li> </ol> </li> </ol> </li> </ol>

<i>Category Code</i>	<i>Item Description</i>
	<p style="text-align: center;">b. A “specific tensile strength” exceeding <math>17.7 \times 10^4</math> m; <u>or</u></p> <p style="text-align: center;">2. Materials specified in Category Code 1C010.c.</p> <p><u>Note 1</u>  <i>Category Code 1A002 does not include composite structures or laminates made from epoxy resin impregnated carbon “fibrous or filamentary materials” for the repair of “civil aircraft” structures or laminates, having all of the following:</i></p> <p>a. <i>An area not exceeding 1 m<sup>2</sup>;</i></p> <p>b. <i>A length not exceeding 2.5 m; <u>and</u></i></p> <p>c. <i>A width exceeding 15 mm.</i></p> <p><u>Note 2</u>  <i>Category Code 1A002 does not include semi-finished items, specially designed for purely civilian applications as follows:</i></p> <p>a. <i>Sporting goods;</i></p> <p>b. <i>Automotive industry;</i></p> <p>c. <i>Machine tool industry;</i></p> <p>d. <i>Medical applications.</i></p> <p><u>Note 3</u>  <i>Category Code 1A002.b.1. does not include semi-finished items containing a maximum of two dimensions of interwoven filaments and specially designed for applications as follows:</i></p> <p>a. <i>Metal heat-treatment furnaces for tempering metals;</i></p> <p>b. <i>Silicon boule production equipment.</i></p> <p><u>Note 4</u>  <i>Category Code 1A002 does not include finished items specially designed for a specific application.</i></p>
1A003	<p>Manufactures of non-“fusible” aromatic polyimides in film, sheet, tape or ribbon form having any of the following:</p> <p>a. A thickness exceeding 0.254 mm; <u>or</u></p> <p>b. Coated or laminated with carbon, graphite, metals or magnetic substances.</p>

Category Code	Item Description
1A004	<p><u>Note</u>  <i>Category Code 1A003 does not include manufactures when coated or laminated with copper and designed for the production of electronic printed circuit boards.</i></p> <p><u>N.B.</u>  <i>For “fusible” aromatic polyimides in any form, see Category Code 1C008.a.3.</i></p> <p>Protective and detection equipment and components not specially designed for military use, as follows:</p> <p><u>N.B.</u>  <i>See also Division 2 of Part I of this Schedule, and Category Codes 2B351 and 2B352.</i></p> <p>a. Full face masks, filter canisters and decontamination equipment therefor, designed or modified for defence against any of the following, and specially designed components therefor:</p> <p><u>Note</u>  <i>Category Code 1A004.a. includes Powered Air Purifying Respirators (PAPR) that are designed or modified for defence against agents or materials, listed in Category Code 1A004.a.</i></p> <p><u>Technical Note</u>  <i>For the purpose of Category Code 1A004.a.:</i></p> <ol style="list-style-type: none"> <li>1. Full face masks are also known as gas masks.</li> <li>2. Filter canisters include filter cartridges.</li> <li>1. Biological agents “adapted for use in war”;</li> <li>2. Radioactive materials “adapted for use in war”;</li> <li>3. Chemical warfare (CW) agents; <u>or</u></li> <li>4. “Riot control agents”, including: <ol style="list-style-type: none"> <li>a. <math>\alpha</math>-Bromobenzeneacetonitrile, (Bromobenzyl cyanide) (CA) (5798-79-8);</li> </ol> </li> </ol>

<i>Category Code</i>	<i>Item Description</i>
	<p>b. [(2-chlorophenyl) methylene] propanedinitrile, (o-Chlorobenzylidenemalononitrile) (CS) (2698-41-1);</p> <p>c. 2-Chloro-1-phenylethanone, Phenylacyl chloride (ω-chloroacetophenone) (CN) (532-27-4);</p> <p>d. Dibenz-(b,f)-1,4-oxazepine (CR) (257-07-8);</p> <p>e. 10-Chloro-5,10-dihydrophenarsazine, (Phenarsazine chloride), (Adamsite), (DM) (578-94-9);</p> <p>f. N-Nonanoylmorpholine, (MPA) (5299-64-9);</p> <p>b. Protective suits, gloves and shoes, specially designed or modified for defence against any of the following:</p> <ol style="list-style-type: none"> <li>1. Biological agents “adapted for use in war”;</li> <li>2. Radioactive materials “adapted for use in war”; <u>or</u></li> <li>3. Chemical warfare (CW) agents;</li> </ol> <p>c. Detection systems, specially designed or modified for detection or identification of any of the following, and specially designed components therefor:</p> <ol style="list-style-type: none"> <li>1. Biological agents “adapted for use in war”;</li> <li>2. Radioactive materials “adapted for use in war”; <u>or</u></li> <li>3. Chemical warfare (CW) agents;</li> </ol> <p>d. Electronic equipment designed for automatically detecting or identifying the presence of “explosives” residues and utilising ‘trace detection’ techniques (e.g. surface acoustic wave, ion mobility spectrometry, differential mobility spectrometry, mass spectrometry).</p> <p><u>Technical Note</u>  ‘Trace detection’ is defined as the capability to detect less than 1 ppm vapour, or 1 mg solid or liquid.</p> <p><u>Note 1</u>  Category Code 1A004.d. does not include equipment specially designed for laboratory use.</p>



Category Code	Item Description
	<p data-bbox="539 454 624 488"><u>Note 2</u></p> <p data-bbox="539 495 1262 562">Category Code 1A004.d. does not include non-contact walk-through security portals.</p> <p data-bbox="475 577 539 611"><u>Note</u></p> <p data-bbox="475 618 954 651">Category Code 1A004 does not include:</p> <p data-bbox="475 667 1262 1267"> <ul style="list-style-type: none"> <li>a. Personal radiation monitoring dosimeters;</li> <li>b. Occupational health or safety equipment limited by design or function to protect against hazards specific to residential safety or civil industries, including:               <ul style="list-style-type: none"> <li>1. Mining;</li> <li>2. Quarrying;</li> <li>3. Agriculture;</li> <li>4. Pharmaceutical;</li> <li>5. Medical;</li> <li>6. Veterinary;</li> <li>7. Environmental;</li> <li>8. Waste management;</li> <li>9. Food industry.</li> </ul> </li> </ul> </p> <p data-bbox="475 1283 671 1317"><u>Technical Notes</u></p> <p data-bbox="475 1323 1262 1771"> <ul style="list-style-type: none"> <li>1. Category Code 1A004 includes equipment and components that have been identified, successfully tested to national standards or otherwise proven effective, for the detection of or defence against radioactive materials “adapted for use in war”, biological agents “adapted for use in war”, chemical warfare agents, ‘simulants’ or “riot control agents”, even if such equipment or components are used in civil industries such as mining, quarrying, agriculture, pharmaceuticals, medical, veterinary, environmental, waste management, or the food industry.</li> <li>2. ‘Simulant’ is a substance or material that is used in place of toxic agent (chemical or biological) in training, research, testing or evaluation.</li> </ul> </p>

<i>Category Code</i>	<i>Item Description</i>
1A005	<p>Body armour and components therefor, as follows:</p> <p><u>N.B.</u> See also Division 2 of Part I of this Schedule.</p> <p>a. Soft body armour not manufactured to military standards or specifications, or to their equivalents, and specially designed components therefor;</p> <p>b. Hard body armour plates providing ballistic protection equal to or less than level IIIA (NIJ 0101.06, July 2008) or national equivalents.</p> <p><u>N.B.</u> For “fibrous or filamentary materials” used in the manufacture of body armour, see Category Code 1C010.</p> <p><u>Note 1</u> Category Code 1A005 does not include body armour when accompanying its user for the user’s own personal protection.</p> <p><u>Note 2</u> Category Code 1A005 does not include body armour designed to provide frontal protection only from both fragment and blast from non-military explosive devices.</p> <p><u>Note 3</u> Category Code 1A005 does not include body armour designed to provide protection only from knife, spike, needle or blunt trauma.</p>
1A006	<p>Equipment, specially designed or modified for the disposal of improvised explosive devices, as follows, and specially designed components and accessories therefor:</p> <p><u>N.B.</u> See also Division 2 of Part I of this Schedule.</p> <p>a. Remotely operated vehicles;</p> <p>b. ‘Disruptors’.</p> <p><u>Technical Note</u> ‘Disruptors’ are devices specially designed for the purpose of preventing the operation of an explosive device by projecting a liquid, solid or frangible projectile.</p>

<i>Category Code</i>	<i>Item Description</i>
1A007	<p><u>Note</u>  <i>Category Code 1A006 does not include equipment when accompanying its operator.</i></p> <p>Equipment and devices, specially designed to initiate charges and devices containing “energetic materials”, by electrical means, as follows:</p> <p><u>N.B.</u>  <i>See also Division 2 of Part I of this Schedule, and Category Codes 3A229 and 3A232.</i></p> <ol style="list-style-type: none"> <li>a. Explosive detonator firing sets designed to drive explosive detonators specified in Category Code 1A007.b.;</li> <li>b. Electrically driven explosive detonators as follows: <ol style="list-style-type: none"> <li>1. Exploding bridge (EB);</li> <li>2. Exploding bridge wire (EBW);</li> <li>3. Slapper;</li> <li>4. Exploding foil initiators (EFI).</li> </ol> </li> </ol> <p><u>Technical Notes</u></p> <ol style="list-style-type: none"> <li>1. <i>The word initiator or igniter is sometimes used in place of the word detonator.</i></li> <li>2. <i>For the purpose of Category Code 1A007.b. the detonators of concern all utilise a small electrical conductor (bridge, bridge wire, or foil) that explosively vaporises when a fast, high-current electrical pulse is passed through it. In non-slapper types, the exploding conductor starts a chemical detonation in a contacting high explosive material such as PETN (pentaerythritoltetranitrate). In slapper detonators, the explosive vaporisation of the electrical conductor drives a flyer or slapper across a gap, and the impact of the slapper on an explosive starts a chemical detonation. The slapper in some designs is driven by magnetic force. The term exploding foil detonator may refer to either an EB or a slapper-type detonator.</i></li> </ol>

<i>Category Code</i>	<i>Item Description</i>
1A008	<p>Charges, devices and components, as follows:</p> <ul style="list-style-type: none"> <li>a. ‘Shaped charges’ having all of the following: <ul style="list-style-type: none"> <li>1. Net Explosive Quantity (NEQ) greater than 90 g; <u>and</u></li> <li>2. Outer casing diameter equal to or greater than 75 mm;</li> </ul> </li> <li>b. Linear shaped cutting charges having all of the following, and specially designed components therefor: <ul style="list-style-type: none"> <li>1. An explosive load greater than 40 g/m; <u>and</u></li> <li>2. A width of 10 mm or more;</li> </ul> </li> <li>c. Detonating cord with explosive core load greater than 64 g/m;</li> <li>d. Cutters, other than those specified in Category Code 1A008.b., and severing tools, having a Net Explosive Quantity (NEQ) greater than 3.5 kg.</li> </ul> <p><i>Technical Note</i>  ‘Shaped charges’ are explosive charges shaped to focus the effects of the explosive blast.</p>
1A102	<p>Resaturated pyrolised carbon-carbon components designed for space launch vehicles specified in Category Code 9A004 or sounding rockets specified in Category Code 9A104.</p>
1A202	<p>Composite structures, other than those specified in Category Code 1A002, in the form of tubes and having both of the following characteristics:</p> <p><i>N.B.</i>  See also Category Codes 9A010 and 9A110.</p> <ul style="list-style-type: none"> <li>a. An inside diameter of between 75 mm and 400 mm; <u>and</u></li> <li>b. Made with any of the “fibrous or filamentary materials” specified in Category Code 1C010.a. or 1C010.b. or 1C210.a. or with carbon prepreg materials specified in Category Code 1C210.c.</li> </ul>

<i>Category Code</i>	<i>Item Description</i>
1A225	Platinised catalysts specially designed or prepared for promoting the hydrogen isotope exchange reaction between hydrogen and water for the recovery of tritium from heavy water or for the production of heavy water.
1A226	<p>Specialised packings which may be used in separating heavy water from ordinary water, having both of the following characteristics:</p> <ol style="list-style-type: none"> <li>a. Made of phosphor bronze mesh chemically treated to improve wettability; <u>and</u></li> <li>b. Designed to be used in vacuum distillation towers.</li> </ol>
1A227	<p>High-density (lead glass or other) radiation shielding windows, having all of the following characteristics, and specially designed frames therefor:</p> <ol style="list-style-type: none"> <li>a. A 'cold area' greater than 0.09 m<sup>2</sup>;</li> <li>b. A density greater than 3 g/cm<sup>3</sup>; <u>and</u></li> <li>c. A thickness of 100 mm or greater.</li> </ol> <p><i>Technical Note</i>  <i>In Category Code 1A227, 'cold area' means the viewing area of the window exposed to the lowest level of radiation in the design application.</i></p>
<b>1B</b>	<b>Test, Inspection and Production Equipment</b>
1B001	<p>Equipment for the production or inspection of "composite" structures or laminates specified in Category Code 1A002 or "fibrous or filamentary materials" specified in Category Code 1C010, as follows, and specially designed components and accessories therefor:</p> <p><u>N.B.</u>  <i>See also Category Codes 1B101 and 1B201.</i></p>

<i>Category Code</i>	<i>Item Description</i>
	<p>a. Filament winding machines, of which the motions for positioning, wrapping and winding fibres are coordinated and programmed in three or more ‘primary servo positioning’ axes, specially designed for the manufacture of “composite” structures or laminates, from “fibrous or filamentary materials”;</p> <p>b. ‘Tape-laying machines’, of which the motions for positioning and laying tape are coordinated and programmed in five or more ‘primary servo positioning’ axes, specially designed for the manufacture of “composite” airframe or ‘missile’ structures;</p> <p><i>Note</i>  <i>In Category Code 1B001.b., ‘missile’ means complete rocket systems and unmanned aerial vehicle systems.</i></p> <p><i>Technical Note</i>  <i>For the purpose of Category Code 1B001.b., ‘tape-laying machines’ have the ability to lay one or more ‘filament bands’ limited to widths greater than 25 mm and less than or equal to 305 mm, and to cut and restart individual ‘filament bands’ courses during the laying process.</i></p> <p>c. Multidirectional, multidimensional weaving machines or interlacing machines, including adapters and modification kits, specially designed or modified for weaving, interlacing or braiding fibres, for “composite” structures;</p> <p><i>Technical Note</i>  <i>For the purpose of Category Code 1B001.c., the technique of interlacing includes knitting.</i></p> <p>d. Equipment specially designed or adapted for the production of reinforcement fibres, as follows:</p> <ol style="list-style-type: none"> <li>1. Equipment for converting polymeric fibres (e.g. polyacrylonitrile, rayon, pitch or polycarbosilane) into carbon fibres or silicon carbide fibres, including special equipment to strain the fibre during heating;</li> <li>2. Equipment for the chemical vapour deposition of elements or compounds, on heated filamentary substrates, to manufacture silicon carbide fibres;</li> </ol>

<i>Category Code</i>	<i>Item Description</i>
	<p>3. Equipment for the wet-spinning of refractory ceramics (e.g. aluminium oxide);</p> <p>4. Equipment for converting aluminium containing precursor fibres into alumina fibres by heat treatment;</p> <p>e. Equipment for producing prepregs specified in Category Code 1C010.e. by the hot melt method;</p> <p>f. Non-destructive inspection equipment specially designed for “composite” materials, as follows:</p> <p>1. X-ray tomography systems for three dimensional defect inspection;</p> <p>2. Numerically controlled ultrasonic testing machines of which the motions for positioning transmitters or receivers are simultaneously coordinated and programmed in four or more axes to follow the three dimensional contours of the component under inspection;</p> <p>g. ‘Tow-placement machines’, of which the motions for positioning and laying tows are coordinated and programmed in two or more ‘primary servo positioning’ axes, specially designed for the manufacture of “composite” airframe or ‘missile’ structures.</p> <p><u>Technical Note</u></p> <p><i>For the purpose of Category Code 1B001.g., ‘tow-placement machines’ have the ability to place one or more ‘filament bands’ having widths less than or equal to 25 mm, and to cut and restart individual ‘filament band’ courses during the placement process.</i></p> <p><u>Technical Notes</u></p> <p>1. <i>For the purpose of Category Code 1B001, ‘primary servo positioning’ axes control, under computer program direction, the position of the end effector (i.e. head) in space relative to the workpiece at the correct orientation and direction to achieve the desired process.</i></p> <p>2. <i>For the purpose of Category Code 1B001, a ‘filament band’ is a single continuous width of fully or partially resin-impregnated tape, tow or fibre.</i></p>

<i>Category Code</i>	<i>Item Description</i>
1B002	<p>Equipment for producing metal alloys, metal alloy powder or alloyed materials, specially designed to avoid contamination and specially designed for use in one of the processes specified in Category Code 1C002.c.2.</p> <p><u>N.B.</u> See also Category Code 1B102.</p>
1B003	<p>Tools, dies, moulds or fixtures, for “superplastic forming” or “diffusion bonding” titanium, aluminium or their alloys, specially designed for the manufacture of any of the following:</p> <ol style="list-style-type: none"> <li>a. Airframe or aerospace structures;</li> <li>b. “Aircraft” or aerospace engines; <u>or</u></li> <li>c. Specially designed components for structures specified in Category Code 1B003.a. or for engines specified in Category Code 1B003.b.</li> </ol>
1B101	<p>Equipment, other than that specified in Category Code 1B001, for the “production” of structural composites as follows; and specially designed components and accessories therefor:</p> <p><u>N.B.</u> See also Category Code 1B201.</p> <p><u>Note</u> <i>Components and accessories specified in Category Code 1B101 include moulds, mandrels, dies, fixtures and tooling for the preform pressing, curing, casting, sintering or bonding of composite structures, laminates and manufactures thereof.</i></p> <ol style="list-style-type: none"> <li>a. Filament winding machines or fibre placement machines, of which the motions for positioning, wrapping and winding fibres can be coordinated and programmed in three or more axes, designed to fabricate composite structures or laminates from fibrous or filamentary materials, and coordinating and programming controls;</li> <li>b. Tape-laying machines of which the motions for positioning and laying tape and sheets can be coordinated and programmed in two or more axes, designed for the manufacture of composite airframe and “missile” structures;</li> </ol>



<i>Category Code</i>	<i>Item Description</i>
	<p>c. Equipment designed or modified for the “production” of “fibrous or filamentary materials” as follows:</p> <ol style="list-style-type: none"> <li>1. Equipment for converting polymeric fibres (e.g. polyacrylonitrile, rayon or polycarbosilane) including special provision to strain the fibre during heating;</li> <li>2. Equipment for the vapour deposition of elements or compounds on heated filament substrates;</li> <li>3. Equipment for the wet-spinning of refractory ceramics (e.g. aluminium oxide);</li> </ol> <p>d. Equipment designed or modified for special fibre surface treatment or for producing prepregs and preforms specified in Category Code 9C110.</p> <p><i>Note</i> Category Code 1B101.d. includes rollers, tension stretchers, coating equipment, cutting equipment and clicker dies.</p>
1B102	<p>Metal powder “production equipment”, other than that specified in Category Code 1B002, and components, as follows:</p> <p><i>N.B.</i> See also Category Code 1B115.b.</p> <ol style="list-style-type: none"> <li>a. Metal powder “production equipment” usable for the “production”, in a controlled environment, of spherical, spheroidal or atomised materials specified in Category Code 1C011.a., 1C011.b., 1C111.a.1., 1C111.a.2. or in Division 2 of Part I of this Schedule.</li> <li>b. Specially designed components for “production equipment” specified in Category Code 1B002 or 1B102.a.</li> </ol> <p><i>Note</i> Category Code 1B102 includes:</p> <ol style="list-style-type: none"> <li>a. Plasma generators (high frequency arc-jet) usable for obtaining sputtered or spherical metallic powders with organisation of the process in an argon-water environment;</li> <li>b. Electrobust equipment usable for obtaining sputtered or spherical metallic powders with organisation of the process in an argon-water environment;</li> </ol>

<i>Category Code</i>	<i>Item Description</i>
1B115	<p data-bbox="478 456 1272 555">c. <i>Equipment usable for the “production” of spherical aluminium powders by powdering a melt in an inert medium (e.g. nitrogen).</i></p> <p data-bbox="478 622 1272 752">Equipment, other than that specified in Category Code 1B002 or 1B102, for the production of propellant and propellant constituents, as follows, and specially designed components therefor:</p> <p data-bbox="478 775 1272 904">a. “Production equipment” for the “production”, handling or acceptance testing of liquid propellants or propellant constituents specified in Category Code 1C011.a., 1C011.b., 1C111 or in Division 2 of Part I of this Schedule;</p> <p data-bbox="478 927 1272 1088">b. “Production equipment” for the “production”, handling, mixing, curing, casting, pressing, machining, extruding or acceptance testing of solid propellants or propellant constituents specified in Category Code 1C011.a., 1C011.b., 1C111 or in Division 2 of Part I of this Schedule.</p> <p data-bbox="539 1111 1272 1281"><i>Note</i> Category Code 1B115.b. does not include batch mixers, continuous mixers or fluid energy mills. For batch mixers, continuous mixers and fluid energy mills see Category Codes 1B117, 1B118 and 1B119.</p> <p data-bbox="478 1303 1272 1406"><i>Note 1</i> For equipment specially designed for the production of military goods, see Division 2 of Part I of this Schedule.</p> <p data-bbox="478 1429 1272 1532"><i>Note 2</i> Category Code 1B115 does not include equipment for the “production”, handling and acceptance testing of boron carbide.</p>
1B116	<p data-bbox="478 1603 1272 1765">Specially designed nozzles for producing pyrolitically derived materials formed on a mould, mandrel or other substrate from precursor gases which decompose in the 1,573 K (1,300°C) to 3,173 K (2,900°C) temperature range at pressures of 130 Pa to 20 kPa.</p>

<i>Category Code</i>	<i>Item Description</i>
1B117	<p>Batch mixers with provision for mixing under vacuum in the range of zero to 13.326 kPa and with temperature control capability of the mixing chamber and having all of the following, and specially designed components therefor:</p> <ul style="list-style-type: none"> <li>a. A total volumetric capacity of 110 litres or more; <u>and</u></li> <li>b. At least one ‘mixing/kneading shaft’ mounted off centre.</li> </ul> <p><i>Note</i>  <i>In Category Code 1B117.b., ‘mixing/kneading shaft’ does not refer to deagglomerators or knife-spindles.</i></p>
1B118	<p>Continuous mixers with provision for mixing under vacuum in the range of zero to 13.326 kPa and with a temperature control capability of the mixing chamber having any of the following, and specially designed components therefor:</p> <ul style="list-style-type: none"> <li>a. Two or more mixing/kneading shafts; <u>or</u></li> <li>b. A single rotating shaft which oscillates and having kneading teeth/pins on the shaft as well as inside the casing of the mixing chamber.</li> </ul>
1B119	<p>Fluid energy mills usable for grinding or milling substances specified in Category Code 1C011.a., 1C011.b., 1C111 or in Division 2 of Part I of this Schedule, and specially designed components therefor.</p>
1B201	<p>Filament winding machines, other than those specified in Category Code 1B001 or 1B101, and related equipment, as follows:</p> <ul style="list-style-type: none"> <li>a. Filament winding machines having all of the following characteristics: <ul style="list-style-type: none"> <li>1. Having motions for positioning, wrapping, and winding fibres coordinated and programmed in two or more axes;</li> <li>2. Specially designed to fabricate composite structures or laminates from “fibrous or filamentary materials”; <u>and</u></li> </ul> </li> </ul>

<i>Category Code</i>	<i>Item Description</i>
	<ul style="list-style-type: none"> <li>3. Capable of winding cylindrical tubes with an internal diameter between 75 mm and 650 mm and lengths of 300 mm or greater;</li> <li>b. Coordinating and programming controls for the filament winding machines specified in Category Code 1B201.a.;</li> <li>c. Precision mandrels for the filament winding machines specified in Category Code 1B201.a.</li> </ul>
1B225	Electrolytic cells for fluorine production with an output capacity greater than 250 g of fluorine per hour.
1B226	<p>Electromagnetic isotope separators designed for, or equipped with, single or multiple ion sources capable of providing a total ion beam current of 50 mA or greater.</p> <p><u>Note</u>  <i>Category Code 1B226 includes separators:</i></p> <ul style="list-style-type: none"> <li>a. Capable of enriching stable isotopes;</li> <li>b. With the ion sources and collectors both in the magnetic field and those configurations in which they are external to the field.</li> </ul>
1B228	<p>Hydrogen-cryogenic distillation columns having all of the following characteristics:</p> <ul style="list-style-type: none"> <li>a. Designed for operation with internal temperatures of 35 K (-238°C) or less;</li> <li>b. Designed for operation at an internal pressure of 0.5 MPa to 5 MPa;</li> <li>c. Constructed of either: <ul style="list-style-type: none"> <li>1. Stainless steel of the 300 series with low sulphur content and with an austenitic ASTM (or equivalent standard) grain size number of 5 or greater; <u>or</u></li> <li>2. Equivalent materials which are both cryogenic and H<sub>2</sub>-compatible; <u>and</u></li> </ul> </li> </ul>

Category Code	Item Description
1B229	<p>d. With internal diameters of 30 cm or greater and ‘effective lengths’ of 4 m or greater.</p> <p><i>Technical Note</i>  <i>In Category Code 1B228, ‘effective length’ means the active height of packing material in a packed-type column, or the active height of internal contactor plates in a plate-type column.</i></p> <p>Water-hydrogen sulphide exchange tray columns and ‘internal contactors’, as follows:</p> <p><i>N.B.</i>  <i>For columns which are specially designed or prepared for the production of heavy water see Category Code 0B004.</i></p> <p>a. Water-hydrogen sulphide exchange tray columns, having all of the following characteristics:</p> <ol style="list-style-type: none"> <li>1. Can operate at pressures of 2 MPa or greater;</li> <li>2. Constructed of carbon steel having an austenitic ASTM (or equivalent standard) grain size number of 5 or greater; <u>and</u></li> <li>3. With a diameter of 1.8 m or greater;</li> </ol> <p>b. ‘Internal contactors’ for the water-hydrogen sulphide exchange tray columns specified in Category Code 1B229.a.</p> <p><i>Technical Note</i>  <i>‘Internal contactors’ of the columns are segmented trays which have an effective assembled diameter of 1.8 m or greater, are designed to facilitate countercurrent contacting and are constructed of stainless steels with a carbon content of 0.03% or less. These may be sieve trays, valve trays, bubble cap trays, or turbogrid trays.</i></p>
1B230	<p>Pumps capable of circulating solutions of concentrated or dilute potassium amide catalyst in liquid ammonia (<math>\text{KNH}_2/\text{NH}_3</math>), having all of the following characteristics:</p> <ol style="list-style-type: none"> <li>a. Airtight (i.e. hermetically sealed);</li> <li>b. A capacity greater than <math>8.5 \text{ m}^3/\text{h}</math>; <u>and</u></li> </ol>

<i>Category Code</i>	<i>Item Description</i>
	<ul style="list-style-type: none"> <li>c. Either of the following characteristics:               <ul style="list-style-type: none"> <li>1. For concentrated potassium amide solutions (1% or greater), an operating pressure of 1.5 MPa to 60 MPa; <u>or</u></li> <li>2. For dilute potassium amide solutions (less than 1%), an operating pressure of 20 MPa to 60 MPa.</li> </ul> </li> </ul>
1B231	<p>Tritium facilities or plants, and equipment therefor, as follows:</p> <ul style="list-style-type: none"> <li>a. Facilities or plants for the production, recovery, extraction, concentration, or handling of tritium;</li> <li>b. Equipment for tritium facilities or plants, as follows:               <ul style="list-style-type: none"> <li>1. Hydrogen or helium refrigeration units capable of cooling to 23 K (-250°C) or less, with heat removal capacity greater than 150 W;</li> <li>2. Hydrogen isotope storage or purification systems using metal hydrides as the storage or purification medium.</li> </ul> </li> </ul>
1B232	<p>Turboexpanders or turboexpander-compressor sets having both of the following characteristics:</p> <ul style="list-style-type: none"> <li>a. Designed for operation with an outlet temperature of 35 K (-238°C) or less; <u>and</u></li> <li>b. Designed for a throughput of hydrogen gas of 1,000 kg/h or greater.</li> </ul>
1B233	<p>Lithium isotope separation facilities or plants, and systems and equipment therefor, as follows:</p> <ul style="list-style-type: none"> <li>a. Facilities or plants for the separation of lithium isotopes;</li> <li>b. Equipment for the separation of lithium isotopes based on the lithium-mercury amalgam process, as follows:               <ul style="list-style-type: none"> <li>1. Packed liquid-liquid exchange columns specially designed for lithium amalgams;</li> <li>2. Mercury or lithium amalgam pumps;</li> <li>3. Lithium amalgam electrolysis cells;</li> </ul> </li> </ul>

<i>Category Code</i>	<i>Item Description</i>
	<p>4. Evaporators for concentrated lithium hydroxide solution;</p> <p>c. Ion exchange systems specially designed for lithium isotope separation, and specially designed components therefor;</p> <p>d. Chemical exchange systems (employing crown ethers, cryptands, or lariat ethers), specially designed for lithium isotope separation, and specially designed components therefor.</p>
1B234	<p>High explosive containment vessels, chambers, containers and other similar containment devices designed for the testing of high explosives or explosive devices and having both of the following characteristics:</p> <p><u>N.B.</u> See also Division 2 of Part I of this Schedule.</p> <p>a. Designed to fully contain an explosion equivalent to 2 kg of TNT or greater; <u>and</u></p> <p>b. Having design elements or features enabling real time or delayed transfer of diagnostic or measurement information.</p>
1C	<p><b>Materials</b></p> <p><u>Technical Note</u> Unless provision to the contrary is made, the words ‘metals’ and ‘alloys’ in Category Codes 1C001 to 1C012 cover crude and semi-fabricated forms, as follows:</p> <p>“Crude forms”, in relation to materials, means anodes, balls, bars (including notched bars and wire bars), billets, blocks, blooms, brickets, cakes, cathodes, crystals, cubes, dice, grains, granules, ingots, lumps, pellets, pigs, powder, rondelles, shot, slabs, slugs, sponge, sticks;</p> <p>“Semi-fabricated forms”, in relation to materials, means any of the following:</p>

Category Code	Item Description
	<p>a. <i>Wrought or worked materials fabricated by rolling, drawing, extruding, forging, impact extruding, pressing, graining, atomising, and grinding, i.e.: angles, channels, circles, discs, dust, flakes, foils and leaf, forging, plate, powder, pressings and stampings, ribbons, rings, rods (including bare welding rods, wire rods, and rolled wire), sections, shapes, sheets, strip, pipe and tubes (including tube rounds, squares, and hollows), drawn or extruded wire;</i></p> <p>b. <i>Cast material produced by casting in sand, die, metal, plaster or other types of moulds, including high pressure castings, sintered forms, and forms made by powder metallurgy;</i></p> <p><i>whether or not coated, plated, drilled or punched.</i></p> <p><i>Category 1C includes non-listed forms of those materials which are purportedly finished products but are in reality crude forms or semi-fabricated forms.</i></p>
1C001	<p>Materials specially designed for use as absorbers of electromagnetic waves, or intrinsically conductive polymers, as follows:</p> <p><u>N.B.</u></p> <p><i>See also Category Code 1C101.</i></p> <p>a. <i>Materials for absorbing frequencies exceeding <math>2 \times 10^8</math> Hz but less than <math>3 \times 10^{12}</math> Hz;</i></p> <p><u>Note 1</u></p> <p><i>Category Code 1C001.a. does not include:</i></p> <p>a. <i>Hair type absorbers, constructed of natural or synthetic fibres, with non-magnetic loading to provide absorption;</i></p> <p>b. <i>Absorbers having no magnetic loss and whose incident surface is non-planar in shape, including pyramids, cones, wedges and convoluted surfaces;</i></p> <p>c. <i>Planar absorbers, having all of the following characteristics:</i></p> <p>1. <i>Made from any of the following:</i></p>



Category Code	Item Description
	<p>a. Plastic foam materials (flexible or non-flexible) with carbon-loading, or organic materials, including binders, providing more than 5% echo compared with metal over a bandwidth exceeding <math>\pm 15\%</math> of the centre frequency of the incident energy, and not capable of withstanding temperatures exceeding 450 K (177°C); <u>or</u></p> <p>b. Ceramic materials providing more than 20% echo compared with metal over a bandwidth exceeding <math>\pm 15\%</math> of the centre frequency of the incident energy, and not capable of withstanding temperatures exceeding 800 K (527°C);</p> <p><u>Technical Note</u> Absorption test samples for Category Code 1C001.a. Note 1.c.1. should be a square at least 5 wavelengths of the centre frequency on a side and positioned in the far field of the radiating element.</p> <p>2. Tensile strength less than <math>7 \times 10^6</math> N/m<sup>2</sup>; <u>and</u></p> <p>3. Compressive strength less than <math>14 \times 10^6</math> N/m<sup>2</sup>;</p> <p>d. Planar absorbers made of sintered ferrite, having all of the following:</p> <p>1. A specific gravity exceeding 4.4; <u>and</u></p> <p>2. A maximum operating temperature of 548 K (275°C).</p> <p><u>Note 2</u> Nothing in Note 1 to Category Code 1C001.a. releases magnetic materials to provide absorption when contained in paint.</p> <p>b. Materials for absorbing frequencies exceeding <math>1.5 \times 10^{14}</math> Hz but less than <math>3.7 \times 10^{14}</math> Hz and not transparent to visible light;</p>

<i>Category Code</i>	<i>Item Description</i>
	<p><u>Note</u>  <i>Category Code 1C001.b. does not include materials, specially designed or formulated for any of the following applications:</i></p> <ul style="list-style-type: none"> <li><i>a. Laser marking of polymers; <u>or</u></i></li> <li><i>b. Laser welding of polymers.</i></li> </ul> <p><i>c. Intrinsically conductive polymeric materials with a ‘bulk electrical conductivity’ exceeding 10,000 S/m (Siemens per metre) or a ‘sheet (surface) resistivity’ of less than 100 ohms/square, based on any of the following polymers:</i></p> <ul style="list-style-type: none"> <li><i>1. Polyaniline;</i></li> <li><i>2. Polypyrrole;</i></li> <li><i>3. Polythiophene;</i></li> <li><i>4. Poly phenylene-vinylene; <u>or</u></i></li> <li><i>5. Poly thienylene-vinylene.</i></li> </ul> <p><u>Note</u>  <i>Category Code 1C001.c. does not include materials in a liquid form.</i></p> <p><u>Technical Note</u>  <i>‘Bulk electrical conductivity’ and ‘sheet (surface) resistivity’ should be determined using ASTM D-257 or national equivalents.</i></p>
1C002	<p>Metal alloys, metal alloy powder and alloyed materials, as follows:</p> <p><u>N.B.</u>  <i>See also Category Code 1C202.</i></p> <p><u>Note</u>  <i>Category Code 1C002 does not include metal alloys, metal alloy powder and alloyed materials for coating substrates.</i></p>

<i>Category Code</i>	<i>Item Description</i>
	<p data-bbox="475 459 670 488"><u>Technical Notes</u></p> <ol style="list-style-type: none"> <li data-bbox="475 497 1267 593">1. <i>The metal alloys in Category Code 1C002 are those containing a higher percentage by weight of the stated metal than of any other element.</i></li> <li data-bbox="475 604 1267 667">2. <i>'Stress-rupture life' is measured in accordance with ASTM standard E-139 or national equivalents.</i></li> <li data-bbox="475 678 1267 913">3. <i>'Low cycle fatigue life' is measured in accordance with ASTM standard E-606 'Recommended Practice for Constant-Amplitude Low-Cycle Fatigue Testing' or national equivalents. Testing should be axial with an average stress ratio equal to 1 and a stress-concentration factor (<math>K_t</math>) equal to 1. The average stress is defined as maximum stress minus minimum stress divided by maximum stress.</i></li> </ol> <ol style="list-style-type: none"> <li data-bbox="475 929 1267 1198">a. <i>Aluminides, as follows:</i> <ol style="list-style-type: none"> <li data-bbox="539 981 1267 1077">1. <i>Nickel aluminides containing a minimum of 15% by weight aluminium, a maximum of 38% by weight aluminium and at least one additional alloying element;</i></li> <li data-bbox="539 1099 1267 1198">2. <i>Titanium aluminides containing 10% by weight or more aluminium and at least one additional alloying element;</i></li> </ol> </li> <li data-bbox="475 1216 1267 1830">b. <i>Metal alloys, as follows, made from the powder or particulate material specified in Category Code 1C002.c.:</i> <ol style="list-style-type: none"> <li data-bbox="539 1301 1267 1534">1. <i>Nickel alloys having any of the following:</i> <ol style="list-style-type: none"> <li data-bbox="619 1350 1267 1413">a. <i>A 'stress-rupture life' of 10,000 hours or longer at 923 K (650°C) at a stress of 676 MPa; <u>or</u></i></li> <li data-bbox="619 1435 1267 1534">b. <i>A 'low cycle fatigue life' of 10,000 cycles or more at 823 K (550°C) at a maximum stress of 1,095 MPa;</i></li> </ol> </li> <li data-bbox="539 1552 1267 1785">2. <i>Niobium alloys having any of the following:</i> <ol style="list-style-type: none"> <li data-bbox="619 1601 1267 1664">a. <i>A 'stress-rupture life' of 10,000 hours or longer at 1,073 K (800°C) at a stress of 400 MPa; <u>or</u></i></li> <li data-bbox="619 1686 1267 1785">b. <i>A 'low cycle fatigue life' of 10,000 cycles or more at 973 K (700°C) at a maximum stress of 700 MPa;</i></li> </ol> </li> <li data-bbox="539 1803 1267 1830">3. <i>Titanium alloys having any of the following:</i></li> </ol> </li> </ol>

<i>Category Code</i>	<i>Item Description</i>
	<ul style="list-style-type: none"> <li>a. A 'stress-rupture life' of 10,000 hours or longer at 723 K (450°C) at a stress of 200 MPa; <u>or</u></li> <li>b. A 'low cycle fatigue life' of 10,000 cycles or more at 723 K (450°C) at a maximum stress of 400 MPa;</li> </ul> <p>4. Aluminium alloys having any of the following:</p> <ul style="list-style-type: none"> <li>a. A tensile strength of 240 MPa or more at 473 K (200°C); <u>or</u></li> <li>b. A tensile strength of 415 MPa or more at 298 K (25°C);</li> </ul> <p>5. Magnesium alloys having all of the following:</p> <ul style="list-style-type: none"> <li>a. A tensile strength of 345 MPa or more; <u>and</u></li> <li>b. A corrosion rate of less than 1 mm/year in 3% sodium chloride aqueous solution measured in accordance with ASTM standard G-31 or national equivalents;</li> </ul> <p>c. Metal alloy powder or particulate material, having all of the following:</p> <ul style="list-style-type: none"> <li>1. Made from any of the following composition systems:</li> </ul> <p><i>Technical Note</i>  <i>X in the following equals one or more alloying elements.</i></p> <ul style="list-style-type: none"> <li>a. Nickel alloys (Ni-Al-X, Ni-X-Al) qualified for turbine engine parts or components, i.e. with less than 3 non-metallic particles (introduced during the manufacturing process) larger than 100 µm in 10<sup>9</sup> alloy particles;</li> <li>b. Niobium alloys (Nb-Al-X or Nb-X-Al, Nb-Si-X or Nb-X-Si, Nb-Ti-X or Nb-X-Ti);</li> <li>c. Titanium alloys (Ti-Al-X or Ti-X-Al);</li> <li>d. Aluminium alloys (Al-Mg-X or Al-X-Mg, Al-Zn-X or Al-X-Zn, Al-Fe-X or Al-X-Fe); <u>or</u></li> <li>e. Magnesium alloys (Mg-Al-X or Mg-X-Al);</li> </ul>

<i>Category Code</i>	<i>Item Description</i>
	<ol style="list-style-type: none"> <li>2. Made in a controlled environment by any of the following processes:               <ol style="list-style-type: none"> <li>a. “Vacuum atomisation”;</li> <li>b. “Gas atomisation”;</li> <li>c. “Rotary atomisation”;</li> <li>d. “Splat quenching”;</li> <li>e. “Melt spinning” and “comminution”;</li> <li>f. “Melt extraction” and “comminution”; <u>or</u></li> <li>g. “Mechanical alloying”; <u>and</u></li> </ol> </li> <li>3. Capable of forming materials specified in Category Code 1C002.a. or 1C002.b.;</li> <li>d. Alloyed materials having all of the following:               <ol style="list-style-type: none"> <li>1. Made from any of the composition systems specified in Category Code 1C002.c.1.;</li> <li>2. In the form of uncomminuted flakes, ribbons or thin rods; <u>and</u></li> <li>3. Produced in a controlled environment by any of the following:                   <ol style="list-style-type: none"> <li>a. “Splat quenching”;</li> <li>b. “Melt spinning”; <u>or</u></li> <li>c. “Melt extraction”.</li> </ol> </li> </ol> </li> </ol>
1C003	<p>Magnetic metals, of all types and of whatever form, having any of the following:</p> <ol style="list-style-type: none"> <li>a. Initial relative permeability of 120,000 or more and a thickness of 0.05 mm or less;</li> </ol> <p><i><u>Technical Note</u></i>  <i>Measurement of initial relative permeability is that performed on fully annealed materials.</i></p> <ol style="list-style-type: none"> <li>b. Magnetostrictive alloys having any of the following:               <ol style="list-style-type: none"> <li>1. A saturation magnetostriction of more than <math>5 \times 10^{-4}</math>; <u>or</u></li> </ol> </li> </ol>

<i>Category Code</i>	<i>Item Description</i>
	<p>2. A magnetomechanical coupling factor (k) of more than 0.8; <u>or</u></p> <p>c. Amorphous or ‘nanocrystalline’ alloy strips, having all of the following:</p> <ol style="list-style-type: none"> <li>1. A composition having a minimum of 75% by weight of iron, cobalt or nickel;</li> <li>2. A saturation magnetic induction (<math>B_s</math>) of 1.6 T or more; <u>and</u></li> <li>3. Any of the following: <ol style="list-style-type: none"> <li>a. A strip thickness of 0.02 mm or less; <u>or</u></li> <li>b. An electrical resistivity of <math>2 \times 10^{-4}</math> ohm cm or more.</li> </ol> </li> </ol> <p><i>Technical Note</i>  ‘Nanocrystalline’ materials in Category Code 1C003.c. are those materials having a crystal grain size of 50 nm or less, as determined by X-ray diffraction.</p>
1C004	<p>Uranium titanium alloys or tungsten alloys with a “matrix” based on iron, nickel or copper, having all of the following:</p> <ol style="list-style-type: none"> <li>a. A density exceeding <math>17.5 \text{ g/cm}^3</math>;</li> <li>b. An elastic limit exceeding 880 MPa;</li> <li>c. An ultimate tensile strength exceeding 1,270 MPa; <u>and</u></li> <li>d. An elongation exceeding 8%.</li> </ol>
1C005	<p>“Superconductive” “composite” conductors in lengths exceeding 100 m or with a mass exceeding 100 g, as follows:</p> <ol style="list-style-type: none"> <li>a. “Superconductive” “composite” conductors containing one or more niobium-titanium ‘filaments’, having both of the following: <ol style="list-style-type: none"> <li>1. Embedded in a “matrix” other than a copper or copper-based mixed “matrix”; <u>and</u></li> <li>2. Having a cross-section area less than <math>0.28 \times 10^{-4} \text{ mm}^2</math> (6 <math>\mu\text{m}</math> in diameter for circular ‘filaments’);</li> </ol> </li> </ol>

<i>Category Code</i>	<i>Item Description</i>
	<p>b. “Superconductive” “composite” conductors consisting of one or more “superconductive” ‘filaments’ other than niobium-titanium, having all of the following:</p> <ol style="list-style-type: none"> <li>1. A “critical temperature” at zero magnetic induction exceeding 9.85 K (-263.31°C); <u>and</u></li> <li>2. Remaining in the “superconductive” state at a temperature of 4.2 K (-268.96°C) when exposed to a magnetic field oriented in any direction perpendicular to the longitudinal axis of conductor and corresponding to a magnetic induction of 12 T with critical current density exceeding 1,750 A/mm<sup>2</sup> on overall cross-section of the conductor;</li> </ol> <p>c. “Superconductive” “composite” conductors consisting of one or more “superconductive” ‘filaments’ which remain “superconductive” above 115 K (-158.16°C).</p> <p><u>Technical Note</u>  <i>For the purpose of Category Code 1C005, ‘filaments’ may be in wire, cylinder, film, tape or ribbon form.</i></p>
1C006	<p>Fluids and lubricating materials, as follows:</p> <p>a. Hydraulic fluids containing, as their principal ingredients, any of the following:</p> <ol style="list-style-type: none"> <li>1. Synthetic ‘silahydrocarbon oils’ having all of the following: <p><u>Technical Note</u>  <i>For the purpose of Category Code 1C006.a.1., ‘silahydrocarbon oils’ contain exclusively silicon, hydrogen and carbon.</i></p> <ol style="list-style-type: none"> <li>a. A ‘flash point’ exceeding 477 K (204°C);</li> <li>b. A ‘pour point’ at 239 K (-34°C) or less;</li> <li>c. A ‘viscosity index’ of 75 or more; <u>and</u></li> <li>d. A ‘thermal stability’ at 616 K (343°C); <u>or</u></li> </ol> </li> <li>2. ‘Chlorofluorocarbons’ having all of the following:</li> </ol>

<i>Category Code</i>	<i>Item Description</i>
	<p data-bbox="603 454 786 488"><u>Technical Note</u></p> <p data-bbox="603 499 1260 595"><i>For the purpose of Category Code 1C006.a.2., 'chlorofluorocarbons' contain exclusively carbon, fluorine and chlorine.</i></p> <ol style="list-style-type: none"> <li data-bbox="627 613 887 647">a. No 'flash point';</li> <li data-bbox="627 665 1259 730">b. An 'autogenous ignition temperature' exceeding 977 K (704°C);</li> <li data-bbox="627 748 1155 781">c. A 'pour point' at 219 K (-54°C) or less;</li> <li data-bbox="627 799 1142 833">d. A 'viscosity index' of 80 or more; <u>and</u></li> <li data-bbox="627 851 1203 884">e. A boiling point at 473 K (200°C) or higher;</li> </ol> <ol style="list-style-type: none"> <li data-bbox="475 902 1260 967">b. Lubricating materials containing, as their principal ingredients, any of the following: <ol style="list-style-type: none"> <li data-bbox="544 983 1260 1079">1. Phenylene or alkylphenylene ethers or thio-ethers, or their mixtures, containing more than two ether or thio-ether functions or mixtures thereof; <u>or</u></li> <li data-bbox="544 1097 1260 1193">2. Fluorinated silicone fluids with a kinematic viscosity of less than 5,000 mm<sup>2</sup>/s (5,000 centistokes) measured at 298 K (25°C);</li> </ol> </li> <li data-bbox="475 1211 1260 1245">c. Damping or flotation fluids having all of the following: <ol style="list-style-type: none"> <li data-bbox="544 1263 895 1296">1. Purity exceeding 99.8%;</li> <li data-bbox="544 1314 1260 1379">2. Containing less than 25 particles of 200 µm or larger in size per 100 ml; <u>and</u></li> <li data-bbox="544 1397 1260 1431">3. Made from at least 85% of any of the following: <ol style="list-style-type: none"> <li data-bbox="627 1449 1260 1514">a. Dibromotetrafluoroethane (25497-30-7, 124-73-2, 27336-23-8);</li> <li data-bbox="627 1532 1260 1597">b. Polychlorotrifluoroethylene (oily and waxy modifications only); <u>or</u></li> <li data-bbox="627 1615 1027 1648">c. Polybromotrifluoroethylene;</li> </ol> </li> </ol> </li> <li data-bbox="475 1666 1260 1731">d. Fluorocarbon electronic cooling fluids having all of the following: <ol style="list-style-type: none"> <li data-bbox="544 1749 1260 1814">1. Containing 85% by weight or more of any of the following, or mixtures thereof: <ol style="list-style-type: none"> <li data-bbox="627 1832 1260 1897">a. Monomeric forms of perfluoropolyalkylether-triazines or perfluoroaliphatic-ethers;</li> </ol> </li> </ol> </li> </ol>



Category Code	Item Description
	<p data-bbox="539 454 1139 734">           b. Perfluoroalkylamines;            c. Perfluorocycloalkanes; <u>or</u>            d. Perfluoroalkanes;            2. Density at 298 K (25°C) of 1.5 g/ml or more;            3. In a liquid state at 273 K (0°C); <u>and</u>            4. Containing 60% or more by weight of fluorine.         </p> <p data-bbox="539 757 1267 857"> <u>Note</u>  <i>Category Code 1C006.d. does not apply to materials specified and packaged as medical products.</i> </p> <p data-bbox="475 880 1267 947"> <u>Technical Note</u>  <i>For the purpose of Category Code 1C006:</i> </p> <p data-bbox="475 969 1267 1283">           a. 'Flash point' is determined using the Cleveland Open Cup Method described in ASTM D-92 or national equivalents;            b. 'Pour point' is determined using the method described in ASTM D-97 or national equivalents;            c. 'Viscosity index' is determined using the method described in ASTM D-2270 or national equivalents;            d. 'Thermal stability' is determined by the following test procedure or national equivalents:         </p> <p data-bbox="539 1305 1267 1429"> <i>Twenty ml of the fluid under test is placed in a 46 ml type 317 stainless steel chamber containing one each of 12.5 mm (nominal) diameter balls of M-10 tool steel, 52,100 steel and naval bronze (60% Cu, 39% Zn, 0.75% Sn);</i> </p> <p data-bbox="539 1451 1267 1552"> <i>The chamber is purged with nitrogen, sealed at atmospheric pressure and the temperature raised to and maintained at 644 ± 6 K (371 ± 6°C) for six hours;</i> </p> <p data-bbox="539 1574 1267 1664"> <i>The specimen will be considered thermally stable if, on completion of the above procedure, all of the following conditions are met:</i> </p> <p data-bbox="539 1686 1267 1883">           1. The loss in weight of each ball is less than 10 mg/mm<sup>2</sup> of ball surface;            2. The change in original viscosity as determined at 311 K (38°C) is less than 25%; <u>and</u>            3. The total acid or base number is less than 0.40;         </p>

<i>Category Code</i>	<i>Item Description</i>
1C007	<p data-bbox="475 454 1268 521">e. 'Autogenous ignition' temperature is determined using the method described in ASTM E-659 or national equivalents.</p> <p data-bbox="475 589 1268 689">Ceramic base materials, non-“composite” ceramic materials, ceramic-“matrix”, “composite” materials and precursor materials, as follows:</p> <p data-bbox="475 701 531 734"><u>N.B.</u></p> <p data-bbox="475 745 858 779"><i>See also Category Code 1C107.</i></p> <p data-bbox="475 790 1268 969">a. Base materials of single or complex borides of titanium having total metallic impurities, excluding intentional additions, of less than 5,000 ppm, an average particle size equal to or less than 5 µm and no more than 10% of the particles larger than 10 µm;</p> <p data-bbox="475 981 1268 1081">b. Non-“composite” ceramic materials in crude or semi-fabricated form, composed of borides of titanium with a density of 98% or more of the theoretical density;</p> <p data-bbox="475 1093 531 1126"><u>Note</u></p> <p data-bbox="475 1137 1169 1171"><i>Category Code 1C007.b. does not include abrasives.</i></p> <p data-bbox="475 1182 1268 1283">c. Ceramic-ceramic “composite” materials with a glass or oxide-“matrix” and reinforced with fibres having all of the following:</p> <ol data-bbox="539 1305 1268 1619" style="list-style-type: none"> <li data-bbox="539 1305 1114 1339">1. Made from any of the following materials: <ol data-bbox="619 1350 866 1541" style="list-style-type: none"> <li data-bbox="619 1350 754 1384">a. Si-N;</li> <li data-bbox="619 1395 754 1429">b. Si-C;</li> <li data-bbox="619 1440 866 1473">c. Si-Al-O-N; <u>or</u></li> <li data-bbox="619 1485 842 1541">d. Si-O-N; <u>and</u></li> </ol> </li> <li data-bbox="539 1552 1268 1619">2. Having a “specific tensile strength” exceeding <math>12.7 \times 10^3</math> m;</li> </ol> <p data-bbox="475 1630 1268 1765">d. Ceramic-ceramic “composite” materials, with or without a continuous metallic phase, incorporating particles, whiskers or fibres, where carbides or nitrides of silicon, zirconium or boron form the “matrix”;</p>

<i>Category Code</i>	<i>Item Description</i>
	<p>e. Precursor materials (i.e. special purpose polymeric or metallo-organic materials) for producing any phase or phases of the materials specified in Category Code 1C007.c., as follows:</p> <ol style="list-style-type: none"> <li>1. Polydiorganosilanes (for producing silicon carbide);</li> <li>2. Polysilazanes (for producing silicon nitride);</li> <li>3. Polycarbosilazanes (for producing ceramics with silicon, carbon and nitrogen components);</li> </ol> <p>f. Ceramic-ceramic “composite” materials with an oxide or glass “matrix” reinforced with continuous fibres from any of the following systems:</p> <ol style="list-style-type: none"> <li>1. Al<sub>2</sub>O<sub>3</sub> (1344-28-1); <u>or</u></li> <li>2. Si-C-N.</li> </ol> <p><i>Note</i>  <i>Category Code 1C007.f. does not include “composites” containing fibres from these systems with a fibre tensile strength of less than 700 MPa at 1,273 K (1,000°C) or fibre tensile creep resistance of more than 1% creep strain at 100 MPa load and 1,273 K (1,000°C) for 100 hours.</i></p>
1C008	<p>Non-fluorinated polymeric substances as follows:</p> <p>a. Imides, as follows:</p> <ol style="list-style-type: none"> <li>1. Bismaleimides;</li> <li>2. Aromatic polyamide-imides (PAI) having a ‘glass transition temperature (T<sub>g</sub>)’ exceeding 563 K (290°C);</li> <li>3. Aromatic polyimides having a ‘glass transition temperature (T<sub>g</sub>)’ exceeding 505 K (232°C);</li> <li>4. Aromatic polyetherimides having a ‘glass transition temperature (T<sub>g</sub>)’ exceeding 563 K (290°C);</li> </ol> <p><i>Note</i>  <i>Category Code 1C008.a. includes substances in liquid or solid “fusible” form, including resin, powder, pellet, film, sheet, tape or ribbon.</i></p>

Category Code	Item Description
	<p><u>N.B.</u> For non-“fusible” aromatic polyimides in film, sheet, tape or ribbon form, see Category Code 1A003.</p> <p>b. Not used;</p> <p>c. Not used;</p> <p>d. Polyarylene ketones;</p> <p>e. Polyarylene sulphides, where the arylene group is biphenylene, triphenylene or combinations thereof;</p> <p>f. Polybiphenylenethersulphone having a ‘glass transition temperature (<math>T_g</math>)’ exceeding 563 K (290°C).</p> <p><u>Technical Notes</u></p> <p>1. The ‘glass transition temperature (<math>T_g</math>)’ for Category Code 1C008.a.2. thermoplastic materials and Category Code 1C008.a.4. materials is determined using the method described in ISO 11357-2 (1999) or national equivalents.</p> <p>2. The ‘glass transition temperature (<math>T_g</math>)’ for Category Code 1C008.a.2. thermosetting materials and Category Code 1C008.a.3. materials is determined using the 3-point bend method described in ASTM D 7028-07 or equivalent national standard. The test is to be performed using a dry test specimen which has attained a minimum of 90% degree of cure as specified by ASTM E 2160-04 or equivalent national standard, and was cured using the combination of standard and post-cure processes that yield the highest <math>T_g</math>.</p>
1C009	<p>Unprocessed fluorinated compounds as follows:</p> <p>a. Copolymers of vinylidene fluoride having 75% or more beta crystalline structure without stretching;</p> <p>b. Fluorinated polyimides containing 10% by weight or more of combined fluorine;</p> <p>c. Fluorinated phosphazene elastomers containing 30% by weight or more of combined fluorine.</p>

<i>Category Code</i>	<i>Item Description</i>
1C010	<p>“Fibrous or filamentary materials”, as follows:</p> <p><u>N.B.</u>  <i>See also Category Codes 1C210 and 9C110.</i></p> <p>a. Organic “fibrous or filamentary materials”, having both of the following:</p> <ol style="list-style-type: none"> <li>1. “Specific modulus” exceeding <math>12.7 \times 10^6</math> m; <u>and</u></li> <li>2. “Specific tensile strength” exceeding <math>23.5 \times 10^4</math> m;</li> </ol> <p><u>Note</u>  <i>Category Code 1C010.a. does not include polyethylene.</i></p> <p>b. Carbon “fibrous or filamentary materials”, having both of the following:</p> <ol style="list-style-type: none"> <li>1. “Specific modulus” exceeding <math>14.65 \times 10^6</math> m; <u>and</u></li> <li>2. “Specific tensile strength” exceeding <math>26.82 \times 10^4</math> m;</li> </ol> <p><u>Note</u>  <i>Category Code 1C010.b. does not include:</i></p> <ol style="list-style-type: none"> <li>a. “Fibrous or filamentary materials”, for the repair of “civil aircraft” structures or laminates, having all of the following: <ol style="list-style-type: none"> <li>1. An area not exceeding <math>1 \text{ m}^2</math>;</li> <li>2. A length not exceeding 2.5 m; <u>and</u></li> <li>3. A width exceeding 15 mm;</li> </ol> </li> <li>b. Mechanically chopped, milled or cut carbon “fibrous or filamentary materials” 25 mm or less in length.</li> </ol> <p>c. Inorganic “fibrous or filamentary materials”, having both of the following:</p> <ol style="list-style-type: none"> <li>1. “Specific modulus” exceeding <math>2.54 \times 10^6</math> m; <u>and</u></li> <li>2. Melting, softening, decomposition or sublimation point exceeding 1,922 K (1,649°C) in an inert environment;</li> </ol> <p><u>Note</u>  <i>Category Code 1C010.c. does not include:</i></p>

Category Code	Item Description
	<p>a. <i>Discontinuous, multiphase, polycrystalline alumina fibres in chopped fibre or random mat form, containing 3% by weight or more silica, with a “specific modulus” of less than <math>10 \times 10^6</math> m;</i></p> <p>b. <i>Molybdenum and molybdenum alloy fibres;</i></p> <p>c. <i>Boron fibres;</i></p> <p>d. <i>Discontinuous ceramic fibres with a melting, softening, decomposition or sublimation point lower than 2,043 K (1,770°C) in an inert environment.</i></p> <p><u>Technical Notes</u></p> <p>1. <i>For the purpose of calculating “specific tensile strength”, “specific modulus” or specific weight of “fibrous or filamentary materials” in Category Code 1C010.a., 1C010.b. or 1C010.c., the tensile strength and modulus should be determined by using Method A described in ISO 10618 (2004) or national equivalents.</i></p> <p>2. <i>The assessment of the “specific tensile strength”, “specific modulus” or specific weight of non-unidirectional “fibrous or filamentary materials” (e.g. fabrics, random mats or braids) in Category Code 1C010 is to be based on the mechanical properties of the constituent unidirectional monofilaments (e.g. monofilaments, yarns, rovings or tows) prior to processing into the non-unidirectional “fibrous or filamentary materials”.</i></p> <p>d. “Fibrous or filamentary materials”, having any of the following:</p> <ol style="list-style-type: none"> <li>1. Composed of any of the following: <ol style="list-style-type: none"> <li>a. Polyetherimides specified in Category Code 1C008.a.; <u>or</u></li> <li>b. Materials specified in Category Codes 1C008.d. to 1C008.f.; <u>or</u></li> </ol> </li> <li>2. Composed of materials specified in Category Code 1C010.d.1.a. or 1C010.d.1.b. and “commingled” with other fibres specified in Category Code 1C010.a., 1C010.b. or 1C010.c.;</li> </ol>

<i>Category Code</i>	<i>Item Description</i>
	<p>e. Fully or partially resin-impregnated or pitch-impregnated “fibrous or filamentary materials” (prepregs), metal or carbon-coated “fibrous or filamentary materials” (preforms) or “carbon fibre preforms”, having all of the following:</p> <ol style="list-style-type: none"> <li>1. Having any of the following:           <ol style="list-style-type: none"> <li>a. Inorganic “fibrous or filamentary materials” specified in Category Code 1C010.c.; <u>or</u></li> <li>b. Organic or carbon “fibrous or filamentary materials”, having all of the following:               <ol style="list-style-type: none"> <li>1. “Specific modulus” exceeding <math>10.15 \times 10^6</math> m; <u>and</u></li> <li>2. “Specific tensile strength” exceeding <math>17.7 \times 10^4</math> m; <u>and</u></li> </ol> </li> </ol> </li> <li>2. Having any of the following:           <ol style="list-style-type: none"> <li>a. Resin or pitch specified in Category Code 1C008 or 1C009.b.;</li> <li>b. ‘Dynamic Mechanical Analysis glass transition temperature (DMA <math>T_g</math>)’ equal to or exceeding 453 K (180°C) and having a phenolic resin; <u>or</u></li> <li>c. ‘Dynamic Mechanical Analysis glass transition temperature (DMA <math>T_g</math>)’ equal to or exceeding 505 K (232°C) and having a resin or pitch, not specified in Category Code 1C008 or 1C009.b., and not being a phenolic resin.</li> </ol> </li> </ol> <p><u>Note 1</u>  <i>Metal or carbon-coated “fibrous or filamentary materials” (preforms) or “carbon fibre preforms”, not impregnated with resin or pitch, are specified by “fibrous or filamentary materials” in Category Code 1C010.a., 1C010.b. or 1C010.c.</i></p> <p><u>Note 2</u>  <i>Category Code 1C010.e. does not include:</i></p> <ol style="list-style-type: none"> <li>a. Epoxy resin “matrix” impregnated carbon “fibrous or filamentary materials” (prepregs) for the repair of “civil aircraft” structures or laminates, having all of the following;</li> </ol>

Category Code	Item Description
	<ol style="list-style-type: none"> <li>1. An area not exceeding 1 m<sup>2</sup>;</li> <li>2. A length not exceeding 2.5 m; <u>and</u></li> <li>3. A width exceeding 15 mm.</li> </ol> <p>b. Fully or partially resin-impregnated or pitch-impregnated mechanically chopped, milled or cut carbon “fibrous or filamentary materials” 25 mm or less in length when using a resin or pitch other than those specified by Category Code 1C008 or 1C009.b.</p> <p><u>Technical Note</u> The ‘Dynamic Mechanical Analysis glass transition temperature (DMA T<sub>g</sub>)’ for materials specified by Category Code 1C010.e. is determined using the method described in ASTM D 7028-07, or equivalent national standard, on a dry test specimen. In the case of thermoset materials, degree of cure of a dry test specimen is a minimum of 90% as defined by ASTM E 2160-04 or equivalent national standard.</p>
1C011	<p>Metals and compounds, as follows:</p> <p><u>N.B.</u> See also Division 2 of Part I of this Schedule and Category Code 1C111.</p> <p>a. Metals in particle sizes of less than 60 µm whether spherical, atomised, spheroidal, flaked or ground, manufactured from material consisting of 99% or more of zirconium, magnesium and alloys thereof;</p> <p><u>Technical Note</u> The natural content of hafnium in the zirconium (typically 2% to 7%) is counted with the zirconium.</p> <p><u>Note</u> Category Code 1C011.a. includes metals or alloys listed therein whether or not they are encapsulated in aluminium, magnesium, zirconium or beryllium.</p> <p>b. Boron or boron alloys, with a particle size of 60 µm or less, as follows;</p> <ol style="list-style-type: none"> <li>1. Boron with a purity of 85% by weight or more;</li> </ol>



<i>Category Code</i>	<i>Item Description</i>
	<p>2. Boron alloys with a boron content of 85% by weight or more;</p> <p><u>Note</u>  <i>Category Code 1C011.b. includes metals or alloys listed therein whether or not they are encapsulated in aluminium, magnesium, zirconium or beryllium.</i></p> <p>c. Guanidine nitrate (506-93-4);</p> <p>d. Nitroguanidine (NQ) (556-88-7).</p> <p><u>N.B.</u>  <i>See also Division 2 of Part I of this Schedule for metal powders mixed with other substances to form a mixture formulated for military purposes.</i></p>
1C012	<p>Materials as follows:</p> <p><u>Technical Note</u>  <i>These materials are typically used for nuclear heat sources.</i></p> <p>a. Plutonium in any form with a plutonium isotopic assay of plutonium-238 of more than 50% by weight;</p> <p><u>Note</u>  <i>Category Code 1C012.a. does not include:</i></p> <p><i>a. Shipments with a plutonium content of 1 g or less;</i></p> <p><i>b. Shipments of 3 “effective grammes” or less when contained in a sensing component in instruments.</i></p> <p>b. “Previously separated” neptunium-237 in any form.</p> <p><u>Note</u>  <i>Category Code 1C012.b. does not include shipments with a neptunium-237 content of 1 g or less.</i></p>
1C101	<p>Materials and devices for reduced observables such as radar reflectivity, ultraviolet/infrared signatures and acoustic signatures, other than those specified in Category Code 1C001, usable in ‘missiles’, “missile” subsystems or unmanned aerial vehicles specified in Category Code 9A012.</p>

Category Code	Item Description
	<p><u>Note 1</u>            Category Code 1C101 includes:</p> <ul style="list-style-type: none"> <li>a. Structural materials and coatings specially designed for reduced radar reflectivity;</li> <li>b. Coatings, including paints, specially designed for reduced or tailored reflectivity or emissivity in the microwave, infrared or ultraviolet regions of the electromagnetic spectrum.</li> </ul> <p><u>Note 2</u>            Category Code 1C101 does not include coatings when specially used for the thermal control of satellites.</p> <p><u>Technical Note</u>            In Category Code 1C101, 'missile' means complete rocket systems and unmanned aerial vehicle systems capable of a range exceeding 300 km.</p>
1C102	Resaturated pyrolysed carbon-carbon materials designed for space launch vehicles specified in Category Code 9A004 or sounding rockets specified in Category Code 9A104.
1C107	Graphite and ceramic materials, other than those specified in Category Code 1C007, as follows: <ul style="list-style-type: none"> <li>a. Fine grain graphites with a bulk density of 1.72 g/cm<sup>3</sup> or greater, measured at 288 K (15°C), and having a grain size of 100 µm or less, usable for rocket nozzles and re-entry vehicle nose tips, which can be machined to any of the following products:               <ul style="list-style-type: none"> <li>1. Cylinders having a diameter of 120 mm or greater and a length of 50 mm or greater;</li> <li>2. Tubes having an inner diameter of 65 mm or greater and a wall thickness of 25 mm or greater and a length of 50 mm or greater; <u>or</u></li> <li>3. Blocks having a size of 120 mm × 120 mm × 50 mm or greater;</li> </ul> </li> </ul>

<i>Category Code</i>	<i>Item Description</i>
	<p><u><i>N.B.</i></u> <i>See also Category Code 0C004.</i></p> <p>b. Pyrolytic or fibrous reinforced graphites, usable for rocket nozzles and re-entry vehicle nose tips usable in “missiles”, space launch vehicles specified in Category Code 9A004 or sounding rockets specified in Category Code 9A104;</p> <p><u><i>N.B.</i></u> <i>See also Category Code 0C004.</i></p> <p>c. Ceramic composite materials (dielectric constant less than 6 at any frequency from 100 MHz to 100 GHz) for use in radomes usable in “missiles”, space launch vehicles specified in Category Code 9A004 or sounding rockets specified in Category Code 9A104;</p> <p>d. Bulk machinable silicon-carbide reinforced unfired ceramic, usable for nose tips usable in “missiles”, space launch vehicles specified in Category Code 9A004 or sounding rockets specified in Category Code 9A104;</p> <p>e. Reinforced silicon-carbide ceramic composites, usable for nose tips, re-entry vehicles and nozzle flaps usable in “missiles”, space launch vehicles specified in Category Code 9A004 or sounding rockets specified in Category Code 9A104.</p>
1C111	<p>Propellants and constituent chemicals for propellants, other than those specified in Category Code 1C011, as follows:</p> <p>a. Propulsive substances:</p> <ol style="list-style-type: none"> <li>1. Spherical or spheroidal aluminium powder, other than that specified in Division 2 of Part I of this Schedule, in particle size of less than 200 µm and an aluminium content of 97% by weight or more, if at least 10% of the total weight is made up of particles of less than 63 µm, according to ISO 2591:1988 or national equivalents;</li> </ol> <p><u><i>Technical Note</i></u> <i>A particle size of 63 µm (ISO R-565) corresponds to 250 mesh (Tyler) or 230 mesh (ASTM standard E-11).</i></p>

<i>Category Code</i>	<i>Item Description</i>
	<p>2. Metal powders, other than that specified in Division 2 of Part I of this Schedule, as follows:</p> <p>a. Metal powders of zirconium, beryllium or magnesium, or alloys of these metals, if at least 90% of the total particles by particle volume or weight are made up of particles of less than 60 µm (determined by measurement techniques such as using a sieve, laser diffraction or optical scanning), whether spherical, atomised, spheroidal, flaked or ground, consisting 97% by weight or more of any of the following:</p> <ol style="list-style-type: none"> <li>1. Zirconium;</li> <li>2. Beryllium; <u>or</u></li> <li>3. Magnesium;</li> </ol> <p><i>Technical Note</i>  <i>The natural content of hafnium in the zirconium (typically 2% to 7%) is counted with the zirconium.</i></p> <p>b. Metal powders of either boron or boron alloys with a boron content of 85% or more by weight, if at least 90% of the total particles by particle volume or weight are made up of particles of less than 60 µm (determined by measurement techniques such as using a sieve, laser diffraction or optical scanning), whether spherical, atomised, spheroidal, flaked or ground;</p> <p><i>Note</i>  <i>Category Codes 1C111a.2.a. and 1C111a.2.b. include any powder mixture with a multimodal particle distribution (e.g. a mixture of different grain sizes) if one or more modes in the powder mixture are specified in Division 2 of Part II of this Schedule.</i></p> <p>3. Oxidiser substances usable in liquid propellant rocket engines as follows:</p> <ol style="list-style-type: none"> <li>a. Dinitrogen trioxide (10544-73-7);</li> <li>b. Nitrogen dioxide (10102-44-0)/dinitrogen tetroxide (10544-72-6);</li> </ol>

<i>Category Code</i>	<i>Item Description</i>
	<p>c. Dinitrogen pentoxide (10102-03-1);</p> <p>d. Mixed Oxides of Nitrogen (MON);</p> <p><i>Technical Note</i>  <i>Mixed Oxides of Nitrogen (MON) are solutions of Nitric Oxide (NO) in Dinitrogen Tetroxide/ Nitrogen Dioxide (N<sub>2</sub>O<sub>4</sub>/NO<sub>2</sub>) that can be used in missile systems. There are a range of compositions that can be denoted as MON<sub>i</sub> or MON<sub>ij</sub>, where i and j are integers representing the percentage of Nitric Oxide in the mixture (e.g. MON<sub>3</sub> contains 3% Nitric Oxide, MON<sub>25</sub> 25% Nitric Oxide. An upper limit is MON<sub>40</sub>, 40% by weight).</i></p> <p>e. See Inhibited Red Fuming Nitric Acid (IRFNA) in Division 2 of Part I of this Schedule;</p> <p>f. See compounds composed of fluorine and one or more of other halogens, oxygen or nitrogen in Division 2 of Part I of this Schedule and Category Code 1C238;</p> <p>4. Hydrazine derivatives as follows:</p> <p><i>N.B.</i>  <i>See also Division 2 of Part I of this Schedule.</i></p> <p>a. Trimethylhydrazine (1741-01-1);</p> <p>b. Tetramethylhydrazine (6415-12-9);</p> <p>c. N,N diallylhydrazine;</p> <p>d. Allylhydrazine (7422-78-8);</p> <p>e. Ethylene dihydrazine;</p> <p>f. Monomethylhydrazine dinitrate;</p> <p>g. Unsymmetrical dimethylhydrazine nitrate;</p> <p>h. Hydrazinium azide (14546-44-2);</p> <p>i. Dimethylhydrazinium azide;</p> <p>j. Hydrazinium dinitrate;</p> <p>k. Diimido oxalic acid dihydrazine (3457-37-2);</p>

<i>Category Code</i>	<i>Item Description</i>
	<p>l. 2-hydroxyethylhydrazine nitrate (HEHN);</p> <p>m. See Hydrazinium perchlorate in Division 2 of Part I of this Schedule;</p> <p>n. Hydrazinium diperchlorate (13812-39-0);</p> <p>o. Methylhydrazine nitrate (MHN);</p> <p>p. Diethylhydrazine nitrate (DEHN);</p> <p>q. 3,6-dihydrazino tetrazine nitrate (1,4-dihydrazine nitrate) (DHTN);</p> <p>5. High energy density materials, other than that specified in the Division 2 of Part I of this Schedule, usable in ‘missiles’ or unmanned aerial vehicles specified in Category Code 9A012 as follows:</p> <p>a. Mixed fuel that incorporate both solid and liquid fuels, such as boron slurry, having a mass-based energy density of <math>40 \times 10^6</math> J/kg or greater;</p> <p>b. Other high energy density fuels and fuel additives (e.g. cubane, ionic solutions, JP-10) having a volume-based energy density of <math>37.5 \times 10^9</math> J/m<sup>3</sup> or greater, measured at 20°C and one atmosphere (101.325 kPa) pressure;</p> <p><i>Note</i>  <i>Category Code 1C111.a.5.b. does not include fossil refined fuels and biofuels produced from vegetables, including fuels for engines certified for use in civil aviation, unless specially formulated for ‘missiles’ or unmanned aerial vehicles specified in Category Code 9A012.</i></p> <p><i>Technical Note</i>  <i>In Category Code 1C111.a.5., ‘missile’ means complete rocket systems and unmanned aerial vehicle systems capable of a range exceeding 300 km.</i></p> <p>b. Polymeric substances:</p> <p>1. Carboxy-terminated polybutadiene (including carboxyl-terminated polybutadiene) (CTPB);</p>

<i>Category Code</i>	<i>Item Description</i>
	<ol style="list-style-type: none"> <li>2. Hydroxy-terminated polybutadiene (including hydroxyl-terminated polybutadiene) (HTPB), other than that specified in Division 2 of Part I of this Schedule;</li> <li>3. Polybutadiene-acrylic acid (PBAA);</li> <li>4. Polybutadiene-acrylic acid-acrylonitrile (PBAN);</li> <li>5. Polytetrahydrofuran polyethylene glycol (TPEG);</li> </ol> <p><i>Technical Note</i>  <i>Polytetrahydrofuran polyethylene glycol (TPEG) is a block co-polymer of poly 1,4-Butanediol and polyethylene glycol (PEG).</i></p> <p>c. Other propellant additives and agents:</p> <ol style="list-style-type: none"> <li>1. See carboranes, decaboranes, pentaboranes and derivatives thereof in Division 2 of Part I of this Schedule;</li> <li>2. Triethylene glycol dinitrate (TEGDN) (111-22-8);</li> <li>3. 2-Nitrodiphenylamine (119-75-5);</li> <li>4. Trimethylolethane trinitrate (TMETN) (3032-55-1);</li> <li>5. Diethylene glycol dinitrate (DEGDN) (693-21-0);</li> <li>6. Ferrocene derivatives as follows: <ol style="list-style-type: none"> <li>a. See catocene in Division 2 of Part I of this Schedule;</li> <li>b. See ethyl ferrocene in Division 2 of Part I of this Schedule;</li> <li>c. See propyl ferrocene in Division 2 of Part I of this Schedule;</li> <li>d. See n-butyl ferrocene in Division 2 of Part I of this Schedule;</li> <li>e. See pentyl ferrocene in Division 2 of Part I of this Schedule;</li> <li>f. See dicyclopentyl ferrocene in Division 2 of Part I of this Schedule;</li> <li>g. See dicyclohexyl ferrocene in Division 2 of Part I of this Schedule;</li> </ol> </li> </ol>

<i>Category Code</i>	<i>Item Description</i>
	<p>h. See diethyl ferrocene in Division 2 of Part I of this Schedule;</p> <p>i. See dipropyl ferrocene in Division 2 of Part I of this Schedule;</p> <p>j. See dibutyl ferrocene in Division 2 of Part I of this Schedule;</p> <p>k. See dihexyl ferrocene in Division 2 of Part I of this Schedule;</p> <p>l. See acetyl ferrocene /1,1'-diacetyl ferrocene in Division 2 of Part I of this Schedule;</p> <p>m. See ferrocene carboxylic acids in Division 2 of Part I of this Schedule;</p> <p>n. See butacene in Division 2 of Part I of this Schedule;</p> <p>o. Other ferrocene derivatives usable as rocket propellant burning rate modifiers, other than those specified in Division 2 of Part I of this Schedule;</p> <p><u>Note</u> Category Code 1C111.c.6.o. does not include ferrocene derivatives that contain a six carbon aromatic functional group attached to the ferrocene molecule.</p> <p>7. 4,5 diazidomethyl-2-methyl-1,2,3-triazole (iso-DAMTR), other than that specified in Division 2 of Part I of this Schedule.</p> <p><u>Note</u> For propellants and constituent chemicals for propellants not specified in Category Code 1C111, see Division 2 of Part I of this Schedule.</p>
1C116	<p>Maraging steels, usable in 'missiles', having both of the following:</p> <p><u>N.B.</u> See also Category Code 1C216.</p>



<i>Category Code</i>	<i>Item Description</i>
	<p>a. An ultimate tensile strength, measured at 293 K (20°C), equal to or greater than:</p> <ol style="list-style-type: none"> <li>1. 0.9 GPa in the solution annealed stage; <u>or</u></li> <li>2. 1.5 GPa in the precipitation hardened stage; <u>and</u></li> </ol> <p>b. Any of the following forms:</p> <ol style="list-style-type: none"> <li>1. Sheet, plate or tubing with a wall or plate thickness equal to or less than 5 mm;</li> <li>2. Tubular forms with a wall thickness equal to or less than 50 mm and having an inner diameter equal to or greater than 270 mm.</li> </ol> <p><u>Technical Notes</u></p> <ol style="list-style-type: none"> <li>1. <i>Maraging steels are iron alloys:</i> <ol style="list-style-type: none"> <li>a. <i>Generally characterised by high nickel, very low carbon content and the use of substitutional elements or precipitates to produce strengthening and age-hardening of the alloy; <u>and</u></i></li> <li>b. <i>Subjected to heat treatment cycles to facilitate the martensitic transformation process (solution annealed stage) and subsequently age hardened (precipitation hardened stage).</i></li> </ol> </li> <li>2. <i>In Category Code 1C116, 'missile' means complete rocket systems and unmanned aerial vehicle systems capable of a range exceeding 300 km.</i></li> </ol>
1C117	<p>Materials for the fabrication of 'missiles' components as follows:</p> <ol style="list-style-type: none"> <li>a. Tungsten and alloys in particulate form with a tungsten content of 97% by weight or more and a particle size of <math>50 \times 10^{-6}</math> m (50 <math>\mu</math>m) or less;</li> <li>b. Molybdenum and alloys in particulate form with a molybdenum content of 97% by weight or more and a particle size of <math>50 \times 10^{-6}</math> m (50 <math>\mu</math>m) or less;</li> <li>c. Tungsten materials in solid form having all of the following: <ol style="list-style-type: none"> <li>1. Any of the following material compositions:</li> </ol> </li> </ol>

<i>Category Code</i>	<i>Item Description</i>
	<ul style="list-style-type: none"> <li>a. Tungsten and alloys containing 97% by weight or more of tungsten;</li> <li>b. Copper infiltrated tungsten containing 80% by weight or more of tungsten; <u>or</u></li> <li>c. Silver infiltrated tungsten containing 80% by weight or more of tungsten; <u>and</u></li> </ul> <p>2. Able to be machined to any of the following products:</p> <ul style="list-style-type: none"> <li>a. Cylinders having a diameter of 120 mm or greater and a length of 50 mm or greater;</li> <li>b. Tubes having an inner diameter of 65 mm or greater and a wall thickness of 25 mm or greater and a length of 50 mm or greater; <u>or</u></li> <li>c. Blocks having a size of 120 mm by 120 mm by 50 mm or greater.</li> </ul> <p><i><u>Technical Note</u></i>  <i>In Category Code 1C117, 'missile' means complete rocket systems and unmanned aerial vehicle systems capable of a range exceeding 300 km.</i></p>
1C118	<p>Titanium-stabilised duplex stainless steel (Ti-DSS) having all of the following:</p> <ul style="list-style-type: none"> <li>a. Having all of the following characteristics: <ul style="list-style-type: none"> <li>1. Containing 17-23% by weight chromium and 4.5-7% by weight nickel;</li> <li>2. Having a titanium content of greater than 0.10% by weight; <u>and</u></li> <li>3. A ferritic-austenitic microstructure (also referred to as a two-phase microstructure) of which at least 10% is austenite by volume (according to ASTM E-1181-87 or national equivalents); <u>and</u></li> </ul> </li> <li>b. Having any of the following forms: <ul style="list-style-type: none"> <li>1. Ingots or bars having a size of 100 mm or more in each dimension;</li> </ul> </li> </ul>

<i>Category Code</i>	<i>Item Description</i>
1C202	<p data-bbox="539 454 1264 521">2. Sheets having a width of 600 mm or more and a thickness of 3 mm or less; <u>or</u></p> <p data-bbox="539 533 1264 600">3. Tubes having an outer diameter of 600 mm or more and a wall thickness of 3 mm or less.</p> <p data-bbox="475 667 1264 734">Alloys, other than those specified in Category Code 1C002.b.3. or .b.4., as follows:</p> <p data-bbox="475 757 1264 824">a. Aluminium alloys having both of the following characteristics:</p> <p data-bbox="539 835 1264 902">1. ‘Capable of’ an ultimate tensile strength of 460 MPa or more at 293 K (20°C); <u>and</u></p> <p data-bbox="539 913 1264 1014">2. In the form of tubes or cylindrical solid forms (including forgings) with an outside diameter of more than 75 mm;</p> <p data-bbox="475 1037 1264 1070">b. Titanium alloys having both of the following characteristics:</p> <p data-bbox="539 1081 1264 1149">1. ‘Capable of’ an ultimate tensile strength of 900 MPa or more at 293 K (20°C); <u>and</u></p> <p data-bbox="539 1160 1264 1261">2. In the form of tubes or cylindrical solid forms (including forgings) with an outside diameter of more than 75 mm.</p> <p data-bbox="475 1283 659 1317"><u>Technical Note</u></p> <p data-bbox="475 1328 1264 1395"><i>The phrase alloys ‘capable of’ encompasses alloys before or after heat treatment.</i></p>
1C210	<p data-bbox="475 1462 1264 1529">‘Fibrous or filamentary materials’ or prepregs, other than those specified in Category Code 1C010.a., b. or e., as follows:</p> <p data-bbox="475 1541 1264 1608">a. Carbon or aramid ‘fibrous or filamentary materials’ having either of the following characteristics:</p> <p data-bbox="539 1619 1264 1664">1. A “specific modulus” of <math>12.7 \times 10^6</math> m or greater; <u>or</u></p> <p data-bbox="539 1675 1264 1709">2. A “specific tensile strength” of <math>23.5 \times 10^4</math> m or greater;</p> <p data-bbox="475 1731 595 1765"><u>Note</u></p> <p data-bbox="475 1776 1264 1868"><i>Category Code 1C210.a. does not include aramid ‘fibrous or filamentary materials’ having 0.25% by weight or more of an ester based fibre surface modifier;</i></p>

<i>Category Code</i>	<i>Item Description</i>
	<p>b. Glass ‘fibrous or filamentary materials’ having both of the following characteristics:</p> <ol style="list-style-type: none"> <li>1. A “specific modulus” of <math>3.18 \times 10^6</math> m or greater; <u>and</u></li> <li>2. A “specific tensile strength” of <math>7.62 \times 10^4</math> m or greater;</li> </ol> <p>c. Thermoset resin impregnated continuous “yarns”, “rovings”, “tows” or “tapes” with a width of 15 mm or less (prepregs), made from carbon or glass ‘fibrous or filamentary materials’ specified in Category Code 1C210.a. or b.</p> <p><u>Technical Note</u>  <i>The resin forms the matrix of the composite.</i></p> <p><u>Note</u>  <i>In Category Code 1C210, ‘fibrous or filamentary materials’ is restricted to continuous “monofilaments”, “yarns”, “rovings”, “tows” or “tapes”.</i></p>
1C216	<p>Maraging steel, other than that specified in Category Code 1C116, ‘capable of’ an ultimate tensile strength of 1,950 MPa or more, at 293 K (20°C).</p> <p><u>Note</u>  <i>Category Code 1C216 does not include forms in which all linear dimensions are 75 mm or less.</i></p> <p><u>Technical Note</u>  <i>The phrase maraging steel ‘capable of’ encompasses maraging steel before or after heat treatment.</i></p>
1C225	<p>Boron enriched in the boron-10 (<math>^{10}\text{B}</math>) isotope to greater than its natural isotopic abundance, as follows: elemental boron, compounds, mixtures containing boron, manufactures thereof, waste or scrap of any of the foregoing.</p> <p><u>Note</u>  <i>In Category Code 1C225, mixtures containing boron include boron loaded materials.</i></p>

Category Code	Item Description
	<p><u>Technical Note</u>  <i>The natural isotopic abundance of boron-10 is approximately 18.5 weight per cent (20 atom per cent).</i></p>
1C226	<p>Tungsten, tungsten carbide, and alloys containing more than 90% tungsten by weight, other than that specified by Category Code 1C117, having both of the following characteristics:</p> <ol style="list-style-type: none"> <li>a. In forms with a hollow cylindrical symmetry (including cylinder segments) with an inside diameter between 100 mm and 300 mm; <u>and</u></li> <li>b. A mass greater than 20 kg.</li> </ol>
	<p><u>Note</u>  <i>Category Code 1C226 does not include manufactures specially designed as weights or gamma-ray collimators.</i></p>
1C227	<p>Calcium having both of the following characteristics:</p> <ol style="list-style-type: none"> <li>a. Containing less than 1,000 parts per million by weight of metallic impurities other than magnesium; <u>and</u></li> <li>b. Containing less than 10 parts per million by weight of boron.</li> </ol>
1C228	<p>Magnesium having both of the following characteristics:</p> <ol style="list-style-type: none"> <li>a. Containing less than 200 parts per million by weight of metallic impurities other than calcium; <u>and</u></li> <li>b. Containing less than 10 parts per million by weight of boron.</li> </ol>
1C229	<p>Bismuth having both of the following characteristics:</p> <ol style="list-style-type: none"> <li>a. A purity of 99.99% or greater by weight; <u>and</u></li> <li>b. Containing less than 10 ppm (parts per million) by weight of silver.</li> </ol>

<i>Category Code</i>	<i>Item Description</i>
1C230	<p>Beryllium metal, alloys containing more than 50% beryllium by weight, beryllium compounds, manufactures thereof, and waste or scrap of any of the foregoing, other than that specified in Division 2 of Part I of this Schedule.</p> <p><u>N.B.</u> See also Division 2 of Part I of this Schedule.</p> <p><u>Note</u> Category Code 1C230 does not include the following:</p> <ol style="list-style-type: none"> <li>a. Metal windows for X-ray machines, or for bore-hole logging devices;</li> <li>b. Oxide shapes in fabricated or semi-fabricated forms specially designed for electronic component parts or as substrates for electronic circuits;</li> <li>c. Beryl (silicate of beryllium and aluminium) in the form of emeralds or aquamarines.</li> </ol>
1C231	<p>Hafnium metal, alloys containing more than 60% hafnium by weight, hafnium compounds containing more than 60% hafnium by weight, manufactures thereof, and waste or scrap of any of the foregoing.</p>
1C232	<p>Helium-3 (<math>^3\text{He}</math>), mixtures containing helium-3, and products or devices containing any of the foregoing.</p> <p><u>Note</u> Category Code 1C232 does not include a product or device containing less than 1 g of helium-3.</p>
1C233	<p>Lithium enriched in the lithium-6 (<math>^6\text{Li}</math>) isotope to greater than its natural isotopic abundance, and products or devices containing enriched lithium, as follows: elemental lithium, alloys, compounds, mixtures containing lithium, manufactures thereof, waste or scrap of any of the foregoing.</p> <p><u>Note</u> Category Code 1C233 does not include thermoluminescent dosimeters.</p>

<i>Category Code</i>	<i>Item Description</i>
	<p><u>Technical Note</u>  <i>The natural isotopic abundance of lithium-6 is approximately 6.5 weight per cent (7.5 atom per cent).</i></p>
1C234	<p>Zirconium with a hafnium content of less than 1 part hafnium to 500 parts zirconium by weight, as follows: metal, alloys containing more than 50% zirconium by weight, compounds, manufactures thereof, waste or scrap of any of the foregoing, other than those specified in Category Code 0A001.f.</p> <p><u>Note</u>  <i>Category Code 1C234 does not include zirconium in the form of foil having a thickness of 0.10 mm or less.</i></p>
1C235	<p>Tritium, tritium compounds, mixtures containing tritium in which the ratio of tritium to hydrogen atoms exceeds 1 part in 1,000, and products or devices containing any of the foregoing.</p> <p><u>Note</u>  <i>Category Code 1C235 does not include a product or device containing less than <math>1.48 \times 10^3</math> GBq (40 Ci) of tritium.</i></p>
1C236	<p>‘Radionuclides’ appropriate for making neutron sources based on alpha-n reaction, other than those specified in Category Codes 0C001 and 1C012.a., in the following forms:</p> <ol style="list-style-type: none"> <li>a. Elemental;</li> <li>b. Compounds having a total activity of 37 GBq/kg (1 Ci/kg) or greater;</li> <li>c. Mixtures having a total activity of 37 GBq/kg (1 Ci/kg) or greater;</li> <li>d. Products or devices containing any of the foregoing.</li> </ol> <p><u>Note</u>  <i>Category Code 1C236 does not include a product or device containing less than 3.7 GBq (100 millicuries) of activity.</i></p>

<i>Category Code</i>	<i>Item Description</i>
	<p><u>Technical Note</u>  <i>In Category Code 1C236, 'radionuclides' are any of the following:</i></p> <ul style="list-style-type: none"> <li>– Actinium-225 (Ac-225)</li> <li>– Actinium-227 (Ac-227)</li> <li>– Californium-253 (Cf-253)</li> <li>– Curium-240 (Cm-240)</li> <li>– Curium-241 (Cm-241)</li> <li>– Curium-242 (Cm-242)</li> <li>– Curium-243 (Cm-243)</li> <li>– Curium-244 (Cm-244)</li> <li>– Einsteinium-253 (Es-253)</li> <li>– Einsteinium-254 (Es-254)</li> <li>– Gadolinium-148 (Gd-148)</li> <li>– Plutonium-236 (Pu-236)</li> <li>– Plutonium-238 (Pu-238)</li> <li>– Polonium-208 (Po-208)</li> <li>– Polonium-209 (Po-209)</li> <li>– Polonium-210 (Po-210)</li> <li>– Radium-223 (Ra-223)</li> <li>– Thorium-227 (Th-227)</li> <li>– Thorium-228 (Th-228)</li> <li>– Uranium-230 (U-230)</li> <li>– Uranium-232 (U-232)</li> </ul>
1C237	<p>Radium-226 (<sup>226</sup>Ra), radium-226 alloys, radium-226 compounds, mixtures containing radium-226, manufactures thereof, and products or devices containing any of the foregoing.</p> <p><u>Note</u>  <i>Category Code 1C237 does not include the following:</i></p>



<i>Category Code</i>	<i>Item Description</i>
	<p>a. <i>Medical applicators;</i></p> <p>b. <i>A product or device containing less than 0.37 GBq (10 millicuries) of radium-226.</i></p>
1C238	Chlorine trifluoride (ClF <sub>3</sub> ).
1C239	High explosives, other than those specified in Division 2 of Part I of this Schedule, or substances or mixtures containing more than 2% by weight thereof, with a crystal density greater than 1.8 g/cm <sup>3</sup> and having a detonation velocity greater than 8,000 m/s.
1C240	<p>Nickel powder and porous nickel metal, other than those specified in Category Code 0C005, as follows:</p> <p>a. Nickel powder having both of the following characteristics:</p> <ol style="list-style-type: none"> <li>1. A nickel purity content of 99% or greater by weight; <u>and</u></li> <li>2. A mean particle size of less than 10 µm measured by American Society for Testing and Materials (ASTM) B330 standard;</li> </ol> <p>b. Porous nickel metal produced from materials specified in Category Code 1C240.a.</p>
	<p><u>Note</u></p> <p><i>Category Code 1C240 does not include the following:</i></p>
	<p>a. <i>Filamentary nickel powders;</i></p> <p>b. <i>Single porous nickel sheets with an area of 1,000 cm<sup>2</sup> per sheet or less.</i></p>
	<p><u>Technical Note</u></p> <p><i>Category Code 1C240.b. refers to porous metal formed by compacting and sintering the materials in Category Code 1C240.a. to form a metal material with fine pores interconnected throughout the structure.</i></p>

<i>Category Code</i>	<i>Item Description</i>
1C241	<p>Rhenium, and alloys containing 90% by weight or more rhenium; and alloys of rhenium and tungsten containing 90% by weight or more of any combination of rhenium and tungsten, having both of the following characteristics:</p> <ol style="list-style-type: none"> <li>a. In forms with a hollow cylindrical symmetry (including cylinder segments) with an inside diameter between 100 mm and 300 mm; <u>and</u></li> <li>b. A mass greater than 20 kg.</li> </ol>
1C350	<p>Chemicals, which may be used as precursors for toxic chemical agents, as follows, and “chemical mixtures” containing one or more thereof:</p> <p><u>N.B.</u>  <i>See also Division 2 of Part I of this Schedule and Category Code 1C450.</i></p> <ol style="list-style-type: none"> <li>1. Thiodiglycol (111-48-8);</li> <li>2. Phosphorus oxychloride (10025-87-3);</li> <li>3. Dimethyl methylphosphonate (756-79-6);</li> <li>4. See Methyl phosphonyl difluoride (676-99-3) in Division 2 of Part I of this Schedule;</li> <li>5. Methyl phosphonyl dichloride (676-97-1);</li> <li>6. Dimethyl phosphite (DMP) (868-85-9);</li> <li>7. Phosphorus trichloride (7719-12-2);</li> <li>8. Trimethyl phosphite (TMP) (121-45-9);</li> <li>9. Thionyl chloride (7719-09-7);</li> <li>10. 3-Hydroxy-1-methylpiperidine (3554-74-3);</li> <li>11. N,N-Diisopropyl-(beta)-aminoethyl chloride (96-79-7);</li> <li>12. N,N-Diisopropyl-(beta)-aminoethane thiol (5842-07-9);</li> <li>13. 3-Quinuclidinol (1619-34-7);</li> <li>14. Potassium fluoride (7789-23-3);</li> <li>15. 2-Chloroethanol (107-07-3);</li> <li>16. Dimethylamine (124-40-3);</li> </ol>

<i>Category Code</i>	<i>Item Description</i>
	17. Diethyl ethylphosphonate (78-38-6);
	18. Diethyl-N,N-dimethylphosphoramidate (2404-03-7);
	19. Diethyl phosphite (762-04-9);
	20. Dimethylamine hydrochloride (506-59-2);
	21. Ethyl phosphinyl dichloride (1498-40-4);
	22. Ethyl phosphonyl dichloride (1066-50-8);
	23. See Ethyl phosphonyl difluoride (753-98-0) in Division 2 of Part I of this Schedule;
	24. Hydrogen fluoride (7664-39-3);
	25. Methyl benzilate (76-89-1);
	26. Methyl phosphinyl dichloride (676-83-5);
	27. N,N-Diisopropyl-(beta)-amino ethanol (96-80-0);
	28. Pinacolyl alcohol (464-07-3);
	29. See O-Ethyl-2-diisopropylaminoethyl methyl phosphonite (QL) (57856-11-8) in Division 2 of Part I of this Schedule;
	30. Triethyl phosphite (122-52-1);
	31. Arsenic trichloride (7784-34-1);
	32. Benzilic acid (76-93-7);
	33. Diethyl methylphosphonite (15715-41-0);
	34. Dimethyl ethylphosphonate (6163-75-3);
	35. Ethyl phosphinyl difluoride (430-78-4);
	36. Methyl phosphinyl difluoride (753-59-3);
	37. 3-Quinuclidone (3731-38-2);
	38. Phosphorus pentachloride (10026-13-8);
	39. Pinacolone (75-97-8);
	40. Potassium cyanide (151-50-8);
	41. Potassium bifluoride (7789-29-9);
	42. Ammonium hydrogen fluoride or ammonium bifluoride (1341-49-7);
	43. Sodium fluoride (7681-49-4);

<i>Category Code</i>	<i>Item Description</i>
	44. Sodium bifluoride (1333-83-1);
	45. Sodium cyanide (143-33-9);
	46. Triethanolamine (102-71-6);
	47. Phosphorus pentasulphide (1314-80-3);
	48. Di-isopropylamine (108-18-9);
	49. Diethylaminoethanol (100-37-8);
	50. Sodium sulphide (1313-82-2);
	51. Sulphur monochloride (10025-67-9);
	52. Sulphur dichloride (10545-99-0);
	53. Triethanolamine hydrochloride (637-39-8);
	54. N,N-Diisopropyl-(Beta)-aminoethyl chloride hydrochloride (4261-68-1);
	55. Methylphosphonic acid (993-13-5);
	56. Diethyl methylphosphonate (683-08-9);
	57. N,N-Dimethylaminophosphoryl dichloride (677-43-0);
	58. Triisopropyl phosphite (116-17-6);
	59. Ethyldiethanolamine (139-87-7);
	60. O,O-Diethyl phosphorothioate (2465-65-8);
	61. O,O-Diethyl phosphorodithioate (298-06-6);
	62. Sodium hexafluorosilicate (16893-85-9);
	63. Methylphosphonothioic dichloride (676-98-2).
	<i>Note 1</i>
	<i>Category Code 1C350 does not include "chemical mixtures" containing one or more of the chemicals specified in Category Codes 1C350.2., .6., .7., .8., .9., .10., .14., .15., .16., .19., .20., .24., .25., .30., .37., .38., .39., .40., .41., .42., .43., .44., .45., .46., .47., .48., .49., .50., .51., .52., .53., .58., .59., .60., .61. and .62. in which no individually specified chemical constitutes more than 30% by the weight of the mixture.</i>

<i>Category Code</i>	<i>Item Description</i>
1C351	<p data-bbox="475 454 560 488"><u>Note 2</u></p> <p data-bbox="475 495 1265 595"><i>Category Code 1C350 does not include products identified as consumer goods and packaged for retail sale for personal use or packaged for individual use.</i></p> <p data-bbox="475 663 1129 696">Human and animal pathogens and “toxins”, as follows:</p> <p data-bbox="475 712 1265 842">a. Viruses, whether natural, enhanced or modified, either in the form of “isolated live cultures” or as material including living material which has been deliberately inoculated or contaminated with such cultures, as follows:</p> <ol data-bbox="539 864 1265 1859" style="list-style-type: none"> <li data-bbox="539 864 948 898">1. African horse sickness virus;</li> <li data-bbox="539 913 916 947">2. African swine fever virus;</li> <li data-bbox="539 963 756 996">3. Andes virus;</li> <li data-bbox="539 1012 1265 1615">4. Avian influenza virus, which are <ol data-bbox="624 1061 1265 1615" style="list-style-type: none"> <li data-bbox="624 1061 927 1095">a. Uncharacterised; <u>or</u></li> <li data-bbox="624 1111 1265 1211">b. Defined in Annex I(2) EC Directive 2005/94/EC (O.J.L. 10 14.1.2006 p. 16) as having high pathogenicity, as follows: <ol data-bbox="687 1227 1265 1615" style="list-style-type: none"> <li data-bbox="687 1227 1265 1328">1. Type A viruses with an IVPI (intravenous pathogenicity index) in 6 week old chickens of greater than 1.2; <u>or</u></li> <li data-bbox="687 1344 1265 1615">2. Type A viruses of the subtypes H5 or H7 with genome sequences codified for multiple basic amino acids at the cleavage site of the haemagglutinin molecule similar to that observed for other HPAI viruses, indicating that the haemagglutinin molecule can be cleaved by a host ubiquitous protease;</li> </ol> </li> </ol> </li> <li data-bbox="539 1630 820 1664">5. Bluetongue virus;</li> <li data-bbox="539 1680 780 1713">6. Chapare virus;</li> <li data-bbox="539 1729 839 1762">7. Chikungunya virus;</li> <li data-bbox="539 1778 767 1812">8. Choclo virus;</li> <li data-bbox="539 1827 1107 1861">9. Congo-Crimean haemorrhagic fever virus;</li> </ol>

<i>Category Code</i>	<i>Item Description</i>
	10. Dengue fever virus;
	11. Dobrava-Belgrade virus;
	12. Eastern equine encephalitis virus;
	13. Ebola virus;
	14. Foot and mouth disease virus;
	15. Goat pox virus;
	16. Guanarito virus;
	17. Hantaan virus;
	18. Hendra virus (Equine morbillivirus);
	19. Herpes virus (Aujeszky's disease);
	20. Hog cholera virus (swine fever virus);
	21. Japanese encephalitis virus;
	22. Junin virus;
	23. Kyasanur Forest virus;
	24. Laguna Negra virus;
	25. Lassa fever virus;
	26. Louping ill virus;
	27. Lujo virus;
	28. Lumpy skin disease virus;
	29. Lymphocytic choriomeningitis virus;
	30. Machupo virus;
	31. Marburg virus;
	32. Monkey pox virus;
	33. Murray Valley encephalitis virus;
	34. Newcastle disease virus;
	35. Nipah virus;
	36. Omsk haemorrhagic fever virus;
	37. Oropouche virus;
	38. Peste des petits ruminants virus;

<i>Category Code</i>	<i>Item Description</i>
	39. Porcine enterovirus type 9 (swine vesicular disease virus);
	40. Powassan virus;
	41. Rabies virus and all other members of the Lyssavirus genus;
	42. Rift Valley fever virus;
	43. Rinderpest virus;
	44. Rocio virus;
	45. Sabia virus;
	46. Seoul virus;
	47. Sheep pox virus;
	48. Sin nombre virus;
	49. St Louis encephalitis virus;
	50. Teschen disease virus;
	51. Tick-borne encephalitis virus (Russian Spring-Summer encephalitis virus);
	52. Variola virus;
	53. Venezuelan equine encephalitis virus;
	54. Vesicular stomatitis virus;
	55. Western equine encephalitis virus;
	56. Yellow fever virus;
	b. Not used;
	c. Bacteria, whether natural, enhanced or modified, either in the form of "isolated live cultures" or as material including living material which has been deliberately inoculated or contaminated with such cultures, as follows:
	1. Bacillus anthracis;
	2. Brucella abortus;
	3. Brucella melitensis;
	4. Brucella suis;
	5. Burkholderia mallei (Pseudomonas mallei);

<i>Category Code</i>	<i>Item Description</i>
	<ol style="list-style-type: none"> <li>6. Burkholderia pseudomallei (Pseudomonas pseudomallei);</li> <li>7. Chlamydophila psittaci (formally known as Chlamydia psittaci);</li> <li>8. Clostridium argentinense (formerly known as Clostridium botulinum Type G), botulinum neurotoxin producing strains;</li> <li>9. Clostridium baratii, botulinum neurotoxin producing strains;</li> <li>10. Clostridium botulinum;</li> <li>11. Clostridium butyricum, botulinum neurotoxin producing strains;</li> <li>12. Clostridium perfringens epsilon toxin producing types;</li> <li>13. Coxiella burnetii;</li> <li>14. Francisella tularensis;</li> <li>15. Mycoplasma capricolum subspecies capripneumoniae (strain F38);</li> <li>16. Mycoplasma mycoides subspecies mycoides SC (small colony);</li> <li>17. Rickettsia prowasecki;</li> <li>18. Salmonella typhi;</li> <li>19. Shiga toxin producing Escherichia coli (STEC) of serogroups O26, O45, O103, O104, O111, O121, O145, O157, and other shiga toxin producing serogroups;</li> <li>20. Shigella dysenteriae;</li> <li>21. Vibrio cholerae;</li> <li>22. Yersinia pestis;</li> </ol> <p>d. "Toxins", as follows, and "sub-unit of toxins" thereof:</p> <ol style="list-style-type: none"> <li>1. Botulinum toxins;</li> <li>2. Clostridium perfringens alpha, beta 1, beta 2, epsilon and iota toxins;</li> <li>3. Conotoxin;</li> </ol>



<i>Category Code</i>	<i>Item Description</i>
	<p>4. Ricin;</p> <p>5. Saxitoxin;</p> <p>6. Shiga toxin;</p> <p><i>Technical Note</i>  <i>Shiga toxin producing Escherichia coli (STEC) is also known as enterohaemorrhagic E. coli (EHEC) or verocytotoxin producing E. coli (VTEC).</i></p> <p>7. Staphylococcus aureus enterotoxins, hemolysin alpha toxin, and toxic shock syndrome toxin (formerly known as Staphylococcus enterotoxin F);</p> <p>8. Tetrodotoxin;</p> <p>9. Verotoxin and shiga-like ribosome inactivating proteins;</p> <p>10. Microcystin (Cyanginosin);</p> <p>11. Aflatoxins;</p> <p>12. Abrin;</p> <p>13. Cholera toxin;</p> <p>14. Diacetoxyscirpenol toxin;</p> <p>15. T-2 toxin;</p> <p>16. HT-2 toxin;</p> <p>17. Modeccin;</p> <p>18. Volkensin;</p> <p>19. Viscum album Lectin 1 (Viscumin);</p> <p><i>Note</i>  <i>Category Code 1C351.d. does not include botulinum toxins or conotoxins in product form meeting all of the following criteria:</i></p> <p>1. <i>Are pharmaceutical formulations designed for human administration in the treatment of medical conditions;</i></p> <p>2. <i>Are pre-packaged for distribution as medical products;</i>  <i>and</i></p>

<i>Category Code</i>	<i>Item Description</i>
	<p>3. <i>Are authorised by a state authority to be marketed as medical products.</i></p> <p>e. Fungi, whether natural, enhanced or modified, either in the form of “isolated live cultures” or as material including living material which has been deliberately inoculated or contaminated with such cultures, as follows:</p> <ol style="list-style-type: none"> <li>1. <i>Coccidioides immitis;</i></li> <li>2. <i>Coccidioides posadasii.</i></li> </ol> <p><u>Note</u>  <i>Category Code 1C351 does not include “vaccines” or “immunotoxins”.</i></p>
1C353	<p>Genetic elements and genetically modified organisms, as follows:</p> <ol style="list-style-type: none"> <li>a. Genetically modified organisms or genetic elements that contain nucleic acid sequences associated with pathogenicity of organisms specified in Category Code 1C351.a., 1C351.c., 1C351.e. or 1C354;</li> <li>b. Genetically modified organisms or genetic elements that contain nucleic acid sequences coding for any of the “toxins” specified in Category Code 1C351.d. or “sub-units of toxins” thereof.</li> </ol> <p><u>Technical Notes</u></p> <ol style="list-style-type: none"> <li>1. <i>Genetically modified organisms include organisms in which the genetic material (nucleic acid sequences) has been altered in a way that does not occur naturally by mating and/or natural recombination, and encompasses those produced artificially in whole or in part.</i></li> <li>2. <i>Genetic elements include inter alia chromosomes, genomes, plasmids, transposons and vectors whether genetically modified or unmodified, or chemically synthesised in whole or in part.</i></li> <li>3. <i>Nucleic acid sequences associated with the pathogenicity of any of the microorganisms specified in Category Code 1C351.a., 1C351.c., 1C351.e. or 1C354 means any sequence specific to the specified microorganism that:</i></li> </ol>

Category Code	Item Description
	<p>a. <i>In itself or through its transcribed or translated products represents a significant hazard to human, animal or plant health; <u>or</u></i></p> <p>b. <i>Is known to enhance the ability of a specified microorganism, or any other organism into which it may be inserted or otherwise integrated, to cause serious harm to humans, animals or plant health.</i></p> <p><u>Note</u>  <i>Category Code 1C353 does not extend to nucleic acid sequences associated with the pathogenicity of enterohaemorrhagic Escherichia coli, serotype O157 and other verotoxin producing strains, other than those coding for the verotoxin, or for its sub-units.</i></p>
1C354	<p>Plant pathogens, as follows:</p> <p>a. Viruses, whether natural, enhanced or modified, either in the form of “isolated live cultures” or as material including living material which has been deliberately inoculated or contaminated with such cultures, as follows:</p> <ol style="list-style-type: none"> <li>1. Andean potato latent virus (Potato Andean latent tymovirus);</li> <li>2. Potato spindle tuber viroid;</li> </ol> <p>b. Bacteria, whether natural, enhanced or modified, either in the form of “isolated live cultures” or as material which has been deliberately inoculated or contaminated with such cultures, as follows:</p> <ol style="list-style-type: none"> <li>1. Xanthomonas albilineans;</li> <li>2. Xanthomonas axonopodis pv. citri (Xanthomonas campestris pv. citri A) [Xanthomonas campestris pv. citri];</li> <li>3. Xanthomonas oryzae pv. oryzae (Pseudomonas campestris pv. oryzae);</li> <li>4. Clavibacter michiganensis subsp. sepedonicus (Corynebacterium michiganensis subsp. sepedonicum or Corynebacterium sepedonicum);</li> <li>5. Ralstonia solanacearum, race 3, biovar 2;</li> </ol>

<i>Category Code</i>	<i>Item Description</i>
	<p>c. Fungi, whether natural, enhanced or modified, either in the form of “isolated live cultures” or as material which has been deliberately inoculated or contaminated with such cultures, as follows:</p> <ol style="list-style-type: none"> <li>1. Colletotrichum kahawae (Colletotrichum coffeanum var. virulans);</li> <li>2. Cochliobolus miyabeanus (Helminthosporium oryzae);</li> <li>3. Microcyclus ulei (syn. Dothidella ulei);</li> <li>4. Puccinia graminis ssp. graminis var. graminis/Puccinia graminis ssp. graminis var. stakmanii (Puccinia graminis [syn. Puccinia graminis f. sp. tritici]);</li> <li>5. Puccinia striiformis (syn. Puccinia glumarum);</li> <li>6. Magnaporthe oryzae (Pyricularia oryzae).</li> <li>7. Peronosclerospora philippinensis (Peronosclerospora sacchari);</li> <li>8. Sclerophthora rayssiae var. zea;</li> <li>9. Synchytrium endobioticum;</li> <li>10. Tilletia indica;</li> <li>11. Thecaphora solani.</li> </ol>
1C450	<p>Toxic chemicals and toxic chemical precursors, as follows, and “chemical mixtures” containing one or more thereof:</p> <p><u><i>N.B.</i></u>  <i>See also Category Codes 1C350, 1C351.d. and Division 2 of Part I of this Schedule.</i></p> <p>a. Toxic chemicals, as follows:</p> <ol style="list-style-type: none"> <li>1. Amiton: O,O-Diethyl S-[2-(diethylamino)ethyl] phosphorothiolate (78-53-5) and corresponding alkylated or protonated salts;</li> <li>2. PFIB: 1,1,3,3,3-Pentafluoro-2-(trifluoromethyl)-1-propene (382-21-8);</li> <li>3. See BZ: 3-Quinuclidinyl benzilate (6581-06-2) in Division 2 of Part I of this Schedule;</li> </ol>

<i>Category Code</i>	<i>Item Description</i>
	<ol style="list-style-type: none"> <li>4. Phosgene: Carbonyl dichloride (75-44-5);</li> <li>5. Cyanogen chloride (506-77-4);</li> <li>6. Hydrogen cyanide (74-90-8);</li> <li>7. Chloropicrin: Trichloronitromethane (76-06-2).</li> </ol> <p>b. Toxic chemical precursors, as follows:</p> <ol style="list-style-type: none"> <li>1. Chemicals, other than those specified in Division 2 of Part I of this Schedule or in Category Code 1C350, containing a phosphorus atom to which is bonded one methyl, ethyl or propyl (normal or iso) group but not further carbon atoms; <p><i>Note</i>  <i>Category Code 1C450.b.1. does not include Fonofos: O-Ethyl S-phenyl ethylphosphonothiolothionate (944-22-9).</i></p> </li> <li>2. N,N-Dialkyl [methyl, ethyl or propyl (normal or iso)] phosphoramidic dihalides, other than N,N-Dimethylaminophosphoryl dichloride; <p><i>N.B.</i>  <i>See Category Code 1C350.57. for N,N-Dimethylaminophosphoryl dichloride.</i></p> </li> <li>3. Dialkyl [methyl, ethyl or propyl (normal or iso)] N,N-dialkyl [methyl, ethyl or propyl (normal or iso)]-phosphoramidates, other than Diethyl-N,N-dimethylphosphoramidate which is specified in Category Code 1C350;</li> <li>4. N,N-Dialkyl [methyl, ethyl or propyl (normal or iso)] aminoethyl-2-chlorides and corresponding protonated salts, other than N,N-Diisopropyl-(beta)-aminoethyl chloride or N,N-Diisopropyl-(beta)-aminoethyl chloride hydrochloride which are specified in Category Code 1C350;</li> <li>5. N,N-Dialkyl [methyl, ethyl or propyl (normal or iso)] aminoethane-2-ols and corresponding protonated salts, other than N,N-Diisopropyl-(beta)-aminoethanol (96-80-0) and N,N-Diethylaminoethanol (100-37-8) which are specified in Category Code 1C350;</li> </ol>

Category Code	Item Description
	<p><u>Note</u>            Category Code 1C450.b.5. does not include the following:</p> <ol style="list-style-type: none"> <li>a. N,N-Dimethylaminoethanol (108-01-0) and corresponding protonated salts;</li> <li>b. Protonated salts of N,N-Diethylaminoethanol (100-37-8).</li> </ol> <ol style="list-style-type: none"> <li>6. N,N-Dialkyl [methyl, ethyl or propyl (normal or iso)] aminoethane-2-thiols and corresponding protonated salts, other than N,N-Diisopropyl-(beta)-aminoethane thiol which is specified in Category Code 1C350;</li> <li>7. See Category Code 1C350 for ethyldiethanolamine (139-87-7);</li> <li>8. Methyldiethanolamine (105-59-9).</li> </ol> <p><u>Note 1</u>            Category Code 1C450 does not include “chemical mixtures” containing one or more of the chemicals specified in Category Codes 1C450.a.4., .a.5., .a.6., .a.7. and .b.8. in which no individually specified chemical constitutes more than 30% by weight of the mixture.</p> <p><u>Note 2</u>            Category Code 1C450 does not include products identified as consumer goods packaged for retail sale for personal use or packaged for individual use.</p>
<b>1D</b>	<b>Software</b>
1D001	“Software” specially designed or modified for the “development”, “production” or “use” of equipment specified in Category Codes 1B001 to 1B003.
1D002	“Software” for the “development” of organic “matrix”, metal “matrix” or carbon “matrix” laminates or “composites”.

<i>Category Code</i>	<i>Item Description</i>
1D003	“Software” specially designed or modified to enable equipment to perform the functions of equipment specified in Category Code 1A004.c. or 1A004.d.
1D101	“Software” specially designed or modified for the operation or maintenance of goods specified in Category Code 1B101, 1B102, 1B115, 1B117, 1B118 or 1B119.
1D103	“Software” specially designed for analysis of reduced observables such as radar reflectivity, ultraviolet/infrared signatures and acoustic signatures.
1D201	“Software” specially designed for the “use” of goods specified in Category Code 1B201.
<b>1E</b>	<b>Technology</b>
1E001	“Technology” (according to the General Technology Note) for the “development” or “production” of equipment or materials specified in Category Code 1A001.b., 1A001.c., 1A002 to 1A005, 1A006.b., 1A007 or Category 1B or 1C.
1E002	Other “technology”, as follows: <ul style="list-style-type: none"> <li>a. “Technology” for the “development” or “production” of polybenzothiazoles or polybenzoxazoles;</li> <li>b. “Technology” for the “development” or “production” of fluoroelastomer compounds containing at least one vinyl ether monomer;</li> <li>c. “Technology” for the design or “production” of the following base materials or non-“composite” ceramic materials: <ul style="list-style-type: none"> <li>1. Base materials having all of the following: <ul style="list-style-type: none"> <li>a. Any of the following compositions:</li> </ul> </li> </ul> </li> </ul>

<i>Category Code</i>	<i>Item Description</i>
	<ol style="list-style-type: none"> <li>1. Single or complex oxides of zirconium and complex oxides of silicon or aluminium;</li> <li>2. Single nitrides of boron (cubic crystalline forms);</li> <li>3. Single or complex carbides of silicon or boron; <u>or</u></li> <li>4. Single or complex nitrides of silicon;</li> <li>b. Any of the following total metallic impurities (excluding intentional additions): <ol style="list-style-type: none"> <li>1. Less than 1,000 ppm for single oxides or carbides; <u>or</u></li> <li>2. Less than 5,000 ppm for complex compounds or single nitrides; <u>and</u></li> </ol> </li> <li>c. Being any of the following: <ol style="list-style-type: none"> <li>1. Zirconia (1314-23-4) with an average particle size equal to or less than 1 <math>\mu\text{m}</math> and no more than 10% of the particles larger than 5 <math>\mu\text{m}</math>;</li> <li>2. Other base materials with an average particle size equal to or less than 5 <math>\mu\text{m}</math> and no more than 10% of the particles larger than 10 <math>\mu\text{m}</math>; <u>or</u></li> <li>3. Having all of the following: <ol style="list-style-type: none"> <li>a. Platelets with a length to thickness ratio exceeding 5;</li> <li>b. Whiskers with a length to diameter ratio exceeding 10 for diameters less than 2 <math>\mu\text{m}</math>; <u>and</u></li> <li>c. Continuous or chopped fibres less than 10 <math>\mu\text{m}</math> in diameter;</li> </ol> </li> </ol> </li> <li>2. Non-“composite” ceramic materials composed of the materials specified in Category Code 1E002.c.1.;</li> </ol>



Category Code	Item Description
	<p data-bbox="603 456 662 486"><u>Note</u></p> <p data-bbox="603 497 1265 593"><i>Category Code 1E002.c.2. does not include “technology” for the design or production of abrasives.</i></p> <p data-bbox="475 613 1265 846">d. Not used; e. “Technology” for the installation, maintenance or repair of materials specified in Category Code 1C001; f. “Technology” for the repair of “composite” structures, laminates or materials specified in Category Code 1A002, 1C007.c. or 1C007.d.;</p> <p data-bbox="539 866 598 896"><u>Note</u></p> <p data-bbox="539 907 1265 1037"><i>Category Code 1E002.f. does not include “technology” for the repair of “civil aircraft” structures using carbon “fibrous or filamentary materials” and epoxy resins, contained in aircraft manufacturers’ manuals.</i></p> <p data-bbox="475 1057 1265 1187">g. ‘Libraries (parametric technical databases)’ specially designed or modified to enable equipment to perform the functions of equipment specified in Category Code 1A004.c. or 1A004.d.</p> <p data-bbox="539 1207 722 1236"><u>Technical Note</u></p> <p data-bbox="539 1247 1265 1377"><i>For the purpose of Category Code 1E002.g., ‘library (parametric technical database)’ means a collection of technical information, reference to which may enhance the performance of relevant equipment or systems.</i></p>
1E101	<p data-bbox="475 1447 1265 1576">“Technology” (according to the General Technology Note) for the “use” of goods specified in Category Code 1A102, 1B001, 1B101, 1B102, 1B115 to 1B119, 1C001, 1C101, 1C107, 1C111, 1C116, 1C117, 1C118, 1D101 or 1D103.</p>
1E102	<p data-bbox="475 1648 1265 1744">“Technology” (according to the General Technology Note) for the “development” of “software” specified in Category Code 1D001, 1D101 or 1D103.</p>

<i>Category Code</i>	<i>Item Description</i>
1E103	“Technology” for the regulation of temperature, pressure or atmosphere in autoclaves or hydroclaves, when used for the “production” of “composites” or partially processed “composites”.
1E104	“Technology” relating to the “production” of pyrolytically derived materials formed on a mould, mandrel or other substrate from precursor gases which decompose in the 1,573 K (1,300°C) to 3,173 K (2,900°C) temperature range at pressures of 130 Pa to 20 kPa.
	<p data-bbox="464 842 536 871"><i>Note</i></p> <p data-bbox="464 882 1268 976"><i>Category Code 1E104 includes “technology” for the composition of precursor gases, flow-rates and process control schedules and parameters.</i></p>
1E201	“Technology” (according to the General Technology Note) for the “use” of goods specified in Category Code 1A002, 1A007, 1A202, 1A225 to 1A227, 1B201, 1B225 to 1B234, 1C002.b.3. or .b.4., 1C010.b., 1C202, 1C210, 1C216, 1C225 to 1C241 or 1D201.
1E202	“Technology” (according to the General Technology Note) for the “development” or “production” of goods specified in Category Code 1A007, 1A202 or 1A225 to 1A227.
1E203	“Technology” (according to the General Technology Note) for the “development” of “software” specified in Category Code 1D201.

<i>Category Code</i>	<i>Item Description</i>
<b>CATEGORY 2 — MATERIALS PROCESSING</b>	
<b>2A</b>	<p><b>Systems, Equipment and Components</b></p> <p><u>N.B.</u> For quiet running bearings, see Division 2 of Part I of this Schedule.</p>
2A001	<p>Anti-friction bearings and bearing systems, as follows, and components therefor:</p> <p><u>N.B.</u> See also Category Code 2A101.</p> <p><u>Note</u> Category Code 2A001 does not include balls with tolerances specified by the manufacturer in accordance with ISO 3290 as grade 5 or worse.</p> <p>a. Ball bearings and solid roller bearings, having all tolerances specified by the manufacturer in accordance with ISO 492 Tolerance Class 4 (or national equivalents), or better, and having both rings and rolling elements (ISO 5593), made from monel or beryllium;</p> <p><u>Note</u> Category Code 2A001.a. does not include tapered roller bearings.</p> <p>b. Not used;</p> <p>c. Active magnetic bearing systems using any of the following:</p> <ol style="list-style-type: none"> <li>1. Materials with flux densities of 2 T or greater and yield strengths greater than 414 MPa;</li> <li>2. All-electromagnetic 3D homopolar bias designs for actuators; <u>or</u></li> <li>3. High temperature (450 K (177°C) and above) position sensors.</li> </ol>

<i>Category Code</i>	<i>Item Description</i>
2A101	<p>Radial ball bearings, other than those specified in Category Code 2A001, having all tolerances specified in accordance with ISO 492 Tolerance Class 2 (or ANSI/ABMA Std 20 Tolerance Class ABEC-9 or other national equivalents), or better and having all of the following characteristics:</p> <ol style="list-style-type: none"> <li>a. An inner ring bore diameter between 12 mm and 50 mm;</li> <li>b. An outer ring outside diameter between 25 mm and 100 mm; <u>and</u></li> <li>c. A width between 10 mm and 20 mm.</li> </ol>
2A225	<p>Crucibles made of materials resistant to liquid actinide metals, as follows:</p> <ol style="list-style-type: none"> <li>a. Crucibles having both of the following characteristics: <ol style="list-style-type: none"> <li>1. A volume of between 150 cm<sup>3</sup> and 8,000 cm<sup>3</sup>; <u>and</u></li> <li>2. Made of or coated with any of the following materials, or combination of the following materials, having an overall impurity level of 2% or less by weight: <ol style="list-style-type: none"> <li>a. Calcium fluoride (CaF<sub>2</sub>);</li> <li>b. Calcium zirconate (metazirconate) (CaZrO<sub>3</sub>);</li> <li>c. Cerium sulphide (Ce<sub>2</sub>S<sub>3</sub>);</li> <li>d. Erbium oxide (erbia) (Er<sub>2</sub>O<sub>3</sub>);</li> <li>e. Hafnium oxide (hafnia) (HfO<sub>2</sub>);</li> <li>f. Magnesium oxide (MgO);</li> <li>g. Nitrided niobium-titanium-tungsten alloy (approximately 50% Nb, 30% Ti, 20% W);</li> <li>h. Yttrium oxide (yttria) (Y<sub>2</sub>O<sub>3</sub>); <u>or</u></li> <li>i. Zirconium oxide (zirconia) (ZrO<sub>2</sub>);</li> </ol> </li> </ol> </li> <li>b. Crucibles having both of the following characteristics: <ol style="list-style-type: none"> <li>1. A volume of between 50 cm<sup>3</sup> and 2,000 cm<sup>3</sup>; <u>and</u></li> <li>2. Made of or lined with tantalum, having a purity of 99.9% or greater by weight;</li> </ol> </li> </ol>

<i>Category Code</i>	<i>Item Description</i>
	c. Crucibles having all of the following characteristics: <ol style="list-style-type: none"> <li>1. A volume of between 50 cm<sup>3</sup> and 2,000 cm<sup>3</sup>;</li> <li>2. Made of or lined with tantalum, having a purity of 98% or greater by weight; <u>and</u></li> <li>3. Coated with tantalum carbide, nitride, boride, or any combination thereof.</li> </ol>
2A226	Valves having all of the following characteristics: <ol style="list-style-type: none"> <li>a. A 'nominal size' of 5 mm or greater;</li> <li>b. Having a bellows seal; <u>and</u></li> <li>c. Wholly made of or lined with aluminium, aluminium alloy, nickel, or nickel alloy containing more than 60% nickel by weight.</li> </ol>
	<p><u>Technical Note</u>  <i>For valves with different inlet and outlet diameters, the 'nominal size' in Category Code 2A226 refers to the smallest diameter.</i></p>
<b>2B</b>	<p><b>Test, Inspection and Production Equipment</b></p> <p><u>Technical Notes</u></p> <ol style="list-style-type: none"> <li>1. <i>Secondary parallel contouring axes, (e.g. the w-axis on horizontal boring mills or a secondary rotary axis the centre line of which is parallel to the primary rotary axis) are not counted in the total number of contouring axes. Rotary axes need not rotate over 360°. A rotary axis can be driven by a linear device (e.g. a screw or a rack-and-pinion).</i></li> <li>2. <i>For the purpose of Category 2B, the number of axes which can be coordinated simultaneously for "contouring control" is the number of axes along or around which, during processing of the workpiece, simultaneous and interrelated motions are performed between the workpiece and a tool. This does not include any additional axes along or around which other relative movement within the machine are performed such as:</i> <ol style="list-style-type: none"> <li>a. <i>Wheel-dressing systems in grinding machines;</i></li> </ol> </li> </ol>

Category Code	Item Description
	<p>b. <i>Parallel rotary axes designed for mounting of separate workpieces;</i></p> <p>c. <i>Co-linear rotary axes designed for manipulating the same workpiece by holding it in a chuck from different ends.</i></p> <p>3. <i>Axis nomenclature shall be in accordance with International Standard ISO 841, 'Numerical Control Machines — Axis and Motion Nomenclature'.</i></p> <p>4. <i>For the purposes of Category Codes 2B001 to 2B009 a "tilting spindle" is counted as a rotary axis.</i></p> <p>5. <i>'Stated positioning accuracy' derived from measurements made according to ISO 230/2 or national equivalents may be used for each machine tool model as an alternative to individual machine tests. 'Stated positioning accuracy' means the accuracy value provided to the competent authorities of the country in which the exporter is established as representative of the accuracy of a specific machine model.</i></p> <p><i>Determination of 'Stated Positioning Accuracy'</i></p> <p>a. <i>Select five machines of a model to be evaluated;</i></p> <p>b. <i>Measure the linear axis accuracies according to ISO 230/2;</i></p> <p>c. <i>Determine the A-values for each axis of each machine. The method of calculating the A-value is described in the ISO standard;</i></p> <p>d. <i>Determine the mean value of the A-value of each axis. This mean value <math>\hat{A}</math> becomes the stated value of each axis for the model (<math>\hat{A}_x \hat{A}_y \dots</math>);</i></p> <p>e. <i>Since the Category 2 list refers to each linear axis there will be as many stated values as there are linear axes;</i></p> <p>f. <i>If any axis of a machine model not included under Category Code 2B001.a. to 2B001.c. or 2B201 has a stated accuracy <math>\hat{A}</math> equal to or less than the specified positioning accuracy of each machine tool model plus 2 <math>\mu\text{m}</math>, the manufacturer should be required to reaffirm the accuracy level once every eighteen months.</i></p>

Category Code	Item Description
2B001	<p data-bbox="475 454 1267 618">6. For the purposes of Category Codes 2B001.a. to 2B001.c., measurement uncertainty for the positioning accuracy of machine tools, as defined in the International Standard ISO 230/2 (2006) or national equivalents, shall not be considered.</p> <p data-bbox="475 689 1267 819">Machine tools and any combination thereof, for removing (or cutting) metals, ceramics or “composites”, which, according to the manufacturer’s technical specification, can be equipped with electronic devices for “numerical control”, as follows:</p> <p data-bbox="475 842 533 871"><u>N.B.</u></p> <p data-bbox="475 882 852 911">See also Category Code 2B201.</p> <p data-bbox="475 934 560 963"><u>Note 1</u></p> <p data-bbox="475 974 1267 1070">Category Code 2B001 does not include special purpose machine tools limited to the manufacture of gears. For such machines see Category Code 2B003.</p> <p data-bbox="475 1093 560 1122"><u>Note 2</u></p> <p data-bbox="475 1133 1267 1196">Category Code 2B001 does not include special purpose machine tools limited to the manufacture of any of the following:</p> <ul style="list-style-type: none"> <li data-bbox="475 1218 852 1247">a. Crankshafts or camshafts;</li> <li data-bbox="475 1270 738 1299">b. Tools or cutters;</li> <li data-bbox="475 1321 743 1350">c. Extruder worms;</li> <li data-bbox="475 1373 1011 1402">d. Engraved or faceted jewellery parts;<u>or</u></li> <li data-bbox="475 1424 759 1453">e. Dental prostheses.</li> </ul> <p data-bbox="475 1476 560 1505"><u>Note 3</u></p> <p data-bbox="475 1516 1267 1668">A machine tool having at least two of the three turning, milling or grinding capabilities (e.g. a turning machine with milling capability), shall be treated as coming within those entries in Category Codes 2B001.a., .b. and .c. that are applicable to its capabilities.</p> <p data-bbox="475 1691 533 1720"><u>N.B.</u></p> <p data-bbox="475 1731 1171 1760">For optical finishing machines, see Category Code 2B002.</p> <ul style="list-style-type: none"> <li data-bbox="475 1783 1182 1812">a. Machine tools for turning, having all of the following:</li> </ul>

<i>Category Code</i>	<i>Item Description</i>
	<ol style="list-style-type: none"> <li>1. Positioning accuracy with “all compensations available” equal to or less (better) than 3 µm according to ISO 230/2 (2006) or national equivalents along one or more linear axis; <u>and</u></li> <li>2. Two or more axes which can be coordinated simultaneously for “contouring control”;</li> </ol> <p><i>Note</i>  <i>Category Code 2B001.a. does not include turning machines specially designed for producing contact lenses, having both of the following:</i></p> <ol style="list-style-type: none"> <li>a. <i>Machine controller limited to using ophthalmic based “software” for part programming data input; <u>and</u></i></li> <li>b. <i>No vacuum chucking.</i></li> </ol> <p>b. Machine tools for milling having any of the following:</p> <ol style="list-style-type: none"> <li>1. Having all of the following: <ol style="list-style-type: none"> <li>a. Positioning accuracy with “all compensations available” equal to or less (better) than 3 µm according to ISO 230/2 (2006) or national equivalents along one or more linear axis; <u>and</u></li> <li>b. Three linear axes plus one rotary axis which can be coordinated simultaneously for “contouring control”;</li> </ol> </li> <li>2. Five or more axes which can be coordinated simultaneously for “contouring control” having any of the following:</li> </ol> <p><i>N.B.</i>  <i>‘Parallel mechanism machine tools’ are specified in Category Code 2B001.b.2.d.</i></p> <ol style="list-style-type: none"> <li>a. Positioning accuracy with “all compensations available” equal to or less (better) than 3 µm according to ISO 230/2 (2006) or national equivalents along one or more linear axis with a travel length less than 1 m;</li> </ol>



<i>Category Code</i>	<i>Item Description</i>
	<ul style="list-style-type: none"> <li>b. Positioning accuracy with “all compensations available” equal to or less (better) than 4.5 <math>\mu\text{m}</math> according to ISO 230/2 (2006) or national equivalents along one or more linear axis with a travel length equal to or greater than 1 m and less than 2 m;</li> <li>c. Positioning accuracy with “all compensations available” equal to or less (better) than <math>4.5 + 7(L - 2) \mu\text{m}</math> (L is the travel length in meters) according to ISO 230/2 (2006) or national equivalents along one or more linear axis with a travel length equal to or greater than 2 m; <u>or</u></li> <li>d. Being a ‘parallel mechanism machine tool’;</li> </ul> <p><i>Technical Note</i>  <i>A ‘parallel mechanism machine tool’ is a machine tool having multiple rods which are linked with a platform and actuators; each of the actuators operates the respective rod simultaneously and independently.</i></p> <ul style="list-style-type: none"> <li>3. A positioning accuracy for jig boring machines, with “all compensations available”, equal to or less (better) than 3 <math>\mu\text{m}</math> according to ISO 230/2 (2006) or national equivalents along one or more linear axis; <u>or</u></li> <li>4. Fly cutting machines having all of the following: <ul style="list-style-type: none"> <li>a. Spindle “run-out” and “camming” less (better) than 0.0004 mm TIR; <u>and</u></li> <li>b. Angular deviation of slide movement (yaw, pitch and roll) less (better) than 2 seconds of arc, TIR over 300 mm of travel;</li> </ul> </li> </ul> <ul style="list-style-type: none"> <li>c. Machine tools for grinding having any of the following: <ul style="list-style-type: none"> <li>1. Having all of the following: <ul style="list-style-type: none"> <li>a. Positioning accuracy with “all compensations available” equal to or less (better) than 3 <math>\mu\text{m}</math> according to ISO 230/2 (2006) or national equivalents along one or more linear axis; <u>and</u></li> <li>b. Three or more axes which can be coordinated simultaneously for “contouring control”; <u>or</u></li> </ul> </li> </ul> </li> </ul>

<i>Category Code</i>	<i>Item Description</i>
	<p>2. Five or more axes which can be coordinated simultaneously for “contouring control”;</p> <p><i>Note</i>  <i>Category Code 2B001.c. does not include grinding machines as follows:</i></p> <p>a. <i>Cylindrical external, internal, and external-internal grinding machines, having all of the following:</i></p> <ol style="list-style-type: none"> <li>1. <i>Limited to cylindrical grinding; <u>and</u></i></li> <li>2. <i>Limited to a maximum workpiece capacity of 150 mm outside diameter or length.</i></li> </ol> <p>b. <i>Machines designed specifically as jig grinders that do not have a z-axis or a w-axis, with a positioning accuracy with “all compensations available” less (better) than 3 μm according to ISO 230/2 (2006) or national equivalents.</i></p> <p>c. <i>Surface grinders.</i></p> <p>d. <i>Electrical discharge machines (EDM) of the non-wire type which have two or more rotary axes which can be coordinated simultaneously for “contouring control”;</i></p> <p>e. <i>Machine tools for removing metals, ceramics or “composites”, having all of the following:</i></p> <ol style="list-style-type: none"> <li>1. <i>Removing material by means of any of the following:</i> <ol style="list-style-type: none"> <li>a. <i>Water or other liquid jets, including those employing abrasive additives;</i></li> <li>b. <i>Electron beam; <u>or</u></i></li> <li>c. <i>“Laser” beam; <u>and</u></i></li> </ol> </li> <li>2. <i>At least two rotary axes having all of the following:</i> <ol style="list-style-type: none"> <li>a. <i>Can be coordinated simultaneously for “contouring control”; <u>and</u></i></li> <li>b. <i>A positioning accuracy of less (better) than 0.003°;</i></li> </ol> </li> </ol>

<i>Category Code</i>	<i>Item Description</i>
2B002	<p>f. Deep-hole-drilling machines and turning machines modified for deep-hole-drilling, having a maximum depth-of-bore capability exceeding 5 m.</p> <p>Numerically controlled optical finishing machine tools equipped for selective material removal to produce non-spherical optical surfaces having all of the following characteristics:</p> <ol style="list-style-type: none"> <li>a. Finishing the form to less (better) than 1 <math>\mu\text{m}</math>;</li> <li>b. Finishing to a roughness less (better) than 100 nm rms;</li> <li>c. Four or more axes which can be coordinated simultaneously for “contouring control”; <u>and</u></li> <li>d. Using any of the following processes: <ol style="list-style-type: none"> <li>1. Magnetorheological finishing (‘MRF’);</li> <li>2. Electrorheological finishing (‘ERF’);</li> <li>3. ‘Energetic particle beam finishing’;</li> <li>4. ‘Inflatable membrane tool finishing’; <u>or</u></li> <li>5. ‘Fluid jet finishing’.</li> </ol> </li> </ol> <p><u>Technical Note</u></p> <p><i>For the purpose of Category Code 2B002:</i></p> <ol style="list-style-type: none"> <li>1. ‘MRF’ is a material removal process using an abrasive magnetic fluid whose viscosity is controlled by a magnetic field.</li> <li>2. ‘ERF’ is a removal process using an abrasive fluid whose viscosity is controlled by an electric field.</li> <li>3. ‘Energetic particle beam finishing’ uses Reactive Atom Plasmas (RAP) or ion-beams to selectively remove material.</li> <li>4. ‘Inflatable membrane tool finishing’ is a process that uses a pressurised membrane that deforms to contact the workpiece over a small area.</li> <li>5. ‘Fluid jet finishing’ makes use of a fluid stream for material removal.</li> </ol>

<i>Category Code</i>	<i>Item Description</i>
2B003	<p>“Numerically controlled” or manual machine tools, and specially designed components, controls and accessories therefor, specially designed for the shaving, finishing, grinding or honing of hardened (<math>R_c = 40</math> or more) spur, helical and double-helical gears with a pitch diameter exceeding 1,250 mm and a face width of 15% of pitch diameter or larger finished to a quality of AGMA 14 or better (equivalent to ISO 1328 class 3).</p>
2B004	<p>Hot “isostatic presses” having all of the following, and specially designed components and accessories therefor:</p> <p><u>N.B.</u>  <i>See also Category Codes 2B104 and 2B204.</i></p> <ol style="list-style-type: none"> <li>a. A controlled thermal environment within the closed cavity and a chamber cavity with an inside diameter of 406 mm or more; <u>and</u></li> <li>b. Having any of the following: <ol style="list-style-type: none"> <li>1. A maximum working pressure exceeding 207 MPa;</li> <li>2. A controlled thermal environment exceeding 1,773 K (1,500 °C); <u>or</u></li> <li>3. A facility for hydrocarbon impregnation and removal of resultant gaseous degradation products.</li> </ol> </li> </ol> <p><u>Technical Note</u>  <i>The inside chamber dimension is that of the chamber in which both the working temperature and the working pressure are achieved and does not include fixtures. That dimension will be the smaller of either the inside diameter of the pressure chamber or the inside diameter of the insulated furnace chamber, depending on which of the two chambers is located inside the other.</i></p> <p><u>N.B.</u>  <i>For specially designed dies, moulds and tooling, see Category Codes 1B003, 9B009 and Division 2 of Part I of this Schedule.</i></p>

<i>Category Code</i>	<i>Item Description</i>
2B005	<p>Equipment specially designed for the deposition, processing and in-process control of inorganic overlays, coatings and surface modifications, as follows, for non-electronic substrates, by processes shown in the Table and associated Notes following Category Code 2E003.f., and specially designed automated handling, positioning, manipulation and control components therefor:</p> <ol style="list-style-type: none"> <li>a. Chemical vapour deposition (CVD) production equipment having both of the following:           <p><i>N.B.</i> See also Category Code 2B105.</p> <ol style="list-style-type: none"> <li>1. A process modified for one of the following:               <ol style="list-style-type: none"> <li>a. Pulsating CVD;</li> <li>b. Controlled nucleation thermal deposition (CNTD); <u>or</u></li> <li>c. Plasma enhanced or plasma assisted CVD; <u>and</u></li> </ol> </li> <li>2. Having any of the following:               <ol style="list-style-type: none"> <li>a. Incorporating high vacuum (equal to or less than 0.01 Pa) rotating seals; <u>or</u></li> <li>b. Incorporating <i>in situ</i> coating thickness control;</li> </ol> </li> </ol> </li> <li>b. Ion implantation production equipment having beam currents of 5 mA or more;</li> <li>c. Electron beam physical vapour deposition (EB-PVD) production equipment incorporating power systems rated for over 80 kW and having any of the following:           <ol style="list-style-type: none"> <li>1. A liquid pool level “laser” control system which regulates precisely the ingots feed rate; <u>or</u></li> <li>2. A computer controlled rate monitor operating on the principle of photo-luminescence of the ionised atoms in the evaporant stream to control the deposition rate of a coating containing two or more elements;</li> </ol> </li> <li>d. Plasma spraying production equipment having any of the following:</li> </ol>

<i>Category Code</i>	<i>Item Description</i>
	<ol style="list-style-type: none"> <li>1. Operating at reduced pressure controlled atmosphere (equal to or less than 10 kPa measured above and within 300 mm of the gun nozzle exit) in a vacuum chamber capable of evacuation down to 0.01 Pa prior to the spraying process; <u>or</u></li> <li>2. Incorporating <i>in situ</i> coating thickness control;</li> </ol> <p>e. Sputter deposition production equipment capable of current densities of 0.1 mA/mm<sup>2</sup> or higher at a deposition rate of 15 µm/h or more;</p> <p>f. Cathodic arc deposition production equipment incorporating a grid of electromagnets for steering control of the arc spot on the cathode;</p> <p>g. Ion plating production equipment capable of the <i>in situ</i> measurement of any of the following:</p> <ol style="list-style-type: none"> <li>1. Coating thickness on the substrate and rate control; <u>or</u></li> <li>2. Optical characteristics.</li> </ol> <p><u>Note</u>  <i>Category Code 2B005 does not include chemical vapour deposition, cathodic arc, sputter deposition, ion plating or ion implantation equipment, specially designed for cutting or machining tools.</i></p>
2B006	<p>Dimensional inspection or measuring systems, equipment and “electronic assemblies”, as follows:</p> <p>a. Computer controlled or “numerically controlled” Coordinate Measuring Machines (CMM), having a three dimensional (volumetric) maximum permissible error of length measurement (<math>E_{0,MPE}</math>) at any point within the operating range of the machine (i.e. within the length of axes) equal to or less (better) than <math>(1.7 + L/1,000)</math> µm (L is the measured length in mm), according to ISO 10360-2 (2009);</p> <p><u>Technical Note</u>  <i>The <math>E_{0,MPE}</math> of the most accurate configuration of the CMM specified by the manufacturer (e.g. best of the following: probe, stylus length, motion parameters, environment) and with “all compensations available” shall be compared to the <math>1.7 + L/1,000</math> µm threshold.</i></p>

<i>Category Code</i>	<i>Item Description</i>
	<p><u><i>N.B.</i></u>  <i>See also Category Code 2B206.</i></p> <p>b. Linear and angular displacement measuring instruments, as follows:</p> <p>1. ‘Linear displacement’ measuring instruments having any of the following:</p> <p><u><i>Note</i></u>  <i>Displacement measuring “laser” interferometers are only included in Category Code 2B006.b.1.c.</i></p> <p><u><i>Technical Note</i></u>  <i>For the purpose of Category Code 2B006.b.1., ‘linear displacement’ means the change of distance between the measuring probe and the measured object.</i></p> <p>a. Non-contact type measuring systems with a “resolution” equal to or less (better) than 0.2 µm within a measuring range up to 0.2 mm;</p> <p>b. Linear Variable Differential Transformer (LVDT) systems having both of the following:</p> <p>1. Having any of the following:</p> <p>a. “Linearity” equal to or less (better) than 0.1% measured from 0 to the ‘full operating range’, for LVDTs with a ‘full operating range’ up to and including ± 5 mm; <u>or</u></p> <p>b. “Linearity” equal to or less (better) than 0.1% measured from 0 to 5 mm for LVDTs with a ‘full operating range’ greater than ± 5 mm; <u>and</u></p> <p>2. Drift equal to or less (better) than 0.1% per day at a standard ambient test room temperature ±1 K;</p>

Category Code	Item Description
	<p data-bbox="687 456 871 488"><u>Technical Note</u></p> <p data-bbox="687 499 1268 730"><i>For the purpose of Category Code 2B006.b.1.b., 'full operating range' is half of the total possible linear displacement of the LVDT. For example, LVDTs with a 'full operating range' up to and including <math>\pm 5</math> mm can measure a total possible linear displacement of 10 mm.</i></p> <p data-bbox="624 748 1268 1397"> <ul style="list-style-type: none"> <li>c. Measuring systems having all of the following:               <ul style="list-style-type: none"> <li>1. Containing a "laser"; <u>and</u></li> <li>2. Maintaining, for at least 12 hours, at a temperature of <math>20\pm 1^{\circ}\text{C}</math>, all of the following:                   <ul style="list-style-type: none"> <li>a. A "resolution" over their full scale of <math>0.1\ \mu\text{m}</math> or less (better); <u>and</u></li> <li>b. Capable of achieving a "measurement uncertainty" equal to or less (better) than <math>(0.2 + L/2,000)\ \mu\text{m}</math> (L is the measured length in mm) at any point within a measuring range, when compensated for the refractive index of air; <u>or</u></li> </ul> </li> <li>d. "Electronic assemblies" specially designed to provide feedback capability in systems specified in Category Code 2B006.b.1.c.;</li> </ul> </li> </ul> </p> <p data-bbox="603 1417 663 1449"><u>Note</u></p> <p data-bbox="603 1458 1268 1657"><i>Category Code 2B006.b.1. does not include measuring interferometer systems, with an automatic control system that is designed to use no feedback techniques, containing a "laser" to measure slide movement errors of machine-tools, dimensional inspection machines or similar equipment.</i></p> <p data-bbox="539 1675 1268 1774"> <ul style="list-style-type: none"> <li>2. Angular displacement measuring instruments having an angular position "accuracy" equal to or less (better) than <math>0.00025^{\circ}</math>;</li> </ul> </p>



Category Code	Item Description
	<p data-bbox="603 454 663 483"><u>Note</u></p> <p data-bbox="603 495 1267 622"><i>Category Code 2B006.b.2. does not include optical instruments, such as autocollimators, using collimated light (e.g. laser light) to detect angular displacement of a mirror.</i></p> <p data-bbox="475 645 1267 741">c. Equipment for measuring surface roughness (including surface defects), by measuring optical scatter with a sensitivity of 0.5 nm or less (better).</p> <p data-bbox="475 763 536 792"><u>Note</u></p> <p data-bbox="475 804 1267 931"><i>Category Code 2B006 includes machine tools, other than those specified by Category Code 2B001, that can be used as measuring machines if they meet or exceed the criteria specified for the measuring machine function.</i></p> <p data-bbox="347 1003 432 1032">2B007</p> <p data-bbox="475 1003 1267 1066">“Robots” having any of the following characteristics and specially designed controllers and “end-effectors” therefor:</p> <p data-bbox="475 1088 536 1117"><u>N.B.</u></p> <p data-bbox="475 1128 852 1158"><i>See also Category Code 2B207.</i></p> <p data-bbox="475 1180 1267 1308">a. Capable in real-time of full three-dimensional image processing or full three-dimensional ‘scene analysis’ to generate or modify “programs” or to generate or modify numerical program data;</p> <p data-bbox="539 1330 724 1359"><u>Technical Note</u></p> <p data-bbox="539 1370 1267 1498"><i>The ‘scene analysis’ limitation does not include approximation of the third dimension by viewing at a given angle, or limited grey scale interpretation for the perception of depth or texture for the approved tasks (2½ D).</i></p> <p data-bbox="475 1520 1267 1583">b. Specially designed to comply with national safety standards applicable to potentially explosive munitions environments;</p> <p data-bbox="539 1606 600 1635"><u>Note</u></p> <p data-bbox="539 1646 1267 1709"><i>Category Code 2B007.b. does not include “robots” specially designed for paint-spraying booths.</i></p> <p data-bbox="475 1731 1267 1827">c. Specially designed or rated as radiation-hardened to withstand a total radiation dose greater than <math>5 \times 10^3</math> Gy (silicon) without operational degradation; <u>or</u></p>

Category Code	Item Description
2B008	<p><u>Technical Note</u> The term Gy (silicon) refers to the energy in Joules per kilogram absorbed by an unshielded silicon sample when exposed to ionising radiation.</p> <p>d. Specially designed to operate at altitudes exceeding 30,000 m.</p> <p>Assemblies or units, specially designed for machine tools, or dimensional inspection or measuring systems and equipment, as follows:</p> <p>a. Linear position feedback units having an overall “accuracy” less (better) than <math>(800 + (600 \times L/1,000))</math> nm (L equals the effective length in mm);</p> <p><u>N.B.</u> For “laser” systems see also Note to Category Codes 2B006.b.1.c. and d.</p> <p>b. Rotary position feedback units having an “accuracy” less (better) than 0.00025°;</p> <p><u>N.B.</u> For “laser” systems see also Note to Category Code 2B006.b.2.</p> <p><u>Note</u> Category Codes 2B008.a. and 2B008.b. include units, which are designed to determine the positioning information for feedback control, such as inductive type devices, graduated scales, infrared systems or “laser” systems.</p> <p>c. “Compound rotary tables” and “tilting spindles”, capable of upgrading, according to the manufacturer’s specifications, machine tools to or above the levels specified in Category 2B.</p>
2B009	Spin-forming machines and flow-forming machines, which, according to the manufacturer’s technical specification, can be equipped with “numerical control” units or a computer control and having both of the following:

<i>Category Code</i>	<i>Item Description</i>
	<p><u>N.B.</u>  <i>See also Category Codes 2B109 and 2B209.</i></p> <p>a. Three or more axes which can be coordinated simultaneously for “contouring control”; <u>and</u></p> <p>b. A roller force more than 60 kN.</p> <p><u>Technical Note</u>  <i>For the purpose of Category Code 2B009, machines combining the function of spin-forming and flow-forming are regarded as flow-forming machines.</i></p>
2B104	<p>“Isostatic presses”, other than those specified in Category Code 2B004, having all of the following:</p> <p><u>N.B.</u>  <i>See also Category Code 2B204.</i></p> <p>a. Maximum working pressure of 69 MPa or greater;</p> <p>b. Designed to achieve and maintain a controlled thermal environment of 873 K (600°C) or greater; <u>and</u></p> <p>c. Possessing a chamber cavity with an inside diameter of 254 mm or greater.</p>
2B105	<p>Chemical Vapour Deposition (CVD) furnaces, other than those specified in Category Code 2B005.a., designed or modified for the densification of carbon-carbon composites.</p>
2B109	<p>Flow-forming machines, other than those specified in Category Code 2B009, and specially designed components as follows:</p> <p><u>N.B.</u>  <i>See also Category Code 2B209.</i></p> <p>a. Flow-forming machines having both of the following:</p> <ol style="list-style-type: none"> <li>1. According to the manufacturer’s technical specification, can be equipped with “numerical control” units or a computer control, even when not equipped with such units; <u>and</u></li> </ol>

<i>Category Code</i>	<i>Item Description</i>
	<p>2. With more than two axes which can be coordinated simultaneously for “contouring control”;</p> <p>b. Specially designed components for flow-forming machines specified in Category Code 2B009 or 2B109.a.</p> <p><i>Note</i>  <i>Category Code 2B109 does not include machines that are not usable in the production of propulsion components and equipment (e.g. motor cases) for systems specified in Category Code 9A005, 9A007.a. or 9A105.a.</i></p> <p><i>Technical Note</i>  <i>Machines combining the function of spin-forming and flow-forming are for the purpose of Category Code 2B109 regarded as flow-forming machines.</i></p>
2B116	<p>Vibration test systems, equipment and components therefor, as follows:</p> <p>a. Vibration test systems employing feedback or closed loop techniques and incorporating a digital controller, capable of vibrating a system at an acceleration equal to or greater than 10 g rms between 20 Hz and 2 kHz while imparting forces equal to or greater than 50 kN, measured ‘bare table’;</p> <p>b. Digital controllers, combined with specially designed vibration test software, with a ‘real-time control bandwidth’ greater than 5 kHz designed for use with vibration test systems specified in Category Code 2B116.a.;</p> <p><i>Technical Note</i>  <i>In Category Code 2B116.b., ‘real-time control bandwidth’ means the maximum rate at which a controller can execute complete cycles of sampling, processing data and transmitting control signals.</i></p> <p>c. Vibration thrusters (shaker units), with or without associated amplifiers, capable of imparting a force equal to or greater than 50 kN, measured ‘bare table’, and usable in vibration test systems specified in Category Code 2B116.a.;</p>

<i>Category Code</i>	<i>Item Description</i>
	<p>d. Test piece support structures and electronic units designed to combine multiple shaker units in a system capable of providing an effective combined force equal to or greater than 50 kN, measured 'bare table', and usable in vibration systems specified in Category Code 2B116.a.</p> <p><u>Technical Note</u>  <i>In Category Code 2B116, 'bare table' means a flat table, or surface, with no fixture or fittings.</i></p>
2B117	<p>Equipment and process controls, other than those specified in Category Code 2B004, 2B005.a., 2B104 or 2B105, designed or modified for densification and pyrolysis of structural composite rocket nozzles and re-entry vehicle nose tips.</p>
2B119	<p>Balancing machines and related equipment, as follows:</p> <p><u>N.B.</u>  <i>See also Category Code 2B219.</i></p> <p>a. Balancing machines having all the following characteristics:</p> <ol style="list-style-type: none"> <li>1. Not capable of balancing rotors/assemblies having a mass greater than 3 kg;</li> <li>2. Capable of balancing rotors/assemblies at speeds greater than 12,500 rpm;</li> <li>3. Capable of correcting unbalance in two planes or more; <u>and</u></li> <li>4. Capable of balancing to a residual specific unbalance of 0.2 g mm per kg of rotor mass;</li> </ol> <p><u>Note</u>  <i>Category Code 2B119.a. does not include balancing machines designed or modified for dental or other medical equipment.</i></p> <p>b. Indicator heads designed or modified for use with machines specified in Category Code 2B119.a.</p>

<i>Category Code</i>	<i>Item Description</i>
	<p data-bbox="539 456 722 488"><u>Technical Note</u></p> <p data-bbox="539 497 1260 562"><i>Indicator heads are sometimes known as balancing instrumentation.</i></p>
2B120	<p data-bbox="475 629 1260 694">Motion simulators or rate tables having all of the following characteristics:</p> <ol data-bbox="475 712 1260 1361" style="list-style-type: none"> <li data-bbox="475 712 762 743">a. Two axes or more;</li> <li data-bbox="475 763 1260 864">b. Designed or modified to incorporate slip rings or integrated non-contact devices capable of transferring electrical power, signal information, or both; <u>and</u></li> <li data-bbox="475 882 1059 913">c. Having any of the following characteristics: <ol data-bbox="539 931 1260 1361" style="list-style-type: none"> <li data-bbox="539 931 1158 963">1. For any single axis having all of the following: <ol data-bbox="624 981 1260 1160" style="list-style-type: none"> <li data-bbox="624 981 1260 1046">a. Capable of rates of 400 degrees/s or more, or 30 degrees/s or less; <u>and</u></li> <li data-bbox="624 1064 1260 1160">b. A rate resolution equal to or less than 6 degrees/s and an accuracy equal to or less than 0.6 degrees/s;</li> </ol> </li> <li data-bbox="539 1178 1260 1279">2. Having a worst-case rate stability equal to or better (less) than plus or minus 0.05% averaged over 10 degrees or more; <u>or</u></li> <li data-bbox="539 1296 1260 1361">3. A positioning “accuracy” equal to or less (better) than 5 arc second.</li> </ol> </li> </ol> <p data-bbox="475 1379 560 1411"><u>Note 1</u></p> <p data-bbox="475 1420 1260 1520"><i>Category Code 2B120 does not include rotary tables designed or modified for machine tools or for medical equipment. For machine tool rotary tables see Category Code 2B008.</i></p> <p data-bbox="475 1538 560 1570"><u>Note 2</u></p> <p data-bbox="475 1579 1260 1711"><i>Motion simulators or rate tables that satisfy all the characteristics under Category Code 2B120 remain within that Code whether or not slip rings or integrated non-contact devices are fitted on them at time of export.</i></p>
2B121	<p data-bbox="475 1778 1260 1879">Positioning tables (equipment capable of precise rotary positioning in any axes), other than those specified in Category Code 2B120, having all of the following characteristics:</p>

<i>Category Code</i>	<i>Item Description</i>
	<p>a. Two axes or more; <u>and</u></p> <p>b. A positioning “accuracy” equal to or less (better) than 5 arc second.</p> <p><i>Note</i>  <i>Category Code 2B121 does not include rotary tables designed or modified for machine tools or for medical equipment. For machine tool rotary tables see Category Code 2B008.</i></p>
2B122	<p>Centrifuges capable of imparting accelerations above 100 g and designed or modified to incorporate slip rings or integrated non-contact devices capable of transferring electrical power, signal information, or both.</p> <p><i>Note</i>  <i>Centrifuges that come within the description in Category Code 2B122 remain within that Code whether or not slip rings or integrated non-contact devices are fitted on them at time of export.</i></p>
2B201	<p>Machine tools and any combination thereof, other than those specified in Category Code 2B001, as follows, for removing or cutting metals, ceramics or “composites”, which, according to the manufacturer’s technical specification, can be equipped with electronic devices for simultaneous “contouring control” in two or more axes:</p> <p>a. Machine tools for milling, having any of the following characteristics:</p> <ol style="list-style-type: none"> <li>1. Positioning accuracies with “all compensations available” equal to or less (better) than 6 µm according to ISO 230/2 (1988) or national equivalents along any linear axis; <u>or</u></li> <li>2. Two or more contouring rotary axes;</li> </ol> <p><i>Note</i>  <i>Category Code 2B201.a. does not include milling machines having the following characteristics:</i></p> <p>a. <i>X-axis travel greater than 2 m; <u>and</u></i></p>

<i>Category Code</i>	<i>Item Description</i>
	<p data-bbox="539 454 1268 521"><i>b. Overall positioning accuracy on the x-axis more (worse) than 30 <math>\mu\text{m}</math>.</i></p> <p data-bbox="475 539 1268 600"><i>b. Machine tools for grinding, having any of the following characteristics:</i></p> <ol data-bbox="539 622 1268 801" style="list-style-type: none"> <li data-bbox="539 622 1268 757"><i>1. Positioning accuracies with “all compensations available” equal to or less (better) than 4 <math>\mu\text{m}</math> according to ISO 230/2 (1988) or national equivalents along any linear axis; <u>or</u></i></li> <li data-bbox="539 775 1038 801"><i>2. Two or more contouring rotary axes.</i></li> </ol> <p data-bbox="539 824 600 853"><i><u>Note</u></i></p> <p data-bbox="539 864 1268 925"><i>Category Code 2B201.b. does not include the following grinding machines:</i></p> <ol data-bbox="539 947 1268 1294" style="list-style-type: none"> <li data-bbox="539 947 1268 1043"><i>a. Cylindrical external, internal, and external-internal grinding machines having both of the following characteristics:</i> <ol data-bbox="624 1066 1268 1178" style="list-style-type: none"> <li data-bbox="624 1066 1268 1126"><i>1. Limited to a maximum workpiece capacity of 150 mm outside diameter or length; <u>and</u></i></li> <li data-bbox="624 1149 994 1178"><i>2. Axes limited to x, z and c;</i></li> </ol> </li> <li data-bbox="539 1200 1268 1294"><i>b. Jig grinders that do not have a z-axis or a w-axis with an overall positioning accuracy less (better) than 4 <math>\mu\text{m}</math> according to ISO 230/2 (1988) or national equivalents.</i></li> </ol> <p data-bbox="475 1317 560 1346"><i><u>Note 1</u></i></p> <p data-bbox="475 1357 1268 1417"><i>Category Code 2B201 does not include special purpose machine tools limited to the manufacture of any of the following parts:</i></p> <ol data-bbox="475 1440 850 1585" style="list-style-type: none"> <li data-bbox="475 1440 624 1469"><i>a. Gears;</i></li> <li data-bbox="475 1480 850 1509"><i>b. Crankshafts or camshafts;</i></li> <li data-bbox="475 1520 775 1550"><i>c. Tools or cutters; <u>or</u></i></li> <li data-bbox="475 1561 738 1590"><i>d. Extruder worms.</i></li> </ol> <p data-bbox="475 1612 560 1641"><i><u>Note 2</u></i></p> <p data-bbox="475 1653 1268 1809"><i>A machine tool having at least two of the three turning, milling or grinding capabilities (e.g. a turning machine with milling capability) shall be treated as coming within those entries in Category Code 2B001.a. or b. or c.; or 2B201.a. or .b. that are applicable to its capabilities.</i></p>



<i>Category Code</i>	<i>Item Description</i>
2B204	<p>“Isostatic presses”, other than those specified in Category Code 2B004 or 2B104, and related equipment, as follows:</p> <ol style="list-style-type: none"> <li>a. “Isostatic presses” having both of the following characteristics:               <ol style="list-style-type: none"> <li>1. Capable of achieving a maximum working pressure of 69 MPa or greater; <u>and</u></li> <li>2. A chamber cavity with an inside diameter in excess of 152 mm;</li> </ol> </li> <li>b. Dies, moulds and controls, specially designed for “isostatic presses” specified in Category Code 2B204.a.</li> </ol> <p><i>Technical Note</i>  <i>In Category Code 2B204, the inside chamber dimension is that of the chamber in which both the working temperature and the working pressure are achieved and does not include fixtures. That dimension will be the smaller of either the inside diameter of the pressure chamber or the inside diameter of the insulated furnace chamber, depending on which of the two chambers is located inside the other.</i></p>
2B206	<p>Dimensional inspection machines, instruments or systems, other than those specified in Category Code 2B006, as follows:</p> <ol style="list-style-type: none"> <li>a. Computer controlled or numerically controlled coordinate measuring machines (CMM) having either of the following characteristics:               <ol style="list-style-type: none"> <li>1. Having only two axes and having a maximum permissible error of length measurement along any axis (one dimensional), identified as any combination of <math>E_{0x,MPE}</math>, <math>E_{0y,MPE}</math>, or <math>E_{0z,MPE}</math>, equal to or less (better) than <math>(1.25 + L/1,000) \mu\text{m}</math> (where L is the measured length in mm) at any point within the operating range of the machine (i.e. within the length of the axis), according to ISO 10360-2(2009); <u>or</u></li> </ol> </li> </ol>

<i>Category Code</i>	<i>Item Description</i>
	<p>2. Three or more axes and having a three dimensional (volumetric) maximum permissible error of length measurement (<math>E_{0,MPE}</math>) equal to or less (better) than <math>(1.7 + L/800) \mu\text{m}</math> (where L is the measured length in mm) at any point within the operating range of the machine (i.e. within the length of the axis), according to ISO 10360-2(2009);</p> <p><i>Technical Note</i>  <i>The <math>E_{0,MPE}</math> of the most accurate configuration of the CMM specified according to ISO 10360-2(2009) by the manufacturer (e.g. best of the following: probe, stylus, length, motion parameters, environments) and with all compensations available shall be compared to the <math>1.7 + L/800 \mu\text{m}</math> threshold.</i></p> <p>b. Systems for simultaneous linear-angular inspection of hemishells, having both of the following characteristics:</p> <ol style="list-style-type: none"> <li>1. “Measurement uncertainty” along any linear axis equal to or less (better) than <math>3.5 \mu\text{m}</math> per 5 mm; <u>and</u></li> <li>2. “Angular position deviation” equal to or less than <math>0.02^\circ</math>.</li> </ol> <p><i>Note 1</i>  <i>Machine tools that can be used as measuring machines are included if they meet or exceed the criteria specified for the machine tool function or the measuring machine function.</i></p> <p><i>Note 2</i>  <i>A machine specified in Category Code 2B206 is included in that Category Code if it exceeds the specifications stated therein anywhere within its operating range.</i></p> <p><i>Technical Note</i>  <i>All parameters of measurement values in Category Code 2B206 represent plus/minus i.e. not total band.</i></p>
2B207	<p>“Robots”, “end-effectors” and control units, other than those specified in Category Code 2B007, as follows:</p>

<i>Category Code</i>	<i>Item Description</i>
	<ul style="list-style-type: none"> <li>a. “Robots” or “end-effectors” specially designed to comply with national safety standards applicable to handling high explosives (e.g. meeting electrical code ratings for high explosives);</li> <li>b. Control units specially designed for any of the “robots” or “end-effectors” specified in Category Code 2B207.a.</li> </ul>
2B209	<p>Flow forming machines, spin forming machines capable of flow forming functions, other than those specified in Category Code 2B009 or 2B109, and mandrels, as follows:</p> <ul style="list-style-type: none"> <li>a. Machines having both of the following characteristics:               <ul style="list-style-type: none"> <li>1. Three or more rollers (active or guiding); <u>and</u></li> <li>2. Which, according to the manufacturer’s technical specification, can be equipped with “numerical control” units or a computer control;</li> </ul> </li> <li>b. Rotor-forming mandrels designed to form cylindrical rotors of inside diameter between 75 mm and 400 mm.</li> </ul> <p><u>Note</u>  <i>Category Code 2B209.a. includes machines which have only a single roller designed to deform metal plus two auxiliary rollers which support the mandrel, but do not participate directly in the deformation process.</i></p>
2B219	<p>Centrifugal multiplane balancing machines, fixed or portable, horizontal or vertical, as follows:</p> <ul style="list-style-type: none"> <li>a. Centrifugal balancing machines designed for balancing flexible rotors having a length of 600 mm or more and having all of the following characteristics:               <ul style="list-style-type: none"> <li>1. Swing or journal diameter greater than 75 mm;</li> <li>2. Mass capability of from 0.9 kg to 23 kg; <u>and</u></li> <li>3. Capable of balancing speed of revolution greater than 5,000 rpm;</li> </ul> </li> <li>b. Centrifugal balancing machines designed for balancing hollow cylindrical rotor components and having all of the following characteristics:</li> </ul>

<i>Category Code</i>	<i>Item Description</i>
2B225	<ol style="list-style-type: none"> <li>1. Journal diameter greater than 75 mm;</li> <li>2. Mass capability of from 0.9 kg to 23 kg;</li> <li>3. Capable of balancing to a residual imbalance equal to or less than 0.01 kg × mm/kg per plane; <u>and</u></li> <li>4. Belt drive type.</li> </ol> <p>Remote manipulators that can be used to provide remote actions in radiochemical separation operations or hot cells, having either of the following characteristics:</p> <ol style="list-style-type: none"> <li>a. A capability of penetrating 0.6 m or more of hot cell wall (through-the-wall operation); <u>or</u></li> <li>b. A capability of bridging over the top of a hot cell wall with a thickness of 0.6 m or more (over-the-wall operation).</li> </ol> <p><u>Technical Note</u>  <i>Remote manipulators provide translation of human operator actions to a remote operating arm and terminal fixture. They may be of 'master/slave' type or operated by joystick or keypad.</i></p>
2B226	<p>Controlled atmosphere (vacuum or inert gas) induction furnaces, and power supplies therefor, as follows:</p> <p><u>N.B.</u>  <i>See also Category 3B.</i></p> <ol style="list-style-type: none"> <li>a. Furnaces having all of the following characteristics: <ol style="list-style-type: none"> <li>1. Capable of operation above 1,123 K (850 °C);</li> <li>2. Induction coils 600 mm or less in diameter; <u>and</u></li> <li>3. Designed for power inputs of 5 kW or more;</li> </ol> </li> <li>b. Power supplies, with a specified power output of 5 kW or more, specially designed for furnaces specified in Category Code 2B226.a.</li> </ol> <p><u>Note</u>  <i>Category Code 2B226.a. does not include furnaces designed for the processing of semiconductor wafers.</i></p>

<i>Category Code</i>	<i>Item Description</i>
2B227	<p>Vacuum or other controlled atmosphere metallurgical melting and casting furnaces and related equipment as follows:</p> <ol style="list-style-type: none"> <li>a. Arc remelt and casting furnaces having both of the following characteristics:               <ol style="list-style-type: none"> <li>1. Consumable electrode capacities between 1,000 cm<sup>3</sup> and 20,000 cm<sup>3</sup>; <u>and</u></li> <li>2. Capable of operating with melting temperatures above 1,973 K (1,700 °C);</li> </ol> </li> <li>b. Electron beam melting furnaces and plasma atomisation and melting furnaces, having both of the following characteristics:               <ol style="list-style-type: none"> <li>1. A power of 50 kW or greater; <u>and</u></li> <li>2. Capable of operating with melting temperatures above 1,473 K (1,200°C);</li> </ol> </li> <li>c. Computer control and monitoring systems specially configured for any of the furnaces specified in Category Code 2B227.a. or 2B227.b.</li> </ol>
2B228	<p>Rotor fabrication or assembly equipment, rotor straightening equipment, bellows-forming mandrels and dies, as follows:</p> <ol style="list-style-type: none"> <li>a. Rotor assembly equipment for assembly of gas centrifuge rotor tube sections, baffles, and end caps;           <p style="margin-left: 20px;"><i>Note</i> Category Code 2B228.a. includes precision mandrels, clamps, and shrink fit machines.</p> </li> <li>b. Rotor straightening equipment for alignment of gas centrifuge rotor tube sections to a common axis;           <p style="margin-left: 20px;"><i>Technical Note</i> Equipment specified in Category Code 2B228.b. normally consists of precision measuring probes linked to a computer that subsequently controls the action of, e.g. pneumatic rams used for aligning the rotor tube sections.</p> </li> <li>c. Bellows-forming mandrels and dies for producing single-convolution bellows.</li> </ol>

Category Code	Item Description
2B230	<p data-bbox="539 454 722 483"><u>Technical Note</u></p> <p data-bbox="539 495 1262 562"><i>In Category Code 2B228.c., the bellows have all of the following characteristics:</i></p> <ol data-bbox="539 577 1262 824" style="list-style-type: none"> <li>1. <i>Inside diameter between 75 mm and 400 mm;</i></li> <li>2. <i>Length equal to or greater than 12.7 mm;</i></li> <li>3. <i>Single convolution depth greater than 2 mm; <u>and</u></i></li> <li>4. <i>Made of high-strength aluminium alloys, maraging steel or high strength “fibrous or filamentary materials”.</i></li> </ol> <p data-bbox="475 896 1262 958">All types of ‘pressure transducers’ capable of measuring absolute pressures and having all of the following:</p> <ol data-bbox="475 981 1262 1541" style="list-style-type: none"> <li>a. Pressure sensing elements made of or protected by aluminium, aluminium alloy, aluminium oxide (alumina or sapphire), nickel, nickel alloy with more than 60% nickel by weight, or fully fluorinated hydrocarbon polymers;</li> <li>b. Seals, if any, essential for sealing the pressure sensing element, and in direct contact with the process medium, made of or protected by aluminium, aluminium alloy, aluminium oxide (alumina or sapphire), nickel, nickel alloy with more than 60% nickel by weight, or fully fluorinated hydrocarbon polymers; <u>and</u></li> <li>c. Having either of the following characteristics: <ol data-bbox="539 1395 1262 1541" style="list-style-type: none"> <li>1. A full scale of less than 13 kPa and an ‘accuracy’ of better than <math>\pm 1\%</math> of full-scale; <u>or</u></li> <li>2. A full scale of 13 kPa or greater and an ‘accuracy’ of better than <math>\pm 130</math> Pa when measured at 13 kPa.</li> </ol> </li> </ol> <p data-bbox="475 1563 671 1592"><u>Technical Notes</u></p> <ol data-bbox="475 1603 1262 1787" style="list-style-type: none"> <li>1. <i>In Category Code 2B230, ‘pressure transducer’ means a device that converts a pressure measurement into a signal.</i></li> <li>2. <i>For the purpose of Category Code 2B230, ‘accuracy’ includes non-linearity, hysteresis and repeatability at ambient temperature.</i></li> </ol>

<i>Category Code</i>	<i>Item Description</i>
2B231	<p>Vacuum pumps having all of the following characteristics:</p> <ol style="list-style-type: none"> <li>a. Input throat size equal to or greater than 380 mm;</li> <li>b. Pumping speed equal to or greater than 15 m<sup>3</sup>/s; <u>and</u></li> <li>c. Capable of producing an ultimate vacuum better than 13 mPa.</li> </ol> <p><u>Technical Notes</u></p> <ol style="list-style-type: none"> <li>1. The pumping speed is determined at the measurement point with nitrogen gas or air.</li> <li>2. The ultimate vacuum is determined at the input of the pump with the input of the pump blocked off.</li> </ol>
2B232	<p>High-velocity gun systems (propellant, gas, coil, electromagnetic, and electrothermal types, and other advanced systems) capable of accelerating projectiles to 1.5 km/s or greater.</p> <p><u>N.B.</u> See also Division 2 of Part I of this Schedule.</p>
2B233	<p>Bellows-sealed scroll-type compressors and bellows-sealed scroll-type vacuum pumps having all of the following:</p> <p><u>N.B.</u> See also Category Code 2B350.i.</p> <ol style="list-style-type: none"> <li>a. Capable of an inlet volume flow rate of 50 m<sup>3</sup>/h or greater;</li> <li>b. Capable of a pressure ratio of 2:1 or greater; <u>and</u></li> <li>c. Having all surfaces that come in contact with the process gas made from any of the following materials: <ol style="list-style-type: none"> <li>1. Aluminium or aluminium alloy;</li> <li>2. Aluminium oxide;</li> <li>3. Stainless steel;</li> <li>4. Nickel or nickel alloy;</li> <li>5. Phosphor bronze; <u>or</u></li> <li>6. Fluoropolymers.</li> </ol> </li> </ol>

<i>Category Code</i>	<i>Item Description</i>
2B350	<p>Chemical manufacturing facilities, equipment and components, as follows:</p> <p>a. Reaction vessels or reactors, with or without agitators, with total internal (geometric) volume greater than 0.1 m<sup>3</sup> (100 litres) and less than 20 m<sup>3</sup> (20,000 litres), where all surfaces that come in direct contact with the chemical(s) being processed or contained are made from any of the following materials:</p> <ol style="list-style-type: none"> <li>1. 'Alloys' with more than 25% nickel and 20% chromium by weight;</li> <li>2. Fluoropolymers (polymeric or elastomeric materials with more than 35% fluorine by weight);</li> <li>3. Glass (including vitrified or enamelled coatings or glass lining);</li> <li>4. Nickel or 'alloys' with more than 40% nickel by weight;</li> <li>5. Tantalum or tantalum 'alloys';</li> <li>6. Titanium or titanium 'alloys';</li> <li>7. Zirconium or zirconium 'alloys'; <u>or</u></li> <li>8. Niobium (columbium) or niobium 'alloys';</li> </ol> <p>b. Agitators designed for use in reaction vessels or reactors specified in Category Code 2B350.a.; and impellers, blades or shafts designed for such agitators, where all surfaces of the agitator that come in direct contact with the chemical(s) being processed or contained are made from any of the following materials:</p> <ol style="list-style-type: none"> <li>1. 'Alloys' with more than 25% nickel and 20% chromium by weight;</li> <li>2. Fluoropolymers (polymeric or elastomeric materials with more than 35% fluorine by weight);</li> <li>3. Glass (including vitrified or enamelled coatings or glass lining);</li> <li>4. Nickel or 'alloys' with more than 40% nickel by weight;</li> <li>5. Tantalum or tantalum 'alloys';</li> </ol>



<i>Category Code</i>	<i>Item Description</i>
	<ul style="list-style-type: none"> <li>6. Titanium or titanium ‘alloys’;</li> <li>7. Zirconium or zirconium ‘alloys’; <u>or</u></li> <li>8. Niobium (columbium) or niobium ‘alloys’;</li> </ul> <p>c. Storage tanks, containers or receivers with a total internal (geometric) volume greater than 0.1 m<sup>3</sup> (100 litres) where all surfaces that come in direct contact with the chemical(s) being processed or contained are made from any of the following materials:</p> <ul style="list-style-type: none"> <li>1. ‘Alloys’ with more than 25% nickel and 20% chromium by weight;</li> <li>2. Fluoropolymers (polymeric or elastomeric materials with more than 35% fluorine by weight);</li> <li>3. Glass (including vitrified or enamelled coatings or glass lining);</li> <li>4. Nickel or ‘alloys’ with more than 40% nickel by weight;</li> <li>5. Tantalum or tantalum ‘alloys’;</li> <li>6. Titanium or titanium ‘alloys’;</li> <li>7. Zirconium or zirconium ‘alloys’; <u>or</u></li> <li>8. Niobium (columbium) or niobium ‘alloys’;</li> </ul> <p>d. Heat exchangers or condensers with a heat transfer surface area greater than 0.15 m<sup>2</sup>, and less than 20 m<sup>2</sup>; and tubes, plates, coils or blocks (cores) designed for such heat exchangers or condensers, where all surfaces that come in direct contact with the chemical(s) being processed are made from any of the following materials:</p> <ul style="list-style-type: none"> <li>1. ‘Alloys’ with more than 25% nickel and 20% chromium by weight;</li> <li>2. Fluoropolymers (polymeric or elastomeric materials with more than 35% fluorine by weight);</li> <li>3. Glass (including vitrified or enamelled coatings or glass lining);</li> <li>4. Graphite or ‘carbon graphite’;</li> </ul>

<i>Category Code</i>	<i>Item Description</i>
	<ol style="list-style-type: none"> <li>5. Nickel or 'alloys' with more than 40% nickel by weight;</li> <li>6. Tantalum or tantalum 'alloys';</li> <li>7. Titanium or titanium 'alloys';</li> <li>8. Zirconium or zirconium 'alloys';</li> <li>9. Silicon carbide;</li> <li>10. Titanium carbide; <u>or</u></li> <li>11. Niobium (columbium) or niobium 'alloys';</li> </ol> <p>e. Distillation or absorption columns of internal diameter greater than 0.1 m; and liquid distributors, vapour distributors or liquid collectors designed for such distillation or absorption columns, where all surfaces that come in direct contact with the chemical(s) being processed are made from any of the following materials:</p> <ol style="list-style-type: none"> <li>1. 'Alloys' with more than 25% nickel and 20% chromium by weight;</li> <li>2. Fluoropolymers (polymeric or elastomeric materials with more than 35% fluorine by weight);</li> <li>3. Glass (including vitrified or enamelled coatings or glass lining);</li> <li>4. Graphite or 'carbon graphite';</li> <li>5. Nickel or 'alloys' with more than 40% nickel by weight;</li> <li>6. Tantalum or tantalum 'alloys';</li> <li>7. Titanium or titanium 'alloys';</li> <li>8. Zirconium or zirconium 'alloys'; <u>or</u></li> <li>9. Niobium (columbium) or niobium 'alloys';</li> </ol> <p>f. Remotely operated filling equipment in which all surfaces that come in direct contact with the chemical(s) being processed are made from any of the following materials:</p> <ol style="list-style-type: none"> <li>1. 'Alloys' with more than 25% nickel and 20% chromium by weight; <u>or</u></li> </ol>

<i>Category Code</i>	<i>Item Description</i>
	<p>2. Nickel or ‘alloys’ with more than 40% nickel by weight;</p> <p>g. Valves and components, as follows:</p> <p>1. Valves, having both of the following:</p> <ul style="list-style-type: none"> <li>a. A ‘nominal size’ greater than 10 mm (3/8"); <u>and</u></li> <li>b. All surfaces that come in direct contact with the chemical(s) being produced, processed, or contained are made from ‘corrosion resistant materials’;</li> </ul> <p>2. Valves, other than those specified in Category Code 2B350.g.1., having all of the following:</p> <ul style="list-style-type: none"> <li>a. A ‘nominal size’ equal to or greater than 25.4 mm (1") and equal to or less than 101.6 mm (4");</li> <li>b. Casings (valve bodies) or preformed casing liners;</li> <li>c. A closure element designed to be interchangeable; <u>and</u></li> <li>d. All surfaces of the casing (valve body) or preformed case liner that come in direct contact with the chemical(s) being produced, processed, or contained are made from ‘corrosion resistant materials’;</li> </ul> <p>3. Components, designed for valves specified in Category Code 2B350.g.1. or 2B350.g.2., in which all surfaces that come in direct contact with the chemical(s) being produced, processed, or contained are made from ‘corrosion resistant materials’, as follows:</p> <ul style="list-style-type: none"> <li>a. Casings (valve bodies);</li> <li>b. Preformed casing liners;</li> </ul> <p><u>Technical Notes</u></p> <p>1. For the purpose of Category Code 2B350.g., ‘corrosion resistant materials’ means any of the following materials:</p>

<i>Category Code</i>	<i>Item Description</i>
	<ul style="list-style-type: none"> <li>a. <i>Nickel or alloys with more than 40% nickel by weight;</i></li> <li>b. <i>Alloys with more than 25% nickel and 20% chromium by weight;</i></li> <li>c. <i>Fluoropolymers (polymeric or elastomeric materials with more than 35% fluorine by weight);</i></li> <li>d. <i>Glass or glass-lined (including vitrified or enamelled coatings);</i></li> <li>e. <i>Tantalum or tantalum alloys;</i></li> <li>f. <i>Titanium or titanium alloys;</i></li> <li>g. <i>Zirconium or zirconium alloys;</i></li> <li>h. <i>Niobium (columbium) or niobium alloys; <u>or</u></i></li> <li>i. <i>Ceramic materials as follows:</i> <ul style="list-style-type: none"> <li>1. <i>Silicon carbide with a purity of 80% or more by weight;</i></li> <li>2. <i>Aluminium oxide (alumina) with a purity of 99.9% or more by weight;</i></li> <li>3. <i>Zirconium oxide (zirconia);</i></li> </ul> </li> </ul> <p>2. <i>The 'nominal size' is defined as the smaller of the inlet and outlet diameters.</i></p> <ul style="list-style-type: none"> <li>h. Multi-walled piping incorporating a leak detection port, in which all surfaces that come in direct contact with the chemical(s) being processed or contained are made from any of the following materials: <ul style="list-style-type: none"> <li>1. 'Alloys' with more than 25% nickel and 20% chromium by weight;</li> <li>2. Fluoropolymers (polymeric or elastomeric materials with more than 35% fluorine by weight);</li> <li>3. Glass (including vitrified or enamelled coatings or glass lining);</li> <li>4. Graphite or 'carbon graphite';</li> </ul> </li> </ul>

<i>Category Code</i>	<i>Item Description</i>
	<ol style="list-style-type: none"> <li>5. Nickel or 'alloys' with more than 40% nickel by weight;</li> <li>6. Tantalum or tantalum 'alloys';</li> <li>7. Titanium or titanium 'alloys';</li> <li>8. Zirconium or zirconium 'alloys'; <u>or</u></li> <li>9. Niobium (columbium) or niobium 'alloys';</li> </ol> <p>i. Multiple-seal and seal-less pumps, with manufacturer's specified maximum flow-rate greater than 0.6 m<sup>3</sup>/hour, or vacuum pumps with manufacturer's specified maximum flow-rate greater than 5 m<sup>3</sup>/hour (under standard temperature (273 K (0°C)) and pressure (101.3 kPa) conditions), other than those specified in Category Code 2B233; and casings (pump bodies), preformed casing liners, impellers, rotors or jet pump nozzles designed for such pumps, in which all surfaces that come in direct contact with the chemical(s) being processed are made from any of the following materials:</p> <ol style="list-style-type: none"> <li>1. 'Alloys' with more than 25% nickel and 20% chromium by weight;</li> <li>2. Ceramics;</li> <li>3. Ferrosilicon (high silicon iron alloys);</li> <li>4. Fluoropolymers (polymeric or elastomeric materials with more than 35% fluorine by weight);</li> <li>5. Glass (including vitrified or enamelled coatings or glass lining);</li> <li>6. Graphite or 'carbon graphite';</li> <li>7. Nickel or 'alloys' with more than 40% nickel by weight;</li> <li>8. Tantalum or tantalum 'alloys';</li> <li>9. Titanium or titanium 'alloys';</li> <li>10. Zirconium or zirconium 'alloys'; <u>or</u></li> <li>11. Niobium (columbium) or niobium 'alloys';</li> </ol>

Category Code	Item Description
	<p data-bbox="539 456 722 488"><u>Technical Note</u></p> <p data-bbox="539 499 1262 663"><i>In Category Code 2B350.i., the term seal refers to only those seals that come into direct contact with the chemical(s) being processed (or are designed to), and provide a sealing function where a rotary or reciprocating drive shaft passes through a pump body.</i></p> <p data-bbox="475 680 1262 913">j. Incinerators designed to destroy chemicals specified in Category Code 1C350, having specially designed waste supply systems, special handling facilities and an average combustion chamber temperature greater than 1,273 K (1,000°C), in which all surfaces in the waste supply system that come into direct contact with the waste products are made from or lined with any of the following materials:</p> <ol data-bbox="539 931 1262 1128" style="list-style-type: none"> <li data-bbox="539 931 1262 999">1. ‘Alloys’ with more than 25% nickel and 20% chromium by weight;</li> <li data-bbox="539 1016 759 1048">2. Ceramics; <u>or</u></li> <li data-bbox="539 1066 1262 1128">3. Nickel or ‘alloys’ with more than 40% nickel by weight.</li> </ol> <p data-bbox="475 1151 536 1182"><u>Note</u></p> <p data-bbox="475 1193 1262 1357"><i>For the purpose of Category Code 2B350, the materials used for gaskets, packing, seals, screws, washers or other materials performing a sealing function do not determine the control status, provided that such components are designed to be interchangeable.</i></p> <p data-bbox="475 1375 671 1406"><u>Technical Notes</u></p> <ol data-bbox="475 1417 1262 1697" style="list-style-type: none"> <li data-bbox="475 1417 1262 1518">1. ‘Carbon graphite’ is a composition of amorphous carbon and graphite, in which the graphite content is 8% or more by weight.</li> <li data-bbox="475 1536 1262 1697">2. For the listed materials in the above entries, the term ‘alloy’ when not accompanied by a specific elemental concentration is understood as identifying those alloys where the identified metal is present in a higher percentage by weight than any other element.</li> </ol>

<i>Category Code</i>	<i>Item Description</i>
2B351	<p>Toxic gas monitoring systems and their dedicated detecting components, other than those specified in Category Code 1A004, as follows; and detectors; sensor devices; and replaceable sensor cartridges therefor:</p> <ol style="list-style-type: none"> <li>a. Designed for continuous operation and usable for the detection of chemical warfare agents or chemicals specified in Category Code 1C350, at concentrations of less than 0.3 mg/m<sup>3</sup>; <u>or</u></li> <li>b. Designed for the detection of cholinesterase-inhibiting activity.</li> </ol>
2B352	<p>Equipment capable of use in handling biological materials, as follows:</p> <ol style="list-style-type: none"> <li>a. Complete biological containment facilities at P3, P4 containment level; <ul style="list-style-type: none"> <li><i>Technical Note</i></li> <li><i>P3 or P4 (BL3, BL4, L3, L4) containment levels are as specified in the WHO Laboratory Biosafety manual (3rd edition, Geneva 2004).</i></li> </ul> </li> <li>b. Fermenters and components as follows: <ol style="list-style-type: none"> <li>1. Fermenters capable of cultivation of pathogenic “microorganisms” or of live cells, for the production of pathogenic viruses or toxins, without the propagation of aerosols, having a total capacity of 20 litres or more;</li> <li>2. Components designed for fermenters in Category Code 2B352.b.1. as follows: <ol style="list-style-type: none"> <li>a. Cultivation chambers designed to be sterilised or disinfected <i>in situ</i>;</li> <li>b. Cultivation chamber holding devices;</li> <li>c. Process control units capable of simultaneously monitoring and controlling two or more fermentation system parameters (e.g. temperature, pH, nutrients, agitation, dissolved oxygen, air flow, foam control);</li> </ol> </li> </ol> </li> </ol>

<i>Category Code</i>	<i>Item Description</i>
	<p data-bbox="539 454 722 483"><u>Technical Note</u></p> <p data-bbox="539 495 1262 591"><i>For the purpose of Category Code 2B352.b., fermenters include bioreactors, single-use (disposable) bioreactors, chemostats and continuous-flow systems.</i></p> <p data-bbox="475 613 1262 710">c. Centrifugal separators, capable of continuous separation without the propagation of aerosols, having all of the following characteristics:</p> <ol data-bbox="539 725 1262 943" style="list-style-type: none"> <li data-bbox="539 725 1078 754">1. Flow-rate exceeding 100 litres per hour;</li> <li data-bbox="539 777 1206 806">2. Components of polished stainless steel or titanium;</li> <li data-bbox="539 828 1262 891">3. One or more sealing joints within the steam containment area; <u>and</u></li> <li data-bbox="539 913 1238 943">4. Capable of <i>in situ</i> steam sterilisation in a closed state;</li> </ol> <p data-bbox="539 965 722 994"><u>Technical Note</u></p> <p data-bbox="539 1005 1031 1034"><i>Centrifugal separators include decanters.</i></p> <p data-bbox="475 1057 1262 1117">d. Cross (tangential) flow filtration equipment and components as follows:</p> <ol data-bbox="539 1140 1262 1570" style="list-style-type: none"> <li data-bbox="539 1140 1262 1267">1. Cross (tangential) flow filtration equipment capable of separation of pathogenic microorganisms, viruses, toxins or cell cultures having all of the following characteristics: <ol data-bbox="624 1290 1262 1570" style="list-style-type: none"> <li data-bbox="624 1290 1262 1352">a. A total filtration area equal to or greater than 1 m<sup>2</sup>; <u>and</u></li> <li data-bbox="624 1375 1262 1480">b. Having any of the following characteristics: <ol data-bbox="687 1420 1262 1570" style="list-style-type: none"> <li data-bbox="687 1420 1262 1480">1. Capable of being sterilised or disinfected <i>in situ</i>; <u>or</u></li> <li data-bbox="687 1503 1262 1570">2. Using disposable or single-use filtration components;</li> </ol> </li> </ol> </li> </ol>



<i>Category Code</i>	<i>Item Description</i>
	<p data-bbox="687 454 871 483"><u>Technical Note</u></p> <p data-bbox="687 495 1262 927"><i>In Category Code 2B352.d.1.b., sterilised denotes the elimination of all viable microbes from the equipment through the use of either physical (e.g. steam) or chemical agents. Disinfected denotes the destruction of potential microbial infectivity in the equipment through the use of chemical agents with a germicidal effect. Disinfection and sterilisation are distinct from sanitisation, the latter referring to cleaning procedures designed to lower the microbial content of equipment without necessarily achieving elimination of all microbial infectivity or viability.</i></p> <p data-bbox="539 949 600 978"><u>Note</u></p> <p data-bbox="539 990 1262 1055"><i>Category Code 2B352.d. does not include reverse osmosis equipment, as specified by the manufacturer.</i></p> <p data-bbox="539 1072 1262 1272">2. Cross (tangential) flow filtration components (e.g. modules, elements, cassettes, cartridges, units or plates) with filtration area equal to or greater than 0.2 m<sup>2</sup> for each component and designed for use in cross (tangential) flow filtration equipment specified in Category Code 2B352.d.;</p> <p data-bbox="475 1292 1262 1391">e. Steam sterilisable freeze drying equipment with a condenser capacity exceeding 10 kg of ice in 24 hours and less than 1,000 kg of ice in 24 hours;</p> <p data-bbox="475 1411 1262 1556">f. Protective and containment equipment, as follows:</p> <p data-bbox="539 1458 1262 1556">1. Protective full or half suits, or hoods dependent upon a tethered external air supply and operating under positive pressure;</p> <p data-bbox="603 1576 663 1606"><u>Note</u></p> <p data-bbox="603 1617 1262 1715"><i>Category Code 2B352.f.1. does not include suits designed to be worn with self-contained breathing apparatus.</i></p> <p data-bbox="539 1736 1262 1800">2. Class III biological safety cabinets or isolators with similar performance standards;</p>

Category Code	Item Description
	<p style="text-align: center;"><u>Note</u></p> <p style="text-align: center;"><i>In Category Code 2B352.f.2., isolators include flexible isolators, dry boxes, anaerobic chambers, glove boxes and laminar flow hoods (closed with vertical flow).</i></p> <p>g. Chambers designed for aerosol challenge testing with “microorganisms”, viruses or “toxins” and having a capacity of 1 m<sup>3</sup> or greater.</p> <p>h. Spray drying equipment capable of drying toxins or pathogenic microorganisms having all of the following:</p> <ol style="list-style-type: none"> <li>1. A water evaporation capacity of <math>\geq 0.4</math> kg/h and <math>\leq 400</math> kg/h;</li> <li>2. The ability to generate a typical mean product particle size of <math>\leq 10</math> <math>\mu\text{m}</math> with existing fittings or by minimal modification of the spray-dryer with atomisation nozzles enabling generation of the required particle size; <u>and</u></li> <li>3. Capable of being sterilised or disinfected <i>in situ</i>.</li> </ol>
<b>2C</b>	<p><b>Materials</b></p> <p>None.</p>
<b>2D</b> 2D001	<p><b>Software</b></p> <p>“Software”, other than that specified in Category Code 2D002, as follows:</p> <ol style="list-style-type: none"> <li>a. “Software” specially designed or modified for the “development” or “production” of equipment specified in Category Code 2A001 or 2B001;</li> <li>b. “Software” specially designed or modified for the “use” of equipment specified in Category Code 2A001.c., 2B001 or 2B003 to 2B009.</li> </ol> <p><u>Note</u></p> <p><i>Category Code 2D001 does not include part programming “software” that generates “numerical control” codes for machining various parts.</i></p>

<i>Category Code</i>	<i>Item Description</i>
2D002	<p>“Software” for electronic devices, even when residing in an electronic device or system, enabling such devices or systems to function as a “numerical control” unit, capable of coordinating simultaneously more than four axes for “contouring control”.</p> <p><u>Note 1</u> Category Code 2D002 does not include “software” specially designed or modified for the operation of items not specified in Category 2.</p> <p><u>Note 2</u> Category Code 2D002 does not include “software” for items specified in Category Code 2B002. See Category Codes 2D001 and 2D003 for “software” for items specified in Category Code 2B002.</p> <p><u>Note 3</u> Category Code 2D002 does not include “software” that is exported with, and the minimum necessary for the operation of, items not specified by Category 2.</p>
2D003	<p>“Software”, designed or modified for the operation of equipment specified in Category Code 2B002, that converts optical design, workpiece measurements and material removal functions into “numerical control” commands to achieve the desired workpiece form.</p>
2D101	<p>“Software” specially designed or modified for the “use” of equipment specified in Category Code 2B104, 2B105, 2B109, 2B116, 2B117 or 2B119 to 2B122.</p> <p><u>N.B.</u> See also Category Code 9D004.</p>
2D201	<p>“Software” specially designed for the “use” of equipment specified in Category Code 2B204, 2B206, 2B207, 2B209, 2B219 or 2B227.</p>

<i>Category Code</i>	<i>Item Description</i>
2D202	<p>“Software” specially designed or modified for the “development”, “production” or “use” of equipment specified in Category Code 2B201.</p> <p><i>Note</i>  <i>Category Code 2D202 does not include part programming “software” that generates “numerical control” command codes but does not allow direct use of equipment for machining various parts.</i></p>
2D351	<p>“Software”, other than that specified in Category Code 1D003, specially designed for the “use” of equipment specified in Category Code 2B351.</p>
<b>2E</b>	<b>Technology</b>
2E001	<p>“Technology” (according to the General Technology Note) for the “development” of equipment or “software” specified in Category 2A, 2B or 2D.</p> <p><i>Note</i>  <i>Category Code 2E001 includes “technology” for the integration of probe systems into coordinate measuring machines specified in Category Code 2B006.a.</i></p>
2E002	<p>“Technology” (according to the General Technology Note) for the “production” of equipment specified in Category 2A or 2B.</p>
2E003	<p>Other “technology”, as follows:</p> <ol style="list-style-type: none"> <li>a. “Technology” for the “development” of interactive graphics as an integrated part in “numerical control” units for preparation or modification of part programs;</li> <li>b. “Technology” for metal-working manufacturing processes, as follows: <ol style="list-style-type: none"> <li>1. “Technology” for the design of tools, dies or fixtures specially designed for any of the following processes: <ol style="list-style-type: none"> <li>a. “Superplastic forming”;</li> </ol> </li> </ol> </li> </ol>

<i>Category Code</i>	<i>Item Description</i>
	<ul style="list-style-type: none"> <li>b. "Diffusion bonding"; <u>or</u></li> <li>c. "Direct-acting hydraulic pressing";</li> </ul> <p>2. Technical data consisting of process methods or parameters as listed below used to control:</p> <ul style="list-style-type: none"> <li>a. "Superplastic forming" of aluminium alloys, titanium alloys or "superalloys": <ul style="list-style-type: none"> <li>1. Surface preparation;</li> <li>2. Strain rate;</li> <li>3. Temperature;</li> <li>4. Pressure;</li> </ul> </li> <li>b. "Diffusion bonding" of "superalloys" or titanium alloys: <ul style="list-style-type: none"> <li>1. Surface preparation;</li> <li>2. Temperature;</li> <li>3. Pressure;</li> </ul> </li> <li>c. "Direct-acting hydraulic pressing" of aluminium alloys or titanium alloys: <ul style="list-style-type: none"> <li>1. Pressure;</li> <li>2. Cycle time;</li> </ul> </li> <li>d. "Hot isostatic densification" of titanium alloys, aluminium alloys or "superalloys": <ul style="list-style-type: none"> <li>1. Temperature;</li> <li>2. Pressure;</li> <li>3. Cycle time;</li> </ul> </li> </ul> <p>c. "Technology" for the "development" or "production" of hydraulic stretch-forming machines and dies therefor, for the manufacture of airframe structures;</p> <p>d. "Technology" for the "development" of generators of machine tool instructions (e.g. part programs) from design data residing inside "numerical control" units;</p>

<i>Category Code</i>	<i>Item Description</i>
	<p>e. “Technology” for the “development” of integration “software” for incorporation of expert systems for advanced decision support of shop floor operations into “numerical control” units;</p> <p>f. “Technology” for the application of inorganic overlay coatings or inorganic surface modification coatings (specified in column 3 of the Table entitled Deposition Techniques) to non-electronic substrates (specified in column 2 of that Table), by processes specified in column 1 of that Table and defined in the Technical Note.</p> <p><u>Note</u> The Table entitled Deposition Techniques and Technical Note appear after Category Code 2E301.</p> <p><u>N.B</u> This table should be read to specify the technology of a particular Coating Process only when the Resultant Coating in column 3 is in a paragraph directly across from the relevant Substrate under column 2. e.g. Chemical Vapour Deposition (CVD) coating process technical data are included for the application of silicides to carbon-carbon, ceramic and metal “matrix” “composites” substrates, but are not included for the application of silicides to ‘cemented tungsten carbide’ (16), ‘silicon carbide’ (18) substrates. In the second case, the resultant coating is not listed in the paragraph under column 3 directly across from the paragraph under column 2 listing ‘cemented tungsten carbide’ (16), ‘silicon carbide’ (18).</p>
2E101	“Technology” (according to the General Technology Note) for the “use” of equipment or “software” specified in Category Code 2B004, 2B009, 2B104, 2B109, 2B116, 2B119 to 2B122 or 2D101.
2E201	“Technology” (according to the General Technology Note) for the “use” of equipment or “software” specified in Category Code 2A225, 2A226, 2B001, 2B006, 2B007.b., 2B007.c., 2B008, 2B009, 2B201, 2B204, 2B206, 2B207, 2B209, 2B225 to 2B233, 2D201 or 2D202.

<i>Category Code</i>	<i>Item Description</i>
2E301	“Technology” (according to the General Technology Note) for the “use” of goods specified in Category Codes 2B350 to 2B352.

TABLE – DEPOSITION TECHNIQUES

Notes

1. Bracketed numbers are explained in the Notes that appear after the table.
2. The coating processes under column 1 are further explained in the Technical Notes below.

1. Coating Process (1)	2. Substrate	3. Resultant Coating
A. Chemical Vapour Deposition (CVD)	“Superalloys”	Aluminides for internal passages
	Ceramics (19) and Low-expansion glasses (14)	Silicides Carbides Dielectric layers (15) Diamond Diamond-like carbon (17)
	Carbon-carbon, Ceramic and Metal “matrix” “composites”	Silicides Carbides Refractory metals Mixtures thereof (4) Dielectric layers (15) Aluminides Alloyed aluminides (2) Boron nitride
	Cemented tungsten carbide (16), Silicon carbide (18)	Carbides Tungsten Mixtures thereof (4) Dielectric layers (15)
	Molybdenum and Molybdenum alloys	Dielectric layers (15)

1. Coating Process (1)	2. Substrate	3. Resultant Coating
	Beryllium and Beryllium alloys  Sensor window materials (9)	Dielectric layers (15) Diamond Diamond-like carbon (17)  Dielectric layers (15) Diamond Diamond-like carbon (17)
B. Thermal-Evaporation Physical Vapour Deposition (TE-PVD)  B.1 Physical Vapour Deposition (PVD): Electron-Beam (EB-PVD)	“Superalloys”  Ceramics (19) and Low-expansion glasses (14)  Corrosion resistant steel (7)  Carbon-carbon, Ceramic and Metal “matrix” “composites”	Alloyed silicides Alloyed aluminides (2) MCrAlX (5) Modified zirconia (12) Silicides Aluminides Mixtures thereof (4)  Dielectric layers (15)  MCrAlX (5) Modified zirconia (12) Mixtures thereof (4)  Silicides Carbides Refractory metals Mixtures thereof (4) Dielectric layers (15) Boron nitride



1. Coating Process (1)	2. Substrate	3. Resultant Coating
B.2 Ion assisted resistive heating Physical Vapour Deposition (PVD) (Ion Plating)	Cemented tungsten carbide (16), Silicon carbide (18)	Carbides Tungsten Mixtures thereof (4) Dielectric layers (15)
	Molybdenum and Molybdenum alloys	Dielectric layers (15)
	Beryllium and Beryllium alloys	Dielectric layers (15) Borides Beryllium
	Sensor window materials (9)	Dielectric layers (15)
	Titanium alloys (13)	Borides Nitrides
	Ceramics (19) and Low-expansion glasses (14)	Dielectric layers (15) Diamond-like carbon (17)
	Carbon-carbon, Ceramic and Metal "matrix" "composites"	Dielectric layers (15)
	Cemented tungsten carbide (16), Silicon carbide	Dielectric layers (15)
	Molybdenum and Molybdenum alloys	Dielectric layers (15)
	Beryllium and Beryllium alloys	Dielectric layers (15)
Sensor window materials (9)	Dielectric layers (15) Diamond-like carbon (17)	

1. Coating Process (1)	2. Substrate	3. Resultant Coating
<p>B.3 Physical Vapour Deposition (PVD): “Laser” Vaporisation</p> <p>B.4 Physical Vapour Deposition (PVD): Cathodic Arc Discharge</p>	<p>Ceramics (19) and Low-expansion glasses (14)</p> <p>Carbon-carbon, Ceramic and Metal “matrix” “composites”</p> <p>Cemented tungsten carbide (16), Silicon carbide</p> <p>Molybdenum and Molybdenum alloys</p> <p>Beryllium and Beryllium alloys</p> <p>Sensor window materials (9)</p> <p>“Superalloys”</p> <p>Polymers (11) and Organic “matrix” “composites”</p>	<p>Silicides</p> <p>Dielectric layers (15)</p> <p>Diamond-like carbon (17)</p> <p>Dielectric layers (15)</p> <p>Dielectric layers (15)</p> <p>Dielectric layers (15)</p> <p>Dielectric layers (15)</p> <p>Dielectric layers (15)</p> <p>Dielectric layers (15)</p> <p>Diamond-like carbon (17)</p> <p>Alloyed silicides</p> <p>Alloyed aluminides (2)</p> <p>MCrAlX (5)</p> <p>Borides</p> <p>Carbides</p> <p>Nitrides</p> <p>Diamond-like carbon (17)</p>
<p>C. Pack cementation (See A above for out-of-pack cementation) (10)</p>	<p>Carbon-carbon, Ceramic and Metal “matrix” “composites”</p> <p>Titanium alloys (13)</p> <p>Refractory metals and alloys (8)</p>	<p>Silicides</p> <p>Carbides</p> <p>Mixtures thereof (4)</p> <p>Silicides</p> <p>Aluminides</p> <p>Alloyed aluminides (2)</p> <p>Silicides</p> <p>Oxides</p>

1. Coating Process (1)	2. Substrate	3. Resultant Coating
D. Plasma spraying	“Superalloys”	MCrAlX (5) Modified zirconia (12) Mixtures thereof (4) Abradable Nickel-Graphite Abradable materials containing Ni-Cr-Al Abradable Al-Si-Polyester Alloyed aluminides (2)
	Aluminium alloys (6)	MCrAlX (5) Modified zirconia (12) Silicides Mixtures thereof (4)
	Refractory metals and alloys (8)	Aluminides Silicides Carbides
	Corrosion resistant steel (7)	MCrAlX (5) Modified zirconia (12) Mixtures thereof (4)
	Titanium alloys (13)	Carbides Aluminides Silicides Alloyed aluminides (2) Abradable Nickel-Graphite Abradable materials containing Ni-Cr-Al Abradable Al-Si-Polyester

1. Coating Process (1)	2. Substrate	3. Resultant Coating
E. Slurry Deposition	Refractory metals and alloys (8)  Carbon-carbon, Ceramic and Metal "matrix" "composites"	Fused silicides Fused aluminides except for resistance heating elements  Silicides Carbides Mixtures thereof (4)
F. Sputter Deposition	"Superalloys"  Ceramics and Low-expansion glasses (14)  Titanium alloys (13)	Alloyed silicides Alloyed aluminides (2) Noble metal modified aluminides (3) MCrAlX (5) Modified zirconia (12) Platinum Mixtures thereof (4)  Silicides Platinum Mixtures thereof (4) Dielectric layers (15) Diamond-like carbon (17)  Borides Nitrides Oxides Silicides Aluminides Alloyed aluminides (2) Carbides

1. Coating Process (1)	2. Substrate	3. Resultant Coating
	<p>Carbon-carbon, Ceramic and Metal “matrix” “composites”</p> <p>Cemented tungsten carbide (16), Silicon carbide (18)</p> <p>Molybdenum and Molybdenum alloys</p> <p>Beryllium and Beryllium alloys</p> <p>Sensor window materials (9)</p> <p>Refractory metals and alloys (8)</p>	<p>Silicides</p> <p>Carbides</p> <p>Refractory metals</p> <p>Mixtures thereof (4)</p> <p>Dielectric layers (15)</p> <p>Boron nitride</p> <p>Carbides</p> <p>Tungsten</p> <p>Mixtures thereof (4)</p> <p>Dielectric layers (15)</p> <p>Boron nitride</p> <p>Dielectric layers (15)</p> <p>Borides</p> <p>Dielectric layers (15)</p> <p>Beryllium</p> <p>Dielectric layers (15)</p> <p>Diamond-like carbon (17)</p> <p>Aluminides</p> <p>Silicides</p> <p>Oxides</p> <p>Carbides</p>
G. Ion Implantation	<p>High temperature bearing steels</p> <p>Titanium alloys (13)</p> <p>Beryllium and Beryllium alloys</p> <p>Cemented tungsten carbide (16)</p>	<p>Additions of Chromium Tantalum or Niobium (Columbium)</p> <p>Borides</p> <p>Nitrides</p> <p>Borides</p> <p>Carbides</p> <p>Nitrides</p>

TABLE — DEPOSITION TECHNIQUES — NOTES

1. The term ‘coating process’ includes coating repair and refurbishing as well as original coating.
2. The term ‘alloyed aluminide coating’ includes single or multiple-step coatings in which an element or elements are deposited prior to or during application of the aluminide coating, even if these elements are deposited by another coating process. It does not, however, include the multiple use of single-step pack cementation processes to achieve alloyed aluminides.
3. The term ‘noble metal modified aluminide’ coating includes multiple-step coatings in which the noble metal or noble metals are laid down by some other coating process prior to application of the aluminide coating.
4. The term ‘mixtures thereof’ includes infiltrated material, graded compositions, co-deposits and multilayer deposits and are obtained by one or more of the coating processes specified in the Table.
5. ‘MCrAlX’ refers to a coating alloy where M equals cobalt, iron, nickel or combinations thereof and X equals hafnium, yttrium, silicon, tantalum in any amount or other intentional additions over 0.01% by weight in various proportions and combinations, except:
  - a. CoCrAlY coatings which contain less than 22% by weight of chromium, less than 7% by weight of aluminium and less than 2% by weight of yttrium;
  - b. CoCrAlY coatings which contain 22% to 24% by weight of chromium, 10% to 12% by weight of aluminium and 0.5% to 0.7% by weight of yttrium; or
  - c. NiCrAlY coatings which contain 21% to 23% by weight of chromium, 10% to 12% by weight of aluminium and 0.9% to 1.1% by weight of yttrium.
6. The term ‘aluminium alloys’ refers to alloys having an ultimate tensile strength of 190 MPa or more measured at 293 K (20°C).
7. The term ‘corrosion resistant steel’ refers to AISI (American Iron and Steel Institute) 300 series or equivalent national standard steels.
8. ‘Refractory metals and alloys’ include the following metals and their alloys: niobium (columbium), molybdenum, tungsten and tantalum.

- 
9. 'Sensor window materials', as follows: alumina, silicon, germanium, zinc sulphide, zinc selenide, gallium arsenide, diamond, gallium phosphide, sapphire and the following metal halides: sensor window materials of more than 40 mm diameter for zirconium fluoride and hafnium fluoride.
  10. "Technology" for single-step pack cementation of solid airfoils is not included in Category 2.
  11. 'Polymers', as follows: polyimide, polyester, polysulphide, polycarbonates and polyurethanes.
  12. 'Modified zirconia' refers to additions of other metal oxides (e.g. calcia, magnesia, yttria, hafnia, rare earth oxides) to zirconia in order to stabilise certain crystallographic phases and phase compositions. Thermal barrier coatings made of zirconia, modified with calcia or magnesia by mixing or fusion, are not included.
  13. 'Titanium alloys' refers only to aerospace alloys having an ultimate tensile strength of 900 MPa or more measured at 293 K (20°C).
  14. 'Low-expansion glasses' refers to glasses which have a coefficient of thermal expansion of  $1 \times 10^{-7} \text{ K}^{-1}$  or less measured at 293 K (20°C).
  15. 'Dielectric layers' are coatings constructed of multi-layers of insulator materials in which the interference properties of a design composed of materials of various refractive indices are used to reflect, transmit or absorb various wavelength bands. Dielectric layers refer to more than four dielectric layers or dielectric/metal "composite" layers.
  16. 'Cemented tungsten carbide' does not include cutting and forming tool materials consisting of tungsten carbide/(cobalt, nickel), titanium carbide/(cobalt, nickel), chromium carbide/nickel-chromium and chromium carbide/nickel.
  17. "Technology" specially designed to deposit diamond-like carbon on any of the following is not included in Category 2:  
magnetic disk drives and heads, equipment for the manufacture of disposables, valves for faucets, acoustic diaphragms for speakers, engine parts for automobiles, cutting tools, punching-pressing dies, office automation equipment, microphones or medical devices or moulds, for casting or moulding of plastics, manufactured from alloys containing less than 5% beryllium.
  18. 'Silicon carbide' does not include cutting and forming tool materials.
  19. Ceramic substrates, as used in this Table, does not include ceramic materials containing 5% by weight, or greater, clay or cement content, either as separate constituents or in combination.

## TABLE — DEPOSITION TECHNIQUES — TECHNICAL NOTE

Processes specified in Column 1 of the Table are defined as follows:

- a. Chemical Vapour Deposition (CVD) is an overlay coating or surface modification coating process wherein a metal, alloy, “composite”, dielectric or ceramic is deposited upon a heated substrate. Gaseous reactants are decomposed or combined in the vicinity of a substrate resulting in the deposition of the desired elemental, alloy or compound material on the substrate. Energy for this decomposition or chemical reaction process may be provided by the heat of the substrate, a glow discharge plasma, or “laser” irradiation.

Note 1

*CVD includes the following processes: directed gas flow out-of-pack deposition, pulsating CVD, controlled nucleation thermal deposition (CNTD), plasma enhanced or plasma assisted CVD processes.*

Note 2

*Pack denotes a substrate immersed in a powder mixture.*

Note 3

*The gaseous reactants used in the out-of-pack process are produced using the same basic reactions and parameters as the pack cementation process, except that the substrate to be coated is not in contact with the powder mixture.*

- b. Thermal Evaporation-Physical Vapour Deposition (TE-PVD) is an overlay coating process conducted in a vacuum with a pressure less than 0.1 Pa wherein a source of thermal energy is used to vaporise the coating material. This process results in the condensation, or deposition, of the evaporated species onto appropriately positioned substrates.

The addition of gases to the vacuum chamber during the coating process to synthesise compound coatings is an ordinary modification of the process.

The use of ion or electron beams, or plasma, to activate or assist the coating's deposition is also a common modification in this technique. The use of monitors to provide in-process measurement of optical characteristics and thickness of coatings can be a feature of these processes.



---

Specific TE-PVD processes are as follows:

1. Electron Beam PVD uses an electron beam to heat and evaporate the material which forms the coating;
2. Ion Assisted Resistive Heating PVD employs electrically resistive heating sources in combination with impinging ion beam(s) to produce a controlled and uniform flux of evaporated coating species;
3. “Laser” Vaporisation uses either pulsed or continuous wave “laser” beams to vaporise the material which forms the coating;
4. Cathodic Arc Deposition employs a consumable cathode of the material which forms the coating and has an arc discharge established on the surface by a momentary contact of a ground trigger. Controlled motion of arcing erodes the cathode surface creating a highly ionised plasma. The anode can be either a cone attached to the periphery of the cathode, through an insulator, or the chamber. Substrate biasing is used for non-line-of-sight deposition.

*Note*

*This definition does not include random cathodic arc deposition with non-biased substrates.*

5. Ion Plating is a special modification of a general TE-PVD process in which a plasma or an ion source is used to ionise the species to be deposited, and a negative bias is applied to the substrate in order to facilitate the extraction of the species from the plasma. The introduction of reactive species, evaporation of solids within the process chamber, and the use of monitors to provide in-process measurement of optical characteristics and thicknesses of coatings are ordinary modifications of the process.
- c. Pack Cementation is a surface modification coating or overlay coating process wherein a substrate is immersed in a powder mixture (a pack), that consists of:
1. The metallic powders that are to be deposited (usually aluminium, chromium, silicon or combinations thereof);
  2. An activator (normally a halide salt); and
  3. An inert powder, most frequently alumina.

The substrate and powder mixture is contained within a retort which is heated to between 1,030 K (757°C) and 1,375 K (1,102°C) for sufficient time to deposit the coating.

- 
- d. Plasma Spraying is an overlay coating process wherein a gun (spray torch) which produces and controls a plasma accepts powder or wire coating materials, melts them and propels them towards a substrate, whereon an integrally bonded coating is formed. Plasma spraying constitutes either low pressure plasma spraying or high velocity plasma spraying.

Note 1

*Low pressure means less than ambient atmospheric pressure.*

Note 2

*High velocity refers to nozzle-exit gas velocity exceeding 750 m/s calculated at 293 K (20°C) at 0.1 MPa.*

- e. Slurry Deposition is a surface modification coating or overlay coating process wherein a metallic or ceramic powder with an organic binder is suspended in a liquid and is applied to a substrate by either spraying, dipping or painting, subsequent air or oven drying, and heat treatment to obtain the desired coating.
- f. Sputter Deposition is an overlay coating process based on a momentum transfer phenomenon, wherein positive ions are accelerated by an electric field towards the surface of a target (coating material). The kinetic energy of the impacting ions is sufficient to cause target surface atoms to be released and deposited on an appropriately positioned substrate.

Note 1

*The Table refers only to triode, magnetron or reactive sputter deposition which is used to increase adhesion of the coating and rate of deposition and to radio frequency (RF) augmented sputter deposition used to permit vaporisation of non-metallic coating materials.*

Note 2

*Low-energy ion beams (less than 5 keV) can be used to activate the deposition.*

- g. Ion Implantation is a surface modification coating process in which the element to be alloyed is ionised, accelerated through a potential gradient and implanted into the surface region of the substrate. This includes processes in which ion implantation is performed simultaneously with electron beam physical vapour deposition or sputter deposition.

Category Code	Item Description
<b>CATEGORY 3 — ELECTRONICS</b>	
<b>3A</b>	<p><b>Systems, Equipment and Components</b></p> <p><u>Note 1</u>  <i>Equipment and components described in Category Code 3A001 or 3A002, other than those described in Category Code 3A001.a.3. to 3A001.a.10., 3A001.a.12. or 3A001.a.13., which are specially designed for or which have the same functional characteristics as other equipment shall only be treated as coming within that description if that other equipment is included in Division 2 of this Part.</i></p> <p><u>Note 2</u>  <i>Integrated circuits described in Category Code 3A001.a.3. to 3A001.a.9., 3A001.a.12. or 3A001.a.13., which are unalterably programmed or designed for a specific function for another equipment shall only be treated as coming within that description if that other equipment is included in Division 2 of this Part.</i></p> <p><u>N.B.</u>  <i>Where it is unclear if the other equipment is included in Division 2 of this Part, then the integrated circuit is treated as falling within Category Code 3A001.a.3. to 3A001.a.9., 3A001.a.12. and 3A001.a.13. if it comes within the relevant description therein.</i></p>
3A001	<p>Electronic components and specially designed components therefor, as follows:</p> <p>a. General purpose integrated circuits, as follows:</p> <p><u>Note 1</u>  <i>Category Code 3A001.a. includes wafers (finished or unfinished) in which the function has been determined, if it comes within the parameters set out therein.</i></p> <p><u>Note 2</u>  <i>Integrated circuits include the following types:</i></p> <ul style="list-style-type: none"> <li>– “Monolithic integrated circuits”;</li> <li>– “Hybrid integrated circuits”;</li> <li>– “Multichip integrated circuits”;</li> </ul>

<i>Category Code</i>	<i>Item Description</i>
	<ul style="list-style-type: none"> <li>– “Film type integrated circuits”, including silicon-on-sapphire integrated circuits;</li> <li>– “Optical integrated circuits”;</li> <li>– “Three dimensional integrated circuits”.</li> </ul> <p>1. Integrated circuits designed or rated as radiation hardened to withstand any of the following:</p> <ul style="list-style-type: none"> <li>a. A total dose of <math>5 \times 10^3</math> Gy (silicon) or higher;</li> <li>b. A dose rate upset of <math>5 \times 10^6</math> Gy (silicon)/s or higher; <u>or</u></li> <li>c. A fluence (integrated flux) of neutrons (1 MeV equivalent) of <math>5 \times 10^{13}</math> n/cm<sup>2</sup> or higher on silicon, or its equivalent for other materials;</li> </ul> <p><i>Note</i>  <i>Category Code 3A001.a.1.c. does not include Metal Insulator Semiconductors (MIS).</i></p> <p>2. “Microprocessor microcircuits”, “microcomputer microcircuits”, microcontroller microcircuits, storage integrated circuits manufactured from a compound semiconductor, analogue-to-digital converters, digital-to-analogue converters, electro-optical or “optical integrated circuits” designed for “signal processing”, field programmable logic devices, custom integrated circuits for which either the function is unknown or it is unknown if the equipment in which the integrated circuit will be used is included in this Part, Fast Fourier Transform (FFT) processors, electrical erasable programmable read-only memories (EEPROMs), flash memories or static random-access memories (SRAMs), having any of the following:</p> <ul style="list-style-type: none"> <li>a. Rated for operation at an ambient temperature above 398 K (125°C);</li> <li>b. Rated for operation at an ambient temperature below 218 K (-55°C); <u>or</u></li> <li>c. Rated for operation over the entire ambient temperature range from 218 K (-55°C) to 398K (125°C);</li> </ul>

<i>Category Code</i>	<i>Item Description</i>
	<p data-bbox="603 456 667 488"><u>Note</u></p> <p data-bbox="603 497 1267 595"><i>Category Code 3A001.a.2. does not include integrated circuits for civil automobiles or railway train applications.</i></p> <p data-bbox="539 613 1267 748">3. “Microprocessor microcircuits”, “microcomputer microcircuits” and microcontroller microcircuits, manufactured from a compound semiconductor and operating at a clock frequency exceeding 40 MHz;</p> <p data-bbox="603 766 667 797"><u>Note</u></p> <p data-bbox="603 806 1267 904"><i>Category Code 3A001.a.3. includes digital signal processors, digital array processors and digital coprocessors.</i></p> <p data-bbox="539 922 724 954">4. Not used;</p> <p data-bbox="539 972 1267 1070">5. Analogue-to-Digital Converter (ADC) and Digital-to-Analogue Converter (DAC) integrated circuits, as follows:</p> <p data-bbox="628 1088 1114 1120">a. ADCs having any of the following:</p> <p data-bbox="692 1137 756 1169"><u>N.B.</u></p> <p data-bbox="692 1178 1069 1209"><i>See also Category Code 3A101.</i></p> <ol data-bbox="692 1227 1267 1830" style="list-style-type: none"> <li data-bbox="692 1227 1267 1326">1. A resolution of 8 bit or more, but less than 10 bit, with an output rate greater than 1,000 million words per second;</li> <li data-bbox="692 1344 1267 1442">2. A resolution of 10 bit or more, but less than 12 bit, with an output rate greater than 300 million words per second;</li> <li data-bbox="692 1460 1267 1559">3. A resolution of 12 bit with an output rate greater than 200 million words per second;</li> <li data-bbox="692 1576 1267 1711">4. A resolution of more than 12 bit, but equal to or less than 14 bit, with an output rate greater than 125 million words per second; <u>or</u></li> <li data-bbox="692 1729 1267 1830">5. A resolution of more than 14 bit with an output rate greater than 20 million words per second;</li> </ol>

Category Code	Item Description
	<p data-bbox="608 456 799 488"><u>Technical Notes</u></p> <ol data-bbox="628 499 1267 1700" style="list-style-type: none"> <li data-bbox="628 499 1267 562">1. A resolution of <math>n</math> bit corresponds to a quantisation of <math>2^n</math> levels.</li> <li data-bbox="628 577 1267 640">2. The number of bits in the output word is equal to the resolution of the ADC.</li> <li data-bbox="628 656 1267 763">3. The output rate is the maximum output rate of the converter, regardless of the architecture or oversampling.</li> <li data-bbox="628 779 1267 887">4. For ‘multiple channel ADCs’, the outputs are not aggregated and the output rate is the maximum output rate of any single channel.</li> <li data-bbox="628 902 1267 1064">5. For ‘interleaved ADCs’ or for ‘multiple channel ADCs’ that are specified to have an interleaved mode of operation, the outputs are aggregated and the output rate is the maximum combined total output rate of all of the outputs.</li> <li data-bbox="628 1079 1267 1216">6. Vendors may also refer to the output rate as sampling rate, conversion rate or throughput rate. It is often specified in megahertz (MHz) or mega samples per second (MSPS).</li> <li data-bbox="628 1232 1267 1339">7. For the purpose of measuring output rate, one output word per second is equivalent to one Hertz or one sample per second.</li> <li data-bbox="628 1355 1267 1491">8. ‘Multiple channel ADCs’ are defined as devices which integrate more than one ADC, designed so that each ADC has a separate analogue input.</li> <li data-bbox="628 1507 1267 1700">9. ‘Interleaved ADCs’ are defined as devices which have multiple ADC units that sample the same analogue input at different times such that when the outputs are aggregated, the analogue input has been effectively sampled and converted at a higher sampling rate.</li> </ol>

<i>Category Code</i>	<i>Item Description</i>
	<p>b. Digital-to-Analogue Converters (DAC) having any of the following:</p> <ol style="list-style-type: none"> <li>1. A resolution of 10 bit or more with an ‘adjusted update rate’ of 3,500 MSPS or greater; <u>or</u></li> <li>2. A resolution of 12 bit or more with an ‘adjusted update rate’ of equal to or greater than 1,250 MSPS and having any of the following: <ol style="list-style-type: none"> <li>a. A “settling time” less than 9 ns to 0.024% of full scale from a full scale step; <u>or</u></li> <li>b. A ‘Spurious Free Dynamic Range’ (SFDR) greater than 68 dBc (carrier) when synthesising a full scale analogue signal of 100 MHz or the highest full scale analogue signal frequency specified below 100 MHz.</li> </ol> </li> </ol> <p><i>Technical Notes</i></p> <ol style="list-style-type: none"> <li>1. ‘Spurious Free Dynamic Range’ (SFDR) is defined as the ratio of the RMS value of the carrier frequency (maximum signal component) at the input of the DAC to the RMS value of the next largest noise or harmonic distortion component at its output.</li> <li>2. SFDR is determined directly from the specification table or from the characterisation plots of SFDR versus frequency.</li> <li>3. A signal is defined to be full scale when its amplitude is greater than – 3 dBfs (full scale).</li> </ol>

Category Code	Item Description
	<p data-bbox="692 454 1150 488">4. <i>'Adjusted update rate' for DACs:</i></p> <p data-bbox="756 506 1262 902">a. <i>For conventional (non-interpolating) DACs, the 'adjusted update rate' is the rate at which the digital signal is converted to an analogue signal and the output analogue values are changed by the DAC. For DACs where the interpolation mode may be bypassed (interpolation factor of one), the DAC should be considered as a conventional (non-interpolating) DAC.</i></p> <p data-bbox="756 925 1262 1189">b. <i>For interpolating DACs (oversampling DACs), the 'adjusted update rate' is defined as the DAC update rate divided by the smallest interpolating factor. For interpolating DACs, the 'adjusted update rate' may be referred to by different terms including:</i></p> <ul style="list-style-type: none"> <li data-bbox="820 1211 1059 1245">– <i>input data rate</i></li> <li data-bbox="820 1261 1067 1294">– <i>input word rate</i></li> <li data-bbox="820 1310 1091 1344">– <i>input sample rate</i></li> <li data-bbox="820 1359 1230 1393">– <i>maximum total input bus rate</i></li> <li data-bbox="820 1408 1259 1473">– <i>maximum DAC clock rate for DAC clock input.</i></li> </ul> <p data-bbox="544 1491 1262 1592">6. <i>Electro-optical and "optical integrated circuits", designed for "signal processing" and having all of the following:</i></p> <ul style="list-style-type: none"> <li data-bbox="628 1610 1219 1644">a. <i>One or more than one internal "laser" diode;</i></li> <li data-bbox="628 1659 1262 1724">b. <i>One or more than one internal light detecting element; <u>and</u></i></li> <li data-bbox="628 1740 935 1774">c. <i>Optical waveguides;</i></li> </ul>



<i>Category Code</i>	<i>Item Description</i>
	<p>7. 'Field programmable logic devices' having any of the following:</p> <ol style="list-style-type: none"> <li>a. A 'maximum number of single-ended digital input/outputs' of greater than 700; <u>or</u></li> <li>b. An 'aggregate one-way peak serial transceiver data rate' of 500 Gb/s or greater;</li> </ol> <p><u>Note</u>  <i>Category Code 3A001.a.7. includes:</i></p> <ul style="list-style-type: none"> <li>– <i>Simple Programmable Logic Devices (SPLDs)</i></li> <li>– <i>Complex Programmable Logic Devices (CPLDs)</i></li> <li>– <i>Field Programmable Gate Arrays (FPGAs)</i></li> <li>– <i>Field Programmable Logic Arrays (FPLAs)</i></li> <li>– <i>Field Programmable Interconnects (FPICs)</i></li> </ul> <p><u>Technical Notes</u></p> <ol style="list-style-type: none"> <li>1. 'Field programmable logic devices' are also known as field programmable gate or field programmable logic arrays.</li> <li>2. Maximum number of digital inputs/outputs in Category Code 3A001.a.7.a. is also referred to as the maximum user inputs/outputs or maximum available inputs/outputs, whether the integrated circuit is packaged or bare die.</li> <li>3. 'Aggregate one-way peak serial transceiver data rate' is the product of the peak serial one-way transceiver data rate times the number of transceivers on the FPGA.</li> </ol> <p>8. Not used;</p> <p>9. Neural network integrated circuits;</p> <p>10. Custom integrated circuits for which the function is unknown, or the control status of the equipment in which the integrated circuits will be used is unknown to the manufacturer, having any of the following:</p> <ol style="list-style-type: none"> <li>a. More than 1,500 terminals;</li> </ol>

<i>Category Code</i>	<i>Item Description</i>
	<p data-bbox="628 454 1257 517">b. A typical “basic gate propagation delay time” of less than 0.02 ns; <u>or</u></p> <p data-bbox="628 539 1193 568">c. An operating frequency exceeding 3 GHz;</p> <p data-bbox="544 591 1257 719">11. Digital integrated circuits, other than those described in Category Codes 3A001.a.3. to 3A001.a.10. and 3A001.a.12., based upon any compound semiconductor and having either of the following:</p> <p data-bbox="628 741 1257 804">a. An equivalent gate count of more than 3,000 (2 input gates); <u>or</u></p> <p data-bbox="628 826 1161 855">b. A toggle frequency exceeding 1.2 GHz;</p> <p data-bbox="544 878 1257 1005">12. Fast Fourier Transform (FFT) processors having a rated execution time for an N-point complex FFT of less than <math>(N \log_2 N)/20,480</math> ms, where N is the number of points;</p> <p data-bbox="600 1028 783 1057"><i>Technical Note</i></p> <p data-bbox="600 1068 1257 1162"><i>When N is equal to 1,024 points, the formula in Category Code 3A001.a.12. gives an execution time of 500 <math>\mu</math>s.</i></p> <p data-bbox="544 1184 1257 1247">13. Direct Digital Synthesizer (DDS) integrated circuits having any of the following:</p> <p data-bbox="628 1270 1257 1397">a. A Digital-to-Analogue Converter (DAC) clock frequency of 3.5 GHz or more and a DAC resolution of 10 bit or more, but less than 12 bit; <u>or</u></p> <p data-bbox="628 1420 1257 1482">b. A DAC clock frequency of 1.25 GHz or more and a DAC resolution of 12 bit or more;</p> <p data-bbox="600 1505 783 1534"><i>Technical Note</i></p> <p data-bbox="600 1545 1257 1608"><i>The DAC clock frequency may be specified as the master clock frequency or the input clock frequency.</i></p> <p data-bbox="480 1630 1203 1659">b. Microwave or millimetre wave components, as follows:</p> <p data-bbox="544 1682 727 1711"><i>Technical Note</i></p> <p data-bbox="544 1722 1257 1877"><i>For the purpose of Category Code 3A001.b., the parameter peak saturated power output may also be referred to on product data sheets as output power, saturated power output, maximum power output, peak power output, or peak envelope power output.</i></p>

Category Code	Item Description
	<p>1. Electronic vacuum tubes and cathodes, as follows:</p> <p><u>Note 1</u>  <i>Category Code 3A001.b.1. does not include tubes designed or rated for operation in any frequency band and having both of the following:</i></p> <ul style="list-style-type: none"> <li>a. <i>Does not exceed 31.8 GHz; <u>and</u></i></li> <li>b. <i>Is “allocated by the ITU” for radio-communications services, but not for radio-determination.</i></li> </ul> <p><u>Note 2</u>  <i>Category Code 3A001.b.1. does not include non-“space-qualified” tubes having all of the following:</i></p> <ul style="list-style-type: none"> <li>a. <i>An average output power equal to or less than 50 W; <u>and</u></i></li> <li>b. <i>Designed or rated for operation in any frequency band and having all of the following:</i> <ul style="list-style-type: none"> <li>1. <i>Exceeds 31.8 GHz but does not exceed 43.5 GHz; <u>and</u></i></li> <li>2. <i>Is “allocated by the ITU” for radio-communications services, but not for radio-determination.</i></li> </ul> </li> <li>a. Travelling wave tubes, pulsed or continuous wave, as follows: <ul style="list-style-type: none"> <li>1. Tubes operating at frequencies exceeding 31.8 GHz;</li> <li>2. Tubes having a cathode heater element with a turn on time to rated RF power of less than 3 seconds;</li> <li>3. Coupled cavity tubes, or derivatives thereof, with a “fractional bandwidth” of more than 7% or a peak power exceeding 2.5 kW;</li> </ul> </li> </ul>

<i>Category Code</i>	<i>Item Description</i>
	<ol style="list-style-type: none"> <li data-bbox="692 456 1267 936">4. Helix tubes, or derivatives thereof, having any of the following:               <ol style="list-style-type: none"> <li data-bbox="756 539 1267 703">a. An “instantaneous bandwidth” of more than one octave, and average power (expressed in kW) times frequency (expressed in GHz) of more than 0.5;</li> <li data-bbox="756 725 1267 889">b. An “instantaneous bandwidth” of one octave or less, and average power (expressed in kW) times frequency (expressed in GHz) of more than 1; <u>or</u></li> <li data-bbox="756 911 1267 936">c. Being “space-qualified”;</li> </ol> </li> <li data-bbox="628 958 1267 1019">b. Crossed-field amplifier tubes with a gain of more than 17 dB;</li> <li data-bbox="628 1041 1267 1169">c. Impregnated cathodes designed for electronic tubes producing a continuous emission current density at rated operating conditions exceeding 5 A/cm<sup>2</sup>;</li> </ol> <ol style="list-style-type: none"> <li data-bbox="544 1191 1267 1859">2. Microwave “Monolithic Integrated Circuits” (MMIC) power amplifiers having any of the following:               <ol style="list-style-type: none"> <li data-bbox="628 1276 1267 1404">a. Rated for operation at frequencies exceeding 2.7 GHz up to and including 6.8 GHz with a “fractional bandwidth” greater than 15%, and having any of the following:                   <ol style="list-style-type: none"> <li data-bbox="692 1426 1267 1554">1. A peak saturated power output greater than 75 W (48.75 dBm) at any frequency exceeding 2.7 GHz up to and including 2.9 GHz;</li> <li data-bbox="692 1576 1267 1704">2. A peak saturated power output greater than 55 W (47.4 dBm) at any frequency exceeding 2.9 GHz up to and including 3.2 GHz;</li> <li data-bbox="692 1727 1267 1854">3. A peak saturated power output greater than 40 W (46 dBm) at any frequency exceeding 3.2 GHz up to and including 3.7 GHz; <u>or</u></li> </ol> </li> </ol> </li> </ol>

<i>Category Code</i>	<i>Item Description</i>
	<p data-bbox="692 456 1267 584">4. A peak saturated power output greater than 20 W (43 dBm) at any frequency exceeding 3.7 GHz up to and including 6.8 GHz;</p> <p data-bbox="628 607 1267 734">b. Rated for operation at frequencies exceeding 6.8 GHz up to and including 16 GHz with a “fractional bandwidth” greater than 10%, and having any of the following:</p> <ol data-bbox="692 757 1267 1032" style="list-style-type: none"> <li data-bbox="692 757 1267 884">1. A peak saturated power output greater than 10 W (40 dBm) at any frequency exceeding 6.8 GHz up to and including 8.5 GHz; <u>or</u></li> <li data-bbox="692 907 1267 1032">2. A peak saturated power output greater than 5 W (37 dBm) at any frequency exceeding 8.5 GHz up to and including 16 GHz;</li> </ol> <p data-bbox="628 1055 1267 1220">c. Rated for operation with a peak saturated power output greater than 3 W (34.77 dBm) at any frequency exceeding 16 GHz up to and including 31.8 GHz, and with a “fractional bandwidth” of greater than 10%;</p> <p data-bbox="628 1243 1267 1370">d. Rated for operation with a peak saturated power output greater than 0.1 nW (-70 dBm) at any frequency exceeding 31.8 GHz up to and including 37 GHz;</p> <p data-bbox="628 1393 1267 1559">e. Rated for operation with a peak saturated power output greater than 1 W (30 dBm) at any frequency exceeding 37 GHz up to and including 43.5 GHz, and with a “fractional bandwidth” of greater than 10%;</p> <p data-bbox="628 1581 1267 1740">f. Rated for operation with a peak saturated power output greater than 31.62 mW (15 dBm) at any frequency exceeding 43.5 GHz up to and including 75 GHz, and with a “fractional bandwidth” of greater than 10%;</p>

<i>Category Code</i>	<i>Item Description</i>
	<p data-bbox="628 456 1259 618">g. Rated for operation with a peak saturated power output greater than 10 mW (10 dBm) at any frequency exceeding 75 GHz up to and including 90 GHz, and with a “fractional bandwidth” of greater than 5%; <u>or</u></p> <p data-bbox="628 640 1259 734">h. Rated for operation with a peak saturated power output greater than 0.1 nW (-70 dBm) at any frequency exceeding 90 GHz;</p> <p data-bbox="604 757 687 786"><u>Note 1</u></p> <p data-bbox="604 797 719 826"><i>Not used.</i></p> <p data-bbox="604 848 687 878"><u>Note 2</u></p> <p data-bbox="604 889 1259 1084"><i>Whether any MMIC whose rated operating frequency includes frequencies listed in more than one frequency range, as defined by Category Codes 3A001.b.2.a. to 3A001.b.2.h., is included in that Category is determined by the lowest peak saturated power output threshold.</i></p> <p data-bbox="604 1106 687 1135"><u>Note 3</u></p> <p data-bbox="604 1146 1259 1279"><i>Notes 1 and 2 in Category 3A mean that Category Code 3A001.b.2. does not include MMICs if they are specially designed for other applications, e.g. telecommunications, radar, automobiles.</i></p> <p data-bbox="544 1301 1259 1361">3. Discrete microwave transistors having any of the following:</p> <p data-bbox="628 1384 1259 1478">a. Rated for operation at frequencies exceeding 2.7 GHz up to and including 6.8 GHz and having any of the following:</p> <ol data-bbox="692 1500 1259 1783" style="list-style-type: none"> <li data-bbox="692 1500 1259 1632">1. A peak saturated power output greater than 400 W (56 dBm) at any frequency exceeding 2.7 GHz up to and including 2.9 GHz;</li> <li data-bbox="692 1655 1259 1783">2. A peak saturated power output greater than 205 W (53.12 dBm) at any frequency exceeding 2.9 GHz up to and including 3.2 GHz;</li> </ol>

<i>Category Code</i>	<i>Item Description</i>
	<ol style="list-style-type: none"> <li data-bbox="692 456 1267 584">3. A peak saturated power output greater than 115 W (50.61 dBm) at any frequency exceeding 3.2 GHz up to and including 3.7 GHz; <u>or</u></li> <li data-bbox="692 607 1267 734">4. A peak saturated power output greater than 60 W (47.78 dBm) at any frequency exceeding 3.7 GHz up to and including 6.8 GHz;</li> </ol> <p data-bbox="628 757 1267 853">b. Rated for operation at frequencies exceeding 6.8 GHz up to and including 31.8 GHz and having any of the following:</p> <ol style="list-style-type: none"> <li data-bbox="692 875 1267 1003">1. A peak saturated power output greater than 50 W (47 dBm) at any frequency exceeding 6.8 GHz up to and including 8.5 GHz;</li> <li data-bbox="692 1025 1267 1153">2. A peak saturated power output greater than 15 W (41.76 dBm) at any frequency exceeding 8.5 GHz up to and including 12 GHz;</li> <li data-bbox="692 1176 1267 1303">3. A peak saturated power output greater than 40 W (46 dBm) at any frequency exceeding 12 GHz up to and including 16 GHz; <u>or</u></li> <li data-bbox="692 1326 1267 1453">4. A peak saturated power output greater than 7 W (38.45 dBm) at any frequency exceeding 16 GHz up to and including 31.8 GHz;</li> </ol> <p data-bbox="628 1476 1267 1603">c. Rated for operation with a peak saturated power output greater than 0.5 W (27 dBm) at any frequency exceeding 31.8 GHz up to and including 37 GHz;</p> <p data-bbox="628 1626 1267 1753">d. Rated for operation with a peak saturated power output greater than 1 W (30 dBm) at any frequency exceeding 37 GHz up to and including 43.5 GHz; <u>or</u></p> <p data-bbox="628 1776 1267 1874">e. Rated for operation with a peak saturated power output greater than 0.1 nW (-70 dBm) at any frequency exceeding 43.5 GHz;</p>

Category Code	Item Description
	<p data-bbox="603 454 687 488"><u>Note 1</u></p> <p data-bbox="603 497 1267 696"><i>Whether a transistor whose rated operating frequency includes frequencies listed in more than one frequency range, as defined by Category Codes 3A001.b.3.a. to 3A001.b.3.e., is included under that Category is determined by the lowest peak saturated power output threshold.</i></p> <p data-bbox="603 712 687 745"><u>Note 2</u></p> <p data-bbox="603 754 1267 954"><i>Category Code 3A001.b.3. includes bare dice, dice mounted on carriers, or dice mounted in packages. Some discrete transistors may also be referred to as power amplifiers, but the status of these discrete transistors is determined by Category Code 3A001.b.3.</i></p> <p data-bbox="539 969 1267 1825">           4. Microwave solid state amplifiers and microwave assemblies/modules containing microwave solid state amplifiers, that are any of the following:           <ol style="list-style-type: none"> <li data-bbox="627 1093 1267 1225">a. Rated for operation at frequencies exceeding 2.7 GHz up to and including 6.8 GHz with a “fractional bandwidth” greater than 15%, and having any of the following:               <ol style="list-style-type: none"> <li data-bbox="691 1240 1267 1373">1. A peak saturated power output greater than 500 W (57 dBm) at any frequency exceeding 2.7 GHz up to and including 2.9 GHz;</li> <li data-bbox="691 1388 1267 1520">2. A peak saturated power output greater than 270 W (54.3 dBm) at any frequency exceeding 2.9 GHz up to and including 3.2 GHz;</li> <li data-bbox="691 1536 1267 1668">3. A peak saturated power output greater than 200 W (53 dBm) at any frequency exceeding 3.2 GHz up to and including 3.7 GHz; <u>or</u></li> <li data-bbox="691 1684 1267 1816">4. A peak saturated power output greater than 90 W (49.54 dBm) at any frequency exceeding 3.7 GHz up to and including 6.8 GHz;</li> </ol> </li> </ol> </p>



<i>Category Code</i>	<i>Item Description</i>
	<ul style="list-style-type: none"> <li data-bbox="628 456 1267 584">b. Rated for operation at frequencies exceeding 6.8 GHz up to and including 31.8 GHz with a “fractional bandwidth” greater than 10%, and having any of the following:               <ul style="list-style-type: none"> <li data-bbox="692 607 1267 734">1. A peak saturated power output greater than 70 W (48.54 dBm) at any frequency exceeding 6.8 GHz up to and including 8.5 GHz;</li> <li data-bbox="692 757 1267 884">2. A peak saturated power output greater than 50 W (47 dBm) at any frequency exceeding 8.5 GHz up to and including 12 GHz;</li> <li data-bbox="692 907 1267 1034">3. A peak saturated power output greater than 30 W (44.77 dBm) at any frequency exceeding 12 GHz up to and including 16 GHz; <u>or</u></li> <li data-bbox="692 1057 1267 1184">4. A peak saturated power output greater than 20 W (43 dBm) at any frequency exceeding 16 GHz up to and including 31.8 GHz;</li> </ul> </li> <li data-bbox="628 1207 1267 1335">c. Rated for operation with a peak saturated power output greater than 0.5 W (27 dBm) at any frequency exceeding 31.8 GHz up to and including 37 GHz;</li> <li data-bbox="628 1357 1267 1525">d. Rated for operation with a peak saturated power output greater than 2 W (33 dBm) at any frequency exceeding 37 GHz up to and including 43.5 GHz, and with a “fractional bandwidth” of greater than 10%;</li> <li data-bbox="628 1547 1267 1787">e. Rated for operation at frequencies exceeding 43.5 GHz and having any of the following:               <ul style="list-style-type: none"> <li data-bbox="692 1630 1267 1787">1. A peak saturated power output greater than 0.2 W (23 dBm) at any frequency exceeding 43.5 GHz up to and including 75 GHz, and with a “fractional bandwidth” of greater than 10%;</li> </ul> </li> </ul>

<i>Category Code</i>	<i>Item Description</i>
	<p data-bbox="692 456 1267 622">2. A peak saturated power output greater than 20 mW (13 dBm) at any frequency exceeding 75 GHz up to and including 90 GHz, and with a “fractional bandwidth” of greater than 5%; <u>or</u></p> <p data-bbox="692 640 1267 741">3. A peak saturated power output greater than 0.1 nW (-70 dBm) at any frequency exceeding 90 GHz;</p> <p data-bbox="628 759 1267 824">f. Rated for operation at frequencies above 2.7 GHz and having all of the following:</p> <p data-bbox="692 842 1267 976">1. A peak saturation power (in watts), <math>P_{sat}</math>, greater than 400 divided by the maximum operating frequency (in GHz) squared [<math>P_{sat} &gt; 400 \text{ W} \cdot \text{GHz}^2 / f_{\text{GHz}}^2</math>];</p> <p data-bbox="692 994 1267 1059">2. A “fractional bandwidth” of 5% or greater; <u>and</u></p> <p data-bbox="692 1077 1267 1243">3. Any two sides perpendicular to one another with either length <math>d</math> (in cm) equal to or less than 15 divided by the lowest operating frequency in GHz [<math>d \leq 15 \text{ cm} \cdot \text{GHz} / f_{\text{GHz}}</math>];</p> <p data-bbox="756 1261 938 1290"><u>Technical Note</u></p> <p data-bbox="756 1308 1267 1496">2.7 GHz should be used as the lowest operating frequency (<math>f_{\text{GHz}}</math>) in the formula in Category Code 3A001.b.4.f.3., for amplifiers that have a rated operating range extending downward to 2.7 GHz and below [<math>d \leq 15 \text{ cm} \cdot \text{GHz} / 2.7 \text{ GHz}</math>].</p> <p data-bbox="608 1514 660 1543"><u>N.B.</u></p> <p data-bbox="608 1561 1267 1626">MMIC power amplifiers should be evaluated against the criteria in Category Code 3A001.b.2.</p> <p data-bbox="608 1644 687 1673"><u>Note 1</u></p> <p data-bbox="608 1691 719 1720">Not used.</p>

<i>Category Code</i>	<i>Item Description</i>
	<p data-bbox="603 454 687 483"><u>Note 2</u></p> <p data-bbox="603 495 1267 689"><i>Whether an item whose rated operating frequency includes frequencies listed in more than one frequency range, as defined by Category Codes 3A001.b.4.a. to 3A001.b.4.e., is included in that Category is determined by the lowest peak saturation output threshold.</i></p> <p data-bbox="603 712 687 741"><u>Note 3</u></p> <p data-bbox="603 752 1267 817"><i>Category Code 3A001.b.4. includes transmit/receive modules and transmit modules.</i></p> <ol style="list-style-type: none"> <li data-bbox="544 840 1267 1003">5. Electronically or magnetically tunable band-pass or band-stop filters, having more than 5 tunable resonators capable of tuning across 1.5:1 frequency band (<math>f_{\max}/f_{\min}</math>) in less than 10 <math>\mu</math>s and having any of the following: <ol style="list-style-type: none"> <li data-bbox="628 1025 1267 1090">a. A band-pass bandwidth of more than 0.5% of centre frequency; <u>or</u></li> <li data-bbox="628 1113 1267 1178">b. A band-stop bandwidth of less than 0.5% of centre frequency;</li> </ol> </li> <li data-bbox="544 1200 719 1229">6. Not used;</li> <li data-bbox="544 1252 1267 1370">7. Converters and harmonic mixers, designed to extend the frequency range of equipment described in Category Code 3A002.c., 3A002.d., 3A002.e. or 3A002.f. beyond the limits stated therein;</li> <li data-bbox="544 1393 1267 1671">8. Microwave power amplifiers containing tubes specified in Category Code 3A001.b.1. and having all of the following: <ol style="list-style-type: none"> <li data-bbox="628 1514 1126 1543">a. Operating frequencies above 3 GHz;</li> <li data-bbox="628 1565 1267 1630">b. An average output power to mass ratio exceeding 80 W/kg; <u>and</u></li> <li data-bbox="628 1653 1062 1682">c. A volume of less than 400 cm<sup>3</sup>;</li> </ol> </li> </ol>

Category Code	Item Description
	<p data-bbox="603 456 667 488"><u>Note</u></p> <p data-bbox="603 497 1267 663"><i>Category Code 3A001.b.8. does not include equipment designed or rated for operation in any frequency band which is “allocated by the ITU” for radio-communications services, but not for radio-determination.</i></p> <p data-bbox="539 680 1267 815">9. Microwave power modules (MPM), consisting of, at least, a travelling wave tube, a microwave “monolithic integrated circuit” and an integrated electronic power conditioner and having all of the following:</p> <ul style="list-style-type: none"> <li data-bbox="624 833 1267 898">a. A ‘turn-on time’ from off to fully operational in less than 10 seconds;</li> <li data-bbox="624 916 1267 981">b. A volume less than the maximum rated power in Watts multiplied by 10 cm<sup>3</sup>/W; <u>and</u></li> <li data-bbox="624 999 1267 1263">c. An “instantaneous bandwidth” greater than 1 octave (<math>f_{\max} &gt; 2f_{\min}</math>) and having any of the following: <ul style="list-style-type: none"> <li data-bbox="692 1115 1267 1211">1. For frequencies equal to or less than 18 GHz, an RF output power greater than 100 W; <u>or</u></li> <li data-bbox="692 1229 1267 1263">2. A frequency greater than 18 GHz;</li> </ul> </li> </ul> <p data-bbox="603 1281 799 1312"><u>Technical Notes</u></p> <ul style="list-style-type: none"> <li data-bbox="624 1330 1267 1487">1. <i>To calculate the volume in Category Code 3A001.b.9.b., the following example is provided: for a maximum rated power of 20 W, the volume would be: <math>20 \text{ W} \times 10 \text{ cm}^3/\text{W} = 200 \text{ cm}^3</math>.</i></li> <li data-bbox="624 1505 1267 1639">2. <i>The ‘turn-on time’ in Category Code 3A001.b.9.a. refers to the time from fully-off to fully operational, i.e. it includes the warm-up time of the MPM.</i></li> </ul> <p data-bbox="539 1657 1267 1724">10. Oscillators or oscillator assemblies, specified to operate with all of the following:</p> <ul style="list-style-type: none"> <li data-bbox="624 1742 1267 1874">a. A single sideband (SSB) phase noise, in dBc/Hz, better than <math>-(126 + 20\log_{10}F - 20\log_{10}f)</math> anywhere in the range of <math>10 \text{ Hz} &lt; F &lt; 10 \text{ kHz}</math>; <u>and</u></li> </ul>

<i>Category Code</i>	<i>Item Description</i>
	<p data-bbox="628 450 1267 584">b. A single sideband (SSB) phase noise, in dBc/Hz, better than <math>-(114 + 20\log_{10}F - 20\log_{10}f)</math> anywhere in the range of <math>10 \text{ kHz} \leq F &lt; 500 \text{ kHz}</math>;</p> <p data-bbox="603 607 788 636"><i>Technical Note</i></p> <p data-bbox="603 647 1267 745"><i>In Category Code 3A001.b.10., F is the offset from the operating frequency in Hz and f is the operating frequency in MHz.</i></p> <p data-bbox="544 763 1267 862">11. “Frequency synthesiser” “electronic assemblies” having a “frequency switching time” as specified by any of the following:</p> <p data-bbox="628 882 900 911">a. Less than 156 ps;</p> <p data-bbox="628 931 1267 1066">b. Less than 100 <math>\mu\text{s}</math> for any frequency change exceeding 1.6 GHz within the synthesised frequency range exceeding 4.8 GHz but not exceeding 10.6 GHz;</p> <p data-bbox="628 1086 1267 1220">c. Less than 250 <math>\mu\text{s}</math> for any frequency change exceeding 550 MHz within the synthesised frequency range exceeding 10.6 GHz but not exceeding 31.8 GHz;</p> <p data-bbox="628 1240 1267 1375">d. Less than 500 <math>\mu\text{s}</math> for any frequency change exceeding 550 MHz within the synthesised frequency range exceeding 31.8 GHz but not exceeding 43.5 GHz;</p> <p data-bbox="628 1395 1267 1529">e. Less than 1 ms for any frequency change exceeding 550 MHz within the synthesised frequency range exceeding 43.5 GHz but not exceeding 56 GHz;</p> <p data-bbox="628 1550 1267 1684">f. Less than 1 ms for any frequency change exceeding 2.2 GHz within the synthesised frequency range exceeding 56 GHz but not exceeding 75 GHz; <u>or</u></p> <p data-bbox="628 1704 1267 1747">g. Less than 1 ms within the synthesised frequency range exceeding 75 GHz;</p>

Category Code	Item Description
	<p data-bbox="603 456 660 488"><u>N.B.</u></p> <p data-bbox="603 499 1262 629"><i>For general purpose “signal analysers”, signal generators, network analysers and microwave test receivers, see Category Codes 3A002.c., 3A002.d., 3A002.e. and 3A002.f., respectively.</i></p> <p data-bbox="475 649 1262 712">c. Acoustic wave devices as follows and specially designed components therefor:</p> <p data-bbox="544 730 1262 831">1. Surface acoustic wave and surface skimming (shallow bulk) acoustic wave devices, having any of the following:</p> <p data-bbox="628 851 1262 882">a. A carrier frequency exceeding 6 GHz;</p> <p data-bbox="628 900 1262 1001">b. A carrier frequency exceeding 1 GHz, but not exceeding 6 GHz, and having any of the following:</p> <p data-bbox="692 1019 1262 1081">1. A ‘frequency side-lobe rejection’ exceeding 65 dB;</p> <p data-bbox="692 1099 1262 1200">2. A product of the maximum delay time and the bandwidth (time in <math>\mu\text{s}</math> and bandwidth in MHz) of more than 100;</p> <p data-bbox="692 1218 1262 1249">3. A bandwidth greater than 250 MHz; <u>or</u></p> <p data-bbox="692 1267 1262 1299">4. A dispersive delay of more than 10 <math>\mu\text{s}</math>; <u>or</u></p> <p data-bbox="628 1317 1262 1379">c. A carrier frequency of 1 GHz or less and having any of the following:</p> <p data-bbox="692 1397 1262 1498">1. A product of the maximum delay time and the bandwidth (time in <math>\mu\text{s}</math> and bandwidth in MHz) of more than 100;</p> <p data-bbox="692 1516 1262 1547">2. A dispersive delay of more than 10 <math>\mu\text{s}</math>; <u>or</u></p> <p data-bbox="692 1565 1262 1666">3. A ‘frequency side-lobe rejection’ exceeding 65 dB and a bandwidth greater than 100 MHz;</p> <p data-bbox="603 1684 788 1715"><u>Technical Note</u></p> <p data-bbox="603 1727 1262 1789"><i>‘Frequency side-lobe rejection’ is the maximum rejection value specified in data sheet.</i></p>

<i>Category Code</i>	<i>Item Description</i>
	<ol style="list-style-type: none"> <li data-bbox="544 454 1267 555">2. Bulk (volume) acoustic wave devices which permit the direct processing of signals at frequencies exceeding 6 GHz;</li> <li data-bbox="544 568 1267 741">3. Acoustic-optic “signal processing” devices employing interaction between acoustic waves (bulk wave or surface wave) and light waves which permit the direct processing of signals or images, including spectral analysis, correlation or convolution;</li> </ol> <p data-bbox="544 757 603 786"><u>Note</u></p> <p data-bbox="544 797 1267 898"><i>Category Code 3A001.c. does not include acoustic wave devices that are limited to a single band pass, low pass, high pass or notch filtering, or resonating function.</i></p> <ol style="list-style-type: none"> <li data-bbox="480 913 1267 1086">d. Electronic devices and circuits containing components, manufactured from “superconductive” materials, specially designed for operation at temperatures below the “critical temperature” of at least one of the “superconductive” constituents and having any of the following: <ol style="list-style-type: none"> <li data-bbox="544 1099 1267 1234">1. Current switching for digital circuits using “superconductive” gates with a product of delay time per gate (in seconds) and power dissipation per gate (in watts) of less than <math>10^{-14}</math> J; <u>or</u></li> <li data-bbox="544 1247 1267 1317">2. Frequency selection at all frequencies using resonant circuits with Q-values exceeding 10,000;</li> </ol> </li> <li data-bbox="480 1330 1267 1368">e. High energy devices, as follows: <ol style="list-style-type: none"> <li data-bbox="544 1382 1267 1420">1. ‘Cells’, as follows: <ol style="list-style-type: none"> <li data-bbox="624 1433 1267 1503">a. ‘Primary cells’ having an ‘energy density’ exceeding 550 Wh/kg at 20°C;</li> <li data-bbox="624 1516 1267 1585">b. ‘Secondary cells’ having an ‘energy density’ exceeding 300 Wh/kg at 20°C;</li> </ol> </li> </ol> </li> </ol>

Category Code	Item Description
	<p data-bbox="603 454 799 488"><u>Technical Notes</u></p> <ol style="list-style-type: none"> <li data-bbox="627 499 1267 831">1. For the purpose of Category Code 3A001.e.1., 'energy density' (Wh/kg) is calculated from the nominal voltage multiplied by the nominal capacity in ampere-hours (Ah) divided by the mass in kilograms. If the nominal capacity is not stated, energy density is calculated from the nominal voltage squared then multiplied by the discharge duration in hours divided by the discharge load in ohms and the mass in kilograms.</li> <li data-bbox="627 846 1267 1014">2. For the purpose of Category Code 3A001.e.1., a 'cell' is defined as an electrochemical device, which has positive and negative electrodes, an electrolyte, and is a source of electrical energy. It is the basic building block of a battery.</li> <li data-bbox="627 1030 1267 1160">3. For the purpose of Category Code 3A001.e.1.a., a 'primary cell' is a 'cell' that is not designed to be charged by any other source.</li> <li data-bbox="627 1176 1267 1305">4. For the purpose of Category Code 3A001.e.1.b., a 'secondary cell' is a 'cell' that is designed to be charged by an external electrical source.</li> </ol> <p data-bbox="603 1339 667 1373"><u>Note</u></p> <p data-bbox="603 1373 1267 1440">Category Code 3A001.e.1. does not include batteries, including single-cell batteries.</p> <ol style="list-style-type: none"> <li data-bbox="539 1456 1118 1489">2. High energy storage capacitors, as follows:           <p data-bbox="603 1507 667 1541"><u>N.B.</u></p> <p data-bbox="603 1552 1267 1619">See also Category Code 3A201.a. and Division 2 of Part I of this Schedule.</p> <ol style="list-style-type: none"> <li data-bbox="627 1635 1267 1731">a. Capacitors with a repetition rate of less than 10 Hz (single shot capacitors) and having all of the following:               <ol style="list-style-type: none"> <li data-bbox="691 1747 1267 1816">1. A voltage rating equal to or more than 5 kV;</li> </ol> </li> </ol> </li> </ol>



<i>Category Code</i>	<i>Item Description</i>
	<ol style="list-style-type: none"> <li data-bbox="692 456 1267 521">2. An energy density equal to or more than 250 J/kg; <u>and</u></li> <li data-bbox="692 539 1267 604">3. A total energy equal to or more than 25 kJ;</li> </ol> <p data-bbox="628 622 1267 719">b. Capacitors with a repetition rate of 10 Hz or more (repetition rated capacitors) and having all of the following:</p> <ol style="list-style-type: none"> <li data-bbox="692 736 1267 801">1. A voltage rating equal to or more than 5 kV;</li> <li data-bbox="692 819 1267 884">2. An energy density equal to or more than 50 J/kg;</li> <li data-bbox="692 902 1267 967">3. A total energy equal to or more than 100 J; <u>and</u></li> <li data-bbox="692 985 1267 1050">4. A charge/discharge cycle life equal to or more than 10,000;</li> </ol> <p data-bbox="544 1068 1267 1164">3. “Superconductive” electromagnets and solenoids specially designed to be fully charged or discharged in less than one second and having all of the following:</p> <p data-bbox="604 1182 660 1216"><u>N.B.</u></p> <p data-bbox="604 1227 1003 1261"><i>See also Category Code 3A201.b.</i></p> <p data-bbox="604 1279 660 1312"><u>Note</u></p> <p data-bbox="604 1323 1267 1451"><i>Category Code 3A001.e.3. does not include “superconductive” electromagnets or solenoids specially designed for Magnetic Resonance Imaging (MRI) medical equipment.</i></p> <ol style="list-style-type: none"> <li data-bbox="628 1469 1267 1534">a. Energy delivered during the discharge exceeding 10 kJ in the first second;</li> <li data-bbox="628 1552 1267 1617">b. Inner diameter of the current carrying windings of more than 250 mm; <u>and</u></li> <li data-bbox="628 1635 1267 1731">c. Rated for a magnetic induction of more than 8 T or “overall current density” in the winding of more than 300 A/mm<sup>2</sup>;</li> </ol>

<i>Category Code</i>	<i>Item Description</i>
	<p data-bbox="539 454 1267 689">4. Solar cells, cell-interconnect-coverglass (CIC) assemblies, solar panels, and solar arrays, which are “space-qualified”, having a minimum average efficiency exceeding 20% at an operating temperature of 301 K (28°C) under simulated ‘AM0’ illumination with an irradiance of 1,367 watts per square metre (W/m<sup>2</sup>);</p> <p data-bbox="603 703 788 736"><u>Technical Note</u></p> <p data-bbox="603 745 1267 880">‘AM0’, or ‘Air Mass Zero’, refers to the spectral irradiance of sun light in the earth's outer atmosphere when the distance between the earth and sun is one astronomical unit (AU).</p> <p data-bbox="475 898 1267 965">f. Rotary input type absolute position encoders having an accuracy equal to or less (better) than <math>\pm 1</math> second of arc;</p> <p data-bbox="475 981 1267 1115">g. Solid-state pulsed power switching thyristor devices and ‘thyristor modules’, using either electrically, optically, or electron radiation controlled switch methods and having any of the following:</p> <ol data-bbox="539 1131 1267 1480" style="list-style-type: none"> <li data-bbox="539 1131 1267 1234">1. A maximum turn-on current rate of rise (di/dt) greater than 30,000 A/<math>\mu</math>s and off-state voltage greater than 1,100 V; <u>or</u></li> <li data-bbox="539 1249 1267 1480">2. A maximum turn-on current rate of rise (di/dt) greater than 2,000 A/<math>\mu</math>s and having both of the following: <ol data-bbox="624 1332 1267 1480" style="list-style-type: none"> <li data-bbox="624 1332 1267 1400">a. An off-state peak voltage equal to or greater than 3,000 V; <u>and</u></li> <li data-bbox="624 1415 1267 1480">b. A peak (surge) current equal to or greater than 3,000 A;</li> </ol> </li> </ol> <p data-bbox="539 1496 624 1529"><u>Note 1</u></p> <p data-bbox="539 1538 954 1572"><i>Category Code 3A001.g. includes:</i></p> <ul data-bbox="539 1585 1190 1771" style="list-style-type: none"> <li data-bbox="539 1585 1038 1619">– <i>Silicon Controlled Rectifiers (SCRs)</i></li> <li data-bbox="539 1635 1078 1668">– <i>Electrical Triggering Thyristors (ETTs)</i></li> <li data-bbox="539 1684 1023 1718">– <i>Light Triggering Thyristors (LTTs)</i></li> <li data-bbox="539 1733 1190 1767">– <i>Integrated Gate Commutated Thyristors (IGCTs)</i></li> </ul>

Category Code	Item Description
	<ul style="list-style-type: none"> <li>– Gate Turn-off Thyristors (GTOs)</li> <li>– MOS Controlled Thyristors (MCTs)</li> <li>– Solidtrons</li> </ul> <p><u>Note 2</u> Category Code 3A001.g. does not include thyristor devices and ‘thyristor modules’ incorporated into equipment designed for civil railway or “civil aircraft” applications.</p> <p><u>Technical Note</u> For the purpose of Category Code 3A001.g., a ‘thyristor module’ contains one or more thyristor devices.</p> <p>h. Solid-state power semiconductor switches, diodes, or ‘modules’, having all of the following:</p> <ol style="list-style-type: none"> <li>1. Rated for a maximum operating junction temperature greater than 488 K (215°C);</li> <li>2. ‘Repetitive peak off-state voltage’ (blocking voltage) exceeding 300V; <u>and</u></li> <li>3. Continuous current greater than 1 A.</li> </ol> <p><u>Note 1</u> ‘Repetitive peak off-state voltage’ in Category Code 3A001.h. includes drain to source voltage, collector to emitter voltage, repetitive peak reverse voltage and peak repetitive off-state blocking voltage.</p> <p><u>Note 2</u> Category Code 3A001.h. includes:</p> <ul style="list-style-type: none"> <li>– Junction Field Effect Transistors (JFETs)</li> <li>– Vertical Junction Field Effect Transistors (VJFETs)</li> <li>– Metal Oxide Semiconductor Field Effect Transistors (MOSFETs)</li> <li>– Double Diffused Metal Oxide Semiconductor Field Effect Transistor (DMOSFET)</li> <li>– Insulated Gate Bipolar Transistor (IGBT)</li> <li>– High Electron Mobility Transistors (HEMTs)</li> <li>– Bipolar Junction Transistors (BJTs)</li> </ul>

<i>Category Code</i>	<i>Item Description</i>
	<ul style="list-style-type: none"> <li>– <i>Thyristors and Silicon Controlled Rectifiers (SCRs)</i></li> <li>– <i>Gate Turn-Off Thyristors (GTOs)</i></li> <li>– <i>Emitter Turn-Off Thyristors (ETOs)</i></li> <li>– <i>PiN Diodes</i></li> <li>– <i>Schottky Diodes</i></li> </ul> <p><u>Note 3</u>  <i>Category Code 3A001.h. does not include switches, diodes, or ‘modules’ incorporated into equipment designed for civil automobile, civil railway or “civil aircraft” applications.</i></p> <p><u>Technical Note</u>  <i>For the purpose of Category Code 3A001.h., ‘modules’ contain one or more solid-state power semiconductor switches or diodes.</i></p>
3A002	<p>General purpose electronic equipment as follows:</p> <ul style="list-style-type: none"> <li>a. Recording equipment and oscilloscopes as follows: <ul style="list-style-type: none"> <li>1. Not used;</li> <li>2. Not used;</li> <li>3. Not used;</li> <li>4. Not used;</li> <li>5. Waveform digitisers and transient recorders having all of the following: <ul style="list-style-type: none"> <li>a. Digitising rate equal to or more than 200 million samples per second and a resolution of 10 bit or more;</li> <li>b. A ‘continuous throughput’ of 2 Gbit/s or more; <u>and</u></li> <li>c. Triggered acquisition of transients or aperiodic signals;</li> </ul> </li> </ul> </li> </ul>

<i>Category Code</i>	<i>Item Description</i>
	<p data-bbox="603 454 799 488"><u>Technical Notes</u></p> <ol style="list-style-type: none"> <li data-bbox="627 499 1267 629">1. For those instruments with a parallel bus architecture, the 'continuous throughput' rate is the highest word rate multiplied by the number of bits in a word.</li> <li data-bbox="627 645 1267 815">2. 'Continuous throughput' is the fastest data rate the instrument can output to mass storage without the loss of any information whilst sustaining the sampling rate and analogue-to-digital conversion.</li> <li data-bbox="627 831 1267 931">3. For the purpose of Category Code 3A002.a.5.c., acquisition can be triggered internally or externally.</li> </ol> <p data-bbox="544 947 1267 1249">6. Digital instrumentation data recorder systems using magnetic disk storage technique and having both of the following, and specially designed digital recorders therefor:</p> <ol style="list-style-type: none"> <li data-bbox="627 1099 1267 1200">a. Digitised instrumentation data rate equal to or more than 100 million samples per second at a resolution of 8 bit or more; <u>and</u></li> <li data-bbox="627 1216 1267 1249">b. A 'continuous throughput' of 1 Gbit/s or more;</li> </ol> <p data-bbox="603 1265 788 1299"><u>Technical Note</u></p> <p data-bbox="603 1310 1267 1406"><i>Digital instrumentation data recorder systems can be configured either with a digitiser integrated within or outside the digital recorder.</i></p> <p data-bbox="544 1422 1267 1592">7. Real-time oscilloscopes having a vertical root-mean-square (rms) noise voltage of less than 2% of full-scale at the vertical scale setting that provides the lowest noise value for any input 3 dB bandwidth of 60 GHz or greater per channel;</p> <p data-bbox="603 1608 667 1641"><u>Note</u></p> <p data-bbox="603 1653 1267 1720"><i>Category Code 3A002.a.7. does not include equivalent-time sampling oscilloscopes.</i></p> <p data-bbox="475 1736 660 1769">b. Not used;</p>

<i>Category Code</i>	<i>Item Description</i>
	<p>c. Radio-frequency “signal analysers”, as follows:</p> <ol style="list-style-type: none"> <li>1. “Signal analysers” having a 3 dB resolution bandwidth (RBW) exceeding 10 MHz anywhere within the frequency range exceeding 31.8 GHz but not exceeding 37.5 GHz;</li> <li>2. “Signal analysers” having Displayed Average Noise Level (DANL) less (better) than – 150 dBm/Hz anywhere within the frequency range exceeding 43.5 GHz but not exceeding 75 GHz;</li> <li>3. “Signal analysers” having a frequency exceeding 75 GHz;</li> <li>4. “Signal analysers” having all of the following: <ol style="list-style-type: none"> <li>a. “Real-time bandwidth” exceeding 85 MHz; <u>and</u></li> <li>b. 100% probability of discovery with less than a 3 dB reduction from full amplitude due to gaps or windowing effects of signals having a duration of 15 µs or less;</li> </ol> <p><u>Technical Notes</u></p> <ol style="list-style-type: none"> <li>1. <i>Probability of discovery in Category Code 3A002.c.4.b. is also referred to as probability of intercept or probability of capture.</i></li> <li>2. <i>For the purpose of Category Code 3A002.c.4.b., the duration for 100% probability of discovery is equivalent to the minimum signal duration necessary for the specified level measurement uncertainty.</i></li> </ol> <p><u>Note</u></p> <p><i>Category Code 3A002.c.4. does not include those “signal analysers” using only constant percentage bandwidth filters (also known as octave or fractional octave filters).</i></p> </li> <li>5. “Signal analysers” having a “frequency mask trigger” function with 100% probability of trigger (capture) for signals having a duration of 15 µs or less;</li> </ol>

<i>Category Code</i>	<i>Item Description</i>
	<p>d. Frequency synthesised signal generators producing output frequencies, the accuracy and short term and long term stability of which are controlled, derived from or disciplined by the internal master reference oscillator, and having any of the following:</p> <ol style="list-style-type: none"> <li>1. Specified to generate pulse-modulated signals having all of the following, anywhere within the synthesised frequency range exceeding 31.8 GHz but not exceeding 75 GHz: <ol style="list-style-type: none"> <li>a. ‘Pulse duration’ of less than 100 ns; <u>and</u></li> <li>b. On/off ratio equal to or exceeding 65 dB;</li> </ol> </li> <li>2. An output power exceeding 100 mW (20 dBm) anywhere within the synthesised frequency range exceeding 43.5 GHz but not exceeding 75 GHz;</li> <li>3. A “frequency switching time” as specified by any of the following: <ol style="list-style-type: none"> <li>a. Not used;</li> <li>b. Less than 100 <math>\mu</math>s for any frequency change exceeding 1.6 GHz within the synthesised frequency range exceeding 4.8 GHz but not exceeding 10.6 GHz;</li> <li>c. Less than 250 <math>\mu</math>s for any frequency change exceeding 550 MHz within the synthesised frequency range exceeding 10.6 GHz but not exceeding 31.8 GHz;</li> <li>d. Less than 500 <math>\mu</math>s for any frequency change exceeding 550 MHz within the synthesised frequency range exceeding 31.8 GHz but not exceeding 43.5 GHz;</li> <li>e. Less than 1 ms for any frequency change exceeding 550 MHz within the synthesised frequency range exceeding 43.5 GHz but not exceeding 56 GHz; <u>or</u></li> <li>f. Less than 1 ms for any frequency change exceeding 2.2 GHz within the synthesised frequency range exceeding 56 GHz but not exceeding 75 GHz;</li> </ol> </li> </ol>

Category Code	Item Description
	<p>4. Single sideband (SSB) phase noise, in dBc/Hz, specified as being both of the following:</p> <ol style="list-style-type: none"> <li>a. Less (better) than <math>-(126 + 20\log_{10}F - 20\log_{10}f)</math> anywhere in the range of <math>10 \text{ Hz} &lt; F &lt; 10 \text{ kHz}</math> anywhere within the synthesised frequency range exceeding 3.2 GHz but not exceeding 75 GHz; <u>and</u></li> <li>b. Less (better) than <math>-(114 + 20\log_{10}F - 20\log_{10}f)</math> anywhere in the range of <math>10 \text{ kHz} \leq F &lt; 500 \text{ kHz}</math> anywhere within the synthesised frequency range exceeding 3.2 GHz but not exceeding 75 GHz; <u>or</u></li> </ol> <p><u>Technical Note</u>  <i>In Category Code 3A002.b.4., F is the offset from the operating frequency in Hz and f is the operating frequency in MHz.</i></p> <p>5. A maximum synthesised frequency exceeding 75 GHz;</p> <p><u>Note 1</u>  <i>For the purpose of Category Code 3A002.d., the term frequency synthesised signal generators includes arbitrary waveform and function generators.</i></p> <p><u>Note 2</u>  <i>Category Code 3A002.d. does not include equipment in which the output frequency is either produced by the addition or subtraction of two or more crystal oscillator frequencies, or by an addition or subtraction followed by a multiplication of the result.</i></p> <p><u>Technical Notes</u></p> <ol style="list-style-type: none"> <li>1. <i>The maximum synthesised frequency of an arbitrary waveform or function generator is calculated by dividing the sample rate, in samples/second, by a factor of 2.5.</i></li> <li>2. <i>For the purpose of Category Code 3A002.d.1.a., 'pulse duration' is defined as the time interval from the point on the leading edge that is 50% of the pulse amplitude to the point on the trailing edge that is 50% of the pulse amplitude.</i></li> </ol>



<i>Category Code</i>	<i>Item Description</i>
	<p>e. Network analysers having any of the following:</p> <ol style="list-style-type: none"> <li>1. An output power exceeding 31.62 mW (15 dBm) anywhere within the operating frequency range exceeding 43.5 GHz but not exceeding 75 GHz;</li> <li>2. An output power exceeding 1 mW (0 dBm) anywhere within the operating frequency range exceeding 75 GHz but not exceeding 110 GHz;</li> <li>3. ‘Non-linear vector measurement functionality’ at frequencies exceeding 50 GHz but not exceeding 110 GHz; <u>or</u></li> </ol> <p><i>Technical Note</i></p> <p><i>‘Non-linear vector measurement functionality’ is an instrument’s ability to analyse the test results of devices driven into the large-signal domain or the non-linear distortion range.</i></p> <ol style="list-style-type: none"> <li>4. A maximum operating frequency exceeding 110 GHz;</li> </ol> <p>f. Microwave test receivers having both of the following:</p> <ol style="list-style-type: none"> <li>1. A maximum operating frequency exceeding 110 GHz; <u>and</u></li> <li>2. Being capable of measuring amplitude and phase simultaneously;</li> </ol> <p>g. Atomic frequency standards being any of the following:</p> <ol style="list-style-type: none"> <li>1. “Space-qualified”;</li> <li>2. Non-rubidium and having a long-term stability less (better) than <math>1 \times 10^{-11}</math>/month; <u>or</u></li> <li>3. Non-“space-qualified” and having all of the following: <ol style="list-style-type: none"> <li>a. Being a rubidium standard;</li> <li>b. Long-term stability less (better) than <math>1 \times 10^{-11}</math>/month; <u>and</u></li> <li>c. Total power consumption of less than 1 W.</li> </ol> </li> </ol>

<i>Category Code</i>	<i>Item Description</i>
3A003	Spray cooling thermal management systems employing closed loop fluid handling and reconditioning equipment in a sealed enclosure where a dielectric fluid is sprayed onto electronic components using specially designed spray nozzles that are designed to maintain electronic components within their operating temperature range, and specially designed components therefor.
3A101	<p>Electronic equipment, devices and components, other than those specified in Category Code 3A001, as follows:</p> <ol style="list-style-type: none"> <li>a. Analogue-to-digital converters, usable in “missiles”, designed to meet military specifications for ruggedised equipment;</li> <li>b. Accelerators capable of delivering electromagnetic radiation produced by bremsstrahlung from accelerated electrons of 2 MeV or greater, and systems containing those accelerators.</li> </ol> <p><i>Note</i>  <i>Category Code 3A101.b. does not include equipment specially designed for medical purposes.</i></p>
3A102	<p>‘Thermal batteries’ designed or modified for ‘missiles’.</p> <p><i>Technical Notes</i></p> <ol style="list-style-type: none"> <li>1. <i>In Category Code 3A102, ‘thermal batteries’ are single use batteries that contain a solid non-conducting inorganic salt as the electrolyte. These batteries incorporate a pyrolytic material that, when ignited, melts the electrolyte and activates the battery.</i></li> <li>2. <i>In Category Code 3A102, ‘missile’ means complete rocket systems and unmanned aerial vehicle systems capable of a range exceeding 300 km.</i></li> </ol>

<i>Category Code</i>	<i>Item Description</i>
3A201	<p>Electronic components, other than those specified in Category Code 3A001, as follows:</p> <ol style="list-style-type: none"> <li>a. Capacitors having either of the following sets of characteristics:               <ol style="list-style-type: none"> <li>1. a. Voltage rating greater than 1.4 kV;</li> <li>b. Energy storage greater than 10 J;</li> <li>c. Capacitance greater than 0.5 <math>\mu\text{F}</math>; <u>and</u></li> <li>d. Series inductance less than 50 nH; <u>or</u></li> <li>2. a. Voltage rating greater than 750 V;</li> <li>b. Capacitance greater than 0.25 <math>\mu\text{F}</math>; <u>and</u></li> <li>c. Series inductance less than 10 nH;</li> </ol> </li> <li>b. Superconducting solenoidal electromagnets having all of the following characteristics:               <ol style="list-style-type: none"> <li>1. Capable of creating magnetic fields greater than 2 T;</li> <li>2. A ratio of length to inner diameter greater than 2;</li> <li>3. Inner diameter greater than 300 mm; <u>and</u></li> <li>4. Magnetic field uniform to better than 1% over the central 50% of the inner volume;</li> </ol> <p><u>Note</u>  <i>Category Code 3A201.b. does not include magnets specially designed for and exported 'as part of' medical nuclear magnetic resonance (NMR) imaging systems. For this purpose, the magnets and NMR imaging systems may be part of the same shipment or in separate shipments from different sources, provided the related export documents clearly specify that the separate shipments are dispatched 'as part of' the imaging systems.</i></p> </li> <li>c. Flash X-ray generators or pulsed electron accelerators having either of the following sets of characteristics:               <ol style="list-style-type: none"> <li>1. a. An accelerator peak electron energy of 500 keV or greater but less than 25 MeV; <u>and</u></li> <li>b. With a 'figure of merit' (K) of 0.25 or greater; <u>or</u></li> </ol> </li> </ol>

Category Code	Item Description
	<p data-bbox="544 454 1267 568">2. a. An accelerator peak electron energy of 25 MeV or greater; <u>and</u> b. A ‘peak power’ greater than 50 MW.</p> <p data-bbox="544 589 603 618"><u>Note</u></p> <p data-bbox="544 629 1267 763"><i>Category Code 3A201.c. does not include accelerators that are component parts of devices designed for purposes other than electron beam or X-ray radiation (e.g. electron microscopy) nor those designed for medical purposes.</i></p> <p data-bbox="544 779 735 808"><u>Technical Notes</u></p> <p data-bbox="544 819 1038 853">1. The ‘figure of merit’ <math>K</math> is defined as: <math display="block">K = 1.7 \times 10^3 V^{2.65} Q</math> <i>V is the peak electron energy in million electron volts. If the accelerator beam pulse duration is less than or equal to 1 <math>\mu</math>s, then <math>Q</math> is the total accelerated charge in Coulombs. If the accelerator beam pulse duration is greater than 1 <math>\mu</math>s, then <math>Q</math> is the maximum accelerated charge in 1 <math>\mu</math>s. <math>Q</math> equals the integral of <math>i</math> with respect to <math>t</math>, over the lesser of 1 <math>\mu</math>s or the time duration of the beam pulse (<math>Q = \int idt</math>), where <math>i</math> is beam current in amperes and <math>t</math> is time in seconds.</i></p> <p data-bbox="544 1272 1267 1339">2. ‘Peak power’ = (peak potential in volts) <math>\times</math> (peak beam current in amperes).</p> <p data-bbox="544 1357 1267 1491">3. In machines based on microwave accelerating cavities, the time duration of the beam pulse is the lesser of 1 <math>\mu</math>s or the duration of the bunched beam packet resulting from one microwave modulator pulse.</p> <p data-bbox="544 1509 1267 1610">4. In machines based on microwave accelerating cavities, the peak beam current is the average current in the time duration of a bunched beam packet.</p>

<i>Category Code</i>	<i>Item Description</i>
3A225	<p>Frequency changers or generators, other than those specified in Category Code 0B001.b.13., usable as a variable or fixed frequency motor drive, having all of the following characteristics:</p> <p><u>N.B.</u></p> <ol style="list-style-type: none"> <li>1. “Software” specially designed to enhance or release the performance of a frequency changer or generator to meet the characteristics of Category Code 3A225 is specified in Category Code 3D225.</li> <li>2. “Technology” in the form of codes or keys to enhance or release the performance of a frequency changer or generator to meet the characteristics of Category Code 3A225 is specified in Category Code 3E225.</li> </ol> <ol style="list-style-type: none"> <li>a. Multiphase output providing a power of 40 VA or greater;</li> <li>b. Operating at a frequency of 600 Hz or more; <u>and</u></li> <li>c. Frequency control better (less) than 0.2%.</li> </ol> <p><u>Note</u></p> <p>Category Code 3A225 does not include frequency changers or generators if they have hardware, “software” or “technology” constraints that limit the performance to less than that specified above, provided they meet any of the following:</p> <ol style="list-style-type: none"> <li>1. They need to be returned to the original manufacturer to make the enhancements or release the constraints;</li> <li>2. They require “software” as specified in Category Code 3D225 to enhance or release the performance to meet the characteristics of Category Code 3A225; <u>or</u></li> <li>3. They require “technology” in the form of keys or codes as specified in Category Code 3E225 to enhance or release the performance to meet the characteristics of Category Code 3A225.</li> </ol> <p><u>Technical Notes</u></p> <ol style="list-style-type: none"> <li>1. Frequency changers in Category Code 3A225 are also known as converters or inverters.</li> </ol>

<i>Category Code</i>	<i>Item Description</i>
	<p>2. <i>Frequency changers in Category Code 3A225 may be marketed as Generators, Electronic Test Equipment, AC Power Supplies, Variable Speed Motors Drives, Variable Speed Drives (VSDs), Variable Frequency Drives (VFDs), Adjustable Frequency Drives (AFDs), or Adjustable Speed Drives (ASDs).</i></p>
3A226	<p>High-power direct current power supplies, other than those specified in Category Code 0B001.j.6., having both of the following characteristics:</p> <ol style="list-style-type: none"> <li>a. Capable of continuously producing, over a time period of 8 hours, 100 V or greater with current output of 500 A or greater; <u>and</u></li> <li>b. Current or voltage stability better than 0.1% over a time period of 8 hours.</li> </ol>
3A227	<p>High-voltage direct current power supplies, other than those specified in Category Code 0B001.j.5., having both of the following characteristics:</p> <ol style="list-style-type: none"> <li>a. Capable of continuously producing, over a time period of 8 hours, 20 kV or greater with current output of 1 A or greater; <u>and</u></li> <li>b. Current or voltage stability better than 0.1% over a time period of 8 hours.</li> </ol>
3A228	<p>Switching devices, as follows:</p> <ol style="list-style-type: none"> <li>a. Cold-cathode tubes, whether gas filled or not, operating similarly to a spark gap, having all of the following characteristics: <ol style="list-style-type: none"> <li>1. Containing three or more electrodes;</li> <li>2. Anode peak voltage rating of 2.5 kV or more;</li> </ol> </li> </ol>

<i>Category Code</i>	<i>Item Description</i>
	<ol style="list-style-type: none"> <li>3. Anode peak current rating of 100 A or more; <u>and</u></li> <li>4. Anode delay time of 10 <math>\mu</math>s or less;</li> </ol> <p><u>Note</u> Category Code 3A228 includes gas krytron tubes and vacuum spraytron tubes.</p> <ol style="list-style-type: none"> <li>b. Triggered spark-gaps having both of the following characteristics: <ol style="list-style-type: none"> <li>1. An anode delay time of 15 <math>\mu</math>s or less; <u>and</u></li> <li>2. Rated for a peak current of 500 A or more;</li> </ol> </li> <li>c. Modules or assemblies with a fast switching function, other than those specified in Category Code 3A001.g. or 3A001.h., having all of the following characteristics: <ol style="list-style-type: none"> <li>1. Anode peak voltage rating greater than 2 kV;</li> <li>2. Anode peak current rating of 500 A or more; <u>and</u></li> <li>3. Turn-on time of 1 <math>\mu</math>s or less.</li> </ol> </li> </ol>
3A229	<p>High-current pulse generators as follows:</p> <p><u>N.B.</u> <i>See also Division 2 of Part I of this Schedule.</i></p> <ol style="list-style-type: none"> <li>a. Detonator firing sets (initiator systems, firesets), including electronically-charged, explosively-driven and optically-driven firing sets, other than those specified in Category Code 1A007.a., designed to drive multiple controlled detonators specified in Category Code 1A007.b.;</li> <li>b. Modular electrical pulse generators (pulsers) having all of the following characteristics: <ol style="list-style-type: none"> <li>1. Designed for portable, mobile, or ruggedised-use;</li> <li>2. Capable of delivering their energy in less than 15 <math>\mu</math>s into loads of less than 40 ohms;</li> <li>3. Having an output greater than 100 A;</li> <li>4. No dimension greater than 30 cm;</li> </ol> </li> </ol>

<i>Category Code</i>	<i>Item Description</i>
	<p>5. Weight less than 30 kg; <u>and</u></p> <p>6. Specified for use over an extended temperature range 223 K (-50°C) to 373 K (100°C) or specified as suitable for aerospace applications.</p> <p><i>Note</i>  <i>Category Code 3A229.b. includes xenon flash-lamp drivers.</i></p> <p>c. Micro-firing units having all of the following characteristics:</p> <ol style="list-style-type: none"> <li>1. No dimension greater than 35 mm;</li> <li>2. Voltage rating of equal to or greater than 1 kV; <u>and</u></li> <li>3. Capacitance of equal to or greater than 100 nF.</li> </ol>
3A230	<p>High-speed pulse generators and ‘pulse heads’ therefor, having both of the following characteristics:</p> <ol style="list-style-type: none"> <li>a. Output voltage greater than 6 V into a resistive load of less than 55 ohms; <u>and</u></li> <li>b. ‘Pulse transition time’ less than 500 ps.</li> </ol> <p><i>Technical Notes</i></p> <ol style="list-style-type: none"> <li>1. <i>In Category Code 3A230, ‘pulse transition time’ is defined as the time interval between 10% and 90% voltage amplitude.</i></li> <li>2. <i>‘Pulse heads’ are impulse forming networks designed to accept a voltage step function and shape it into a variety of pulse forms that can include rectangular, triangular, step, impulse, exponential, or monocycle types. ‘Pulse heads’ can be an integral part of the pulse generator, they can be a plug-in module to the device or they can be an externally connected device.</i></li> </ol>
3A231	<p>Neutron generator systems, including tubes, having both of the following characteristics:</p> <ol style="list-style-type: none"> <li>a. Designed for operation without an external vacuum system; <u>and</u></li> </ol>



<i>Category Code</i>	<i>Item Description</i>
3A232	<p>b. Utilising any of the following:</p> <ol style="list-style-type: none"> <li>1. Electrostatic acceleration to induce a tritium-deuterium nuclear reaction; <u>or</u></li> <li>2. Electrostatic acceleration to induce a deuterium-deuterium nuclear reaction and capable of an output of <math>3 \times 10^9</math> neutrons/s or greater.</li> </ol> <p>Multipoint initiation systems, other than those specified in Category Code 1A007, as follows:</p> <p><u>N.B.</u>  <i>See also Division 2 of Part I of this Schedule.</i>  <i>See Category Code 1A007.b. for detonators.</i></p> <p>a. Not used;</p> <p>b. Arrangements using single or multiple detonators designed to nearly simultaneously initiate an explosive surface over greater than 5,000 mm<sup>2</sup> from a single firing signal with an initiation timing spread over the surface of less than 2.5 µs.</p> <p><u>Note</u>  <i>Category Code 3A232 does not include detonators using only primary explosives, such as lead azide.</i></p>
3A233	<p>Mass spectrometers, other than those specified in Category Code 0B002.g., capable of measuring ions of 230 atomic mass units or greater and having a resolution of better than 2 parts in 230, as follows, and ion sources therefor:</p> <ol style="list-style-type: none"> <li>a. Inductively coupled plasma mass spectrometers (ICP/MS);</li> <li>b. Glow discharge mass spectrometers (GDMS);</li> <li>c. Thermal ionisation mass spectrometers (TIMS);</li> <li>d. Electron bombardment mass spectrometers having both of the following features: <ol style="list-style-type: none"> <li>1. A molecular beam inlet system that injects a collimated beam of analyte molecules into a region of the ion source where the molecules are ionized by an electron beam; <u>and</u></li> </ol> </li> </ol>

<i>Category Code</i>	<i>Item Description</i>
	<p>2. One or more 'cold traps' that can be cooled to a temperature of 193 K (-80 °C);</p> <p>e. Not used;</p> <p>f. Mass spectrometers equipped with a microfluorination ion source designed for actinides or actinide fluorides.</p> <p><u>Technical Notes</u></p> <p>1. <i>Electron bombardment mass spectrometers in Category Code 3A233.d. are also known as electron impact mass spectrometers or electron ionization mass spectrometers.</i></p> <p>2. <i>In Category Code 3A233.d.2., a 'cold trap' is a device that traps gas molecules by condensing or freezing them on cold surfaces. For the purpose of Category Code 3A233.d.2., a closed-loop gaseous helium cryogenic vacuum pump is not a 'cold trap'.</i></p>
3A234	<p>Striplines to provide low inductance path to detonators with the following characteristics:</p> <p>a. Voltage rating greater than 2 kV; <u>and</u></p> <p>b. Inductance of less than 20 nH.</p>
<b>3B</b>	<b>Test, Inspection and Production Equipment</b>
3B001	<p>Equipment for the manufacturing of semiconductor devices or materials, as follows and specially designed components and accessories therefor:</p> <p>a. Equipment designed for epitaxial growth, as follows:</p> <p>1. Equipment capable of producing a layer of any material other than silicon with a thickness uniform to less than <math>\pm 2.5\%</math> across a distance of 75 mm or more;</p> <p><u>Note</u></p> <p><i>Category Code 3B001.a.1. includes Atomic Layer Epitaxy (ALE) equipment.</i></p>

<i>Category Code</i>	<i>Item Description</i>
	<ol style="list-style-type: none"> <li data-bbox="544 454 1264 651">2. Metal Organic Chemical Vapour Deposition (MOCVD) reactors designed for compound semiconductor epitaxial growth of material having two or more of the following elements: aluminium, gallium, indium, arsenic, phosphorus, antimony, or nitrogen;</li> <li data-bbox="544 674 1264 734">3. Molecular beam epitaxial growth equipment using gas or solid sources;</li> </ol> <p data-bbox="480 757 1264 817">b. Equipment designed for ion implantation and having any of the following:</p> <ol style="list-style-type: none"> <li data-bbox="544 840 719 869">1. Not used;</li> <li data-bbox="544 891 1264 1021">2. Being designed and optimised to operate at a beam energy of 20 keV or more and a beam current of 10 mA or more for hydrogen, deuterium or helium implant;</li> <li data-bbox="544 1043 879 1072">3. Direct write capability;</li> <li data-bbox="544 1095 1264 1182">4. A beam energy of 65 keV or more and a beam current of 45 mA or more for high energy oxygen implant into a heated semiconductor material “substrate”; <u>or</u></li> <li data-bbox="544 1205 1264 1368">5. Being designed and optimised to operate at a beam energy of 20 keV or more and a beam current of 10 mA or more for silicon implant into a semiconductor material “substrate” heated to 600°C or greater;</li> </ol> <p data-bbox="480 1391 1264 1451">c. Anisotropic plasma dry etching equipment having both of the following:</p> <ol style="list-style-type: none"> <li data-bbox="544 1473 1264 1534">1. Designed or optimised to produce critical dimensions of 65 nm or less; <u>and</u></li> <li data-bbox="544 1556 1264 1644">2. Within-wafer non-uniformity equal to or less than 10% <math>3\sigma</math> measured with an edge exclusion of 2 mm or less;</li> </ol> <p data-bbox="480 1666 655 1695">d. Not used;</p>

<i>Category Code</i>	<i>Item Description</i>
	<p>e. Automatic loading multi-chamber central wafer handling systems, having both of the following:</p> <ol style="list-style-type: none"> <li>1. Interfaces for wafer input and output, to which more than two functionally different ‘semiconductor process tools’ specified in Category Code 3B001.a., 3B001.b. or 3B001.c. are designed to be connected; <u>and</u></li> <li>2. Designed to form an integrated system in a vacuum environment for ‘sequential multiple wafer processing’;</li> </ol> <p><i>Note</i>  <i>Category Code 3B001.e. does not include automatic robotic wafer handling systems specially designed for parallel wafer processing.</i></p> <p><i>Technical Notes</i></p> <ol style="list-style-type: none"> <li>1. <i>For the purpose of Category Code 3B001.e., ‘semiconductor process tools’ refers to modular tools that provide physical processes for semiconductor production that are functionally different, such as deposition, etch, implant or thermal processing.</i></li> <li>2. <i>For the purpose of Category Code 3B001.e., ‘sequential multiple wafer processing’ means the capability to process each wafer in different ‘semiconductor process tools’, such as by transferring each wafer from one tool to a second tool and on to a third tool with the automatic loading multi-chamber central wafer handling systems.</i></li> </ol> <p>f. Lithography equipment as follows:</p> <ol style="list-style-type: none"> <li>1. Align and expose step and repeat (direct step on wafer) or step and scan (scanner) equipment for wafer processing using photo-optical or X-ray methods and having any of the following: <ol style="list-style-type: none"> <li>a. A light source wavelength shorter than 193 nm; <u>or</u></li> </ol> </li> </ol>

Category Code	Item Description
	<p>b. Capable of producing a pattern with a ‘Minimum Resolvable Feature size’ (MRF) of 45 nm or less;</p> <p><i>Technical Note</i> The ‘Minimum Resolvable Feature size’ (MRF) is calculated by the following formula:</p> $MRF = \frac{\left[ \frac{\text{an exposure light source wavelength in nm}}{\text{numerical aperture}} \right] \times [K \text{ factor}]}{\text{numerical aperture}}$ <p>where the K factor = 0.35</p> <p>2. Imprint lithography equipment capable of producing features of 45 nm or less;</p> <p><i>Note</i> Category Code 3B001.f.2. includes:</p> <ul style="list-style-type: none"> <li>– Micro contact printing tools</li> <li>– Hot embossing tools</li> <li>– Nano-imprint lithography tools</li> <li>– Step and flash imprint lithography (S-FIL) tools</li> </ul> <p>3. Equipment specially designed for mask making or semiconductor device processing using direct writing methods and having all of the following:</p> <ol style="list-style-type: none"> <li>a. Using deflected focused electron beam, ion beam or “laser” beam; <u>and</u></li> <li>b. Having any of the following: <ol style="list-style-type: none"> <li>1. A spot size smaller than 0.2 μm;</li> <li>2. Being capable of producing a pattern with a feature size of less than 1 μm; <u>or</u></li> <li>3. An overlay accuracy of better than ±0.20 μm (3 sigma);</li> </ol> </li> </ol> <p>g. Masks and reticles, designed for integrated circuits specified in Category Code 3A001;</p>

<i>Category Code</i>	<i>Item Description</i>
	<p>h. Multi-layer masks with a phase shift layer not specified by Category Code 3B001.g. and having any of the following:</p> <ol style="list-style-type: none"> <li>1. Made on a mask “substrate blank” from glass specified as having less than 7 nm/cm birefringence; <u>or</u></li> <li>2. Designed to be used by lithography equipment having a light source wavelength less than 245 nm;</li> </ol> <p><i>Note</i> Category Code 3B001.h. does not include multi-layer masks with a phase shift layer designed for the fabrication of memory devices not specified in Category Code 3A001.</p> <p>i. Imprint lithography templates designed for integrated circuits specified in Category Code 3A001.</p>
3B002	<p>Test equipment specially designed for testing finished or unfinished semiconductor devices as follows and specially designed components and accessories therefor:</p> <ol style="list-style-type: none"> <li>a. For testing S-parameters of transistor devices at frequencies exceeding 31.8 GHz;</li> <li>b. Not used;</li> <li>c. For testing microwave integrated circuits specified in Category Code 3A001.b.2.</li> </ol>
<b>3C</b>	<b>Materials</b>
3C001	<p>Hetero-epitaxial materials consisting of a “substrate” having stacked epitaxially grown multiple layers of any of the following:</p> <ol style="list-style-type: none"> <li>a. Silicon (Si);</li> <li>b. Germanium (Ge);</li> <li>c. Silicon carbide (SiC); <u>or</u></li> <li>d. “III/V compounds” of gallium or indium.</li> </ol>

Category Code	Item Description
	<p><u>Note</u>  <i>Category Code 3C001.d. does not apply to a “substrate” having one or more P-type epitaxial layers of GaN, InGaN, AlGaN, InAlN, InAlGaN, GaP, InGaP, AlInP or InGaAlP, independent of the sequence of the elements, except if the P-type epitaxial layer is between N-type layers.</i></p>
3C002	<p>Resist materials as follows and “substrates” coated with the following resists:</p> <ul style="list-style-type: none"> <li>a. Resists designed for semiconductor lithography as follows: <ul style="list-style-type: none"> <li>1. Positive resists adjusted (optimised) for use at wavelengths less than 245 nm but equal to or greater than 15 nm;</li> <li>2. Resists adjusted (optimised) for use at wavelengths less than 15 nm but greater than 1 nm;</li> </ul> </li> <li>b. All resists designed for use with electron beams or ion beams, with a sensitivity of 0.01 <math>\mu\text{coulomb}/\text{mm}^2</math> or better;</li> <li>c. Not used;</li> <li>d. All resists optimised for surface imaging technologies;</li> <li>e. All resists designed or optimised for use with imprint lithography equipment specified in Category Code 3B001.f.2. that use either a thermal or photo-curable process.</li> </ul>
3C003	<p>Organo-inorganic compounds as follows:</p> <ul style="list-style-type: none"> <li>a. Organo-metallic compounds of aluminium, gallium or indium having a purity (metal basis) better than 99.999%;</li> <li>b. Organo-arsenic, organo-antimony and organo-phosphorus compounds having a purity (inorganic element basis) better than 99.999%.</li> </ul> <p><u>Note</u>  <i>Category Code 3C003 only includes compounds whose metallic, partly metallic or non-metallic element is directly linked to carbon in the organic part of the molecule.</i></p>

<i>Category Code</i>	<i>Item Description</i>
3C004	<p>Hydrides of phosphorus, arsenic or antimony, having a purity better than 99.999%, even diluted in inert gases or hydrogen.</p> <p><u>Note</u>  <i>Category Code 3C004 does not include hydrides containing 20% molar or more of inert gases or hydrogen.</i></p>
3C005	<p>Silicon carbide (SiC), gallium nitride (GaN), aluminium nitride (AlN) or aluminium gallium nitride (AlGaN) semiconductor “substrates”, or ingots, boules, or other preforms of those materials, having resistivities greater than 10,000 ohm-cm at 20°C.</p>
3C006	<p>“Substrates” specified in Category Code 3C005 with at least one epitaxial layer of silicon carbide, gallium nitride, aluminium nitride or aluminium gallium nitride.</p>
<b>3D</b>	<b>Software</b>
3D001	<p>“Software” specially designed for the “development” or “production” of equipment specified in Category Codes 3A001.b. to 3A002.g. or Category 3B.</p>
3D002	<p>“Software” specially designed for the “use” of equipment specified in Category Code 3A225, 3B001.a. to f. or 3B002.</p>
3D003	<p>‘Physics-based’ simulation “software” specially designed for the “development” of lithographic, etching or deposition processes for translating masking patterns into specific topographical patterns in conductors, dielectrics or semiconductor materials.</p> <p><u>Technical Note</u>  <i>‘Physics-based’ in Category Code 3D003 means using computations to determine a sequence of physical cause and effect events based on physical properties (e.g. temperature, pressure, diffusion constants and semiconductor materials properties).</i></p>



<i>Category Code</i>	<i>Item Description</i>
	<p><u>Note</u>  <i>Libraries, design attributes or associated data for the design of semiconductor devices or integrated circuits are considered as “technology”.</i></p>
3D004	<p>“Software” specially designed for the “development” of the equipment specified in Category Code 3A003.</p>
3D101	<p>“Software” specially designed or modified for the “use” of equipment specified in Category Code 3A101.b.</p>
3D225	<p>“Software” specially designed to enhance or release the performance of frequency changers or generators to meet the characteristics of Category Code 3A225.</p>
<b>3E</b>	<b>Technology</b>
3E001	<p>“Technology” (according to the General Technology Note) for the “development” or “production” of equipment or materials specified in Category 3A, 3B or 3C.</p>
	<p><u>Note 1</u>  <i>Category Code 3E001 does not include “technology” for the “production” of equipment or components specified in Category Code 3A003.</i></p>
	<p><u>Note 2</u>  <i>Category Code 3E001 does not include “technology” for the “development” or “production” of integrated circuits specified in Category Codes 3A001.a.3. to 3A001.a.12., having all of the following:</i></p> <ol style="list-style-type: none"> <li data-bbox="480 1608 1107 1644">1. <i>Using “technology” at or above 0.130 μm; <u>and</u></i></li> <li data-bbox="480 1659 1267 1727">2. <i>Incorporating multi-layer structures with three or fewer metal layers.</i></li> </ol>

<i>Category Code</i>	<i>Item Description</i>
3E002	<p>“Technology” (according to the General Technology Note) other than that specified in Category Code 3E001, for the “development” or “production” of a “microprocessor microcircuit”, “microcomputer microcircuit” or microcontroller microcircuit core, having an arithmetic logic unit with an access width of 32 bits or more and any of the following features or characteristics:</p> <p>a. A ‘vector processor unit’ designed to perform more than two calculations on floating-point vectors (one-dimensional arrays of 32-bit or larger numbers) simultaneously;</p> <p><i>Technical Note</i> A ‘vector processing unit’ is a processor element with built-in instructions that perform multiple calculations on floating-point vectors (one-dimensional arrays of 32-bit or larger numbers) simultaneously, having at least one vector arithmetic logic unit.</p> <p>b. Designed to perform more than four 64-bit or larger floating-point operation results per cycle; <u>or</u></p> <p>c. Designed to perform more than four 16-bit fixed-point multiply-accumulate results per cycle (e.g. digital manipulation of analogue information that has been previously converted into digital form, also known as digital “signal processing”).</p> <p><i>Note</i> Category Code 3E002.c. does not include “technology” for multimedia extensions.</p> <p><i>Note 1</i> Category Code 3E002 does not include “technology” for the “development” or “production” of micro-processor cores, having all of the following:</p> <p>a. Using “technology” at or above 0.130 <math>\mu\text{m}</math>; <u>and</u></p> <p>b. Incorporating multi-layer structures with five or fewer metal layers.</p> <p><i>Note 2</i> Category Code 3E002 includes “technology” for digital signal processors and digital array processors.</p>

<i>Category Code</i>	<i>Item Description</i>
3E003	<p>Other “technology” for the “development” or “production” of the following:</p> <ul style="list-style-type: none"> <li>a. Vacuum microelectronic devices;</li> <li>b. Hetero-structure semiconductor devices such as high electron mobility transistors (HEMT), hetero-bipolar transistors (HBT), quantum well and super lattice devices;</li> </ul> <p><i>Note</i>  <i>Category Code 3E003.b. does not include “technology” for high electron mobility transistors (HEMT) operating at frequencies lower than 31.8 GHz and hetero-junction bipolar transistors (HBT) operating at frequencies lower than 31.8 GHz.</i></p> <ul style="list-style-type: none"> <li>c. “Superconductive” electronic devices;</li> <li>d. Substrates of films of diamond for electronic components;</li> <li>e. Substrates of silicon-on-insulator (SOI) for integrated circuits in which the insulator is silicon dioxide;</li> <li>f. Substrates of silicon carbide for electronic components;</li> <li>g. Electronic vacuum tubes operating at frequencies of 31.8 GHz or higher.</li> </ul>
3E101	<p>“Technology” (according to the General Technology Note) for the “use” of equipment or “software” specified in Category Code 3A001.a.1. or 2., 3A101, 3A102 or 3D101.</p>
3E102	<p>“Technology” (according to the General Technology Note) for the “development” of “software” specified in Category Code 3D101.</p>
3E201	<p>“Technology” (according to the General Technology Note) for the “use” of equipment specified in Category Codes 3A001.e.2., 3A001.e.3., 3A001.g., 3A201, 3A225 to 3A234.</p>

<i>Category Code</i>	<i>Item Description</i>
3E225	“Technology”, in the form of codes or keys, to enhance or release the performance of frequency changers or generators to meet the characteristics of Category Code 3A225.

Category Code	Item Description
<b>CATEGORY 4 — COMPUTERS</b>	
<i>Note 1</i>	
Computers, related equipment and “software” performing telecommunications or “local area network” functions with the performance characteristics in Category 5 – Part 1 (Telecommunications) shall also be treated as coming within that Category.	
<i>Note 2</i>	
Control units which directly interconnect the buses or channels of central processing units, “main storage” or disk controllers are not regarded as telecommunications equipment described in Category 5 – Part 1 (Telecommunications).	
<i>N.B.</i>	
For “software” specially designed for packet switching, see Category Code 5D001.	
<i>Note 3</i>	
Computers, related equipment and “software” performing cryptographic, cryptanalytic, certifiable multi-level security or certifiable user isolation functions, or which limit electromagnetic compatibility (EMC), with the performance characteristics in Category 5 – Part 2 (“Information Security”) shall also be treated as coming within that Category.	
4A 4A001	<p><b>Systems, Equipment and Components</b></p> <p>Electronic computers and related equipment, having any of the following, and “electronic assemblies” and specially designed components therefor:</p> <p><i>N.B.</i></p> <p>See also Category Code 4A101.</p> <p>a. Specially designed to have any of the following:</p> <ol style="list-style-type: none"> <li>1. Rated for operation at an ambient temperature below 228 K (-45°C) or above 358 K (85°C); <u>or</u></li> </ol> <p><i>Note</i></p> <p>Category Code 4A001.a.1. does not apply to computers specially designed for civil automobile, railway train or “civil aircraft” applications.</p>

<i>Category Code</i>	<i>Item Description</i>
	<p>2. Radiation hardened to exceed any of the following specifications:</p> <p>a. Total Dose <math>5 \times 10^3</math> Gy (silicon);</p> <p>b. Dose Rate Upset <math>5 \times 10^6</math> Gy (silicon)/s; <u>or</u></p> <p>c. Single Event Upset <math>1 \times 10^{-8}</math> Error/bit/day;</p> <p><i>Note</i>  <i>Category Code 4A001.a.2. does not include computers specially designed for “civil aircraft” applications.</i></p> <p>b. Not used.</p>
4A003	<p>“Digital computers”, “electronic assemblies”, and related equipment therefor, as follows, and specially designed components therefor:</p> <p><i>Note 1</i>  <i>Category Code 4A003 includes the following:</i></p> <ul style="list-style-type: none"> <li>– ‘Vector processors’;</li> <li>– Array processors;</li> <li>– Digital signal processors;</li> <li>– Logic processors;</li> <li>– Equipment designed for “image enhancement”;</li> <li>– Equipment designed for “signal processing”.</li> </ul> <p><i>Note 2</i>  <i>The control status of the “digital computers” and related equipment described in Category Code 4A003 is determined by the control status of other equipment or systems provided:</i></p> <p>a. The “digital computers” or related equipment are essential for the operation of the other equipment or systems;</p> <p>b. The “digital computers” or related equipment are not a “principal element” of the other equipment or systems; <u>and</u></p>

Category Code	Item Description
	<p><u>N.B. 1</u>  <i>The control status of “signal processing” or “image enhancement” equipment specially designed for other equipment with functions limited to those required for the other equipment is determined by the control status of the other equipment even if it exceeds the “principal element” criterion.</i></p> <p><u>N.B. 2</u>  <i>For the control status of “digital computers” or related equipment for telecommunications equipment, see Category 5 – Part 1 (Telecommunications).</i></p> <p>c. <i>The “technology” for the “digital computers” and related equipment is determined by Category 4E.</i></p> <p>a. Not used;</p> <p>b. “Digital computers” having an “Adjusted Peak Performance” (“APP”) exceeding 8 Weighted TeraFLOPS (WT);</p> <p>c. “Electronic assemblies” specially designed or modified for enhancing performance by aggregation of processors so that the “APP” of the aggregation exceeds the limit specified in Category Code 4A003.b.;</p> <p><u>Note 1</u>  <i>Category Code 4A003.c. includes only “electronic assemblies” and programmable interconnections not exceeding the limit specified in Category Code 4A003.b. when shipped as unintegrated “electronic assemblies”. It does not include “electronic assemblies” inherently limited by nature of their design for use as related equipment specified in Category Code 4A003.e.</i></p> <p><u>Note 2</u>  <i>Category Code 4A003.c. does not include “electronic assemblies” specially designed for a product or family of products whose maximum configuration does not exceed the limit specified in Category Code 4A003.b.</i></p> <p>d. Not used;</p> <p>e. Equipment performing analogue-to-digital conversions exceeding the limits specified in Category Code 3A001.a.5.;</p> <p>f. Not used;</p>

<i>Category Code</i>	<i>Item Description</i>
g.	Equipment specially designed for aggregating the performance of “digital computers” by providing external interconnections which allows communications at unidirectional data rates exceeding 2 Gbyte/s per link.  <i>Note</i> <i>Category Code 4A003.g. does not include internal interconnection equipment (e.g. backplanes and buses), passive interconnection equipment, “network access controllers” or “communications channel controllers”.</i>
4A004	Computers as follows and specially designed related equipment, “electronic assemblies” and components therefor:  a. “Systolic array computers”; b. “Neural computers”; c. “Optical computers”.
4A005	Systems, equipment, and components therefor, specially designed or modified for the generation, operation or delivery of, or communication with, “intrusion software”.
4A101	Analogue computers, “digital computers” or digital differential analysers, other than those specified in Category Code 4A001.a.1., which are ruggedised and designed or modified for use in space launch vehicles specified in Category Code 9A004 or sounding rockets specified in Category Code 9A104.
4A102	“Hybrid computers” specially designed for modelling, simulation or design integration of space launch vehicles specified in Category Code 9A004 or sounding rockets specified in Category Code 9A104.  <i>Note</i> <i>Category Code 4A102 only extends to equipment supplied with “software” specified in Category Code 7D103 or 9D103.</i>



<i>Category Code</i>	<i>Item Description</i>
<b>4B</b>	<b>Test, Inspection and Production Equipment</b> None.
<b>4C</b>	<b>Materials</b> None.
<b>4D</b>	<b>Software</b> <u>Note</u> <i>For “software” for equipment described in other Categories, please see the appropriate Category.</i>
4D001	<p>“Software” as follows:</p> <ol style="list-style-type: none"> <li>a. “Software” specially designed or modified for the “development” or “production” of equipment or “software” specified in Category Code 4A001 to 4A004, or Category 4D;</li> <li>b. “Software”, other than that specified in Category Code 4D001.a., specially designed or modified for the “development” or “production” of equipment, as follows: <ol style="list-style-type: none"> <li>1. “Digital computers” having an “Adjusted Peak Performance” (“APP”) exceeding 0.6 Weighted TeraFLOPS (WT);</li> <li>2. “Electronic assemblies” specially designed or modified for enhancing performance by aggregation of processors so that the “APP” of the aggregation exceeds the limit in Category Code 4D001.b.1.</li> </ol> </li> </ol> <p><u>Note</u> <i>Please see Technical Note on calculation of “APP” immediately after Category Code 4E001.</i></p>
4D002	Not used.
4D003	Not used.

<i>Category Code</i>	<i>Item Description</i>
4D004	“Software” specially designed or modified for the generation, operation or delivery of, or communication with, “intrusion software”.
<b>4E</b>	<b>Technology</b>
4E001	<p>a. “Technology” (according to the General Technology Note) for the “development”, “production” or “use” of equipment or “software” specified in Category 4A or 4D;</p> <p>b. “Technology”, other than that specified in Category Code 4E001.a., specially designed or modified for the “development” or “production” of equipment as follows:</p> <ol style="list-style-type: none"> <li>1. “Digital computers” having an “Adjusted Peak Performance” (“APP”) exceeding 0.6 Weighted TeraFLOPS (WT);</li> <li>2. “Electronic assemblies” specially designed or modified for enhancing performance by aggregation of processors so that the “APP” of the aggregation exceeds the limit in Category Code 4E001.b.1.;</li> </ol> <p>c. “Technology” for the “development” of “intrusion software”.</p> <p><i>Note</i> Please see Technical Note on calculation of “APP” immediately after Category Code 4E001.</p>

---



---

TECHNICAL NOTE ON “ADJUSTED PEAK PERFORMANCE” (“APP”)

“APP” is an adjusted peak rate at which “digital computers” perform 64-bit or larger floating point additions and multiplications.

“APP” is expressed in Weighted TeraFLOPS (WT), in units of  $10^{12}$  adjusted floating point operations per second.

Abbreviations used in this Technical Note

n	number of processors in the “digital computer”
i	processor number ( $i = 1, \dots, n$ )
$t_i$	processor cycle time ( $t_i = 1/F_i$ )
$F_i$	processor frequency
$R_i$	peak floating point calculating rate
$W_i$	architecture adjustment factor

Outline of “APP” calculation method

1. For each processor  $i$ , determine the peak number of 64-bit or larger floating point operations,  $FPO_i$ , performed per cycle for each processor in the “digital computer”.

Note

*In determining FPO, include only 64-bit or larger floating point additions and/or multiplications. All floating point operations must be expressed in operations per processor cycle; operations requiring multiple cycles may be expressed in fractional results per cycle. For processors not capable of performing calculations on floating point operands of 64-bit or more, the effective calculating rate  $R$  is zero.*

2. Calculate the floating point rate  $R$  for each processor  $R_i = FPO_i/t_i$ .
3. Calculate “APP” as “APP” =  $W_1 \times R_1 + W_2 \times R_2 + \dots + W_n \times R_n$ .
4. For ‘vector processors’,  $W_i = 0.9$ . For non-‘vector processors’,  $W_i = 0.3$ .

Note 1

*For processors that perform compound operations in a cycle, such as addition and multiplication, each operation is counted.*

Note 2

*For a pipelined processor the effective calculating rate  $R$  is the faster of the pipelined rate, once the pipeline is full, or the non-pipelined rate.*

---

---

Note 3

The calculating rate *R* of each contributing processor is to be calculated at its maximum value theoretically possible before the “APP” of the combination is derived. Simultaneous operations are assumed to exist when the computer manufacturer claims concurrent, parallel, or simultaneous operation or execution in a manual or brochure for the computer.

Note 4

Do not include processors that are limited to input/output and peripheral functions (e.g. disk drive, communication and video display) when calculating “APP”.

Note 5

“APP” values are not to be calculated for processor combinations (inter)connected by “Local Area Networks”, Wide Area Networks, I/O shared connections/devices, I/O controllers and any communication interconnection implemented by “software”.

Note 6

“APP” values must be calculated for:

1. Processor combinations containing processors specially designed to enhance performance by aggregation, operating simultaneously and sharing memory; or
2. Multiple memory/processor combinations operating simultaneously utilising specially designed hardware.

Technical Note

Aggregate all processors and accelerators operating simultaneously and located on the same die.

Note 7

A ‘vector processor’ is defined as a processor with built-in instructions that perform multiple calculations on floating-point vectors (one-dimensional arrays of 64-bit or larger numbers) simultaneously, having at least 2 vector functional units and at least 8 vector registers of at least 64 elements each.

Category Code	Item Description
<b>CATEGORY 5 — TELECOMMUNICATIONS AND “INFORMATION SECURITY”</b>	
<b>Part 1 — TELECOMMUNICATIONS</b>	
<i>Note 1</i>	
<i>Category 5 – Part 1 concerns components, “lasers”, test and “production” equipment and “software” therefor which are specially designed for telecommunications equipment or systems.</i>	
<i>N.B. 1</i>	
<i>For “lasers” specially designed for telecommunications equipment or systems, see Category Code 6A005.</i>	
<i>N.B. 2</i>	
<i>See also Category 5 – Part 2 for equipment, components, and “software”, performing or incorporating “information security” functions.</i>	
<i>Note 2</i>	
<i>“Digital computers”, related equipment or “software”, when essential for the operation and support of telecommunications equipment described in this Category, are regarded as specially designed components for the purposes of this Category, provided they are the standard models customarily supplied by the manufacturer. This includes operation, administration, maintenance, engineering or billing computer systems.</i>	
<b>5A1</b>	<b>Systems, Equipment and Components</b>
5A001	Telecommunications systems, equipment, components and accessories as follows: <ul style="list-style-type: none"> <li>a. Any type of telecommunications equipment having any of the following characteristics, functions or features: <ol style="list-style-type: none"> <li>1. Specially designed to withstand transitory electronic effects or electromagnetic pulse effects, both arising from a nuclear explosion;</li> <li>2. Specially hardened to withstand gamma, neutron or ion radiation; <u>or</u></li> <li>3. Specially designed to operate outside the temperature range from 218 K (-55°C) to 397 K (124°C);</li> </ol> </li> </ul>

Category Code	Item Description
	<p data-bbox="603 456 667 488"><u>Note</u></p> <p data-bbox="603 497 1264 562">Category Code 5A001.a.3. applies only to electronic equipment.</p> <p data-bbox="539 580 603 611"><u>Note</u></p> <p data-bbox="539 620 1264 685">Category Codes 5A001.a.2. and 5A001.a.3. do not include equipment designed or modified for use on board satellites.</p> <p data-bbox="475 703 1264 801">b. Telecommunications systems and equipment, and specially designed components and accessories therefor, having any of the following characteristics, functions or features:</p> <ol data-bbox="539 819 1264 1774" style="list-style-type: none"> <li data-bbox="539 819 1264 884">1. Being underwater untethered communications systems having any of the following: <ol data-bbox="625 902 1264 1220" style="list-style-type: none"> <li data-bbox="625 902 1264 967">a. An acoustic carrier frequency outside the range from 20 kHz to 60 kHz;</li> <li data-bbox="625 985 1264 1050">b. Using an electromagnetic carrier frequency below 30 kHz;</li> <li data-bbox="625 1068 1264 1099">c. Using electronic beam steering techniques; <u>or</u></li> <li data-bbox="625 1120 1264 1220">d. Using “lasers” or light-emitting diodes (LEDs) with an output wavelength greater than 400 nm and less than 700 nm, in a “local area network”;</li> </ol> </li> <li data-bbox="539 1238 1264 1303">2. Being radio equipment operating in the 1.5 MHz to 87.5 MHz band and having all of the following: <ol data-bbox="625 1321 1264 1774" style="list-style-type: none"> <li data-bbox="625 1321 1264 1420">a. Automatically predicting and selecting frequencies and “total digital transfer rates” per channel to optimise the transmission; <u>and</u></li> <li data-bbox="625 1438 1264 1774">b. Incorporating a linear power amplifier configuration having a capability to support multiple signals simultaneously at an output power of 1 kW or more in the frequency range of 1.5 MHz or more but less than 30 MHz, or 250 W or more in the frequency range of 30 MHz or more but not exceeding 87.5 MHz, over an “instantaneous bandwidth” of one octave or more and with an output harmonic and distortion content of better than -80 dB;</li> </ol> </li> </ol>

<i>Category Code</i>	<i>Item Description</i>
	<p>3. Being radio equipment employing “spread spectrum” techniques, including “frequency hopping” techniques, other than those specified in Category Code 5A001.b.4. and having any of the following:</p> <ul style="list-style-type: none"> <li>a. User programmable spreading codes; <u>or</u></li> <li>b. A total transmitted bandwidth which is 100 or more times the bandwidth of any one information channel and in excess of 50 kHz;</li> </ul> <p><i>Note</i>  <i>Category Code 5A001.b.3.b. does not apply to radio equipment specially designed for use with any of the following:</i></p> <ul style="list-style-type: none"> <li>a. <i>Civil cellular radio-communications systems; <u>or</u></i></li> <li>b. <i>Fixed or mobile satellite earth stations for commercial civil telecommunications.</i></li> </ul> <p><i>Note</i>  <i>Category Code 5A001.b.3. does not include equipment designed to operate at an output power of 1 W or less.</i></p> <p>4. Being radio equipment employing ultra-wideband modulation techniques, having user programmable channelising codes, scrambling codes or network identification codes and having any of the following:</p> <ul style="list-style-type: none"> <li>a. A bandwidth exceeding 500 MHz; <u>or</u></li> <li>b. A “fractional bandwidth” of 20% or more;</li> </ul> <p>5. Being digitally controlled radio receivers having all of the following:</p> <ul style="list-style-type: none"> <li>a. More than 1,000 channels;</li> <li>b. A ‘channel switching time’ of less than 1 ms;</li> <li>c. Automatic searching or scanning of a part of the electromagnetic spectrum; <u>and</u></li> <li>d. Identification of the received signals or the type of transmitter; <u>or</u></li> </ul>

Category Code	Item Description
	<p><u>Note</u></p> <p>Category Code 5A001.b.5. does not include radio equipment specially designed for use with civil cellular radio-communications systems.</p> <p><u>Technical Note</u></p> <p>'Channel switching time' means the time (i.e. delay) to change from one receiving frequency to another, to arrive at or within <math>\pm 0.05\%</math> of the final specified receiving frequency. Items having a specified frequency range of less than <math>\pm 0.05\%</math> around their centre frequency are defined to be incapable of channel frequency switching.</p> <p>6. Employing functions of digital "signal processing" to provide 'voice coding' output at rates of less than 2,400 bit/s.</p> <p><u>Technical Notes</u></p> <ol style="list-style-type: none"> <li>1. For variable rate 'voice coding', Category Code 5A001.b.6. applies to the 'voice coding' output of continuous speech.</li> <li>2. For the purpose of Category Code 5A001.b.6., 'voice coding' is defined as the technique to take samples of human voice and then convert these samples into a digital signal, taking into account specific characteristics of human speech.</li> </ol> <p>c. Optical fibres of more than 500 m in length and specified by the manufacturer as being capable of withstanding a 'proof test' tensile stress of <math>2 \times 10^9</math> N/m<sup>2</sup> or more;</p> <p><u>N.B.</u></p> <p>For underwater umbilical cables, see Category Code 8A002.a.3.</p>



Category Code	Item Description
	<p data-bbox="544 454 724 483"><u>Technical Note</u></p> <p data-bbox="544 495 1262 725"><i>‘Proof Test’: on-line or off-line production screen testing that dynamically applies a prescribed tensile stress over a 0.5 m to 3 m length of fibre at a running rate of 2 m/s to 5 m/s while passing between capstans approximately 150 mm in diameter. The ambient temperature is a nominal 293 K (20°C) and relative humidity 40%. Equivalent national standards may be used for executing the proof test.</i></p> <p data-bbox="480 748 1262 808">d. “Electronically steerable phased array antennae” operating above 31.8 GHz;</p> <p data-bbox="544 831 603 860"><u>Note</u></p> <p data-bbox="544 871 1262 1003"><i>Category Code 5A001.d. does not include “electronically steerable phased array antennae” for landing systems with instruments meeting ICAO standards covering Microwave Landing Systems (MLS).</i></p> <p data-bbox="480 1025 1262 1122">e. Radio direction finding equipment operating at frequencies above 30 MHz and having all of the following, and specially designed components therefor:</p> <ol data-bbox="544 1137 1262 1285" style="list-style-type: none"> <li data-bbox="544 1137 1262 1173">1. “Instantaneous bandwidth” of 10 MHz or more; <u>and</u></li> <li data-bbox="544 1189 1262 1285">2. Capable of finding a Line Of Bearing (LOB) to non-cooperating radio transmitters with a signal duration of less than 1 ms;</li> </ol> <p data-bbox="480 1308 1262 1404">f. Mobile telecommunications interception or jamming equipment, and monitoring equipment therefor, as follows, and specially designed components therefor:</p> <ol data-bbox="544 1420 1262 1823" style="list-style-type: none"> <li data-bbox="544 1420 1262 1480">1. Interception equipment designed for the extraction of voice or data, transmitted over the air interface;</li> <li data-bbox="544 1503 1262 1666">2. Interception equipment not specified in Category Code 5A001.f.1., designed for the extraction of client device or subscriber identifiers (e.g. IMSI, TIMSI or IMEI), signalling, or other metadata transmitted over the air interface;</li> <li data-bbox="544 1688 1262 1823">3. Jamming equipment specially designed or modified to intentionally and selectively interfere with, deny, inhibit, degrade or seduce mobile telecommunication services and performing any of the following:</li> </ol>

<i>Category Code</i>	<i>Item Description</i>
	<p data-bbox="628 456 1262 517">a. Simulate the functions of Radio Access Network (RAN) equipment;</p> <p data-bbox="628 539 1262 636">b. Detect and exploit specific characteristics of the mobile telecommunications protocol employed (e.g. GSM); <u>or</u></p> <p data-bbox="628 658 1262 754">c. Exploit specific characteristics of the mobile telecommunications protocol employed (e.g. GSM);</p> <p data-bbox="544 777 1262 873">4. RF monitoring equipment designed or modified to identify the operation of items specified in Category Code 5A001.f.1., 5A001.f.2. or 5A001.f.3.;</p> <p data-bbox="544 893 603 922"><u>Note</u></p> <p data-bbox="544 931 1262 992"><i>Category Codes 5A001.f.1. and 5A001.f.2. do not include any of the following:</i></p> <p data-bbox="544 1014 1262 1111">a. <i>Equipment specially designed for the interception of analogue Private Mobile Radio (PMR), IEEE 802.11 WLAN;</i></p> <p data-bbox="544 1133 1262 1193">b. <i>Equipment designed for mobile telecommunications network operators; <u>or</u></i></p> <p data-bbox="544 1216 1262 1312">c. <i>Equipment designed for the “development” or “production” of mobile telecommunications equipment or systems.</i></p> <p data-bbox="544 1335 624 1364"><u>N.B. 1</u></p> <p data-bbox="544 1373 1078 1402"><i>See also Division 2 of Part I of this Schedule.</i></p> <p data-bbox="544 1424 624 1453"><u>N.B. 2</u></p> <p data-bbox="544 1462 1150 1491"><i>For radio receivers, see Category Code 5A001.b.5.</i></p> <p data-bbox="480 1514 1262 1644">g. Passive Coherent Location (PCL) systems or equipment, specially designed for detecting and tracking moving objects by measuring reflections of ambient radio frequency emissions, supplied by non-radar transmitters;</p> <p data-bbox="544 1666 727 1695"><u>Technical Note</u></p> <p data-bbox="544 1704 1262 1765"><i>Non-radar transmitters may include commercial radio, television or cellular telecommunications base stations.</i></p>

Category Code	Item Description
	<p data-bbox="539 454 603 483"><u>Note</u></p> <p data-bbox="539 495 1267 562">Category Code 5A001.g. does not include any of the following:</p> <ul style="list-style-type: none"> <li data-bbox="539 577 1023 607">a. Radio-astronomical equipment; <u>or</u></li> <li data-bbox="539 629 1267 696">b. Systems or equipment, that require any radio transmission from the target.</li> </ul> <p data-bbox="475 712 1267 779">h. Counter Improvised Explosive Device (IED) equipment and related equipment, as follows:</p> <ul style="list-style-type: none"> <li data-bbox="539 795 1267 929">1. Radio Frequency (RF) transmitting equipment, not specified in Category Code 5A001.f., designed or modified for prematurely activating or preventing the initiation of Improvised Explosive Devices;</li> <li data-bbox="539 945 1267 1079">2. Equipment using techniques designed to enable radio communications in the same frequency channels on which co-located equipment specified in Category Code 5A001.h.1. is transmitting;</li> </ul> <p data-bbox="539 1095 603 1124"><u>N.B.</u></p> <p data-bbox="539 1135 1082 1164">See also Division 2 of Part I of this Schedule.</p> <ul style="list-style-type: none"> <li data-bbox="475 1180 660 1209">i. Not used;</li> <li data-bbox="475 1232 1267 1332">j. Internet Protocol (IP) network communications surveillance systems or equipment, and specially designed components therefor, having all of the following: <ul style="list-style-type: none"> <li data-bbox="539 1348 1267 1449">1. Performing all of the following on a carrier class Internet Protocol (IP) network (e.g. national grade IP backbone): <ul style="list-style-type: none"> <li data-bbox="624 1464 1267 1568">a. Analysis at the application layer (e.g. Layer 7 of Open Systems Interconnection (OSI) model (ISO/IEC 7498-1));</li> <li data-bbox="624 1583 1267 1686">b. Extraction of selected metadata and application content (e.g. voice, video, messages, attachments); <u>and</u></li> <li data-bbox="624 1702 1062 1731">c. Indexing of extracted data; <u>and</u></li> </ul> </li> <li data-bbox="539 1747 1267 1818">2. Being specially designed to carry out all of the following:</li> </ul> </li> </ul>

<i>Category Code</i>	<i>Item Description</i>
	<p>a. Execution of searches on the basis of ‘hard selectors’; <u>and</u></p> <p>b. Mapping of the relational network of an individual or of a group of people.</p> <p><u>Note</u>  <i>Category Code 5A001.j. does not include systems or equipment, specially designed for any of the following:</i></p> <p>a. <i>Marketing purposes;</i></p> <p>b. <i>Network Quality of Service (QoS); or</i></p> <p>c. <i>Quality of Experience (QoE).</i></p> <p><u>Technical Note</u>  <i>‘Hard selectors’ means data or set of data, related to an individual (e.g. family name, given name, e-mail, street address, phone number or group affiliations).</i></p>
5A101	<p>Telemetry and telecontrol equipment, including ground equipment, designed or modified for ‘missiles’.</p> <p><u>Technical Note</u>  <i>In Category Code 5A101, ‘missile’ means complete rocket systems and unmanned aerial vehicle systems capable of a range exceeding 300 km.</i></p> <p><u>Note</u>  <i>Category Code 5A101 does not include:</i></p> <p>a. <i>Equipment designed or modified for manned aircraft or satellites;</i></p> <p>b. <i>Ground based equipment designed or modified for terrestrial or marine applications;</i></p> <p>c. <i>Equipment designed for commercial, civil or ‘Safety of Life’ (e.g. data integrity, flight safety) GNSS services.</i></p>

<i>Category Code</i>	<i>Item Description</i>
<b>5B1</b>	<b>Test, Inspection and Production Equipment</b>
5B001	<p>Telecommunications test, inspection and production equipment, components and accessories, as follows:</p> <p>a. Equipment and specially designed components or accessories therefor, specially designed for the “development” or “production” of equipment, functions or features specified in Category Code 5A001;</p> <p><i>Note</i>  <i>Category Code 5B001.a. does not include optical fibre characterisation equipment.</i></p> <p>b. Equipment and specially designed components or accessories therefor, specially designed for the “development” of any of the following telecommunication transmission or switching equipment:</p> <ol style="list-style-type: none"> <li>1. Not used;</li> <li>2. Equipment employing a “laser” and having any of the following: <ol style="list-style-type: none"> <li>a. A transmission wavelength exceeding 1,750 nm;</li> <li>b. Performing “optical amplification” using praseodymium-doped fluoride fibre amplifiers (PDFFA);</li> <li>c. Employing coherent optical transmission or coherent optical detection techniques; <u>or</u></li> </ol> </li> </ol> <p><i>Note</i>  <i>Category Code 5B001.b.2.c. includes equipment specially designed for the “development” of systems using an optical local oscillator in the receiving side to synchronise with a carrier “laser”.</i></p> <p><i>Technical Note</i>  <i>For the purpose of Category Code 5B001.b.2.c., these techniques include optical heterodyne, homodyne or intradyne techniques.</i></p>

<i>Category Code</i>	<i>Item Description</i>
	<p>d. Employing analogue techniques and having a bandwidth exceeding 2.5 GHz; <u>or</u></p> <p><i>Note</i>  <i>Category Code 5B001.b.2.d. does not include equipment specially designed for the “development” of commercial TV systems.</i></p> <p>3. Not used;</p> <p>4. Radio equipment employing Quadrature-Amplitude-Modulation (QAM) techniques above level 256.</p> <p>5. Not used.</p>
<b>5C1</b>	<p><b>Materials</b></p> <p>None.</p>
<b>5D1</b>	<p><b>Software</b></p>
5D001	<p>“Software” as follows:</p> <p>a. “Software” specially designed or modified for the “development”, “production” or “use” of equipment, functions or features, specified in Category Code 5A001;</p> <p>b. Not used;</p> <p>c. Specific “software” specially designed or modified to provide characteristics, functions or features of equipment, specified in Category Code 5A001 or 5B001;</p> <p>d. “Software” specially designed or modified for the “development” of any of the following telecommunication transmission or switching equipment:</p> <p>1. Not used;</p> <p>2. Equipment employing a “laser” and having any of the following:</p> <p>a. A transmission wavelength exceeding 1,750 nm; <u>or</u></p> <p>b. Employing analogue techniques and having a bandwidth exceeding 2.5 GHz; <u>or</u></p>

<i>Category Code</i>	<i>Item Description</i>
	<p data-bbox="691 454 751 483"><u>Note</u></p> <p data-bbox="691 495 1262 591"><i>Category Code 5D001.d.2.b. does not include “software” specially designed or modified for the “development” of commercial TV systems.</i></p> <ol data-bbox="544 611 1262 725" style="list-style-type: none"> <li data-bbox="544 611 722 640">3. Not used;</li> <li data-bbox="544 660 1262 725">4. Radio equipment employing Quadrature-Amplitude-Modulation (QAM) techniques above level 256.</li> </ol>
5D101	“Software” specially designed or modified for the “use” of equipment specified in Category Code 5A101.
<b>5E1</b>	<b>Technology</b>
5E001	<p data-bbox="480 976 791 1005">“Technology”, as follows:</p> <ol data-bbox="480 1025 1262 1879" style="list-style-type: none"> <li data-bbox="480 1025 1262 1189">a. “Technology” (according to the General Technology Note) for the “development”, “production” or “use” (excluding operation) of equipment, functions or features specified in Category Code 5A001 or “software” specified in Category Code 5D001.a.;</li> <li data-bbox="480 1209 1262 1879">b. Specific “technology” as follows: <ol data-bbox="544 1256 1262 1879" style="list-style-type: none"> <li data-bbox="544 1256 1262 1352">1. “Required” “technology” for the “development” or “production” of telecommunications equipment specially designed to be used on board satellites;</li> <li data-bbox="544 1373 1262 1536">2. “Technology” for the “development” or “use” of “laser” communication techniques with the capability of automatically acquiring and tracking signals and maintaining communications through exoatmosphere or sub-surface (water) media;</li> <li data-bbox="544 1556 1262 1756">3. “Technology” for the “development” of digital cellular radio base station receiving equipment whose reception capabilities that allow multi-band, multi-channel, multi-mode, multi-coding algorithm or multi-protocol operation can be modified by changes in “software”;</li> <li data-bbox="544 1776 1262 1879">4. “Technology” for the “development” of “spread spectrum” techniques, including “frequency hopping” techniques;</li> </ol> </li> </ol>

Category Code	Item Description
	<p data-bbox="603 456 667 488"><u>Note</u></p> <p data-bbox="603 497 1262 595"><i>Category Code 5E001.b.4. does not apply to “technology” for the “development” of any of the following:</i></p> <ul style="list-style-type: none"> <li data-bbox="628 613 1262 680">a. <i>Civil cellular radio-communications systems;</i> <i>or</i></li> <li data-bbox="628 698 1262 766">b. <i>Fixed or mobile satellite earth stations for commercial civil telecommunications.</i></li> </ul> <p data-bbox="480 779 1262 878">c. “Technology” (according to the General Technology Note) for the “development” or “production” of any of the following:</p> <ul style="list-style-type: none"> <li data-bbox="544 896 1262 994">1. Equipment employing digital techniques designed to operate at a “total digital transfer rate” exceeding 560 Gbit/s;</li> </ul> <p data-bbox="603 1012 788 1043"><u>Technical Note</u></p> <p data-bbox="603 1052 1262 1182"><i>For telecommunication switching equipment the “total digital transfer rate” is the unidirectional speed of a single interface, measured at the highest speed port or line.</i></p> <ul style="list-style-type: none"> <li data-bbox="544 1200 1262 1276">2. Equipment employing a “laser” and having any of the following: <ul style="list-style-type: none"> <li data-bbox="628 1290 1262 1357">a. A transmission wavelength exceeding 1,750 nm;</li> <li data-bbox="628 1370 1262 1469">b. Performing “optical amplification” using Praseodymium-Doped Fluoride Fibre Amplifiers (PDFFA);</li> <li data-bbox="628 1482 1262 1559">c. Employing coherent optical transmission or coherent optical detection techniques;</li> </ul> </li> </ul> <p data-bbox="692 1576 756 1608"><u>Note</u></p> <p data-bbox="692 1617 1262 1783"><i>Category Code 5E001.c.2.c. includes “technology” for the “development” or “production” of systems using an optical local oscillator in the receiving side to synchronise with a carrier “laser”.</i></p>



<i>Category Code</i>	<i>Item Description</i>
	<p data-bbox="691 454 874 488"><u>Technical Note</u></p> <p data-bbox="691 499 1267 629"><i>For the purpose of Category Code 5E001.c.2.c., these techniques include optical heterodyne, homodyne or intradyne techniques.</i></p> <p data-bbox="627 645 1267 745">d. Employing wavelength division multiplexing techniques of optical carriers at less than 100 GHz spacing; <u>or</u></p> <p data-bbox="627 763 1267 831">e. Employing analogue techniques and having a bandwidth exceeding 2.5 GHz;</p> <p data-bbox="691 846 751 880"><u>Note</u></p> <p data-bbox="691 891 1267 992"><i>Category Code 5E001.c.2.e. does not include “technology” for the “development” or “production” of commercial TV systems.</i></p> <p data-bbox="603 1008 663 1041"><u>N.B.</u></p> <p data-bbox="603 1052 1267 1153"><i>For “technology” for the “development” or “production” of non-telecommunications equipment employing a laser, see Category 6E.</i></p> <p data-bbox="544 1169 1267 1236">3. Equipment employing “optical switching” and having a switching time less than 1 ms;</p> <p data-bbox="544 1252 1267 1285">4. Radio equipment having any of the following:</p> <p data-bbox="627 1301 1267 1368">a. Quadrature-Amplitude-Modulation (QAM) techniques above level 256;</p> <p data-bbox="627 1384 1267 1451">b. Operating at input or output frequencies exceeding 31.8 GHz; <u>or</u></p> <p data-bbox="691 1467 751 1500"><u>Note</u></p> <p data-bbox="691 1512 1267 1736"><i>Category Code 5E001.c.4.b. does not include “technology” for the “development” or “production” of equipment designed or modified for operation in any frequency band which is “allocated by the ITU” for radio-communications services, but not for radio-determination.</i></p> <p data-bbox="627 1751 1267 1890">c. Operating in the 1.5 MHz to 87.5 MHz band and incorporating adaptive techniques providing more than 15 dB suppression of an interfering signal; <u>or</u></p>

<i>Category Code</i>	<i>Item Description</i>
	<p>5. Not used;</p> <p>6. Mobile equipment having all of the following:</p> <ol style="list-style-type: none"> <li>a. Operating at an optical wavelength greater than or equal to 200 nm and less than or equal to 400 nm; <u>and</u></li> <li>b. Operating as a “local area network”;</li> </ol> <p>d. “Technology” (according to the General Technology Note) for the “development” or “production” of Microwave Monolithic Integrated Circuit (MMIC) power amplifiers specially designed for telecommunications and that are any of the following:</p> <p><i>Technical Note</i></p> <p><i>For the purpose of Category Code 5E001.d., the parameter peak saturated power output may also be referred to on product data sheets as output power, saturated power output, maximum power output, peak power output, or peak envelope power output.</i></p> <ol style="list-style-type: none"> <li>1. Rated for operation at frequencies exceeding 2.7 GHz up to and including 6.8 GHz with a “fractional bandwidth” greater than 15%, and having any of the following: <ol style="list-style-type: none"> <li>a. A peak saturated power output greater than 75 W (48.75 dBm) at any frequency exceeding 2.7 GHz up to and including 2.9 GHz;</li> <li>b. A peak saturated power output greater than 55 W (47.4 dBm) at any frequency exceeding 2.9 GHz up to and including 3.2 GHz;</li> <li>c. A peak saturated power output greater than 40 W (46 dBm) at any frequency exceeding 3.2 GHz up to and including 3.7 GHz; <u>or</u></li> <li>d. A peak saturated power output greater than 20 W (43 dBm) at any frequency exceeding 3.7 GHz up to and including 6.8 GHz;</li> </ol> </li> <li>2. Rated for operation at frequencies exceeding 6.8 GHz up to and including 16 GHz with a “fractional bandwidth” greater than 10%, and having any of the following:</li> </ol>

<i>Category Code</i>	<i>Item Description</i>
	<ul style="list-style-type: none"> <li>a. A peak saturated power output greater than 10 W (40 dBm) at any frequency exceeding 6.8 GHz up to and including 8.5 GHz; <u>or</u></li> <li>b. A peak saturated power output greater than 5 W (37 dBm) at any frequency exceeding 8.5 GHz up to and including 16 GHz;</li> </ul> <ul style="list-style-type: none"> <li>3. Rated for operation with a peak saturated power output greater than 3 W (34.77 dBm) at any frequency exceeding 16 GHz up to and including 31.8 GHz, and with a “fractional bandwidth” greater than 10%;</li> <li>4. Rated for operation with a peak saturated power output greater than 0.1 nW (-70 dBm) at any frequency exceeding 31.8 GHz up to and including 37 GHz;</li> <li>5. Rated for operation with a peak saturated power output greater than 1 W (30 dBm) at any frequency exceeding 37 GHz up to and including 43.5 GHz, and with a “fractional bandwidth” greater than 10%;</li> <li>6. Rated for operation with a peak saturated power output greater than 31.62 mW (15 dBm) at any frequency exceeding 43.5 GHz up to and including 75 GHz, and with a “fractional bandwidth” of greater than 10%;</li> <li>7. Rated for operation with a peak saturated power output greater than 10 mW (10 dBm) at any frequency exceeding 75 GHz up to and including 90 GHz, and with a “fractional bandwidth” of greater than 5%; <u>or</u></li> <li>8. Rated for operation with a peak saturated power output greater than 0.1 nW (-70 dBm) at any frequency exceeding 90 GHz;</li> </ul> <ul style="list-style-type: none"> <li>e. “Technology” (according to the General Technology Note) for the “development” or “production” of electronic devices and circuits, specially designed for telecommunications and containing components manufactured from “superconductive” materials, specially designed for operation at temperatures below the “critical temperature” of at least one of the “superconductive” constituents and having any of the following:</li> </ul>

<i>Category Code</i>	<i>Item Description</i>
5E101	<ol style="list-style-type: none"><li data-bbox="544 454 1267 589">1. Current switching for digital circuits using “superconductive” gates with a product of delay time per gate (in seconds) and power dissipation per gate (in Watts) of less than <math>10^{-14}</math> J; <u>or</u></li><li data-bbox="544 607 1267 674">2. Frequency selection at all frequencies using resonant circuits with Q-values exceeding 10,000.</li></ol> <p data-bbox="480 734 1267 842">“Technology” (according to the General Technology Note) for the “development”, “production” or “use” of equipment specified in Category Code 5A101.</p>

Category Code	Item Description
---------------	------------------

**Part 2 — “INFORMATION SECURITY”**

Note 1

*Category 5 – Part 2 concerns “information security” equipment, “software”, systems, application specific “electronic assemblies”, modules, integrated circuits, components or functions whether or not they are components or “electronic assemblies” of other equipment.*

Note 2

*Category 5 – Part 2 does not include products when accompanying their user for the user’s personal use.*

Note 3

*Cryptography Note*

*Category Codes 5A002 and 5D002 do not include goods as follows:*

- a. *Goods that meet all of the following:*
  1. *Generally available to the public by being sold, without restriction, from stock at retail selling points by means of any of the following:*
    - a. *Over-the-counter transactions;*
    - b. *Mail order transactions;*
    - c. *Electronic transactions; or*
    - d. *Telephone call transactions;*
  2. *The cryptographic functionality cannot easily be changed by the user; and*
  3. *Designed for installation by the user without further substantial support by the supplier;*
- b. *Hardware components or ‘executable software’, of existing items described in paragraph a. of this Note, that have been designed for these existing items, meeting all of the following:*
  1. *“Information security” is not the primary function or set of functions of the component or ‘executable software’;*
  2. *The component or ‘executable software’ does not change any cryptographic functionality of the existing items, or add new cryptographic functionality to the existing items; and*
  3. *The feature set of the component or ‘executable software’ is fixed and is not designed or modified to customer specification.*

Category Code	Item Description
---------------	------------------

Technical Note

For the purpose of the Cryptography Note, ‘executable software’ means “software” in executable form, from an existing hardware component excluded from Category Code 5A002 by the Cryptography Note.

Note

‘Executable software’ does not include complete binary images of the “software” running on an end-item.

Note to the Cryptography Note

1. To meet paragraph a. of Note 3, all of the following must apply:
  - a. The item is of potential interest to a wide range of individuals and businesses; and
  - b. The price and information about the main functionality of the item are available before purchase without the need to consult the vendor or supplier.
2. In determining eligibility of paragraph a. of Note 3, factors such as quantity, price, required technical skill, existing sales channels, typical customers, typical use or any exclusionary practices of the supplier may be taken into account.

Note 4

Category 5 – Part 2 does not include items incorporating or using “cryptography” and meeting all of the following:

- a. The primary function or set of functions is not any of the following:
  1. “Information security”;
  2. A computer, including operating systems, parts and components therefor;
  3. Sending, receiving or storing information (except in support of entertainment, mass commercial broadcasts, digital rights management or medical records management); or
  4. Networking (includes operation, administration, management and provisioning); and
- b. The cryptographic functionality is limited to supporting their primary function or set of functions.

<i>Category Code</i>	<i>Item Description</i>
5A2	<b>Systems, Equipment and Components</b>
5A002	<p>“Information security” systems, equipment and components therefor, as follows:</p> <p>a. Systems, equipment, application specific “electronic assemblies”, modules and integrated circuits for “information security”, as follows, and components therefor specially designed for “information security”:</p> <p><u><i>N.B.</i></u></p> <p><i>For Global Navigation Satellite Systems (GNSS) receiving equipment containing or employing decryption, see Category Code 7A005 and for related decryption “software” and “technology”, see Category Codes 7D005 and 7E001.</i></p> <p>1. Designed or modified to use “cryptography” employing digital techniques performing any cryptographic function other than authentication, digital signature or the execution of copy-protected “software”, and having any of the following:</p> <p><u><i>Technical Notes</i></u></p> <p>1. <i>Functions for authentication, digital signature and the execution of copy-protected “software” include their associated key management function.</i></p> <p>2. <i>Authentication includes all aspects of access control where there is no encryption of files or text except as directly related to the protection of passwords, Personal Identification Numbers (PINs) or similar data to prevent unauthorised access.</i></p> <p>a. A “symmetric algorithm” employing a key length in excess of 56 bits; <u>or</u></p> <p><u><i>Technical Note</i></u></p> <p><i>In Category 5 – Part 2, parity bits are not included in the key length.</i></p> <p>b. An “asymmetric algorithm” where the security of the algorithm is based on any of the following:</p>

<i>Category Code</i>	<i>Item Description</i>
	<ol style="list-style-type: none"> <li>1. Factorisation of integers in excess of 512 bits (e.g. RSA);</li> <li>2. Computation of discrete logarithms in a multiplicative group of a finite field of size greater than 512 bits (e.g. Diffie-Hellman over <math>Z/pZ</math>); <u>or</u></li> <li>3. Discrete logarithms in a group other than mentioned in Category Code 5A002.a.1.b.2. in excess of 112 bits (e.g. Diffie-Hellman over an elliptic curve);</li> </ol> <p>2. Designed or modified to perform cryptanalytic functions;</p> <p><i>Note</i>  <i>Category Code 5A002.a.2. includes systems or equipment, designed or modified to perform cryptanalysis by means of reverse engineering.</i></p> <ol style="list-style-type: none"> <li>3. Not used;</li> <li>4. Specially designed or modified to reduce the compromising emanations of information-bearing signals beyond what is necessary for health, safety or electromagnetic interference standards;</li> <li>5. Designed or modified to use cryptographic techniques to generate the spreading code for “spread spectrum” systems, other than those specified in Category Code 5A002.a.6., including the hopping code for “frequency hopping” systems;</li> <li>6. Designed or modified to use cryptographic techniques to generate channelising codes, scrambling codes or network identification codes, for systems using ultra-wideband modulation techniques and having any of the following: <ol style="list-style-type: none"> <li>a. A bandwidth exceeding 500 MHz; <u>or</u></li> <li>b. A “fractional bandwidth” of 20% or more;</li> </ol> </li> </ol>



<i>Category Code</i>	<i>Item Description</i>
	<p data-bbox="544 454 1267 618">7. Non-cryptographic information and communications technology (ICT) security systems and devices that have been evaluated and certified by a national authority to exceed class EAL-6 (evaluation assurance level) of the Common Criteria (CC) or equivalent;</p> <p data-bbox="544 640 1267 734">8. Communications cable systems designed or modified using mechanical, electrical or electronic means to detect surreptitious intrusion;</p> <p data-bbox="604 757 667 786"><u>Note</u></p> <p data-bbox="604 797 1267 864"><i>Category Code 5A002.a.8. applies only to physical layer security.</i></p> <p data-bbox="544 887 1267 954">9. Designed or modified to use or perform “quantum cryptography”;</p> <p data-bbox="604 965 788 994"><u>Technical Note</u></p> <p data-bbox="604 1005 1267 1072"><i>“Quantum cryptography” is also known as Quantum Key Distribution (QKD).</i></p> <p data-bbox="480 1095 1267 1290">b. Systems, equipment, application specific “electronic assemblies”, modules and integrated circuits, designed or modified to enable an item to achieve or exceed the controlled performance levels for functionality specified by Category Code 5A002.a. that would not otherwise be enabled.</p> <p data-bbox="480 1312 539 1341"><u>Note</u></p> <p data-bbox="480 1352 1198 1382"><i>Category Code 5A002 does not include any of the following:</i></p> <p data-bbox="480 1404 1222 1433">a. <i>Smart cards and smart card ‘readers/writers’ as follows:</i></p> <p data-bbox="544 1456 1267 1550">1. <i>A smart card or an electronically readable personal document (e.g. token coin, e-passport) that meets any of the following:</i></p> <p data-bbox="628 1572 1267 1769">a. <i>The cryptographic capability is restricted for use in equipment or systems excluded from Category Code 5A002 by Note 4 in Category 5 – Part 2 or entries d. to i. of this Note, and cannot be reprogrammed for any other use; <u>or</u></i></p> <p data-bbox="628 1792 1023 1821">b. <i>Having all of the following:</i></p>

Category Code	Item Description
	<p>1. It is specially designed and limited to allow protection of 'personal data' stored within;</p> <p>2. Has been, or can only be, personalised for public or commercial transactions or individual identification; <u>and</u></p> <p>3. Where the cryptographic capability is not user accessible;</p> <p><u>Technical Note</u> 'Personal data' includes any data specific to a particular person or entity, such as the amount of money stored and data necessary for authentication.</p> <p>2. 'Readers/writers' specially designed or modified, and limited, for items specified in a.1. of this Note;</p> <p><u>Technical Note</u> 'Readers/writers' include equipment that communicates with smart cards or electronically readable documents through a network.</p> <p>b. Not used;</p> <p>c. Not used;</p> <p>d. Cryptographic equipment specially designed and limited for banking use or 'money transactions';</p> <p><u>Technical Note</u> 'Money transactions' in Category Code 5A002 Note d. includes the collection and settlement of fares or credit functions.</p> <p>e. Portable or mobile radiotelephones for civil use (e.g. for use with commercial civil cellular radio communication systems) that are not capable of transmitting encrypted data directly to another radiotelephone or equipment (other than Radio Access Network (RAN) equipment), nor of passing encrypted data through RAN equipment (e.g. Radio Network Controller (RNC) or Base Station Controller (BSC));</p>

Category Code	Item Description
	<p>f. Cordless telephone equipment not capable of end-to-end encryption where the maximum effective range of unboosted cordless operation (i.e. a single, unrelayed hop between terminal and home base station) is less than 400 metres according to the manufacturer's specifications;</p> <p>g. Portable or mobile radiotelephones and similar client wireless devices for civil use, that implement only published or commercial cryptographic standards (except for anti-piracy functions, which may be non-published) and also meet the provisions of paragraphs a.2. and a.3. of the Cryptography Note (Note 3 in Category 5 – Part 2), that have been customised for a specific civil industry application with features that do not affect the cryptographic functionality of these original non-customised devices;</p> <p>h. Not used;</p> <p>i. Wireless “personal area network” equipment that implement only published or commercial cryptographic standards and where the cryptographic capability is limited to a nominal operating range not exceeding 30 metres according to the manufacturer's specifications, or not exceeding 100 metres according to the manufacturer's specifications for equipment that cannot interconnect with more than seven devices;</p> <p>j. Equipment, having no functionality specified by Category Code 5A002.a.2., 5A002.a.4., 5A002.a.7., or 5A002.a.8., where all cryptographic capability specified by Category Code 5A002.a. meets any of the following:</p> <ol style="list-style-type: none"> <li>1. It cannot be used; <u>or</u></li> <li>2. It can only be made useable by means of “cryptographic activation”;</li> </ol> <p><u>N.B.</u> See Category Code 5A002.a. for equipment that has undergone “cryptographic activation”.</p>

Category Code	Item Description
	<ul style="list-style-type: none"> <li>k. <i>Mobile telecommunications Radio Access Network (RAN) equipment designed for civil use, which also meet the provisions of paragraphs a.2. and a.3. of the Cryptography Note (Note 3 in Category 5 – Part 2), having an RF output power limited to 0.1W (20 dBm) or less, and supporting 16 or fewer concurrent users;</i></li> <li>l. <i>Routers, switches or relays, where the “information security” functionality is limited to the tasks of “Operations, Administration or Maintenance” (“OAM”) implementing only published or commercial cryptographic standards; <u>or</u></i></li> <li>m. <i>General purpose computing equipment or servers, where the “information security” functionality meets all of the following:</i> <ul style="list-style-type: none"> <li>1. <i>Uses only published or commercial cryptographic standards; <u>and</u></i></li> <li>2. <i>Is any of the following:</i> <ul style="list-style-type: none"> <li>a. <i>Integral to a CPU that meets the provisions of Note 3 to Category 5 – Part 2;</i></li> <li>b. <i>Integral to an operating system that is not specified by Category Code 5D002; <u>or</u></i></li> <li>c. <i>Limited to “OAM” of the equipment.</i></li> </ul> </li> </ul> </li> </ul>
<b>5B2</b>	<b>Test, Inspection and Production Equipment</b>
5B002	<p>“Information security” test, inspection and “production” equipment, as follows:</p> <ul style="list-style-type: none"> <li>a. <i>Equipment specially designed for the “development” or “production” of equipment specified in Category Code 5A002 or 5B002.b.;</i></li> <li>b. <i>Measuring equipment specially designed to evaluate and validate the “information security” functions of the equipment specified in Category Code 5A002 or “software” specified in Category Code 5D002.a. or 5D002.c.</i></li> </ul>

<i>Category Code</i>	<i>Item Description</i>
<b>5C2</b>	<p><b>Materials</b></p> <p>None.</p>
<p><b>5D2</b></p> <p>5D002</p>	<p><b>Software</b></p> <p>“Software” as follows:</p> <ol style="list-style-type: none"> <li>a. “Software” specially designed or modified for the “development”, “production” or “use” of equipment specified in Category Code 5A002 or “software” specified in Category Code 5D002.c.;</li> <li>b. “Software” specially designed or modified to support “technology” specified in Category Code 5E002;</li> <li>c. Specific “software”, as follows: <ol style="list-style-type: none"> <li>1. “Software” having the characteristics, or performing or simulating the functions of the equipment specified in Category Code 5A002;</li> <li>2. “Software” to certify “software” specified in Category Code 5D002.c.1.;</li> </ol> <p><i>Note</i></p> <p><i>Category Code 5D002.c. does not apply to “software” limited to the tasks of “OAM” implementing only published or commercial cryptographic standards.</i></p> </li> <li>d. “Software” designed or modified to enable an item to achieve or exceed the controlled performance levels for functionality specified by Category Code 5A002.a. that would not otherwise be enabled.</li> </ol>
<p><b>5E2</b></p> <p>5E002</p>	<p><b>Technology</b></p> <p>“Technology” as follows:</p> <ol style="list-style-type: none"> <li>a. “Technology” (according to the General Technology Note) for the “development”, “production” or “use” of equipment specified in Category Code 5A002, 5B002 or “software” specified in Category Code 5D002.a. or 5D002.c.;</li> </ol>

<i>Category Code</i>	<i>Item Description</i>
	<p>b. “Technology” to enable an item to achieve or exceed the controlled performance levels for functionality specified by Category Code 5A002.a. that would not otherwise be enabled.</p> <p><u>Note</u> Category Code 5E002 includes “information security” technical data resulting from procedures carried out to evaluate or determine the implementation of functions, features or techniques specified in Category 5 – Part 2.</p>

<i>Category Code</i>	<i>Item Description</i>
<b>CATEGORY 6 — SENSORS AND LASERS</b>	
<b>6A</b>	<b>Systems, Equipment and Components</b>
6A001	<p>Acoustic systems, equipment and components, as follows:</p> <p>a. Marine acoustic systems, equipment and specially designed components therefor, as follows:</p> <p>1. Active (transmitting or transmitting-and-receiving) systems, equipment and specially designed components therefor, as follows:</p> <p><i>Note</i>  <i>Category Code 6A001.a.1. does not include equipment as follows:</i></p> <p>a. <i>Depth sounders operating vertically below the apparatus, not including a scanning function exceeding <math>\pm 20^\circ</math>, and limited to measuring the depth of water, the distance of submerged or buried objects or fish finding;</i></p> <p>b. <i>Acoustic beacons, as follows:</i></p> <p>1. <i>Acoustic emergency beacons;</i></p> <p>2. <i>Pingers specially designed for relocating or returning to an underwater position.</i></p> <p>a. Acoustic seabed survey equipment as follows:</p> <p>1. Surface vessel survey equipment designed for seabed topographic mapping and having all of the following:</p> <p>a. Designed to take measurements at an angle exceeding <math>20^\circ</math> from the vertical;</p> <p>b. Designed to measure seabed topography at seabed depths exceeding 600 m;</p> <p>c. ‘Sounding resolution’ less than 2; <u>and</u></p> <p>d. ‘Enhancement’ of the depth accuracy through compensation for all of the following:</p>

<i>Category Code</i>	<i>Item Description</i>
	<ol style="list-style-type: none"> <li>1. Motion of the acoustic sensor;</li> <li>2. In-water propagation from sensor to the seabed and back; <u>and</u></li> <li>3. Sound speed at the sensor;</li> </ol> <p><i><u>Technical Notes</u></i></p> <ol style="list-style-type: none"> <li>1. 'Sounding resolution' is the swath width (degrees) divided by the maximum number of soundings per swath.</li> <li>2. 'Enhancement' includes the ability to compensate by external means.</li> </ol> <ol style="list-style-type: none"> <li>2. Underwater survey equipment designed for seabed topographic mapping and having any of the following: <p><i><u>Technical Note</u></i></p> <p><i>The acoustic sensor pressure rating determines the depth rating of the equipment specified in Category Code 6A001.a.1.a.2.</i></p> <ol style="list-style-type: none"> <li>a. Having all of the following: <ol style="list-style-type: none"> <li>1. Designed or modified to operate at depths exceeding 300 m; <u>and</u></li> <li>2. 'Sounding rate' greater than 3,800 m/s; <u>or</u></li> </ol> <p><i><u>Technical Note</u></i></p> <p><i>'Sounding rate' is the product of the maximum speed (m/s) at which the sensor can operate and the maximum number of soundings per swath assuming 100% coverage.</i></p> </li> <li>b. Survey equipment, not specified in Category Code 6A001.a.1.a.2.a., having all of the following:</li> </ol> </li> </ol>



<i>Category Code</i>	<i>Item Description</i>
	<ol style="list-style-type: none"> <li>1. Designed or modified to operate at depths exceeding 100 m;</li> <li>2. Designed to take measurements at an angle exceeding 20° from the vertical;</li> <li>3. Having any of the following: <ol style="list-style-type: none"> <li>a. Operating frequency below 350 kHz; <u>or</u></li> <li>b. Designed to measure seabed topography at a range exceeding 200 m from the acoustic sensor; <u>and</u></li> </ol> </li> <li>4. 'Enhancement' of the depth accuracy through compensation of all of the following: <ol style="list-style-type: none"> <li>a. Motion of the acoustic sensor;</li> <li>b. In-water propagation from sensor to the seabed and back; <u>and</u></li> <li>c. Sound speed at the sensor;</li> </ol> </li> <li>3. Side Scan Sonar (SSS) or Synthetic Aperture Sonar (SAS), designed for seabed imaging and having all of the following: <ol style="list-style-type: none"> <li>a. Designed or modified to operate at depths exceeding 500 m;</li> <li>b. An 'area coverage rate' of greater than 570 m<sup>2</sup>/s while operating at the maximum range that it can operate with an 'along track resolution' of less than 15 cm; <u>and</u></li> </ol> </li> </ol>

<i>Category Code</i>	<i>Item Description</i>
	<p data-bbox="751 454 1257 517">c. An ‘across track resolution’ of less than 15 cm;</p> <p data-bbox="815 539 1010 566"><u>Technical Notes</u></p> <ol data-bbox="815 577 1257 1043" style="list-style-type: none"> <li data-bbox="815 577 1257 745">1. ‘Area coverage rate’ (<math>m^2/s</math>) is twice the product of the sonar range (<math>m</math>) and the maximum speed (<math>m/s</math>) at which the sensor can operate at that range.</li> <li data-bbox="815 763 1257 931">2. ‘Along track resolution’ (<math>cm</math>), for SSS only, is the product of azimuth (horizontal) beamwidth (degrees) and sonar range (<math>m</math>) and 0.873.</li> <li data-bbox="815 949 1257 1043">3. ‘Across track resolution’ (<math>cm</math>) is 75 divided by the signal bandwidth (<math>kHz</math>).</li> </ol> <p data-bbox="628 1066 1257 1162">b. Systems or transmitting and receiving arrays, designed for object detection or location, having any of the following:</p> <ol data-bbox="692 1184 1257 1868" style="list-style-type: none"> <li data-bbox="692 1184 1257 1211">1. A transmitting frequency below 10 kHz;</li> <li data-bbox="692 1234 1257 1357">2. Sound pressure level exceeding 224 dB (reference 1 <math>\mu Pa</math> at 1 m) for equipment with an operating frequency in the band from 10 kHz to 24 kHz inclusive;</li> <li data-bbox="692 1379 1257 1503">3. Sound pressure level exceeding 235 dB (reference 1 <math>\mu Pa</math> at 1 m) for equipment with an operating frequency in the band between 24 kHz and 30 kHz;</li> <li data-bbox="692 1525 1257 1621">4. Forming beams of less than 1° on any axis and having an operating frequency of less than 100 kHz;</li> <li data-bbox="692 1644 1257 1706">5. Designed to operate with an unambiguous display range exceeding 5,120 m; <u>or</u></li> <li data-bbox="692 1729 1257 1868">6. Designed to withstand pressure during normal operation at depths exceeding 1,000 m and having transducers with any of the following:</li> </ol>

<i>Category Code</i>	<i>Item Description</i>
	<p>a. Dynamic compensation for pressure; <u>or</u></p> <p>b. Incorporating other than lead zirconate titanate as the transduction element;</p> <p>c. Acoustic projectors (including transducers), incorporating piezoelectric, magnetostrictive, electrostrictive, electrodynamic or hydraulic elements operating individually or in a designed combination, and having any of the following:</p> <p><u>Note 1</u> <i>Whether acoustic projectors (including transducers), which are not specified by Category Code 6A001 and which are specially designed for other equipment, is included in Category Code 6A001.c. is determined by whether the other equipment is specified in Division 2 of Part II of this Schedule.</i></p> <p><u>Note 2</u> <i>Category Code 6A001.a.1.c. does not include electronic sources which direct the sound vertically only, or mechanical (e.g. air gun or vapour-shock gun) or chemical (e.g. explosive) sources.</i></p> <p><u>Note 3</u> <i>Piezoelectric elements specified in Category Code 6A001.a.1.c. include those made from lead-magnesium-niobate/lead-titanate (<math>Pb(Mg_{1/3}Nb_{2/3})O_3-PbTiO_3</math>, or PMN-PT) single crystals grown from solid solution or lead-indium-niobate/lead-magnesium-niobate/lead-titanate (<math>Pb(In_{1/2}Nb_{1/2})O_3-Pb(Mg_{1/3}Nb_{2/3})O_3-PbTiO_3</math>, or PIN-PMN-PT) single crystals grown from solid solution.</i></p> <p>1. An instantaneous radiated ‘acoustic power density’ exceeding <math>0.01 \text{ mW/mm}^2/\text{Hz}</math> for devices operating at frequencies below 10 kHz;</p>

<i>Category Code</i>	<i>Item Description</i>
	<p data-bbox="692 456 1257 584">2. A continuously radiated ‘acoustic power density’ exceeding <math>0.001 \text{ mW/mm}^2/\text{Hz}</math> for devices operating at frequencies below 10 kHz; <u>or</u></p> <p data-bbox="692 607 874 636"><i>Technical Note</i></p> <p data-bbox="692 651 1257 779"><i>‘Acoustic power density’ is obtained by dividing the output acoustic power by the product of the area of the radiating surface and the frequency of operation.</i></p> <p data-bbox="692 801 1230 831">3. Side-lobe suppression exceeding 22 dB;</p> <p data-bbox="628 853 1257 1010">d. Acoustic systems and equipment, designed to determine the position of surface vessels or underwater vehicles and having all of the following, and specially designed components therefor:</p> <ol data-bbox="692 1032 1257 1182" style="list-style-type: none"> <li>1. Detection range exceeding 1,000 m; <u>and</u></li> <li>2. Positioning accuracy of less than 10 m rms (root mean square) when measured at a range of 1,000 m;</li> </ol> <p data-bbox="692 1205 751 1234"><i>Note</i></p> <p data-bbox="692 1245 1145 1274"><i>Category Code 6A001.a.1.d. includes:</i></p> <ol data-bbox="692 1296 1257 1574" style="list-style-type: none"> <li>a. <i>Equipment using coherent “signal processing” between two or more beacons and the hydrophone unit carried by the surface vessel or underwater vehicle;</i></li> <li>b. <i>Equipment capable of automatically correcting speed-of-sound propagation errors for calculation of a point.</i></li> </ol> <p data-bbox="628 1597 1257 1753">e. Active individual sonars, specially designed or modified to detect, locate and automatically classify swimmers or divers, having all of the following, and specially designed transmitting and receiving acoustic arrays therefor:</p> <ol data-bbox="692 1776 1161 1805" style="list-style-type: none"> <li>1. Detection range exceeding 530 m;</li> </ol>

<i>Category Code</i>	<i>Item Description</i>
	<p data-bbox="692 454 1257 555">2. Positioning accuracy of less than 15 m rms (root mean square) when measured at a range of 530 m; <u>and</u></p> <p data-bbox="692 568 1257 636">3. Transmitted pulse signal bandwidth exceeding 3 kHz;</p> <p data-bbox="692 656 746 685"><u><i>N.B.</i></u></p> <p data-bbox="692 696 1257 797"><i>For diver detection systems specially designed or modified for military use, see Division 2 of Part I of this Schedule.</i></p> <p data-bbox="692 815 751 844"><u><i>Note</i></u></p> <p data-bbox="692 855 1257 987"><i>For Category Code 6A001.a.1.e., where multiple detection ranges are specified for various environments, the greatest detection range is used.</i></p> <p data-bbox="544 1005 1257 1072">2. Passive systems, equipment and specially designed components therefor, as follows:</p> <p data-bbox="628 1090 1193 1120">a. Hydrophones having any of the following:</p> <p data-bbox="692 1140 751 1169"><u><i>Note</i></u></p> <p data-bbox="692 1180 1257 1346"><i>Whether hydrophones specially designed for other equipment is included in Category Code 6A001.a.2.a. is determined by whether the other equipment is included in that Category Code.</i></p> <p data-bbox="692 1364 874 1393"><u><i>Technical Note</i></u></p> <p data-bbox="692 1404 1257 1536"><i>Hydrophones consist of one or more sensing elements producing a single acoustic output channel. Those that contain multiple elements can be referred to as a hydrophone group.</i></p> <p data-bbox="692 1556 1257 1624">1. Incorporating continuous flexible sensing elements;</p> <p data-bbox="692 1641 1257 1807">2. Incorporating flexible assemblies of discrete sensing elements with either a diameter or length less than 20 mm and with a separation between elements of less than 20 mm;</p> <p data-bbox="692 1825 1257 1892">3. Having any of the following sensing elements:</p>

<i>Category Code</i>	<i>Item Description</i>
	<p>a. Optical fibres;</p> <p>b. 'Piezoelectric polymer films' other than polyvinylidene-fluoride (PVDF) and its co-polymers {P(VDF-TrFE) and P(VDF-TFE)};</p> <p>c. 'Flexible piezoelectric composites';</p> <p>d. Lead-magnesium-niobate/lead-titanate (i.e. <math>\text{Pb}(\text{Mg}_{1/3}\text{Nb}_{2/3})\text{O}_3</math>-<math>\text{PbTiO}_3</math>, or PMN-PT) piezoelectric single crystals grown from solid solution; <u>or</u></p> <p>e. Lead-indium-niobate/lead-magnesium niobate/lead-titanate (i.e. <math>\text{Pb}(\text{In}_{1/2}\text{Nb}_{1/2})\text{O}_3</math>-<math>\text{Pb}(\text{Mg}_{1/3}\text{Nb}_{2/3})\text{O}_3</math>-<math>\text{PbTiO}_3</math>, or PIN-PMN-PT) piezoelectric single crystals grown from solid solution;</p> <p>4. A 'hydrophone sensitivity' better than -180 dB at any depth with no acceleration compensation;</p> <p>5. Designed to operate at depths exceeding 35 m with acceleration compensation; <u>or</u></p> <p>6. Designed for operation at depths exceeding 1,000 m;</p> <p><u>Technical Notes</u></p> <p>1. 'Piezoelectric polymer film' sensing elements consist of polarised polymer film that is stretched over and attached to a supporting frame or spool (mandrel).</p> <p>2. 'Flexible piezoelectric composite' sensing elements consist of piezoelectric ceramic particles or fibres combined with an electrically insulating, acoustically transparent rubber, polymer or epoxy compound, where the compound is an integral part of the sensing elements.</p>

Category Code	Item Description
	<p data-bbox="692 454 1267 891">3. 'Hydrophone sensitivity' is defined as twenty times the logarithm to the base 10 of the ratio of rms output voltage to a 1 V rms reference, when the hydrophone sensor, without a pre-amplifier, is placed in a plane wave acoustic field with an rms pressure of 1 <math>\mu</math>Pa. For example, a hydrophone of -160 dB (reference 1 V per <math>\mu</math>Pa) would yield an output voltage of <math>10^{-8}</math> V in such a field, while one of -180 dB sensitivity would yield only <math>10^{-9}</math> V output. Thus, -160 dB is better than -180 dB.</p> <p data-bbox="628 909 1267 972">b. Towed acoustic hydrophone arrays having any of the following:</p> <p data-bbox="692 990 874 1021"><u>Technical Note</u></p> <p data-bbox="692 1034 1267 1128"><i>Hydrophone arrays consist of a number of hydrophones providing multiple acoustic output channels.</i></p> <ol data-bbox="692 1146 1267 1361" style="list-style-type: none"> <li>1. Hydrophone group spacing of less than 12.5 m or 'able to be modified' to have hydrophone group spacing of less than 12.5 m;</li> <li>2. Designed or 'able to be modified' to operate at depths exceeding 35 m;</li> </ol> <p data-bbox="756 1384 938 1415"><u>Technical Note</u></p> <p data-bbox="756 1429 1267 1827"><i>'Able to be modified' in Category Codes 6A001.a.2.b.1. and 2. means having provisions to allow a change of the wiring or interconnections to alter hydrophone group spacing or operating depth limits. These provisions are: spare wiring exceeding 10% of the number of wires, hydrophone group spacing adjustment blocks or internal depth limiting devices that are adjustable or that control more than one hydrophone group.</i></p>

<i>Category Code</i>	<i>Item Description</i>
	<ol style="list-style-type: none"> <li>3. Heading sensors specified in Category Code 6A001.a.2.d.;</li> <li>4. Longitudinally reinforced array hoses;</li> <li>5. An assembled array of less than 40 mm in diameter;</li> <li>6. Not used;</li> <li>7. Hydrophone characteristics specified in Category Code 6A001.a.2.a.; <u>or</u></li> <li>8. Accelerometer-based hydro-acoustic sensors specified in Category Code 6A001.a.2.g.;</li> </ol> <p>c. Processing equipment, specially designed for towed acoustic hydrophone arrays, having “user accessible programmability” and time or frequency domain processing and correlation, including spectral analysis, digital filtering and beamforming using Fast Fourier or other transforms or processes;</p> <p>d. Heading sensors having all of the following:</p> <ol style="list-style-type: none"> <li>1. An accuracy of better than <math>\pm 0.5^\circ</math>; <u>and</u></li> <li>2. Designed to operate at depths exceeding 35 m or having an adjustable or removable depth sensing device in order to operate at depths exceeding 35 m;</li> </ol> <p>e. Bottom or bay-cable hydrophone arrays, having any of the following:</p> <ol style="list-style-type: none"> <li>1. Incorporating hydrophones specified in Category Code 6A001.a.2.a.;</li> <li>2. Incorporating multiplexed hydrophone group signal modules having all of the following characteristics: <ol style="list-style-type: none"> <li>a. Designed to operate at depths exceeding 35 m or having an adjustable or removable depth sensing device in order to operate at depths exceeding 35 m; <u>and</u></li> </ol> </li> </ol>



<i>Category Code</i>	<i>Item Description</i>
	<p>b. Capable of being operationally interchanged with towed acoustic hydrophone array modules; <u>or</u></p> <p>3. Incorporating accelerometer-based hydro-acoustic sensors specified in Category Code 6A001.a.2.g.;</p> <p>f. Processing equipment, specially designed for bottom or bay cable systems, having “user accessible programmability” and time or frequency domain processing and correlation, including spectral analysis, digital filtering and beamforming using Fast Fourier or other transforms or processes;</p> <p>g. Accelerometer-based hydro-acoustic sensors having all of the following:</p> <ol style="list-style-type: none"> <li>1. Composed of three accelerometers arranged along three distinct axes;</li> <li>2. Having an overall ‘acceleration sensitivity’ better than 48 dB (reference 1,000 mV rms per 1 g);</li> <li>3. Designed to operate at depths greater than 35 m; <u>and</u></li> <li>4. Operating frequency below 20 kHz.</li> </ol> <p><u>Note</u> Category Code 6A001.a.2.g. does not include particle velocity sensors or geophones.</p> <p><u>Technical Notes</u></p> <ol style="list-style-type: none"> <li>1. Accelerometer-based hydro-acoustic sensors are also known as vector sensors.</li> <li>2. ‘Acceleration sensitivity’ is defined as twenty times the logarithm to the base 10 of the ratio of rms output voltage to a 1 V rms reference, when the hydro-acoustic sensor, without a preamplifier, is placed in a plane wave acoustic field with an rms acceleration of 1 g (i.e. 9.81 m/s<sup>2</sup>).</li> </ol>

<i>Category Code</i>	<i>Item Description</i>
	<p><u>Note</u>  <i>Category Code 6A001.a.2. also includes receiving equipment, whether or not related in normal application to separate active equipment, and specially designed components therefor.</i></p> <p>b. Correlation-velocity and Doppler-velocity sonar log equipment, designed to measure the horizontal speed of the equipment carrier relative to the seabed, as follows:</p> <ol style="list-style-type: none"> <li>1. Correlation-velocity sonar log equipment having any of the following characteristics: <ol style="list-style-type: none"> <li>a. Designed to operate at distances between the carrier and the seabed exceeding 500 m; <u>or</u></li> <li>b. Having speed accuracy better than 1% of speed;</li> </ol> </li> <li>2. Doppler-velocity sonar log equipment having speed accuracy better than 1% of speed.</li> </ol> <p><u>Note 1</u>  <i>Category Code 6A001.b. does not include depth sounders limited to any of the following:</i></p> <ol style="list-style-type: none"> <li>a. <i>Measuring the depth of water;</i></li> <li>b. <i>Measuring the distance of submerged or buried objects; <u>or</u></i></li> <li>c. <i>Fish finding.</i></li> </ol> <p><u>Note 2</u>  <i>Category Code 6A001.b. does not include equipment specially designed for installation on surface vessels.</i></p> <p>c. Not used.</p>
6A002	<p>Optical sensors or equipment and components therefor, as follows:</p> <p><u>N.B.</u>  <i>See also Category Code 6A102.</i></p> <ol style="list-style-type: none"> <li>a. Optical detectors as follows: <ol style="list-style-type: none"> <li>1. “Space-qualified” solid-state detectors as follows:</li> </ol> </li> </ol>

<i>Category Code</i>	<i>Item Description</i>
	<p data-bbox="603 456 663 488"><u>Note</u></p> <p data-bbox="603 497 1257 562"><i>For the purpose of Category Code 6A002.a.1., solid-state detectors include “focal plane arrays”.</i></p> <ol style="list-style-type: none"> <li data-bbox="627 577 1257 880">a. “Space-qualified” solid-state detectors having all of the following: <ol style="list-style-type: none"> <li data-bbox="691 663 1257 763">1. A peak response in the wavelength range exceeding 10 nm but not exceeding 300 nm; <u>and</u></li> <li data-bbox="691 779 1257 880">2. A response of less than 0.1% relative to the peak response at a wavelength exceeding 400 nm;</li> </ol> </li> <li data-bbox="627 896 1257 1160">b. “Space-qualified” solid-state detectors having all of the following: <ol style="list-style-type: none"> <li data-bbox="691 981 1257 1081">1. A peak response in the wavelength range exceeding 900 nm but not exceeding 1,200 nm; <u>and</u></li> <li data-bbox="691 1097 1257 1160">2. A response “time constant” of 95 ns or less;</li> </ol> </li> <li data-bbox="627 1176 1257 1312">c. “Space-qualified” solid-state detectors having a peak response in the wavelength range exceeding 1,200 nm but not exceeding 30,000 nm;</li> <li data-bbox="627 1328 1257 1464">d. “Space-qualified” “focal plane arrays” having more than 2,048 elements per array and having a peak response in the wavelength range exceeding 300 nm but not exceeding 900 nm;</li> </ol> <p data-bbox="539 1480 1257 1545">2. Image intensifier tubes and specially designed components therefor, as follows:</p> <p data-bbox="603 1561 663 1592"><u>Note</u></p> <p data-bbox="603 1601 1257 1738"><i>Category Code 6A002.a.2. does not include non-imaging photomultiplier tubes having an electron sensing device in the vacuum space limited solely to any of the following:</i></p> <ol style="list-style-type: none"> <li data-bbox="627 1753 986 1785">a. <i>A single metal anode; <u>or</u></i></li> <li data-bbox="627 1800 1257 1865">b. <i>Metal anodes with a centre to centre spacing greater than 500 <math>\mu\text{m}</math>.</i></li> </ol>

Category Code	Item Description
	<p data-bbox="603 454 788 488"><u>Technical Note</u></p> <p data-bbox="603 499 1267 696"><i>‘Charge multiplication’ is a form of electronic image amplification and is defined as the generation of charge carriers as a result of an impact ionisation gain process. ‘Charge multiplication’ sensors may take the form of an image intensifier tube, solid state detector or “focal plane array”.</i></p> <p data-bbox="627 712 1267 779">a. Image intensifier tubes having all of the following:</p> <ol data-bbox="691 795 1267 1682" style="list-style-type: none"> <li data-bbox="691 795 1267 898">1. A peak response in the wavelength range exceeding 400 nm but not exceeding 1,050 nm;</li> <li data-bbox="691 913 1267 1317">2. Electron image amplification using any of the following: <ol data-bbox="754 996 1267 1317" style="list-style-type: none"> <li data-bbox="754 996 1267 1099">a. A microchannel plate with a hole pitch (centre-to-centre spacing) of 12 µm or less; <u>or</u></li> <li data-bbox="754 1115 1267 1317">b. An electron sensing device with a non-binned pixel pitch of 500 µm or less, specially designed or modified to achieve ‘charge multiplication’ other than by a microchannel plate; <u>and</u></li> </ol> </li> <li data-bbox="691 1332 1267 1682">3. Any of the following photocathodes: <ol data-bbox="754 1384 1267 1682" style="list-style-type: none"> <li data-bbox="754 1384 1267 1487">a. Multialkali photocathodes (e.g. S-20 and S-25) having a luminous sensitivity exceeding 350 µA/lm;</li> <li data-bbox="754 1503 1267 1536">b. GaAs or GaInAs photocathodes; <u>or</u></li> <li data-bbox="754 1552 1267 1682">c. Other “III/V compound” semiconductor photocathodes having a maximum “radiant sensitivity” exceeding 10 mA/W;</li> </ol> </li> </ol> <p data-bbox="627 1697 1267 1765">b. Image intensifier tubes having all of the following:</p> <ol data-bbox="691 1780 1267 1883" style="list-style-type: none"> <li data-bbox="691 1780 1267 1883">1. A peak response in the wavelength range exceeding 1,050 nm but not exceeding 1,800 nm;</li> </ol>

<i>Category Code</i>	<i>Item Description</i>
	<p data-bbox="692 454 1267 521">2. Electron image amplification using any of the following:</p> <p data-bbox="756 539 1267 640">a. A microchannel plate with a hole pitch (centre-to-centre spacing) of 12 <math>\mu\text{m}</math> or less; <u>or</u></p> <p data-bbox="756 658 1267 853">b. An electron sensing device with a non-binned pixel pitch of 500 <math>\mu\text{m}</math> or less, specially designed or modified to achieve ‘charge multiplication’ other than by a microchannel plate; <u>and</u></p> <p data-bbox="692 875 1267 1037">3. “III/V compound” semiconductor (e.g. GaAs or GaInAs) photocathodes and transferred electron photocathodes, having a maximum “radiant sensitivity” exceeding 15 mA/W;</p> <p data-bbox="628 1059 1267 1093">c. Specially designed components as follows:</p> <p data-bbox="692 1111 1267 1200">1. Microchannel plates having a hole pitch (centre-to-centre spacing) of 12 <math>\mu\text{m}</math> or less;</p> <p data-bbox="692 1223 1267 1391">2. An electron sensing device with a non-binned pixel pitch of 500 <math>\mu\text{m}</math> or less, specially designed or modified to achieve ‘charge multiplication’ other than by a microchannel plate;</p> <p data-bbox="692 1413 1267 1503">3. “III/V compound” semiconductor (e.g. GaAs or GaInAs) photocathodes and transferred electron photocathodes;</p> <p data-bbox="756 1525 820 1559"><u>Note</u></p> <p data-bbox="756 1570 1267 1738"><i>Category Code 6A002.a.2.c.3. does not include compound semiconductor photocathodes designed to achieve a maximum “radiant sensitivity” of any of the following:</i></p> <p data-bbox="756 1760 1267 1886">a. <i>10 mA/W or less at the peak response in the wavelength range exceeding 400 nm but not exceeding 1,050 nm; <u>or</u></i></p>

Category Code	Item Description
	<p data-bbox="758 454 1267 589">b. 15 mA/W or less at the peak response in the wavelength range exceeding 1,050 nm but not exceeding 1,800 nm.</p> <p data-bbox="544 607 1267 640">3. Non-“space-qualified” “focal plane arrays” as follows:</p> <p data-bbox="604 658 660 692"><u>N.B.</u></p> <p data-bbox="604 696 1267 797">‘Microbolometer’ non-“space-qualified” “focal plane arrays” are only specified in Category Code 6A002.a.3.f.</p> <p data-bbox="604 815 788 848"><u>Technical Note</u></p> <p data-bbox="604 853 1267 920">Linear or two-dimensional multi-element detector arrays are referred to as “focal plane arrays”.</p> <p data-bbox="604 938 687 972"><u>Note 1</u></p> <p data-bbox="604 976 1267 1043">Category Code 6A002.a.3. includes photoconductive arrays and photovoltaic arrays.</p> <p data-bbox="604 1061 687 1095"><u>Note 2</u></p> <p data-bbox="604 1099 1139 1133">Category Code 6A002.a.3. does not include:</p> <p data-bbox="628 1151 1267 1252">a. Multi-element (not to exceed 16 elements) encapsulated photoconductive cells using either lead sulphide or lead selenide;</p> <p data-bbox="628 1270 1267 1337">b. Pyroelectric detectors using any of the following:</p> <ol data-bbox="692 1355 1267 1615" style="list-style-type: none"> <li>1. Triglycine sulphate and variants;</li> <li>2. Lead-lanthanum-zirconium titanate and variants;</li> <li>3. Lithium tantalate;</li> <li>4. Polyvinylidene fluoride and variants; <u>or</u></li> <li>5. Strontium barium niobate and variants;</li> </ol> <p data-bbox="628 1632 1267 1836">c. “Focal plane arrays” specially designed or modified to achieve ‘charge multiplication’ and limited by design to have a maximum “radiant sensitivity” of 10 mA/W or less for wavelengths exceeding 760 nm, having all of the following:</p>

<i>Category Code</i>	<i>Item Description</i>
	<ol style="list-style-type: none"> <li>1. <i>Incorporating a response limiting mechanism designed not to be removed or modified; <u>and</u></i></li> <li>2. <i>Any of the following:</i> <ol style="list-style-type: none"> <li>a. <i>The response limiting mechanism is integral to or combined with the detector element; <u>or</u></i></li> <li>b. <i>The “focal plane array” is only operable with the response limiting mechanism in place.</i></li> </ol> </li> </ol> <p><i><u>Technical Note</u></i>  <i>A response limiting mechanism integral to the detector element is designed not to be removed or modified without rendering the detector inoperable.</i></p> <p><i><u>Technical Note</u></i>  <i>‘Charge multiplication’ is a form of electronic image amplification and is defined as the generation of charge carriers as a result of an impact ionisation gain process. ‘Charge multiplication’ sensors may take the form of an image intensifier tube, solid state detector or “focal plane array”.</i></p> <ol style="list-style-type: none"> <li>a. <i>Non-“space-qualified” “focal plane arrays” having all of the following:</i> <ol style="list-style-type: none"> <li>1. <i>Individual elements with a peak response within the wavelength range exceeding 900 nm but not exceeding 1,050 nm; <u>and</u></i></li> <li>2. <i>Any of the following:</i> <ol style="list-style-type: none"> <li>a. <i>A response “time constant” of less than 0.5 ns; <u>or</u></i></li> <li>b. <i>Specially designed or modified to achieve ‘charge multiplication’ and having a maximum “radiant sensitivity” exceeding 10 mA/W;</i></li> </ol> </li> </ol> </li> <li>b. <i>Non-“space-qualified” “focal plane arrays” having all of the following:</i></li> </ol>

<i>Category Code</i>	<i>Item Description</i>
	<ol style="list-style-type: none"> <li>1. Individual elements with a peak response in the wavelength range exceeding 1,050 nm but not exceeding 1,200 nm; <u>and</u></li> <li>2. Any of the following: <ol style="list-style-type: none"> <li>a. A response “time constant” of 95 ns or less; <u>or</u></li> <li>b. Specially designed or modified to achieve ‘charge multiplication’ and having a maximum “radiant sensitivity” exceeding 10 mA/W;</li> </ol> </li> <li>c. Non-“space-qualified” non-linear (2-dimensional) “focal plane arrays” having individual elements with a peak response in the wavelength range exceeding 1,200 nm but not exceeding 30,000 nm; <p><u>N.B.</u>  <i>Silicon and other material based ‘microbolometer’ non-“space-qualified” “focal plane arrays” are only specified in Category Code 6A002.a.3.f.</i></p> </li> <li>d. Non-“space-qualified” linear (1-dimensional) “focal plane arrays” having all of the following: <ol style="list-style-type: none"> <li>1. Individual elements with a peak response in the wavelength range exceeding 1,200 nm but not exceeding 3,000 nm; <u>and</u></li> <li>2. Any of the following: <ol style="list-style-type: none"> <li>a. A ratio of ‘scan direction’ dimension of the detector element to the ‘cross-scan direction’ dimension of the detector element of less than 3.8; <u>or</u></li> <li>b. Signal processing in the detector elements;</li> </ol> </li> </ol> </li> </ol>



Category Code	Item Description
	<p data-bbox="691 454 751 483"><u>Note</u></p> <p data-bbox="691 495 1259 624"><i>Category Code 6A002.a.3.d. does not include “focal plane arrays” (not to exceed 32 elements) having detector elements limited solely to germanium material.</i></p> <p data-bbox="691 645 874 674"><u>Technical Note</u></p> <p data-bbox="691 685 1259 884"><i>For the purpose of Category Code 6A002.a.3.d., ‘cross-scan direction’ is defined as the axis parallel to the linear array of detector elements and the ‘scan direction’ is defined as the axis perpendicular to the linear array of detector elements.</i></p> <p data-bbox="627 904 1259 1070">e. Non-“space-qualified” linear (1-dimensional) “focal plane arrays” having individual elements with a peak response in the wavelength range exceeding 3,000 nm but not exceeding 30,000 nm;</p> <p data-bbox="627 1090 1259 1290">f. Non-“space-qualified” non-linear (2-dimensional) infrared “focal plane arrays” based on ‘microbolometer’ material, having individual elements with an unfiltered response in the wavelength range equal to or exceeding 8,000 nm but not exceeding 14,000 nm;</p> <p data-bbox="691 1310 874 1339"><u>Technical Note</u></p> <p data-bbox="691 1350 1259 1550"><i>For the purpose of Category Code 6A002.a.3.f., ‘microbolometer’ is defined as a thermal imaging detector that, as a result of a temperature change in the detector caused by the absorption of infrared radiation, is used to generate any usable signal.</i></p> <p data-bbox="627 1570 1259 1783">g. Non-“space-qualified” “focal plane arrays” having all of the following:</p> <ol data-bbox="691 1653 1259 1783" style="list-style-type: none"> <li>1. Individual detector elements with a peak response in the wavelength range exceeding 400 nm but not exceeding 900 nm;</li> </ol>

<i>Category Code</i>	<i>Item Description</i>
	<p data-bbox="692 456 1267 622">2. Specially designed or modified to achieve ‘charge multiplication’ and having a maximum “radiant sensitivity” exceeding 10 mA/W for wavelengths exceeding 760 nm; <u>and</u></p> <p data-bbox="692 640 1059 674">3. Greater than 32 elements;</p> <p data-bbox="475 692 1267 790">b. “Monospectral imaging sensors” and “multispectral imaging sensors”, designed for remote sensing applications and having any of the following:</p> <p data-bbox="544 808 1267 875">1. An Instantaneous-Field-Of-View (IFOV) of less than 200 <math>\mu</math>rad (microradians); <u>or</u></p> <p data-bbox="544 893 1267 992">2. Specified for operation in the wavelength range exceeding 400 nm but not exceeding 30,000 nm and having all the following:</p> <p data-bbox="628 1010 1267 1077">a. Providing output imaging data in digital format; <u>and</u></p> <p data-bbox="628 1095 1267 1128">b. Having any of the following characteristics:</p> <p data-bbox="692 1146 1011 1180">1. “Space-qualified”; <u>or</u></p> <p data-bbox="692 1198 1267 1296">2. Designed for airborne operation, using other than silicon detectors, and having an IFOV of less than 2.5 mrad (milliradians);</p> <p data-bbox="544 1314 603 1348"><u>Note</u></p> <p data-bbox="544 1352 1267 1518"><i>Category Code 6A002.b.1. does not include “monospectral imaging sensors” with a peak response in the wavelength range exceeding 300 nm but not exceeding 900 nm and only incorporating any of the following non-“space-qualified” detectors or non-“space-qualified” “focal plane arrays”:</i></p> <p data-bbox="544 1536 1267 1603">a. <i>Charged Coupled Devices (CCD) not designed or modified to achieve ‘charge multiplication’; <u>or</u></i></p> <p data-bbox="544 1621 1267 1720">b. <i>Complementary Metal Oxide Semiconductor (CMOS) devices not designed or modified to achieve ‘charge multiplication’.</i></p> <p data-bbox="475 1738 1267 1805">c. ‘Direct view’ imaging equipment incorporating any of the following:</p> <p data-bbox="544 1823 1267 1890">1. Image intensifier tubes specified in Category Code 6A002.a.2.a. or 6A002.a.2.b.;</p>

<i>Category Code</i>	<i>Item Description</i>
	<ol style="list-style-type: none"> <li data-bbox="544 454 1259 521">2. “Focal plane arrays” specified in Category Code 6A002.a.3.; <u>or</u></li> <li data-bbox="544 539 1259 607">3. Solid state detectors specified in Category Code 6A002.a.1.;</li> </ol> <p data-bbox="544 622 724 651"><i><u>Technical Note</u></i></p> <p data-bbox="544 667 1259 831"><i>‘Direct view’ refers to imaging equipment that presents a visual image to a human observer without converting the image into an electronic signal for television display, and that cannot record or store the image photographically, electronically or by any other means.</i></p> <p data-bbox="544 853 603 882"><i><u>Note</u></i></p> <p data-bbox="544 898 1259 987"><i>Category Code 6A002.c. does not include equipment as follows, when incorporating other than GaAs or GaInAs photocathodes:</i></p> <ol style="list-style-type: none"> <li data-bbox="544 1010 1259 1077"><i>a. Industrial or civilian intrusion alarm, traffic or industrial movement control or counting systems;</i></li> <li data-bbox="544 1099 842 1128"><i>b. Medical equipment;</i></li> <li data-bbox="544 1151 1259 1218"><i>c. Industrial equipment used for inspection, sorting or analysis of the properties of materials;</i></li> <li data-bbox="544 1240 1082 1270"><i>d. Flame detectors for industrial furnaces;</i></li> <li data-bbox="544 1292 1187 1321"><i>e. Equipment specially designed for laboratory use.</i></li> </ol> <ol style="list-style-type: none"> <li data-bbox="480 1330 1259 1870">d. Special support components for optical sensors, as follows: <ol style="list-style-type: none"> <li data-bbox="544 1375 975 1404">1. “Space-qualified” cryocoolers;</li> <li data-bbox="544 1426 1259 1718">2. Non-“space-qualified” cryocoolers having a cooling source temperature below 218 K (-55°C), as follows: <ol style="list-style-type: none"> <li data-bbox="624 1516 1259 1606">a. Closed cycle type with a specified Mean-Time-To-Failure (MTTF) or Mean-Time-Between-Failures (MTBF), exceeding 2,500 hours;</li> <li data-bbox="624 1628 1259 1718">b. Joule-Thomson (JT) self-regulating minicoolers having bore (outside) diameters of less than 8 mm;</li> </ol> </li> <li data-bbox="544 1740 1259 1870">3. Optical sensing fibres specially fabricated either compositionally or structurally, or modified by coating, to be acoustically, thermally, inertially, electromagnetically or nuclear radiation sensitive;</li> </ol> </li> </ol>

Category Code	Item Description
6A003	<p data-bbox="603 456 663 488"><u>Note</u></p> <p data-bbox="603 497 1259 595"><i>Category Code 6A002.d.3. does not include encapsulated optical sensing fibres specially designed for bore hole sensing applications.</i></p> <p data-bbox="475 613 655 645">e. Not used.</p> <p data-bbox="475 712 1259 775">Cameras, systems or equipment, and components therefor, as follows:</p> <p data-bbox="475 792 536 824"><u>N.B.</u></p> <p data-bbox="475 837 855 869"><i>See also Category Code 6A203.</i></p> <p data-bbox="475 887 536 918"><u>N.B.</u></p> <p data-bbox="475 927 1259 1025"><i>For television and film-based photographic still cameras specially designed or modified for underwater use, see Category Codes 8A002.d.1. and 8A002.e.</i></p> <p data-bbox="475 1043 1259 1106">a. Instrumentation cameras and specially designed components therefor, as follows:</p> <p data-bbox="539 1128 600 1160"><u>Note</u></p> <p data-bbox="539 1169 1259 1335"><i>Instrumentation cameras, specified in Category Codes 6A003.a.3. to 6A003.a.5., with modular structures should be evaluated by their maximum capability, using plug-ins available according to the camera manufacturer's specifications.</i></p> <ol data-bbox="539 1352 1259 1518" style="list-style-type: none"> <li data-bbox="539 1352 1259 1518">1. High-speed cinema recording cameras using any film format from 8 mm to 16 mm inclusive, in which the film is continuously advanced throughout the recording period, and that are capable of recording at framing rates exceeding 13,150 frames/s;</li> </ol> <p data-bbox="603 1536 663 1568"><u>Note</u></p> <p data-bbox="603 1576 1259 1639"><i>Category Code 6A003.a.1. does not include cinema recording cameras designed for civil purposes.</i></p> <ol data-bbox="539 1657 1259 1863" style="list-style-type: none"> <li data-bbox="539 1657 1259 1863">2. Mechanical high speed cameras, in which the film does not move, capable of recording at rates exceeding 1,000,000 frames/s for the full framing height of 35 mm film, or at proportionately higher rates for lesser frame heights, or at proportionately lower rates for greater frame heights;</li> </ol>

<i>Category Code</i>	<i>Item Description</i>
	<ol style="list-style-type: none"> <li>3. Mechanical or electronic streak cameras, having writing speeds exceeding 10 mm/<math>\mu</math>s;</li> <li>4. Electronic framing cameras having a speed exceeding 1,000,000 frames/s;</li> <li>5. Electronic cameras having all of the following:               <ol style="list-style-type: none"> <li>a. An electronic shutter speed (gating capability) of less than 1 <math>\mu</math>s per full frame; <u>and</u></li> <li>b. A read out time allowing a framing rate of more than 125 full frames per second;</li> </ol> </li> <li>6. Plug-ins having all of the following characteristics:               <ol style="list-style-type: none"> <li>a. Specially designed for instrumentation cameras which have modular structures and which are specified in Category Code 6A003.a.; <u>and</u></li> <li>b. Enabling these cameras to meet the characteristics specified in Category Code 6A003.a.3., 6A003.a.4. or 6A003.a.5., according to the manufacturer's specifications;</li> </ol> </li> </ol> <p>b. Imaging cameras as follows:</p> <p><u>Note</u>  <i>Category Code 6A003.b. does not include television or video cameras, specially designed for television broadcasting.</i></p> <ol style="list-style-type: none"> <li>1. Video cameras incorporating solid state sensors, having a peak response in the wavelength range exceeding 10 nm, but not exceeding 30,000 nm and having all of the following:               <ol style="list-style-type: none"> <li>a. Having any of the following:                   <ol style="list-style-type: none"> <li>1. More than <math>4 \times 10^6</math> "active pixels" per solid state array for monochrome (black and white) cameras;</li> <li>2. More than <math>4 \times 10^6</math> "active pixels" per solid state array for colour cameras incorporating three solid state arrays; <u>or</u></li> </ol> </li> </ol> </li> </ol>

<i>Category Code</i>	<i>Item Description</i>
	<p data-bbox="692 454 1257 555">3. More than <math>12 \times 10^6</math> “active pixels” for solid state array colour cameras incorporating one solid state array; <u>and</u></p> <p data-bbox="628 573 1034 607">b. Having any of the following:</p> <ol data-bbox="692 622 1257 853" style="list-style-type: none"> <li data-bbox="692 622 1257 689">1. Optical mirrors specified in Category Code 6A004.a.;</li> <li data-bbox="692 707 1257 775">2. Optical control equipment specified in Category Code 6A004.d.; <u>or</u></li> <li data-bbox="692 792 1257 853">3. The capability for annotating internally generated ‘camera tracking data’;</li> </ol> <p data-bbox="608 875 799 909"><u>Technical Notes</u></p> <ol data-bbox="628 925 1257 1339" style="list-style-type: none"> <li data-bbox="628 925 1257 1055">1. For the purpose of this entry, digital video cameras should be evaluated by the maximum number of “active pixels” used for capturing moving images.</li> <li data-bbox="628 1072 1257 1339">2. For the purpose of this entry, ‘camera tracking data’ is the information necessary to define camera line of sight orientation with respect to the earth. This includes: 1) the horizontal angle the camera line of sight makes with respect to the earth’s magnetic field direction; and 2) the vertical angle between the camera line of sight and the earth’s horizon.</li> </ol> <p data-bbox="544 1357 1257 1424">2. Scanning cameras and scanning camera systems, having all of the following:</p> <ol data-bbox="628 1442 1257 1675" style="list-style-type: none"> <li data-bbox="628 1442 1257 1541">a. A peak response in the wavelength range exceeding 10 nm, but not exceeding 30,000 nm;</li> <li data-bbox="628 1559 1257 1626">b. Linear detector arrays with more than 8,192 elements per array; <u>and</u></li> <li data-bbox="628 1644 1145 1675">c. Mechanical scanning in one direction;</li> </ol> <p data-bbox="608 1693 667 1727"><u>Note</u></p> <p data-bbox="608 1738 1257 1827"><i>Category Code 6A003.b.2. does not include scanning cameras and scanning camera systems, specially designed for any of the following:</i></p> <ol data-bbox="628 1845 1114 1879" style="list-style-type: none"> <li data-bbox="628 1845 1114 1879">a. <i>Industrial or civilian photocopiers;</i></li> </ol>

<i>Category Code</i>	<i>Item Description</i>
	<p data-bbox="628 454 1259 622">b. <i>Image scanners specially designed for civil, stationary, close proximity scanning applications (e.g. reproduction of images or print contained in documents, artwork or photographs); <u>or</u></i></p> <p data-bbox="628 640 927 674">c. <i>Medical equipment.</i></p> <p data-bbox="544 689 1259 786">3. <i>Imaging cameras incorporating image intensifier tubes specified in Category Code 6A002.a.2.a. or 6A002.a.2.b.;</i></p> <p data-bbox="544 804 1259 1122">4. <i>Imaging cameras incorporating “focal plane arrays” having any of the following:</i></p> <p data-bbox="628 891 1259 958">a. <i>Incorporating “focal plane arrays” specified in Category Codes 6A002.a.3.a. to 6A002.a.3.e.;</i></p> <p data-bbox="628 976 1259 1043">b. <i>Incorporating “focal plane arrays” specified in Category Code 6A002.a.3.f.; <u>or</u></i></p> <p data-bbox="628 1061 1259 1128">c. <i>Incorporating “focal plane arrays” specified in Category Code 6A002.a.3.g.;</i></p> <p data-bbox="604 1144 687 1178"><u><i>Note 1</i></u></p> <p data-bbox="604 1182 1259 1384"><i>Imaging cameras specified in Category Code 6A003.b.4. include “focal plane arrays” combined with sufficient “signal processing” electronics, beyond the read out integrated circuit, to enable as a minimum the output of an analogue or digital signal once power is supplied.</i></p> <p data-bbox="604 1402 687 1435"><u><i>Note 2</i></u></p> <p data-bbox="604 1440 1259 1608"><i>Category Code 6A003.b.4.a. does not include imaging cameras incorporating linear “focal plane arrays” with 12 elements or fewer, not employing time-delay-and-integration within the element and designed for any of the following:</i></p> <p data-bbox="628 1626 1259 1727">a. <i>Industrial or civilian intrusion alarm, traffic or industrial movement control or counting systems;</i></p> <p data-bbox="628 1744 1259 1845">b. <i>Industrial equipment used for inspection or monitoring of heat flows in buildings, equipment or industrial processes;</i></p>

Category Code	Item Description
	<p data-bbox="628 456 1268 555">c. Industrial equipment used for inspection, sorting or analysis of the properties of materials;</p> <p data-bbox="628 568 1268 645">d. Equipment specially designed for laboratory use; <u>or</u></p> <p data-bbox="628 658 927 689">e. Medical equipment.</p> <p data-bbox="604 703 687 734"><u>Note 3</u></p> <p data-bbox="604 748 1268 824">Category Code 6A003.b.4.b. does not include imaging cameras having any of the following:</p> <p data-bbox="628 837 1268 913">a. A maximum frame rate equal to or less than 9 Hz;</p> <p data-bbox="628 927 1023 958">b. Having all of the following:</p> <ol data-bbox="692 972 1268 1563" style="list-style-type: none"> <li data-bbox="692 972 1268 1115">1. Having a minimum horizontal or vertical 'Instantaneous-Field-of-View (IFOV)' of at least 10 mrad/pixel (milliradians/pixel);</li> <li data-bbox="692 1128 1268 1182">2. Incorporating a fixed focal-length lens that is not designed to be removed;</li> <li data-bbox="692 1196 1268 1272">3. Not incorporating a 'direct view' display; <u>and</u></li> <li data-bbox="692 1285 1268 1563">4. Having any of the following: <ol data-bbox="756 1330 1268 1563" style="list-style-type: none"> <li data-bbox="756 1330 1268 1451">a. No facility to obtain a viewable image of the detected field-of-view; <u>or</u></li> <li data-bbox="756 1464 1268 1563">b. The camera is designed for a single kind of application and designed not to be user modified; <u>or</u></li> </ol> </li> </ol> <p data-bbox="628 1576 1268 1697">c. The camera is specially designed for installation into a civilian passenger land vehicle of less than 3 tonnes (gross vehicle weight) and having all of the following:</p> <ol data-bbox="692 1711 1268 1863" style="list-style-type: none"> <li data-bbox="692 1711 1268 1809">1. Is only operable when installed in any of the following: <ol data-bbox="756 1800 1268 1863" style="list-style-type: none"> <li data-bbox="756 1800 1268 1863">a. The civilian passenger land vehicle for which it was intended; <u>or</u></li> </ol> </li> </ol>



Category Code	Item Description
	<p data-bbox="754 454 1259 521">b. A specially designed, authorised maintenance test facility; <u>and</u></p> <p data-bbox="691 539 1259 667">2. Incorporates an active mechanism that forces the camera not to function when it is removed from the vehicle for which it was intended.</p> <p data-bbox="691 689 884 719"><u>Technical Notes</u></p> <p data-bbox="691 739 1259 902">1. ‘Instantaneous-Field-of-View (IFOV)’ specified in Category Code 6A003.b.4. Note 3.b. is the lesser figure of the ‘Horizontal IFOV’ or the ‘Vertical IFOV’.</p> <p data-bbox="746 925 1259 1021">‘Horizontal IFOV’ = horizontal Field of View (FOV) / number of horizontal detector elements</p> <p data-bbox="746 1043 1259 1140">‘Vertical IFOV’ = vertical Field of View (FOV) / number of vertical detector elements</p> <p data-bbox="691 1162 1259 1391">2. ‘Direct view’ in Category Code 6A003.b.4. Note 3.b. refers to an imaging camera operating in the infrared spectrum that presents a visual image to a human observer using a near-to-eye micro display incorporating any light-security mechanism.</p> <p data-bbox="608 1413 687 1442"><u>Note 4</u></p> <p data-bbox="608 1458 1259 1518">Category Code 6A003.b.4.c. does not include imaging cameras having any of the following:</p> <p data-bbox="627 1541 1018 1570">a. Having all of the following:</p> <p data-bbox="691 1592 1259 1783">1. Where the camera is specially designed for installation as an integrated component into indoor and wall-plug-operated systems or equipment, limited by design for a single kind of application, as follows:</p>

<i>Category Code</i>	<i>Item Description</i>
	<ul style="list-style-type: none"> <li>a. <i>Industrial process monitoring, quality control, or analysis of the properties of materials;</i></li> <li>b. <i>Laboratory equipment specially designed for scientific research;</i></li> <li>c. <i>Medical equipment;</i></li> <li>d. <i>Financial fraud detection equipment; <u>and</u></i></li> </ul> <p>2. <i>Is only operable when installed in any of the following:</i></p> <ul style="list-style-type: none"> <li>a. <i>The system(s) or equipment for which it was intended; <u>or</u></i></li> <li>b. <i>A specially designed, authorised maintenance facility; <u>and</u></i></li> </ul> <p>3. <i>Incorporates an active mechanism that forces the camera not to function when it is removed from the system(s) or equipment for which it was intended;</i></p> <ul style="list-style-type: none"> <li>b. <i>Where the camera is specially designed for installation into a civilian passenger land vehicle of less than three tonnes (gross vehicle weight), or passenger and vehicle ferries having a length overall (LOA) 65 m or greater, and having all of the following:</i> <ul style="list-style-type: none"> <li>1. <i>Is only operable when installed in any of the following:</i> <ul style="list-style-type: none"> <li>a. <i>The civilian passenger land vehicle or passenger and vehicle ferry for which it was intended; <u>or</u></i></li> <li>b. <i>A specially designed, authorised maintenance test facility; <u>and</u></i></li> </ul> </li> <li>2. <i>Incorporates an active mechanism that forces the camera not to function when it is removed from the vehicle for which it was intended;</i></li> </ul> </li> </ul>

Category Code	Item Description
6A004	<p data-bbox="627 454 1259 555">c. Limited by design to have a maximum “radiant sensitivity” of 10 mA/W or less for wavelengths exceeding 760 nm, having all of the following:</p> <ol data-bbox="692 568 1259 902" style="list-style-type: none"> <li data-bbox="692 568 1259 669">1. Incorporating a response limiting mechanism designed not to be removed or modified;</li> <li data-bbox="692 683 1259 824">2. Incorporates an active mechanism that forces the camera not to function when the response limiting mechanism is removed; <u>and</u></li> <li data-bbox="692 837 1259 902">3. Not specially designed or modified for underwater use; <u>or</u></li> </ol> <p data-bbox="627 920 1018 954">d. Having all of the following:</p> <ol data-bbox="692 969 1259 1417" style="list-style-type: none"> <li data-bbox="692 969 1259 1034">1. Not incorporating a ‘direct view’ or electronic image display;</li> <li data-bbox="692 1048 1259 1113">2. Has no facility to output a viewable image of the detected field of view;</li> <li data-bbox="692 1126 1259 1236">3. The “focal plane array” is only operable when installed in the camera for which it was intended; <u>and</u></li> <li data-bbox="692 1249 1259 1417">4. The “focal plane array” incorporates an active mechanism that forces it to be permanently inoperable when removed from the camera for which it was intended.</li> </ol> <p data-bbox="544 1435 1259 1500">5. Imaging cameras incorporating solid-state detectors specified by Category Code 6A002.a.1.</p> <p data-bbox="480 1570 1042 1603">Optical equipment and components, as follows:</p> <p data-bbox="480 1621 999 1655">a. Optical mirrors (reflectors) as follows:</p> <p data-bbox="544 1673 596 1706"><u>N.B.</u></p> <p data-bbox="544 1711 1259 1778"><i>For optical mirrors specially designed for lithography equipment, see Category Code 3B001.</i></p>

<i>Category Code</i>	<i>Item Description</i>
	<ol style="list-style-type: none"> <li>1. “Deformable mirrors” having either continuous or multi-element surfaces, and specially designed components therefor, capable of dynamically repositioning portions of the surface of the mirror at rates exceeding 100 Hz;</li> <li>2. Lightweight monolithic mirrors having an average “equivalent density” of less than 30 kg/m<sup>2</sup> and a total mass exceeding 10 kg;</li> <li>3. Lightweight “composite” or foam mirror structures having an average “equivalent density” of less than 30 kg/m<sup>2</sup> and a total mass exceeding 2 kg;</li> <li>4. Beam steering mirrors more than 100 mm in diameter or length of major axis, which maintain a flatness of <math>\lambda/2</math> or better (<math>\lambda</math> is equal to 633 nm) having a control bandwidth exceeding 100 Hz;</li> </ol> <p>b. Optical components made from zinc selenide (ZnSe) or zinc sulphide (ZnS) with transmission in the wavelength range exceeding 3,000 nm but not exceeding 25,000 nm and having any of the following:</p> <ol style="list-style-type: none"> <li>1. Exceeding 100 cm<sup>3</sup> in volume; <u>or</u></li> <li>2. Exceeding 80 mm in diameter or length of major axis and 20 mm in thickness (depth);</li> </ol> <p>c. “Space-qualified” components for optical systems, as follows:</p> <ol style="list-style-type: none"> <li>1. Components lightweighted to less than 20% “equivalent density” compared with a solid blank of the same aperture and thickness;</li> <li>2. Raw substrates, processed substrates having surface coatings (single-layer or multi-layer, metallic or dielectric, conducting, semiconducting or insulating) or having protective films;</li> <li>3. Segments or assemblies of mirrors designed to be assembled in space into an optical system with a collecting aperture equivalent to or larger than a single optic 1 m in diameter;</li> </ol>

<i>Category Code</i>	<i>Item Description</i>
	<p>4. Components manufactured from “composite” materials having a coefficient of linear thermal expansion equal to or less than <math>5 \times 10^{-6}</math> in any coordinate direction;</p> <p>d. Optical control equipment as follows:</p> <ol style="list-style-type: none"> <li>1. Equipment specially designed to maintain the surface figure or orientation of the “space-qualified” components specified in Category Code 6A004.c.1. or 6A004.c.3.;</li> <li>2. Equipment having steering, tracking, stabilisation or resonator alignment bandwidths equal to or more than 100 Hz and an accuracy of 10 <math>\mu</math>rad (microradians) or less;</li> <li>3. Gimbals having all of the following: <ol style="list-style-type: none"> <li>a. A maximum slew exceeding 5°;</li> <li>b. A bandwidth of 100 Hz or more;</li> <li>c. Angular pointing errors of 200 <math>\mu</math>rad (microradians) or less; <u>and</u></li> <li>d. Having any of the following: <ol style="list-style-type: none"> <li>1. Exceeding 0.15 m but not exceeding 1 m in diameter or major axis length and capable of angular accelerations exceeding 2 rad (radians)/s<sup>2</sup>; <u>or</u></li> <li>2. Exceeding 1 m in diameter or major axis length and capable of angular accelerations exceeding 0.5 rad (radians)/s<sup>2</sup>;</li> </ol> </li> </ol> </li> <li>4. Not used;</li> </ol> <p>e. ‘Aspheric optical elements’ having all of the following:</p> <ol style="list-style-type: none"> <li>1. Largest dimension of the optical-aperture greater than 400 mm;</li> <li>2. Surface roughness less than 1 nm (rms) for sampling lengths equal to or greater than 1 mm; <u>and</u></li> <li>3. Coefficient of linear thermal expansion’s absolute magnitude less than <math>3 \times 10^{-6}</math>/K at 25°C.</li> </ol>

Category Code	Item Description
	<p><u>Technical Notes</u></p> <ol style="list-style-type: none"> <li>1. An ‘aspheric optical element’ is any element used in an optical system whose imaging surface or surfaces are designed to depart from the shape of an ideal sphere.</li> <li>2. It is not necessary to evaluate the surface roughness of the optical element against the criteria in Category Code 6A004.e.2. unless the optical element was designed or manufactured with the intent to meet, or exceed the control parameter.</li> </ol> <p><u>Note</u></p> <p>Category Code 6A004.e. does not include ‘aspheric optical elements’ having any of the following:</p> <ol style="list-style-type: none"> <li>a. Largest optical-aperture dimension less than 1 m and focal length to aperture ratio equal to or greater than 4.5:1;</li> <li>b. Largest optical-aperture dimension equal to or greater than 1 m and focal length to aperture ratio equal to or greater than 7:1;</li> <li>c. Designed as Fresnel, flyeye, stripe, prism or diffractive optical elements;</li> <li>d. Fabricated from borosilicate glass having a coefficient of linear thermal expansion greater than <math>2.5 \times 10^{-6}/K</math> at 25°C; <u>or</u></li> <li>e. An X-ray optical element having inner mirror capabilities (e.g. tube-type mirrors).</li> </ol> <p><u>N.B.</u></p> <p>For ‘aspheric optical elements’ specially designed for lithography equipment, see Category Code 3B001.</p>
6A005	<p>“Lasers”, other than those specified in Category Code 0B001.g.5. or 0B001.h.6., components and optical equipment, as follows:</p> <p><u>N.B.</u></p> <p>See also Category Code 6A205.</p>

Category Code	Item Description
	<p><u>Note 1</u> Pulsed “lasers” include those that run in a continuous wave (CW) mode with pulses superimposed.</p> <p><u>Note 2</u> Excimer, semiconductor, chemical, CO, CO<sub>2</sub>, and ‘non-repetitive pulsed’ Nd:glass “lasers” are only specified in Category Code 6A005.d.</p> <p><u>Technical Note</u> ‘Non-repetitive pulsed’ refers to “lasers” that produce either a single output pulse or that have a time interval between pulses exceeding one minute.</p> <p><u>Note 3</u> Category Code 6A005 includes fibre “lasers”.</p> <p><u>Note 4</u> The control status of “lasers” incorporating frequency conversion (i.e. wavelength change) by means other than one “laser” pumping another “laser” is determined by applying the control parameters for both the output of the source “laser” and the frequency-converted optical output.</p> <p><u>Note 5</u> Category Code 6A005 does not include “lasers” as follows:</p> <ul style="list-style-type: none"> <li>a. Ruby with output energy below 20 J;</li> <li>b. Nitrogen;</li> <li>c. Krypton.</li> </ul> <p><u>Technical Note</u> In Category Code 6A005, ‘Wall-plug efficiency’ is defined as the ratio of “laser” output power (or “average output power”) to total electrical input power required to operate the “laser”, including the power supply/conditioning and thermal conditioning/heat exchanger.</p> <ul style="list-style-type: none"> <li>a. Non-“tunable” continuous wave “(CW) lasers” having any of the following: <ul style="list-style-type: none"> <li>1. Output wavelength less than 150 nm and output power exceeding 1 W;</li> </ul> </li> </ul>

<i>Category Code</i>	<i>Item Description</i>
	<p>2. Output wavelength of 150 nm or more but not exceeding 510 nm and output power exceeding 30 W;</p> <p><i>Note</i>  <i>Category Code 6A005.a.2. does not include Argon “lasers” having an output power equal or less than 50 W.</i></p> <p>3. Output wavelength exceeding 510 nm but not exceeding 540 nm and any of the following:</p> <ol style="list-style-type: none"> <li>a. Single transverse mode output and output power exceeding 50 W; <u>or</u></li> <li>b. Multiple transverse mode output and output power exceeding 150 W;</li> </ol> <p>4. Output wavelength exceeding 540 nm but not exceeding 800 nm and output power exceeding 30 W;</p> <p>5. Output wavelength exceeding 800 nm but not exceeding 975 nm and any of the following:</p> <ol style="list-style-type: none"> <li>a. Single transverse mode output and output power exceeding 50 W; <u>or</u></li> <li>b. Multiple transverse mode output and output power exceeding 80 W;</li> </ol> <p>6. Output wavelength exceeding 975 nm but not exceeding 1,150 nm and any of the following:</p> <ol style="list-style-type: none"> <li>a. Single transverse mode output and output power exceeding 200 W; <u>or</u></li> <li>b. Multiple transverse mode output and any of the following: <ol style="list-style-type: none"> <li>1. ‘Wall-plug efficiency’ exceeding 18% and output power exceeding 500 W; <u>or</u></li> <li>2. Output power exceeding 2 kW;</li> </ol> </li> </ol>



Category Code	Item Description
	<p data-bbox="687 454 772 488"><u>Note 1</u></p> <p data-bbox="687 495 1260 797"><i>Category Code 6A005.a.6.b. does not include multiple transverse mode, industrial “lasers” with output power exceeding 2 kW and not exceeding 6 kW with a total mass greater than 1,200 kg. For the purpose of this Note, total mass includes all components required to operate the “laser”, e.g. “laser”, power supply, heat exchanger, but excludes external optics for beam conditioning and/or delivery.</i></p> <p data-bbox="687 813 772 846"><u>Note 2</u></p> <p data-bbox="687 853 1260 958"><i>Category Code 6A005.a.6.b. does not include multiple transverse mode, industrial “lasers” having any of the following:</i></p> <ul style="list-style-type: none"> <li data-bbox="687 972 1260 1070">a. <i>Output power exceeding 500 W but not exceeding 1 kW and having all of the following:</i> <ul style="list-style-type: none"> <li data-bbox="751 1086 1260 1160">1. <i>Beam Parameter Product (BPP) exceeding 0.7 mm•mrad; <u>and</u></i></li> <li data-bbox="751 1171 1260 1245">2. <i>‘Brightness’ not exceeding 1,024 W/(mm•mrad)<sup>2</sup>;</i></li> </ul> </li> <li data-bbox="687 1256 1260 1352">b. <i>Output power exceeding 1 kW but not exceeding 1.6 kW and having a BPP exceeding 1.25 mm•mrad;</i></li> <li data-bbox="687 1368 1260 1464">c. <i>Output power exceeding 1.6 kW but not exceeding 2.5 kW and having a BPP exceeding 1.7 mm•mrad;</i></li> <li data-bbox="687 1480 1260 1576">d. <i>Output power exceeding 2.5 kW but not exceeding 3.3 kW and having a BPP exceeding 2.5 mm•mrad;</i></li> <li data-bbox="687 1592 1260 1688">e. <i>Output power exceeding 3.3 kW but not exceeding 4 kW and having a BPP exceeding 3.5 mm•mrad;</i></li> <li data-bbox="687 1704 1260 1800">f. <i>Output power exceeding 4 kW but not exceeding 5 kW and having a BPP exceeding 5 mm•mrad;</i></li> </ul>

<i>Category Code</i>	<i>Item Description</i>
	<p data-bbox="692 456 1257 555">g. <i>Output power exceeding 5 kW but not exceeding 6 kW and having a BPP exceeding 7.2 mm•mrad;</i></p> <p data-bbox="692 568 1257 667">h. <i>Output power exceeding 6 kW but not exceeding 8 kW and having a BPP exceeding 12 mm•mrad; <u>or</u></i></p> <p data-bbox="692 680 1257 779">i. <i>Output power exceeding 8 kW but not exceeding 10 kW and having a BPP exceeding 24 mm•mrad.</i></p> <p data-bbox="756 792 938 831"><u>Technical Note</u></p> <p data-bbox="756 844 1257 1043"><i>For the purpose of Category Code 6A005.a.6.b., Note 2.a., ‘brightness’ is defined as the output power of the “laser” divided by the squared Beam Parameter Product (BPP), i.e. (output power)/BPP<sup>2</sup>.</i></p> <p data-bbox="544 1057 1257 1128">7. Output wavelength exceeding 1,150 nm but not exceeding 1,555 nm and any of the following:</p> <p data-bbox="628 1142 1257 1214">a. Single transverse mode and output power exceeding 50 W; <u>or</u></p> <p data-bbox="628 1227 1257 1299">b. Multiple transverse mode and output power exceeding 80 W; <u>or</u></p> <p data-bbox="544 1312 1257 1384">8. Output wavelength exceeding 1,555 nm and output power exceeding 1 W;</p> <p data-bbox="480 1397 1257 1429">b. Non-“tunable” “pulsed lasers” having any of the following:</p> <p data-bbox="544 1442 1257 1514">1. Output wavelength less than 150 nm and any of the following:</p> <p data-bbox="628 1527 1257 1599">a. Output energy exceeding 50 mJ per pulse and “peak power” exceeding 1 W; <u>or</u></p> <p data-bbox="628 1612 1174 1644">b. “Average output power” exceeding 1 W;</p> <p data-bbox="544 1657 1257 1729">2. Output wavelength of 150 nm or more but not exceeding 510 nm and having any of the following:</p> <p data-bbox="628 1742 1257 1814">a. Output power exceeding 1.5 J per pulse and “peak power” exceeding 30 W; <u>or</u></p> <p data-bbox="628 1827 1190 1859">b. “Average output power” exceeding 30 W;</p>

<i>Category Code</i>	<i>Item Description</i>
	<p data-bbox="687 456 751 488"><u>Note</u></p> <p data-bbox="687 497 1259 595"><i>Category Code 6A005.b.2.b. does not include Argon “lasers” having an “average output power” equal to or less than 50 W.</i></p> <ol style="list-style-type: none"> <li data-bbox="544 613 1259 680">3. Output wavelength exceeding 510 nm but not exceeding 540 nm and any of the following:           <ol style="list-style-type: none"> <li data-bbox="628 696 1259 763">a. Single transverse mode output and any of the following:               <ol style="list-style-type: none"> <li data-bbox="692 779 1259 846">1. Output energy exceeding 1.5 J per pulse and “peak power” exceeding 50 W; <u>or</u></li> <li data-bbox="692 862 1259 929">2. “Average output power” exceeding 50 W; <u>or</u></li> </ol> </li> <li data-bbox="628 945 1259 1012">b. Multiple transverse mode output and any of the following:               <ol style="list-style-type: none"> <li data-bbox="692 1028 1259 1095">1. Output energy exceeding 1.5 J per pulse and “peak power” exceeding 150 W; <u>or</u></li> <li data-bbox="692 1111 1259 1178">2. “Average output power” exceeding 150 W;</li> </ol> </li> </ol> </li> <li data-bbox="544 1193 1259 1261">4. Output wavelength exceeding 540 nm but not exceeding 800 nm and any of the following:           <ol style="list-style-type: none"> <li data-bbox="628 1276 1259 1344">a. “Pulse duration” less than 1 ps and any of the following:               <ol style="list-style-type: none"> <li data-bbox="692 1359 1259 1458">1. Output energy exceeding 0.005 J per pulse and “peak power” exceeding 5 GW; <u>or</u></li> <li data-bbox="692 1473 1259 1541">2. “Average output power” exceeding 20 W; <u>or</u></li> </ol> </li> <li data-bbox="628 1556 1259 1624">b. “Pulse duration” equal to or exceeding 1 ps and any of the following:               <ol style="list-style-type: none"> <li data-bbox="692 1639 1259 1706">1. Output energy exceeding 1.5 J per pulse and “peak power” exceeding 30 W; <u>or</u></li> <li data-bbox="692 1722 1259 1762">2. “Average output power” exceeding 30 W;</li> </ol> </li> </ol> </li> </ol>

<i>Category Code</i>	<i>Item Description</i>
	<p>5. Output wavelength exceeding 800 nm but not exceeding 975 nm and any of the following:</p> <ul style="list-style-type: none"> <li>a. “Pulse duration” less than 1 ps and any of the following: <ul style="list-style-type: none"> <li>1. Output energy exceeding 0.005 J per pulse and “peak power” exceeding 5 GW; <u>or</u></li> <li>2. Single transverse mode output and “average output power” exceeding 20 W;</li> </ul> </li> <li>b. “Pulse duration” equal to or exceeding 1 ps and not exceeding 1 <math>\mu</math>s and any of the following: <ul style="list-style-type: none"> <li>1. Output energy exceeding 0.5 J per pulse and “peak power” exceeding 50 W;</li> <li>2. Single transverse mode output and “average output power” exceeding 20 W; <u>or</u></li> <li>3. Multiple transverse mode output and “average output power” exceeding 50 W; <u>or</u></li> </ul> </li> <li>c. “Pulse duration” exceeding 1 <math>\mu</math>s and any of the following: <ul style="list-style-type: none"> <li>1. Output energy exceeding 2 J per pulse and “peak power” exceeding 50 W;</li> <li>2. Single transverse mode output and “average output power” exceeding 50 W; <u>or</u></li> <li>3. Multiple transverse mode output and “average output power” exceeding 80 W; <u>or</u></li> </ul> </li> </ul> <p>6. Output wavelength exceeding 975 nm but not exceeding 1,150 nm and any of the following:</p> <ul style="list-style-type: none"> <li>a. “Pulse duration” of less than 1 ps and any of the following: <ul style="list-style-type: none"> <li>1. Output “peak power” exceeding 2 GW per pulse;</li> </ul> </li> </ul>

<i>Category Code</i>	<i>Item Description</i>
	<ul style="list-style-type: none"> <li>2. “Average output power” exceeding 10 W; <u>or</u></li> <li>3. Output energy exceeding 0.002 J per pulse;</li> </ul> <p>b. “Pulse duration” equal to or exceeding 1 ps and less than 1 ns and any of the following:</p> <ul style="list-style-type: none"> <li>1. Output “peak power” exceeding 5 GW per pulse;</li> <li>2. “Average output power” exceeding 10 W; <u>or</u></li> <li>3. Output energy exceeding 0.1 J per pulse;</li> </ul> <p>c. “Pulse duration” equal to or exceeding 1 ns but not exceeding 1 <math>\mu</math>s, and any of the following:</p> <ul style="list-style-type: none"> <li>1. Single transverse mode output and any of the following: <ul style="list-style-type: none"> <li>a. “Peak power” exceeding 100 MW;</li> <li>b. “Average output power” exceeding 20 W limited by design to a maximum pulse repetition frequency less than or equal to 1 kHz;</li> <li>c. ‘Wall-plug efficiency’ exceeding 12%, “average output power” exceeding 100 W and capable of operating at a pulse repetition frequency greater than 1 kHz;</li> <li>d. “Average output power” exceeding 150 W and capable of operating at a pulse repetition frequency greater than 1 kHz; <u>or</u></li> <li>e. Output energy exceeding 2 J per pulse; <u>or</u></li> </ul> </li> <li>2. Multiple transverse mode output and any of the following: <ul style="list-style-type: none"> <li>a. “Peak power” exceeding 400 MW;</li> </ul> </li> </ul>

<i>Category Code</i>	<i>Item Description</i>
	<ul style="list-style-type: none"> <li>b. ‘Wall-plug efficiency’ exceeding 18% and “average output power” exceeding 500 W;</li> <li>c. “Average output power” exceeding 2 kW; <u>or</u></li> <li>d. Output energy exceeding 4 J per pulse; <u>or</u></li> </ul> <p>d. “Pulse duration” exceeding 1 <math>\mu</math>s and any of the following:</p> <ul style="list-style-type: none"> <li>1. Single transverse mode output and any of the following: <ul style="list-style-type: none"> <li>a. “Peak power” exceeding 500 kW;</li> <li>b. ‘Wall-plug efficiency’ exceeding 12% and “average output power” exceeding 100 W; <u>or</u></li> <li>c. “Average output power” exceeding 150 W; <u>or</u></li> </ul> </li> <li>2. Multiple transverse mode output and any of the following: <ul style="list-style-type: none"> <li>a. “Peak power” exceeding 1 MW;</li> <li>b. ‘Wall-plug efficiency’ exceeding 18% and “average output power” exceeding 500 W; <u>or</u></li> <li>c. “Average output power” exceeding 2 kW;</li> </ul> </li> </ul> <p>7. Output wavelength exceeding 1,150 nm but not exceeding 1,555 nm, and any of the following:</p> <ul style="list-style-type: none"> <li>a. “Pulse duration” not exceeding 1 <math>\mu</math>s and any of the following: <ul style="list-style-type: none"> <li>1. Output energy exceeding 0.5 J per pulse and “peak power” exceeding 50 W;</li> <li>2. Single transverse mode output and “average output power” exceeding 20 W; <u>or</u></li> </ul> </li> </ul>

<i>Category Code</i>	<i>Item Description</i>
	<p data-bbox="692 454 1259 555">3. Multiple transverse mode output and “average output power” exceeding 50 W; <u>or</u></p> <p data-bbox="628 568 1259 636">b. “Pulse duration” exceeding 1 <math>\mu</math>s and any of the following:</p> <p data-bbox="692 651 1259 719">1. Output energy exceeding 2 J per pulse and “peak power” exceeding 50 W;</p> <p data-bbox="692 734 1259 835">2. Single transverse mode output and “average output power” exceeding 50 W; <u>or</u></p> <p data-bbox="692 851 1259 952">3. Multiple transverse mode output and “average output power” exceeding 80 W; <u>or</u></p> <p data-bbox="544 967 1259 1034">8. Output wavelength exceeding 1,555 nm and any of the following:</p> <p data-bbox="628 1050 1259 1117">a. Output energy exceeding 100 mJ per pulse and “peak power” exceeding 1 W; <u>or</u></p> <p data-bbox="628 1133 1174 1167">b. “Average output power” exceeding 1 W;</p> <p data-bbox="480 1182 1110 1216">c. “Tunable” “lasers” having any of the following:</p> <p data-bbox="544 1232 603 1265"><u>Note</u></p> <p data-bbox="544 1281 1259 1406"><i>Category Code 6A005.c. includes titanium-sapphire (Ti:Al<sub>2</sub>O<sub>3</sub>), thulium-YAG (Tm: YAG), thulium-YSGG (Tm: YSGG), alexandrite (Cr: BeAl<sub>2</sub>O<sub>4</sub>) and colour centre “lasers”, dye “lasers”, and liquid “lasers”.</i></p> <p data-bbox="544 1422 1259 1489">1. Output wavelength less than 600 nm and any of the following:</p> <p data-bbox="628 1505 1259 1572">a. Output energy exceeding 50 mJ per pulse and “peak power” exceeding 1 W; <u>or</u></p> <p data-bbox="628 1588 1238 1621">b. Average or CW output power exceeding 1 W;</p>

Category Code	Item Description
	<p data-bbox="603 456 667 488"><u>Note</u></p> <p data-bbox="603 497 1259 629"><i>Category Code 6A005.c.1. does not include dye lasers or other liquid lasers, having a multimode output and a wavelength of 150 nm or more but not exceeding 600 nm and all of the following:</i></p> <ol style="list-style-type: none"> <li data-bbox="628 647 1259 712">1. <i>Output energy less than 1.5 J per pulse or a “peak power” less than 20 W; <u>and</u></i></li> <li data-bbox="628 730 1225 761">2. <i>Average or CW output power less than 20 W.</i></li> </ol> <ol style="list-style-type: none"> <li data-bbox="541 779 1259 844">2. <i>Output wavelength of 600 nm or more but not exceeding 1,400 nm, and any of the following:</i> <ol style="list-style-type: none"> <li data-bbox="628 862 1259 927">a. <i>Output energy exceeding 1 J per pulse and “peak power” exceeding 20 W; <u>or</u></i></li> <li data-bbox="628 945 1259 1010">b. <i>Average or CW output power exceeding 20 W; <u>or</u></i></li> </ol> </li> <li data-bbox="541 1028 1259 1093">3. <i>Output wavelength exceeding 1,400 nm and any of the following:</i> <ol style="list-style-type: none"> <li data-bbox="628 1111 1259 1176">a. <i>Output energy exceeding 50 mJ per pulse and “peak power” exceeding 1 W; <u>or</u></i></li> <li data-bbox="628 1193 1235 1225">b. <i>Average or CW output power exceeding 1 W;</i></li> </ol> </li> </ol> <ol style="list-style-type: none"> <li data-bbox="478 1243 1259 1308">d. <i>Other “lasers”, not specified in Category Code 6A005.a., 6A005.b. or 6A005.c. as follows:</i> <ol style="list-style-type: none"> <li data-bbox="541 1326 1023 1357">1. <i>Semiconductor “lasers” as follows:</i> <p data-bbox="603 1375 687 1406"><u>Note 1</u></p> <p data-bbox="603 1415 1259 1518"><i>Category Code 6A005.d.1. includes semiconductor “lasers” having optical output connectors (e.g. fibre optic pigtails).</i></p> <p data-bbox="603 1536 687 1568"><u>Note 2</u></p> <p data-bbox="603 1576 1259 1680"><i>The control status of semiconductor “lasers” specially designed for other equipment is determined by the control status of the other equipment.</i></p> </li> </ol> </li> </ol>



<i>Category Code</i>	<i>Item Description</i>
	<ul style="list-style-type: none"> <li>a. Individual single-transverse mode semiconductor “lasers” having any of the following:               <ul style="list-style-type: none"> <li>1. Wavelength equal or less than 1,510 nm and average or CW output power, exceeding 1.5 W; <u>or</u></li> <li>2. Wavelength greater than 1,510 nm and average or CW output power, exceeding 500 mW;</li> </ul> </li> <li>b. Individual, multiple-transverse mode semiconductor “lasers” having any of the following:               <ul style="list-style-type: none"> <li>1. Wavelength of less than 1,400 nm and average or CW output power, exceeding 15 W;</li> <li>2. Wavelength equal to or greater than 1,400 nm and less than 1,900 nm and average or CW output power, exceeding 2.5 W; <u>or</u></li> <li>3. Wavelength equal to or greater than 1,900 nm and average or CW output power, exceeding 1 W;</li> </ul> </li> <li>c. Individual semiconductor “laser” ‘bars’, having any of the following:               <ul style="list-style-type: none"> <li>1. Wavelength of less than 1,400 nm and average or CW output power, exceeding 100 W;</li> <li>2. Wavelength equal to or greater than 1,400 nm and less than 1,900 nm and average or CW output power, exceeding 25 W; <u>or</u></li> <li>3. Wavelength equal to or greater than 1,900 nm and average or CW output power, exceeding 10 W;</li> </ul> </li> </ul>

<i>Category Code</i>	<i>Item Description</i>
	<p>d. Semiconductor “laser” ‘stacked arrays’ (two-dimensional arrays) having any of the following:</p> <ol style="list-style-type: none"> <li>1. Wavelength less than 1,400 nm and having any of the following: <ol style="list-style-type: none"> <li>a. Average or CW total output power less than 3 kW and having average or CW output ‘power density’ greater than 500 W/cm<sup>2</sup>;</li> <li>b. Average or CW total output power equal to or exceeding 3 kW but less than or equal to 5 kW, and having average or CW output ‘power density’ greater than 350 W/cm<sup>2</sup>;</li> <li>c. Average or CW total output power exceeding 5 kW;</li> <li>d. Peak pulsed ‘power density’ exceeding 2,500 W/cm<sup>2</sup>; <u>or</u></li> <li>e. Spatially coherent average or CW total output power, greater than 150 W;</li> </ol> </li> <li>2. Wavelength greater than or equal to 1,400 nm but less than 1,900 nm, and having any of the following: <ol style="list-style-type: none"> <li>a. Average or CW total output power less than 250 W and average or CW output ‘power density’ greater than 150 W/cm<sup>2</sup>;</li> <li>b. Average or CW total output power equal to or exceeding 250 W but less than or equal to 500 W, and having average or CW output ‘power density’ greater than 50 W/cm<sup>2</sup>;</li> <li>c. Average or CW total output power exceeding 500 W;</li> </ol> </li> </ol>

<i>Category Code</i>	<i>Item Description</i>
	<p>d. Peak pulsed ‘power density’ exceeding 500 W/cm<sup>2</sup>; <u>or</u></p> <p>e. Spatially coherent average or CW total output power, exceeding 15 W;</p> <p>3. Wavelength greater than or equal to 1,900 nm and having any of the following:</p> <p>a. Average or CW output ‘power density’ greater than 50 W/cm<sup>2</sup>;</p> <p>b. Average or CW output power greater than 10 W; <u>or</u></p> <p>c. Spatially coherent average or CW total output power, exceeding 1.5 W; <u>or</u></p> <p>4. At least one “laser” ‘bar’ specified in Category Code 6A005.d.1.c.;</p> <p><u>Technical Note</u>  <i>For the purpose of Category Code 6A005.d.1.d., ‘power density’ means the total “laser” output power divided by the emitter surface area of the ‘stacked array’.</i></p> <p>e. Semiconductor “laser” ‘stacked arrays’, other than those specified in Category Code 6A005.d.1.d., having all of the following:</p> <p>1. Specially designed or modified to be combined with other ‘stacked arrays’ to form a larger ‘stacked array’; <u>and</u></p> <p>2. Integrated connections, common for both electronics and cooling;</p> <p><u>Note 1</u>  <i>‘Stacked arrays’, formed by combining semiconductor “laser” ‘stacked arrays’ specified by Category Code 6A005.d.1.e., that are not designed to be further combined or modified are specified by Category Code 6A005.d.1.d.</i></p>

Category Code	Item Description
	<p data-bbox="691 456 770 488"><u>Note 2</u></p> <p data-bbox="691 497 1259 696"><i>'Stacked arrays', formed by combining semiconductor "laser" 'stacked arrays' specified by Category Code 6A005.d.1.e., that are designed to be further combined or modified are specified by Category Code 6A005.d.1.e.</i></p> <p data-bbox="691 714 770 745"><u>Note 3</u></p> <p data-bbox="691 754 1259 887"><i>Category Code 6A005.d.1.e. does not include modular assemblies of single 'bars' designed to be fabricated into end-to-end stacked linear arrays.</i></p> <p data-bbox="608 904 799 936"><u>Technical Notes</u></p> <ol data-bbox="544 945 1259 1848" style="list-style-type: none"> <li data-bbox="628 945 1259 1010">1. Semiconductor "lasers" are commonly called "laser" diodes.</li> <li data-bbox="628 1028 1259 1160">2. A 'bar' (also called a semiconductor "laser" 'bar', a "laser" diode 'bar' or diode 'bar') consists of multiple semiconductor "lasers" in a one-dimensional array.</li> <li data-bbox="628 1178 1259 1279">3. A 'stacked array' consists of multiple 'bars' forming a two-dimensional array of semiconductor "lasers".</li> </ol> <ol data-bbox="544 1299 1259 1848" style="list-style-type: none"> <li data-bbox="544 1299 1259 1496">2. Carbon monoxide (CO) "lasers" having any of the following: <ol data-bbox="628 1384 1259 1496" style="list-style-type: none"> <li data-bbox="628 1384 1259 1449">a. Output energy exceeding 2 J per pulse and "peak power" exceeding 5 kW; <u>or</u></li> <li data-bbox="628 1467 1259 1496">b. Average or CW output power exceeding 5 kW;</li> </ol> </li> <li data-bbox="544 1514 1259 1848">3. Carbon dioxide (CO<sub>2</sub>) "lasers" having any of the following: <ol data-bbox="628 1599 1259 1848" style="list-style-type: none"> <li data-bbox="628 1599 1259 1628">a. CW output power exceeding 15 kW;</li> <li data-bbox="628 1646 1259 1794">b. Pulsed output with a "pulse duration" exceeding 10 μs and any of the following: <ol data-bbox="691 1731 1259 1848" style="list-style-type: none"> <li data-bbox="691 1731 1259 1796">1. "Average output power" exceeding 10 kW; <u>or</u></li> <li data-bbox="691 1814 1259 1848">2. "Peak power" exceeding 100 kW; <u>or</u></li> </ol> </li> </ol> </li> </ol>

<i>Category Code</i>	<i>Item Description</i>
	<p>c. Pulsed output with a “pulse duration” equal to or less than 10 <math>\mu</math>s and any of the following:</p> <ol style="list-style-type: none"> <li>1. Pulse energy exceeding 5 J per pulse; <u>or</u></li> <li>2. “Average output power” exceeding 2.5 kW;</li> </ol> <p>4. Excimer “lasers” having any of the following:</p> <ol style="list-style-type: none"> <li>a. Output wavelength not exceeding 150 nm and any of the following: <ol style="list-style-type: none"> <li>1. Output energy exceeding 50 mJ per pulse; <u>or</u></li> <li>2. “Average output power” exceeding 1 W;</li> </ol> </li> <li>b. Output wavelength exceeding 150 nm but not exceeding 190 nm and any of the following: <ol style="list-style-type: none"> <li>1. Output energy exceeding 1.5 J per pulse; <u>or</u></li> <li>2. “Average output power” exceeding 120 W;</li> </ol> </li> <li>c. Output wavelength exceeding 190 nm but not exceeding 360 nm and any of the following: <ol style="list-style-type: none"> <li>1. Output energy exceeding 10 J per pulse; <u>or</u></li> <li>2. “Average output power” exceeding 500 W; <u>or</u></li> </ol> </li> <li>d. Output wavelength exceeding 360 nm and any of the following: <ol style="list-style-type: none"> <li>1. Output energy exceeding 1.5 J per pulse; <u>or</u></li> <li>2. “Average output power” exceeding 30 W;</li> </ol> </li> </ol> <p><u>N.B.</u>  For excimer “lasers” specially designed for lithography equipment, see Category Code 3B001.</p>

<i>Category Code</i>	<i>Item Description</i>
	<p>5. “Chemical lasers” as follows:</p> <ol style="list-style-type: none"> <li>a. Hydrogen Fluoride (HF) “lasers”;</li> <li>b. Deuterium Fluoride (DF) “lasers”;</li> <li>c. “Transfer lasers”, as follows: <ol style="list-style-type: none"> <li>1. Oxygen Iodine (O<sub>2</sub>-I) “lasers”;</li> <li>2. Deuterium Fluoride-Carbon dioxide (DF-CO<sub>2</sub>) “lasers”;</li> </ol> </li> </ol> <p>6. ‘Non-repetitive pulsed’ Nd: glass “lasers” having any of the following:</p> <ol style="list-style-type: none"> <li>a. “Pulse duration” not exceeding 1 μs and output energy exceeding 50 J per pulse; <u>or</u></li> <li>b. “Pulse duration” exceeding 1 μs and output energy exceeding 100 J per pulse;</li> </ol> <p><i>Note</i>  ‘Non-repetitive pulsed’ refers to “lasers” that produce either a single output pulse or that have a time interval between pulses exceeding one minute.</p> <p>e. Components as follows:</p> <ol style="list-style-type: none"> <li>1. Mirrors cooled either by ‘active cooling’ or by heat pipe cooling;</li> </ol> <p><i>Technical Note</i>  ‘Active cooling’ is a cooling technique for optical components using flowing fluids within the subsurface (nominally less than 1 mm below the optical surface) of the optical component to remove heat from the optic.</p> <ol style="list-style-type: none"> <li>2. Optical mirrors or transmissive or partially transmissive optical or electro-optical components, specially designed for use with specified “lasers”;</li> </ol> <p>f. Optical equipment as follows:</p> <p><i>N.B.</i>  For shared aperture optical elements, capable of operating in “Super-High Power Laser” (“SHPL”) applications, see Division 2 of Part I of this Schedule.</p>

<i>Category Code</i>	<i>Item Description</i>
	<ol style="list-style-type: none"> <li>1. Dynamic wavefront (phase) measuring equipment capable of mapping at least 50 positions on a beam wavefront and any of the following:               <ol style="list-style-type: none"> <li>a. Frame rates equal to or more than 100 Hz and phase discrimination of at least 5% of the beam's wavelength; <u>or</u></li> <li>b. Frame rates equal to or more than 1,000 Hz and phase discrimination of at least 20% of the beam's wavelength;</li> </ol> </li> <li>2. "Laser" diagnostic equipment capable of measuring "SHPL" system angular beam steering errors of equal to or less than 10 <math>\mu</math>rad;</li> <li>3. Optical equipment and components, specially designed for a phased-array "SHPL" system for coherent beam combination to an accuracy of <math>\lambda/10</math> at the designed wavelength, or 0.1 <math>\mu</math>m, whichever is the smaller;</li> <li>4. Projection telescopes specially designed for use with "SHPL" systems;</li> <li>g. 'Laser acoustic detection equipment' having all of the following:               <ol style="list-style-type: none"> <li>1. CW laser output power equal to or exceeding 20 mW;</li> <li>2. Laser frequency stability equal to or better (less) than 10 MHz;</li> <li>3. Laser wavelengths equal to or exceeding 1,000 nm but not exceeding 2,000 nm;</li> <li>4. Optical system resolution better (less) than 1 nm; <u>and</u></li> <li>5. Optical Signal to Noise ratio equal to or exceeding <math>10^3</math>.</li> </ol> </li> </ol> <p><i><u>Technical Note</u></i>  '<i>Laser acoustic detection equipment</i>' is sometimes referred to as a <i>Laser Microphone or Particle Flow Detection Microphone</i>.</p>

<i>Category Code</i>	<i>Item Description</i>
6A006	<p>“Magnetometers”, “magnetic gradiometers”, “intrinsic magnetic gradiometers”, underwater electric field sensors, “compensation systems”, and specially designed components therefor, as follows:</p> <p><u>N.B.</u> See also Category Code 7A103.d.</p> <p><u>Note</u> Category Code 6A006 does not include instruments specially designed for fishery applications or biomagnetic measurements for medical diagnostics.</p> <p>a. “Magnetometers” and subsystems, as follows:</p> <ol style="list-style-type: none"> <li>1. “Magnetometers” using “superconductive” (SQUID) “technology” and having any of the following: <ol style="list-style-type: none"> <li>a. SQUID systems designed for stationary operation, without specially designed subsystems designed to reduce in-motion noise, and having a ‘sensitivity’ equal to or lower (better) than 50 fT (rms) per square root Hz at a frequency of 1 Hz; <u>or</u></li> <li>b. SQUID systems having an in-motion-magnetometer ‘sensitivity’ lower (better) than 20 pT (rms) per square root Hz at a frequency of 1 Hz and specially designed to reduce in-motion noise;</li> </ol> </li> <li>2. “Magnetometers” using optically pumped or nuclear precession (proton/Overhauser) “technology” having a ‘sensitivity’ lower (better) than 20 pT (rms) per square root Hz at a frequency of 1 Hz;</li> <li>3. “Magnetometers” using fluxgate “technology” having a ‘sensitivity’ equal to or lower (better) than 10 pT (rms) per square root Hz at a frequency of 1 Hz;</li> <li>4. Induction coil “magnetometers” having a ‘sensitivity’ lower (better) than any of the following: <ol style="list-style-type: none"> <li>a. 0.05 nT (rms) per square root Hz at frequencies of less than 1 Hz;</li> </ol> </li> </ol>



<i>Category Code</i>	<i>Item Description</i>
	<p>b. <math>1 \times 10^{-3}</math> nT (rms) per square root Hz at frequencies of 1 Hz or more but not exceeding 10 Hz; <u>or</u></p> <p>c. <math>1 \times 10^{-4}</math> nT (rms) per square root Hz at frequencies exceeding 10 Hz;</p> <p>5. Fibre optic “magnetometers” having a ‘sensitivity’ lower (better) than 1 nT (rms) per square root Hz;</p> <p>b. Underwater electric field sensors having a ‘sensitivity’ lower (better) than 8 nanovolt per metre per square root Hz when measured at 1 Hz;</p> <p>c. “Magnetic gradiometers” as follows:</p> <ol style="list-style-type: none"> <li>1. “Magnetic gradiometers” using multiple “magnetometers” specified in Category Code 6A006.a.;</li> <li>2. Fibre optic “intrinsic magnetic gradiometers” having a magnetic gradient field ‘sensitivity’ lower (better) than 0.3 nT/m (rms) per square root Hz;</li> <li>3. “Intrinsic magnetic gradiometers”, using “technology” other than fibre-optic “technology”, having a magnetic gradient field ‘sensitivity’ lower (better) than 0.015 nT/m (rms) per square root Hz;</li> </ol> <p>d. “Compensation systems” for magnetic or underwater electric field sensors resulting in a performance equal to or better than the specified parameters of Category Code 6A006.a., 6A006.b. or 6A006.c.;</p> <p>e. Underwater electromagnetic receivers incorporating magnetic field sensors specified by Category Code 6A006.a. or underwater electric field sensors specified by Category Code 6A006.b.</p> <p><u>Technical Note</u>  <i>For the purpose of Category Code 6A006, ‘sensitivity’ (noise level) is the root mean square of the device-limited noise floor which is the lowest signal that can be measured.</i></p>

Category Code	Item Description
6A007	<p>Gravity meters (gravimeters) and gravity gradiometers, as follows:</p> <p><u>N.B.</u> See also Category Code 6A107.</p> <p>a. Gravity meters designed or modified for ground use and having a static accuracy of less (better) than 10 <math>\mu</math>Gal;</p> <p><u>Note</u> Category Code 6A007.a. does not include ground gravity meters of the quartz element (Worden) type.</p> <p>b. Gravity meters designed for mobile platforms and having all of the following:</p> <ol style="list-style-type: none"> <li>1. A static accuracy of less (better) than 0.7 mGal; <u>and</u></li> <li>2. An in-service (operational) accuracy of less (better) than 0.7 mGal having a 'time-to-steady-state registration' of less than 2 minutes under any combination of attendant corrective compensations and motional influences;</li> </ol> <p><u>Technical Note</u> For the purpose of Category Code 6A007.b., 'time-to-steady-state registration' (also referred to as the gravimeter's response time) is the time over which the disturbing effects of platform induced accelerations (high frequency noise) are reduced.</p> <p>c. Gravity gradiometers.</p>
6A008	<p>Radar systems, equipment and assemblies having any of the following, and specially designed components therefor:</p> <p><u>N.B.</u> See also Category Code 6A108.</p> <p><u>Note</u> Category Code 6A008 does not include:</p> <ul style="list-style-type: none"> <li>– Secondary surveillance radar (SSR);</li> <li>– Civil Automotive Radar;</li> <li>– Displays or monitors used for air traffic control (ATC);</li> </ul>

<i>Category Code</i>	<i>Item Description</i>
	<ul style="list-style-type: none"> <li>– <i>Meteorological (weather) radar;</i></li> <li>– <i>Precision approach radar (PAR) equipment conforming to ICAO standards and employing electronically steerable linear (1-dimensional) arrays or mechanically positioned passive antennae.</i></li> <li>a. Operating at frequencies from 40 GHz to 230 GHz and having any of the following: <ul style="list-style-type: none"> <li>1. An average output power exceeding 100 mW; <u>or</u></li> <li>2. Locating accuracy of 1 m or less (better) in range and 0.2 degree or less (better) in azimuth;</li> </ul> </li> <li>b. A tunable bandwidth exceeding <math>\pm 6.25\%</math> of the ‘centre operating frequency’; <p style="margin-left: 20px;"><u>Technical Note</u> The ‘centre operating frequency’ equals one half of the sum of the highest plus the lowest specified operating frequencies.</p> </li> <li>c. Capable of operating simultaneously on more than two carrier frequencies;</li> <li>d. Capable of operating in synthetic aperture (SAR), inverse synthetic aperture (ISAR) radar mode, or sidelooking airborne (SLAR) radar mode;</li> <li>e. Incorporating electronically steerable array antennae;</li> <li>f. Capable of heightfinding non-cooperative targets;</li> <li>g. Specially designed for airborne (balloon or airframe mounted) operation and having Doppler “signal processing” for the detection of moving targets;</li> <li>h. Employing processing of radar signals and using any of the following: <ul style="list-style-type: none"> <li>1. “Radar spread spectrum” techniques; <u>or</u></li> <li>2. “Radar frequency agility” techniques;</li> </ul> </li> <li>i. Providing ground-based operation with a maximum “instrumented range” exceeding 185 km;</li> </ul> <p style="margin-left: 20px;"><u>Note</u> Category Code 6A008.i. does not include:</p>

<i>Category Code</i>	<i>Item Description</i>
	<p>a. <i>Fishing ground surveillance radar;</i></p> <p>b. <i>Ground radar equipment specially designed for enroute air traffic control and having all of the following:</i></p> <ol style="list-style-type: none"> <li>1. <i>A maximum “instrumented range” of 500 km or less;</i></li> <li>2. <i>Configured so that radar target data can be transmitted only one way from the radar site to one or more civil ATC centres;</i></li> <li>3. <i>Contains no provisions for remote control of the radar scan rate from the enroute ATC centre; <u>and</u></i></li> <li>4. <i>Permanently installed;</i></li> </ol> <p>c. <i>Weather balloon tracking radars.</i></p> <p>j. <i>Being “laser” radar or Light Detection and Ranging (LIDAR) equipment and having any of the following:</i></p> <ol style="list-style-type: none"> <li>1. <i>“Space-qualified”;</i></li> <li>2. <i>Employing coherent heterodyne or homodyne detection techniques and having an angular resolution of less (better) than 20 µrad (microradians); <u>or</u></i></li> <li>3. <i>Designed for carrying out airborne bathymetric littoral surveys to International Hydrographic Organisation (IHO) Order 1a Standard (5th Edition February 2008) for Hydrographic Surveys or better, and using one or more lasers with a wavelength exceeding 400 nm but not exceeding 600 nm;</i></li> </ol> <p><u>Note 1</u> <i>LIDAR equipment specially designed for surveying is only specified in Category Code 6A008.j.3.</i></p> <p><u>Note 2</u> <i>Category Code 6A008.j. does not include LIDAR equipment specially designed for meteorological observation.</i></p>

Category Code	Item Description
	<p><u>Note 3</u></p> <p><i>Parameters in the IHO Order 1a Standard 5th Edition February 2008 are summarised as follows:</i></p> <ul style="list-style-type: none"> <li>– <i>Horizontal Accuracy (95% Confidence Level) = 5 m + 5% of depth</i></li> <li>– <i>Depth Accuracy for Reduced Depths (95% confidence level) = <math>\pm\sqrt{(a^2+(b*d)^2)}</math>, where:</i> <ul style="list-style-type: none"> <li><i>a = 0.5 m = constant depth error, i.e. the sum of all constant depth errors</i></li> <li><i>b = 0.013 = factor of depth dependent error</i></li> <li><i>b*d = depth dependent error, i.e. the sum of all depth dependent errors</i></li> <li><i>d = depth</i></li> </ul> </li> <li>– <i>Feature Detection = Cubic features &gt; 2 m in depths up to 40 m; 10% of depth beyond 40 m.</i></li> </ul> <p>k. Having “signal processing” sub-systems using “pulse compression” and having any of the following:</p> <ol style="list-style-type: none"> <li>1. A “pulse compression” ratio exceeding 150; <u>or</u></li> <li>2. A compressed pulse width of less than 200 ns; <u>or</u></li> </ol> <p><u>Note</u></p> <p><i>Category Code 6A008.k.2. does not include two dimensional ‘marine radar’ or ‘vessel traffic service’ radar, having all of the following:</i></p> <ol style="list-style-type: none"> <li>a. <i>“Pulse compression” ratio not exceeding 150;</i></li> <li>b. <i>Compressed pulse width of greater than 30 ns;</i></li> <li>c. <i>Single and rotating mechanically scanned antenna;</i></li> <li>d. <i>Peak output power not exceeding 250 W; <u>and</u></i></li> <li>e. <i>Not capable of “frequency hopping”.</i></li> </ol>

<i>Category Code</i>	<i>Item Description</i>
	<p>1. Having data processing sub-systems and having any of the following:</p> <ol style="list-style-type: none"> <li>1. “Automatic target tracking” providing, at any antenna rotation, the predicted target position beyond the time of the next antenna beam passage; <u>or</u></li> </ol> <p><i>Note</i> Category Code 6A008.l.1. does not include conflict alert capability in ATC systems, or ‘marine radar’.</p> <ol style="list-style-type: none"> <li>2. Not used;</li> <li>3. Not used;</li> <li>4. Configured to provide superposition and correlation, or fusion, of target data within six seconds from two or more “geographically dispersed” radar sensors to improve the aggregate performance beyond that of any single sensor specified in Category Code 6A008.f. or 6A008.i.</li> </ol> <p><i>N.B.</i> See also Division 2 of Part I of this Schedule.</p> <p><i>Note</i> Category Code 6A008.l.4. does not include systems, equipment and assemblies used for ‘vessel traffic service’.</p> <p><u>Technical Notes</u></p> <ol style="list-style-type: none"> <li>1. For the purpose of Category Code 6A008, ‘marine radar’ is a radar that is used to navigate safely at sea, inland waterways or near-shore environments.</li> <li>2. For the purpose of Category Code 6A008, ‘vessel traffic service’ is a vessel traffic monitoring and control service similar to air traffic control for aircraft.</li> </ol>

<i>Category Code</i>	<i>Item Description</i>
6A102	<p>Radiation hardened ‘detectors’, other than those specified in Category Code 6A002, specially designed or modified for protecting against nuclear effects (e.g. electromagnetic pulse (EMP), X-rays, combined blast and thermal effects) and usable for “missiles”, designed or rated to withstand radiation levels which meet or exceed a total irradiation dose of <math>5 \times 10^5</math> rads (silicon).</p> <p><u>Technical Note</u>  <i>In Category Code 6A102, a ‘detector’ is defined as a mechanical, electrical, optical or chemical device that automatically identifies and records, or registers a stimulus such as an environmental change in pressure or temperature, an electrical or electromagnetic signal or radiation from a radioactive material. This includes devices that sense by one time operation or failure.</i></p>
6A107	<p>Gravity meters (gravimeters) and components for gravity meters and gravity gradiometers, as follows:</p> <ol style="list-style-type: none"> <li>a. Gravity meters, other than those specified in Category Code 6A007.b., designed or modified for airborne or marine use, and having a static or operational accuracy equal to or less (better) than 0.7 milligal (mgal), and having a time-to-steady-state registration of two minutes or less;</li> <li>b. Specially designed components for gravity meters specified in Category Code 6A007.b. or 6A107.a. and gravity gradiometers specified in Category Code 6A007.c.</li> </ol>
6A108	<p>Radar systems and tracking systems, other than those specified in Category Code 6A008, as follows:</p> <ol style="list-style-type: none"> <li>a. Radar and laser radar systems designed or modified for use in space launch vehicles specified in Category Code 9A004 or sounding rockets specified in Category Code 9A104;</li> </ol> <p><u>Note</u>  <i>Category Code 6A108.a. includes the following:</i></p> <ol style="list-style-type: none"> <li>a. <i>Terrain contour mapping equipment;</i></li> <li>b. <i>Imaging sensor equipment;</i></li> </ol>

<i>Category Code</i>	<i>Item Description</i>
	<p>c. <i>Scene mapping and correlation (both digital and analogue) equipment;</i></p> <p>d. <i>Doppler navigation radar equipment.</i></p> <p>b. Precision tracking systems, usable for ‘missiles’, as follows:</p> <ol style="list-style-type: none"> <li>1. Tracking systems which use a code translator in conjunction with either surface or airborne references or navigation satellite systems to provide real-time measurements of in-flight position and velocity;</li> <li>2. Range instrumentation radars including associated optical/infrared trackers with all of the following capabilities: <ol style="list-style-type: none"> <li>a. Angular resolution better than 1.5 milliradians;</li> <li>b. Range of 30 km or greater with a range resolution better than 10 m rms; <u>and</u></li> <li>c. Velocity resolution better than 3 m/s.</li> </ol> </li> </ol> <p><u>Technical Note</u>  <i>In Category Code 6A108.b., ‘missile’ means complete rocket systems and unmanned aerial vehicle systems capable of a range exceeding 300 km.</i></p>
6A202	<p>Photomultiplier tubes having both of the following characteristics:</p> <ol style="list-style-type: none"> <li>a. Photocathode area of greater than 20 cm<sup>2</sup>; <u>and</u></li> <li>b. Anode pulse rise time of less than 1 ns.</li> </ol>
6A203	<p>Cameras and components, other than those specified in Category Code 6A003, as follows:</p> <p><u>N.B. 1</u>  <i>“Software” specially designed to enhance or release the performance of a camera or imaging device to meet the characteristics of Category Code 6A203.a., 6A203.b. or 6A203.c. is specified in Category Code 6D203.</i></p>



Category Code	Item Description
	<p data-bbox="475 454 555 488"><u>N.B. 2</u></p> <p data-bbox="475 499 1257 629"><i>“Technology” in the form of codes or keys to enhance or release the performance of a camera or imaging device to meet the characteristics of Category Code 6A203.a., 6A203.b. or 6A203.c. is specified in Category Code 6E203.</i></p> <p data-bbox="475 645 539 678"><u>Note</u></p> <p data-bbox="475 689 1257 819"><i>Category Codes 6A203.a. to 6A203.c. do not include cameras or imaging devices if they have hardware, “software” or “technology” constraints that limit the performance to less than that specified above, provided they meet any of the following:</i></p> <ol data-bbox="475 835 1257 1807" style="list-style-type: none"> <li data-bbox="475 835 1257 902">1. <i>They need to be returned to the original manufacturer to make the enhancements or release the constraints;</i></li> <li data-bbox="475 918 1257 1019">2. <i>They require “software” as specified in Category Code 6D203 to enhance or release the performance to meet the characteristics of Category Code 6A203; <u>or</u></i></li> <li data-bbox="475 1034 1257 1164">3. <i>They require “technology” in the form of keys or codes as specified in Category Code 6E203 to enhance or release the performance to meet the characteristics of Category Code 6A203.</i></li> </ol> <p data-bbox="475 1180 1257 1247">a. <i>Streak cameras, and specially designed components therefor, as follows:</i></p> <ol data-bbox="539 1263 1257 1807" style="list-style-type: none"> <li data-bbox="539 1263 1257 1330">1. <i>Streak cameras with writing speeds greater than 0.5 mm/μs;</i></li> <li data-bbox="539 1346 1257 1413">2. <i>Electronic streak cameras capable of 50 ns or less time resolution;</i></li> <li data-bbox="539 1429 1257 1496">3. <i>Streak tubes for cameras specified in Category Code 6A203.a.2.;</i></li> <li data-bbox="539 1512 1257 1641">4. <i>Plug-ins specially designed for use with streak cameras which have modular structures and that enable the performance specifications in Category Code 6A203.a.1. or 6A203.a.2.;</i></li> <li data-bbox="539 1657 1257 1807">5. <i>Synchronising electronics units, rotor assemblies consisting of turbines, mirrors and bearings specially designed for cameras specified in Category Code 6A203.a.1.;</i></li> </ol>

<i>Category Code</i>	<i>Item Description</i>
	<p>b. Framing cameras, and specially designed components therefor, as follows:</p> <ol style="list-style-type: none"> <li>1. Framing cameras with recording rates greater than 225,000 frames per second;</li> <li>2. Framing cameras capable of 50 ns or less frame exposure time;</li> <li>3. Framing tubes and solid-state imaging devices having a fast image gating (shutter) time of 50 ns or less specially designed for cameras specified in Category Code 6A203.b.1. or 6A203.b.2.;</li> <li>4. Plug-ins specially designed for use with framing cameras which have modular structures and that enable the performance specifications in Category Code 6A203.b.1. or 6A203.b.2.;</li> <li>5. Synchronising electronics units, rotor assemblies consisting of turbines, mirrors and bearings specially designed for cameras specified in Category Code 6A203.b.1. or 6A203.b.2.;</li> </ol> <p><i>Technical Note</i></p> <p><i>In Category Code 6A203.b., high speed single frame cameras can be used alone to produce a single image of a dynamic event, or several such cameras can be combined in a sequentially triggered system to produce multiple images of an event.</i></p> <p>c. Solid state or electron tube cameras, and specially designed components therefor, as follows:</p> <ol style="list-style-type: none"> <li>1. Solid-state cameras or electron tube cameras with a fast image gating (shutter) time of 50 ns or less;</li> <li>2. Solid-state imaging devices and image intensifier tubes having a fast image gating (shutter) time of 50 ns or less specially designed for cameras specified in Category Code 6A203.c.1.;</li> <li>3. Electro-optical shuttering devices (Kerr or Pockels cells) with a fast image gating (shutter) time of 50 ns or less;</li> </ol>

<i>Category Code</i>	<i>Item Description</i>
	<p>4. Plug-ins specially designed for use with cameras which have modular structures and that enable the performance specifications in Category Code 6A203.c.1.</p> <p>d. Radiation-hardened TV cameras, or lenses therefor, specially designed or rated as radiation hardened to withstand a total radiation dose greater than <math>50 \times 10^3</math> Gy (silicon) (<math>5 \times 10^6</math> rad (silicon)) without operational degradation.</p> <p><i>Technical Note</i>  <i>The term Gy (silicon) refers to the energy in Joules per kilogram absorbed by an unshielded silicon sample when exposed to ionising radiation.</i></p>
6A205	<p>“Lasers”, “laser” amplifiers and oscillators, other than those specified in Category Codes 0B001.g.5., 0B001.h.6. and 6A005; as follows:</p> <p><i>N.B.</i>  <i>For copper vapour lasers, see Category Code 6A005.b.</i></p> <p>a. Argon ion “lasers” having both of the following characteristics:</p> <ol style="list-style-type: none"> <li>1. Operating at wavelengths between 400 nm and 515 nm; <u>and</u></li> <li>2. An average output power greater than 40 W;</li> </ol> <p>b. Tunable pulsed single-mode dye laser oscillators having all of the following characteristics:</p> <ol style="list-style-type: none"> <li>1. Operating at wavelengths between 300 nm and 800 nm;</li> <li>2. An average output power greater than 1 W;</li> <li>3. A repetition rate greater than 1 kHz; <u>and</u></li> <li>4. Pulse width less than 100 ns;</li> </ol> <p>c. Tunable pulsed dye laser amplifiers and oscillators, having all of the following characteristics:</p> <ol style="list-style-type: none"> <li>1. Operating at wavelengths between 300 nm and 800 nm;</li> </ol>

<i>Category Code</i>	<i>Item Description</i>
	<ol style="list-style-type: none"> <li>2. An average output power greater than 30 W;</li> <li>3. A repetition rate greater than 1 kHz; <u>and</u></li> <li>4. Pulse width less than 100 ns;</li> </ol> <p><i>Note</i>  <i>Category Code 6A205.c. does not include single mode oscillators.</i></p> <ol style="list-style-type: none"> <li>d. Pulsed carbon dioxide “lasers” having all of the following characteristics: <ol style="list-style-type: none"> <li>1. Operating at wavelengths between 9,000 nm and 11,000 nm;</li> <li>2. A repetition rate greater than 250 Hz;</li> <li>3. An average output power greater than 500 W; <u>and</u></li> <li>4. Pulse width of less than 200 ns;</li> </ol> </li> <li>e. Para-hydrogen Raman shifters designed to operate at 16 <math>\mu\text{m}</math> output wavelength and at a repetition rate greater than 250 Hz;</li> <li>f. Neodymium-doped (other than glass) “lasers” with an output wavelength between 1,000 nm and 1,100 nm having either of the following: <ol style="list-style-type: none"> <li>1. Pulse-excited and Q-switched with a pulse duration equal to or more than 1 ns, and having either of the following: <ol style="list-style-type: none"> <li>a. A single-transverse mode output with an average output power greater than 40 W; <u>or</u></li> <li>b. A multiple-transverse mode output having an average power greater than 50 W; <u>or</u></li> </ol> </li> <li>2. Incorporating frequency doubling to give an output wavelength between 500 nm and 550 nm with an average output power of more than 40 W;</li> </ol> </li> <li>g. Pulsed carbon monoxide lasers, other than those specified in Category Code 6A005.d.2., having all of the following: <ol style="list-style-type: none"> <li>1. Operating at wavelengths between 5,000 nm and 6,000 nm;</li> <li>2. A repetition rate greater than 250 Hz;</li> </ol> </li> </ol>

<i>Category Code</i>	<i>Item Description</i>
	<ol style="list-style-type: none"> <li>3. An average output power greater than 200 W; <u>and</u></li> <li>4. Pulse width of less than 200 ns.</li> </ol>
6A225	<p>Velocity interferometers for measuring velocities exceeding 1 km/s during time intervals of less than 10 microseconds.</p> <p><i>Note</i>  <i>Category Code 6A225 includes velocity interferometers such as VISARs (Velocity Interferometer Systems for Any Reflector), DLIs (Doppler Laser Interferometers) and PDV (Photonic Doppler Velocimeters) also known as Het-V (Heterodyne Velocimeters).</i></p>
6A226	<p>Pressure sensors, as follows:</p> <ol style="list-style-type: none"> <li>a. Shock pressure gauges capable of measuring pressures greater than 10 GPa, including gauges made with manganin, ytterbium, and polyvinylidene bifluoride (PVBF, PVF<sub>2</sub>);</li> <li>b. Quartz pressure transducers for pressures greater than 10 GPa.</li> </ol>
<b>6B</b>	<b>Test, Inspection and Production Equipment</b>
6B004	<p>Optical equipment as follows:</p> <ol style="list-style-type: none"> <li>a. Equipment for measuring absolute reflectance to an accuracy of <math>\pm 0.1\%</math> of the reflectance value;</li> <li>b. Equipment other than optical surface scattering measurement equipment, having an unobscured aperture of more than 10 cm, specially designed for the non-contact optical measurement of a non-planar optical surface figure (profile) to an “accuracy” of 2 nm or less (better) against the required profile.</li> </ol> <p><i>Note</i>  <i>Category Code 6B004 does not include microscopes.</i></p>

<i>Category Code</i>	<i>Item Description</i>
6B007	Equipment to produce, align and calibrate land-based gravity meters with a static accuracy of better than 0.1 mGal.
6B008	Pulse radar cross-section measurement systems having transmit pulse widths of 100 ns or less, and specially designed components therefor.  <u><i>N.B.</i></u> <i>See also Category Code 6B108.</i>
6B108	Systems, other than those specified in Category Code 6B008, specially designed for radar cross-section measurement usable for 'missiles' and their subsystems.  <u><i>Technical Note</i></u> <i>In Category Code 6B108, 'missile' means complete rocket systems and unmanned aerial vehicle systems capable of a range exceeding 300 km.</i>
<b>6C</b>	<b>Materials</b>
6C002	Optical sensor materials as follows: <ul style="list-style-type: none"> <li>a. Elemental tellurium (Te) of purity levels of 99.9995% or more;</li> <li>b. Single crystals (including epitaxial wafers) of any of the following: <ol style="list-style-type: none"> <li>1. Cadmium zinc telluride (CdZnTe), with zinc content of less than 6% by 'mole fraction';</li> <li>2. Cadmium telluride (CdTe) of any purity level; <u>or</u></li> <li>3. Mercury cadmium telluride (HgCdTe) of any purity level.</li> </ol> </li> </ul> <u><i>Technical Note</i></u> <i>'Mole fraction' is defined as the ratio of moles of ZnTe to the sum of moles of CdTe and ZnTe present in the crystal.</i>

<i>Category Code</i>	<i>Item Description</i>
6C004	<p>Optical materials as follows:</p> <ul style="list-style-type: none"> <li>a. Zinc selenide (ZnSe) and zinc sulphide (ZnS) “substrate blanks”, produced by the chemical vapour deposition process and having any of the following:               <ul style="list-style-type: none"> <li>1. A volume greater than 100 cm<sup>3</sup>; <u>or</u></li> <li>2. A diameter greater than 80 mm and a thickness of 20 mm or more;</li> </ul> </li> <li>b. Electro-optic materials and non-linear optical materials, as follows:               <ul style="list-style-type: none"> <li>1. Potassium titanyl arsenate (KTA) (59400-80-5);</li> <li>2. Silver gallium selenide (AgGaSe<sub>2</sub>, also known as AGSE) (12002-67-4);</li> <li>3. Thallium arsenic selenide (Tl<sub>3</sub>AsSe<sub>3</sub>, also known as TAS) (16142-89-5);</li> <li>4. Zinc germanium phosphide (ZnGeP<sub>2</sub>, also known as ZGP, zinc germanium biphosphide or zinc germanium diphosphide); <u>or</u></li> <li>5. Gallium selenide (GaSe) (12024-11-2);</li> </ul> </li> <li>c. Non-linear optical materials, other than those specified in Category Code 6C004.b., having any of the following:               <ul style="list-style-type: none"> <li>1. Having all of the following:                   <ul style="list-style-type: none"> <li>a. Dynamic (also known as non-stationary) third order non-linear susceptibility (<math>\chi^{(3)}</math>, chi 3) of 10<sup>-6</sup> m<sup>2</sup>/V<sup>2</sup> or more; <u>and</u></li> <li>b. Response time of less than 1 ms; <u>or</u></li> </ul> </li> <li>2. Second order non-linear susceptibility (<math>\chi^{(2)}</math>, chi 2) of 3.3 × 10<sup>-11</sup> m/V or more;</li> </ul> </li> <li>d. “Substrate blanks” of silicon carbide or beryllium beryllium (Be/Be) deposited materials, exceeding 300 mm in diameter or major axis length;</li> </ul>

<i>Category Code</i>	<i>Item Description</i>
	<p>e. Glass, including fused silica, phosphate glass, fluorophosphate glass, zirconium fluoride (ZrF<sub>4</sub>) (7783-64-4) and hafnium fluoride (HfF<sub>4</sub>) (13709-52-9) and having all of the following:</p> <ol style="list-style-type: none"> <li>1. A hydroxyl ion (OH<sup>-</sup>) concentration of less than 5 ppm;</li> <li>2. Integrated metallic purity levels of less than 1 ppm; <u>and</u></li> <li>3. High homogeneity (index of refraction variance) less than <math>5 \times 10^{-6}</math>;</li> </ol> <p>f. Synthetically produced diamond material with an absorption of less than <math>10^{-5} \text{ cm}^{-1}</math> for wavelengths exceeding 200 nm but not exceeding 14,000 nm.</p>
6C005	<p>Synthetic crystalline “laser” host material in unfinished form as follows:</p> <ol style="list-style-type: none"> <li>a. Titanium doped sapphire;</li> <li>b. Not used.</li> </ol>
<b>6D</b>	<b>Software</b>
6D001	<p>“Software” specially designed for the “development” or “production” of equipment specified in Category Code 6A004, 6A005, 6A008 or 6B008.</p>
6D002	<p>“Software” specially designed for the “use” of equipment specified in Category Code 6A002.b., 6A008 or 6B008.</p>
6D003	<p>Other “software” as follows:</p> <ol style="list-style-type: none"> <li>a. “Software” as follows: <ol style="list-style-type: none"> <li>1. “Software” specially designed for acoustic beam forming for the “real-time processing” of acoustic data for passive reception using towed hydrophone arrays;</li> </ol> </li> </ol>



<i>Category Code</i>	<i>Item Description</i>
	<ol style="list-style-type: none"> <li>2. "Source code" for the "real-time processing" of acoustic data for passive reception using towed hydrophone arrays;</li> <li>3. "Software" specially designed for acoustic beam forming for "real-time processing" of acoustic data for passive reception using bottom or bay cable systems;</li> <li>4. "Source code" for "real-time processing" of acoustic data for passive reception using bottom or bay cable systems;</li> <li>5. "Software" or "source code", specially designed for all of the following: <ol style="list-style-type: none"> <li>a. "Real-time processing" of acoustic data from sonar systems specified by Category Code 6A001.a.1.e.; <u>and</u></li> <li>b. Automatically detecting, classifying and determining the location of divers or swimmers;</li> </ol> <p><u><i>N.B.</i></u>  <i>For diver detection "software" or "source code", specially designed or modified for military use, see Division 2 of Part I of this Schedule.</i></p> </li> <li>b. Not used;</li> <li>c. "Software" designed or modified for cameras incorporating "focal plane arrays" specified in Category Code 6A002.a.3.f. and designed or modified to remove a frame rate restriction and allow the camera to exceed the frame rate specified in Category Code 6A003.b.4. Note 3.a.;</li> <li>d. Not used;</li> <li>e. Not used;</li> <li>f. "Software" as follows: <ol style="list-style-type: none"> <li>1. "Software" specially designed for magnetic and electric field "compensation systems" for magnetic sensors designed to operate on mobile platforms;</li> <li>2. "Software" specially designed for magnetic and electric field anomaly detection on mobile platforms;</li> </ol> </li> </ol>

<i>Category Code</i>	<i>Item Description</i>
	<p>3. “Software” specially designed for “real-time processing” of electromagnetic data using underwater electromagnetic receivers specified in Category Code 6A006.e.;</p> <p>4. “Source code” for “real-time processing” of electromagnetic data using underwater electromagnetic receivers specified in Category Code 6A006.e.;</p> <p>g. “Software” specially designed to correct motional influences of gravity meters or gravity gradiometers;</p> <p>h. “Software” as follows:</p> <ol style="list-style-type: none"> <li>1. Air Traffic Control (ATC) “software” application “programs” designed to be hosted on general purpose computers located at Air Traffic Control centres and capable of accepting radar target data from more than four primary radars;</li> <li>2. “Software” for the design or “production” of radomes and having all of the following: <ol style="list-style-type: none"> <li>a. Specially designed to protect the “electronically steerable phased array antennae” specified in Category Code 6A008.e.; <u>and</u></li> <li>b. Resulting in an antenna pattern having an ‘average side lobe level’ more than 40 dB below the peak of the main beam level.</li> </ol> </li> </ol> <p><i>Technical Note</i>  ‘Average side lobe level’ in Category Code 6D003.h.2.b. is measured over the entire array excluding the angular extent of the main beam and the first two side lobes on either side of the main beam.</p>
6D102	“Software” specially designed or modified for the “use” of goods specified in Category Code 6A108.

<i>Category Code</i>	<i>Item Description</i>
6D103	<p>“Software” which processes post-flight, recorded data, enabling determination of vehicle position throughout its flight path, specially designed or modified for ‘missiles’.</p>
	<p><u>Technical Note</u>  <i>In Category Code 6D103, ‘missile’ means complete rocket systems and unmanned aerial vehicle systems capable of a range exceeding 300 km.</i></p>
6D203	<p>“Software” specially designed to enhance or release the performance of cameras or imaging devices to meet the characteristics of Category Codes 6A203.a. to 6A203.c.</p>
<b>6E</b>	<b>Technology</b>
6E001	<p>“Technology” (according to the General Technology Note) for the “development” of equipment, materials or “software” specified in Category 6A, 6B, 6C or 6D.</p>
6E002	<p>“Technology” (according to the General Technology Note) for the “production” of equipment or materials specified in Category 6A, 6B or 6C.</p>
6E003	<p>Other “technology”, as follows:</p> <p>a. “Technology” as follows:</p> <ol style="list-style-type: none"> <li>1. Optical surface coating and treatment “technology”, “required” to achieve an ‘optical thickness’ uniformity of 99.5% or better for optical coatings 500 mm or more in diameter or major axis length and with a total loss (absorption and scatter) of less than <math>5 \times 10^{-3}</math>;</li> </ol> <p><u>N.B.</u>  <i>See also Category Code 2E003.f.</i></p> <p><u>Technical Note</u>  <i>‘Optical thickness’ is the mathematical product of the index of refraction and the physical thickness of the coating.</i></p>

<i>Category Code</i>	<i>Item Description</i>
	<p>2. Optical fabrication “technology” using single point diamond turning techniques to produce surface finish accuracies of better than 10 nm rms on non-planar surfaces exceeding 0.5 m<sup>2</sup>;</p> <p>b. “Technology” “required” for the “development”, “production” or “use” of specially designed diagnostic instruments or targets in test facilities for “SHPL” testing or testing or evaluation of materials irradiated by “SHPL” beams.</p>
6E101	<p>“Technology” (according to the General Technology Note) for the “use” of equipment or “software” specified in Category Code 6A002, 6A007.b. and .c., 6A008, 6A102, 6A107, 6A108, 6B108, 6D102 or 6D103.</p> <p><i>Note</i>  <i>Category Code 6E101 only specifies “technology” for equipment specified in Category Code 6A008 when it is designed for airborne applications and is usable in “missiles”.</i></p>
6E201	<p>“Technology” (according to the General Technology Note) for the “use” of equipment specified in Category Code 6A003, 6A005.a.2., 6A005.b.2., 6A005.b.3., 6A005.b.4., 6A005.b.6., 6A005.c.2., 6A005.d.3.c., 6A005.d.4.c., 6A202, 6A203, 6A205, 6A225 or 6A226.</p>
6E203	<p>“Technology”, in the form of codes or keys, to enhance or release the performance of cameras or imaging devices to meet the characteristics of Category Codes 6A203.a. to 6A203.c.</p>

<i>Category Code</i>	<i>Item Description</i>
<b>CATEGORY 7 — NAVIGATION AND AVIONICS</b>	
<b>7A</b>	<p><b>Systems, Equipment and Components</b></p> <p><u><i>N.B.</i></u>  <i>For automatic pilots for underwater vehicles, see Category 8. For radar, see Category 6.</i></p>
7A001	<p>Accelerometers as follows and specially designed components therefor:</p> <p><u><i>N.B.</i></u>  <i>See also Category Code 7A101.</i>  <i>For angular or rotational accelerometers, see Category Code 7A001.b.</i></p> <p>a. Linear accelerometers having any of the following:</p> <ol style="list-style-type: none"> <li>1. Specified to function at linear acceleration levels less than or equal to 15 g and having any of the following: <ol style="list-style-type: none"> <li>a. A “bias” “stability” of less (better) than 130 micro g with respect to a fixed calibration value over a period of one year; <u>or</u></li> <li>b. A “scale factor” “stability” of less (better) than 130 ppm with respect to a fixed calibration value over a period of one year;</li> </ol> </li> <li>2. Specified to function at linear acceleration levels exceeding 15 g but less than or equal to 100 g and having all of the following: <ol style="list-style-type: none"> <li>a. A “bias” “repeatability” of less (better) than 1,250 micro g over a period of one year; <u>and</u></li> <li>b. A “scale factor” “repeatability” of less (better) than 1,250 ppm over a period of one year; <u>or</u></li> </ol> </li> <li>3. Designed for use in inertial navigation or guidance systems and specified to function at linear acceleration levels exceeding 100 g;</li> </ol>

<i>Category Code</i>	<i>Item Description</i>
7A002	<p data-bbox="539 456 600 488"><u>Note</u></p> <p data-bbox="539 497 1262 591"><i>Category Codes 7A001.a.1. and 7A001.a.2. do not include accelerometers limited to measurement of only vibration or shock.</i></p> <p data-bbox="475 613 1262 680">b. Angular or rotational accelerometers, specified to function at linear acceleration levels exceeding 100 g.</p> <p data-bbox="475 748 1262 815">Gyros or angular rate sensors, having any of the following and specially designed components therefor:</p> <p data-bbox="475 837 536 869"><u>N.B.</u></p> <p data-bbox="475 878 852 909"><i>See also Category Code 7A102.</i></p> <p data-bbox="475 922 1262 990"><i>For angular or rotational accelerometers, see Category Code 7A001.b.</i></p> <p data-bbox="475 1012 1262 1079">a. Specified to function at linear acceleration levels less than or equal to 100 g and having any of the following:</p> <ol data-bbox="539 1088 1262 1393" style="list-style-type: none"> <li data-bbox="539 1088 1262 1155">1. A rate range of less than 500 degrees per second and having any of the following: <ol data-bbox="625 1169 1262 1393" style="list-style-type: none"> <li data-bbox="625 1169 1262 1303">a. A “bias” “stability” of less (better) than 0.5 degree per hour, when measured in a 1 g environment over a period of one month, and with respect to a fixed calibration value; <u>or</u></li> <li data-bbox="625 1326 1262 1393">b. An “angle random walk” of less (better) than or equal to 0.0035 degree per square root hour; <u>or</u></li> </ol> </li> </ol> <p data-bbox="689 1406 750 1438"><u>Note</u></p> <p data-bbox="689 1447 1262 1514"><i>Category Code 7A002.a.1.b. does not include “spinning mass gyros”.</i></p> <ol data-bbox="539 1527 1262 1827" style="list-style-type: none"> <li data-bbox="539 1527 1262 1594">2. A rate range greater than or equal to 500 degrees per second and having any of the following: <ol data-bbox="625 1608 1262 1827" style="list-style-type: none"> <li data-bbox="625 1608 1262 1742">a. A “bias” “stability” of less (better) than 4 degrees per hour, when measured in a 1 g environment over a period of three minutes, and with respect to a fixed calibration value; <u>or</u></li> <li data-bbox="625 1765 1262 1827">b. An “angle random walk” of less (better) than or equal to 0.1 degree per square root hour; <u>or</u></li> </ol> </li> </ol>

<i>Category Code</i>	<i>Item Description</i>
7A003	<p style="text-align: center;"><u>Note</u> Category Code 7A002.a.2.b. does not include “spinning mass gyros”.</p> <p>b. Specified to function at linear acceleration levels exceeding 100 g.</p> <p>‘Inertial measurement equipment or systems’, having any of the following:</p> <p><u>N.B.</u> See also Category Code 7A103.</p> <p><u>Note 1</u> ‘Inertial measurement equipment or systems’ incorporate accelerometers or gyroscopes to measure changes in velocity and orientation in order to determine or maintain heading or position without requiring an external reference once aligned. ‘Inertial measurement equipment or systems’ include:</p> <ul style="list-style-type: none"> <li>– Attitude and Heading Reference Systems (AHRSSs);</li> <li>– Gyrocompasses;</li> <li>– Inertial Measurement Units (IMUs);</li> <li>– Inertial Navigation Systems (INSs);</li> <li>– Inertial Reference Systems (IRSs);</li> <li>– Inertial Reference Units (IRUs).</li> </ul> <p><u>Note 2</u> Category Code 7A003 does not include ‘inertial measurement equipment or systems’ which are certified for use on “civil aircraft” by civil authorities of “participating states”.</p> <p><u>Technical Notes</u></p> <p>1. ‘Positional aiding references’ independently provide position, and include:</p> <ul style="list-style-type: none"> <li>a. Global Navigation Satellite Systems (GNSS);</li> <li>b. “Data-Based Referenced Navigation” (“DBRN”).</li> </ul>

Category Code	Item Description
	<p>2. ‘Circular Error Probable’ (‘CEP’) - In a circular normal distribution, the radius of the circle containing 50% of the individual measurements being made, or the radius of the circle within which there is a 50% probability of being located.</p> <p>a. Designed for “aircraft”, land vehicles or vessels, providing position without the use of ‘positional aiding references’, and having any of the following accuracies subsequent to normal alignment:</p> <ol style="list-style-type: none"> <li>1. 0.8 nautical miles per hour (nm/hr) ‘Circular Error Probable’ (‘CEP’) rate or less (better);</li> <li>2. 0.5 % distanced travelled ‘CEP’ or less (better); <u>or</u></li> <li>3. Total drift of 1 nautical mile ‘CEP’ or less (better) in a 24-hour period;</li> </ol> <p><u>Technical Note</u>  <i>The performance parameters in Category Codes 7A003.a.1., 7A003.a.2. and 7A003.a.3. typically apply to ‘inertial measurement equipment or systems’ designed for “aircraft”, vehicles and vessels, respectively. These parameters result from the utilisation of specialised non-positional aiding references (e.g. altimeter, odometer, velocity log). As a consequence, the specified performance values cannot be readily converted between these parameters. Equipment designed for multiple platforms are evaluated against each applicable Category Code 7A003.a.1., 7A003.a.2. or 7A003.a.3.</i></p> <p>b. Designed for “aircraft”, land vehicles or vessels, with an embedded ‘positional aiding reference’ and providing position after loss of all ‘positional aiding references’ for a period of up to 4 minutes, having an accuracy of less (better) than 10 meters ‘CEP’;</p> <p><u>Technical Note</u>  <i>Category Code 7A003.b. refers to systems in which ‘inertial measurement equipment or systems’ and other independent ‘positional aiding references’ are built into a single unit (i.e. embedded) in order to achieve improved performance.</i></p>



<i>Category Code</i>	<i>Item Description</i>
	<p>c. Designed for “aircraft”, land vehicles or vessels, providing heading or True North determination and having any of the following:</p> <ol style="list-style-type: none"> <li>1. A maximum operating angular rate less (lower) than 500 deg/s and a heading accuracy without the use of ‘positional aiding references’ equal to or less (better) than 0.07 deg sec(Lat) (equivalent to 6 arc minutes rms at 45 degrees latitude); <u>or</u></li> <li>2. A maximum operating angular rate equal to or greater (higher) than 500 deg/s and a heading accuracy without the use of ‘positional aiding references’ equal to or less (better) than 0.2 deg sec(Lat) (equivalent to 17 arc minutes rms at 45 degrees latitude); <u>or</u></li> </ol> <p>d. Providing acceleration measurements or angular rate measurements, in more than one dimension, and having any of the following:</p> <ol style="list-style-type: none"> <li>1. Performance specified by Category Code 7A001 or 7A002 along any axis, without the use of any aiding references; <u>or</u></li> <li>2. Being “space-qualified” and providing angular rate measurements having an “angle random walk” along any axis of less (better) than or equal to 0.1 degree per square root hour.</li> </ol> <p><i>Note</i>  <i>Category Code 7A003.d.2. does not include ‘inertial measurement equipment or systems’ that contain “spinning mass gyros” as the only type of gyro.</i></p>
7A004	<p>‘Star trackers’ and components therefor, as follows:</p> <p><u>N.B.</u>  <i>See also Category Code 7A104.</i></p> <p>a. ‘Star trackers’ with a specified azimuth accuracy of equal to or less (better) than 20 seconds of arc throughout the specified lifetime of the equipment;</p>

<i>Category Code</i>	<i>Item Description</i>
7A005	<p>b. Components specially designed for equipment specified in Category Code 7A004.a. as follows:</p> <ol style="list-style-type: none"> <li>1. Optical heads or baffles;</li> <li>2. Data processing units.</li> </ol> <p><i>Technical Note</i>  ‘Star trackers’ are also referred to as stellar attitude sensors or gyro-astro compasses.</p> <p>Global Navigation Satellite Systems (GNSS) receiving equipment having any of the following and specially designed components therefor:</p> <p><i>N.B.</i>  See also Category Code 7A105.  For equipment specially designed for military use, see Division 2 of Part I of this Schedule.</p> <ol style="list-style-type: none"> <li>a. Employing a decryption algorithm specially designed or modified for government use to access the ranging code for position and time; <u>or</u></li> <li>b. Employing ‘adaptive antenna systems’.</li> </ol> <p><i>Note</i>  Category Code 7A005.b. does not include GNSS receiving equipment that only uses components designed to filter, switch or combine signals from multiple omni-directional antennae that do not implement adaptive antenna techniques.</p> <p><i>Technical Note</i>  For the purpose of Category Code 7A005.b., ‘adaptive antenna systems’ dynamically generate one or more spatial nulls in an antenna array pattern by signal processing in the time domain or frequency domain.</p>

<i>Category Code</i>	<i>Item Description</i>
7A006	<p>Airborne altimeters operating at frequencies other than 4.2 GHz to 4.4 GHz inclusive and having any of the following:</p> <p><u>N.B.</u> See also Category Code 7A106.</p> <p>a. “Power management”; <u>or</u></p> <p>b. Using phase shift key modulation.</p>
7A008	<p>Underwater sonar navigation systems using doppler velocity or correlation velocity logs integrated with a heading source and having a positioning accuracy of equal to or less (better) than 3% of distance travelled ‘Circular Error Probable’ (‘CEP’) and specially designed components therefor.</p> <p><u>Note</u> Category Code 7A008 does not include systems specially designed for installation on surface vessels or systems requiring acoustic beacons or buoys to provide positioning data.</p> <p><u>N.B.</u> See Category Code 6A001.a. for acoustic systems, and Category Code 6A001.b. for correlation-velocity and Doppler-velocity sonar log equipment. See Category Code 8A002 for other marine systems.</p>
7A101	<p>Linear accelerometers, other than those specified in Category Code 7A001, designed for use in inertial navigation systems or in guidance systems of all types, usable in ‘missiles’, having all the following characteristics, and specially designed components therefor:</p> <p>a. A “bias” “repeatability” of less (better) than 1,250 micro g; <u>and</u></p> <p>b. A “scale factor” “repeatability” of less (better) than 1,250 ppm.</p> <p><u>Note</u> Category Code 7A101 does not include accelerometers specially designed and developed as Measurement While Drilling (MWD) Sensors for use in downhole well service operations.</p>

<i>Category Code</i>	<i>Item Description</i>
	<p><u>Technical Notes</u></p> <ol style="list-style-type: none"> <li data-bbox="475 495 1272 595">1. In Category Code 7A101, 'missile' means complete rocket systems and unmanned aerial vehicle systems capable of a range exceeding 300 km;</li> <li data-bbox="475 607 1272 707">2. In Category Code 7A101, the measurement of "bias" and "scale factor" refers to a one sigma standard deviation with respect to a fixed calibration over a period of one year.</li> </ol>
7A102	<p>All types of gyros, other than those specified in Category Code 7A002, usable in 'missiles', with a rated "drift rate" 'stability' of less than 0.5° (1 sigma or rms) per hour in a 1 g environment and specially designed components therefor.</p> <p><u>Technical Notes</u></p> <ol style="list-style-type: none"> <li data-bbox="475 965 1272 1066">1. In Category Code 7A102, 'missile' means complete rocket systems and unmanned aerial vehicle systems capable of a range exceeding 300 km.</li> <li data-bbox="475 1077 1272 1245">2. In Category Code 7A102, 'stability' is defined as a measure of the ability of a specific mechanism or performance coefficient to remain invariant when continuously exposed to a fixed operating condition (IEEE STD 528-2001 paragraph 2.247).</li> </ol>
7A103	<p>Instrumentation, navigation equipment and systems, other than those specified in Category Code 7A003, as follows; and specially designed components therefor:</p> <ol style="list-style-type: none"> <li data-bbox="475 1424 1272 1758">a. Inertial or other equipment, using accelerometers or gyros as follows, and systems incorporating such equipment: <ol style="list-style-type: none"> <li data-bbox="539 1503 1272 1603">1. Accelerometers specified in Category Code 7A001.a.3., 7A001.b. or 7A101 or gyros specified in Category Code 7A002 or 7A102;</li> <li data-bbox="539 1615 1272 1758">2. Accelerometers specified in Category Code 7A001.a.1. or 7A001.a.2., designed for use in inertial navigation systems or in guidance systems of all types, and usable in 'missiles';</li> </ol> </li> </ol>

Category Code	Item Description
	<p data-bbox="539 454 600 483"><u>Note</u></p> <p data-bbox="539 495 1267 663"><i>Category Code 7A103.a. does not include equipment containing accelerometers specified in Category Code 7A001 where such accelerometers are specially designed and developed as MWD (Measurement While Drilling) sensors for use in down-hole well services operations.</i></p> <p data-bbox="475 678 1267 779">b. Integrated flight instrument systems which include gyrostabilisers or automatic pilots, designed or modified for use in ‘missiles’;</p> <p data-bbox="475 795 1267 896">c. ‘Integrated navigation systems’, designed or modified for ‘missiles’ and capable of providing a navigational accuracy of 200 m Circle of Equal Probability (CEP) or less;</p> <p data-bbox="539 911 724 940"><u>Technical Note</u></p> <p data-bbox="539 952 1267 1019"><i>An ‘integrated navigation system’ typically incorporates the following components:</i></p> <ol data-bbox="539 1030 1267 1344" style="list-style-type: none"> <li data-bbox="539 1030 1267 1131">1. <i>An inertial measurement device (e.g. an attitude and heading reference system, inertial reference unit, or inertial navigation system);</i></li> <li data-bbox="539 1142 1267 1310">2. <i>One or more external sensors used to update the position and/or velocity, either periodically or continuously throughout the flight (e.g. satellite navigation receiver, radar altimeter, and/or Doppler radar); and</i></li> <li data-bbox="539 1321 1029 1344">3. <i>Integration hardware and software.</i></li> </ol> <p data-bbox="475 1361 1267 1529">d. Three axis magnetic heading sensors, designed or modified to be integrated with flight control and navigation systems, other than those specified in Category Code 6A006, having all the following characteristics, and specially designed components therefor:</p> <ol data-bbox="539 1545 1267 1736" style="list-style-type: none"> <li data-bbox="539 1545 1267 1624">1. <i>Internal tilt compensation in pitch (<math>\pm 90</math> degrees) and roll (<math>\pm 180</math> degrees) axes; and</i></li> <li data-bbox="539 1635 1267 1736">2. <i>Capable of providing azimuthal accuracy better (less) than 0.5 degrees rms at latitude of <math>\pm 80</math> degrees, reference to local magnetic field.</i></li> </ol> <p data-bbox="539 1751 600 1780"><u>Note</u></p> <p data-bbox="539 1792 1267 1890"><i>Flight control and navigation systems in Category Code 7A103.d. include gyrostabilisers, automatic pilots and inertial navigation systems.</i></p>

<i>Category Code</i>	<i>Item Description</i>
	<p><u>Technical Note</u>  <i>In Category Code 7A103, 'missile' means complete rocket systems and unmanned aerial vehicle systems capable of a range exceeding 300 km.</i></p>
7A104	<p>Gyro-astro compasses and other devices, other than those specified in Category Code 7A004, which derive position or orientation by means of automatically tracking celestial bodies or satellites and specially designed components therefor.</p>
7A105	<p>Receiving equipment for Global Navigation Satellite Systems (GNSS; e.g. GPS, GLONASS, or Galileo), other than those specified in Category Code 7A005, having any of the following characteristics, and specially designed components therefor:</p> <ol style="list-style-type: none"> <li>a. Designed or modified for use in space launch vehicles specified in Category Code 9A004, unmanned aerial vehicles specified in Category Code 9A012 or sounding rockets specified in Category Code 9A104; <u>or</u></li> <li>b. Designed or modified for airborne applications and having any of the following: <ol style="list-style-type: none"> <li>1. Capable of providing navigation information at speeds in excess of 600 m/s;</li> <li>2. Employing decryption, designed or modified for military or governmental services, to gain access to GNSS secured signal/data; <u>or</u></li> <li>3. Being specially designed to employ anti-jam features (e.g. null steering antenna or electronically steerable antenna) to function in an environment of active or passive countermeasures.</li> </ol> </li> </ol> <p><u>Note</u>  <i>Category Codes 7A105.b.2. and 7A105.b.3. do not include equipment designed for commercial, civil or 'Safety of Life' (e.g. data integrity, flight safety) GNSS services.</i></p>

<i>Category Code</i>	<i>Item Description</i>
7A106	Altimeters, other than those specified in Category Code 7A006, of radar or laser radar type, designed or modified for use in space launch vehicles specified in Category Code 9A004 or sounding rockets specified in Category Code 9A104.
7A115	Passive sensors for determining bearing to specific electromagnetic source (direction finding equipment) or terrain characteristics, designed or modified for use in space launch vehicles specified in Category Code 9A004 or sounding rockets specified in Category Code 9A104.
	<p data-bbox="464 837 539 869"><u>Note</u></p> <p data-bbox="464 875 1272 943"><i>Category Code 7A115 includes sensors for the following equipment:</i></p> <ul style="list-style-type: none"> <li data-bbox="464 958 986 990">a. <i>Terrain contour mapping equipment;</i></li> <li data-bbox="464 1003 1166 1034">b. <i>Imaging sensor equipment (both active and passive);</i></li> <li data-bbox="464 1048 948 1079">c. <i>Passive interferometer equipment.</i></li> </ul>
7A116	<p data-bbox="464 1160 1272 1279">Flight control systems and servo valves, as follows; designed or modified for use in space launch vehicles specified in Category Code 9A004 or sounding rockets specified in Category Code 9A104:</p> <ul style="list-style-type: none"> <li data-bbox="464 1301 1272 1406">a. Hydraulic, mechanical, electro-optical, or electro-mechanical flight control systems (including fly-by-wire types);</li> <li data-bbox="464 1420 874 1451">b. Attitude control equipment;</li> <li data-bbox="464 1464 1272 1637">c. Flight control servo valves designed or modified for the systems specified in Category Code 7A116.a. or 7A116.b., and designed or modified to operate in a vibration environment greater than 10 g rms between 20 Hz and 2 kHz.</li> </ul>
7A117	“Guidance sets”, usable in “missiles” capable of achieving system accuracy of 3.33% or less of the range (e.g. a “CEP” of 10 km or less at a range of 300 km).

<i>Category Code</i>	<i>Item Description</i>
<b>7B</b>	<b>Test, Inspection and Production Equipment</b>
7B001	<p data-bbox="475 499 1268 566">Test, calibration or alignment equipment, specially designed for equipment specified in Category 7A.</p> <p data-bbox="475 589 1268 622"><i>Note</i></p> <p data-bbox="475 633 1268 723"><i>Category Code 7B001 does not include test, calibration or alignment equipment for ‘Maintenance Level I’ or ‘Maintenance Level II’.</i></p> <p data-bbox="475 745 1268 779"><i>Technical Notes</i></p> <ol data-bbox="475 790 1268 1541" style="list-style-type: none"> <li data-bbox="475 790 1268 1059">1. <u><i>‘Maintenance Level I’</i></u>  <i>The failure of an inertial navigation unit is detected on the aircraft by indications from the Control and Display Unit (CDU) or by the status message from the corresponding subsystem. By following the manufacturer’s manual, the cause of the failure may be localised at the level of the malfunctioning Line Replaceable Unit (LRU). The operator then removes the LRU and replaces it with a spare.</i> </li> <li data-bbox="475 1081 1268 1541">2. <u><i>‘Maintenance Level II’</i></u>  <i>The defective LRU is sent to the maintenance workshop (the manufacturer’s or that of the operator responsible for level II maintenance). At the maintenance workshop, the malfunctioning LRU is tested by various appropriate means to verify and localise the defective Shop Replaceable Assembly (SRA) module responsible for the failure. This SRA is removed and replaced by an operative spare. The defective SRA (or possibly the complete LRU) is then shipped to the manufacturer. ‘Maintenance Level II’ does not include the disassembly or repair of controlled accelerometers or gyro sensors.</i> </li> </ol>



<i>Category Code</i>	<i>Item Description</i>
7B002	<p>Equipment specially designed to characterise mirrors for ring “laser” gyros, as follows:</p> <p><u><i>N.B.</i></u>  <i>See also Category Code 7B102.</i></p> <ol style="list-style-type: none"> <li>a. Scatterometers having a measurement accuracy of 10 ppm or less (better);</li> <li>b. Profilometers having a measurement accuracy of 0.5 nm (5 angstrom) or less (better).</li> </ol>
7B003	<p>Equipment specially designed for the “production” of equipment specified in Category 7A.</p> <p><u><i>Note</i></u>  <i>Category Code 7B003 includes:</i></p> <ul style="list-style-type: none"> <li>– <i>Gyro tuning test stations;</i></li> <li>– <i>Gyro dynamic balance stations;</i></li> <li>– <i>Gyro run-in/motor test stations;</i></li> <li>– <i>Gyro evacuation and fill stations;</i></li> <li>– <i>Centrifuge fixtures for gyro bearings;</i></li> <li>– <i>Accelerometer axis align stations;</i></li> <li>– <i>Fibre optic gyro coil winding machines.</i></li> </ul>
7B102	<p>Reflectometers specially designed to characterise mirrors, for “laser” gyros, having a measurement accuracy of 50 ppm or less (better).</p>
7B103	<p>“Production facilities” and “production equipment” as follows:</p> <ol style="list-style-type: none"> <li>a. “Production facilities” specially designed for equipment specified in Category Code 7A117;</li> <li>b. “Production equipment”, and other test, calibration and alignment equipment, other than that specified in Category Codes 7B001 to 7B003, designed or modified to be used with equipment specified in Category 7A.</li> </ol>

<i>Category Code</i>	<i>Item Description</i>
<b>7C</b>	<b>Materials</b> None.
<b>7D</b>	<b>Software</b>
7D001	“Software” specially designed or modified for the “development” or “production” of equipment specified in Category 7A or 7B.
7D002	“Source code” for the operation or maintenance of any inertial navigation equipment, including inertial equipment not specified in Category Code 7A003 or 7A004, or Attitude and Heading Reference Systems (‘AHRs’).  <i>Note</i> <i>Category Code 7D002 does not include “source code” for the “use” of gimballed ‘AHRs’.</i>  <i>Technical Note</i> <i>‘AHRs’ generally differ from Inertial Navigation Systems (INS) in that an ‘AHRs’ provides attitude and heading information and normally does not provide the acceleration, velocity and position information associated with an INS.</i>
7D003	Other “software” as follows: a. “Software” specially designed or modified to improve the operational performance or reduce the navigational error of systems to the levels specified in Category Code 7A003, 7A004 or 7A008; b. “Source code” for hybrid integrated systems which improves the operational performance or reduces the navigational error of systems to the level specified in Category Code 7A003 or 7A008 by continuously combining heading data with any of the following: 1. Doppler radar or sonar velocity data; 2. Global Navigation Satellite Systems (GNSS) reference data; <u>or</u> 3. Data from “Data-Based Referenced Navigation” (“DBRN”) systems;

<i>Category Code</i>	<i>Item Description</i>
7D004	<p>c. Not used;</p> <p>d. Not used;</p> <p>e. Computer-Aided-Design (CAD) “software” specially designed for the “development” of “active flight control systems”, helicopter multi-axis fly-by-wire or fly-by-light controllers or helicopter “circulation controlled anti-torque or circulation-controlled direction control systems”, whose “technology” is specified in Category Code 7E004.b., 7E004.c.1. or 7E004.c.2.</p> <p>“Source code” incorporating “development” “technology” specified in Category Code 7E004.a.2., 7E004.a.3., 7E004.a.5., 7E004.a.6. or 7E004.b., for any of the following:</p> <p>a. Digital flight management systems for “total control of flight”;</p> <p>b. Integrated propulsion and flight control systems;</p> <p>c. Fly-by-wire or fly-by-light control systems;</p> <p>d. Fault-tolerant or self-reconfiguring “active flight control systems”;</p> <p>e. Not used;</p> <p>f. Air data systems based on surface static data; <u>or</u></p> <p>g. Three dimensional displays.</p> <p><i>Note</i>  <i>Category Code 7D004 does not include “source code” associated with common computer elements and utilities (e.g. input signal acquisition, output signal transmission, computer program and data loading, built-in test, task scheduling mechanisms) not providing a specific flight control system function.</i></p>
7D005	<p>“Software” specially designed to decrypt Global Navigation Satellite Systems (GNSS) ranging code designed for government use.</p>

<i>Category Code</i>	<i>Item Description</i>
7D101	“Software” specially designed or modified for the “use” of equipment specified in Category Code 7A001 to 7A006, 7A101 to 7A106, 7A115, 7A116.a., 7A116.b., 7B001, 7B002, 7B003, 7B102 or 7B103.
7D102	<p>Integration “software” as follows:</p> <ol style="list-style-type: none"> <li>a. Integration “software” for the equipment specified in Category Code 7A103.b.;</li> <li>b. Integration “software” specially designed for the equipment specified in Category Code 7A003 or 7A103.a.;</li> <li>c. Integration “software” designed or modified for the equipment specified in Category Code 7A103.c.</li> </ol> <p><u>Note</u>  <i>A common form of integration “software” employs Kalman filtering.</i></p>
7D103	<p>“Software” specially designed for modelling or simulation of the “guidance sets” specified in Category Code 7A117 or for their design integration with the space launch vehicles specified in Category Code 9A004 or sounding rockets specified in Category Code 9A104.</p> <p><u>Note</u>  <i>“Software” specified in Category Code 7D103 remains within the description in that Category when combined with specially designed hardware specified in Category Code 4A102.</i></p>
<b>7E</b>	<b>Technology</b>
7E001	<p>“Technology” (according to the General Technology Note) for the “development” of equipment or “software”, specified in Category 7A, 7B or Category Codes 7D001, 7D002, 7D003, 7D005 and 7D101 to 7D103.</p> <p><u>Note</u>  <i>Category Code 7E001 includes key management “technology” exclusively for equipment specified in Category Code 7A005.a.</i></p>

<i>Category Code</i>	<i>Item Description</i>
7E002	“Technology” (according to the General Technology Note) for the “production” of equipment specified in Category 7A or 7B.
7E003	<p>“Technology” (according to the General Technology Note) for the repair, refurbishing or overhaul of equipment specified in Category Codes 7A001 to 7A004.</p> <p><u>Note</u>  <i>Category Code 7E003 does not include maintenance “technology” directly associated with calibration, removal or replacement of damaged or unserviceable LRUs and SRAs of a “civil aircraft” as described in ‘Maintenance Level I’ or ‘Maintenance Level II’.</i></p> <p><u>N.B.</u>  <i>See Technical Notes to Category Code 7B001.</i></p>
7E004	<p>Other “technology” as follows:</p> <p>a. “Technology” for the “development” or “production” of any of the following:</p> <ol style="list-style-type: none"> <li>1. Not used;</li> <li>2. Air data systems based on surface static data only, i.e. which dispense with conventional air data probes;</li> <li>3. Three dimensional displays for “aircraft”;</li> <li>4. Not used;</li> <li>5. Electric actuators (i.e. electromechanical, electrohydrostatic and integrated actuator package) specially designed for “primary flight control”;</li> <li>6. “Flight control optical sensor array” specially designed for implementing “active flight control systems”; <u>or</u></li> <li>7. “DBRN” systems designed to navigate underwater, using sonar or gravity databases, that provide a positioning accuracy equal to or less (better) than 0.4 nautical miles;</li> </ol> <p>b. “Development” “technology”, as follows, for “active flight control systems” (including fly-by-wire or fly-by-light):</p>

<i>Category Code</i>	<i>Item Description</i>
	<ol style="list-style-type: none"> <li data-bbox="539 456 1268 622">1. Photonic-based “technology” for sensing aircraft or flight control component state, transferring flight control data, or commanding actuator movement, “required” for fly-by-light “active flight control systems”;</li> <li data-bbox="539 640 719 674">2. Not used;</li> <li data-bbox="539 692 1268 824">3. Real-time algorithms to analyse component sensor information to predict and preemptively mitigate impending degradation and failures of components within an “active flight control system”;</li> </ol> <p data-bbox="603 842 663 875"><i>Note</i></p> <p data-bbox="603 882 1268 949"><i>Category Code 7E004.b.3. does not include algorithms for purpose of off-line maintenance.</i></p> <ol style="list-style-type: none"> <li data-bbox="539 967 1268 1099">4. Real-time algorithms to identify component failures and reconfigure force and moment controls to mitigate “active flight control system” degradations and failures;</li> </ol> <p data-bbox="603 1117 663 1151"><i>Note</i></p> <p data-bbox="603 1158 1268 1290"><i>Category Code 7E004.b.4. does not include algorithms for the elimination of fault effects through comparison of redundant data sources, or off-line pre-planned responses to anticipated failures.</i></p> <ol style="list-style-type: none"> <li data-bbox="539 1308 1268 1417">5. Integration of digital flight control, navigation and propulsion control data, into a digital flight management system for “total control of flight”;</li> </ol> <p data-bbox="603 1435 663 1469"><i>Note</i></p> <p data-bbox="603 1476 1134 1509"><i>Category Code 7E004.b.5. does not include:</i></p> <ol style="list-style-type: none"> <li data-bbox="624 1527 1268 1659">a. “Development” “technology” for integration of digital flight control, navigation and propulsion control data, into a digital flight management system for “flight path optimisation”;</li> <li data-bbox="624 1677 1268 1809">b. “Development” “technology” for “aircraft” flight instrument systems integrated solely for VOR, DME, ILS or MLS navigation or approaches.</li> </ol> <ol style="list-style-type: none"> <li data-bbox="539 1827 719 1861">6. Not used;</li> </ol>

<i>Category Code</i>	<i>Item Description</i>
	<p data-bbox="539 454 600 483"><u>Note</u></p> <p data-bbox="539 495 1260 696"><i>Category Code 7E004.b. does not include technology associated with common computer elements and utilities (e.g. input signal acquisition, output signal transmission, computer program and data loading, built-in test, task scheduling mechanisms) not providing a specific flight control system function.</i></p> <p data-bbox="475 712 1260 779">c. “Technology” for the “development” of helicopter systems, as follows:</p> <ol data-bbox="539 795 1260 1243" style="list-style-type: none"> <li data-bbox="539 795 1260 896">1. Multi-axis fly-by-wire or fly-by-light controllers, which combine the functions of at least two of the following into one controlling element: <ol data-bbox="624 913 922 1041" style="list-style-type: none"> <li data-bbox="624 913 922 947">a. Collective controls;</li> <li data-bbox="624 965 922 999">b. Cyclic controls;</li> <li data-bbox="624 1016 922 1050">c. Yaw controls;</li> </ol> </li> <li data-bbox="539 1059 1260 1126">2. “Circulation-controlled anti-torque or circulation-controlled directional control systems”;</li> <li data-bbox="539 1144 1260 1243">3. Rotor blades incorporating “variable geometry airfoils”, for use in systems using individual blade control.</li> </ol>
7E101	<p data-bbox="475 1310 1260 1444">“Technology” (according to the General Technology Note) for the “use” of equipment specified in Category Codes 7A001 to 7A006, 7A101 to 7A106, 7A115 to 7A117, 7B001, 7B002, 7B003, 7B102, 7B103, 7D101 to 7D103.</p>
7E102	<p data-bbox="475 1512 1260 1612">“Technology” for protection of avionics and electrical subsystems against electromagnetic pulse (EMP) and electromagnetic interference (EMI) hazards, from external sources, as follows:</p> <ol data-bbox="475 1630 1260 1825" style="list-style-type: none"> <li data-bbox="475 1630 1260 1664">a. Design “technology” for shielding systems;</li> <li data-bbox="475 1682 1260 1749">b. Design “technology” for the configuration of hardened electrical circuits and subsystems;</li> <li data-bbox="475 1767 1260 1825">c. Design “technology” for the determination of hardening criteria of Category Codes 7E102.a. and 7E102.b.</li> </ol>

<i>Category Code</i>	<i>Item Description</i>
7E104	“Technology” for the integration of the flight control, guidance, and propulsion data into a flight management system for optimisation of rocket system trajectory.



<i>Category Code</i>	<i>Item Description</i>
<b>CATEGORY 8 — MARINE</b>	
<b>8A</b>	<b>Systems, Equipment and Components</b>
8A001	<p>Submersible vehicles and surface vessels, as follows:</p> <p><u><i>N.B.</i></u>  <i>For equipment for submersible vehicles, see:</i></p> <ul style="list-style-type: none"> <li>– <i>Category 5, Part 2 “Information Security” for encrypted communication equipment;</i></li> <li>– <i>Category 6 for sensors;</i></li> <li>– <i>Categories 7 and 8 for navigation equipment;</i></li> <li>– <i>Category 8A for underwater equipment.</i></li> </ul> <p>a. Manned, tethered submersible vehicles designed to operate at depths exceeding 1,000 m;</p> <p>b. Manned, untethered submersible vehicles having any of the following:</p> <ol style="list-style-type: none"> <li>1. Designed to ‘operate autonomously’ and having a lifting capacity of all the following: <ol style="list-style-type: none"> <li>a. 10% or more of their weight in air; <u>and</u></li> <li>b. 15 kN or more;</li> </ol> </li> <li>2. Designed to operate at depths exceeding 1,000 m; <u>or</u></li> <li>3. Having all of the following: <ol style="list-style-type: none"> <li>a. Designed to continuously ‘operate autonomously’ for 10 hours or more; <u>and</u></li> <li>b. ‘Range’ of 25 nautical miles or more;</li> </ol> </li> </ol> <p><u><i>Technical Notes</i></u></p> <ol style="list-style-type: none"> <li>1. <i>For the purpose of Category Code 8A001.b., ‘operate autonomously’ means fully submerged, without snorkel, all systems working and cruising at minimum speed at which the submersible can safely control its depth dynamically by using its depth planes only, with no need for a support vessel or support base on the surface, sea-bed or shore, and containing a propulsion system for submerged or surface use.</i></li> </ol>

<i>Category Code</i>	<i>Item Description</i>
	<p data-bbox="539 454 1262 555">2. For the purpose of Category Code 8A001.b., 'range' means half the maximum distance a submersible vehicle can 'operate autonomously'.</p> <p data-bbox="475 573 1262 674">c. Unmanned, tethered submersible vehicles designed to operate at depths exceeding 1,000 m and having any of the following:</p> <ol data-bbox="539 689 1262 837" style="list-style-type: none"> <li data-bbox="539 689 1262 790">1. Designed for self-propelled manoeuvre using propulsion motors or thrusters specified in Category Code 8A002.a.2.; <u>or</u></li> <li data-bbox="539 801 852 837">2. Fibre optic data link;</li> </ol> <p data-bbox="475 855 1262 920">d. Unmanned, untethered submersible vehicles having any of the following:</p> <ol data-bbox="539 936 1262 1137" style="list-style-type: none"> <li data-bbox="539 936 1262 1037">1. Designed for deciding a course relative to any geographical reference without real-time human assistance;</li> <li data-bbox="539 1048 1018 1084">2. Acoustic data or command link; <u>or</u></li> <li data-bbox="539 1095 1198 1137">3. Optical data or command link exceeding 1,000 m;</li> </ol> <p data-bbox="475 1155 1262 1256">e. Ocean salvage systems with a lifting capacity exceeding 5 MN for salvaging objects from depths exceeding 250 m and having any of the following:</p> <ol data-bbox="539 1272 1262 1518" style="list-style-type: none"> <li data-bbox="539 1272 1262 1373">1. Dynamic positioning systems capable of position keeping within 20 m of a given point provided by the navigation system; <u>or</u></li> <li data-bbox="539 1384 1262 1518">2. Seafloor navigation and navigation integration systems, for depths exceeding 1,000 m and with positioning accuracies to within 10 m of a predetermined point;</li> </ol> <p data-bbox="475 1536 1262 1601">f. Surface-effect vehicles (fully skirted variety) having all of the following:</p> <ol data-bbox="539 1617 1262 1854" style="list-style-type: none"> <li data-bbox="539 1617 1262 1718">1. Maximum design speed, fully loaded, exceeding 30 knots in a significant wave height of 1.25 m (Sea State 3) or more;</li> <li data-bbox="539 1729 1107 1765">2. Cushion pressure exceeding 3,830 Pa; <u>and</u></li> <li data-bbox="539 1776 1262 1854">3. Light-ship-to-full-load displacement ratio of less than 0.70;</li> </ol>

<i>Category Code</i>	<i>Item Description</i>
	<p>g. Surface-effect vehicles (rigid sidewalls) with a maximum design speed, fully loaded, exceeding 40 knots in a significant wave height of 3.25 m (Sea State 5) or more;</p> <p>h. Hydrofoil vessels with active systems for automatically controlling foil systems, with a maximum design speed, fully loaded, of 40 knots or more in a significant wave height of 3.25 m (Sea State 5) or more;</p> <p>i. ‘Small waterplane area vessels’ having any of the following:</p> <ol style="list-style-type: none"> <li>1. Full load displacement exceeding 500 tonnes with a maximum design speed, fully loaded, exceeding 35 knots in a significant wave height of 3.25 m (Sea State 5) or more; <u>or</u></li> <li>2. Full load displacement exceeding 1,500 tonnes with a maximum design speed, fully loaded, exceeding 25 knots in a significant wave height of 4 m (Sea State 6) or more.</li> </ol> <p><u>Technical Note</u>  <i>A ‘small waterplane area vessel’ is defined by the following formula: waterplane area at an operational design draught less than <math>2 \times (\text{displaced volume at the operational design draught})^{2/3}</math>.</i></p>
8A002	<p>Marine systems, equipment and components, as follows:</p> <p><u>N.B.</u>  <i>For underwater communications systems, see Category 5 – Part 1 – Telecommunications.</i></p> <p>a. Systems, equipment and components, specially designed or modified for submersible vehicles and designed to operate at depths exceeding 1,000 m, as follows:</p> <ol style="list-style-type: none"> <li>1. Pressure housings or pressure hulls with a maximum inside chamber diameter exceeding 1.5 m;</li> <li>2. Direct current propulsion motors or thrusters;</li> <li>3. Umbilical cables, and connectors therefor, using optical fibre and having synthetic strength members;</li> <li>4. Components manufactured from material specified in Category Code 8C001;</li> </ol>

<i>Category Code</i>	<i>Item Description</i>
	<p data-bbox="603 454 788 488"><i><u>Technical Note</u></i></p> <p data-bbox="603 495 1262 629"><i>Category Code 8A002.a.4. includes 'syntactic foam' specified in Category Code 8C001 when an intermediate stage of manufacture has been performed and it is not yet in the final component form.</i></p> <p data-bbox="475 645 1262 779">b. Systems specially designed or modified for the automated control of the motion of submersible vehicles specified in Category Code 8A001, using navigation data, having closed loop servo-controls and having any of the following:</p> <ol data-bbox="539 792 1262 1032" style="list-style-type: none"> <li data-bbox="539 792 1262 864">1. Enabling a vehicle to move within 10 m of a predetermined point in the water column;</li> <li data-bbox="539 878 1262 949">2. Maintaining the position of the vehicle within 10 m of a predetermined point in the water column; <u>or</u></li> <li data-bbox="539 963 1262 1032">3. Maintaining the position of the vehicle within 10 m while following a cable on or under the seabed;</li> </ol> <p data-bbox="475 1046 975 1079">c. Fibre optic pressure hull penetrators;</p> <p data-bbox="475 1093 995 1126">d. Underwater vision systems as follows:</p> <ol data-bbox="539 1142 1262 1796" style="list-style-type: none"> <li data-bbox="539 1142 1262 1176">1. Television systems and television cameras, as follows: <ol data-bbox="624 1191 1262 1796" style="list-style-type: none"> <li data-bbox="624 1191 1262 1395">a. Television systems (comprising camera, monitoring and signal transmission equipment) having a 'limiting resolution' when measured in air of more than 800 lines and specially designed or modified for remote operation with a submersible vehicle;</li> <li data-bbox="624 1408 1262 1512">b. Underwater television cameras having a 'limiting resolution' when measured in air of more than 1,100 lines;</li> <li data-bbox="624 1525 1262 1628">c. Low light level television cameras specially designed or modified for underwater use and having all of the following: <ol data-bbox="687 1644 1262 1796" style="list-style-type: none"> <li data-bbox="687 1644 1262 1715">1. Image intensifier tubes specified in Category Code 6A002.a.2.a.; <u>and</u></li> <li data-bbox="687 1729 1262 1796">2. More than 150,000 "active pixels" per solid state area array;</li> </ol> </li> </ol> </li> </ol>

Category Code	Item Description
	<p data-bbox="603 454 786 483"><u>Technical Note</u></p> <p data-bbox="603 495 1268 663"><i>'Limiting resolution' is a measure of horizontal resolution usually expressed in terms of the maximum number of lines per picture height discriminated on a test chart, using IEEE Standard 208/1960 or any equivalent standard.</i></p> <ol style="list-style-type: none"> <li data-bbox="539 678 1268 813">2. Systems specially designed or modified for remote operation with an underwater vehicle, employing techniques to minimise the effects of back scatter and including range-gated illuminators or "laser" systems;</li> </ol> <p data-bbox="475 831 1268 931">e. Photographic still cameras specially designed or modified for underwater use below 150 m, with a film format of 35 mm or larger and having any of the following:</p> <ol style="list-style-type: none"> <li data-bbox="539 947 1268 1014">1. Annotation of the film with data provided by a source external to the camera;</li> <li data-bbox="539 1030 1268 1059">2. Automatic back focal distance correction; <u>or</u></li> <li data-bbox="539 1075 1268 1176">3. Automatic compensation control specially designed to permit an underwater camera housing to be usable at depths exceeding 1,000 m;</li> </ol> <p data-bbox="475 1193 659 1223">f. Not used;</p> <p data-bbox="475 1240 1268 1308">g. Light systems specially designed or modified for underwater use, as follows:</p> <ol style="list-style-type: none"> <li data-bbox="539 1323 1268 1424">1. Stroboscopic light systems capable of a light output energy of more than 300 J per flash and a flash rate of more than 5 flashes per second;</li> <li data-bbox="539 1440 1268 1507">2. Argon arc light systems specially designed for use below 1,000 m;</li> </ol> <p data-bbox="475 1525 1268 1626">h. "Robots" specially designed for underwater use, controlled by using a dedicated computer and having any of the following:</p> <ol style="list-style-type: none"> <li data-bbox="539 1641 1268 1809">1. Systems that control the "robot" using information from sensors which measure force or torque applied to an external object, distance to an external object, or tactile sense between the "robot" and an external object; <u>or</u></li> </ol>

<i>Category Code</i>	<i>Item Description</i>
	<p>2. The ability to exert a force of 250 N or more or a torque of 250 Nm or more and using titanium based alloys or “composite” “fibrous or filamentary materials” in their structural members;</p> <p>i. Remotely controlled articulated manipulators specially designed or modified for use with submersible vehicles and having any of the following:</p> <p>1. Systems which control the manipulator using information from sensors which measure any of the following:</p> <p>a. Torque or force applied to an external object; <u>or</u></p> <p>b. Tactile sense between the manipulator and an external object; <u>or</u></p> <p>2. Controlled by proportional master-slave techniques and having 5 degrees of ‘freedom of movement’ or more;</p> <p><i><u>Technical Note</u></i>  <i>Only functions having proportionally related motion control using positional feedback are counted when determining the number of degrees of ‘freedom of movement’.</i></p> <p>j. Air independent power systems specially designed for underwater use, as follows:</p> <p>1. Brayton or Rankine cycle engine air independent power systems having any of the following:</p> <p>a. Chemical scrubber or absorber systems, specially designed to remove carbon dioxide, carbon monoxide and particulates from recirculated engine exhaust;</p> <p>b. Systems specially designed to use a monoatomic gas;</p> <p>c. Devices or enclosures, specially designed for underwater noise reduction in frequencies below 10 kHz, or special mounting devices for shock mitigation; <u>or</u></p> <p>d. Systems having all of the following:</p>

<i>Category Code</i>	<i>Item Description</i>
	<ol style="list-style-type: none"> <li>1. Specially designed to pressurise the products of reaction or for fuel reformation;</li> <li>2. Specially designed to store the products of the reaction; <u>and</u></li> <li>3. Specially designed to discharge the products of the reaction against a pressure of 100 kPa or more;</li> </ol> <ol style="list-style-type: none"> <li>2. Diesel cycle engine air independent systems having all of the following: <ol style="list-style-type: none"> <li>a. Chemical scrubber or absorber systems, specially designed to remove carbon dioxide, carbon monoxide and particulates from recirculated engine exhaust;</li> <li>b. Systems specially designed to use a monoatomic gas;</li> <li>c. Devices or enclosures, specially designed for underwater noise reduction in frequencies below 10 kHz, or special mounting devices for shock mitigation; <u>and</u></li> <li>d. Specially designed exhaust systems that do not exhaust continuously the products of combustion;</li> </ol> </li> <li>3. "Fuel cell" air independent power systems with an output exceeding 2 kW and having any of the following: <ol style="list-style-type: none"> <li>a. Devices or enclosures, specially designed for underwater noise reduction in frequencies below 10 kHz, or special mounting devices for shock mitigation; <u>or</u></li> <li>b. Systems having all of the following: <ol style="list-style-type: none"> <li>1. Specially designed to pressurise the products of reaction or for fuel reformation;</li> <li>2. Specially designed to store the products of the reaction; <u>and</u></li> </ol> </li> </ol> </li> </ol>

<i>Category Code</i>	<i>Item Description</i>
	<p>3. Specially designed to discharge the products of the reaction against a pressure of 100 kPa or more;</p> <p>4. Stirling cycle engine air independent power systems having all of the following:</p> <ul style="list-style-type: none"> <li>a. Devices or enclosures, specially designed for underwater noise reduction in frequencies below 10 kHz, or special mounting devices for shock mitigation; <u>and</u></li> <li>b. Specially designed exhaust systems which discharge the products of combustion against a pressure of 100 kPa or more;</li> </ul> <p>k. Skirts, seals and fingers, having any of the following:</p> <ul style="list-style-type: none"> <li>1. Designed for cushion pressures of 3,830 Pa or more, operating in a significant wave height of 1.25 m (Sea State 3) or more and specially designed for surface effect vehicles (fully skirted variety) specified in Category Code 8A001.f.; <u>or</u></li> <li>2. Designed for cushion pressures of 6,224 Pa or more, operating in a significant wave height of 3.25 m (Sea State 5) or more and specially designed for surface effect vehicles (rigid sidewalls) specified in Category Code 8A001.g.;</li> </ul> <p>l. Lift fans rated at more than 400 kW and specially designed for surface effect vehicles specified in Category Code 8A001.f. or 8A001.g.;</p> <p>m. Fully submerged subcavitating or supercavitating hydrofoils, specially designed for vessels specified in Category Code 8A001.h.;</p> <p>n. Active systems specially designed or modified to control automatically the sea-induced motion of vehicles or vessels, specified in Category Code 8A001.f., 8A001.g., 8A001.h. or 8A001.i.;</p> <p>o. Propellers, power transmission systems, power generation systems and noise reduction systems, as follows:</p>



<i>Category Code</i>	<i>Item Description</i>
	<ol style="list-style-type: none"> <li>1. Water-screw propeller or power transmission systems, as follows, specially designed for surface effect vehicles (fully skirted or rigid sidewall variety), hydrofoils or ‘small waterplane area vessels’ specified in Category Code 8A001.f., 8A001.g., 8A001.h. or 8A001.i., as follows:           <ol style="list-style-type: none"> <li>a. Supercavitating, super-ventilated, partially-submerged or surface piercing propellers, rated at more than 7.5 MW;</li> <li>b. Contrarotating propeller systems rated at more than 15 MW;</li> <li>c. Systems employing pre-swirl or post-swirl techniques, for smoothing the flow into a propeller;</li> <li>d. Light-weight, high capacity (K factor exceeding 300) reduction gearing;</li> <li>e. Power transmission shaft systems incorporating “composite” material components and capable of transmitting more than 1 MW;</li> </ol> </li> <li>2. Water-screw propeller, power generation systems or transmission systems, designed for use on vessels, as follows:           <ol style="list-style-type: none"> <li>a. Controllable-pitch propellers and hub assemblies, rated at more than 30 MW;</li> <li>b. Internally liquid-cooled electric propulsion engines with a power output exceeding 2.5 MW;</li> <li>c. “Superconductive” propulsion engines or permanent magnet electric propulsion engines, with a power output exceeding 0.1 MW;</li> <li>d. Power transmission shaft systems incorporating “composite” material components and capable of transmitting more than 2 MW;</li> <li>e. Ventilated or base-ventilated propeller systems, rated at more than 2.5 MW;</li> </ol> </li> </ol>

<i>Category Code</i>	<i>Item Description</i>
	<p>3. Noise reduction systems designed for use on vessels of 1,000 tonnes displacement or more, as follows:</p> <ol style="list-style-type: none"> <li>a. Systems that attenuate underwater noise at frequencies below 500 Hz and consist of compound acoustic mounts for the acoustic isolation of diesel engines, diesel generator sets, gas turbines, gas turbine generator sets, propulsion motors or propulsion reduction gears, specially designed for sound or vibration isolation and having an intermediate mass exceeding 30% of the equipment to be mounted;</li> <li>b. 'Active noise reduction or cancellation systems' or magnetic bearings, specially designed for power transmission systems;</li> </ol> <p><i>Technical Note</i>  <i>'Active noise reduction or cancellation systems' incorporate electronic control systems capable of actively reducing equipment vibration by the generation of anti-noise or anti-vibration signals directly to the source.</i></p> <p>p. Pumpjet propulsion systems having all of the following:</p> <ol style="list-style-type: none"> <li>1. Power output exceeding 2.5 MW; <u>and</u></li> <li>2. Using divergent nozzle and flow conditioning vane techniques to improve propulsive efficiency or reduce propulsion-generated underwater-radiated noise;</li> </ol> <p>q. Underwater swimming and diving equipment as follows:</p> <ol style="list-style-type: none"> <li>1. Closed circuit rebreathers;</li> <li>2. Semi-closed circuit rebreathers;</li> </ol> <p><i>Note</i>  <i>Category Code 8A002.q. does not include individual rebreathers for personal use when accompanying their users.</i></p> <p><i>N.B.</i>  <i>For equipment and devices specially designed for military use, see Division 2 of Part I of this Schedule.</i></p>

<i>Category Code</i>	<i>Item Description</i>
	<p>r. Diver deterrent acoustic systems specially designed or modified to disrupt divers and having a sound pressure level equal to or exceeding 190 dB (reference 1µPa at 1 m) at frequencies of 200 Hz and below.</p> <p><u>Note 1</u> Category Code 8A002.r. does not include diver deterrent systems based on underwater explosive devices, air guns or combustible sources.</p> <p><u>Note 2</u> Category Code 8A002.r. includes diver deterrent acoustic systems that use spark gap sources, also known as plasma sound sources.</p>
<b>8B</b>	<b>Test, Inspection and Production Equipment</b>
8B001	Water tunnels having a background noise of less than 100 dB (reference 1 µPa, 1 Hz), in the frequency range from 0 Hz to 500 Hz and designed for measuring acoustic fields generated by a hydro-flow around propulsion system models.
<b>8C</b>	<b>Materials</b>
8C001	<p>‘Syntactic foam’ designed for underwater use and having all of the following:</p> <p><u>N.B.</u> See also Category Code 8A002.a.4.</p> <p>a. Designed for marine depths exceeding 1,000 m; <u>and</u></p> <p>b. A density less than 561 kg/m<sup>3</sup>.</p> <p><u>Technical Note</u> ‘Syntactic foam’ consists of hollow spheres of plastic or glass embedded in a resin matrix.</p>

<i>Category Code</i>	<i>Item Description</i>
<b>8D</b>	<b>Software</b>
8D001	“Software” specially designed or modified for the “development”, “production” or “use” of equipment or materials, specified in Category 8A, 8B or 8C.
8D002	Specific “software” specially designed or modified for the “development”, “production”, repair, overhaul or refurbishing (re-machining) of propellers specially designed for underwater noise reduction.
<b>8E</b>	<b>Technology</b>
8E001	“Technology” (according to the General Technology Note) for the “development” or “production” of equipment or materials specified in Category 8A, 8B or 8C.
8E002	Other “technology”, as follows: <ul style="list-style-type: none"> <li>a. “Technology” for the “development”, “production”, repair, overhaul or refurbishing (re-machining) of propellers specially designed for underwater noise reduction;</li> <li>b. “Technology” for the overhaul or refurbishing of equipment specified in Category Code 8A001, 8A002.b., 8A002.j., 8A002.o. or 8A002.p.</li> </ul>

Category Code	Item Description
<b>CATEGORY 9 — AEROSPACE AND PROPULSION</b>	
<b>9A</b>	<b>Systems, Equipment and Components</b>
	<p><u>N.B.</u>  <i>For propulsion systems designed or rated against neutron or transient ionising radiation, see Division 2 of Part I of this Schedule.</i></p>
9A001	<p>Aero gas turbine engines having any of the following:</p> <p><u>N.B.</u>  <i>See also Category Code 9A101.</i></p> <p>a. Incorporating any of the “technologies” specified in Category Code 9E003.a., 9E003.h. or 9E003.i.; <u>or</u></p> <p><u>Note 1</u>  <i>Category Code 9A001.a. does not include aero gas turbine engines which meet all of the following:</i></p> <p>a. <i>Certified by the civil aviation authority of a “participating state”; <u>and</u></i></p> <p>b. <i>Intended to power non-military manned aircraft for which any of the following has been issued by a “participating state”:</i></p> <ol style="list-style-type: none"> <li>1. <i>A civil type certificate; <u>or</u></i></li> <li>2. <i>An equivalent document recognised by the International Civil Aviation Organisation (ICAO).</i></li> </ol> <p><u>Note 2</u>  <i>Category Code 9A001.a. does not include aero gas turbine engines designed for Auxiliary Power Units (APUs) approved by the civil aviation authority of a “participating state”.</i></p> <p>b. Designed to power an aircraft to cruise at Mach 1 or higher, for more than 30 minutes.</p>

<i>Category Code</i>	<i>Item Description</i>
9A002	<p>‘Marine gas turbine engines’ with an ISO standard continuous power rating of 24,245 kW or more and a specific fuel consumption not exceeding 0.219 kg/kWh in the power range from 35% to 100%, and specially designed assemblies and components therefor.</p> <p><u>Note</u>  <i>The term ‘marine gas turbine engines’ includes those industrial, or aero-derivative, gas turbine engines adapted for a ship’s electric power generation or propulsion.</i></p>
9A003	<p>Specially designed assemblies and components, incorporating any of the “technologies” specified in Category Code 9E003.a., 9E003.h. or 9E003.i., for any of the following gas turbine engine propulsion systems:</p> <ul style="list-style-type: none"> <li>a. Specified in Category Code 9A001; <u>or</u></li> <li>b. Whose design or production origins are either non-“participating state” or unknown to the manufacturer.</li> </ul>
9A004	<p>Space launch vehicles and “spacecraft”.</p> <p><u>N.B.</u>  <i>See also Category Code 9A104.</i></p> <p><u>Note</u>  <i>Category Code 9A004 does not include payloads.</i></p> <p><u>N.B.</u>  <i>For products contained in “spacecraft” payloads, see the appropriate Categories.</i></p>
9A005	<p>Liquid rocket propulsion systems containing any of the systems or components, specified in Category Code 9A006.</p> <p><u>N.B.</u>  <i>See also Category Codes 9A105 and 9A119.</i></p>

<i>Category Code</i>	<i>Item Description</i>
9A006	<p>Systems and components, specially designed for liquid rocket propulsion systems, as follows:</p> <p><u>N.B.</u></p> <p><i>See also Category Codes 9A106, 9A108 and 9A120.</i></p> <ol style="list-style-type: none"> <li>a. Cryogenic refrigerators, flightweight dewars, cryogenic heat pipes or cryogenic systems, specially designed for use in space vehicles and capable of restricting cryogenic fluid losses to less than 30% per year;</li> <li>b. Cryogenic containers or closed-cycle refrigeration systems, capable of providing temperatures of 100 K (-173°C) or less for “aircraft” capable of sustained flight at speeds exceeding Mach 3, launch vehicles or “spacecraft”;</li> <li>c. Slush hydrogen storage or transfer systems;</li> <li>d. High pressure (exceeding 17.5 MPa) turbo pumps, pump components or their associated gas generator or expander cycle turbine drive systems;</li> <li>e. High-pressure (exceeding 10.6 MPa) thrust chambers and nozzles therefor;</li> <li>f. Propellant storage systems using the principle of capillary containment or positive expulsion (i.e. with flexible bladders);</li> <li>g. Liquid propellant injectors with individual orifices of 0.381 mm or smaller in diameter (an area of <math>1.14 \times 10^{-3} \text{ cm}^2</math> or smaller for non-circular orifices) and specially designed for liquid rocket engines;</li> <li>h. One-piece carbon-carbon thrust chambers or one-piece carbon-carbon exit cones, with densities exceeding <math>1.4 \text{ g/cm}^3</math> and tensile strengths exceeding 48 MPa.</li> </ol>
9A007	<p>Solid rocket propulsion systems having any of the following:</p> <p><u>N.B.</u></p> <p><i>See also Category Codes 9A107 and 9A119.</i></p> <ol style="list-style-type: none"> <li>a. Total impulse capacity exceeding 1.1 MNs;</li> </ol>

<i>Category Code</i>	<i>Item Description</i>
	<p>b. Specific impulse of 2.4 kNs/kg or more, when the nozzle flow is expanded to ambient sea level conditions for an adjusted chamber pressure of 7 MPa;</p> <p>c. Stage mass fractions exceeding 88% and propellant solid loadings exceeding 86%;</p> <p>d. Components specified in Category Code 9A008; <u>or</u></p> <p>e. Insulation and propellant bonding systems, using direct-bonded motor designs to provide a 'strong mechanical bond' or a barrier to chemical migration between the solid propellant and case insulation material.</p> <p><u>Technical Note</u> 'Strong mechanical bond' means bond strength equal to or more than propellant strength.</p>
9A008	<p>Components specially designed for solid rocket propulsion systems, as follows:</p> <p><u>N.B.</u> See also Category Code 9A108.</p> <p>a. Insulation and propellant bonding systems, using liners to provide a 'strong mechanical bond' or a barrier to chemical migration between the solid propellant and case insulation material;</p> <p><u>Technical Note</u> 'Strong mechanical bond' means bond strength equal to or more than propellant strength.</p> <p>b. Filament-wound "composite" motor cases exceeding 0.61 m in diameter or having 'structural efficiency ratios (PV/W)' exceeding 25 km;</p> <p><u>Technical Note</u> 'Structural efficiency ratio (PV/W)' is the burst pressure (P) multiplied by the vessel volume (V) divided by the total pressure vessel weight (W).</p> <p>c. Nozzles with thrust levels exceeding 45 kN or nozzle throat erosion rates of less than 0.075 mm/s;</p>



<i>Category Code</i>	<i>Item Description</i>
	<p>d. Movable nozzle or secondary fluid injection thrust vector control systems, capable of any of the following:</p> <ol style="list-style-type: none"> <li>1. Omni-axial movement exceeding <math>\pm 5^\circ</math>;</li> <li>2. Angular vector rotations of <math>20^\circ/\text{s}</math> or more; <u>or</u></li> <li>3. Angular vector accelerations of <math>40^\circ/\text{s}^2</math> or more.</li> </ol>
9A009	<p>Hybrid rocket propulsion systems having any of the following:</p> <p><u>N.B.</u> See also Category Codes 9A109 and 9A119.</p> <ol style="list-style-type: none"> <li>a. Total impulse capacity exceeding 1.1 MNs; <u>or</u></li> <li>b. Thrust levels exceeding 220 kN in vacuum exit conditions.</li> </ol>
9A010	<p>Specially designed components, systems and structures, for launch vehicles, launch vehicle propulsion systems or "spacecraft", as follows:</p> <p><u>N.B.</u> See also Category Codes 1A002 and 9A110.</p> <ol style="list-style-type: none"> <li>a. Components and structures, each exceeding 10 kg and specially designed for launch vehicles manufactured using metal "matrix", "composite", organic "composite", ceramic "matrix" or intermetallic reinforced materials, specified in Category Code 1C007 or 1C010;</li> </ol> <p><u>Note</u> <i>The weight cut-off is not relevant for nose cones.</i></p> <ol style="list-style-type: none"> <li>b. Components and structures, specially designed for launch vehicle propulsion systems specified in Category Codes 9A005 to 9A009 manufactured using metal "matrix", "composite", organic "composite", ceramic "matrix" or intermetallic reinforced materials, specified in Category Code 1C007 or 1C010;</li> <li>c. Structural components and isolation systems, specially designed to control actively the dynamic response or distortion of "spacecraft" structures;</li> </ol>

<i>Category Code</i>	<i>Item Description</i>
	<p>d. Pulsed liquid rocket engines with thrust-to-weight ratios equal to or more than 1 kN/kg and a response time (the time required to achieve 90% of total rated thrust from start-up) of less than 30 ms.</p>
9A011	<p>Ramjet, scramjet or combined cycle engines, and specially designed components therefor.</p> <p><u>N.B.</u> See also Category Codes 9A111 and 9A118.</p>
9A012	<p>“Unmanned aerial vehicles” (“UAVs”), unmanned “airships”, related systems, equipment and components, as follows:</p> <p>a. “UAVs” or unmanned “airships”, having any of the following:</p> <ol style="list-style-type: none"> <li>1. An autonomous flight control and navigation capability (e.g. an autopilot with an Inertial Navigation System); <u>or</u></li> <li>2. Capability of controlled-flight out of the direct vision range involving a human operator (e.g. televisual remote control);</li> </ol> <p>b. Related systems, equipment and components, as follows:</p> <ol style="list-style-type: none"> <li>1. Equipment specially designed for remotely controlling the “UAVs” or unmanned “airships”, specified in Category Code 9A012.a.;</li> <li>2. Systems for navigation, attitude, guidance or control, other than those specified in Category 7A, specially designed to be integrated into “UAVs” or unmanned “airships”, specified in Category Code 9A012.a.;</li> <li>3. Equipment or components, specially designed to convert a manned “aircraft” or manned “airship”, to a “UAV” or unmanned “airship”, specified in Category Code 9A012.a.;</li> <li>4. Air breathing reciprocating or rotary internal combustion type engines, specially designed or modified to propel “UAVs” or unmanned “airships”, at altitudes above 50,000 feet (15,240 metres).</li> </ol>

<i>Category Code</i>	<i>Item Description</i>
9A101	<p>Turbojet and turbofan engines, other than those specified in Category Code 9A001, as follows:</p> <p>a. Engines having both of the following characteristics:</p> <ol style="list-style-type: none"> <li>1. ‘Maximum thrust value’ greater than 400 N (achieved un-installed) excluding civil certified engines with a ‘maximum thrust value’ greater than 8,890 N (achieved un-installed); <u>and</u></li> <li>2. Specific fuel consumption of 0.15 kg/N/hr or less (at maximum continuous power at sea level static conditions using the ICAO standard atmosphere);</li> </ol> <p><i>Technical Note</i></p> <p><i>For the purpose of Category Code 9A101.a.1., ‘maximum thrust value’ is the manufacturer’s demonstrated maximum thrust for the engine type un-installed. The civil type certified thrust value will be equal to or less than the manufacturer’s demonstrated maximum thrust for the engine type.</i></p> <p>b. Engines designed or modified for use in “missiles” or unmanned aerial vehicles specified in Category Code 9A012.</p>
9A102	<p>‘Turboprop engine systems’ specially designed for unmanned aerial vehicles specified in Category Code 9A012, and specially designed components therefor, having a ‘maximum power’ greater than 10 kW.</p> <p><i>Note</i></p> <p><i>Category Code 9A102 does not include civil certified engines.</i></p> <p><i>Technical Notes</i></p> <ol style="list-style-type: none"> <li>1. <i>For the purpose of Category Code 9A102, a ‘turboprop engine system’ incorporates all of the following:</i> <ol style="list-style-type: none"> <li>a. <i>Turboshaft engine; <u>and</u></i></li> <li>b. <i>Power transmission system to transfer the power to a propeller.</i></li> </ol> </li> <li>2. <i>For the purpose of Category Code 9A102, the ‘maximum power’ is achieved un-installed at sea level static conditions using the ICAO standard atmosphere.</i></li> </ol>

<i>Category Code</i>	<i>Item Description</i>
9A104	<p>Sounding rockets, capable of a range of at least 300 km.</p> <p><u>N.B.</u> See also Category Code 9A004.</p>
9A105	<p>Liquid propellant rocket engines, as follows:</p> <p><u>N.B.</u> See also Category Code 9A119.</p> <ul style="list-style-type: none"> <li>a. Liquid propellant rocket engines usable in “missiles”, other than those specified in Category Code 9A005, integrated, or designed or modified to be integrated, into a liquid propellant propulsion system which has a total impulse capacity equal to or greater than 1.1 MNs;</li> <li>b. Liquid propellant rocket engines, usable in complete rocket systems or unmanned aerial vehicles, capable of a range of 300 km, other than those specified in Category Code 9A005 or 9A105.a., integrated, or designed or modified to be integrated, into a liquid propellant propulsion system which has a total impulse capacity equal to or greater than 0.841 MNs.</li> </ul>
9A106	<p>Systems or components, other than those specified in Category Code 9A006 as follows, specially designed for liquid rocket propulsion systems:</p> <ul style="list-style-type: none"> <li>a. Ablative liners for thrust or combustion chambers, usable in “missiles”, space launch vehicles specified in Category Code 9A004 or sounding rockets specified in Category Code 9A104;</li> <li>b. Rocket nozzles, usable in “missiles”, space launch vehicles specified in Category Code 9A004 or sounding rockets specified in Category Code 9A104;</li> <li>c. Thrust vector control subsystems, usable in “missiles”;</li> </ul> <p><u>Technical Note</u> Examples of methods of achieving thrust vector control specified in Category Code 9A106.c. are:</p> <ol style="list-style-type: none"> <li>1. Flexible nozzle;</li> </ol>

<i>Category Code</i>	<i>Item Description</i>
	<p>2. <i>Fluid or secondary gas injection;</i></p> <p>3. <i>Movable engine or nozzle;</i></p> <p>4. <i>Deflection of exhaust gas stream (jet vanes or probes);<u>or</u></i></p> <p>5. <i>Thrust tabs.</i></p> <p>d. Liquid, slurry and gel propellant (including oxidisers) control systems, and specially designed components therefor, usable in “missiles”, designed or modified to operate in vibration environments greater than 10 g rms between 20 Hz and 2 kHz.</p> <p><u>Note</u>  <i>The only servo valves and pumps specified in Category Code 9A106.d. are the following:</i></p> <p>a. <i>Servo valves designed for flow rates equal to or greater than 24 litres per minute, at an absolute pressure equal to or greater than 7 MPa, that have an actuator response time of less than 100 ms;</i></p> <p>b. <i>Pumps, for liquid propellants, with shaft speeds equal to or greater than 8,000 rpm or with discharge pressures equal to or greater than 7 MPa.</i></p>
9A107	<p>Solid propellant rocket engines, usable in complete rocket systems or unmanned aerial vehicles, capable of a range of 300 km, other than those specified in Category Code 9A007, having total impulse capacity equal to or greater than 0.841 MNs.</p> <p><u>N.B.</u>  <i>See also Category Code 9A119.</i></p>
9A108	<p>Components, other than those specified in Category Code 9A008, as follows, specially designed for solid rocket propulsion systems:</p> <p>a. Rocket motor cases and “insulation” components therefor, usable in “missiles”, space launch vehicles specified in Category Code 9A004 or sounding rockets specified in Category Code 9A104;</p>

<i>Category Code</i>	<i>Item Description</i>
	<p>b. Rocket nozzles, usable in “missiles”, space launch vehicles specified in Category Code 9A004 or sounding rockets specified in Category Code 9A104;</p> <p>c. Thrust vector control subsystems, usable in “missiles”.</p> <p><u>Technical Note</u>  <i>Examples of methods of achieving thrust vector control specified in Category Code 9A108.c. are:</i></p> <ol style="list-style-type: none"> <li>1. <i>Flexible nozzle;</i></li> <li>2. <i>Fluid or secondary gas injection;</i></li> <li>3. <i>Movable engine or nozzle;</i></li> <li>4. <i>Deflection of exhaust gas stream (jet vanes or probes);</i> <i>or</i></li> <li>5. <i>Thrust tabs.</i></li> </ol>
9A109	<p>Hybrid rocket motors and specially designed components as follows:</p> <p>a. Hybrid rocket motors usable in complete rocket systems or unmanned aerial vehicles, capable of 300 km, other than those specified in Category Code 9A009, having a total impulse capacity equal to or greater than 0.841 MNs, and specially designed components therefor;</p> <p>b. Specially designed components for hybrid rocket motors specified in Category Code 9A009 that are usable in “missiles”.</p> <p><u>N.B.</u>  <i>See also Category Codes 9A009 and 9A119.</i></p>
9A110	<p>Composite structures, laminates and manufactures thereof, other than those specified in Category Code 9A010, specially designed for use in ‘missiles’ or the subsystems specified in Category Code 9A005, 9A007, 9A105, 9A106.c., 9A107, 9A108.c., 9A116 or 9A119.</p> <p><u>N.B.</u>  <i>See also Category Code 1A002.</i></p>

<i>Category Code</i>	<i>Item Description</i>
	<p><u>Technical Note</u>  <i>In Category Code 9A110, ‘missiles’ means complete rocket systems and unmanned aerial vehicle systems capable of a range exceeding 300 km.</i></p>
9A111	<p>Pulse jet engines, usable in “missiles” or unmanned aerial vehicles specified in Category Code 9A012, and specially designed components therefor.</p> <p><u>N.B.</u>  <i>See also Category Codes 9A011 and 9A118.</i></p>
9A115	<p>Launch support equipment as follows:</p> <ol style="list-style-type: none"> <li>a. Apparatus and devices for handling, control, activation or launching, designed or modified for space launch vehicles specified in Category Code 9A004, unmanned aerial vehicles specified in Category Code 9A012 or sounding rockets specified in Category Code 9A104;</li> <li>b. Vehicles for transport, handling, control, activation or launching, designed or modified for space launch vehicles specified in Category Code 9A004 or sounding rockets specified in Category Code 9A104.</li> </ol>
9A116	<p>Re-entry vehicles, usable in “missiles”, and equipment designed or modified therefor, as follows:</p> <ol style="list-style-type: none"> <li>a. Re-entry vehicles;</li> <li>b. Heat shields and components therefor, fabricated of ceramic or ablative materials;</li> <li>c. Heat sinks and components therefor, fabricated of light-weight, high heat capacity materials;</li> <li>d. Electronic equipment specially designed for re-entry vehicles.</li> </ol>

<i>Category Code</i>	<i>Item Description</i>
9A117	<p>Staging mechanisms, separation mechanisms, and interstages, usable in “missiles”.</p> <p><u>N.B.</u> See also Category Code 9A121.</p>
9A118	<p>Devices to regulate combustion usable in engines, which are usable in “missiles” or unmanned aerial vehicles specified in Category Code 9A012, specified in Category Code 9A011 or 9A111.</p>
9A119	<p>Individual rocket stages, usable in complete rocket systems or unmanned aerial vehicles, capable of a range of 300 km, other than those specified in Category Codes 9A005, 9A007, 9A009, 9A105, 9A107 and 9A109.</p>
9A120	<p>Liquid propellant tanks, other than those specified in Category Code 9A006, specially designed for propellants specified in Category Code 1C111 or ‘other liquid propellants’, used in rocket systems capable of delivering at least a 500 kg payload to a range of at least 300 km.</p> <p><u>Note</u> In Category Code 9A120, ‘other liquid propellants’ includes, but is not limited to, propellants specified in Division 2 of Part I of this Schedule.</p>
9A121	<p>Umbilical and interstage electrical connectors specially designed for “missiles”, space launch vehicles specified in Category Code 9A004 or sounding rockets specified in Category Code 9A104.</p> <p><u>Technical Note</u> Interstage connectors referred to in Category Code 9A121 also include electrical connectors installed between the “missile”, space launch vehicle or sounding rocket and their payload.</p>



<i>Category Code</i>	<i>Item Description</i>
9A350	<p>Spraying or fogging systems, specially designed or modified for fitting to aircraft, "lighter-than-air vehicles" or unmanned aerial vehicles, and specially designed components therefor, as follows:</p> <ol style="list-style-type: none"> <li>a. Complete spraying or fogging systems capable of delivering, from a liquid suspension, an initial droplet 'VMD' of less than 50 <math>\mu\text{m}</math> at a flow rate of greater than two litres per minute;</li> <li>b. Spray booms or arrays of aerosol generating units capable of delivering, from a liquid suspension, an initial droplet 'VMD' of less than 50 <math>\mu\text{m}</math> at a flow rate of greater than two litres per minute;</li> <li>c. Aerosol generating units specially designed for fitting to systems specified in Category Codes 9A350.a. and .b.</li> </ol> <p><u>Note</u>  <i>Aerosol generating units are devices specially designed or modified for fitting to aircraft such as nozzles, rotary drum atomisers and similar devices.</i></p> <p><u>Note</u>  <i>Category Code 9A350 does not include spraying or fogging systems and components that are demonstrated not to be capable of delivering biological agents in the form of infectious aerosols.</i></p> <p><u>Technical Notes</u></p> <ol style="list-style-type: none"> <li>1. <i>Droplet size for spray equipment or nozzles specially designed for use on aircraft, "lighter-than-air vehicles" or unmanned aerial vehicles should be measured using either of the following:</i> <ol style="list-style-type: none"> <li>a. <i>Doppler laser method;</i></li> <li>b. <i>Forward laser diffraction method.</i></li> </ol> </li> <li>2. <i>In Category Code 9A350, 'VMD' means Volume Median Diameter and for water-based systems this equates to Mass Median Diameter (MMD).</i></li> </ol>

<i>Category Code</i>	<i>Item Description</i>
<b>9B</b>	<b>Test, Inspection and Production Equipment</b>
9B001	<p>Equipment, tooling and fixtures, specially designed for manufacturing gas turbine blades, vanes or “tip shroud” castings, as follows:</p> <ul style="list-style-type: none"> <li>a. Directional solidification or single crystal casting equipment;</li> <li>b. Ceramic cores or shells.</li> </ul>
9B002	<p>On-line (real-time) control systems, instrumentation (including sensors) or automated data acquisition and processing equipment, having all of the following:</p> <ul style="list-style-type: none"> <li>a. Specially designed for the “development” of gas turbine engines, assemblies or components; <u>and</u></li> <li>b. Incorporating “technology” specified in Category Code 9E003.h. or 9E003.i.</li> </ul>
9B003	<p>Equipment specially designed for the “production” or test of gas turbine brush seals designed to operate at tip speeds exceeding 335 m/s and temperatures in excess of 773 K (500°C), and specially designed components or accessories therefor.</p>
9B004	<p>Tools, dies or fixtures, for the solid state joining of “superalloy”, titanium or intermetallic airfoil-to-disk combinations described in Category Code 9E003.a.3. or 9E003.a.6. for gas turbines.</p>
9B005	<p>On-line (real-time) control systems, instrumentation (including sensors) or automated data acquisition and processing equipment, specially designed for use with any of the following:</p> <p><u>N.B.</u> See also Category Code 9B105.</p>

Category Code	Item Description
	<p>a. Wind tunnels designed for speeds of Mach 1.2 or more;</p> <p><u>Note</u>  <i>Category Code 9B005.a. does not include wind tunnels specially designed for educational purposes and having a 'test section size' (measured laterally) of less than 250 mm.</i></p> <p><u>Technical Note</u>  <i>'Test section size' means the diameter of the circle, or the side of the square, or the longest side of the rectangle, at the largest test section location.</i></p> <p>b. Devices for simulating flow-environments at speeds exceeding Mach 5, including hot-shot tunnels, plasma arc tunnels, shock tubes, shock tunnels, gas tunnels and light gas guns; <u>or</u></p> <p>c. Wind tunnels or devices, other than two-dimensional sections, capable of simulating Reynolds number flows exceeding <math>25 \times 10^6</math>.</p>
9B006	<p>Acoustic vibration test equipment capable of producing sound pressure levels of 160 dB or more (referenced to 20 <math>\mu</math>Pa) with a rated output of 4 kW or more at a test cell temperature exceeding 1,273 K (1,000°C), and specially designed quartz heaters therefor.</p> <p><u>N.B.</u>  <i>See also Category Code 9B106.</i></p>
9B007	<p>Equipment specially designed for inspecting the integrity of rocket motors and using Non-Destructive Test (NDT) techniques other than planar X-ray or basic physical or chemical analysis.</p>
9B008	<p>Direct measurement wall skin friction transducers specially designed to operate at a test flow total (stagnation) temperature exceeding 833 K (560°C).</p>

<i>Category Code</i>	<i>Item Description</i>
9B009	Tooling specially designed for producing turbine engine powder metallurgy rotor components capable of operating at stress levels of 60% of Ultimate Tensile Strength (UTS) or more and metal temperatures of 873 K (600°C) or more.
9B010	Equipment specially designed for the production of “UAVs” and associated systems, equipment and components, specified in Category Code 9A012.
9B105	‘Aerodynamic test facilities’ for speeds of Mach 0.9 or more, usable for ‘missiles’ and their subsystems.
	<p><u>N.B.</u> See also Category Code 9B005.</p>
	<p><u>Note</u> Category Code 9B105 does not include wind tunnels for speeds of Mach 3 or less with dimension of the ‘test cross section size’ equal to or less than 250 mm.</p>
	<p><u>Technical Notes</u></p> <ol style="list-style-type: none"> <li data-bbox="480 1196 1267 1290">1. In Category Code 9B105, ‘aerodynamics test facilities’ includes wind tunnels and shock tunnels for the study of airflow over objects.</li> <li data-bbox="480 1312 1267 1514">2. In Note to Category Code 9B105, ‘test cross section size’ means the diameter of the circle, or the side of the square, or the longest side of the rectangle, or the major axis of the ellipse at the largest ‘test cross section’ location. ‘Test cross section’ is the section perpendicular to the flow direction.</li> <li data-bbox="480 1536 1267 1630">3. In Category Code 9B105, ‘missile’ means complete rocket systems and unmanned aerial vehicle systems capable of a range exceeding 300 km.</li> </ol>

<i>Category Code</i>	<i>Item Description</i>
9B106	<p>Environmental chambers and anechoic chambers, as follows:</p> <ol style="list-style-type: none"> <li>a. Environmental chambers capable of simulating all of the following flight conditions:               <ol style="list-style-type: none"> <li>1. Having any of the following:                   <ol style="list-style-type: none"> <li>a. Altitude equal to or greater than 15 km; <u>or</u></li> <li>b. Temperature range from below 223 K (-50°C) to above 398 K (+125°C); <u>and</u></li> </ol> </li> <li>2. Incorporating, or ‘designed or modified’ to incorporate, a shaker unit or other vibration test equipment to produce vibration environments equal to or greater than 10 g rms, measured ‘bare table’, between 20 Hz and 2 kHz while imparting forces equal to or greater than 5 kN;</li> </ol> <p><i>Technical Notes</i></p> <ol style="list-style-type: none"> <li>1. <i>Category Code 9B106.a.2. describes systems that are capable of generating a vibration environment with a single wave (e.g. a sine wave) and systems capable of generating a broad band random vibration (i.e. power spectrum).</i></li> <li>2. <i>In Category Code 9B106.a.2., ‘designed or modified’ means the environmental chamber provides appropriate interfaces (e.g. sealing devices) to incorporate a shaker unit or other vibration test equipment as specified in Category Code 2B116.</i></li> <li>3. <i>In Category Code 9B106.a.2., ‘bare table’ means a flat table, or surface, with no fixture or fittings.</i></li> </ol> </li> <li>b. Environmental chambers capable of simulating all of the following flight conditions:               <ol style="list-style-type: none"> <li>1. Acoustic environments at an overall sound pressure level of 140 dB or greater (referenced to 20 µPa) or with a total rated acoustic power output of 4 kW or greater; <u>and</u></li> <li>2. Having any of the following:                   <ol style="list-style-type: none"> <li>a. Altitude equal to greater than 15 km; <u>or</u></li> <li>b. Temperature range from below 223 K (-50°C) to above 398 K (+125°C).</li> </ol> </li> </ol> </li> </ol>

<i>Category Code</i>	<i>Item Description</i>
9B115	Specially designed “production equipment” for the systems, subsystems and components specified in Category Codes 9A005 to 9A009, 9A011, 9A101, 9A102, 9A105 to 9A109, 9A111, 9A116 to 9A120.
9B116	<p>Specially designed “production facilities” for the space launch vehicles specified in Category Code 9A004, or systems, subsystems, and components specified in Category Codes 9A005 to 9A009, 9A011, 9A101, 9A102, 9A104 to 9A109, 9A111, 9A116 to 9A120 or ‘missiles’.</p> <p><u>Technical Note</u>  <i>In Category Code 9B116, ‘missile’ means complete rocket systems and unmanned aerial vehicle systems capable of a range exceeding 300 km.</i></p>
9B117	<p>Test benches and test stands for solid or liquid propellant rockets or rocket motors, having either of the following characteristics:</p> <ol style="list-style-type: none"> <li>a. The capacity to handle more than 68 kN of thrust; <u>or</u></li> <li>b. Capable of simultaneously measuring the three axial thrust components.</li> </ol>
<b>9C</b>	<b>Materials</b>
9C108	<p>“Insulation” material in bulk form and “interior lining”, other than those specified in Category Code 9A008, for rocket motor cases usable in ‘missiles’ or specially designed for ‘missiles’.</p> <p><u>Technical Note</u>  <i>In Category Code 9C108, ‘missile’ means complete rocket systems and unmanned aerial vehicle systems capable of a range exceeding 300 km.</i></p>

<i>Category Code</i>	<i>Item Description</i>
9C110	<p>Resin impregnated fibre prepregs and metal coated fibre preforms therefor, for composite structures, laminates and manufactures specified in Category Code 9A110, made either with organic matrix or metal matrix utilising fibrous or filamentary reinforcements having a “specific tensile strength” greater than <math>7.62 \times 10^4</math> m and a “specific modulus” greater than <math>3.18 \times 10^6</math> m.</p>
	<p><u>N.B.</u></p>
	<p><i>See also Category Codes 1C010 and 1C210.</i></p>
	<p><u>Note</u></p>
	<p><i>The only resin impregnated fibre prepregs specified in Category Code 9C110 are those using resins with a glass transition temperature (<math>T_g</math>), after cure, exceeding 418 K (145°C) as determined by ASTM D4065 or equivalent.</i></p>
	<p><b>9D Software</b></p>
9D001	<p>“Software” specially designed or modified for the “development” of equipment or “technology”, specified in Category Codes 9A001 to 9A119, Category 9B or Category Code 9E003.</p>
9D002	<p>“Software” specially designed or modified for the “production” of equipment specified in Category Codes 9A001 to 9A119 or Category 9B.</p>
9D003	<p>“Software” incorporating “technology” specified in Category Code 9E003.h. and used in “FADEC Systems” for propulsion systems specified in Category 9A or equipment specified in Category 9B.</p>

<i>Category Code</i>	<i>Item Description</i>
9D004	<p>Other “software” as follows:</p> <ul style="list-style-type: none"> <li>a. 2D or 3D viscous “software”, validated with wind tunnel or flight test data required for detailed engine flow modelling;</li> <li>b. “Software” for testing aero gas turbine engines, assemblies or components, specially designed to collect, reduce and analyse data in real time and capable of feedback control, including the dynamic adjustment of test articles or test conditions, as the test is in progress;</li> <li>c. “Software” specially designed to control directional solidification or single crystal casting;</li> <li>d. Not used;</li> <li>e. “Software” specially designed or modified for the operation of “UAVs” and associated systems, equipment and components, specified in Category Code 9A012;</li> <li>f. “Software” specially designed to design the internal cooling passages of aero gas turbine blades, vanes and “tip shrouds”;</li> <li>g. “Software” having all of the following: <ul style="list-style-type: none"> <li>1. Specially designed to predict aero thermal, aeromechanical and combustion conditions in aero gas turbine engines; <u>and</u></li> <li>2. Theoretical modelling predictions of the aero thermal, aeromechanical and combustion conditions, which have been validated with actual aero gas turbine engine (experimental or production) performance data.</li> </ul> </li> </ul>
9D101	<p>“Software” specially designed or modified for the “use” of goods specified in Category Code 9B105, 9B106, 9B116 or 9B117.</p>



<i>Category Code</i>	<i>Item Description</i>
9D103	<p>“Software” specially designed for modelling, simulation or design integration of the space launch vehicles specified in Category Code 9A004 or sounding rockets specified in Category Code 9A104, or the subsystems specified in Category Code 9A005, 9A007, 9A105, 9A106.c., 9A107, 9A108.c., 9A116 or 9A119.</p> <p><u>Note</u>  <i>“Software” specified in Category Code 9D103 remains within the description of that Category when combined with specially designed hardware specified in Category Code 4A102.</i></p>
9D104	<p>“Software” specially designed or modified for the “use” of goods specified in Category Code 9A001, 9A005, 9A006.d., 9A006.g., 9A007.a., 9A008.d., 9A009.a., 9A010.d., 9A011, 9A101, 9A102, 9A105, 9A106.c., 9A106.d., 9A107, 9A108.c., 9A109, 9A111, 9A115.a., 9A116.d., 9A117 or 9A118.</p>
9D105	<p>“Software” which coordinates the function of more than one subsystem, specially designed or modified for “use” in space launch vehicles specified in Category Code 9A004 or sounding rockets specified in Category Code 9A104.</p>
<b>9E</b>	<p><b>Technology</b></p> <p><u>Note</u>  <i>“Development” or “production” “technology” specified in Category Codes 9E001 to 9E003 for gas turbine engines remains within the description of that Category when used for repair or overhaul. Excluded from that Category are: technical data, drawings or documentation for maintenance activities directly associated with calibration, removal or replacement of damaged or unserviceable line replaceable units, including replacement of whole engines or engine modules.</i></p>
9E001	<p>“Technology” (according to the General Technology Note) for the “development” of equipment or “software”, specified in Category Code 9A001.b., 9A004 to 9A012, 9A350, Category 9B or 9D.</p>

<i>Category Code</i>	<i>Item Description</i>
9E002	<p>“Technology” (according to the General Technology Note) for the “production” of equipment specified in Category Code 9A001.b., 9A004 to 9A011, 9A350 or Category 9B.</p> <p><u>N.B.</u> For “technology” for the repair of structures, laminates or materials, see Category Code 1E002.f.</p>
9E003	<p>Other “technology” as follows:</p> <p>a. “Technology” “required” for the “development” or “production” of any of the following gas turbine engine components or systems:</p> <ol style="list-style-type: none"> <li>1. Gas turbine blades, vanes or “tip shrouds”, made from directionally solidified (DS) or single crystal (SC) alloys and having (in the 001 Miller Index Direction) a stress-rupture life exceeding 400 hours at 1,273 K (1,000°C) at a stress of 200 MPa, based on the average property values;</li> <li>2. Combustors having any of the following: <ol style="list-style-type: none"> <li>a. Thermally decoupled liners designed to operate at ‘combustor exit temperature’ exceeding 1,883 K (1,610°C);</li> <li>b. Non-metallic liners;</li> <li>c. Non-metallic shells; <u>or</u></li> <li>d. Liners designed to operate at ‘combustor exit temperature’ exceeding 1,883 K (1,610°C) and having holes that meet the parameters specified by Category Code 9E003.c.;</li> </ol> </li> </ol> <p><u>Note</u> The “required” “technology” for holes in Category Code 9E003.a.2. is limited to the derivation of the geometry and location of the holes.</p>

<i>Category Code</i>	<i>Item Description</i>
	<p data-bbox="608 454 791 488"><u>Technical Note</u></p> <p data-bbox="608 499 1260 763"><i>‘Combustor exit temperature’ is the bulk average gas path total (stagnation) temperature between the combustor exit plane and the leading edge of the turbine inlet guide vane (i.e. measured at engine station T40 as defined in SAE ARP 755A) when the engine is running in a ‘steady state mode’ of operation at the certificated maximum continuous operating temperature.</i></p> <p data-bbox="544 786 600 819"><u>N.B.</u></p> <p data-bbox="544 824 1257 891"><i>See Category Code 9E003.c. for “technology” “required” for manufacturing cooling holes.</i></p> <ol style="list-style-type: none"> <li data-bbox="544 909 1260 1290">3. Components manufactured from any of the following: <ol style="list-style-type: none"> <li data-bbox="632 958 1260 1025">a. Organic “composite” materials designed to operate above 588 K (315°C);</li> <li data-bbox="632 1043 1260 1178">b. Metal “matrix” “composite”, ceramic “matrix”, intermetallic or intermetallic reinforced materials, specified in Category Code 1C007; <u>or</u></li> <li data-bbox="632 1196 1260 1290">c. “Composite” material specified in Category Code 1C010 and manufactured with resins specified in Category Code 1C008;</li> </ol> </li> <li data-bbox="544 1308 1260 1469">4. Uncooled turbine blades, vanes, “tip-shrouds” or other components, designed to operate at gas path total (stagnation) temperatures of 1,323 K (1,050°C) or more at sea-level static take-off (ISA) in a ‘steady state mode’ of engine operation;</li> <li data-bbox="544 1487 1260 1624">5. Cooled turbine blades, vanes, “tip-shrouds” other than those described in Category Code 9E003.a.1., designed to operate at a ‘gas path temperature’ of 1,693 K (1,420°C) or more;</li> </ol>

Category Code	Item Description
	<p data-bbox="608 454 799 488"><u>Technical Notes</u></p> <ol style="list-style-type: none"> <li data-bbox="632 499 1262 730">1. 'Gas path temperature' is the bulk average gas path total (stagnation) temperature at the leading edge plane of the turbine component when the engine is running in a 'steady state mode' of operation at the certificated or specified maximum continuous operating temperature.</li> <li data-bbox="632 745 1262 947">2. The term 'steady state mode' defines engine operation conditions, where the engine parameters, such as thrust/power, rpm and others, have no appreciable fluctuations, when the ambient air temperature and pressure at the engine inlet are constant.</li> <li data-bbox="544 963 1262 1030">6. Airfoil-to-disk blade combinations using solid state joining;</li> <li data-bbox="544 1046 1262 1146">7. Gas turbine engine components using "diffusion bonding" "technology" specified in Category Code 2E003.b.;</li> <li data-bbox="544 1162 1262 1263">8. 'Damage tolerant' gas turbine engine rotor components using powder metallurgy materials specified in Category Code 1C002.b.; <u>or</u></li> </ol> <p data-bbox="608 1279 791 1312"><u>Technical Note</u></p> <p data-bbox="608 1323 1262 1424">'Damage tolerant' components are designed using methodology and substantiation to predict and limit crack growth.</p> <ol style="list-style-type: none"> <li data-bbox="544 1440 724 1473">9. Not used;</li> <li data-bbox="544 1489 724 1523">10. Not used;</li> <li data-bbox="544 1538 834 1572">11. Hollow fan blades;</li> </ol> <p data-bbox="480 1588 1262 1657">b. "Technology" "required" for the "development" or "production" of any of the following:</p> <ol style="list-style-type: none"> <li data-bbox="544 1673 1262 1774">1. Wind tunnel aero-models equipped with non-intrusive sensors capable of transmitting data from the sensors to the data acquisition system; <u>or</u></li> <li data-bbox="544 1789 1262 1890">2. "Composite" propeller blades or propfans, capable of absorbing more than 2,000 kW at flight speeds exceeding Mach 0.55;</li> </ol>

<i>Category Code</i>	<i>Item Description</i>
	<p>c. “Technology” “required” for manufacturing cooling holes, in gas turbine engine components incorporating any of the “technologies” specified by Category Code 9E003.a.1., 9E003.a.2. or 9E003.a.5., and having any of the following:</p> <ol style="list-style-type: none"> <li>1. Having all of the following: <ol style="list-style-type: none"> <li>a. Minimum ‘cross-sectional area’ less than 0.45 mm<sup>2</sup>;</li> <li>b. ‘Hole shape ratio’ greater than 4.52; <u>and</u></li> <li>c. ‘Incidence angle’ equal to or less than 25°; <u>or</u></li> </ol> </li> <li>2. Having all of the following: <ol style="list-style-type: none"> <li>a. Minimum ‘cross-sectional area’ less than 0.12 mm<sup>2</sup>;</li> <li>b. ‘Hole shape ratio’ greater than 5.65; <u>and</u></li> <li>c. ‘Incidence angle’ more than 25°;</li> </ol> </li> </ol> <p><u>Note</u></p> <p><i>Category Code 9E003.c. does not include “technology” for manufacturing constant radius cylindrical holes that are straight through and enter and exit on the external surfaces of the component.</i></p> <p><u>Technical Notes</u></p> <ol style="list-style-type: none"> <li>1. <i>For the purpose of Category Code 9E003.c., the ‘cross-sectional area’ is the area of the hole in the plane perpendicular to the hole axis.</i></li> <li>2. <i>For the purpose of Category Code 9E003.c., ‘hole shape ratio’ is the nominal length of the axis of the hole divided by the square root of its minimum ‘cross-sectional area’.</i></li> <li>3. <i>For the purpose of Category Code 9E003.c., ‘incidence angle’ is the acute angle measured between the plane tangential to the aerofoil surface and the hole axis at the point where the hole axis enters the aerofoil surface.</i></li> <li>4. <i>Techniques for manufacturing holes in Category Code 9E003.c. include “laser”, water jet, Electro-Chemical Machining (ECM) or Electrical Discharge Machining (EDM) methods.</i></li> </ol>

<i>Category Code</i>	<i>Item Description</i>
	<p>d. “Technology” “required” for the “development” or “production” of helicopter power transfer systems or tilt rotor or tilt wing “aircraft” power transfer systems;</p> <p>e. “Technology” for the “development” or “production” of reciprocating diesel engine ground vehicle propulsion systems having all of the following:</p> <ol style="list-style-type: none"> <li>1. ‘Box volume’ of 1.2 m<sup>3</sup> or less;</li> <li>2. An overall power output of more than 750 kW based on 80/1269/EEC, ISO 2534 or national equivalents; <u>and</u></li> <li>3. Power density of more than 700 kW/m<sup>3</sup> of ‘box volume’;</li> </ol> <p><i>Technical Note</i></p> <p><i>‘Box volume’ in Category Code 9E003.e. is the product of three perpendicular dimensions measured in the following way:</i></p> <p><i>Length:</i></p> <p><i>The length of the crankshaft from front flange to flywheel face;</i></p> <p><i>Width:</i></p> <p><i>The widest of any of the following:</i></p> <ol style="list-style-type: none"> <li>a. <i>The outside dimension from valve cover to valve cover;</i></li> <li>b. <i>The dimensions of the outside edges of the cylinder heads; <u>or</u></i></li> <li>c. <i>The diameter of the flywheel housing;</i></li> </ol> <p><i>Height:</i></p> <p><i>The largest of any of the following:</i></p> <ol style="list-style-type: none"> <li>a. <i>The dimension of the crankshaft centre-line to the top plane of the valve cover (or cylinder head) plus twice the stroke; <u>or</u></i></li> <li>b. <i>The diameter of the flywheel housing.</i></li> </ol>

<i>Category Code</i>	<i>Item Description</i>
	<p>f. “Technology” “required” for the “production” of specially designed components for high output diesel engines, as follows:</p> <ol style="list-style-type: none"> <li>1. “Technology” “required” for the “production” of engine systems having all of the following components employing ceramics materials specified in Category Code 1C007: <ol style="list-style-type: none"> <li>a. Cylinder liners;</li> <li>b. Pistons;</li> <li>c. Cylinder heads; <u>and</u></li> <li>d. One or more other components (including exhaust ports, turbochargers, valve guides, valve assemblies or insulated fuel injectors);</li> </ol> </li> <li>2. “Technology” “required” for the “production” of turbocharger systems with single-stage compressors and having all of the following: <ol style="list-style-type: none"> <li>a. Operating at pressure ratios of 4:1 or higher;</li> <li>b. Mass flow in the range from 30 kg to 130 kg per minute; <u>and</u></li> <li>c. Variable flow area capability within the compressor or turbine sections;</li> </ol> </li> <li>3. “Technology” “required” for the “production” of fuel injection systems with a specially designed multifuel (e.g. diesel or jet fuel) capability covering a viscosity range from diesel fuel (2.5 cSt at 310.8 K (37.8°C)) down to gasoline fuel (0.5 cSt at 310.8 K (37.8°C)) and having all of the following: <ol style="list-style-type: none"> <li>a. Injection amount in excess of 230 mm<sup>3</sup> per injection per cylinder; <u>and</u></li> <li>b. Electronic control features specially designed for switching governor characteristics automatically depending on fuel property to provide the same torque characteristics by using the appropriate sensors;</li> </ol> </li> </ol>

<i>Category Code</i>	<i>Item Description</i>
	<p data-bbox="480 454 1267 651">g. “Technology” “required” for the “development” or “production” of ‘high output diesel engines’ for solid, gas phase or liquid film (or combinations thereof) cylinder wall lubrication and permitting operation to temperatures exceeding 723 K (450°C), measured on the cylinder wall at the top limit of travel of the top ring of the piston;</p> <p data-bbox="544 674 727 701"><i>Technical Note</i></p> <p data-bbox="544 712 1267 846"><i>‘High output diesel engines’ are diesel engines with a specified brake mean effective pressure of 1.8 MPa or more at a speed of 2,300 rpm, provided the rated speed is 2,300 rpm or more.</i></p> <p data-bbox="480 869 1267 925">h. “Technology” for gas turbine engine “FADEC systems” as follows:</p> <ol data-bbox="544 947 1267 1413" style="list-style-type: none"> <li data-bbox="544 947 1267 1115">1. “Development” “technology” for deriving the functional requirements for the components necessary for the “FADEC system” to regulate engine thrust or shaft power (e.g. feedback sensor time constants and accuracies, fuel valve slew rate);</li> <li data-bbox="544 1137 1267 1261">2. “Development” or “production” “technology” for control and diagnostic components unique to the “FADEC system” and used to regulate engine thrust or shaft power;</li> <li data-bbox="544 1283 1267 1413">3. “Development” “technology” for the control law algorithms, including “source code”, unique to the “FADEC system” and used to regulate engine thrust or shaft power;</li> </ol> <p data-bbox="608 1435 667 1462"><i>Note</i></p> <p data-bbox="608 1473 1267 1740"><i>Category Code 9E003.h. does not include technical data related to engine-aircraft integration required by the relevant civil aviation certification authorities to be published for general airline use (e.g. installation manuals, operating instructions, instructions for continued airworthiness) or interface functions (e.g. input/output processing, airframe thrust or shaft power demand).</i></p>



<i>Category Code</i>	<i>Item Description</i>
	<p>i. “Technology” for adjustable flow path systems designed to maintain engine stability for gas generator turbines, fan or power turbines, or propelling nozzles, as follows:</p> <ol style="list-style-type: none"> <li>1. “Development” “technology” for deriving the functional requirements for the components that maintain engine stability;</li> <li>2. “Development” or “production” “technology” for components unique to the adjustable flow path system and that maintain engine stability;</li> <li>3. “Development” “technology” for the control law algorithms, including “source code”, unique to the adjustable flow path system and that maintain engine stability.</li> </ol> <p><u>Note</u>  <i>Category Code 9E003.i. does not include “development” or “production” “technology” for any of the following:</i></p> <ol style="list-style-type: none"> <li>a. <i>Inlet guide vanes;</i></li> <li>b. <i>Variable pitch fans or prop-fans;</i></li> <li>c. <i>Variable compressor vanes;</i></li> <li>d. <i>Compressor bleed valves; <u>or</u></i></li> <li>e. <i>Adjustable flow path geometry for reverse thrust.</i></li> </ol>
9E101	<p>a. “Technology” (according to the General Technology Note) for the “development” of goods specified in Category Codes 9A006.b., 9A006.f., 9A101, 9A102, 9A104 to 9A111 or 9A115 to 9A121.</p> <p>b. “Technology” (according to the General Technology Note) for the “production” of ‘UAVs’ specified in Category Code 9A012 or goods specified in Category Codes 9A006.b., 9A006.f., 9A101, 9A102, 9A104 to 9A111 or 9A115 to 9A121.</p> <p><u>Technical Note</u>  <i>In Category Code 9E101.b., ‘UAV’ means unmanned aerial vehicle systems capable of a range exceeding 300 km.</i></p>

<i>Category Code</i>	<i>Item Description</i>
9E102	<p>“Technology” (according to the General Technology Note) for the “use” of space launch vehicles specified in Category Code 9A004, goods specified in Category Codes 9A005 to 9A011, ‘UAVs’ specified in Category Code 9A012 or goods specified in Category Code 9A101, 9A102, 9A104 to 9A111, 9A115 to 9A121, 9B105, 9B106, 9B115, 9B116, 9B117, 9D101 or 9D103.</p> <p><i>Technical Note</i> In Category Code 9E102, ‘UAV’ means unmanned aerial vehicle systems capable of a range exceeding 300 km.</p>

Made on 3 September 2015.

OW FOONG PHENG  
*Permanent Secretary,*  
*Ministry of Trade and Industry,*  
*Singapore.*

[Customs (Conf.) 0117/2003/PTA; MTI 66/1-2-24 PT1 VOL3;  
AG/LEGIS/SL/300/2015/1 Vol. 9]