
First published in the *Government Gazette*, Electronic Edition, on 3 July 2017 at 5 pm.

No. S 366

STRATEGIC GOODS (CONTROL) ACT
(CHAPTER 300)

STRATEGIC GOODS (CONTROL)
ORDER 2017

ARRANGEMENT OF PARAGRAPHS

Paragraph

1. Citation and commencement
2. Strategic goods and strategic goods technology
3. Revocation

The Schedule

In exercise of the powers conferred by section 4A(1) of the Strategic Goods (Control) Act, the Minister for Trade and Industry (Trade) makes the following Order:

Citation and commencement

1. This Order is the Strategic Goods (Control) Order 2017 and comes into operation on 1 September 2017.

Strategic goods and strategic goods technology

2. The goods and technology specified in the Schedule are strategic goods and strategic goods technology, respectively, for the purposes of the Act.

Revocation

3. The Strategic Goods (Control) Order 2016 (G.N. No. S 427/2016) is revoked.

THE SCHEDULE

Paragraph 2

PART 1**MILITARY GOODS THE EXPORT, TRANSHIPMENT OR BRINGING
IN TRANSIT OF WHICH, AND TECHNOLOGY THE EXPORT OR
TRANSMISSION OF WHICH, REQUIRE A PERMIT***Division 1 — Preliminary Provisions**Subdivision 1 — General Notes*

1. Non-controlled goods (including plant) containing one or more controlled components set out in Division 2 are to be considered controlled goods within Division 2, if the controlled components are the principal element of the non-controlled goods and can feasibly be removed or used for other purposes.
2. In determining whether goods are to be considered the principal element of other goods for the purposes of paragraph 1, factors such as the quantity, value and technological know-how involved, and other special circumstances which might establish the goods as the principal element of those other goods, must be weighed.
3. Goods specified in Division 2 include both new and used goods.
4. Chemicals in Division 2 are listed by name and CAS number. Chemicals of the same structural formula (including hydrates) as chemicals listed in Division 2 are to be considered as coming within the descriptions of the second-mentioned chemicals regardless of name or CAS number. CAS numbers are shown in order to assist in identifying whether a particular chemical or mixture is a chemical within Division 2, irrespective of nomenclature. CAS numbers are not intended to be used as unique identifiers, because some forms of the listed chemical have different CAS numbers, and mixtures containing a listed chemical may also have different CAS numbers.
5. Specially formulated pharmaceutical products that contain any item under Category Code ML8 in Division 2 are not treated as coming under that Division.
6. An aircraft is not treated as coming under Category Code ML10 in Division 2, if it has no item listed in that Division and it is not configured for military use.

*Subdivision 2 — Definitions of Words and
Expressions in this Part*

7. In this Part, a word or expression in quotation marks (“ ”) takes the definition set out against it in this paragraph:

“additives” (ML8) means substances used in explosive formulations to improve their properties;

“aircraft” (ML8, ML10, ML14) means a fixed wing, swivel wing, rotary wing (helicopter), tilt rotor or tilt-wing airborne vehicle;

“automated command and control systems” (ML11) means electronic systems, through which information essential to the effective operation of the grouping, major formation, tactical formation, unit, ship, subunit or weapons under command is entered, processed and transmitted. This is achieved by the use of computer and other specialised hardware designed to support the functions of a military command and control organisation. The main functions of an automated command and control system are the efficient automated collection, accumulation, storage and processing of information; the display of the situation and the circumstances affecting the preparation and conduct of combat operations; operational and tactical calculations for the allocation of resources among force groupings or elements of the operational order of battle or battle deployment according to the mission or stage of the operation; the preparation of data for appreciation of the situation and decision-making at any point during operation or battle; and computer simulation of operations;

“biocatalysts” (ML7, ML22) means enzymes for specific chemical or biochemical reactions or other biological compounds which bind to and accelerate the degradation of CW agents;

“biological agents” (ML7) means pathogens or toxins, selected or modified (such as by altering the purity, shelf life, virulence, dissemination characteristics, or resistance to UV radiation) to produce casualties in humans or animals, degrade equipment or damage crops or the environment;

“biopolymers” (ML7) means any of the following biological macromolecules:

- a. Enzymes for specific chemical or biochemical reactions;
- b. ‘Anti-idiotypic antibodies’, ‘monoclonal antibodies’ or ‘polyclonal antibodies’; or

- c. Specially designed or specially processed ‘receptors’;

Technical Notes

1. *‘Anti-idiotypic antibodies’ means antibodies which bind to the specific antigen binding sites of other antibodies.*
2. *‘Monoclonal antibodies’ means proteins which bind to one antigenic site and are produced by a single clone of cells.*
3. *‘Polyclonal antibodies’ means a mixture of proteins which bind to the specific antigen and are produced by more than one clone of cells.*
4. *‘Receptors’ means biological macromolecular structures capable of binding ligands, the binding of which affects physiological functions.*

“civil aircraft” (ML4, ML10) means an “aircraft” listed by designation in published airworthiness certification lists by civil aviation authorities of one or more “participating states” to fly commercial civil internal and external routes or for legitimate civil, private or business use;

“deactivated firearm” (ML1) means a firearm that has been made incapable of firing any projectile by processes. These processes permanently modify the essential elements of the firearm. Deactivation of the firearm may be attested by a certificate delivered by a competent authority of the country in which the firearm is deactivated and may be marked on the firearm by a stamp on an essential part;

“development” (All Categories) has the same meaning as in the Act;

“end-effectors” (ML17) means grippers, ‘active tooling units’ and any other tooling that is attached to the baseplate on the end of a “robot” manipulator arm;

Technical Note

‘Active tooling units’ means devices for applying motive power, process energy or sensing to a workpiece.

“energetic materials” (ML8) means substances or mixtures that react chemically to release energy required for their intended application. “Explosives”, “pyrotechnics” and “propellants” are subclasses of energetic materials;

“explosives” (ML8, ML18) means solid, liquid or gaseous substances or mixtures of substances which, in their application as primary, booster, or main charges in warheads, demolition and other applications, are required to detonate;

“expression vectors” (ML7) means carriers (e.g. plasmid and virus) used to introduce genetic material into host cells;

“fibrous or filamentary materials” (ML13) includes the following:

- a. Continuous monofilaments;
- b. Continuous yarns and rovings;
- c. Tapes, fabrics, random mats and braids;
- d. Chopped fibres, staple fibres and coherent fibre blankets;
- e. Whiskers, either monocrystalline or polycrystalline, of any length;
- f. Aromatic polyamide pulp;

“first generation image intensifier tubes” (ML15) means electrostatically focused tubes, employing input and output fibre optic or glass face plates, or multi-alkali photocathodes (S-20 or S-25), but not microchannel plate amplifiers;

“fuel cell” (ML17) means an electrochemical device that converts chemical energy directly into Direct Current (DC) electricity by consuming fuel from an external source;

“laser” (ML9, ML17, ML19) means an item that produces spatially and temporally coherent light through amplification by stimulated emission of radiation;

“library” (parametric technical database) (ML17) means a collection of technical information, reference to which may enhance the performance of relevant systems, equipment or components;

“lighter-than-air vehicles” (ML10) means balloons and ‘airships’ that rely on hot air or on lighter-than-air gases such as helium or hydrogen for their lift;

Technical Note

‘Airship’ means a power-driven airborne vehicle that is kept buoyant by a body of gas (usually helium, formerly hydrogen) which is lighter than air.

“nuclear reactor” (ML17) includes the items within or attached directly to the reactor vessel, the equipment which controls the level of power in the core, and the components which normally contain or come into direct contact with or control the primary coolant of the reactor core;

“participating state” (ML4, ML10) means a state participating in the Wassenaar Arrangement (details of which are set out in <http://www.wassenaar.org/participants/index.html>);

“precursors” (ML8) means speciality chemicals used in the manufacture of “explosives”;

“production” (All Categories) has the same meaning as in the Act;

“propellants” (ML8, ML18) means substances or mixtures that react chemically to produce large volumes of hot gases at controlled rates to perform mechanical work;

“pyrotechnic(s)” (ML4, ML8) means mixtures of solid or liquid fuels and oxidisers which, when ignited, undergo an energetic chemical reaction at a controlled rate intended to produce specific time delays, or quantities of heat, noise, smoke, visible light or infrared radiation. Pyrophorics are a subclass of “pyrotechnics”, which contain no oxidisers but ignite spontaneously on contact with air;

“required” (ML22), in relation to “technology”, means only that portion of “technology” which is peculiarly responsible for achieving or exceeding the controlled performance levels, characteristics or functions. Such “required” “technology” may be shared by different products;

“riot control agents” (ML7) means substances which, under the expected conditions of use for riot control purposes, produce rapidly in human sensory irritation or disabling physical effects which disappear within a short time following termination of exposure;

Technical Note

Tear gases are a subset of “riot control agents”.

“robot” (ML17) means a manipulation mechanism, which may be of the continuous path or the point-to-point variety, may use sensors, and has all the following characteristics:

- a. It is multifunctional;
- b. It is capable of positioning or orienting material, parts, tools or special devices through variable movements in three dimensional space;
- c. It incorporates three or more closed or open loop servo-devices which may include stepping motors; and
- d. It has ‘user-accessible programmability’ by means of the teach/playback method or by means of an electronic computer which may be a programmable logic controller, i.e. without mechanical intervention;

Technical Note

'User-accessible programmability' means the facility allowing a user to insert, modify or replace 'programs' by means other than:

- a. A physical change in wiring or interconnections; or*
- b. The setting of function controls including entry of parameters;*

Technical Note

'Program' means a sequence of instructions to carry out a process in, or convertible into, a form executable by an electronic computer.

Note

"Robot" does not include the following devices:

- a. Manipulation mechanisms which are only manually or teleoperator controllable;*
- b. Fixed sequence manipulation mechanisms which are automated moving devices, operating according to mechanically fixed programmed motions. The program is mechanically limited by fixed stops, such as pins or cams. The sequence of motions and the selection of paths or angles are not variable or changeable by mechanical, electronic or electrical means;*
- c. Mechanically controlled variable sequence manipulation mechanisms which are automated moving devices, operating according to mechanically fixed programmed motions. The program is mechanically limited by fixed, but adjustable stops such as pins or cams. The sequence of motions and the selection of paths or angles are variable within the fixed program pattern. Variations or modifications of the program pattern (e.g. changes of pins or exchanges of cams) in one or more motion axes are accomplished only through mechanical operations;*
- d. Non-servo-controlled variable sequence manipulation mechanisms which are automated moving devices, operating according to mechanically fixed programmed motions. The program is variable but the sequence proceeds only by the binary signal from mechanically fixed electrical binary devices or adjustable stops;*

- e. *Stacker cranes defined as Cartesian coordinate manipulator systems manufactured as an integral part of a vertical array of storage bins and designed to access the contents of those bins for storage or retrieval.*

“software” (All Categories) means a collection of one or more ‘programs’ or ‘microprograms’ recorded, stored or embodied in any device;

Technical Notes

1. *‘Program’ means a sequence of instructions to carry out a process in, or convertible into, a form executable by an electronic computer.*
2. *‘Microprogram’ means a sequence of elementary instructions, maintained in a special storage, the execution of which is initiated by the introduction of its reference instruction into an instruction register.*

“spacecraft” (ML11) means active and passive satellites and space probes;

“space-qualified” (ML19) means designed, manufactured, or qualified through successful testing, for operation at altitudes greater than 100 km above the surface of the Earth;

Note

A determination that a specific item is “space-qualified” by virtue of testing does not mean that other items in the same production run or model series are “space-qualified” if not individually tested.

“superconductive” (ML20), in relation to any equipment, means the equipment is made of any material (such as a metal, alloy or compound) which can lose all electrical resistance (i.e. it can attain infinite electrical conductivity and carry very large electrical currents without Joule heating);

Technical Note

The “superconductive” state of a material is individually characterised by a ‘critical temperature’, a critical magnetic field, which is a function of temperature, and a critical current density, which is a function of both magnetic field and temperature.

Technical Note

‘Critical temperature’ (sometimes referred to as the transition temperature) of a specific “superconductive” material is the temperature at which the material loses all resistance to the flow of direct electrical current.

“technology” (All Categories) means information (including information comprised in such documents as specifications, blueprints, plans, manuals, models, diagrams, formulae, tables and designs) that is necessary for the “development”, “production” or ‘use’ of any goods;

Technical Note

‘Use’ has the same meaning as in the Act.

“unmanned aerial vehicle” (“UAV”) (ML10) means any “aircraft” capable of initiating flight and sustaining controlled flight and navigation without any human presence on board.

8. In paragraph 7, a reference to a Category Code (prefixed with the abbreviation “ML”) in brackets is a reference to that Category Code in Division 2 in which the defined word or expression appears.
9. In this Part, a word or expression enclosed with single quotation marks (‘ ’) takes the definition set out against it in the Technical Note that follows immediately after the definition in which the word or expression appears.

Subdivision 3 — Acronyms and Abbreviations used in this Part

The acronyms and abbreviations used in this Part and set out in the first column have the meanings set out against them in the second column.

<i>First Column</i>	<i>Second Column</i>
<i>Acronym or Abbreviation</i>	<i>Meaning</i>
CAS	Chemical Abstract Service
CW	chemical warfare
UV	ultraviolet

Division 2 — List of Military Goods

<i>Category Code</i>	<i>Item Description</i>
ML1	<p>Smooth-bore weapons with a calibre of less than 20 mm, other arms and automatic weapons with a calibre of 12.7 mm (calibre 0.5 inches) or less and accessories, as follows, and specially designed components therefor:</p> <p><i>Note</i></p> <p><i>Category Code ML1 does not apply to the following:</i></p> <ul style="list-style-type: none"> a. <i>Firearms specially designed for dummy ammunition and which are incapable of discharging a projectile;</i> b. <i>Firearms specially designed to launch tethered projectiles having no high explosive charge or communications link, to a range of less than or equal to 500 m;</i> c. <i>Weapons using non-centre fire cased ammunition and which are not of the fully automatic firing type;</i> d. <i>“Deactivated firearms”.</i> <ul style="list-style-type: none"> a. Rifles and combination guns, handguns, machine, sub-machine and volley guns; <p><i>Note</i></p> <p><i>Category Code ML1.a. does not apply to the following:</i></p> <ul style="list-style-type: none"> a. <i>Rifles and combination guns, manufactured earlier than 1938;</i> b. <i>Reproductions of rifles and combination guns, the originals of which were manufactured earlier than 1890;</i> c. <i>Handguns, volley guns and machine guns, manufactured earlier than 1890, and their reproductions;</i> d. <i>Rifles or handguns, specially designed to discharge an inert projectile by compressed air or CO₂.</i> <ul style="list-style-type: none"> b. Smooth-bore weapons as follows: <ul style="list-style-type: none"> 1. Smooth-bore weapons specially designed for military use;

<i>Category Code</i>	<i>Item Description</i>
	<p>2. Other smooth-bore weapons as follows:</p> <ol style="list-style-type: none"> a. Fully automatic type weapons; b. Semi-automatic or pump-action type weapons; <p><u>Note</u> <i>Category Code ML1.b.2. does not apply to weapons specially designed to discharge an inert projectile by compressed air or CO₂.</i></p> <p><u>Note</u> <i>Category Code ML1.b. does not apply to the following:</i></p> <ol style="list-style-type: none"> a. Smooth-bore weapons manufactured earlier than 1938; b. Reproductions of smooth-bore weapons, the originals of which were manufactured earlier than 1890; c. Smooth-bore weapons used for hunting or sporting purposes. These weapons must not be specially designed for military use or of the fully automatic firing type; d. Smooth-bore weapons specially designed for any of the following: <ol style="list-style-type: none"> 1. Slaughtering of domestic animals; 2. Tranquilizing of animals; 3. Seismic testing; 4. Firing of industrial projectiles; <u>or</u> 5. Disrupting Improvised Explosive Devices (IEDs). <p><u>N.B.</u> <i>For disruptors, see Category Code ML4 and Category Code 1A006 in Division 2 of Part 2 of this Schedule.</i></p> <p>c. Weapons using caseless ammunition;</p>

<i>Category Code</i>	<i>Item Description</i>
ML2	<p>d. Detachable cartridge magazines, sound suppressors or moderators, special gun-mountings, optical weapon-sights and flash suppressors, for arms specified in Category Code ML1.a., ML1.b. or ML1.c.</p> <p><i>Note</i> <i>Category Code ML1.d. does not apply to optical weapon-sights without electronic image processing, with a magnification of 9 times or less, provided they are not specially designed or modified for military use, and do not incorporate any reticles specially designed for military use.</i></p> <p>Smooth-bore weapons with a calibre of 20 mm or more, other weapons or armament with a calibre greater than 12.7 mm (calibre 0.5 inches), projectors and accessories, as follows, and specially designed components therefor:</p> <p>a. Guns, howitzers, cannon, mortars, anti-tank weapons, projectile launchers, military flame throwers, rifles, recoilless rifles, smooth-bore weapons and signature reduction devices therefor;</p> <p><i>Note 1</i> <i>Category Code ML2.a. includes injectors, metering devices, storage tanks and other specially designed components for use with liquid propelling charges for any of the equipment specified in Category Code ML2.a.</i></p> <p><i>Note 2</i> <i>Category Code ML2.a. does not apply to weapons as follows:</i></p> <p>a. <i>Rifles, smooth-bore weapons and combination guns, manufactured earlier than 1938;</i></p> <p>b. <i>Reproductions of rifles, smooth-bore weapons and combination guns, the originals of which were manufactured earlier than 1890;</i></p> <p>c. <i>Guns, howitzers, cannons and mortars, manufactured earlier than 1890;</i></p>

<i>Category Code</i>	<i>Item Description</i>
	<p>d. <i>Smooth-bore weapons used for hunting or sporting purposes. These weapons must not be specially designed for military use or of the fully automatic firing type;</i></p> <p>e. <i>Smooth-bore weapons specially designed for any of the following:</i></p> <ol style="list-style-type: none"> 1. <i>Slaughtering of domestic animals;</i> 2. <i>Tranquilizing of animals;</i> 3. <i>Seismic testing;</i> 4. <i>Firing of industrial projectiles; <u>or</u></i> 5. <i>Disrupting Improvised Explosive Devices (IEDs);</i> <p><u><i>N.B.</i></u> <i>For disruptors, see Category Code ML4 and Category Code 1A006 in Division 2 of Part 2 of this Schedule.</i></p> <p>f. <i>Hand-held projectile launchers specially designed to launch tethered projectiles having no high explosive charge or communications link, to a range of less than or equal to 500 m.</i></p> <p>b. <i>Smoke, gas and pyrotechnic projectors or generators, specially designed or modified for military use;</i></p> <p><u><i>Note</i></u> <i>Category Code ML2.b. does not apply to signal pistols.</i></p> <p>c. <i>Weapon-sights and weapon-sight mounts, having all of the following characteristics:</i></p> <ol style="list-style-type: none"> 1. <i>Specially designed for military use; <u>and</u></i> 2. <i>Specially designed for weapons specified in Category Code ML2.a.;</i> <p>d. <i>Mountings and detachable cartridge magazines, specially designed for the weapons specified in Category Code ML2.a.</i></p>

<i>Category Code</i>	<i>Item Description</i>
ML3	<p>Ammunition and fuse setting devices, as follows, and specially designed components therefor:</p> <ol style="list-style-type: none"> a. Ammunition for weapons specified in Category Code ML1, ML2 or ML12; b. Fuse setting devices specially designed for ammunition specified in Category Code ML3.a. <p><u>Note 1</u> Specially designed components specified in Category Code ML3 include:</p> <ol style="list-style-type: none"> a. Metal or plastic fabrications such as primer anvils, bullet cups, cartridge links, rotating bands and munitions metal parts; b. Safing and arming devices, fuses, sensors and initiation devices; c. Power supplies with high one-time operational output; d. Combustible cases for charges; e. Submunitions including bomblets, minelets and terminally guided projectiles. <p><u>Note 2</u> Category Code ML3.a. does not apply to any of the following:</p> <ol style="list-style-type: none"> a. Ammunition crimped without a projectile (blank star); b. Dummy ammunition with a pierced powder chamber; c. Other blank and dummy ammunition, not incorporating components designed for live ammunition; <u>or</u> d. Components specially designed for blank or dummy ammunition, specified in this Note 2.a., b., or c. <p><u>Note 3</u> Category Code ML3.a. does not apply to cartridges specially designed for any of the following purposes:</p> <ol style="list-style-type: none"> a. Signalling; b. Bird scaring; <u>or</u> c. Lighting of gas flares at oil wells.

<i>Category Code</i>	<i>Item Description</i>
ML4	<p>Bombs, torpedoes, rockets, missiles, other explosive devices and charges and related equipment and accessories, as follows, and specially designed components therefor:</p> <p><u><i>N.B. 1</i></u> <i>For guidance and navigation equipment, see Category Code ML11.</i></p> <p><u><i>N.B. 2</i></u> <i>For Aircraft Missile Protection Systems (AMPS), see Category Code ML4.c.</i></p> <p>a. Bombs, torpedoes, grenades, smoke canisters, rockets, mines, missiles, depth charges, demolition-charges, demolition-devices, demolition-kits, “pyrotechnic” devices, cartridges and simulators (i.e. equipment simulating the characteristics of any of these items), specially designed for military use;</p> <p><u><i>Note</i></u> <i>Category Code ML4.a. includes:</i></p> <p>a. <i>Smoke grenades, fire bombs, incendiary bombs and explosive devices;</i></p> <p>b. <i>Missile rocket nozzles and re-entry vehicle nosetips.</i></p> <p>b. Equipment having all of the following characteristics:</p> <ol style="list-style-type: none"> 1. Specially designed for military use; <u>and</u> 2. Specially designed for ‘activities’ relating to any of the following: <ol style="list-style-type: none"> a. Items specified in Category Code ML4.a.; <u>or</u> b. Improvised Explosive Devices (IEDs); <p><u><i>Technical Note</i></u> <i>For the purpose of Category Code ML4.b.2., ‘activities’ applies to handling, launching, laying, controlling, discharging, detonating, activating, powering with one-time operational output, decoying, jamming, sweeping, detecting, disrupting or disposing.</i></p>

<i>Category Code</i>	<i>Item Description</i>
	<p><u>Note 1</u> Category Code ML4.b. includes:</p> <ul style="list-style-type: none"> a. Mobile gas liquefying equipment capable of producing 1,000 kg or more per day of gas in liquid form; b. Buoyant electric conducting cable suitable for sweeping magnetic mines. <p><u>Note 2</u> Category Code ML4.b. does not apply to hand-held devices limited by design solely to the detection of metal objects and incapable of distinguishing between mines and other metal objects.</p> <ul style="list-style-type: none"> c. Aircraft Missile Protection Systems (AMPS). <p><u>Note</u> Category Code ML4.c. does not apply to AMPS having all of the following characteristics:</p> <ul style="list-style-type: none"> a. Have any of the following missile warning sensors: <ul style="list-style-type: none"> 1. Passive sensors having peak response between 100 nm - 400 nm; <u>or</u> 2. Active pulsed Doppler missile warning sensors; b. Have countermeasures dispensing systems; c. Have flares, which exhibit both a visible signature and an infrared signature, for acting as decoys for surface-to-air missiles; <u>and</u> d. Installed on “civil aircraft” and having all of the following characteristics: <ul style="list-style-type: none"> 1. The AMPS is only operable in a specific “civil aircraft” in which the specific AMPS is installed and for which any of the following has been issued: <ul style="list-style-type: none"> a. A civil Type Certificate issued by civil aviation authorities of one or more “participating states”; <u>or</u>

<i>Category Code</i>	<i>Item Description</i>
ML5	<p data-bbox="715 454 1272 555"><i>b. An equivalent document recognised by the International Civil Aviation Organisation (ICAO);</i></p> <p data-bbox="651 573 1272 640"><i>2. The AMPS employs protection to prevent unauthorised access to “software”; and</i></p> <p data-bbox="651 658 1272 786"><i>3. The AMPS incorporates an active mechanism that forces the system not to function when it is removed from the “civil aircraft” in which it was installed.</i></p> <p data-bbox="501 857 1272 985">Fire control, and related alerting and warning equipment, and related systems, test and alignment and countermeasure equipment, as follows, specially designed for military use, and specially designed components and accessories therefor:</p> <p data-bbox="501 1003 1272 1070"><i>a. Weapon-sights, bombing computers, gun laying equipment and weapon control systems;</i></p> <p data-bbox="501 1088 1272 1216"><i>b. Target acquisition, designation, range-finding, surveillance or tracking systems; detection, data fusion, recognition or identification equipment; and sensor integration equipment;</i></p> <p data-bbox="501 1234 1272 1301"><i>c. Countermeasure equipment for items specified in Category Code ML5.a. or ML5.b.;</i></p> <p data-bbox="564 1323 628 1357"><i>Note</i></p> <p data-bbox="564 1361 1272 1429"><i>For the purpose of Category Code ML5.c., countermeasure equipment includes detection equipment.</i></p> <p data-bbox="501 1447 1272 1547"><i>d. Field test or alignment equipment, specially designed for items specified in Category Code ML5.a., ML5.b. or ML5.c.</i></p>
ML6	<p data-bbox="501 1619 1043 1653">Ground vehicles and components, as follows:</p> <p data-bbox="501 1664 564 1697"><i>N.B.</i></p> <p data-bbox="501 1709 1272 1776"><i>For guidance and navigation equipment, see Category Code ML11.</i></p> <p data-bbox="501 1794 1272 1861"><i>a. Ground vehicles and components therefor, specially designed or modified for military use;</i></p>

<i>Category Code</i>	<i>Item Description</i>
	<p><u>Technical Note</u> <i>For the purpose of Category Code ML6.a., the term ground vehicles includes trailers.</i></p> <p>b. Other ground vehicles and components, as follows:</p> <p>1. Vehicles having all of the following characteristics:</p> <p>a. Manufactured or fitted with materials or components to provide ballistic protection to level III (NIJ 0108.01, September 1985, or comparable national standard) or better;</p> <p>b. Have a transmission to provide drive to both front and rear wheels simultaneously, including those vehicles having additional wheels for load bearing purposes whether driven or not;</p> <p>c. Gross Vehicle Weight Rating (GVWR) greater than 4,500 kg; <u>and</u></p> <p>d. Designed or modified for off-road use;</p> <p>2. Components having all of the following characteristics:</p> <p>a. Specially designed for vehicles specified in Category Code ML6.b.1.; <u>and</u></p> <p>b. Providing ballistic protection to level III (NIJ 0108.01, September 1985, or comparable national standard) or better.</p> <p><u>N.B.</u> <i>See also Category Code ML13.a.</i></p> <p><u>Note 1</u> <i>Category Code ML6.a. includes:</i></p> <p>a. <i>Tanks and other military armed vehicles and military vehicles fitted with mountings for arms or equipment for mine laying or the launching of munitions specified in Category Code ML4;</i></p> <p>b. <i>Armoured vehicles;</i></p> <p>c. <i>Amphibious and deep water fording vehicles;</i></p>

<i>Category Code</i>	<i>Item Description</i>
	<p data-bbox="502 448 1260 548"><i>d. Recovery vehicles and vehicles for towing or transporting ammunition or weapon systems and associated load handling equipment.</i></p> <p data-bbox="502 571 582 600"><u>Note 2</u></p> <p data-bbox="502 604 1260 739"><i>Under Category Code ML6.a., modification of a ground vehicle for military use entails a structural, electrical or mechanical change involving one or more components that are specially designed for military use. Such components include:</i></p> <p data-bbox="502 761 1260 817"><i>a. Pneumatic tyre casings of a kind specially designed to be bullet-proof;</i></p> <p data-bbox="502 840 1260 907"><i>b. Armoured protection of vital parts (e.g. fuel tanks or vehicle cabs);</i></p> <p data-bbox="502 929 1165 958"><i>c. Special reinforcements or mountings for weapons;</i></p> <p data-bbox="502 974 790 1003"><i>d. Black-out lighting.</i></p> <p data-bbox="502 1025 582 1055"><u>Note 3</u></p> <p data-bbox="502 1064 1260 1131"><i>Category Code ML6 does not apply to civil vehicles designed or modified for transporting money or valuables.</i></p> <p data-bbox="502 1153 582 1182"><u>Note 4</u></p> <p data-bbox="502 1191 1260 1258"><i>Category Code ML6 does not apply to vehicles that meet all of the following:</i></p> <p data-bbox="502 1276 957 1305"><i>a. Were manufactured before 1946;</i></p> <p data-bbox="502 1328 1260 1429"><i>b. Do not have items specified in any part of this Division and manufactured after 1945, except for reproductions of original components or accessories for the vehicle; <u>and</u></i></p> <p data-bbox="502 1444 1260 1545"><i>c. Do not incorporate weapons specified in Category Code ML1, ML2 or ML4 unless they are inoperable and incapable of discharging a projectile.</i></p>
ML7	<p data-bbox="502 1612 1260 1713"><i>Chemical agents, “biological agents”, “riot control agents”, radioactive materials, related equipment, components and materials, as follows:</i></p> <p data-bbox="502 1724 1260 1859"><i>a. “Biological agents” or radioactive materials selected or modified to increase their effectiveness in producing casualties in humans or animals, degrading equipment or damaging crops or the environment;</i></p>

<i>Category Code</i>	<i>Item Description</i>
	<p>b. Chemical warfare (CW) agents, including:</p> <p>1. CW nerve agents:</p> <p>a. O-Alkyl (equal to or less than C₁₀, including cycloalkyl) alkyl (Methyl, Ethyl, n-Propyl or Isopropyl)-phosphonofluoridates, such as:</p> <ol style="list-style-type: none"> 1. Sarin (GB):O-Isopropyl methylphosphonofluoridate (107-44-8); 2. Soman (GD):O-Pinacolyl methylphosphonofluoridate (96-64-0); <p>b. O-Alkyl (equal to or less than C₁₀, including cycloalkyl) N,N-dialkyl (Methyl, Ethyl, n-Propyl or Isopropyl) phosphoramidocyanidates, such as:</p> <ol style="list-style-type: none"> 1. Tabun (GA):O-Ethyl N,N-dimethylphosphoramidocyanidate (77-81-6); <p>c. O-Alkyl (H or equal to or less than C₁₀, including cycloalkyl) S-2-dialkyl (Methyl, Ethyl, n-Propyl or Isopropyl)-aminoethyl alkyl (Methyl, Ethyl, n-Propyl or Isopropyl) phosphonothiolates and corresponding alkylated and protonated salts, such as:</p> <ol style="list-style-type: none"> 1. VX: O-Ethyl S-2-diisopropylaminoethyl methyl phosphonothiolate (50782-69-9); <p>2. CW vesicant agents:</p> <p>a. Sulphur mustards, such as:</p> <ol style="list-style-type: none"> 1. 2-Chloroethylchloromethylsulphide (2625-76-5); 2. Bis(2-chloroethyl) sulphide (505-60-2); 3. Bis(2-chloroethylthio) methane (63869-13-6); 4. 1,2-bis (2-chloroethylthio) ethane (3563-36-8); 5. 1,3-bis (2-chloroethylthio) -n-propane (63905-10-2);

<i>Category Code</i>	<i>Item Description</i>
	6. 1,4-bis (2-chloroethylthio) -n-butane (142868-93-7);
	7. 1,5-bis (2-chloroethylthio) -n-pentane (142868-94-8);
	8. Bis (2-chloroethylthiomethyl) ether (63918-90-1);
	9. Bis (2-chloroethylthioethyl) ether (63918-89-8);
	b. Lewisites, such as:
	1. 2-chlorovinylchloroarsine (541-25-3);
	2. Tris (2-chlorovinyl) arsine (40334-70-1);
	3. Bis (2-chlorovinyl) chloroarsine (40334-69-8);
	c. Nitrogen mustards, such as:
	1. HN1: bis (2-chloroethyl) ethylamine (538-07-8);
	2. HN2: bis (2-chloroethyl) methylamine (51-75-2);
	3. HN3: tris (2-chloroethyl) amine (555-77-1);
	3. CW incapacitating agents, such as:
	a. 3-Quinuclidinyl benzilate (BZ) (6581-06-2);
	4. CW defoliants, such as
	a. Butyl 2-chloro-4-fluorophenoxyacetate (LNF);
	b. 2,4,5-trichlorophenoxyacetic acid (93-76-5) mixed with 2,4-dichlorophenoxyacetic acid (94-75-7) (Agent Orange (39277-47-9));

<i>Category Code</i>	<i>Item Description</i>
	<p>c. CW binary precursors and key precursors, as follows:</p> <ol style="list-style-type: none"> 1. Alkyl (Methyl, Ethyl, n-Propyl or Isopropyl) Phosphonyl Difluorides, such as: <ol style="list-style-type: none"> a. DF: Methyl Phosphonyldifluoride (676-99-3); 2. O-Alkyl (H or equal to or less than C₁₀, including cycloalkyl) O-2-dialkyl (Methyl, Ethyl, n-Propyl or Isopropyl)-aminoethyl alkyl (Methyl, Ethyl, n-Propyl or Isopropyl) phosphonites and corresponding alkylated and protonated salts, such as: <ol style="list-style-type: none"> a. QL: O-Ethyl O-2-di-isopropylaminoethyl methylphosphonite (57856-11-8); 3. Chlorosarin: O-Isopropyl methylphosphonochloridate (1445-76-7); 4. Chlorosoman: O-Pinacolyl methylphosphonochloridate (7040-57-5); <p>d. “Riot control agents”, active constituent chemicals and combinations thereof, including:</p> <ol style="list-style-type: none"> 1. α-Bromobenzeneacetonitrile, (Bromobenzyl cyanide) (CA) (5798-79-8); 2. [(2-chlorophenyl) methylene] propanedinitrile, (o-Chlorobenzylidenemalononitrile) (CS) (2698-41-1); 3. 2-Chloro-1-phenylethanone, Phenylacetyl chloride (ω-chloroacetophenone) (CN) (532-27-4); 4. Dibenz-(b,f)-1,4-oxazephine, (CR) (257-07-8); 5. 10-Chloro-5,10-dihydrophenarsazine, (Phenarsazine chloride), (Adamsite), (DM) (578-94-9); 6. N-Nonanoylmorpholine, (MPA) (5299-64-9); <p><u>Note 1</u> <i>Category Code ML7.d. does not apply to “riot control agents” individually packaged for personal self-defence purposes.</i></p>

<i>Category Code</i>	<i>Item Description</i>
	<p data-bbox="566 448 646 481"><u>Note 2</u></p> <p data-bbox="566 492 1260 593"><i>Category Code ML7.d. does not apply to active constituent chemicals, and combinations thereof, identified and packaged for food production or medical purposes.</i></p> <p data-bbox="502 604 1260 705">e. Equipment, specially designed or modified for military use, designed or modified for the dissemination of any of the following, and specially designed components therefor:</p> <ol data-bbox="566 716 1260 873" style="list-style-type: none"> <li data-bbox="566 716 1260 795">1. Materials or agents specified in Category Code ML7.a., ML7.b. or ML7.d.; <u>or</u> <li data-bbox="566 806 1260 873">2. CW agents made up of precursors specified in Category Code ML7.c.; <p data-bbox="502 884 1260 985">f. Protective and decontamination equipment, specially designed or modified for military use, components and chemical mixtures, as follows:</p> <ol data-bbox="566 996 1260 1444" style="list-style-type: none"> <li data-bbox="566 996 1260 1142">1. Equipment designed or modified for defence against materials specified in Category Code ML7.a., ML7.b. or ML7.d., and specially designed components therefor; <li data-bbox="566 1153 1260 1299">2. Equipment designed or modified for decontamination of objects contaminated with materials specified in Category Code ML7.a. or ML7.b., and specially designed components therefor; <li data-bbox="566 1310 1260 1444">3. Chemical mixtures specially developed or formulated for the decontamination of objects contaminated with materials specified in Category Code ML7.a. or ML7.b.; <p data-bbox="566 1456 630 1489"><u>Note</u></p> <p data-bbox="566 1500 965 1534"><i>Category Code ML7.f.1. includes:</i></p> <ol data-bbox="566 1545 1260 1668" style="list-style-type: none"> <li data-bbox="566 1545 1260 1624">a. <i>Air conditioning units specially designed or modified for nuclear, biological or chemical filtration;</i> <li data-bbox="566 1635 861 1668">b. <i>Protective clothing.</i> <p data-bbox="566 1680 622 1713"><u>N.B.</u></p> <p data-bbox="566 1724 1260 1825"><i>For civil gas masks, protective and decontamination equipment, see also Category Code 1A004 in Division 2 of Part 2 of this Schedule.</i></p>

<i>Category Code</i>	<i>Item Description</i>
	<p data-bbox="501 456 1268 584">g. Equipment, specially designed or modified for military use, designed or modified for the detection or identification of materials specified in Category Code ML7.a., ML7.b. or ML7.d., and specially designed components therefor;</p> <p data-bbox="564 607 624 633"><i>Note</i></p> <p data-bbox="564 647 1268 712"><i>Category Code ML7.g. does not apply to personal radiation monitoring dosimeters.</i></p> <p data-bbox="564 732 624 759"><i>N.B.</i></p> <p data-bbox="564 772 1268 837"><i>See also Category Code 1A004 in Division 2 of Part 2 of this Schedule.</i></p> <p data-bbox="501 857 1268 985">h. “Biopolymers” specially designed or processed for the detection or identification of CW agents specified in Category Code ML7.b., and the cultures of specific cells used to produce them;</p> <p data-bbox="501 1005 1268 1070">i. “Biocatalysts” for the decontamination or degradation of CW agents, and biological systems therefor, as follows:</p> <ol data-bbox="564 1090 1268 1518" style="list-style-type: none"> <li data-bbox="564 1090 1268 1256">1. “Biocatalysts” specially designed for the decontamination or degradation of CW agents specified in Category Code ML7.b., and resulting from directed laboratory selection or genetic manipulation of biological systems; <li data-bbox="564 1274 1268 1518">2. Biological systems containing the genetic information specific to the production of “biocatalysts” specified in Category Code ML7.i.1., as follows: <ol data-bbox="651 1391 975 1518" style="list-style-type: none"> <li data-bbox="651 1391 975 1424">a. “Expression vectors”; <li data-bbox="651 1442 815 1476">b. Viruses; <li data-bbox="651 1494 916 1527">c. Cultures of cells. <p data-bbox="501 1541 584 1568"><i>Note 1</i></p> <p data-bbox="501 1581 1268 1646"><i>Category Codes ML7.b. and ML7.d. do not apply to the following:</i></p> <ol data-bbox="501 1666 1054 1841" style="list-style-type: none"> <li data-bbox="501 1666 938 1700">a. Cyanogen chloride (506-77-4); <li data-bbox="501 1718 911 1751">b. Hydrocyanic acid (74-90-8); <li data-bbox="501 1769 831 1803">c. Chlorine (7782-50-5); <li data-bbox="501 1821 1054 1854">d. Carbonyl chloride (phosgene) (75-44-5);

Category Code	Item Description
	<p>e. <i>Diphosgene (trichloromethyl-chloroformate) (503-38-8);</i></p> <p>f. <i>Not used;</i></p> <p>g. <i>Xylyl bromide, ortho: (89-92-9), meta: (620-13-3), para: (104-81-4);</i></p> <p>h. <i>Benzyl bromide (100-39-0);</i></p> <p>i. <i>Benzyl iodide (620-05-3);</i></p> <p>j. <i>Bromo acetone (598-31-2);</i></p> <p>k. <i>Cyanogen bromide (506-68-3);</i></p> <p>l. <i>Bromo methylethylketone (816-40-0);</i></p> <p>m. <i>Chloro acetone (78-95-5);</i></p> <p>n. <i>Ethyl iodoacetate (623-48-3);</i></p> <p>o. <i>Iodo acetone (3019-04-3);</i></p> <p>p. <i>Chloropicrin (76-06-2).</i></p>
	<p><u>Note 2</u></p> <p><i>The cultures of cells and biological systems specified in Category Codes ML7.h. and ML7.i.2. are exclusive and these sub-items do not apply to cells or biological systems for civil purposes, such as:</i></p> <p>a. <i>agricultural, pharmaceutical, medical, veterinary, environmental or waste management purposes; <u>or</u></i></p> <p>b. <i>in the food industry.</i></p>
ML8	<p>“Energetic materials” and related substances, as follows:</p> <p><u>N.B. 1</u></p> <p><i>See also Category Code 1C011 in Division 2 of Part 2 of this Schedule.</i></p> <p><u>N.B. 2</u></p> <p><i>For charges and devices, see Category Code ML4 and Category Code 1A008 in Division 2 of Part 2 of this Schedule.</i></p>

<i>Category Code</i>	<i>Item Description</i>
	<p><u>Technical Notes</u></p> <ol style="list-style-type: none"> 1. For the purpose of Category Code ML8, excluding Category Code ML8.c.11. or ML8.c.12., 'mixture' refers to a composition of two or more substances with at least one substance being listed in the sub-items under this Category Code. 2. Any substance listed in the sub-items under Category Code ML8 is treated as coming within the description of that substance even when utilised in an application other than that indicated. (e.g. TAGN is predominantly used as an explosive but can also be used either as a fuel or an oxidiser.) 3. For the purpose of Category Code ML8, particle size is the mean particle diameter on a weight or volume basis. International or equivalent national standards will be used in sampling and determining particle size. <ol style="list-style-type: none"> a. "Explosives" as follows, and 'mixtures' thereof: <ol style="list-style-type: none"> 1. ADNBF (aminodinitrobenzofuroxan or 7-amino-4,6-dinitrobenzofurazane-1-oxide) (97096-78-1); 2. BNCP (cis-bis (5-nitrotetrazolato) tetra amine-cobalt (III) perchlorate) (117412-28-9); 3. CL-14 (diamino dinitrobenzofuroxan or 5,7-diamino-4,6-dinitrobenzofurazane-1-oxide) (117907-74-1); 4. CL-20 (HNIW or Hexanitrohexaazaisowurtzitane) (135285-90-4); chlathrates of CL-20 (see also Category Codes ML8.g.3. and g.4. for its "precursors"); 5. CP (2-(5-cyanotetrazolato) penta amine-cobalt (III) perchlorate) (70247-32-4); 6. DADE (1,1-diamino-2,2-dinitroethylene, FOX7) (145250-81-3); 7. DATB (diaminotrinitrobenzene) (1630-08-6); 8. DDFP (1,4-dinitrodifurazanopiperazine); 9. DDPO (2,6-diamino-3,5-dinitropyrazine-1-oxide, PZO) (194486-77-6);

<i>Category Code</i>	<i>Item Description</i>
	10. DIPAM (3,3'-diamino-2,2',4,4',6,6'-hexanitrobiphenyl or dipicramide) (17215-44-0);
	11. DNGU (DINGU or dinitroglycoluril) (55510-04-8);
	12. Furazans as follows:
	a. DAAOF (DAAF, DAAFox, or diaminoazoxyfuran);
	b. DAAzF (diaminoazofuran) (78644-90-3);
	13. HMX and derivatives (see also Category Code ML8.g.5. for its "precursors"), as follows:
	a. HMX (Cyclotetramethylenetetranitramine, octahydro-1,3,5,7-tetranitro-1,3,5,7-tetrazine, 1,3,5,7-tetranitro-1,3,5,7-tetraza-cyclooctane, octogen or octogene) (2691-41-0);
	b. Difluoroaminated analogs of HMX;
	c. K-55 (2,4,6,8-tetranitro-2,4,6,8-tetraazabicyclo [3,3,0]-octanone-3, tetranitrosemiglycouril or keto-bicyclic HMX) (130256-72-3);
	14. HNAD (hexanitroadamantane) (143850-71-9);
	15. HNS (hexanitrostilbene) (20062-22-0);
	16. Imidazoles as follows:
	a. BNNII (Octahydro-2,5-bis(nitroimino)imidazo [4,5-d]imidazole);
	b. DNI (2,4-dinitroimidazole) (5213-49-0);
	c. FDIA (1-fluoro-2,4-dinitroimidazole);
	d. NTDNIA (N-(2-nitrotriazolo)-2,4-dinitroimidazole);
	e. PTIA (1-picryl-2,4,5-trinitroimidazole);
	17. NTNMH (1-(2-nitrotriazolo)-2-dinitromethylene hydrazine);
	18. NTO (ONTA or 3-nitro-1,2,4-triazol-5-one) (932-64-9);
	19. Polynitrocubanes with more than four nitro groups;

<i>Category Code</i>	<i>Item Description</i>
	<p>20. PYX (2,6-Bis(picrylamino)-3,5-dinitropyridine) (38082-89-2);</p> <p>21. RDX and derivatives, as follows:</p> <ul style="list-style-type: none"> a. RDX (cyclotrimethylenetrinitramine, cyclonite, T4, hexahydro-1,3,5-trinitro-1,3,5-triazine, 1,3,5-trinitro-1,3,5-triazacyclohexane, hexogen or hexogene) (121-82-4); b. Keto-RDX (K-6 or 2,4,6-trinitro-2,4,6-triazacyclohexanone) (115029-35-1); <p>22. TAGN (triaminoguanidinenitrate) (4000-16-2);</p> <p>23. TATB (triaminotrinitrobenzene) (3058-38-6) (see also Category Code ML8.g.7. for its “precursors”);</p> <p>24. TEDDZ (3,3,7,7-tetrabis(difluoroamine) octahydro-1,5-dinitro-1,5-diazocine);</p> <p>25. Tetrazoles as follows:</p> <ul style="list-style-type: none"> a. NTAT (nitrotriazol aminotetrazole); b. NTNT (1-N-(2-nitrotriazolo)-4-nitrotetrazole); <p>26. Tetryl (trinitrophenylmethylnitramine) (479-45-8);</p> <p>27. TNAD (1,4,5,8-tetranitro-1,4,5,8-tetraazadecalin) (135877-16-6) (see also Category Code ML8.g.6. for its “precursors”);</p> <p>28. TNAZ (1,3,3-trinitroazetidine) (97645-24-4) (see also Category Code ML8.g.2. for its “precursors”);</p> <p>29. TNGU (SORGUYL or tetranitroglycoluril) (55510-03-7);</p> <p>30. TNP (1,4,5,8-tetranitro-pyridazino[4,5-d]pyridazine) (229176-04-9);</p> <p>31. Triazines as follows:</p> <ul style="list-style-type: none"> a. DNAM (2-oxy-4,6-dinitroamino-s-triazine) (19899-80-0); b. NNHT (2-nitroimino-5-nitro-hexahydro-1,3,5-triazine) (130400-13-4);

<i>Category Code</i>	<i>Item Description</i>
	<p>32. Triazoles as follows:</p> <ul style="list-style-type: none"> a. 5-azido-2-nitrotriazole; b. ADHTDN (4-amino-3,5-dihydrazino-1,2,4-triazole dinitramide) (1614-08-0); c. ADNT (1-amino-3,5-dinitro-1,2,4-triazole); d. BDNTA ((bis-dinitrotriazole)amine); e. DBT (3,3'-dinitro-5,5-bi-1,2,4-triazole) (30003-46-4); f. DNBT (dinitrobistriazole) (70890-46-9); g. Not used; h. NTDNT (1-N-(2-nitrotriazolo) 3,5-dinitrotriazole); i. PDNT (1-picryl-3,5-dinitrotriazole); j. TACOT (tetranitrobenzotriazolobenzotriazole) (25243-36-1); <p>33. Explosives not listed elsewhere in Category Code ML8.a. and having any of the following characteristics:</p> <ul style="list-style-type: none"> a. Detonation velocity exceeding 8,700 m/s, at maximum density; <u>or</u> b. Detonation pressure exceeding 34 GPa (340 kbar); <p>34. Not used;</p> <p>35. DNAN (2,4-dinitroanisole) (119-27-7);</p> <p>36. TEX (4,10-Dinitro-2,6,8,12-tetraoxa-4,10-diazaisowurtzitane);</p> <p>37. GUDN (Guanylurea dinitramide) FOX-12 (217464-38-5);</p> <p>38. Tetrazines as follows:</p> <ul style="list-style-type: none"> a. BTAT (Bis(2,2,2-trinitroethyl)-3,6-diaminotetrazine);

<i>Category Code</i>	<i>Item Description</i>
	<p data-bbox="638 448 1268 515">b. LAX-112 (3,6-diamino-1,2,4,5-tetrazine-1,4-dioxide);</p> <p data-bbox="558 537 1268 660">39. Energetic ionic materials melting between 343 K (70°C) and 373 K (100°C) and with detonation velocity exceeding 6,800 m/s or detonation pressure exceeding 18 GPa (180 kbar);</p> <p data-bbox="558 683 1268 750">40. BTNEN (Bis(2,2,2-trinitroethyl)-nitramine) (19836-28-3);</p> <p data-bbox="558 772 1268 840">41. FTDO (5,6-(3',4'-furazano)-1,2,3,4-tetrazine-1,3-dioxide);</p> <p data-bbox="558 862 1268 929"><u>Note</u> Category Code ML8.a. includes 'explosive co-crystals'.</p> <p data-bbox="622 952 1268 1153"><u>Technical Note</u> An 'explosive co-crystal' is a solid material consisting of an ordered three dimensional arrangement of two or more explosive molecules, where at least one is specified in Category Code ML8.a.</p> <p data-bbox="494 1176 1268 1818">b. "Propellants" as follows:</p> <ol data-bbox="558 1220 1268 1818" style="list-style-type: none"> <li data-bbox="558 1220 1268 1377">1. Any solid "propellant" with a theoretical specific impulse (under standard conditions) of more than: <ol data-bbox="638 1310 1268 1512" style="list-style-type: none"> <li data-bbox="638 1310 1268 1377">a. 240 seconds for non-metallised, non-halogenised "propellant"; <li data-bbox="638 1388 1268 1456">b. 250 seconds for non-metallised, halogenised "propellant"; <u>or</u> <li data-bbox="638 1467 1268 1512">c. 260 seconds for metallised "propellant"; <li data-bbox="558 1523 1268 1556">2. Not used; <li data-bbox="558 1568 1268 1635">3. "Propellants" having a force constant of more than 1,200 kJ/kg; <li data-bbox="558 1646 1268 1818">4. "Propellants" that can sustain a steady-state linear burning rate of more than 38 mm/s under standard conditions (as measured in the form of an inhibited single strand) of 6.89 MPa (68.9 bar) pressure and 294 K (21°C);

<i>Category Code</i>	<i>Item Description</i>
	<p>5. Elastomer Modified Cast Double Base (EMCDB) “propellants” with extensibility at maximum stress of more than 5% at 233 K (-40°C);</p> <p>6. Any “propellant” containing substances specified in Category Code ML8.a.;</p> <p>7. “Propellants”, not specified elsewhere in any part of this Division, specially designed for military use;</p> <p>c. “Pyrotechnics”, fuels and related substances, as follows, and ‘mixtures’ thereof:</p> <p>1. “Aircraft” fuels specially formulated for military purposes;</p> <p><i>Note</i> <i>“Aircraft” fuels specified in Category Code ML8.c.1. are finished products, not their constituents.</i></p> <p>2. Alane (aluminium hydride) (7784-21-6);</p> <p>3. Boranes, as follows, and their derivatives:</p> <p>a. Carbones;</p> <p>b. Borane homologues, as follows:</p> <p>1. Decaborane (14) (17702-41-9);</p> <p>2. Pentaborane (9) (19624-22-7);</p> <p>3. Pentaborane (11) (18433-84-6);</p> <p>4. Hydrazine and derivatives, as follows (see also Category Codes ML8.d.8. and d.9. for oxidising hydrazine derivatives):</p> <p>a. Hydrazine (302-01-2) in concentrations of 70% or more;</p> <p>b. Monomethyl hydrazine (60-34-4);</p> <p>c. Symmetrical dimethyl hydrazine (540-73-8);</p> <p>d. Unsymmetrical dimethyl hydrazine (57-14-7);</p> <p><i>Note</i> <i>Category Code ML8.c.4.a. does not apply to hydrazine ‘mixtures’ specially formulated for corrosion control.</i></p>

<i>Category Code</i>	<i>Item Description</i>
	<p>5. Metal fuels, fuel ‘mixtures’ or “pyrotechnic” ‘mixtures’, in particle form whether spherical, atomised, spheroidal, flaked or ground, manufactured from material consisting of 99% or more of any of the following:</p> <ol style="list-style-type: none"> a. Metals as follows and ‘mixtures’ thereof: <ol style="list-style-type: none"> 1. Beryllium (7440-41-7) in particle sizes of less than 60 µm; 2. Iron powder (7439-89-6) with particle size of 3 µm or less produced by reduction of iron oxide with hydrogen; b. ‘Mixtures’ containing any of the following: <ol style="list-style-type: none"> 1. Zirconium (7440-67-7), magnesium (7439-95-4) or alloys of these in particle sizes of less than 60 µm; <u>or</u> 2. Boron (7440-42-8) or boron carbide (12069-32-8) fuels of 85% purity or higher and particle sizes of less than 60 µm; <p><u>Note 1</u> <i>Category Code ML8.c.5. applies to “explosives” and fuels, whether or not the metals or alloys are encapsulated in aluminium, magnesium, zirconium, or beryllium.</i></p> <p><u>Note 2</u> <i>Category Code ML8.c.5.b. only applies to metal fuels in particle form when they are mixed with other substances to form a ‘mixture’ formulated for military purposes such as liquid “propellant” slurries, solid “propellants”, or “pyrotechnic” ‘mixtures’.</i></p> <p><u>Note 3</u> <i>Category Code ML8.c.5.b.2. does not apply to boron and boron carbide enriched with boron-10 (20% or more of total boron-10 content).</i></p>

<i>Category Code</i>	<i>Item Description</i>
	<p>6. Military materials, containing thickeners for hydrocarbon fuels, specially formulated for use in flame throwers or incendiary munitions, such as metal stearates (e.g. octal (637-12-7)) or palmitates;</p> <p>7. Perchlorates, chlorates and chromates, composited with powdered metal or other high energy fuel components;</p> <p>8. Spherical or spheroidal aluminium powder (7429-90-5) with a particle size of 60 µm or less and manufactured from material with an aluminium content of 99% or more;</p> <p>9. Titanium subhydride (TiH_n) of stoichiometry equivalent to n = 0.65-1.68;</p> <p>10. Liquid high energy density fuels not specified in Category Code ML8.c.1., as follows:</p> <ul style="list-style-type: none"> a. Mixed fuels, that incorporate both solid and liquid fuels (e.g. boron slurry), having a mass-based energy density of 40 MJ/kg or greater; b. Other high energy density fuels and fuel additives (e.g. cubane, ionic solutions, JP-7, JP-10), having a volume-based energy density of 37.5 GJ per cubic metre or greater, measured at 293 K (20°C) and one atmosphere (101.325 kPa) pressure; <p><i>Note</i> <i>Category Code ML8.c.10.b. does not apply to JP-4, JP-8, fossil refined fuels or biofuels, or fuels for engines certified for used in civil aviation.</i></p> <p>11. “Pyrotechnic” and pyrophoric materials, as follows:</p> <ul style="list-style-type: none"> a. “Pyrotechnic” and pyrophoric materials specifically formulated to enhance or control the production of radiated energy in any part of the IR spectrum;

<i>Category Code</i>	<i>Item Description</i>
	<p>b. Mixtures of magnesium, polytetrafluoroethylene (PTFE) and a vinylidene difluoride-hexafluoropropylene copolymer (e.g. MTV);</p> <p>12. Fuel mixtures, “pyrotechnic” mixtures or “energetic materials”, not specified elsewhere in Category Code ML8, having all of the following characteristics:</p> <p>a. Containing greater than 0.5% of particles of any of the following:</p> <ol style="list-style-type: none"> 1. Aluminium; 2. Beryllium; 3. Boron; 4. Zirconium; 5. Magnesium; <u>or</u> 6. Titanium; <p>b. Particles specified in Category Code ML8.c.12.a. with a size less than 200 nm in any direction; <u>and</u></p> <p>c. Particles specified in Category Code ML8.c.12.a. with a metal content of 60% or greater;</p> <p>d. Oxidisers as follows, and ‘mixtures’ thereof:</p> <ol style="list-style-type: none"> 1. ADN (ammonium dinitramide or SR 12) (140456-78-6); 2. AP (ammonium perchlorate) (7790-98-9); 3. Compounds composed of fluorine and any of the following: <ol style="list-style-type: none"> a. Other halogens; b. Oxygen; <u>or</u> c. Nitrogen; <p><i>Note 1</i> Category Code ML8.d.3. does not apply to chlorine trifluoride (7790-91-2).</p>

<i>Category Code</i>	<i>Item Description</i>
	<p data-bbox="630 454 710 488"><u>Note 2</u></p> <p data-bbox="630 495 1264 562"><i>Category Code ML8.d.3. does not apply to nitrogen trifluoride (7783-54-2) in its gaseous state.</i></p> <ol data-bbox="566 577 1264 974" style="list-style-type: none"> 4. DNAD (1,3-dinitro-1,3-diazetidine) (78246-06-7); 5. HAN (hydroxylammonium nitrate) (13465-08-2); 6. HAP (hydroxylammonium perchlorate) (15588-62-2); 7. HNF (hydrazinium nitroformate) (20773-28-8); 8. Hydrazine nitrate (37836-27-4); 9. Hydrazine perchlorate (27978-54-7); 10. Liquid oxidisers comprised of or containing inhibited red fuming nitric acid (IRFNA) (8007-58-7); <p data-bbox="630 992 689 1025"><u>Note</u></p> <p data-bbox="630 1032 1264 1099"><i>Category Code ML8.d.10. does not apply to non-inhibited fuming nitric acid.</i></p> <p data-bbox="502 1120 1257 1153">e. Binders, plasticisers, monomers and polymers, as follows:</p> <ol data-bbox="566 1169 1264 1832" style="list-style-type: none"> 1. AMMO (azidomethylmethyloxetane and its polymers) (90683-29-7) (see also Category Code ML8.g.1. for its “precursors”); 2. BAMO (3,3-bis(azidomethyl)oxetane and its polymers) (17607-20-4) (see also Category Code ML8.g.1. for its “precursors”); 3. BDNPA (bis (2,2-dinitropropyl)acetal) (5108-69-0); 4. BDNPF (bis (2,2-dinitropropyl)formal) (5917-61-3); 5. BTTN (butanetrioltrinitrate) (6659-60-5) (see also Category Code ML8.g.8. for its “precursors”); 6. Energetic monomers, plasticisers or polymers, specially formulated for military use and containing any of the following: <ol data-bbox="651 1702 896 1832" style="list-style-type: none"> a. Nitro groups; b. Azido groups; c. Nitrate groups;

<i>Category Code</i>	<i>Item Description</i>
	<ul style="list-style-type: none"> d. Nitraza groups; <u>or</u> e. Difluoroamino groups;
	7. FAMA0 (3-difluoroaminomethyl-3-azidomethyl oxetane) and its polymers;
	8. FEFO (bis-(2-fluoro-2,2-dinitroethyl) formal) (17003-79-1);
	9. FPF-1 (poly-2,2,3,3,4,4-hexafluoropentane-1,5-diol formal) (376-90-9);
	10. FPF-3 (poly-2,4,4,5,5,6,6-heptafluoro-2-trifluoromethyl-3-oxaheptane-1,7-diol formal);
	11. GAP (glycidylazide polymer) (143178-24-9) and its derivatives;
	12. HTPB (hydroxyl terminated polybutadiene) with a hydroxyl functionality equal to or greater than 2.2 and less or equal to 2.4, a hydroxyl value of less than 0.77 meq/g, and a viscosity at 30°C of less than 47 poise (69102-90-5);
	13. Alcohol functionalised poly(epichlorohydrin) with a molecular weight of less than 10,000, as follows: <ul style="list-style-type: none"> a. Poly(epichlorohydrindiol); b. Poly(epichlorohydrintriol);
	14. NENAs (nitrateethylnitramine compounds) (17096-47-8, 85068-73-1, 82486-83-7, 82486-82-6 and 85954-06-9);
	15. PGN (poly-GLYN, polyglycidylnitrate or poly(nitratomethyl oxirane)) (27814-48-8);
	16. Poly-NIMMO (poly nitratomethylmethyloxetane), poly-NMMO or (poly(3-Nitratomethyl-3-methyloxetane)) (84051-81-0);
	17. Polynitroorthocarbonates;
	18. TVOPA (1,2,3-tris[1,2-bis(difluoroamino)ethoxy] propane or tris vinoxy propane adduct) (53159-39-0);
	19. 4,5 diazidomethyl-2-methyl-1,2,3-triazole (iso-DAMTR);

<i>Category Code</i>	<i>Item Description</i>
	<p>20. PNO (Poly(3-nitrato oxetane));</p> <p>f. “Additives” as follows:</p> <ol style="list-style-type: none"> 1. Basic copper salicylate (62320-94-9); 2. BHEGA (bis-(2-hydroxyethyl) glycolamide) (17409-41-5); 3. BNO (butadienenitrileoxide); 4. Ferrocene derivatives, as follows: <ol style="list-style-type: none"> a. Butacene (125856-62-4); b. Catocene (2,2-bis-ethylferrocenyl propane) (37206-42-1); c. Ferrocene carboxylic acids and ferrocene carboxylic acid esters; d. n-butyl-ferrocene (31904-29-7); e. Other adducted polymer ferrocene derivatives not specified elsewhere in Category Code ML8.f.4.; f. Ethyl ferrocene (1273-89-8); g. Propyl ferrocene; h. Pentyl ferrocene (1274-00-6); i. Dicyclopentyl ferrocene; j. Dicyclohexyl ferrocene; k. Diethyl ferrocene (1273-97-8); l. Dipropyl ferrocene; m. Dibutyl ferrocene (1274-08-4); n. Dihexyl ferrocene (93894-59-8); o. Acetyl ferrocene (1271-55-2)/1,1'-diacetyl ferrocene (1273-94-5); 5. Lead beta-resorcyate (20936-32-7); 6. Lead citrate (14450-60-3); 7. Lead-copper chelates of beta-resorcyate or salicylates (68411-07-4);

<i>Category Code</i>	<i>Item Description</i>
	<ol style="list-style-type: none"> 8. Lead maleate (19136-34-6); 9. Lead salicylate (15748-73-9); 10. Lead stannate (12036-31-6); 11. MAPO (tris-1-(2-methyl)aziridiny phosphine oxide) (57-39-6); BOBBA 8 (bis(2-methyl aziridiny) 2-(2-hydroxypropanoxy) propylamino phosphine oxide); and other MAPO derivatives; 12. Methyl BAPO (bis(2-methyl aziridiny) methylamino phosphine oxide) (85068-72-0); 13. N-methyl-p-nitroaniline (100-15-2); 14. 3-Nitrazo-1,5-pentane diisocyanate (7406-61-9); 15. Organo-metallic coupling agents as follows: <ol style="list-style-type: none"> a. Neopentyl[diallyl]oxy, tri[diethyl]phosphato-titanate (103850-22-2); also known as titanium IV, 2,2[bis 2-propenolato-methyl, butanolato, tris (diethyl) phosphato] (110438-25-0); or LICA 12 (103850-22-2); b. Titanium IV, [(2-propenolato-1) methyl, n-propanolatomethyl] butanolato-1, tris[diethyl] pyrophosphate or KR3538; c. Titanium IV, [(2-propenolato-1)methyl, n-propanolatomethyl] butanolato-1, tris(diethyl)phosphate; 16. Polycyanodifluoroaminoethyleneoxide; 17. Bonding agents as follows: <ol style="list-style-type: none"> a. 1,1R,1S-trimesoyl-tris(2-ethylaziridine) (HX-868, BITA) (7722-73-8); b. Polyfunctional aziridine amides with isophthalic, trimesic, isocyanuric or trimethyladipic backbone also having a 2-methyl or 2-ethyl aziridine group;

<i>Category Code</i>	<i>Item Description</i>
	<p style="text-align: center;"><u>Note</u></p> <p style="text-align: center;"><i>Category Code ML8.f.17.b. includes:</i></p> <p style="margin-left: 40px;">a. <i>1,1 H-Isophthaloyl-bis(2-methylaziridine) (HX-752) (7652-64-4);</i></p> <p style="margin-left: 40px;">b. <i>2,4,6-tris(2-ethyl-1-aziridinyl)-1,3,5-triazine (HX-874) (18924-91-9);</i></p> <p style="margin-left: 40px;">c. <i>1,1'-trimethyladipoyl-bis(2-ethylaziridine) (HX-877) (71463-62-2).</i></p> <p>18. Propyleneimine (2-methylaziridine) (75-55-8);</p> <p>19. Superfine iron oxide (Fe₂O₃) (1317-60-8) with a specific surface area more than 250 m²/g and an average particle size of 3 nm or less;</p> <p>20. TEPAN (tetraethylenepentaamineacrylonitrile) (68412-45-3); cyanoethylated polyamines and their salts;</p> <p>21. TEPANOL (tetraethylenepentaamineacrylonitrileglycidol) (68412-46-4); cyanoethylated polyamines adducted with glycidol and their salts;</p> <p>22. TPB (triphenyl bismuth) (603-33-8);</p> <p>23. TEPB (Tris (ethoxyphenyl) bismuth) (90591-48-3);</p> <p>g. "Precursors" as follows:</p> <p><u>N.B.</u></p> <p><i>The references in Category Code ML8.g. are specified "energetic materials" manufactured from these substances.</i></p> <p>1. BCMO (3,3-bis(chloromethyl)oxetane) (78-71-7) (see also Category Codes ML8.e.1. and e.2.);</p> <p>2. Dinitroazetidine-t-butyl salt (125735-38-8) (see also Category Code ML8.a.28.);</p> <p>3. Hexaazaisowurtzitane derivatives including HBIW (hexabenzylhexaazaisowurtzitane) (124782-15-6) (see also Category Code ML8.a.4.) and TAIW (tetraacetyldibenzylhexaazaisowurtzitane) (182763-60-6) (see also Category Code ML8.a.4.);</p>

<i>Category Code</i>	<i>Item Description</i>
	<ol style="list-style-type: none"> 4. Not used; 5. TAT (1,3,5,7 tetraacetyl-1,3,5,7,-tetraaza cyclo-octane) (41378-98-7) (see also Category Code ML8.a.13.); 6. 1,4,5,8-tetraazadecalin (5409-42-7) (see also Category Code ML8.a.27.); 7. 1,3,5-trichlorobenzene (108-70-3) (see also Category Code ML8.a.23.); 8. 1,2,4-trihydroxybutane (1,2,4-butanetriol) (3068-00-6) (see also Category Code ML8.e.5.); 9. DADN (1,5-diacetyl-3,7-dinitro-1, 3, 5, 7-tetraaza-cyclooctane) (see also Category Code ML8.a.13.); <p>h. 'Reactive material' powders and shapes, as follows:</p> <ol style="list-style-type: none"> 1. Powders of any of the following materials, with a particle size less than 250 µm in any direction and not specified elsewhere in Category Code ML8: <ol style="list-style-type: none"> a. Aluminium; b. Niobium; c. Boron; d. Zirconium; e. Magnesium; f. Titanium; g. Tantalum; h. Tungsten; i. Molybdenum; <u>or</u> j. Hafnium; 2. Shapes, not specified in Category Code ML3, ML4, ML12 or ML16, fabricated from powders specified in Category Code ML8.h.1.

Category Code	Item Description
	<p data-bbox="566 454 758 488"><u>Technical Notes</u></p> <ol data-bbox="566 504 1268 772" style="list-style-type: none"> <li data-bbox="566 504 1268 600">1. 'Reactive materials' are designed to produce an exothermic reaction only at high shear rates, and are designed for use as liners or casings in warheads. <li data-bbox="566 616 1268 689">2. 'Reactive material' powders are produced by, for example, a high energy ball milling process. <li data-bbox="566 705 1268 772">3. 'Reactive material' shapes are produced by, for example, selective laser sintering. <p data-bbox="502 788 587 822"><u>Note 1</u></p> <p data-bbox="502 837 1268 969">Category Code ML8 does not apply to the following substances unless they are compounded or mixed with the "energetic material" specified in Category Code ML8.a. or powdered metals specified in Category Code ML8.c.:</p> <ol data-bbox="502 985 1268 1863" style="list-style-type: none"> <li data-bbox="502 985 933 1019">a. Ammonium picrate (131-74-8); <li data-bbox="502 1034 742 1068">b. Black powder; <li data-bbox="502 1084 1005 1117">c. Hexanitrodiphenylamine (131-73-7); <li data-bbox="502 1133 917 1167">d. Difluoroamine (10405-27-3); <li data-bbox="502 1182 861 1216">e. Nitrostarch (9056-38-6); <li data-bbox="502 1232 933 1265">f. Potassium nitrate (7757-79-1); <li data-bbox="502 1281 845 1314">g. Tetranitronaphthalene; <li data-bbox="502 1330 742 1364">h. Trinitroanisol; <li data-bbox="502 1379 813 1413">i. Trinitronaphthalene; <li data-bbox="502 1429 742 1462">j. Trinitroxylene; <li data-bbox="502 1478 1220 1512">k. N-pyrrolidinone; 1-methyl-2-pyrrolidinone (872-50-4); <li data-bbox="502 1527 893 1561">l. Dioctylmaleate (142-16-5); <li data-bbox="502 1576 933 1610">m. Ethylhexylacrylate (103-11-7); <li data-bbox="502 1626 1268 1731">n. Triethylaluminium (TEA) (97-93-8), trimethylaluminium (TMA) (75-24-1), and other pyrophoric metal alkyls and aryls of lithium, sodium, magnesium, zinc or boron; <li data-bbox="502 1747 885 1780">o. Nitrocellulose (9004-70-0); <li data-bbox="502 1796 1268 1863">p. Nitroglycerin (or glyceroltrinitrate, trinitroglycerine) (NG) (55-63-0);

<i>Category Code</i>	<i>Item Description</i>
	<p>q. 2,4,6-trinitrotoluene (TNT) (118-96-7);</p> <p>r. Ethylenediaminedinitrate (EDDN) (20829-66-7);</p> <p>s. Pentaerythritoltetranitrate (PETN) (78-11-5);</p> <p>t. Lead azide (13424-46-9), normal lead styphnate (15245-44-0) and basic lead styphnate (12403-82-6), and primary explosives or priming compositions containing azides or azide complexes;</p> <p>u. Triethyleneglycoldinitrate (TEGDN) (111-22-8);</p> <p>v. 2,4,6-trinitroresorcinol (styphnic acid) (82-71-3);</p> <p>w. Diethyldiphenylurea (85-98-3); dimethyldiphenylurea (611-92-7); methylethyldiphenylurea; [Centralites];</p> <p>x. N,N-diphenylurea (unsymmetrical diphenylurea) (603-54-3);</p> <p>y. Methyl-N,N-diphenylurea (methyl unsymmetrical diphenylurea) (13114-72-2);</p> <p>z. Ethyl-N,N-diphenylurea (ethyl unsymmetrical diphenylurea) (64544-71-4);</p> <p>aa. 2-Nitrodiphenylamine (2-NDPA) (119-75-5);</p> <p>bb. 4-Nitrodiphenylamine (4-NDPA) (836-30-6);</p> <p>cc. 2,2-dinitropropanol (918-52-5);</p> <p>dd. Nitroguanidine (556-88-7) (see Category Code 1C011.d. in Division 2 of Part 2 of this Schedule).</p> <p><u>Note 2</u></p> <p>Category Code ML8 does not apply to ammonium perchlorate (Category Code ML8.d.2.), NTO (Category Code ML8.a.18.) or catocene (Category Code ML8.f.4.b.), and meeting all of the following:</p> <p>a. Specially shaped and formulated for civil-use gas generation devices;</p> <p>b. Compounded or mixed, with non-active thermoset binders or plasticisers, and having a mass of less than 250 g;</p> <p>c. Having a maximum of 80% ammonium perchlorate (Category Code ML8.d.2.) in mass of active material;</p>

<i>Category Code</i>	<i>Item Description</i>
ML9	<p>d. <i>Having less than or equal to 4 g of NTO (Category Code ML8.a.18.); <u>and</u></i></p> <p>e. <i>Having less than or equal to 1 g of catocene (Category Code ML8.f.4.b.).</i></p> <p>Vessels of war (surface or underwater), special naval equipment, accessories, components and other surface vessels, as follows:</p> <p><u>N.B.</u> <i>For guidance and navigation equipment, see Category Code ML11.</i></p> <p>a. Vessels and components, as follows:</p> <ol style="list-style-type: none"> 1. Vessels (surface or underwater) specially designed or modified for military use, regardless of current state of repair or operating condition, and whether or not they contain weapon delivery systems or armour, and hulls or parts of hulls for such vessels, and components therefor specially designed for military use; 2. Surface vessels, other than those specified in Category Code ML9.a.1., having any of the following, fixed or integrated into the vessel: <ol style="list-style-type: none"> a. Automatic weapons specified in Category Code ML1, or weapons specified in Category Code ML2, ML4, ML12 or ML19, or 'mountings' or hard points for weapons having a calibre of 12.7 mm or greater; <p><u>Technical Note</u> <i>'Mountings' refers to weapon mounts or structural strengthening for the purpose of installing weapons.</i></p> b. Fire control systems specified in Category Code ML5; c. Having all of the following: <ol style="list-style-type: none"> 1. 'Chemical, Biological, Radiological and Nuclear (CBRN) protection'; <u>and</u>

<i>Category Code</i>	<i>Item Description</i>
	<p data-bbox="715 454 1268 521">2. 'Pre-wet or wash down system' designed for decontamination purposes; <u>or</u></p> <p data-bbox="778 539 975 568"><i>Technical Notes</i></p> <p data-bbox="778 580 1268 846">1. 'CBRN protection' is a self-contained interior space containing features such as over-pressurisation, isolation of ventilation systems, limited ventilation openings with CBRN filters and limited personnel access points incorporating air-locks.</p> <p data-bbox="778 864 1268 1025">2. 'Pre-wet or wash down system' is a seawater spray system capable of simultaneously wetting the exterior superstructure and decks of a vessel.</p> <p data-bbox="651 1048 1268 1149">d. Active weapon countermeasure systems specified in Category Code ML4.b., ML5.c. or ML11.a. and having any of the following:</p> <p data-bbox="715 1167 1018 1196">1. 'CBRN protection';</p> <p data-bbox="715 1214 1268 1314">2. Hull and superstructure, specially designed to reduce the radar cross section;</p> <p data-bbox="715 1332 1268 1500">3. Thermal signature reduction devices, (e.g. an exhaust gas cooling system), excluding those specially designed to increase overall power plant efficiency or to reduce the environmental impact; <u>or</u></p> <p data-bbox="715 1518 1268 1619">4. A degaussing system designed to reduce the magnetic signature of the whole vessel;</p>

<i>Category Code</i>	<i>Item Description</i>
	<p data-bbox="778 454 962 488"><u>Technical Note</u></p> <p data-bbox="778 495 1262 725"><i>'CBRN protection' is a self-contained interior space containing features such as over-pressurisation, isolation of ventilation systems, limited ventilation openings with CBRN filters and limited personnel access points incorporating air-locks.</i></p> <p data-bbox="501 745 1262 846">b. Engines and propulsion systems, as follows, specially designed for military use, and components therefor specially designed for military use:</p> <ol data-bbox="568 864 1262 1675" style="list-style-type: none"> <li data-bbox="568 864 1262 931">1. Diesel engines specially designed for submarines and having all of the following characteristics: <ol data-bbox="651 949 1262 1061" style="list-style-type: none"> <li data-bbox="651 949 1262 1016">a. Power output of 1.12 MW (1,500 hp) or more; <u>and</u> <li data-bbox="651 1034 1262 1061">b. Rotary speed of 700 rpm or more; <li data-bbox="568 1079 1262 1146">2. Electric motors specially designed for submarines and having all of the following characteristics: <ol data-bbox="651 1164 1262 1379" style="list-style-type: none"> <li data-bbox="651 1164 1262 1232">a. Power output of more than 0.75 MW (1,000 hp); <li data-bbox="651 1249 1262 1276">b. Quick reversing; <li data-bbox="651 1294 1262 1321">c. Liquid cooled; <u>and</u> <li data-bbox="651 1348 1262 1375">d. Totally enclosed; <li data-bbox="568 1397 1262 1464">3. Non-magnetic diesel engines having all of the following characteristics: <ol data-bbox="651 1482 1262 1594" style="list-style-type: none"> <li data-bbox="651 1482 1262 1509">a. Power output of 37.3 kW (50 hp) or more; <u>and</u> <li data-bbox="651 1527 1262 1594">b. Non-magnetic content in excess of 75% of total mass; <li data-bbox="568 1612 1262 1675">4. 'Air Independent Propulsion' (AIP) systems specially designed for submarines;

<i>Category Code</i>	<i>Item Description</i>
	<p data-bbox="630 448 813 481"><u>Technical Note</u></p> <p data-bbox="630 492 1260 694"><i>'Air Independent Propulsion' (AIP) allows a submerged submarine to operate its propulsion system, without access to atmospheric oxygen, for a longer time than the batteries would have otherwise allowed. For the purpose of Category Code ML9.b.4., AIP does not include nuclear power.</i></p> <p data-bbox="502 705 1260 806">c. Underwater detection devices, specially designed for military use, controls therefor and components therefor specially designed for military use;</p> <p data-bbox="502 817 1260 896">d. Anti-submarine nets and anti-torpedo nets, specially designed for military use;</p> <p data-bbox="502 907 686 940">e. Not used;</p> <p data-bbox="502 952 1260 1097">f. Hull penetrators and connectors, specially designed for military use, that enable interaction with equipment external to a vessel, and components therefor specially designed for military use;</p> <p data-bbox="566 1108 630 1142"><u>Note</u></p> <p data-bbox="566 1153 1260 1489"><i>Category Code ML9.f. includes connectors for vessels which are of the single-conductor, multi-conductor, coaxial or waveguide type, and hull penetrators for vessels, both of which are capable of remaining impervious to leakage from without and of retaining required characteristics at marine depths exceeding 100 m; and fibre-optic connectors and optical hull penetrators, specially designed for "laser" beam transmission, regardless of depth. Category Code ML9.f. does not apply to ordinary propulsive shaft and hydrodynamic control-rod hull penetrators.</i></p> <p data-bbox="502 1500 1260 1601">g. Silent bearings having any of the following, components therefor and equipment containing those bearings, specially designed for military use:</p> <ol data-bbox="566 1612 1005 1758" style="list-style-type: none"> 1. Gas or magnetic suspension; 2. Active signature controls; <u>or</u> 3. Vibration suppression controls.

<i>Category Code</i>	<i>Item Description</i>
ML10	<p data-bbox="502 454 1260 584">“Aircraft”, “lighter-than-air vehicles”, “unmanned aerial vehicles” (“UAVs”), aero-engines and “aircraft” equipment, related equipment and components, as follows, specially designed or modified for military use:</p> <p data-bbox="502 607 558 633"><u><i>N.B.</i></u></p> <p data-bbox="502 647 1260 707"><i>For guidance and navigation equipment, see Category Code ML11.</i></p> <ol data-bbox="502 730 1260 1659" style="list-style-type: none"> <li data-bbox="502 730 1260 790">a. Manned “aircraft” and “lighter-than-air vehicles”, and specially designed components therefor; <li data-bbox="502 813 683 840">b. Not used; <li data-bbox="502 862 1260 1211">c. Unmanned “aircraft” and “lighter-than-air vehicles”, and related equipment, as follows, and specially designed components therefor: <ol style="list-style-type: none"> <li data-bbox="566 981 1260 1077">1. “UAVs”, Remotely Piloted Air Vehicles (RPVs), autonomous programmable vehicles and unmanned “lighter-than-air vehicles”; <li data-bbox="566 1099 1260 1160">2. Launchers, recovery equipment and ground support equipment; <li data-bbox="566 1182 1169 1209">3. Equipment designed for command or control; <li data-bbox="502 1234 1260 1294">d. Propulsion aero-engines and specially designed components therefor; <li data-bbox="502 1317 1260 1541">e. Airborne refuelling equipment specially designed or modified for any of the following, and specially designed components therefor: <ol style="list-style-type: none"> <li data-bbox="566 1429 1230 1456">1. “Aircraft” specified in Category Code ML10.a.; <u>or</u> <li data-bbox="566 1478 1260 1538">2. Unmanned “aircraft” specified in Category Code ML10.c.; <li data-bbox="502 1563 1260 1659">f. ‘Ground equipment’ specially designed for “aircraft” specified in Category Code ML10.a. or aero-engines specified in Category Code ML10.d.; <p data-bbox="566 1682 750 1709"><u><i>Technical Note</i></u></p> <p data-bbox="566 1722 1260 1818"><i>‘Ground equipment’ includes pressure refuelling equipment and equipment designed to facilitate operations in confined areas.</i></p>

<i>Category Code</i>	<i>Item Description</i>
	<p data-bbox="501 456 1268 584">g. Aircrew life support equipment, aircrew safety equipment and other devices for emergency escape, not specified in Category Code ML10.a., designed for “aircraft” specified in Category Code ML10.a.;</p> <p data-bbox="564 607 624 633"><i>Note</i></p> <p data-bbox="564 647 1268 745"><i>Category Code ML10.g. does not include aircrew helmets that do not incorporate, or have mountings or fittings for, equipment specified in any part of this Division.</i></p> <p data-bbox="564 768 624 795"><i>N.B.</i></p> <p data-bbox="564 808 1107 835"><i>For helmets, see also Category Code ML13.c.</i></p> <p data-bbox="501 857 1268 920">h. Parachutes, paragliders and related equipment, as follows, and specially designed components therefor:</p> <ol data-bbox="564 943 1268 1171" style="list-style-type: none"> <li data-bbox="564 943 1268 1005">1. Parachutes not specified elsewhere in any part of this Division; <li data-bbox="564 1028 772 1055">2. Paragliders; <li data-bbox="564 1077 1268 1171">3. Equipment specially designed for high altitude parachutists (e.g. suits, special helmets, breathing systems, navigation equipment); <p data-bbox="501 1193 1268 1256">i. Controlled opening equipment or automatic piloting systems, designed for parachuted loads.</p> <p data-bbox="501 1279 580 1305"><i>Note 1</i></p> <p data-bbox="501 1319 1268 1447"><i>Category Code ML10.a. does not apply to “aircraft” and “lighter-than-air vehicles” or variants of those “aircraft”, specially designed for military use and which are all of the following:</i></p> <ol data-bbox="501 1469 1268 1695" style="list-style-type: none"> <li data-bbox="501 1469 863 1496">a. <i>Not a combat “aircraft”;</i> <li data-bbox="501 1518 1268 1617">b. <i>Not configured for military use and not fitted with equipment or attachments specially designed or modified for military use; <u>and</u></i> <li data-bbox="501 1639 1268 1695">c. <i>Certified for civil use by civil aviation authorities of one or more “participating states”.</i>

<i>Category Code</i>	<i>Item Description</i>
	<p><u>Note 2</u> <i>Category Code ML10.d. does not apply to:</i></p> <p>a. <i>Aero-engines designed or modified for military use which have been certified by civil aviation authorities of one or more “participating states” for use in “civil aircraft”, or specially designed components therefor;</i></p> <p>b. <i>Reciprocating engines or specially designed components therefor, except those specially designed for “UAVs”.</i></p> <p><u>Note 3</u> <i>For the purposes of Category Codes ML10.a. and ML10.d., specially designed components and related equipment for non-military “aircraft” or aero-engines modified for military use applies only to those military components and to military related equipment required for the modification to military use.</i></p> <p><u>Note 4</u> <i>For the purpose of Category Code ML10.a., military use includes: combat, military reconnaissance, assault, military training, logistics support, and transporting and airdropping troops or military equipment.</i></p> <p><u>Note 5</u> <i>Category Code ML10.a. does not apply to “aircraft” that meet all of the following:</i></p> <p>a. <i>Were first manufactured before 1946;</i></p> <p>b. <i>Do not incorporate items specified in any part of this Division, unless the items are required to meet safety or airworthiness standards of civil aviation authorities of one or more “participating states”; <u>and</u></i></p> <p>c. <i>Do not incorporate weapons specified in any part of this Division, unless inoperable and incapable of being returned to operation.</i></p>

<i>Category Code</i>	<i>Item Description</i>
ML11	<p>Electronic equipment, “spacecraft” and components, not specified elsewhere in any part of this Division, as follows:</p> <p>a. Electronic equipment specially designed for military use and specially designed components therefor;</p> <p><i>Note</i> <i>Category Code ML11.a. includes:</i></p> <p>a. <i>Electronic countermeasure and electronic counter-countermeasure equipment (i.e. equipment designed to introduce extraneous or erroneous signals into radar or radio communication receivers or otherwise hinder the reception, operation or effectiveness of adversary electronic receivers including their countermeasure equipment), including jamming and counter-jamming equipment;</i></p> <p>b. <i>Frequency agile tubes;</i></p> <p>c. <i>Electronic systems or equipment, designed either for surveillance and monitoring of the electromagnetic spectrum for military intelligence or security purposes or for counteracting such surveillance and monitoring;</i></p> <p>d. <i>Underwater countermeasures, including acoustic and magnetic jamming and decoy, equipment designed to introduce extraneous or erroneous signals into sonar receivers;</i></p> <p>e. <i>Data processing security equipment, data security equipment and transmission and signalling line security equipment, using cipharing processes;</i></p> <p>f. <i>Identification, authentication and keyloader equipment and key management, manufacturing and distribution equipment;</i></p> <p>g. <i>Guidance and navigation equipment;</i></p> <p>h. <i>Digital troposcatter-radio communications transmission equipment;</i></p> <p>i. <i>Digital demodulators specially designed for signals intelligence;</i></p> <p>j. <i>“Automated Command and Control Systems”.</i></p>

<i>Category Code</i>	<i>Item Description</i>
ML12	<p><u><i>N.B.</i></u> <i>For “software” associated with military “Software” Defined Radio (SDR), see Category Code ML21.</i></p> <p>b. Global Navigation Satellite Systems (GNSS) jamming equipment and specially designed components therefor;</p> <p>c. “Spacecraft” specially designed or modified for military use, and “spacecraft” components specially designed for military use.</p> <p>High velocity kinetic energy weapon systems and related equipment, as follows, and specially designed components therefor:</p> <p>a. Kinetic energy weapon systems specially designed for destruction or effecting mission-abort of a target;</p> <p>b. Specially designed test and evaluation facilities and test models, including diagnostic instrumentation and targets, for dynamic testing of kinetic energy projectiles and systems.</p> <p><u><i>N.B.</i></u> <i>For weapon systems using sub-calibre ammunition or employing solely chemical propulsion, and ammunition therefor, see Category Codes ML1 to ML4.</i></p> <p><u><i>Note 1</i></u> <i>Category Code ML12 includes the following when specially designed for kinetic energy weapon systems:</i></p> <p>a. <i>Launch propulsion systems capable of accelerating masses larger than 0.1 g to velocities in excess of 1.6 km/s, in single or rapid fire modes;</i></p> <p>b. <i>Prime power generation, electric armour, energy storage (e.g. high energy storage capacitors), thermal management, conditioning, switching or fuel-handling equipment; and electrical interfaces between power supply, gun and other turret electric drive functions;</i></p> <p><u><i>N.B.</i></u> <i>See also Category Code 3A001.e.2. in Division 2 of Part 2 of this Schedule for high energy storage capacitors.</i></p>

<i>Category Code</i>	<i>Item Description</i>
	<p>c. <i>Target acquisition, tracking, fire control or damage assessment systems;</i></p> <p>d. <i>Homing seeker, guidance or divert propulsion (lateral acceleration) systems for projectiles.</i></p> <p><u>Note 2</u> <i>Category Code ML12 applies to weapon systems using any of the following methods of propulsion:</i></p> <p>a. <i>Electromagnetic;</i></p> <p>b. <i>Electrothermal;</i></p> <p>c. <i>Plasma;</i></p> <p>d. <i>Light gas; or</i></p> <p>e. <i>Chemical (when used in combination with any of the above).</i></p>
ML13	<p>Armoured or protective equipment, constructions and components, as follows:</p> <p>a. Metallic or non-metallic armoured plate, having any of the following characteristics:</p> <ol style="list-style-type: none"> 1. <i>Manufactured to comply with a military standard or specification; or</i> 2. <i>Suitable for military use;</i> <p><u>N.B.</u> <i>For body armour plate, see Category Code ML13.d.2.</i></p> <p>b. <i>Constructions of metallic or non-metallic materials, or combinations thereof, specially designed to provide ballistic protection for military systems, and specially designed components therefor;</i></p> <p>c. <i>Helmets manufactured according to military standards or specifications, or comparable national standards, and specially designed helmet shells, liners, or comfort pads, therefor;</i></p>

<i>Category Code</i>	<i>Item Description</i>
	<p><u><i>N.B.</i></u> <i>For other military helmet components or accessories, see the relevant Category Code in this Division.</i></p> <p>d. Body armour or protective garments, and components therefor, as follows:</p> <p>1. Soft body armour or protective garments, manufactured to military standards or specifications, or to their equivalents, and specially designed components therefor;</p> <p><u><i>Note</i></u> <i>For the purpose of Category Code ML13.d.1., military standards or specifications include, at a minimum, specifications for fragmentation protection.</i></p> <p>2. Hard body armour plates providing ballistic protection equal to or greater than level III (NIJ 0101.06, July 2008) or national equivalents.</p> <p><u><i>Note 1</i></u> <i>Category Code ML13.b. includes materials specially designed to form explosive reactive armour or to construct military shelters.</i></p> <p><u><i>Note 2</i></u> <i>Category Code ML13.c. does not apply to conventional steel helmets, neither modified or designed to accept, nor equipped with any type of accessory device.</i></p> <p><u><i>Note 3</i></u> <i>Category Codes ML13.c. and ML13.d. do not apply to helmets, body armour or protective garments, when accompanying their user for the user's own personal protection.</i></p> <p><u><i>Note 4</i></u> <i>The only helmets specially designed for bomb disposal personnel that are specified in Category Code ML13 are those specially designed for military use.</i></p> <p><u><i>N.B. 1</i></u> <i>See also Category Code 1A005 in Division 2 of Part 2 of this Schedule.</i></p>

<i>Category Code</i>	<i>Item Description</i>
ML14	<p><u>N.B. 2</u> <i>For “fibrous or filamentary materials” used in the manufacture of body armour and helmets, see Category Code 1C010 in Division 2 of Part 2 of this Schedule.</i></p> <p>‘Specialised equipment for military training’ or for simulating military scenarios, simulators specially designed for training in the use of any firearm or weapon specified in Category Code ML1 or ML2, and specially designed components and accessories therefor.</p> <p><u>Technical Note</u> <i>The term ‘specialised equipment for military training’ includes military types of attack trainers, operational flight trainers, radar target trainers, radar target generators, gunnery training devices, anti-submarine warfare trainers, flight simulators (including human-rated centrifuges for pilot/astronaut training), radar trainers, instrument flight trainers, navigation trainers, missile launch trainers, target equipment, drone “aircraft”, armament trainers, pilotless “aircraft” trainers, mobile training units and training equipment for ground military operations.</i></p> <p><u>Note 1</u> <i>Category Code ML14 includes image generating and interactive environment systems for simulators, when specially designed or modified for military use.</i></p> <p><u>Note 2</u> <i>Category Code ML14 does not apply to equipment specially designed for training in the use of hunting or sporting weapons.</i></p>
ML15	<p>Imaging or countermeasure equipment, as follows, specially designed for military use, and specially designed components and accessories therefor:</p> <ol style="list-style-type: none"> a. Recorders and image processing equipment; b. Cameras, photographic equipment and film processing equipment; c. Image intensifier equipment; d. Infrared or thermal imaging equipment;

<i>Category Code</i>	<i>Item Description</i>
	<p>e. Imaging radar sensor equipment;</p> <p>f. Countermeasure or counter-countermeasure equipment, for the equipment specified in Category Codes ML15.a. to ML15.e.</p> <p><i>Note</i> Category Code ML15.f. includes equipment designed to degrade the operation or effectiveness of military imaging systems or to minimise such degrading effects.</p> <p><i>Note 1</i> In Category Code ML15, the term specially designed components includes the following, when specially designed for military use:</p> <p>a. Infrared image converter tubes;</p> <p>b. Image intensifier tubes (other than first generation);</p> <p>c. Microchannel plates;</p> <p>d. Low-light-level television camera tubes;</p> <p>e. Detector arrays (including electronic interconnection or read out systems);</p> <p>f. Pyroelectric television camera tubes;</p> <p>g. Cooling systems for imaging systems;</p> <p>h. Electrically triggered shutters of the photochromic or electro-optical type having a shutter speed of less than 100 μs, except in the case of shutters which are an essential part of a high speed camera;</p> <p>i. Fibre optic image inverters;</p> <p>j. Compound semiconductor photocathodes.</p> <p><i>Note 2</i> Category Code ML15 does not apply to “first generation image intensifier tubes” or equipment specially designed to incorporate “first generation image intensifier tubes”.</p>

<i>Category Code</i>	<i>Item Description</i>
	<p><u>N.B.</u> For the classification of weapon-sights incorporating “first generation image intensifier tubes” see Category Codes ML1, ML2 and ML5.a.</p> <p><u>N.B.</u> See also Category Codes 6A002.a.2. and 6A002.b. in Division 2 of Part 2 of this Schedule.</p>
ML16	<p>Forgings, castings and other unfinished products, specially designed for items specified in Category Code ML1 to ML4, ML6, ML9, ML10, ML12 or ML19.</p> <p><u>Note</u> Category Code ML16 applies to unfinished products when they are identifiable by material composition, geometry or function.</p>
ML17	<p>Miscellaneous equipment, materials and “libraries”, as follows, and specially designed components therefor:</p> <p>a. Diving and underwater swimming apparatus, specially designed or modified for military use, as follows:</p> <ol style="list-style-type: none"> 1. Self-contained diving rebreathers, closed or semi-closed circuit; 2. Underwater swimming apparatus specially designed for use with the diving apparatus specified in Category Code ML17.a.1.; <p><u>N.B.</u> See also Category Code 8A002.q. in Division 2 of Part 2 of this Schedule.</p> <p>b. Construction equipment specially designed for military use;</p> <p>c. Fittings, coatings and treatments, for signature suppression, specially designed for military use;</p> <p>d. Field engineer equipment specially designed for use in a combat zone;</p>

<i>Category Code</i>	<i>Item Description</i>
	<p>e. “Robots”, “robot” controllers and “robot” “end-effectors”, having any of the following characteristics:</p> <ol style="list-style-type: none"> 1. Specially designed for military use; 2. Incorporating means of protecting hydraulic lines against externally induced punctures caused by ballistic fragments (e.g. incorporating self-sealing lines) and designed to use hydraulic fluids with flash points higher than 839 K (566°C); <u>or</u> 3. Specially designed or rated for operating in an electromagnetic pulse (EMP) environment; <p><i>Technical Note</i> <i>Electromagnetic pulse does not refer to unintentional interference caused by electromagnetic radiation from nearby equipment (e.g. machinery, appliances or electronics) or lightning.</i></p> <p>f. “Libraries” specially designed or modified for military use with systems, equipment or components, specified in this Division;</p> <p>g. Nuclear power generating equipment or propulsion equipment, including “nuclear reactors”, specially designed for military use and components therefor specially designed or ‘modified’ for military use;</p> <p>h. Equipment and material, coated or treated for signature suppression, specially designed for military use, other than those specified elsewhere in this Division;</p> <p>i. Simulators specially designed for military “nuclear reactors”;</p> <p>j. Mobile repair shops specially designed or ‘modified’ to service military equipment;</p> <p>k. Field generators specially designed or ‘modified’ for military use;</p> <p>l. Containers specially designed or ‘modified’ for military use;</p> <p>m. Ferries, other than those specified elsewhere in this Division, bridges and pontoons, specially designed for military use;</p>

<i>Category Code</i>	<i>Item Description</i>
	<p>n. Test models specially designed for the “development” of items specified in Category Code ML4, ML6, ML9 or ML10;</p> <p>o. “Laser” protection equipment (e.g. eye and sensor protection) specially designed for military use;</p> <p>p. “Fuel cells”, other than those specified elsewhere in this Division, specially designed or ‘modified’ for military use.</p> <p><u>Technical Notes</u></p> <p>1. <i>Not used.</i></p> <p>2. <i>For the purpose of Category Code ML17, ‘modified’ means any structural, electrical, mechanical, or other change that provides a non-military item with military capabilities equivalent to an item which is specially designed for military use.</i></p>
ML18	<p>‘Production’ equipment and components, as follows:</p> <p>a. Specially designed or modified ‘production’ equipment for the ‘production’ of products specified in this Division, and specially designed components therefor;</p> <p>b. Specially designed environmental test facilities and specially designed equipment therefor, for the certification, qualification or testing of products specified in this Division.</p> <p><u>Technical Note</u></p> <p><i>For the purpose of Category Code ML18, the term ‘production’ includes design, examination, manufacture, testing and checking.</i></p> <p><u>Note</u></p> <p><i>Category Codes ML18.a. and ML18.b. include the following equipment:</i></p> <p>a. <i>Continuous nitrators;</i></p>

<i>Category Code</i>	<i>Item Description</i>
	<p>b. <i>Centrifugal testing apparatus or equipment, having any of the following characteristics:</i></p> <ol style="list-style-type: none"> 1. <i>Driven by a motor or motors having a total rated horsepower of more than 298 kW (400 hp);</i> 2. <i>Capable of carrying a payload of 113 kg or more; <u>or</u></i> 3. <i>Capable of exerting a centrifugal acceleration of 8 g or more on a payload of 91 kg or more;</i> <p>c. <i>Dehydration presses;</i></p> <p>d. <i>Screw extruders specially designed or modified for military “explosive” extrusion;</i></p> <p>e. <i>Cutting machines for the sizing of extruded “propellants”;</i></p> <p>f. <i>Sweetie barrels (tumblers) 1.85 m or more in diameter and having over 227 kg product capacity;</i></p> <p>g. <i>Continuous mixers for solid “propellants”;</i></p> <p>h. <i>Fluid energy mills for grinding or milling the ingredients of military “explosives”;</i></p> <p>i. <i>Equipment to achieve both sphericity and uniform particle size in metal powder listed in Category Code ML8.c.8.;</i></p> <p>j. <i>Convection current converters for the conversion of materials listed in Category Code ML8.c.3.</i></p>
ML19	<p>Directed Energy Weapon (DEW) systems, related or countermeasure equipment and test models, as follows, and specially designed components therefor:</p> <ol style="list-style-type: none"> a. <i>“Laser” systems specially designed for destruction or effecting mission-abort of a target;</i> b. <i>Particle beam systems capable of destruction or effecting mission-abort of a target;</i> c. <i>High power Radio-Frequency (RF) systems capable of destruction or effecting mission-abort of a target;</i> d. <i>Equipment specially designed for the detection or identification of, or defence against, systems specified in Category Codes ML19.a. to ML19.c.;</i>

<i>Category Code</i>	<i>Item Description</i>
	<p>e. Physical test models for the systems, equipment and components, specified in Category Code ML19;</p> <p>f. “Laser” systems specially designed to cause permanent blindness to unenhanced vision, i.e. to the naked eye or to the eye with corrective eyesight devices.</p> <p><i>Note 1</i> DEW systems specified in Category Code ML19 include systems whose capability is derived from the controlled application of:</p> <p>a. “Lasers” of sufficient power to effect destruction similar to the manner of conventional ammunition;</p> <p>b. Particle accelerators which project a charged or neutral particle beam with destructive power;</p> <p>c. High pulsed power or high average power radio frequency beam transmitters, which produce fields sufficiently intense to disable electronic circuitry at a distant target.</p> <p><i>Note 2</i> Category Code ML19 includes the following when specially designed for DEW systems:</p> <p>a. Prime power generation, energy storage, switching, power conditioning or fuel-handling equipment;</p> <p>b. Target acquisition or tracking systems;</p> <p>c. Systems capable of assessing target damage, destruction or mission-abort;</p> <p>d. Beam-handling, propagation or pointing equipment;</p> <p>e. Equipment with rapid beam slew capability for rapid multiple target operations;</p> <p>f. Adaptive optics and phase conjugators;</p> <p>g. Current injectors for negative hydrogen ion beams;</p> <p>h. “Space-qualified” accelerator components;</p>

<i>Category Code</i>	<i>Item Description</i>
ML20	<p data-bbox="502 448 1260 649"> <i>i. Negative ion beam funnelling equipment;</i> <i>j. Equipment for controlling and slewing a high energy ion beam;</i> <i>k. “Space-qualified” foils for neutralising negative hydrogen isotope beams.</i> </p> <p data-bbox="502 716 1260 784">Cryogenic and “superconductive” equipment, as follows, and specially designed components and accessories therefor:</p> <p data-bbox="502 795 1260 974"> <i>a. Equipment specially designed or configured to be installed in a vehicle for military ground, marine, airborne or space applications, capable of operating while in motion and of producing or maintaining temperatures below 103 K (-170°C);</i> </p> <p data-bbox="566 985 630 1019"><i>Note</i></p> <p data-bbox="566 1030 1260 1198"> <i>Category Code ML20.a. includes mobile systems incorporating or employing accessories or components manufactured from non-metallic or non-electrical conductive materials, such as plastics or epoxy-impregnated materials.</i> </p> <p data-bbox="502 1209 1260 1377"> <i>b. “Superconductive” electrical equipment (rotating machinery and transformers) specially designed or configured to be installed in a vehicle for military ground, marine, airborne or space applications and capable of operating while in motion.</i> </p> <p data-bbox="566 1400 630 1433"><i>Note</i></p> <p data-bbox="566 1444 1260 1601"> <i>Category Code ML20.b. does not apply to direct-current hybrid homopolar generators that have single-pole normal metal armatures which rotate in a magnetic field produced by superconducting windings, provided those windings are the only superconducting components in the generator.</i> </p>

<i>Category Code</i>	<i>Item Description</i>
ML21	<p>“Software” as follows:</p> <ul style="list-style-type: none"> a. “Software” specially designed or modified for any of the following: <ul style="list-style-type: none"> 1. “Development”, “production”, operation or maintenance of equipment specified in this Division; 2. “Development” or “production” of materials specified in this Division; <u>or</u> 3. “Development”, “production”, operation or maintenance of “software” specified in this Division; b. Specific “software”, other than that specified in Category Code ML21.a., as follows: <ul style="list-style-type: none"> 1. “Software” specially designed for military use and specially designed for modelling, simulating or evaluating military weapon systems; 2. “Software” specially designed for military use and specially designed for modelling or simulating military operational scenarios; 3. “Software” for determining the effects of conventional, nuclear, chemical or biological weapons; 4. “Software” specially designed for military use and specially designed for Command, Communications, Control and Intelligence (C³I) or Command, Communications, Control, Computer and Intelligence (C⁴I) applications; c. “Software”, not specified in Category Code ML21.a. or ML21.b., specially designed or modified to enable equipment not specified in this Division to perform the military functions of equipment specified in this Division.
ML22	<p>“Technology” as follows:</p> <ul style="list-style-type: none"> a. “Technology”, other than specified in Category Code ML22.b., which is “required” for the “development”, “production”, operation, installation, maintenance (checking), repair, overhaul or refurbishing of items specified in this Division;

<i>Category Code</i>	<i>Item Description</i>
	<p>b. “Technology” as follows:</p> <ol style="list-style-type: none"> 1. “Technology” “required” for the design of, the assembly of components into, and the operation, maintenance and repair of, complete production installations for items specified in this Division, even if the components of such production installations are not specified; 2. “Technology” “required” for the “development” and “production” of small arms, even if used to produce reproductions of antique small arms; 3. Not used; <i>N.B.</i> <i>See Category Code ML22.a. for “technology” previously specified by Category Code ML22.b.3.</i> 4. Not used; <i>N.B.</i> <i>See Category Code ML22.a. for “technology” previously specified by Category Code ML22.b.4.</i> 5. “Technology” “required” exclusively for the incorporation of “biocatalysts”, specified in Category Code ML7.i.1., into military carrier substances or military material. <p><i>Note 1</i> “Technology” “required” for the “development”, “production”, operation, installation, maintenance (checking), repair, overhaul or refurbishing of items specified in this Division is considered to fall within Category Code ML22 even when applicable to any goods which are not specified in this Division.</p> <p><i>Note 2</i> Category Code ML22 does not include “technology” for magnetic induction for continuous propulsion of civil transport devices.</p>

PART 2

DUAL-USE GOODS THE EXPORT, TRANSHIPMENT OR
BRINGING IN TRANSIT OF WHICH, AND TECHNOLOGY
THE EXPORT OR TRANSMISSION OF WHICH, REQUIRE A PERMIT

Division 1 — Preliminary Provisions

Subdivision 1 — General Notes

1. Non-controlled goods (including plant) containing one or more controlled components set out in Division 2 are considered to be controlled goods within Division 2, if the controlled components are the principal element of the non-controlled goods and can feasibly be removed or used for other purposes.
2. In determining whether goods are to be considered the principal element of other goods for the purposes of paragraph 1, factors such as the quantity, value and technological know-how involved, and other special circumstances which might establish the goods as the principal element of the other goods, must be weighed.
3. Goods specified in Division 2 include both new and used goods.
4. Chemicals in Division 2 are listed by name and CAS number. Chemicals of the same structural formula (including hydrates) as chemicals listed in Division 2 are to be considered as coming within the descriptions of the second-mentioned chemicals regardless of name or CAS number. CAS numbers are shown in order to assist in identifying whether a particular chemical or mixture is a chemical within Division 2, irrespective of nomenclature. CAS numbers are not intended to be used as unique identifiers, because some forms of the listed chemical have different CAS numbers, and mixtures containing a listed chemical may also have different CAS numbers.

Subdivision 2 — Nuclear Technology Note (NTN)

(To be read in conjunction with section E of Category 0.)

5. “Technology” for the “development”, “production” or “use” of goods specified in Category 0 are considered to be “technology” under section E of that Category even when applicable to goods not so specified.

Subdivision 3 — General Technology Note (GTN)

(To be read in conjunction with section E of Categories 1 to 9.)

6. “Technology” under section E of Categories 1 to 9 is “technology” which is “required” for the “development”, “production” or “use” of goods specified in those Categories.

“Technology” for the “development”, “production” or “use” of goods specified in Categories 1 to 9 is considered to be “technology” under section E of those Categories even when applicable to goods not so specified.

Subdivision 4 — General Software Note (GSN)

7. Categories 0 to 9 of Division 2 do not include “software” which is any of the following:

- a. Software generally available to the public by being:
 1. Sold from stock at retail selling points, without restriction, by means of:
 - a. Over-the-counter transactions;
 - b. Mail order transactions;
 - c. Electronic transactions; or
 - d. Telephone order transactions; and
 2. Designed for installation by the user without further substantial support by the supplier; or
- b. The minimum necessary “object code” for the installation, operation, maintenance (checking) or repair of those items whose export has been authorised.

Note

Paragraph 7 does not extend to “software” specified in Category 5 — Part 2 (“Information Security”).

Subdivision 5 — General “Information Security” Note (GISN)

8. “Information security” items or functions, even if they are components, “software” or functions of other items, are treated as coming within Category 5 — Part 2.

Subdivision 6 — Definitions of Words and Expressions in this Part

9. In this Part, a word or expression in quotation marks (“ ”) takes the definition set out against it in this paragraph:

“accuracy” (Categories 2, 3, 6, 7, 8), usually measured in terms of inaccuracy, means the maximum deviation, positive or negative, of an indicated value from an accepted standard or true value;

“active flight control systems” (Category 7) means systems that function to prevent undesirable “aircraft” and missile motions or structural loads by autonomously processing outputs from multiple sensors and then providing the necessary preventive commands to effect automatic control;

“active pixel” (Category 6) means a minimum (single) element of the solid state array which has a photoelectric transfer function when exposed to light (electromagnetic) radiation;

“adapted for use in war” (Category 1) means any modification or selection (such as altering purity, shelf life, virulence, dissemination characteristics, or resistance to UV radiation) designed to increase the effectiveness in producing casualties in humans or animals, degrading equipment or damaging crops or the environment;

“adjusted peak performance” (Category 4) means an adjusted peak rate at which “digital computers” perform 64-bit or larger floating point additions and multiplications, and is expressed in Weighted TeraFLOPS (WT) with units of 10^{12} adjusted floating point operations per second;

N.B.

See Category 4, Technical Note.

“aircraft” (Categories 1, 6, 7, 9) means a fixed wing, swivel wing, rotary wing (helicopter), tilt rotor or tilt-wing airborne vehicle;

N.B.

See also “civil aircraft”.

“airship” (Category 9) means a power-driven airborne vehicle that is kept buoyant by a body of gas (usually helium, formerly hydrogen) which is lighter than air;

“all compensations available” (Category 2) means after all feasible measures available to the manufacturer to minimise all systematic positioning errors for the particular machine-tool model or measuring errors for the particular coordinate measuring machine are considered;

“allocated by the ITU” (Categories 3, 5) means the allocation of frequency bands according to the current edition of the ITU Radio Regulations for primary, permitted and secondary services;

Note

Additional and alternative allocations are not included.

“angle random walk” (Category 7) means the angular error build-up with time that is due to white noise in angular rate (Ref. IEEE Std 528-2001);

“angular position deviation” (Category 2) means the maximum difference between angular position and the actual, very accurately measured angular position after the workpiece mount of the table has been turned out of its initial position;

“APP” (Category 4) is equivalent to “Adjusted Peak Performance”;

“asymmetric algorithm” (Category 5) means a cryptographic algorithm using different, mathematically-related keys for encryption and decryption;

Note

A common use of “asymmetric algorithms” is key management.

“automatic target tracking” (Category 6) means a processing technique that automatically determines and provides as output an extrapolated value of the most probable position of the target in real time;

“average output power” (Category 6) means the total “laser” output energy, in joules, divided by the period over which a series of consecutive pulses is emitted, in seconds. For a series of uniformly spaced pulses it is equal to the total “laser” output energy in a single pulse, in joules, multiplied by the pulse frequency of the “laser”, in Hertz;

“basic gate propagation delay time” (Category 3) means the propagation delay time value corresponding to the basic gate used in a “monolithic integrated circuit”. For a ‘family’ of “monolithic integrated circuits”, this may be specified either as the propagation delay time per typical gate within the given ‘family’ or as the typical propagation delay time per gate within the given ‘family’;

Note 1

“Basic gate propagation delay time” is not to be confused with the input or output delay time of a complex “monolithic integrated circuit”.

Note 2

'Family' consists of all integrated circuits to which all of the following are applied as their manufacturing methodology and specifications except their respective functions:

- a. The common hardware and software architecture;
- b. The common design and process technology; and
- c. The common basic characteristics.

"bias" (accelerometer) (Category 7) means the average over a specified time of accelerometer output, measured at specified operating conditions, that has no correlation with input acceleration or rotation. "Bias" (accelerometer) is expressed in g or in metres per second squared (g or m/s^2). (Ref. IEEE Std 528-2001) (Micro g equals 1×10^{-6} g);

"bias" (gyro) (Category 7) means the average over a specified time of gyro output, measured at specified operating conditions, that has no correlation with input rotation or acceleration. "Bias" (gyro) is typically expressed in degrees per hour (deg/hr). (Ref. IEEE Std 528-2001);

"camming" (Category 2) means axial displacement in one revolution of the main spindle measured in a plane perpendicular to the spindle faceplate, at a point next to the circumference of the spindle faceplate (Ref. ISO 230-1:1986, paragraph 5.63);

"carbon fibre preforms" (Category 1) means an ordered arrangement of uncoated or coated fibres intended to constitute a framework of a part before the "matrix" is introduced to form a "composite";

"chemical laser" (Category 6) means a "laser" in which the excited species is produced by the output energy from a chemical reaction;

"chemical mixture" (Category 1) means a solid, liquid or gaseous product made up of two or more components which do not react together under the conditions under which the mixture is stored;

"Circular Error Probable" ("CEP") (Category 7) means in a circular normal distribution, the radius of the circle containing 50% of the individual measurements being made, or the radius of the circle within which there is a 50% probability of being located;

"circulation-controlled anti-torque or circulation-controlled direction control systems" (Category 7) means systems that use air blown over aerodynamic surfaces to increase or control the forces generated by the surfaces;

“civil aircraft” (Categories 1, 3, 4, 7) means an “aircraft” listed by designation in published airworthiness certification lists by the civil aviation authorities of a “participating state” to fly commercial civil internal and external routes or for legitimate civil, private or business use;

N.B.

See also “aircraft”.

“commingled” (Category 1) means filament to filament blending of thermoplastic fibres and reinforcement fibres in order to produce a fibre reinforcement “matrix” mix in total fibre form;

“comminution” (Category 1) means a process to reduce a material to particles by crushing or grinding;

“communications channel controller” (Category 4) means the physical interface which controls the flow of synchronous or asynchronous digital information. It is an assembly that can be integrated into computer or telecommunications equipment to provide communications access;

“compensation systems” (Category 6) means systems which consist of the primary scalar sensor, one or more reference sensors (e.g. vector magnetometers) together with software that permit reduction of rigid body rotation noise of the platform;

“composite” (Categories 1, 2, 6, 8, 9) means a “matrix” and an additional phase or additional phases consisting of particles, whiskers, fibres or any combination thereof, present for a specific purpose or purposes;

“compound rotary table” (Category 2) means a table allowing the workpiece to rotate and tilt about two non-parallel axes, which can be coordinated simultaneously for “contouring control”;

“III/V compounds” (Categories 3, 6) means polycrystalline or binary or complex monocrystalline products consisting of elements of groups IIIA and VA of Mendeleev’s periodic classification table (e.g. gallium arsenide, gallium-aluminium arsenide, indium phosphide);

“contouring control” (Category 2) means two or more “numerically controlled” motions operating in accordance with instructions that specify the next required position and the required feed rates to that position. These feed rates are varied in relation to each other so that a desired contour is generated (Ref. ISO/DIS 2806-1980);

“critical temperature” (Categories 1, 3, 5) (sometimes referred to as the transition temperature) of a specific “superconductive” material means the temperature at which the material loses all resistance to the flow of direct electrical current;

“cryptographic activation” (Category 5) means any technique that activates or enables cryptographic capability of an item, by means of a secure mechanism implemented by the manufacturer of the item, where this mechanism is uniquely bound to any of the following:

- a. A single instance of the item; or
- b. One customer, for multiple instances of the item;

Technical Notes

1. “Cryptographic activation” techniques and mechanisms may be implemented as hardware, “software” or “technology”.
2. Mechanisms for “cryptographic activation” can, for example, be serial number-based licence keys or authentication instruments such as digitally signed certificates.

“cryptography” (Category 5) means the discipline which embodies principles, means and methods for the transformation of data in order to hide its information content, prevent its undetected modification or prevent its unauthorised use. “Cryptography” is limited to the transformation of information using one or more ‘secret parameters’ (e.g. crypto variables) or associated key management;

Note

“Cryptography” does not include ‘fixed’ data compression or coding techniques.

Technical Note

‘Fixed’ means the coding or compression algorithm cannot accept externally supplied parameters (e.g. cryptographic or key variables) and cannot be modified by the user.

Technical Note

‘Secret parameter’ means a constant or key kept from the knowledge of others or shared only within a group.

“CW laser” (Category 6) means a “laser” that produces a nominally constant output energy for greater than 0.25 seconds;

“Data-Based Referenced Navigation” (“DBRN”) (Category 7) Systems means systems which use various sources of previously measured geo-mapping data integrated to provide accurate navigation information under dynamic conditions. Data sources include bathymetric maps, stellar maps, gravity maps, magnetic maps or 3-D digital terrain maps;

“deformable mirrors” (Category 6) (also known as adaptive optic mirrors) means mirrors having:

- a. A single continuous optical reflecting surface which is dynamically deformed by the application of individual torques or forces to compensate for distortions in the optical waveform incident upon the mirror; or
- b. Multiple optical reflecting elements that can be individually and dynamically repositioned by the application of torques or forces to compensate for distortions in the optical waveform incident upon the mirror;

“depleted uranium” (Category 0) means uranium depleted in the isotope 235 below that occurring in nature;

“development” (GTN, NTN, All Categories) has the same meaning as in the Act;

“diffusion bonding” (Categories 1, 2, 9) means a solid state joining of at least two separate pieces of metals into a single piece with a joint strength equivalent to that of the weakest material, wherein the principal mechanism is interdiffusion of atoms across the interface;

“digital computer” (Categories 4, 5) means equipment which can, in the form of one or more discrete variables, perform all of the following:

- a. Accept data;
- b. Store data or instructions in fixed or alterable (writable) storage devices;
- c. Process data by means of a stored sequence of instructions which is modifiable; and
- d. Provide output of data;

Note

Modifications of a stored sequence of instructions include replacement of fixed storage devices, but not a physical change in wiring or interconnections.

“digital transfer rate” (Category 5) means the total bit rate of the information that is directly transferred on any type of medium;

N.B.

See also “total digital transfer rate”.

“direct-acting hydraulic pressing” (Category 2) means a deformation process which uses a fluid-filled flexible bladder in direct contact with the workpiece;

“drift rate” (gyro) (Category 7) means the component of gyro output that is functionally independent of input rotation. It is expressed as an angular rate. (Ref. IEEE Std 528-2001);

“effective gramme” (Categories 0, 1) of “special fissile material” means:

- a. For plutonium isotopes and uranium-233, the isotope weight in grammes;
- b. For uranium enriched 1 per cent or greater in the isotope uranium-235, the element weight in grammes multiplied by the square of its enrichment expressed as a decimal weight fraction;
- c. For uranium enriched below 1 per cent in the isotope uranium-235, the element weight in grammes multiplied by 0.0001;

“electronic assembly” (Categories 2, 3, 4) means a number of electronic components (i.e. ‘circuit elements’, ‘discrete components’, integrated circuits, etc.) connected together to perform one or more specific functions, replaceable as an entity and normally capable of being disassembled;

Technical Note 1

‘Circuit element’ means a single active or passive functional part of an electronic circuit, such as one diode, one transistor, one resistor, one capacitor, etc.

Technical Note 2

‘Discrete component’ means a separately packaged ‘circuit element’ with its own external connections.

“electronically steerable phased array antenna” (Categories 5, 6) means an antenna which forms a beam by means of phase coupling, i.e. the beam direction is controlled by the complex excitation coefficients of the radiating elements and the direction of that beam can be varied in azimuth or in elevation, or both, by application, both in transmission and reception, of an electrical signal;

“energetic materials” (Category 1) means substances or mixtures that react chemically to release energy required for their intended application. “Explosives”, ‘pyrotechnics’ and ‘propellants’ are subclasses of energetic materials;

Technical Note 1

‘Pyrotechnics’ means mixtures of solid or liquid fuels and oxidisers which, when ignited, undergo an energetic chemical reaction at a controlled rate intended to produce specific time delays, or quantities of heat, noise, smoke, visible light or infrared radiation. Pyrophorics are a subclass of ‘pyrotechnics’, which contain no oxidisers but ignite spontaneously on contact with air.

Technical Note 2

‘Propellants’ means substances or mixtures that react chemically to produce large volumes of hot gases at controlled rates to perform mechanical work.

“end-effectors” (Category 2) means grippers, ‘active tooling units’ and any other tooling that is attached to the baseplate on the end of a “robot” manipulator arm;

Technical Note

‘Active tooling unit’ means a device for applying motive power, process energy or sensing to the workpiece.

“equivalent density” (Category 6) means the mass of an optic per unit optical area projected onto the optical surface;

“explosives” (Category 1) means solid, liquid or gaseous substances or mixtures of substances which, in their application as primary, booster, or main charges in warheads, demolition and other applications, are required to detonate;

“fibrous or filamentary materials” (Categories 0, 1, 2, 8, 9) includes the following:

- a. Continuous “monofilaments”;
- b. Continuous “yarns” and “rovings”;
- c. “Tapes”, fabrics, random mats and braids;
- d. Chopped fibres, staple fibres and coherent fibre blankets;
- e. Whiskers, either monocrystalline or polycrystalline, of any length;
- f. Aromatic polyamide pulp;

“film type integrated circuit” (Category 3) means an array of ‘circuit elements’ and metallic interconnections formed by deposition of a thick or thin film on an insulating “substrate”;

Technical Note

‘Circuit element’ means a single active or passive functional part of an electronic circuit, such as one diode, one transistor, one resistor, one capacitor, etc.

“flight control optical sensor array” (Category 7) means a network of distributed optical sensors, using “laser” beams, to provide real-time flight control data for on-board processing;

“flight path optimisation” (Category 7) means a procedure that minimises deviations from a four-dimensional (space and time) desired trajectory based on maximising performance or effectiveness for mission tasks;

“fly-by-light system” (Category 7) means a primary digital flight control system employing feedback to control the aircraft during flight, where the commands to the effectors or actuators are optical signals;

“fly-by-wire system” (Category 7) means a primary digital flight control system employing feedback to control the aircraft during flight, where the commands to the effectors or actuators are electrical signals;

“focal plane array” (Category 6) means a linear or two-dimensional planar layer, or combination of planar layers, of individual detector elements, with or without readout electronics, which work in the focal plane;

Note

“Focal plane array” does not include a stack of single detector elements or any two, three or four element detectors provided time delay and integration is not performed within the element.

“fractional bandwidth” (Categories 3, 5) means the “instantaneous bandwidth” divided by the centre frequency, expressed as a percentage;

“frequency hopping” (Categories 5, 6) means a form of “spread spectrum” in which the transmission frequency of a single communication channel is made to change by a random or pseudo-random sequence of discrete steps;

“frequency mask trigger” (Category 3) for “signal analysers” means a mechanism where the trigger function is able to select a frequency range to be triggered on as a subset of the acquisition bandwidth while ignoring other signals that may also be present within the same acquisition bandwidth. A “frequency mask trigger” may contain more than one independent set of limits;

“frequency switching time” (Category 3) means the time (i.e. delay) taken by a signal when switched from an initial specified output frequency, to arrive at or within any of the following:

- a. ± 100 Hz of a final specified output frequency of less than 1 GHz;
or
- b. ± 0.1 part per million of a final specified output frequency of equal to or greater than 1 GHz;

“frequency synthesiser” (Category 3) means any kind of frequency source, regardless of the actual technique used, providing a multiplicity of simultaneous or alternative output frequencies, from one or more outputs, controlled by, derived from or disciplined by a lesser number of standard (or master) frequencies;

“fuel cell” (Category 8) means an electrochemical device that converts chemical energy directly into Direct Current (DC) electricity by consuming fuel from an external source;

“Full Authority Digital Engine Control System” or “FADEC System” (Category 9) means a digital electronic control system for a gas turbine engine that is able to autonomously control the engine throughout its whole operating range from demanded engine start until demanded engine shut-down, in both normal and fault conditions;

“fusible” (Category 1) means capable of being cross-linked or polymerised further (cured) by the use of heat, radiation, catalysts, etc., or that can be melted without pyrolysis (charring);

“gas atomisation” (Category 1) means a process to reduce a molten stream of metal alloy to droplets of 500 micrometre diameter or less by a high pressure gas stream;

“geographically dispersed” (Category 6) means a state where each location is distant from any other location by more than 1,500 m in any direction. Mobile sensors are always considered “geographically dispersed”;

“guidance set” (Category 7) means systems that integrate the process of measuring and computing a vehicle’s position and velocity (i.e. navigation) with that of computing and sending commands to the vehicle’s flight control systems to correct the trajectory;

“hot isostatic densification” (Category 2) means the process of pressurising a casting at temperatures exceeding 375 K (102°C) in a closed cavity through various media (gas, liquid, solid particles, etc.) to create equal force in all directions to reduce or eliminate internal voids in the casting;

“hybrid integrated circuit” (Category 3) means any combination of integrated circuit or circuits, or integrated circuit with ‘circuit elements’ or ‘discrete components’ connected together to perform one or more specific functions, and having all of the following characteristics:

- a. Containing at least one unencapsulated device;
- b. Connected together using typical IC production methods;
- c. Replaceable as an entity; and
- d. Not normally capable of being disassembled;

Technical Note 1

‘Circuit element’ means a single active or passive functional part of an electronic circuit, such as one diode, one transistor, one resistor, one capacitor, etc.

Technical Note 2

‘Discrete component’ means a separately packaged ‘circuit element’ with its own external connections.

“image enhancement” (Category 4) means the processing of externally derived information-bearing images by algorithms such as time compression, filtering, extraction, selection, correlation, convolution or transformations between domains (e.g. Fast Fourier Transform or Walsh transform). This does not include algorithms using only linear or rotational transformation of a single image, such as translation, feature extraction, registration or false colouration;

“immunotoxin” (Category 1) means a conjugate of one cell specific monoclonal antibody and a “toxin” or “sub-unit of toxin”, that selectively affects diseased cells;

“information security” (GSN, GISN, Category 5) means all the means and functions ensuring the accessibility, confidentiality or integrity of information or communications, excluding the means and functions intended to safeguard against malfunctions. “Information security” includes “cryptography”, “cryptographic activation”, ‘cryptanalysis’, protection against compromising emanations and computer security;

Technical Note

'Cryptanalysis' means analysis of a cryptographic system or its inputs and outputs to derive confidential variables or sensitive data, including clear text.

“instantaneous bandwidth” (Categories 3, 5) means the bandwidth over which output power remains constant within 3 dB without adjustment of other operating parameters;

“instrumented range” (Category 6) means the specified unambiguous display range of a radar;

“insulation” (Category 9) means insulation that is applied to the components of a rocket motor, i.e. the case, nozzle, inlets, case closures, and includes cured or semi-cured compounded rubber sheet stock containing an insulating or refractory material. It may also be incorporated as stress relief boots or flaps;

“interior lining” (Category 9) means interior lining that is suited for the bond interface between the solid propellant and the case or insulating liner, and is usually a liquid polymer based dispersion of refractory or insulating materials, e.g. carbon filled hydroxyl terminated polybutadiene (HTPB) or other polymer with added curing agents sprayed or screeded over a case interior;

“intrinsic magnetic gradiometer” (Category 6) means a single magnetic field gradient sensing element and associated electronics the output of which is a measure of magnetic field gradient;

N.B.

See also “magnetic gradiometer”.

“intrusion software” (Category 4) means “software” specially designed or modified to avoid detection by ‘monitoring tools’, or to defeat ‘protective countermeasures’, of a computer or network-capable device, and performing any of the following:

- a. The extraction of data or information, from a computer or network-capable device, or the modification of system or user data; or
- b. The modification of the standard execution path of a program or process in order to allow the execution of externally provided instructions;

Note 1

“Intrusion software” does not include any of the following:

- a. *Hypervisors, debuggers or Software Reverse Engineering (SRE) tools;*
- b. *Digital Rights Management (DRM) “software”; or*
- c. *“Software” designed to be installed by manufacturers, administrators or users, for the purposes of asset tracking or recovery.*

Note 2

Network-capable devices include mobile devices and smart meters.

Technical Notes

1. *‘Monitoring tools’ means “software” or hardware devices, that monitor system behaviours or processes running on a device. This includes antivirus (AV) products, end point security products, Personal Security Products (PSP), Intrusion Detection Systems (IDS), Intrusion Prevention Systems (IPS) or firewalls.*
2. *‘Protective countermeasures’ means techniques designed to ensure the safe execution of code, such as Data Execution Prevention (DEP), Address Space Layout Randomisation (ASLR) or sandboxing.*

“isolated live cultures” (Category 1) includes live cultures in dormant form and in dried preparations;

“isostatic presses” (Category 2) means equipment capable of pressurising a closed cavity through various media (e.g. gas, liquid, solid particles, etc.) to create equal pressure in all directions within the cavity upon a workpiece or material;

“laser” (Categories 0, 1, 2, 3, 5, 6, 7, 8, 9) means an item that produces spatially and temporally coherent light through amplification by stimulated emission of radiation;

N.B.

See also:

- *“Chemical laser”;*
- *“CW laser”;*
- *“Pulsed laser”;*
- *“Super High Power Laser”;*
- *“Transfer laser”.*

“library” (Category 1) (parametric technical database) means a collection of technical information, reference to which may enhance the performance of relevant systems, equipment or components;

“lighter-than-air vehicles” (Category 9) means balloons and “airships” that rely on hot air or other lighter-than-air gases such as helium or hydrogen for their lift;

“linearity” (Category 2) (usually measured in terms of non-linearity) means the maximum deviation of the actual characteristic (average of upscale and downscale readings), positive or negative, from a straight line so positioned as to equalise and minimise the maximum deviations;

“local area network” (Categories 4, 5) means a data communication system having all of the following characteristics:

- a. Allows an arbitrary number of independent ‘data devices’ to communicate directly with each other; and
- b. Is confined to a geographical area of moderate size (e.g. office building, plant, campus, warehouse);

Technical Note

‘Data device’ means equipment capable of transmitting or receiving sequences of digital information.

“magnetic gradiometers” (Category 6) means instruments designed to detect the spatial variation of magnetic fields from sources external to the instrument. They consist of multiple “magnetometers” and associated electronics the output of which is a measure of magnetic field gradient;

N.B.

See also “intrinsic magnetic gradiometer”.

“magnetometers” (Category 6) means instruments designed to detect magnetic fields from sources external to the instrument. They consist of a single magnetic field sensing element and associated electronics the output of which is a measure of the magnetic field;

“main storage” (Category 4) means the primary storage for data or instructions for rapid access by a central processing unit. It consists of the internal storage of a “digital computer” and any hierarchical extension thereto, such as cache storage or non-sequentially accessed extended storage;

“materials resistant to corrosion by UF₆” (Category 0) means copper, copper alloys, stainless steel, aluminium, aluminium oxide, aluminium alloys, nickel or alloys containing 60% or more nickel by weight and fluorinated hydrocarbon polymers;

“matrix” (Categories 1, 2, 9) means a substantially continuous phase that fills the space between particles, whiskers or fibres;

“measurement uncertainty” (Category 2) means the characteristic parameter which specifies in what range around the output value the correct value of the measurable variable lies with a confidence level of 95%. It includes the uncorrected systematic deviations, the uncorrected backlash and the random deviations (Ref. ISO 10360-2);

“mechanical alloying” (Category 1) means an alloying process resulting from the bonding, fracturing and rebonding of elemental and master alloy powders by mechanical impact. Non-metallic particles may be incorporated in the alloy by addition of the appropriate powders;

“melt extraction” (Category 1) means a process to ‘solidify rapidly’ and extract a ribbon-like alloy product by the insertion of a short segment of a rotating chilled block into a bath of a molten metal alloy;

Technical Note

‘Solidify rapidly’ means solidification of molten material at cooling rates exceeding 1,000 K/s.

“melt spinning” (Category 1) means a process to ‘solidify rapidly’ a molten metal stream impinging upon a rotating chilled block, forming a flake, ribbon or rod-like product;

Technical Note

‘Solidify rapidly’ means solidification of molten material at cooling rates exceeding 1,000 K/s.

“microcomputer microcircuit” (Category 3) means a “monolithic integrated circuit” or “multichip integrated circuit” containing an arithmetic logic unit (ALU) capable of executing general purpose instructions from an internal storage, on data contained in the internal storage;

Note

The internal storage may be augmented by an external storage.

“microprocessor microcircuit” (Category 3) means a “monolithic integrated circuit” or “multichip integrated circuit” containing an arithmetic logic unit (ALU) capable of executing a series of general purpose instructions from an external storage;

Note 1

“Microprocessor microcircuit” normally does not contain integral user-accessible storage, although storage present on-the-chip may be used in performing its logic function.

Note 2

“Microprocessor microcircuit” includes chip sets which are designed to operate together to provide the function of a “microprocessor microcircuit”.

“microorganisms” (Category 2) means bacteria, viruses, mycoplasmas, rickettsiae, chlamydiae or fungi, whether natural, enhanced or modified, either in the form of “isolated live cultures” or as material including living material which has been deliberately inoculated or contaminated with such cultures;

“missiles” (Categories 1, 3, 6, 7, 9) means complete rocket systems and unmanned aerial vehicle systems, capable of delivering at least 500 kg payload to a range of at least 300 km;

“monofilament” (Category 1) or filament means the smallest increment of fibre, usually several micrometres in diameter;

“monolithic integrated circuit” (Category 3) means a combination of passive or active ‘circuit elements’ or both which:

- a. Are formed by means of diffusion processes, implantation processes or deposition processes in or on a single semiconducting piece of material, a so-called chip;
- b. Can be considered as indivisibly associated; and
- c. Perform the function or functions of a circuit;

Technical Note

‘Circuit element’ means a single active or passive functional part of an electronic circuit, such as one diode, one transistor, one resistor or one capacitor, etc.

“monospectral imaging sensors” (Category 6) means sensors capable of acquisition of imaging data from one discrete spectral band;

“multichip integrated circuit” (Category 3) means two or more “monolithic integrated circuits” bonded to a common “substrate”;

“multispectral imaging sensors” (Category 6) means sensors capable of simultaneous or serial acquisition of imaging data from two or more discrete spectral bands. Sensors having more than twenty discrete spectral bands are sometimes referred to as hyperspectral imaging sensors;

“natural uranium” (Category 0) means uranium containing the mixtures of isotopes occurring in nature;

“network access controller” (Category 4) means a physical interface to a distributed switching network. It uses a common medium which operates throughout at the same “digital transfer rate” using arbitration (e.g. token or carrier sense) for transmission. Independently from any other, it selects data packets or data groups (e.g. Ref. IEEE 802) addressed to it. It is an assembly that can be integrated into computer or telecommunications equipment to provide communications access;

“neural computer” (Category 4) means a computational device designed or modified to mimic the behaviour of a neuron or a collection of neurons, i.e. a computational device which is distinguished by its hardware capability to modulate the weights and numbers of the interconnections of a multiplicity of computational components based on previous data;

“nuclear reactor” (Category 0) means a complete reactor capable of operation so as to maintain a controlled self-sustaining fission chain reaction. A “nuclear reactor” includes all the items within or attached directly to the reactor vessel, the equipment which controls the level of power in the core, and the components which normally contain, come into direct contact with or control the primary coolant of the reactor core;

“numerical control” (Category 2) means the automatic control of a process performed by a device that makes use of numeric data usually introduced as the operation is in progress (Ref. ISO 2382);

“object code” (GSN) means an equipment executable form of a convenient expression of one or more processes (“source code” or source language) which has been compiled by programming system;

“Operations, Administration or Maintenance” (“OAM”) (Category 5) means performing one or more of the following tasks:

- a. Establishing or managing any of the following:
 1. Accounts or privileges of users or administrators;
 2. Settings of an item; or
 3. Authentication data in support of the tasks described in paragraph a.1. or a.2.;
- b. Monitoring or managing the operating condition or performance of an item; or
- c. Managing logs or audit data in support of any of the tasks described in paragraph a. or b.;

Note

“OAM” does not include any of the following tasks or their associated key management functions:

- a. *Provisioning or upgrading any cryptographic functionality that is not directly related to establishing or managing authentication data in support of the tasks described in paragraph a.1. or a.2. above; or*
- b. *Performing any cryptographic functionality on the forwarding or data plane of an item.*

“optical computer” (Category 4) means a computer designed or modified to use light to represent data, and the computational logic elements of which are based on directly coupled optical devices;

“optical integrated circuit” (Category 3) means a “monolithic integrated circuit” or a “hybrid integrated circuit”, containing one or more parts designed to function as a photosensor or photoemitter or to perform an optical or an electro-optical function or functions;

“optical switching” (Category 5) means the routing of or switching of signals in optical form without conversion to electrical signals;

“overall current density” (Category 3) means the total number of ampere-turns in the coil (i.e. the sum of the number of turns multiplied by the maximum current carried by each turn) divided by the total cross-section of the coil (comprising the superconducting filaments, the metallic matrix in which the superconducting filaments are embedded, the encapsulating material, any cooling channels, etc.);

“participating state” (Categories 7, 9) means a state participating in the Wassenaar Arrangement (details of which are set out in <http://www.wassenaar.org/participants/index.html>);

“peak power” (Category 6) means the highest power attained in the “pulse duration”;

“personal area network” (Category 5) means a data communication system having all of the following characteristics:

- a. Allows an arbitrary number of independent or interconnected ‘data devices’ to communicate directly with each other; and
- b. Is confined to the communication between devices within the immediate vicinity of an individual person or device controller (e.g. single room, office, or automobile and their nearby surrounding spaces);

Technical Note

'Data device' means equipment capable of transmitting or receiving sequences of digital information.

“plasma atomisation” (Category 1) means a process to reduce a molten stream or solid metal to droplets of 500 µm diameter or less, using plasma torches in an inert gas environment;

“power management” (Category 7) means changing the transmitted power of the altimeter signal so that received power at the “aircraft” altitude is always at the minimum necessary to determine the altitude;

“previously separated” (Category 1) means the application of any process intended to increase the concentration of the controlled isotope;

“primary flight control” (Category 7) means an “aircraft” stability or manoeuvring control using force or moment generators, i.e. aerodynamic control surfaces or propulsive thrust vectoring;

“principal element” (Category 4), as it applies in Category 4, is an element the replacement value of which is more than 35% of the total value of the system of which it is an element. Element value is the price paid for the element by the manufacturer of the system, or by the system integrator. Total value is the normal international selling price to unrelated parties at the point of manufacture or consolidation of shipment;

“production” (GTN, NTN, All Categories) has the same meaning as in the Act;

“production equipment” (Categories 1, 7, 9) means tooling, templates, jigs, mandrels, moulds, dies, fixtures, alignment mechanisms, test equipment, other machinery and components therefor, limited to those specially designed or modified for “development” or for one or more phases of “production”;

“production facilities” (Categories 7, 9) means “production equipment” and specially designed software therefor integrated into installations for “development” or for one or more phases of “production”;

“program” (Categories 2, 6) means a sequence of instructions to carry out a process in, or convertible into, a form executable by an electronic computer;

“pulse compression” (Category 6) means the coding and processing of a radar signal pulse of long time duration to one of short time duration, while maintaining the benefits of high pulse energy;

“pulse duration” (Category 6) means the duration of a “laser” pulse, or the time between the half-power points on the leading edge and trailing edge of an individual pulse;

“pulsed laser” (Category 6) means a “laser” having a “pulse duration” that is less than or equal to 0.25 seconds;

“quantum cryptography” (Category 5) means a family of techniques for the establishment of shared key for “cryptography” by measuring the quantum-mechanical properties of a physical system (including those physical properties explicitly governed by quantum optics, quantum field theory or quantum electrodynamics);

“radar frequency agility” (Category 6) means any technique which changes, in a pseudo-random sequence, the carrier frequency of a pulsed radar transmitter between pulses or between groups of pulses by an amount equal to or larger than the pulse bandwidth;

“radar spread spectrum” (Category 6) means any modulation technique for spreading energy originating from a signal with a relatively narrow frequency band, over a much wider band of frequencies, by using random or pseudo-random coding;

“radiant sensitivity” (Category 6) means Radiant sensitivity (mA/W) = $0.807 \times (\text{wavelength in nm}) \times \text{Quantum Efficiency (QE)}$;

Technical Note

QE is usually expressed as a percentage; however, for the purposes of this formula, QE is expressed as a decimal number less than one, e.g. 78% is 0.78.

“real-time bandwidth” (Category 3) for “signal analysers” means the widest frequency range for which the analyser can continuously transform time-domain data entirely into frequency-domain results, using a Fourier or other discrete time transformation that processes every incoming time point without gaps or windowing effects that cause a reduction of measured amplitude of more than 3 dB below the actual signal amplitude, while outputting or displaying the transformed data;

“real-time processing” (Category 6) means the processing of data by a computer system providing a required level of service, as a function of available resources, within a guaranteed response time, regardless of the load of the system, when stimulated by an external event;

“repeatability” (Category 7) means the closeness of agreement among repeated measurements of the same variable under the same operating conditions when changes in conditions or non-operating periods occur between measurements (Ref. IEEE Std 528-2001 (one sigma standard deviation));

“required” (GTN, Categories 1-9), as applied to “technology”, refers to only that portion of “technology” which is peculiarly responsible for achieving or extending the controlled performance levels, characteristics or functions. Such “required” “technology” may be shared by different goods;

“resolution” (Category 2) means the least increment of a measuring device; or, on digital instruments, the least significant bit (Ref. ANSI B-89.1.12);

“riot control agents” (Category 1) means substances which, under the expected conditions of use for riot control purposes, produce rapidly in human sensory irritation or disabling physical effects which disappear within a short time following termination of exposure;

Technical Note

Tear gases are a subset of “riot control agents”.

“robot” (Categories 2, 8) means a manipulation mechanism, which may be of the continuous path or the point-to-point variety, may use sensors, and has all the following characteristics:

- a. It is multifunctional;
- b. It is capable of positioning or orienting material, parts, tools or special devices through variable movements in three dimensional space;
- c. It incorporates three or more closed or open loop servo-devices which may include stepping motors; and
- d. It has a “user-accessible programmability” by means of the teach/playback method or by means of an electronic computer which may be a programmable logic controller, i.e. without mechanical intervention;

Note

“Robot” does not include the following devices:

- a. *Manipulation mechanisms which are only manually or teleoperator controllable;*
- b. *Fixed sequence manipulation mechanisms which are automated moving devices, operating according to mechanically fixed programmed motions. The program is mechanically limited by fixed stops, such as pins or cams. The sequence of motions and the selection of paths or angles are not variable or changeable by mechanical, electronic or electrical means;*

-
- c. *Mechanically controlled variable sequence manipulation mechanisms which are automated moving devices, operating according to mechanically fixed programmed motions. The program is mechanically limited by fixed, but adjustable stops, such as pins or cams. The sequence of motions and the selection of paths or angles are variable within the fixed program pattern. Variations or modifications of the program pattern (e.g. changes of pins or exchanges of cams) in one or more motion axes are accomplished only through mechanical operations;*
 - d. *Non-servo-controlled variable sequence manipulation mechanisms which are automated moving devices, operating according to mechanically fixed programmed motions. The program is variable but the sequence proceeds only by the binary signal from mechanically fixed electrical binary devices or adjustable stops;*
 - e. *Stacker cranes defined as Cartesian coordinate manipulator systems manufactured as an integral part of a vertical array of storage bins and designed to access the contents of those bins for storage or retrieval.*

“rotary atomisation” (Category 1) means a process to reduce a stream or pool of molten metal to droplets to a diameter of 500 micrometre or less by centrifugal force;

“roving” (Category 1) means a bundle (typically 12-120) of approximately parallel ‘strands’;

Technical Note

‘Strand’ means a bundle of “monofilaments” (typically over 200) arranged approximately parallel to each other.

“run-out” (Category 2) (out-of-true running) means radial displacement in one revolution of the main spindle measured in a plane perpendicular to the spindle axis at a point on the external or internal revolving surface to be tested (Ref. ISO 230-1:1986, paragraph 5.61);

“scale factor” (gyro or accelerometer) (Category 7) means the ratio of change in output to a change in the input intended to be measured. “Scale factor” is generally evaluated as the slope of the straight line that can be fitted by the method of least squares to input-output data obtained by varying the input cyclically over the input range;

“settling time” (Category 3) means the time required for the output to come within one-half bit of the final value when switching between any two levels of the converter;

“signal analysers” (Category 3) means apparatus capable of measuring and displaying basic properties of the single-frequency components of multi-frequency signals;

“signal processing” (Categories 3, 4, 5, 6) means the processing of externally derived information-bearing signals by algorithms such as time compression, filtering, extraction, selection, correlation, convolution or transformations between domains (e.g. Fast Fourier Transform or Walsh transform);

“software” (GSN, All Categories) means a collection of one or more “programs” or ‘microprograms’ recorded, stored or embodied in any device;

Technical Note

‘Microprogram’ means a sequence of elementary instructions, maintained in a special storage, the execution of which is initiated by the introduction of its reference instruction into an instruction register.

“source code” (or source language) (Categories 6, 7, 9) means a convenient expression of one or more processes which may be turned by a programming system into equipment executable form (“object code” (or object language));

“spacecraft” (Category 9) means active and passive satellites and space probes;

“spacecraft bus” (Category 9) means equipment that provides the support infrastructure of the “spacecraft” and location for the “spacecraft payload”;

“spacecraft payload” (Category 9) means equipment, attached to the “spacecraft bus”, designed to perform a mission in space (e.g. communications, observation, science);

“space-qualified” (Categories 3, 6, 7) means designed, manufactured or qualified through successful testing, for operation at altitudes greater than 100 km above the surface of the Earth;

Note

A determination that a specific item is “space-qualified” by virtue of testing does not mean that other items in the same production run or model series are “space-qualified” if not individually tested.

“special fissile material” (Category 0) means plutonium-239, uranium-233, ‘uranium enriched in the isotopes 235 or 233’, and any material containing the foregoing;

Technical Note

‘uranium enriched in the isotopes 235 or 233’ means uranium containing the isotopes 235 or 233, or both, in an amount such that the abundance ratio of the sum of these isotopes to the isotope 238 is more than the ratio of the isotope 235 to the isotope 238 occurring in nature (isotopic ratio 0.71 per cent).

“specific modulus” (Categories 0, 1, 9) means Young’s modulus in pascals, equivalent to N/m^2 divided by specific weight in N/m^3 , measured at a temperature of (296 ± 2) K ($(23 \pm 2)^\circ C$) and a relative humidity of $(50 \pm 5)\%$;

“specific tensile strength” (Categories 0, 1, 9) means ultimate tensile strength in pascals, equivalent to N/m^2 divided by specific weight in N/m^3 , measured at a temperature of (296 ± 2) K ($(23 \pm 2)^\circ C$) and a relative humidity of $(50 \pm 5)\%$;

“spinning mass gyros” (Category 7) means gyros which use a continually rotating mass to sense angular motion;

“splat quenching” (Category 1) means a process to ‘solidify rapidly’ a molten metal stream impinging upon a chilled block, forming a flake-like product;

Technical Note

‘Solidify rapidly’ means solidification of molten material at cooling rates exceeding 1,000 K/s.

“spread spectrum” (Category 5) means the technique whereby energy in a relatively narrow-band communication channel is spread over a much wider energy spectrum;

“spread spectrum” radar (Category 6) – see “radar spread spectrum”;

“stability” (Category 7) means the standard deviation (1 sigma) of the variation of a particular parameter from its calibrated value measured under stable temperature conditions. It can be expressed as a function of time;

“substrate” (Category 3) means a sheet of base material with or without an interconnection pattern and on which or within which ‘discrete components’ or integrated circuits or both can be located;

Technical Note

'Discrete component' means a separately packaged 'circuit element' with its own external connections.

Technical Note

'Circuit element' means a single active or passive functional part of an electronic circuit, such as one diode, one transistor, one resistor or one capacitor, etc.

“substrate blanks” (Categories 3, 6) means monolithic compounds with dimensions suitable for the production of optical elements such as mirrors or optical windows;

“sub-unit of toxin” (Category 1) means a structurally and functionally discrete component of a whole “toxin”;

“superalloys” (Categories 2, 9) means nickel-, cobalt- or iron-base alloys having strengths superior to any alloys in the AISI 300 series at temperatures over 922 K (649°C) under severe environmental and operating conditions;

“superconductive” (Categories 1, 3, 5, 6, 8) means materials, i.e. metals, alloys or compounds, which can lose all electrical resistance, i.e. which can attain infinite electrical conductivity and carry very large electrical currents without Joule heating;

Note

The “superconductive” state of a material is individually characterised by a “critical temperature”, a critical magnetic field, which is a function of temperature, and a critical current density which is, however, a function of both magnetic field and temperature.

“Super High Power Laser” (“SHPL”) (Category 6) means a “laser” capable of delivering (the total or any portion of) the output energy exceeding 1 kJ within 50 ms or having an average or CW power exceeding 20 kW;

“superplastic forming” (Categories 1, 2) means a deformation process using heat for metals that are normally characterised by low values of elongation (less than 20%) at the breaking point as determined at room temperature by conventional tensile strength testing, in order to achieve elongations during processing which are at least 2 times those values;

“symmetric algorithm” (Category 5) means a cryptographic algorithm using an identical key for both encryption and decryption;

Note

A common use of “symmetric algorithms” is to safeguard confidentiality of data.

“systolic array computer” (Category 4) means a computer where the flow and modification of the data is dynamically controllable at the logic gate level by the user;

“tape” (Category 1) means a material constructed of interlaced or unidirectional “monofilaments”, ‘strands’, “rovings”, “tows”, “yarns”, etc., usually pre-impregnated with resin;

Technical Note

‘Strand’ is a bundle of “monofilaments” (typically over 200) arranged approximately parallel to each other.

“technology” (GTN, NTN, All Categories) means information (including information comprised in such documents as specifications, blueprints, plans, manuals, models, diagrams, formulae, tables and designs) that is necessary for the “development”, “production” or “use” of any goods;

“three dimensional integrated circuit” (Category 3) means a collection of semiconductor die, integrated together, and having vias passing completely through at least one die to establish interconnections between die;

“tilting spindle” (Category 2) means a tool-holding spindle which alters, during the machining process, the angular position of its centre line with respect to any other axis;

“time constant” (Category 6) means the time taken from the application of a light stimulus for the current increment to reach a value of $1 - 1/e$ times the final value (i.e. 63% of the final value);

“tip shroud” (Category 9) means a stationary ring component (solid or segmented) attached to the inner surface of the engine turbine casing or a feature at the outer tip of the turbine blade, which primarily provides a gas seal between the stationary and rotating components;

“total control of flight” (Category 7) means an automated control of “aircraft” state variables and flight path to meet mission objectives responding to real-time changes in data regarding objectives, hazards or other “aircraft”;

“total digital transfer rate” (Category 5) means the number of bits, including line coding, overhead and so forth per unit time passing between corresponding equipment in a digital transmission system;

N.B.

See also “digital transfer rate”.

“tow” (Category 1) means a bundle of “monofilaments”, usually approximately parallel to each other;

“toxins” (Categories 1, 2) means toxins in the form of deliberately isolated preparations or mixtures, no matter how produced, other than toxins present as contaminants of other materials such as pathological specimens, crops, foodstuffs or seed stocks of “microorganisms”;

“transfer laser” (Category 6) means a “laser” in which the lasing species is excited through the transfer of energy by collision of a non-lasing atom or molecule with a lasing atom or molecule species;

“tunable” (Category 6) means the ability of a “laser” to produce a continuous output at all wavelengths over a range of several “laser” transitions. A line selectable “laser” produces discrete wavelengths within one “laser” transition and is not considered “tunable”;

“unidirectional positioning repeatability” (Category 2) means the smaller of values R_{\uparrow} and R_{\downarrow} (forward and backward), as defined by 3.21 of ISO 230-2:2014 or national equivalents, of an individual machine tool axis;

“unmanned aerial vehicle” (“UAV”) (Category 9) means any aircraft capable of initiating flight and sustaining controlled flight and navigation without any human presence on board;

“use” (GTN, NTN, All Categories) has the same meaning as in the Act;

“user-accessible programmability” (Category 6) means the facility allowing a user to insert, modify or replace “programs” by means other than:

- a. A physical change in wiring or interconnections; or
- b. The setting of function controls including entry of parameters;

“vaccine” (Category 1) means a medicinal product in a pharmaceutical formulation licensed by, or having marketing or clinical trial authorisation from, the regulatory authorities of either the country of manufacture or of use, which is intended to stimulate a protective immunological response in humans or animals in order to prevent disease in those to whom or to which it is administered;

“vacuum atomisation” (Category 1) means a process to reduce a molten stream of metal to droplets of a diameter of 500 micrometre or less by the rapid evolution of a dissolved gas upon exposure to a vacuum;

“variable geometry airfoils” (Category 7) means the use of trailing edge flaps or tabs, or leading edge slats or pivoted nose droop, the position of which can be controlled in flight;

“yarn” (Category 1) means a bundle of twisted ‘strands’.

Technical Note

‘Strand’ means a bundle of “monofilaments” (typically over 200) arranged approximately parallel to each other.

10. In this Part, a word or expression enclosed with single quotation marks (‘’) takes the definition set out against it in the Technical Note that follows immediately after the provision in which the word or expression appears.

Subdivision 7 — Acronyms and Abbreviations used in this Part

The acronyms and abbreviations used in this Part and set out in the first column have the meanings set out against them in the second column.

<i>First column</i>	<i>Second column</i>
<i>Acronym or Abbreviation</i>	<i>Meaning</i>
ABEC	Annular Bearing Engineers Committee
ABMA	American Bearing Manufacturers Association
AGMA	American Gear Manufacturers Association
AHRS	Attitude and Heading Reference Systems
AISI	American Iron and Steel Institute
ALU	arithmetic logic unit
ANSI	American National Standards Institute
ASTM	the American Society for Testing and Materials
ATC	air traffic control
CAD	computer-aided design
CAS	Chemical Abstracts Service
CDU	control and display unit
CEP	circular error probable
CNTD	controlled nucleation thermal disposition
CPU	Central processing unit

<i>First column</i>	<i>Second column</i>
<i>Acronym or Abbreviation</i>	<i>Meaning</i>
CVD	chemical vapour deposition
CW	chemical warfare
CW (for laser)	continuous wave
DME	distance measuring equipment
DS	directionally solidified
EB-PVD	electron beam physical vapour deposition
ECM	electro-chemical machining
EDM	electrical discharge machines
EEPROMS	electrically erasable programmable read only memory
FFT	Fast Fourier Transform
GLONASS	global navigation satellite system
GPS	global positioning system
HBT	hetero-bipolar transistors
HEMT	high electron mobility transistors
ICAO	International Civil Aviation Organisation
IEC	International Electro-technical Commission
IEEE	Institute of Electrical and Electronic Engineers
IFOV	instantaneous-field-of-view
ILS	instrument landing system
ISA	international standard atmosphere
ISAR	inverse synthetic aperture radar
ISO	International Organisation for Standardisation
ITU	International Telecommunication Union
JT	Joule-Thomson
LIDAR	light detection and ranging
LRU	line replaceable unit

<i>First column</i>	<i>Second column</i>
<i>Acronym or Abbreviation</i>	<i>Meaning</i>
Mach	ratio of speed of an object to speed of sound (after Ernst Mach)
MLS	microwave landing systems
MOCVD	metal organic chemical vapour deposition
MRI	magnetic resonance imaging
MTBF	mean-time-between-failures
MTTF	mean-time-to-failure
NDT	non-destructive test
PAR	precision approach radar
PIN	personal identification number
ppm	parts per million
QAM	quadrature-amplitude-modulation
RF	radio frequency
SAR	synthetic aperture radar
SC	single crystal
SLAR	sidelooking airborne radar
SRA	shoe replaceable assembly
SRAM	static random access memory
SSB	single sideband
SSR	secondary surveillance radar
TIR	total indicated reading
UV	ultraviolet
UTS	ultimate tensile strength
VOR	very high frequency omni-directional range

Division 2 — List of Dual-Use Goods

<i>Category Code</i>	<i>Item Description</i>
CATEGORY 0 — NUCLEAR MATERIALS, FACILITIES, AND EQUIPMENT	
0A	Systems, Equipment and Components
0A001	<p>“Nuclear reactors” and specially designed or prepared equipment and components therefor, as follows:</p> <ul style="list-style-type: none"> a. “Nuclear reactors”; b. Metal vessels, or major shop-fabricated parts therefor, including the reactor vessel head for a reactor pressure vessel, specially designed or prepared to contain the core of a “nuclear reactor”; c. Manipulative equipment specially designed or prepared for inserting or removing fuel in a “nuclear reactor”; d. Control rods specially designed or prepared for the control of the fission process in a “nuclear reactor”, support or suspension structures therefor, rod drive mechanisms and rod guide tubes; e. Pressure tubes specially designed or prepared to contain both fuel elements and the primary coolant in a “nuclear reactor”; f. Zirconium metal tubes or zirconium alloy tubes (or assemblies of tubes) specially designed or prepared for use as fuel cladding in a “nuclear reactor”, and in quantities exceeding 10 kg; <p><u><i>N.B.</i></u> <i>For zirconium pressure tubes, see Category Code 0A001.e. and for calandria tubes, see Category Code 0A001.h.</i></p> <ul style="list-style-type: none"> g. Coolant pumps or circulators specially designed or prepared for circulating the primary coolant of “nuclear reactors”; h. ‘Nuclear reactor internals’ specially designed or prepared for use in a “nuclear reactor”, including support columns for the core, fuel channels, calandria tubes, thermal shields, baffles, core grid plates, and diffuser plates;

Category Code	Item Description
	<p><u>Technical Note</u></p> <p><i>In Category Code 0A001.h., ‘nuclear reactor internals’ means any major structure within a reactor vessel which has one or more functions such as supporting the core, maintaining fuel alignment, directing primary coolant flow, providing radiation shields for the reactor vessel, and guiding in-core instrumentation.</i></p> <p>i. Heat exchangers as follows:</p> <ol style="list-style-type: none"> 1. Steam generators specially designed or prepared for the primary, or intermediate, coolant circuit of a “nuclear reactor”; 2. Other heat exchangers specially designed or prepared for use in the primary coolant circuit of a “nuclear reactor”; <p><u>Note</u></p> <p><i>Category Code 0A001.i. does not include heat exchangers for the supporting systems of the reactor, e.g. the emergency cooling system or the decay heat cooling system.</i></p> <p>j. Neutron detectors specially designed or prepared for determining neutron flux levels within the core of a “nuclear reactor”;</p> <p>k. ‘External thermal shields’ specially designed or prepared for use in a “nuclear reactor” for the reduction of heat loss and also for the containment vessel protection.</p> <p><u>Technical Note</u></p> <p><i>In Category Code 0A001.k., ‘external thermal shields’ means major structures placed over the reactor vessel which reduce heat loss from the reactor and reduce temperature within the containment vessel.</i></p>
<p>0B</p>	<p>Test, Inspection and Production Equipment</p>
<p>0B001</p>	<p>Plant for the separation of isotopes of “natural uranium”, “depleted uranium” or “special fissile materials”, and specially designed or prepared equipment and components therefor, as follows:</p>

<i>Category Code</i>	<i>Item Description</i>
	<p>a. Plant specially designed for separating isotopes of “natural uranium”, “depleted uranium”, or “special fissile materials”, as follows:</p> <ol style="list-style-type: none"> 1. Gas centrifuge separation plant; 2. Gaseous diffusion separation plant; 3. Aerodynamic separation plant; 4. Chemical exchange separation plant; 5. Ion-exchange separation plant; 6. Atomic vapour “laser” isotope separation plant; 7. Molecular “laser” isotope separation plant; 8. Plasma separation plant; 9. Electromagnetic separation plant; <p>b. Gas centrifuges and assemblies and components, specially designed or prepared for gas centrifuge separation process, as follows:</p> <p><i>Technical Note</i> <i>In Category Code 0B001.b., ‘high strength-to-density ratio material’ means any of the following:</i></p> <ol style="list-style-type: none"> a. <i>Maraging steel capable of an ultimate tensile strength of 1.95 GPa or more;</i> b. <i>Aluminium alloys capable of an ultimate tensile strength of 0.46 GPa or more; <u>or</u></i> c. <i>“Fibrous or filamentary materials” with a “specific modulus” of more than 3.18×10^6 m and a “specific tensile strength” greater than 7.62×10^4 m.</i> <ol style="list-style-type: none"> 1. Gas centrifuges; 2. Complete rotor assemblies; 3. Rotor tube cylinders with a wall thickness of 12 mm or less, a diameter of between 75 mm and 650 mm, made from ‘high strength-to-density ratio materials’;

<i>Category Code</i>	<i>Item Description</i>
	<ol style="list-style-type: none"> <li data-bbox="539 454 1273 622">4. Rings or bellows with a wall thickness of 3 mm or less and a diameter of between 75 mm and 650 mm and designed to give local support to a rotor tube or to join a number together, made from ‘high strength-to-density ratio materials’; <li data-bbox="539 640 1273 741">5. Baffles of between 75 mm and 650 mm diameter for mounting inside a rotor tube, made from ‘high strength-to-density ratio materials’; <li data-bbox="539 759 1273 860">6. Top or bottom caps of between 75 mm and 650 mm diameter to fit the ends of a rotor tube, made from ‘high strength-to-density ratio materials’; <li data-bbox="539 878 1273 1205">7. Magnetic suspension bearings as follows: <ol style="list-style-type: none"> <li data-bbox="625 922 1273 1126">a. Bearing assemblies consisting of an annular magnet suspended within a housing made of or protected by “materials resistant to corrosion by UF₆” containing a damping medium and having the magnet coupling with a pole piece or second magnet fitted to the top cap of the rotor; <li data-bbox="625 1144 1273 1205">b. Active magnetic bearings specially designed or prepared for use with gas centrifuges; <li data-bbox="539 1223 1273 1283">8. Specially prepared bearings comprising a pivot-cup assembly mounted on a damper; <li data-bbox="539 1301 1273 1402">9. Molecular pumps comprised of cylinders having internally machined or extruded helical grooves and internally machined bores; <li data-bbox="539 1420 1273 1559">10. Ring-shaped motor stators for multiphase AC hysteresis (or reluctance) motors for synchronous operation within a vacuum at a frequency of 600 Hz or more and a power of 40 VA or more; <li data-bbox="539 1576 1273 1771">11. Centrifuge housing/recipients to contain the rotor tube assembly of a gas centrifuge, consisting of a rigid cylinder of wall thickness up to 30 mm with precision machined ends that are parallel to each other and perpendicular to the cylinder’s longitudinal axis to within 0.05 degrees or less;

<i>Category Code</i>	<i>Item Description</i>
	<p>12. Scoops consisting of specially designed or prepared tubes for the extraction of UF₆ gas from within the rotor tube by a Pitot tube action and capable of being fixed to the central gas extraction system;</p> <p>13. Frequency changers (converters or inverters) specially designed or prepared to supply motor stators for gas centrifuge enrichment, having all of the following characteristics, and specially designed components therefor:</p> <ol style="list-style-type: none"> a. A multiphase frequency output of 600 Hz or greater; <u>and</u> b. High stability (with frequency control better than 0.2%); <p>14. Shut-off and control valves, as follows:</p> <ol style="list-style-type: none"> a. Shut-off valves specially designed or prepared to act on the feed, product or tails UF₆ gaseous streams of an individual gas centrifuge; b. Bellows-sealed valves, shut-off or control, made of or protected by “materials resistant to corrosion by UF₆”, with an inside diameter of 10 mm to 160 mm, specially designed or prepared for use in main or auxiliary systems of gas centrifuge enrichment plants; <p>c. Equipment and components, specially designed or prepared for gaseous diffusion separation process, as follows:</p> <ol style="list-style-type: none"> 1. Gaseous diffusion barriers made of porous metallic, polymer or ceramic “materials resistant to corrosion by UF₆” with a pore size of 10 nm to 100 nm, a thickness of 5 mm or less, and, for tubular forms, a diameter of 25 mm or less; 2. Gaseous diffuser housings made of or protected by “materials resistant to corrosion by UF₆”; 3. Compressors or gas blowers with a suction volume capacity of 1 m³/min or more of UF₆, discharge pressure up to 500 kPa and having a pressure ratio of 10:1 or less, and made of or protected by “materials resistant to corrosion by UF₆”;

<i>Category Code</i>	<i>Item Description</i>
	<ol style="list-style-type: none"> 4. Rotary shaft seals for compressors or blowers specified in Category Code 0B001.c.3. and designed for a buffer gas in-leakage rate of less than 1,000 cm³/min; 5. Heat exchangers made of or protected by “materials resistant to corrosion by UF₆”, and designed for a leakage pressure rate of less than 10 Pa per hour under a pressure differential of 100 kPa; 6. Bellows-sealed valves, manual or automated, shut-off or control, made of or protected by “materials resistant to corrosion by UF₆”; <p>d. Equipment and components, specially designed or prepared for aerodynamic separation process, as follows:</p> <ol style="list-style-type: none"> 1. Separation nozzles consisting of slit-shaped, curved channels having a radius of curvature less than 1 mm, resistant to corrosion by UF₆, and having a knife-edge contained within the nozzle which separates the gas flowing through the nozzle into two streams; 2. Cylindrical or conical tubes, (vortex tubes), made of or protected by “materials resistant to corrosion by UF₆” and with one or more tangential inlets; 3. Compressors or gas blowers made of or protected by “materials resistant to corrosion by UF₆”, and rotary shaft seals therefor; 4. Heat exchangers made of or protected by “materials resistant to corrosion by UF₆”; 5. Separation element housings, made of or protected by “materials resistant to corrosion by UF₆” to contain vortex tubes or separation nozzles; 6. Bellows-sealed valves, manual or automated, shut-off or control, made of or protected by “materials resistant to corrosion by UF₆”, with a diameter of 40 mm or more; 7. Process systems for separating UF₆ from carrier gas (hydrogen or helium) to 1 ppm UF₆ content or less, including: <ol style="list-style-type: none"> a. Cryogenic heat exchangers and cryoseparators capable of temperatures of 153 K (-120°C) or less;

<i>Category Code</i>	<i>Item Description</i>
	<ul style="list-style-type: none"> b. Cryogenic refrigeration units capable of temperatures of 153 K (-120°C) or less; c. Separation nozzle or vortex tube units for the separation of UF₆ from carrier gas; d. UF₆ cold traps capable of freezing out UF₆; e. Equipment and components, specially designed or prepared for chemical exchange separation process, as follows: <ul style="list-style-type: none"> 1. Fast-exchange liquid-liquid pulse columns with stage residence time of 30 seconds or less and resistant to concentrated hydrochloric acid (e.g. made of or protected by suitable plastic materials such as fluorinated hydrocarbon polymers or glass); 2. Fast-exchange liquid-liquid centrifugal contactors with stage residence time of 30 seconds or less and resistant to concentrated hydrochloric acid (e.g. made of or protected by suitable plastic materials such as fluorinated hydrocarbon polymers or glass); 3. Electrochemical reduction cells resistant to concentrated hydrochloric acid solutions, for reduction of uranium from one valence state to another; 4. Electrochemical reduction cells feed equipment to take U⁺⁴ from the organic stream and, for those parts in contact with the process stream, made of or protected by suitable materials (e.g. glass, fluorocarbon polymers, polyphenyl sulphate, polyether sulfone and resin-impregnated graphite); 5. Feed preparation systems for producing high purity uranium chloride solution consisting of dissolution, solvent extraction and/or ion exchange equipment for purification and electrolytic cells for reducing the uranium U⁺⁶ or U⁺⁴ to U⁺³; 6. Uranium oxidation systems for oxidation of U⁺³ to U⁺⁴;

<i>Category Code</i>	<i>Item Description</i>
	<p>f. Equipment and components, specially designed or prepared for ion-exchange separation process, as follows:</p> <ol style="list-style-type: none"> 1. Fast reacting ion-exchange resins, pellicular or porous macro-reticulated resins in which the active chemical exchange groups are limited to a coating on the surface of an inactive porous support structure, and other composite structures in any suitable form, including particles or fibres, with diameters of 0.2 mm or less, resistant to concentrated hydrochloric acid and designed to have an exchange rate half-time of less than 10 seconds and capable of operating at temperatures in the range of 373 K (100°C) to 473 K (200°C); 2. Ion exchange columns (cylindrical) with a diameter greater than 1,000 mm, made of or protected by materials resistant to concentrated hydrochloric acid (e.g. titanium or fluorocarbon plastics) and capable of operating at temperatures in the range of 373 K (100°C) to 473 K (200°C) and pressures above 0.7 MPa; 3. Ion exchange reflux systems (chemical or electrochemical oxidation or reduction systems) for regeneration of the chemical reducing or oxidising agents used in ion exchange enrichment cascades; <p>g. Equipment and components, specially designed or prepared for laser-based separation processes using atomic vapour laser isotope separation, as follows:</p> <ol style="list-style-type: none"> 1. Uranium metal vaporisation systems designed to achieve a delivered power of 1 kW or more on the target for use in laser enrichment; 2. Liquid or vapour uranium metal handling systems specially designed or prepared for handling molten uranium, molten uranium alloys or uranium metal vapour for use in laser enrichment, and specially designed components therefor; <p><u><i>N.B.</i></u> <i>See also Category Code 2A225.</i></p>

<i>Category Code</i>	<i>Item Description</i>
	<ol style="list-style-type: none"> <li data-bbox="539 454 1273 622">3. Product and tails collector assemblies for uranium metal in liquid or solid form, made of or protected by materials resistant to the heat and corrosion of uranium metal vapour or liquid, such as yttria-coated graphite or tantalum; <li data-bbox="539 640 1273 768">4. Separator module housings (cylindrical or rectangular vessels) for containing the uranium metal vapour source, the electron beam gun and the product and tails collectors; <li data-bbox="539 786 1273 920">5. “Lasers” or “laser” systems specially designed or prepared for the separation of uranium isotopes with a spectrum frequency stabilisation for operation over extended periods of time; <p data-bbox="603 938 1129 1010"><i><u>N.B.</u></i> <i>See also Category Codes 6A005 and 6A205.</i></p> <ol style="list-style-type: none"> <li data-bbox="475 1028 1273 1126">h. Equipment and components, specially designed or prepared for laser-based separation processes using molecular laser isotope separation, as follows: <ol style="list-style-type: none"> <li data-bbox="539 1144 1273 1243">1. Supersonic expansion nozzles for cooling mixtures of UF₆ and carrier gas to 150 K (-123°C) or less and made from “materials resistant to corrosion by UF₆”; <li data-bbox="539 1261 1273 1429">2. Product or tails collector components or devices specially designed or prepared for collecting uranium material or uranium tails material following illumination with laser light, made of “materials resistant to corrosion by UF₆”; <li data-bbox="539 1447 1273 1545">3. Compressors made of or protected by “materials resistant to corrosion by UF₆”, and rotary shaft seals therefor; <li data-bbox="539 1563 1273 1597">4. Equipment for fluorinating UF₅ (solid) to UF₆ (gas); <li data-bbox="539 1615 1273 1798">5. Process systems for separating UF₆ from carrier gas (e.g. nitrogen, argon or other gas) including: <ol style="list-style-type: none"> <li data-bbox="624 1697 1273 1798">a. Cryogenic heat exchangers and cryoseparators capable of temperatures of 153 K (-120°C) or less;

<i>Category Code</i>	<i>Item Description</i>
	<p>b. Cryogenic refrigeration units capable of temperatures of 153 K (-120°C) or less;</p> <p>c. UF₆ cold traps capable of freezing out UF₆;</p> <p>6. “Lasers” or “laser” systems specially designed or prepared for the separation of uranium isotopes with a spectrum frequency stabilisation for operation over extended periods of time;</p> <p><u>N.B.</u> See also Category Codes 6A005 and 6A205.</p> <p>i. Equipment and components, specially designed or prepared for plasma separation process, as follows:</p> <ol style="list-style-type: none"> 1. Microwave power sources and antennae for producing or accelerating ions, with an output frequency greater than 30 GHz and mean power output greater than 50 kW; 2. Radio frequency ion excitation coils for frequencies of more than 100 kHz and capable of handling more than 40 kW mean power; 3. Uranium plasma generation systems; 4. Not used; 5. Product and tails collector assemblies for uranium metal in solid form, made of or protected by materials resistant to the heat and corrosion of uranium vapour such as yttria-coated graphite or tantalum; 6. Separator module housings (cylindrical) for containing the uranium plasma source, radio-frequency drive coil and the product and tails collectors and made of a suitable non-magnetic material (e.g. stainless steel); <p>j. Equipment and components, specially designed or prepared for electromagnetic separation process, as follows:</p> <ol style="list-style-type: none"> 1. Ion sources, single or multiple, consisting of a vapour source, ioniser, and beam accelerator made of suitable non-magnetic materials (e.g. graphite, stainless steel, or copper) and capable of providing a total ion beam current of 50 mA or greater;

<i>Category Code</i>	<i>Item Description</i>
	<ol style="list-style-type: none"> 2. Ion collector plates for collection of enriched or depleted uranium ion beams, consisting of two or more slits and pockets and made of suitable non-magnetic materials (e.g. graphite or stainless steel); 3. Vacuum housings for uranium electromagnetic separators made of non-magnetic materials (e.g. stainless steel) and designed to operate at pressures of 0.1 Pa or lower; 4. Magnet pole pieces with a diameter greater than 2 m; 5. High voltage power supplies for ion sources, having all of the following characteristics: <ol style="list-style-type: none"> a. Capable of continuous operation; b. Output voltage of 20,000 V or greater; c. Output current of 1 A or greater; <u>and</u> d. Voltage regulation of better than 0.01% over a period of 8 hours; <p><u>N.B.</u> See also Category Code 3A227.</p> 6. Magnet power supplies (high power, direct current) having all of the following characteristics: <ol style="list-style-type: none"> a. Capable of continuous operation with a current output of 500 A or greater at a voltage of 100 V or greater; <u>and</u> b. Current or voltage regulation better than 0.01% over a period of 8 hours. <p><u>N.B.</u> See also Category Code 3A226.</p>
0B002	<p>Specially designed or prepared auxiliary systems, equipment and components, as follows, for isotope separation plant specified in Category Code 0B001, made of or protected by “materials resistant to corrosion by UF₆”:</p> <ol style="list-style-type: none"> a. Feed autoclaves, ovens or systems used for passing UF₆ to the enrichment process;

<i>Category Code</i>	<i>Item Description</i>
	<ul style="list-style-type: none"> b. Desublimers or cold traps, used to remove UF₆ from the enrichment process for subsequent transfer upon heating; c. Product and tails stations for transferring UF₆ into containers; d. Liquefaction or solidification stations used to remove UF₆ from the enrichment process by compressing, cooling and converting UF₆ to a liquid or solid form; e. Piping systems and header systems specially designed or prepared for handling UF₆ within gaseous diffusion, centrifuge or aerodynamic cascades; f. Vacuum systems and pumps, as follows: <ul style="list-style-type: none"> 1. Vacuum manifolds, vacuum headers or vacuum pumps having a suction capacity of 5 m³/minute or more; 2. Vacuum pumps specially designed for use in UF₆-bearing atmospheres made of, or protected by “materials resistant to corrosion by UF₆”; 3. Vacuum systems consisting of vacuum manifolds, vacuum headers and vacuum pumps, and designed for service in UF₆-bearing atmospheres; g. UF₆ mass spectrometers/ion sources capable of taking on-line samples from UF₆ gas streams and having all of the following characteristics: <ul style="list-style-type: none"> 1. Capable of measuring ions of 320 atomic mass units or greater and having a resolution of better than 1 part in 320; 2. Have ion sources constructed of or protected by nickel, nickel-copper alloys with a nickel content of 60% or more by weight, or nickel-chrome alloys; 3. Have electron bombardment ionisation sources; <u>and</u> 4. Have a collector system suitable for isotopic analysis.
0B003	<p>Plant for the conversion of uranium and equipment specially designed or prepared therefor, as follows:</p> <ul style="list-style-type: none"> a. Systems for the conversion of uranium ore concentrates to UO₃;

<i>Category Code</i>	<i>Item Description</i>
0B004	<ul style="list-style-type: none"> b. Systems for the conversion of UO_3 to UF_6; c. Systems for the conversion of UO_3 to UO_2; d. Systems for the conversion of UO_2 to UF_4; e. Systems for the conversion of UF_4 to UF_6; f. Systems for the conversion of UF_4 to uranium metal; g. Systems for the conversion of UF_6 to UO_2; h. Systems for the conversion of UF_6 to UF_4; i. Systems for the conversion of UO_2 to UCl_4. <p>Plant for the production or concentration of heavy water, deuterium and deuterium compounds and specially designed or prepared equipment and components therefor, as follows:</p> <ul style="list-style-type: none"> a. Plant for the production of heavy water, deuterium or deuterium compounds, as follows: <ul style="list-style-type: none"> 1. Water-hydrogen sulphide exchange plants; 2. Ammonia-hydrogen exchange plants; b. Equipment and components, as follows: <ul style="list-style-type: none"> 1. Water-hydrogen sulphide exchange towers with diameters of 1.5 m or more, capable of operating at pressures greater than or equal to 2 MPa; 2. Single stage, low head (i.e. 0.2 MPa) centrifugal blowers or compressors for hydrogen sulphide gas circulation (i.e. gas containing more than 70% H_2S) with a throughput capacity greater than or equal to $56 \text{ m}^3/\text{second}$ when operating at pressures greater than or equal to 1.8 MPa suction and having seals designed for wet H_2S service; 3. Ammonia-hydrogen exchange towers greater than or equal to 35 m in height with diameters of 1.5 m to 2.5 m capable of operating at pressures greater than 15 MPa; 4. Tower internals, including stage contactors, and stage pumps, including those which are submersible, for heavy water production utilising the ammonia-hydrogen exchange process;

<i>Category Code</i>	<i>Item Description</i>
0B005	<p>5. Ammonia crackers with operating pressures greater than or equal to 3 MPa for heavy water production utilising the ammonia-hydrogen exchange process;</p> <p>6. Infrared absorption analysers capable of on-line hydrogen/deuterium ratio analysis where deuterium concentrations are equal to or greater than 90%;</p> <p>7. Catalytic burners for the conversion of enriched deuterium gas into heavy water utilising the ammonia-hydrogen exchange process;</p> <p>8. Complete heavy water upgrade systems, or columns therefor, for the upgrade of heavy water to reactor-grade deuterium concentration;</p> <p>9. Ammonia synthesis converters or synthesis units specially designed or prepared for heavy water production utilising the ammonia-hydrogen exchange process.</p> <p>Plant specially designed for the fabrication of “nuclear reactor” fuel elements and specially designed or prepared equipment therefor.</p> <p><u>Technical Note</u> <i>Specially designed or prepared equipment for the fabrication of “nuclear reactor” fuel elements includes equipment which:</i></p> <p>a. <i>Normally comes into direct contact with or directly processes or controls the production flow of nuclear materials;</i></p> <p>b. <i>Seals the nuclear materials within the cladding;</i></p> <p>c. <i>Checks the integrity of the cladding or the seal;</i></p> <p>d. <i>Checks the finish treatment of the sealed fuel; <u>or</u></i></p> <p>e. <i>Is used for assembling reactor elements.</i></p>

Category Code	Item Description
0B006	<p data-bbox="464 450 1262 555">Plant for the reprocessing of irradiated “nuclear reactor” fuel elements, and specially designed or prepared equipment and components therefor.</p> <p data-bbox="464 562 539 595"><u>Note</u></p> <p data-bbox="464 607 858 640"><i>Category Code 0B006 includes:</i></p> <ul style="list-style-type: none"> <li data-bbox="464 651 1262 824">a. <i>Plant for the reprocessing of irradiated “nuclear reactor” fuel elements including equipment and components which normally come into direct contact with and directly control the irradiated fuel and the major nuclear material and fission product processing streams;</i> <li data-bbox="464 835 1262 940">b. <i>Fuel element chopping or shredding machines, i.e. remotely operated equipment to cut, chop or shear irradiated “nuclear reactor” fuel assemblies, bundles or rods;</i> <li data-bbox="464 952 1262 1124">c. <i>Dissolvers, critically safe tanks (e.g. small diameter, annular or slab tanks) specially designed or prepared for the dissolution of irradiated “nuclear reactor” fuel, which are capable of withstanding hot, highly corrosive liquids, and which can be remotely loaded and maintained;</i> <li data-bbox="464 1135 1262 1348">d. <i>Solvent extractors, such as packed or pulsed columns, mixer settlers or centrifugal contactors, resistant to the corrosive effects of nitric acid and specially designed or prepared for use in a plant for the reprocessing of irradiated “natural uranium”, “depleted uranium” or “special fissile materials”;</i> <li data-bbox="464 1359 1262 1426">e. <i>Holding or storage vessels specially designed to be critically safe and resistant to the corrosive effects of nitric acid;</i> <p data-bbox="464 1438 724 1471"><u>Technical Note</u></p> <p data-bbox="464 1482 1251 1516"><i>Holding or storage vessels may have the following features:</i></p> <ul style="list-style-type: none"> <li data-bbox="528 1527 1262 1635">1. <i>Walls or internal structures with a boron equivalent (calculated for all constituent elements as defined in the note to Category Code 0C004) of at least two per cent;</i> <li data-bbox="528 1646 1262 1713">2. <i>A maximum diameter of 175 mm for cylindrical vessels;</i> <i>or</i> <li data-bbox="528 1724 1262 1805">3. <i>A maximum width of 75 mm for either a slab or annular vessel.</i>

<i>Category Code</i>	<i>Item Description</i>
	<p><i>f. Neutron measurement systems specially designed or prepared for integration and use with automated process control systems in a plant for the reprocessing of irradiated “natural uranium”, “depleted uranium” or “special fissile materials”.</i></p>
0B007	<p>Plant for the conversion of plutonium and equipment specially designed or prepared therefor, as follows:</p> <p>a. Systems for the conversion of plutonium nitrate to oxide;</p> <p>b. Systems for plutonium metal production.</p>
0C	Materials
0C001	<p>“Natural uranium” or “depleted uranium” or thorium in the form of metal, alloy, chemical compound or concentrate and any other material containing one or more of the foregoing.</p> <p><u>Note</u></p> <p>Category Code 0C001 does not include the following:</p> <p>a. <i>Four grammes or less of “natural uranium” or “depleted uranium” when contained in a sensing component in instruments;</i></p> <p>b. <i>“Depleted uranium” specially fabricated for the following civil non-nuclear applications:</i></p> <ol style="list-style-type: none"> <i>1. Shielding;</i> <i>2. Packaging;</i> <i>3. Ballasts having a mass not greater than 100 kg;</i> <i>4. Counter-weights having a mass not greater than 100 kg;</i> <p>c. <i>Alloys containing less than 5% thorium;</i></p> <p>d. <i>Ceramic products containing thorium, which have been manufactured for non-nuclear use.</i></p>

Category Code	Item Description
0C002	<p>“Special fissile materials”.</p> <p><u>Note</u> <i>Category Code 0C002 does not include four “effective grammes” or less when contained in a sensing component in instruments.</i></p>
0C003	<p>Deuterium, heavy water (deuterium oxide) and other compounds of deuterium, and mixtures and solutions containing deuterium, in which the isotopic ratio of deuterium to hydrogen exceeds 1:5,000.</p>
0C004	<p>Graphite having a purity level of better than 5 parts per million ‘boron equivalent’ and with a density greater than 1.5 g/cm³ for use in a “nuclear reactor”, in quantities exceeding 1 kg.</p> <p><u>N.B.</u> <i>See also Category Code 1C107.</i></p> <p><u>Note 1</u> <i>For the purpose of Category Code 0C004, whether or not the exports of graphite meeting the above specifications are for “nuclear reactor” use is determined, at or before the time of export, by the competent authorities of the country in which the exporter is established.</i></p> <p><u>Note 2</u> <i>In Category Code 0C004, ‘boron equivalent’ (BE) means the sum of BE_Z for impurities (excluding BE_{carbon} since carbon is not considered an impurity) including boron, where:</i></p> <p><i>BE_Z (ppm) = CF × concentration of element Z in ppm;</i></p> <p><i>where CF is the conversion factor = $\frac{\sigma_Z \times A_B}{\sigma_B \times A_Z}$</i></p> <p><i>and σ_B and σ_Z are the thermal neutron capture cross sections (in barns) for naturally occurring boron and element Z respectively; and A_B and A_Z are the atomic masses of naturally occurring boron and element Z respectively.</i></p>

<i>Category Code</i>	<i>Item Description</i>
0C005	Specially prepared compounds or powders for the manufacture of gaseous diffusion barriers, resistant to corrosion by UF ₆ (e.g. nickel or alloy containing 60% or more nickel by weight, aluminium oxide and fully fluorinated hydrocarbon polymers), having a purity of 99.9% by weight or more and a particle size less than 10 µm measured by American Society for Testing and Materials (ASTM) B330 standard and a high degree of particle size uniformity.
0D	Software
0D001	“Software” specially designed or modified for the “development”, “production” or “use” of goods specified in this Category.
0E	Technology
0E001	“Technology” (according to the Nuclear Technology Note) for the “development”, “production” or “use” of goods specified in this Category.

<i>Category Code</i>	<i>Item Description</i>
CATEGORY 1 — SPECIAL MATERIALS AND RELATED EQUIPMENT	
1A	Systems, Equipment and Components
1A001	<p>Components made from fluorinated compounds, as follows:</p> <ol style="list-style-type: none"> a. Seals, gaskets, sealants or fuel bladders, specially designed for “aircraft” or aerospace use, made from more than 50% by weight of any of the materials specified in Category Code 1C009.b. or 1C009.c.; b. Not used; c. Not used.
1A002	<p>“Composite” structures or laminates, having any of the following characteristics:</p> <p><u><i>N.B.</i></u></p> <p><i>See also Category Codes 1A202, 9A010 and 9A110.</i></p> <ol style="list-style-type: none"> a. Consisting of an organic “matrix” and materials specified in Category Code 1C010.c., 1C010.d. or 1C010.e.; <u>or</u> b. Consisting of a metal or carbon “matrix”, and any of the following: <ol style="list-style-type: none"> 1. Carbon “fibrous or filamentary materials” having all of the following characteristics: <ol style="list-style-type: none"> a. A “specific modulus” exceeding 10.15×10^6 m; <u>and</u> b. A “specific tensile strength” exceeding 17.7×10^4 m; <u>or</u> 2. Materials specified in Category Code 1C010.c. <p><u><i>Note 1</i></u></p> <p><i>Category Code 1A002 does not include “composite” structures or laminates made from epoxy resin impregnated carbon “fibrous or filamentary materials” for the repair of “civil aircraft” structures or laminates, having all of the following characteristics:</i></p> <ol style="list-style-type: none"> a. <i>An area not exceeding 1 m²;</i> b. <i>A length not exceeding 2.5 m; <u>and</u></i>

Category Code	Item Description
	<p>c. A width exceeding 15 mm.</p> <p><u>Note 2</u> Category Code 1A002 does not include semi-finished items, specially designed for purely civilian applications, as follows:</p> <p>a. Sporting goods;</p> <p>b. Automotive industry;</p> <p>c. Machine tool industry;</p> <p>d. Medical applications.</p> <p><u>Note 3</u> Category Code 1A002.b.1. does not include semi-finished items containing a maximum of two dimensions of interwoven filaments and specially designed for applications, as follows:</p> <p>a. Metal heat-treatment furnaces for tempering metals;</p> <p>b. Silicon boule production equipment.</p> <p><u>Note 4</u> Category Code 1A002 does not include finished items specially designed for a specific application.</p>
1A003	<p>Manufactures of non-“fusible” aromatic polyimides in film, sheet, tape or ribbon form having any of the following characteristics:</p> <p>a. A thickness exceeding 0.254 mm; <u>or</u></p> <p>b. Coated or laminated with carbon, graphite, metals or magnetic substances.</p> <p><u>Note</u> Category Code 1A003 does not include manufactures when coated or laminated with copper and designed for the production of electronic printed circuit boards.</p> <p><u>N.B.</u> For “fusible” aromatic polyimides in any form, see Category Code 1C008.a.3.</p>

<i>Category Code</i>	<i>Item Description</i>
1A004	<p>Protective and detection equipment and components not specially designed for military use, as follows:</p> <p><u>N.B.</u> <i>See also Division 2 of Part 1 of this Schedule, and Category Codes 2B351 and 2B352.</i></p> <p>a. Full face masks, filter canisters and decontamination equipment therefor, designed or modified for defence against any of the following, and specially designed components therefor:</p> <p><u>Note</u> <i>Category Code 1A004.a. includes Powered Air Purifying Respirators (PAPR) that are designed or modified for defence against agents or materials, listed in Category Code 1A004.a.</i></p> <p><u>Technical Note</u> <i>For the purpose of Category Code 1A004.a.:</i></p> <ol style="list-style-type: none"> 1. Full face masks are also known as gas masks. 2. Filter canisters include filter cartridges. <ol style="list-style-type: none"> 1. 'Biological agents'; 2. Radioactive materials "adapted for use in war"; 3. Chemical warfare (CW) agents; <u>or</u> 4. "Riot control agents", including: <ol style="list-style-type: none"> a. α-Bromobenzeneacetonitrile, (Bromobenzyl cyanide) (CA) (5798-79-8); b. [(2-chlorophenyl) methylene] propanedinitrile, (o-Chlorobenzylidenemalononitrile) (CS) (2698-41-1); c. 2-Chloro-1-phenylethanone, Phenylacetyl chloride (ω-chloroacetophenone) (CN) (532-27-4); d. Dibenz-(b,f)-1,4-oxazepine (CR) (257-07-8); e. 10-Chloro-5,10-dihydrophenarsazine, (Phenarsazine chloride), (Adamsite), (DM) (578-94-9);

<i>Category Code</i>	<i>Item Description</i>
	<p>f. N-Nonanoylmorpholine, (MPA) (5299-64-9);</p> <p>b. Protective suits, gloves and shoes, specially designed or modified for defence against any of the following:</p> <ol style="list-style-type: none"> 1. 'Biological agents'; 2. Radioactive materials "adapted for use in war"; <u>or</u> 3. Chemical warfare (CW) agents; <p>c. Detection systems, specially designed or modified for detection or identification of any of the following, and specially designed components therefor:</p> <ol style="list-style-type: none"> 1. 'Biological agents'; 2. Radioactive materials "adapted for use in war"; <u>or</u> 3. Chemical warfare (CW) agents; <p>d. Electronic equipment designed for automatically detecting or identifying the presence of "explosives" residues and utilising 'trace detection' techniques (e.g. surface acoustic wave, ion mobility spectrometry, differential mobility spectrometry, mass spectrometry).</p> <p><u>Technical Note</u> <i>'Trace detection' is defined as the capability to detect less than 1 ppm vapour, or 1 mg solid or liquid.</i></p> <p><u>Note 1</u> <i>Category Code 1A004.d. does not include equipment specially designed for laboratory use.</i></p> <p><u>Note 2</u> <i>Category Code 1A004.d. does not include non-contact walk-through security portals.</i></p> <p><u>Note</u> <i>Category Code 1A004 does not include:</i></p> <ol style="list-style-type: none"> a. <i>Personal radiation monitoring dosimeters;</i> b. <i>Occupational health or safety equipment limited by design or function to protect against hazards specific to residential safety or civil industries, including:</i> <ol style="list-style-type: none"> 1. <i>Mining;</i>

Category Code	Item Description
	<ol style="list-style-type: none"> 2. Quarrying; 3. Agriculture; 4. Pharmaceutical; 5. Medical; 6. Veterinary; 7. Environmental; 8. Waste management; 9. Food industry. <p><u>Technical Notes</u></p> <ol style="list-style-type: none"> 1. Category Code 1A004 includes equipment and components that have been identified, successfully tested to national standards or otherwise proven effective, for the detection of or defence against radioactive materials “adapted for use in war”, ‘biological agents’, chemical warfare agents, ‘simulants’ or “riot control agents”, even if such equipment or components are used in civil industries such as mining, quarrying, agriculture, pharmaceuticals, medical, veterinary, environmental, waste management, or the food industry. 2. ‘Simulant’ is a substance or material that is used in place of toxic agent (chemical or biological) in training, research, testing or evaluation. 3. For the purposes of Category Code 1A004, ‘biological agents’ are pathogens or toxins, selected or modified (such as by altering the purity, shelf life, virulence, dissemination characteristics, or resistance to UV radiation) to produce casualties in humans or animals, degrade equipment or damage crops or the environment.
1A005	<p>Body armour and components therefor, as follows:</p> <p><u>N.B.</u></p> <p>See also Division 2 of Part 1 of this Schedule.</p> <ol style="list-style-type: none"> a. Soft body armour not manufactured to military standards or specifications, or to their equivalents, and specially designed components therefor;

<i>Category Code</i>	<i>Item Description</i>
	<p>b. Hard body armour plates providing ballistic protection equal to or less than level IIIA (NIJ 0101.06, July 2008) or national equivalents.</p> <p><u>N.B.</u> For “fibrous or filamentary materials” used in the manufacture of body armour, see Category Code 1C010.</p> <p><u>Note 1</u> Category Code 1A005 does not include body armour when accompanying its user for the user’s own personal protection.</p> <p><u>Note 2</u> Category Code 1A005 does not include body armour designed to provide frontal protection only from both fragment and blast from non-military explosive devices.</p> <p><u>Note 3</u> Category Code 1A005 does not include body armour designed to provide protection only from knife, spike, needle or blunt trauma.</p>
1A006	<p>Equipment, specially designed or modified for the disposal of improvised explosive devices, as follows, and specially designed components and accessories therefor:</p> <p><u>N.B.</u> See also Division 2 of Part 1 of this Schedule.</p> <p>a. Remotely operated vehicles;</p> <p>b. ‘Disruptors’.</p> <p><u>Technical Note</u> ‘Disruptors’ are devices specially designed for the purpose of preventing the operation of an explosive device by projecting a liquid, solid or frangible projectile.</p> <p><u>Note</u> Category Code 1A006 does not include equipment when accompanying its operator.</p>

<i>Category Code</i>	<i>Item Description</i>
1A007	<p>Equipment and devices, specially designed to initiate charges and devices containing “energetic materials”, by electrical means, as follows:</p> <p><u><i>N.B.</i></u></p> <p><i>See also Division 2 of Part 1 of this Schedule, and Category Codes 3A229 and 3A232.</i></p> <ol style="list-style-type: none"> a. Explosive detonator firing sets designed to drive explosive detonators specified in Category Code 1A007.b.; b. Electrically driven explosive detonators as follows: <ol style="list-style-type: none"> 1. Exploding bridge (EB); 2. Exploding bridge wire (EBW); 3. Slapper; 4. Exploding foil initiators (EFI). <p><u><i>Technical Notes</i></u></p> <ol style="list-style-type: none"> 1. <i>The word initiator or igniter is sometimes used in place of the word detonator.</i> 2. <i>For the purpose of Category Code 1A007.b., the detonators of concern all utilise a small electrical conductor (bridge, bridge wire, or foil) that explosively vaporises when a fast, high-current electrical pulse is passed through it. In non-slapper types, the exploding conductor starts a chemical detonation in a contacting high explosive material such as PETN (pentaerythritoltetranitrate). In slapper detonators, the explosive vaporisation of the electrical conductor drives a flyer or slapper across a gap, and the impact of the slapper on an explosive starts a chemical detonation. The slapper in some designs is driven by magnetic force. The term exploding foil detonator may refer to either an EB or a slapper-type detonator.</i>
1A008	<p>Charges, devices and components, as follows:</p> <ol style="list-style-type: none"> a. ‘Shaped charges’ having all of the following characteristics: <ol style="list-style-type: none"> 1. Net Explosive Quantity (NEQ) greater than 90 g; <u>and</u> 2. Outer casing diameter equal to or greater than 75 mm;

<i>Category Code</i>	<i>Item Description</i>
	<p>b. Linear shaped cutting charges having all of the following characteristics, and specially designed components therefor:</p> <ol style="list-style-type: none"> 1. An explosive load greater than 40 g/m; <u>and</u> 2. A width of 10 mm or more; <p>c. Detonating cord with explosive core load greater than 64 g/m;</p> <p>d. Cutters, other than those specified in Category Code 1A008.b., and severing tools, having a Net Explosive Quantity (NEQ) greater than 3.5 kg.</p> <p><u>Technical Note</u> <i>'Shaped charges' are explosive charges shaped to focus the effects of the explosive blast.</i></p>
1A102	Resaturated pyrolised carbon-carbon components designed for space launch vehicles specified in Category Code 9A004 or sounding rockets specified in Category Code 9A104.
1A202	<p>Composite structures, other than those specified in Category Code 1A002, in the form of tubes and having both of the following characteristics:</p> <p><u>N.B.</u> <i>See also Category Codes 9A010 and 9A110.</i></p> <ol style="list-style-type: none"> a. An inside diameter of between 75 mm and 400 mm; <u>and</u> b. Made with any of the "fibrous or filamentary materials" specified in Category Code 1C010.a. or 1C010.b. or 1C210.a. or with carbon prepreg materials specified in Category Code 1C210.c.
1A225	Platinised catalysts specially designed or prepared for promoting the hydrogen isotope exchange reaction between hydrogen and water for the recovery of tritium from heavy water or for the production of heavy water.

<i>Category Code</i>	<i>Item Description</i>
1A226	<p>Specialised packings which may be used in separating heavy water from ordinary water, having both of the following characteristics:</p> <ol style="list-style-type: none"> a. Made of phosphor bronze mesh chemically treated to improve wettability; <u>and</u> b. Designed to be used in vacuum distillation towers.
1A227	<p>High-density (lead glass or other) radiation shielding windows, having all of the following characteristics, and specially designed frames therefor:</p> <ol style="list-style-type: none"> a. A 'cold area' greater than 0.09 m²; b. A density greater than 3 g/cm³; <u>and</u> c. A thickness of 100 mm or greater. <p><i>Technical Note</i> <i>In Category Code 1A227, 'cold area' means the viewing area of the window exposed to the lowest level of radiation in the design application.</i></p>
1B	Test, Inspection and Production Equipment
1B001	<p>Equipment for the production or inspection of "composite" structures or laminates specified in Category Code 1A002 or "fibrous or filamentary materials" specified in Category Code 1C010, as follows, and specially designed components and accessories therefor:</p> <p><u>N.B.</u> <i>See also Category Codes 1B101 and 1B201.</i></p> <ol style="list-style-type: none"> a. Filament winding machines, of which the motions for positioning, wrapping and winding fibres are coordinated and programmed in three or more 'primary servo positioning' axes, specially designed for the manufacture of "composite" structures or laminates, from "fibrous or filamentary materials";

<i>Category Code</i>	<i>Item Description</i>
	<p>b. 'Tape-laying machines', of which the motions for positioning and laying tape are coordinated and programmed in five or more 'primary servo positioning' axes, specially designed for the manufacture of "composite" airframe or 'missile' structures;</p> <p><i>Note</i> In Category Code 1B001.b., 'missile' means complete rocket systems and unmanned aerial vehicle systems.</p> <p><i>Technical Note</i> For the purpose of Category Code 1B001.b., 'tape-laying machines' have the ability to lay one or more 'filament bands' limited to widths greater than 25 mm and less than or equal to 305 mm, and to cut and restart individual 'filament band' courses during the laying process.</p> <p>c. Multidirectional, multidimensional weaving machines or interlacing machines, including adapters and modification kits, specially designed or modified for weaving, interlacing or braiding fibres, for "composite" structures;</p> <p><i>Technical Note</i> For the purpose of Category Code 1B001.c., the technique of interlacing includes knitting.</p> <p>d. Equipment specially designed or adapted for the production of reinforcement fibres, as follows:</p> <ol style="list-style-type: none"> 1. Equipment for converting polymeric fibres (e.g. polyacrylonitrile, rayon, pitch or polycarbosilane) into carbon fibres or silicon carbide fibres, including special equipment to strain the fibre during heating; 2. Equipment for the chemical vapour deposition of elements or compounds, on heated filamentary substrates, to manufacture silicon carbide fibres; 3. Equipment for the wet-spinning of refractory ceramics (e.g. aluminium oxide); 4. Equipment for converting aluminium containing precursor fibres into alumina fibres by heat treatment; <p>e. Equipment for producing prepregs specified in Category Code 1C010.e. by the hot melt method;</p>

<i>Category Code</i>	<i>Item Description</i>
	<p>f. Non-destructive inspection equipment specially designed for “composite” materials, as follows:</p> <ol style="list-style-type: none"> 1. X-ray tomography systems for three dimensional defect inspection; 2. Numerically controlled ultrasonic testing machines of which the motions for positioning transmitters or receivers are simultaneously coordinated and programmed in four or more axes to follow the three dimensional contours of the component under inspection; <p>g. ‘Tow-placement machines’, of which the motions for positioning and laying tows are coordinated and programmed in two or more ‘primary servo positioning’ axes, specially designed for the manufacture of “composite” airframe or ‘missile’ structures.</p> <p><i>Technical Note</i></p> <p><i>For the purpose of Category Code 1B001.g., ‘tow-placement machines’ have the ability to place one or more ‘filament bands’ having widths less than or equal to 25 mm, and to cut and restart individual ‘filament band’ courses during the placement process.</i></p> <p><i>Technical Notes</i></p> <ol style="list-style-type: none"> 1. <i>For the purpose of Category Code 1B001, ‘primary servo positioning’ axes control, under computer program direction, the position of the end-effector (i.e. head) in space relative to the workpiece at the correct orientation and direction to achieve the desired process.</i> 2. <i>For the purpose of Category Code 1B001, a ‘filament band’ is a single continuous width of fully or partially resin-impregnated tape, tow or fibre.</i>
1B002	<p>Equipment for producing metal alloys, metal alloy powder or alloyed materials, specially designed to avoid contamination and specially designed for use in one of the processes specified in Category Code 1C002.c.2.</p> <p><i>N.B.</i></p> <p><i>See also Category Code 1B102.</i></p>

<i>Category Code</i>	<i>Item Description</i>
1B003	<p>Tools, dies, moulds or fixtures, for “superplastic forming” or “diffusion bonding” titanium, aluminium or their alloys, specially designed for the manufacture of any of the following:</p> <ol style="list-style-type: none"> a. Airframe or aerospace structures; b. “Aircraft” or aerospace engines; <u>or</u> c. Specially designed components for structures specified in Category Code 1B003.a. or for engines specified in Category Code 1B003.b.
1B101	<p>Equipment, other than that specified in Category Code 1B001, for the “production” of structural composites as follows; and specially designed components and accessories therefor:</p> <p><u>N.B.</u> See also Category Code 1B201.</p> <p><u>Note</u> <i>Components and accessories specified in Category Code 1B101 include moulds, mandrels, dies, fixtures and tooling for the preform pressing, curing, casting, sintering or bonding of composite structures, laminates and manufactures thereof.</i></p> <ol style="list-style-type: none"> a. Filament winding machines or fibre placement machines, of which the motions for positioning, wrapping and winding fibres can be coordinated and programmed in three or more axes, designed to fabricate composite structures or laminates from fibrous or filamentary materials, and coordinating and programming controls; b. Tape-laying machines of which the motions for positioning and laying tape and sheets can be coordinated and programmed in two or more axes, designed for the manufacture of composite airframe and “missile” structures; c. Equipment designed or modified for the “production” of “fibrous or filamentary materials” as follows: <ol style="list-style-type: none"> 1. Equipment for converting polymeric fibres (e.g. polyacrylonitrile, rayon or polycarbosilane) including special provision to strain the fibre during heating; 2. Equipment for the vapour deposition of elements or compounds on heated filament substrates;

<i>Category Code</i>	<i>Item Description</i>
	<p>3. Equipment for the wet-spinning of refractory ceramics (e.g. aluminium oxide);</p> <p>d. Equipment designed or modified for special fibre surface treatment or for producing prepregs and preforms specified in Category Code 9C110.</p> <p><i>Note</i> Category Code 1B101.d. includes rollers, tension stretchers, coating equipment, cutting equipment and clicker dies.</p>
1B102	<p>Metal powder “production equipment”, other than that specified in Category Code 1B002, and components, as follows:</p> <p><i>N.B.</i> See also Category Code 1B115.b.</p> <p>a. Metal powder “production equipment” usable for the “production”, in a controlled environment, of spherical, spheroidal or atomised materials specified in Category Code 1C011.a., 1C011.b., 1C111.a.1., 1C111.a.2. or in Division 2 of Part 1 of this Schedule;</p> <p>b. Specially designed components for “production equipment” specified in Category Code 1B002 or 1B102.a.</p> <p><i>Note</i> Category Code 1B102 includes:</p> <p>a. Plasma generators (high frequency arc-jet) usable for obtaining sputtered or spherical metallic powders with organisation of the process in an argon-water environment;</p> <p>b. Electrobust equipment usable for obtaining sputtered or spherical metallic powders with organisation of the process in an argon-water environment;</p> <p>c. Equipment usable for the “production” of spherical aluminium powders by powdering a melt in an inert medium (e.g. nitrogen).</p>

<i>Category Code</i>	<i>Item Description</i>
1B115	<p>Equipment, other than that specified in Category Code 1B002 or 1B102, for the production of propellant and propellant constituents, as follows, and specially designed components therefor:</p> <ol style="list-style-type: none"> <li data-bbox="464 568 1272 696">a. “Production equipment” for the “production”, handling or acceptance testing of liquid propellants or propellant constituents specified in Category Code 1C011.a., 1C011.b., 1C111 or in Division 2 of Part 1 of this Schedule; <li data-bbox="464 719 1272 882">b. “Production equipment” for the “production”, handling, mixing, curing, casting, pressing, machining, extruding or acceptance testing of solid propellants or propellant constituents specified in Category Code 1C011.a., 1C011.b., 1C111 or in Division 2 of Part 1 of this Schedule. <p><i>Note</i> <i>Category Code 1B115.b. does not include batch mixers, continuous mixers or fluid energy mills. For batch mixers, continuous mixers and fluid energy mills, see Category Codes 1B117, 1B118 and 1B119.</i></p> <p><i>Note 1</i> <i>For equipment specially designed for the production of military goods, see Division 2 of Part 1 of this Schedule.</i></p> <p><i>Note 2</i> <i>Category Code 1B115 does not include equipment for the “production”, handling and acceptance testing of boron carbide.</i></p>
1B116	<p>Specially designed nozzles for producing pyrolitically derived materials formed on a mould, mandrel or other substrate from precursor gases which decompose in the 1,573 K (1,300°C) to 3,173 K (2,900°C) temperature range at pressures of 130 Pa to 20 kPa.</p>
1B117	<p>Batch mixers with provision for mixing under vacuum in the range of zero to 13.326 kPa and with temperature control capability of the mixing chamber and having all of the following characteristics, and specially designed components therefor:</p> <ol style="list-style-type: none"> <li data-bbox="464 1778 1272 1812">a. A total volumetric capacity of 110 litres or more; <u>and</u> <li data-bbox="464 1823 1272 1856">b. At least one ‘mixing/kneading shaft’ mounted off centre.

<i>Category Code</i>	<i>Item Description</i>
	<p><i>Note</i> <i>In Category Code 1B117.b., 'mixing/kneading shaft' does not refer to deagglomerators or knife-spindles.</i></p>
1B118	<p>Continuous mixers with provision for mixing under vacuum in the range of zero to 13.326 kPa and with a temperature control capability of the mixing chamber having any of the following, and specially designed components therefor:</p> <ol style="list-style-type: none"> a. Two or more mixing/kneading shafts; <u>or</u> b. A single rotating shaft which oscillates and having kneading teeth/pins on the shaft as well as inside the casing of the mixing chamber.
1B119	<p>Fluid energy mills usable for grinding or milling substances specified in Category Code 1C011.a., 1C011.b., 1C111 or in Division 2 of Part 1 of this Schedule, and specially designed components therefor.</p>
1B201	<p>Filament winding machines, other than those specified in Category Code 1B001 or 1B101, and related equipment, as follows:</p> <ol style="list-style-type: none"> a. Filament winding machines having all of the following characteristics: <ol style="list-style-type: none"> 1. Having motions for positioning, wrapping, and winding fibres coordinated and programmed in two or more axes; 2. Specially designed to fabricate composite structures or laminates from "fibrous or filamentary materials"; <u>and</u> 3. Capable of winding cylindrical tubes with an internal diameter between 75 mm and 650 mm and lengths of 300 mm or greater; b. Coordinating and programming controls for the filament winding machines specified in Category Code 1B201.a.; c. Precision mandrels for the filament winding machines specified in Category Code 1B201.a.

<i>Category Code</i>	<i>Item Description</i>
1B225	Electrolytic cells for fluorine production with an output capacity greater than 250 g of fluorine per hour.
1B226	Electromagnetic isotope separators designed for, or equipped with, single or multiple ion sources capable of providing a total ion beam current of 50 mA or greater. <i>Note</i> <i>Category Code 1B226 includes separators:</i> a. Capable of enriching stable isotopes; b. With the ion sources and collectors both in the magnetic field and those configurations in which they are external to the field.
1B228	Hydrogen-cryogenic distillation columns having all of the following characteristics: a. Designed for operation with internal temperatures of 35 K (-238°C) or less; b. Designed for operation at an internal pressure of 0.5 MPa to 5 MPa; c. Constructed of either: 1. Stainless steel of the 300 series with low sulphur content and with an austenitic ASTM (or equivalent standard) grain size number of 5 or greater; <u>or</u> 2. Equivalent materials which are both cryogenic and H ₂ -compatible; <u>and</u> d. With internal diameters of 30 cm or greater and ‘effective lengths’ of 4 m or greater. <i>Technical Note</i> <i>In Category Code 1B228, ‘effective length’ means the active height of packing material in a packed-type column, or the active height of internal contactor plates in a plate-type column.</i>

Category Code	Item Description
1B229	<p>Water-hydrogen sulphide exchange tray columns and 'internal contactors', as follows:</p> <p><u>N.B.</u></p> <p><i>For columns which are specially designed or prepared for the production of heavy water, see Category Code 0B004.</i></p> <p>a. Water-hydrogen sulphide exchange tray columns, having all of the following characteristics:</p> <ol style="list-style-type: none"> 1. Can operate at pressures of 2 MPa or greater; 2. Constructed of carbon steel having an austenitic ASTM (or equivalent standard) grain size number of 5 or greater; <u>and</u> 3. With a diameter of 1.8 m or greater; <p>b. 'Internal contactors' for the water-hydrogen sulphide exchange tray columns specified in Category Code 1B229.a.</p> <p><u>Technical Note</u></p> <p><i>'Internal contactors' of the columns are segmented trays which have an effective assembled diameter of 1.8 m or greater, are designed to facilitate countercurrent contacting and are constructed of stainless steels with a carbon content of 0.03% or less. These may be sieve trays, valve trays, bubble cap trays, or turbogrid trays.</i></p>
1B230	<p>Pumps capable of circulating solutions of concentrated or dilute potassium amide catalyst in liquid ammonia (KNH_2/NH_3), having all of the following characteristics:</p> <p>a. Airtight (i.e. hermetically sealed);</p> <p>b. A capacity greater than 8.5 m³/h; <u>and</u></p> <p>c. Either of the following characteristics:</p> <ol style="list-style-type: none"> 1. For concentrated potassium amide solutions (1% or greater), an operating pressure of 1.5 MPa to 60 MPa; <u>or</u> 2. For dilute potassium amide solutions (less than 1%), an operating pressure of 20 MPa to 60 MPa.

<i>Category Code</i>	<i>Item Description</i>
1B231	<p>Tritium facilities or plants, and equipment therefor, as follows:</p> <ol style="list-style-type: none"> a. Facilities or plants for the production, recovery, extraction, concentration, or handling of tritium; b. Equipment for tritium facilities or plants, as follows: <ol style="list-style-type: none"> 1. Hydrogen or helium refrigeration units capable of cooling to 23 K (-250°C) or less, with heat removal capacity greater than 150 W; 2. Hydrogen isotope storage or purification systems using metal hydrides as the storage or purification medium.
1B232	<p>Turboexpanders or turboexpander-compressor sets having both of the following characteristics:</p> <ol style="list-style-type: none"> a. Designed for operation with an outlet temperature of 35 K (-238°C) or less; <u>and</u> b. Designed for a throughput of hydrogen gas of 1,000 kg/h or greater.
1B233	<p>Lithium isotope separation facilities or plants, and systems and equipment therefor, as follows:</p> <ol style="list-style-type: none"> a. Facilities or plants for the separation of lithium isotopes; b. Equipment for the separation of lithium isotopes based on the lithium-mercury amalgam process, as follows: <ol style="list-style-type: none"> 1. Packed liquid-liquid exchange columns specially designed for lithium amalgams; 2. Mercury or lithium amalgam pumps; 3. Lithium amalgam electrolysis cells; 4. Evaporators for concentrated lithium hydroxide solution; c. Ion exchange systems specially designed for lithium isotope separation, and specially designed components therefor;

<i>Category Code</i>	<i>Item Description</i>
1B234	<p>d. Chemical exchange systems (employing crown ethers, cryptands, or lariat ethers), specially designed for lithium isotope separation, and specially designed components therefor.</p> <p>High explosive containment vessels, chambers, containers and other similar containment devices designed for the testing of high explosives or explosive devices and having both of the following characteristics:</p> <p><u>N.B.</u> <i>See also Division 2 of Part 1 of this Schedule.</i></p> <p>a. Designed to fully contain an explosion equivalent to 2 kg of TNT or greater; <u>and</u></p> <p>b. Having design elements or features enabling real time or delayed transfer of diagnostic or measurement information.</p>
1C	<p>Materials</p> <p><u>Technical Note</u></p> <p><i>Unless provision to the contrary is made, the words ‘metals’ and ‘alloys’ in Category Codes 1C001 to 1C012 cover crude and semi-fabricated forms, as follows:</i></p> <p><i>Crude forms, in relation to materials, means anodes, balls, bars (including notched bars and wire bars), billets, blocks, blooms, brickets, cakes, cathodes, crystals, cubes, dice, grains, granules, ingots, lumps, pellets, pigs, powder, rondelles, shot, slabs, slugs, sponge, sticks;</i></p> <p><i>Semi-fabricated forms, in relation to materials, means any of the following:</i></p> <p>a. <i>Wrought or worked materials fabricated by rolling, drawing, extruding, forging, impact extruding, pressing, graining, atomising, and grinding, i.e.: angles, channels, circles, discs, dust, flakes, foils and leaf, forging, plate, powder, pressings and stampings, ribbons, rings, rods (including bare welding rods, wire rods, and rolled wire), sections, shapes, sheets, strip, pipe and tubes (including tube rounds, squares, and hollows), drawn or extruded wire;</i></p>

Category Code	Item Description
1C001	<p data-bbox="475 454 1264 555"><i>b. Cast material produced by casting in sand, die, metal, plaster or other types of moulds, including high pressure castings, sintered forms, and forms made by powder metallurgy;</i></p> <p data-bbox="475 568 1066 602"><i>whether or not coated, plated, drilled or punched.</i></p> <p data-bbox="475 618 1264 719"><i>Category 1C includes non-listed forms of those materials which are purportedly finished products but are in reality crude forms or semi-fabricated forms.</i></p> <p data-bbox="475 786 1264 887">Materials specially designed for use as absorbers of electromagnetic waves, or intrinsically conductive polymers, as follows:</p> <p data-bbox="475 902 531 936"><u><i>N.B.</i></u></p> <p data-bbox="475 943 855 976"><i>See also Category Code 1C101.</i></p> <p data-bbox="475 992 1264 1059"><i>a. Materials for absorbing frequencies exceeding 2×10^8 Hz but less than 3×10^{12} Hz;</i></p> <p data-bbox="539 1077 624 1111"><u><i>Note 1</i></u></p> <p data-bbox="539 1120 1046 1153"><i>Category Code 1C001.a. does not include:</i></p> <p data-bbox="539 1169 1264 1270"><i>a. Hair type absorbers, constructed of natural or synthetic fibres, with non-magnetic loading to provide absorption;</i></p> <p data-bbox="539 1285 1264 1386"><i>b. Absorbers having no magnetic loss and whose incident surface is non-planar in shape, including pyramids, cones, wedges and convoluted surfaces;</i></p> <p data-bbox="539 1402 1264 1469"><i>c. Planar absorbers, having all of the following characteristics:</i></p> <p data-bbox="624 1485 1070 1518"><i>1. Made from any of the following:</i></p> <p data-bbox="687 1534 1264 1805"><i>a. Plastic foam materials (flexible or non-flexible) with carbon-loading, or organic materials, including binders, providing more than 5% echo compared with metal over a bandwidth exceeding $\pm 15\%$ of the centre frequency of the incident energy, and not capable of withstanding temperatures exceeding 450 K (177°C); <u>or</u></i></p>

Category Code	Item Description
	<p data-bbox="687 454 1272 651">b. Ceramic materials providing more than 20% echo compared with metal over a bandwidth exceeding $\pm 15\%$ of the centre frequency of the incident energy, and not capable of withstanding temperatures exceeding 800 K (527°C);</p> <p data-bbox="687 674 871 703"><u>Technical Note</u></p> <p data-bbox="687 714 1272 875">Absorption test samples for Category Code 1C001.a. Note 1.c.1. should be a square at least 5 wavelengths of the centre frequency on a side and positioned in the far field of the radiating element.</p> <p data-bbox="624 898 1219 927">2. Tensile strength less than 7×10^6 N/m²; <u>and</u></p> <p data-bbox="624 949 1246 978">3. Compressive strength less than 14×10^6 N/m²;</p> <p data-bbox="539 1001 1272 1061">d. Planar absorbers made of sintered ferrite, having all of the following characteristics:</p> <p data-bbox="624 1084 1131 1113">1. A specific gravity exceeding 4.4; <u>and</u></p> <p data-bbox="624 1135 1272 1196">2. A maximum operating temperature of 548 K (275°C).</p> <p data-bbox="539 1218 624 1247"><u>Note 2</u></p> <p data-bbox="539 1258 1272 1352">Nothing in Note 1 to Category Code 1C001.a. releases magnetic materials to provide absorption when contained in paint.</p> <p data-bbox="475 1375 1272 1435">b. Materials for absorbing frequencies exceeding 1.5×10^{14} Hz but less than 3.7×10^{14} Hz and not transparent to visible light;</p> <p data-bbox="539 1458 600 1487"><u>Note</u></p> <p data-bbox="539 1498 1272 1592">Category Code 1C001.b. does not include materials, specially designed or formulated for any of the following applications:</p> <p data-bbox="539 1615 1003 1644">a. “Laser” marking of polymers; <u>or</u></p> <p data-bbox="539 1666 959 1695">b. “Laser” welding of polymers.</p> <p data-bbox="475 1718 1272 1843">c. Intrinsically conductive polymeric materials with a ‘bulk electrical conductivity’ exceeding 10,000 S/m (Siemens per metre) or a ‘sheet (surface) resistivity’ of less than 100 ohms/square, based on any of the following polymers:</p>

Category Code	Item Description
	<ol style="list-style-type: none"> 1. Polyaniline; 2. Polypyrrole; 3. Polythiophene; 4. Poly phenylene-vinylene; <u>or</u> 5. Poly thienylene-vinylene. <p><u>Note</u> Category Code 1C001.c. does not include materials in a liquid form.</p> <p><u>Technical Note</u> 'Bulk electrical conductivity' and 'sheet (surface) resistivity' should be determined using ASTM D-257 or national equivalents.</p>
1C002	<p>Metal alloys, metal alloy powder and alloyed materials, as follows:</p> <p><u>N.B.</u> See also Category Code 1C202.</p> <p><u>Note</u> Category Code 1C002 does not include metal alloys, metal alloy powder and alloyed materials, specially formulated for coating purposes.</p> <p><u>Technical Notes</u></p> <ol style="list-style-type: none"> 1. The metal alloys in Category Code 1C002 are those containing a higher percentage by weight of the stated metal than of any other element. 2. 'Stress-rupture life' is measured in accordance with ASTM standard E-139 or national equivalents. 3. 'Low cycle fatigue life' is measured in accordance with ASTM standard E-606 'Recommended Practice for Constant-Amplitude Low-Cycle Fatigue Testing' or national equivalents. Testing should be axial with an average stress ratio equal to 1 and a stress-concentration factor (K_t) equal to 1. The average stress is defined as maximum stress minus minimum stress divided by maximum stress.

<i>Category Code</i>	<i>Item Description</i>
	<p>a. Aluminides, as follows:</p> <ol style="list-style-type: none"> 1. Nickel aluminides containing a minimum of 15% by weight aluminium, a maximum of 38% by weight aluminium and at least one additional alloying element; 2. Titanium aluminides containing 10% by weight or more aluminium and at least one additional alloying element; <p>b. Metal alloys, as follows, made from the powder or particulate material specified in Category Code 1C002.c.:</p> <ol style="list-style-type: none"> 1. Nickel alloys having any of the following characteristics: <ol style="list-style-type: none"> a. A 'stress-rupture life' of 10,000 hours or longer at 923 K (650°C) at a stress of 676 MPa; <u>or</u> b. A 'low cycle fatigue life' of 10,000 cycles or more at 823 K (550°C) at a maximum stress of 1,095 MPa; 2. Niobium alloys having any of the following characteristics: <ol style="list-style-type: none"> a. A 'stress-rupture life' of 10,000 hours or longer at 1,073 K (800°C) at a stress of 400 MPa; <u>or</u> b. A 'low cycle fatigue life' of 10,000 cycles or more at 973 K (700°C) at a maximum stress of 700 MPa; 3. Titanium alloys having any of the following characteristics: <ol style="list-style-type: none"> a. A 'stress-rupture life' of 10,000 hours or longer at 723 K (450°C) at a stress of 200 MPa; <u>or</u> b. A 'low cycle fatigue life' of 10,000 cycles or more at 723 K (450°C) at a maximum stress of 400 MPa; 4. Aluminium alloys having any of the following characteristics: <ol style="list-style-type: none"> a. A tensile strength of 240 MPa or more at 473 K (200°C); <u>or</u> b. A tensile strength of 415 MPa or more at 298 K (25°C);

<i>Category Code</i>	<i>Item Description</i>
	<p>5. Magnesium alloys having all of the following characteristics:</p> <ol style="list-style-type: none"> a. A tensile strength of 345 MPa or more; <u>and</u> b. A corrosion rate of less than 1 mm/year in 3% sodium chloride aqueous solution measured in accordance with ASTM standard G-31 or national equivalents; <p>c. Metal alloy powder or particulate material, having all of the following characteristics:</p> <ol style="list-style-type: none"> 1. Made from any of the following composition systems: <u>Technical Note</u> <i>X in the following equals one or more alloying elements.</i> <ol style="list-style-type: none"> a. Nickel alloys (Ni-Al-X, Ni-X-Al) qualified for turbine engine parts or components, i.e. with less than 3 non-metallic particles (introduced during the manufacturing process) larger than 100 μm in 10^9 alloy particles; b. Niobium alloys (Nb-Al-X or Nb-X-Al, Nb-Si-X or Nb-X-Si, Nb-Ti-X or Nb-X-Ti); c. Titanium alloys (Ti-Al-X or Ti-X-Al); d. Aluminium alloys (Al-Mg-X or Al-X-Mg, Al-Zn-X or Al-X-Zn, Al-Fe-X or Al-X-Fe); <u>or</u> e. Magnesium alloys (Mg-Al-X or Mg-X-Al); 2. Made in a controlled environment by any of the following processes: <ol style="list-style-type: none"> a. "Vacuum atomisation"; b. "Gas atomisation"; c. "Rotary atomisation"; d. "Splat quenching"; e. "Melt spinning" and "comminution"; f. "Melt extraction" and "comminution"; g. "Mechanical alloying"; <u>or</u> h. "Plasma atomisation"; <u>and</u>

<i>Category Code</i>	<i>Item Description</i>
	<p>3. Capable of forming materials specified in Category Code 1C002.a. or 1C002.b.;</p> <p>d. Alloyed materials having all of the following characteristics:</p> <ol style="list-style-type: none"> 1. Made from any of the composition systems specified in Category Code 1C002.c.1.; 2. In the form of uncomminuted flakes, ribbons or thin rods; <u>and</u> 3. Produced in a controlled environment by any of the following: <ol style="list-style-type: none"> a. “Splat quenching”; b. “Melt spinning”; <u>or</u> c. “Melt extraction”.
1C003	<p>Magnetic metals, of all types and of whatever form, having any of the following characteristics:</p> <p>a. Initial relative permeability of 120,000 or more and a thickness of 0.05 mm or less;</p> <p><i>Technical Note</i> <i>Measurement of initial relative permeability is that performed on fully annealed materials.</i></p> <p>b. Magnetostrictive alloys having any of the following characteristics:</p> <ol style="list-style-type: none"> 1. A saturation magnetostriction of more than 5×10^{-4}; <u>or</u> 2. A magnetomechanical coupling factor (k) of more than 0.8; <u>or</u> <p>c. Amorphous or ‘nanocrystalline’ alloy strips, having all of the following characteristics:</p> <ol style="list-style-type: none"> 1. A composition having a minimum of 75% by weight of iron, cobalt or nickel; 2. A saturation magnetic induction (B_s) of 1.6 T or more; <u>and</u>

<i>Category Code</i>	<i>Item Description</i>
	<p>3. Any of the following characteristics:</p> <ul style="list-style-type: none"> a. A strip thickness of 0.02 mm or less; <u>or</u> b. An electrical resistivity of 2×10^{-4} ohm cm or more. <p><i>Technical Note</i> <i>'Nanocrystalline' materials in Category Code 1C003.c. are those materials having a crystal grain size of 50 nm or less, as determined by X-ray diffraction.</i></p>
1C004	<p>Uranium titanium alloys or tungsten alloys with a “matrix” based on iron, nickel or copper, having all of the following characteristics:</p> <ul style="list-style-type: none"> a. A density exceeding 17.5 g/cm³; b. An elastic limit exceeding 880 MPa; c. An ultimate tensile strength exceeding 1,270 MPa; <u>and</u> d. An elongation exceeding 8%.
1C005	<p>“Superconductive” “composite” conductors in lengths exceeding 100 m or with a mass exceeding 100 g, as follows:</p> <ul style="list-style-type: none"> a. “Superconductive” “composite” conductors containing one or more niobium-titanium ‘filaments’, having both of the following characteristics: <ul style="list-style-type: none"> 1. Embedded in a “matrix” other than a copper or copper-based mixed “matrix”; <u>and</u> 2. Having a cross-section area less than 0.28×10^{-4} mm² (6 μm in diameter for circular ‘filaments’); b. “Superconductive” “composite” conductors consisting of one or more “superconductive” ‘filaments’ other than niobium-titanium, having all of the following characteristics: <ul style="list-style-type: none"> 1. A “critical temperature” at zero magnetic induction exceeding 9.85 K (-263.31°C); <u>and</u>

<i>Category Code</i>	<i>Item Description</i>
	<p>2. Remaining in the “superconductive” state at a temperature of 4.2 K (-268.96°C) when exposed to a magnetic field oriented in any direction perpendicular to the longitudinal axis of conductor and corresponding to a magnetic induction of 12 T with critical current density exceeding 1,750 A/mm² on overall cross-section of the conductor;</p> <p>c. “Superconductive” “composite” conductors consisting of one or more “superconductive” ‘filaments’ which remain “superconductive” above 115 K (-158.16°C).</p> <p><i>Technical Note</i> <i>For the purpose of Category Code 1C005, ‘filaments’ may be in wire, cylinder, film, tape or ribbon form.</i></p>
1C006	<p>Fluids and lubricating materials, as follows:</p> <p>a. Not used;</p> <p>b. Lubricating materials containing, as their principal ingredients, any of the following:</p> <ol style="list-style-type: none"> 1. Phenylene or alkylphenylene ethers or thio-ethers, or their mixtures, containing more than two ether or thio-ether functions or mixtures thereof; <u>or</u> 2. Fluorinated silicone fluids with a kinematic viscosity of less than 5,000 mm²/s (5,000 centistokes) measured at 298 K (25°C); <p>c. Damping or flotation fluids having all of the following characteristics:</p> <ol style="list-style-type: none"> 1. Purity exceeding 99.8%; 2. Containing less than 25 particles of 200 µm or larger in size per 100 ml; <u>and</u> 3. Made from at least 85% of any of the following: <ol style="list-style-type: none"> a. Dibromotetrafluoroethane (25497-30-7, 124-73-2, 27336-23-8); b. Polychlorotrifluoroethylene (oily and waxy modifications only); <u>or</u>

<i>Category Code</i>	<i>Item Description</i>
	<p>c. Polybromotrifluoroethylene;</p> <p>d. Fluorocarbon electronic cooling fluids having all of the following characteristics:</p> <ol style="list-style-type: none"> 1. Containing 85% by weight or more of any of the following, or mixtures thereof: <ol style="list-style-type: none"> a. Monomeric forms of perfluoropolyalkylether-triazines or perfluoroaliphatic-ethers; b. Perfluoroalkylamines; c. Perfluorocycloalkanes; <u>or</u> d. Perfluoroalkanes; 2. Density at 298 K (25°C) of 1.5 g/ml or more; 3. In a liquid state at 273 K (0°C); <u>and</u> 4. Containing 60% or more by weight of fluorine. <p><i>Note</i> <i>Category Code 1C006.d. does not apply to materials specified and packaged as medical products.</i></p>
1C007	<p>Ceramic powders, non-“composite” ceramic materials, ceramic-“matrix” “composite” materials and precursor materials, as follows:</p> <p><i>N.B.</i> <i>See also Category Code 1C107.</i></p> <ol style="list-style-type: none"> a. Ceramic powders of single or complex borides of titanium, having total metallic impurities, excluding intentional additions, of less than 5,000 ppm, an average particle size equal to or less than 5 µm and no more than 10% of the particles larger than 10 µm; b. Non-“composite” ceramic materials in crude or semi-fabricated form, composed of borides of titanium with a density of 98% or more of the theoretical density; <p><i>Note</i> <i>Category Code 1C007.b. does not include abrasives.</i></p>

<i>Category Code</i>	<i>Item Description</i>
	<p>c. Ceramic-ceramic “composite” materials with a glass or oxide-“matrix” and reinforced with fibres having all of the following characteristics:</p> <ol style="list-style-type: none"> 1. Made from any of the following materials: <ol style="list-style-type: none"> a. Si-N; b. Si-C; c. Si-Al-O-N; <u>or</u> d. Si-O-N; <u>and</u> 2. Having a “specific tensile strength” exceeding 12.7×10^3 m; <p>d. Ceramic-ceramic “composite” materials, with or without a continuous metallic phase, incorporating particles, whiskers or fibres, where carbides or nitrides of silicon, zirconium or boron form the “matrix”;</p> <p>e. Precursor materials (i.e. special purpose polymeric or metallo-organic materials) for producing any phase or phases of the materials specified in Category Code 1C007.c., as follows:</p> <ol style="list-style-type: none"> 1. Polydiorganosilanes (for producing silicon carbide); 2. Polysilazanes (for producing silicon nitride); 3. Polycarbosilazanes (for producing ceramics with silicon, carbon and nitrogen components); <p>f. Ceramic-ceramic “composite” materials with an oxide or glass “matrix” reinforced with continuous fibres from any of the following systems:</p> <ol style="list-style-type: none"> 1. Al_2O_3 (1344-28-1); <u>or</u> 2. Si-C-N. <p><u>Note</u></p> <p><i>Category Code 1C007.f. does not include “composites” containing fibres from these systems with a fibre tensile strength of less than 700 MPa at 1,273 K (1,000°C) or fibre tensile creep resistance of more than 1% creep strain at 100 MPa load and 1,273 K (1,000°C) for 100 hours.</i></p>

<i>Category Code</i>	<i>Item Description</i>
1C008	<p>Non-fluorinated polymeric substances as follows:</p> <p>a. Imides, as follows:</p> <ol style="list-style-type: none"> 1. Bismaleimides; 2. Aromatic polyamide-imides (PAI) having a 'glass transition temperature (T_g)' exceeding 563 K (290°C); 3. Aromatic polyimides having a 'glass transition temperature (T_g)' exceeding 505 K (232°C); 4. Aromatic polyetherimides having a 'glass transition temperature (T_g)' exceeding 563 K (290°C); <p><u>Note</u> <i>Category Code 1C008.a. includes substances in liquid or solid "fusible" form, including resin, powder, pellet, film, sheet, tape or ribbon.</i></p> <p><u>N.B.</u> <i>For non-"fusible" aromatic polyimides in film, sheet, tape or ribbon form, see Category Code 1A003.</i></p> <p>b. Not used;</p> <p>c. Not used;</p> <p>d. Polyarylene ketones;</p> <p>e. Polyarylene sulphides, where the arylene group is biphenylene, triphenylene or combinations thereof;</p> <p>f. Polybiphenylenethersulphone having a 'glass transition temperature (T_g)' exceeding 563 K (290°C).</p> <p><u>Technical Notes</u></p> <ol style="list-style-type: none"> 1. <i>The 'glass transition temperature (T_g)' for Category Code 1C008.a.2. thermoplastic materials, Category Code 1C008.a.4. materials and Category Code 1C008.f. materials is determined using the method described in ISO 11357-2 (1999) or national equivalents.</i>

Category Code	Item Description
	<p>2. The 'glass transition temperature (T_g)' for Category Code 1C008.a.2. thermosetting materials and Category Code 1C008.a.3. materials is determined using the 3-point bend method described in ASTM D 7028-07 or equivalent national standard. The test is to be performed using a dry test specimen which has attained a minimum of 90% degree of cure as specified by ASTM E 2160-04 or equivalent national standard, and was cured using the combination of standard and post-cure processes that yield the highest T_g.</p>
1C009	<p>Unprocessed fluorinated compounds as follows:</p> <ol style="list-style-type: none"> a. Not used; b. Fluorinated polyimides containing 10% by weight or more of combined fluorine; c. Fluorinated phosphazene elastomers containing 30% by weight or more of combined fluorine.
1C010	<p>"Fibrous or filamentary materials", as follows:</p> <p><u>N.B.</u> See also Category Codes 1C210 and 9C110.</p> <p><u>Technical Notes</u></p> <ol style="list-style-type: none"> 1. For the purpose of calculating "specific tensile strength", "specific modulus" or specific weight of "fibrous or filamentary materials" in Category Code 1C010.a., 1C010.b., 1C010.c. or 1C010.e.1.b., the tensile strength and modulus should be determined by using Method A described in ISO 10618 (2004) or national equivalents. 2. The assessment of the "specific tensile strength", "specific modulus" or specific weight of non-unidirectional "fibrous or filamentary materials" (e.g. fabrics, random mats or braids) in Category Code 1C010 is to be based on the mechanical properties of the constituent unidirectional monofilaments (e.g. monofilaments, yarns, rovings or tows) prior to processing into the non-unidirectional "fibrous or filamentary materials".

Category Code	Item Description
	<p>a. Organic “fibrous or filamentary materials”, having both of the following characteristics:</p> <ol style="list-style-type: none"> 1. “Specific modulus” exceeding 12.7×10^6 m; <u>and</u> 2. “Specific tensile strength” exceeding 23.5×10^4 m; <p><u>Note</u> Category Code 1C010.a. does not include polyethylene.</p> <p>b. Carbon “fibrous or filamentary materials”, having both of the following characteristics:</p> <ol style="list-style-type: none"> 1. “Specific modulus” exceeding 14.65×10^6 m; <u>and</u> 2. “Specific tensile strength” exceeding 26.82×10^4 m; <p><u>Note</u> Category Code 1C010.b. does not include:</p> <ol style="list-style-type: none"> a. “Fibrous or filamentary materials”, for the repair of “civil aircraft” structures or laminates, having all of the following characteristics: <ol style="list-style-type: none"> 1. An area not exceeding 1 m^2; 2. A length not exceeding 2.5 m; <u>and</u> 3. A width exceeding 15 mm; b. Mechanically chopped, milled or cut carbon “fibrous or filamentary materials” 25 mm or less in length. <p>c. Inorganic “fibrous or filamentary materials”, having both of the following characteristics:</p> <ol style="list-style-type: none"> 1. “Specific modulus” exceeding 2.54×10^6 m; <u>and</u> 2. Melting, softening, decomposition or sublimation point exceeding 1,922 K (1,649°C) in an inert environment; <p><u>Note</u> Category Code 1C010.c. does not include:</p> <ol style="list-style-type: none"> a. Discontinuous, multiphase, polycrystalline alumina fibres in chopped fibre or random mat form, containing 3% by weight or more silica, with a “specific modulus” of less than 10×10^6 m; b. Molybdenum and molybdenum alloy fibres;

<i>Category Code</i>	<i>Item Description</i>
	<p>c. <i>Boron fibres;</i></p> <p>d. <i>Discontinuous ceramic fibres with a melting, softening, decomposition or sublimation point lower than 2,043 K (1,770°C) in an inert environment.</i></p> <p>d. “Fibrous or filamentary materials”, having any of the following characteristics:</p> <ol style="list-style-type: none"> 1. Composed of any of the following: <ol style="list-style-type: none"> a. Polyetherimides specified in Category Code 1C008.a.; <u>or</u> b. Materials specified in Category Codes 1C008.d. to 1C008.f.; <u>or</u> 2. Composed of materials specified in Category Code 1C010.d.1.a. or 1C010.d.1.b. and “commingled” with other fibres specified in Category Code 1C010.a., 1C010.b. or 1C010.c.; <p>e. Fully or partially resin-impregnated or pitch-impregnated “fibrous or filamentary materials” (prepregs), metal or carbon-coated “fibrous or filamentary materials” (preforms) or “carbon fibre preforms”, having all of the following characteristics:</p> <ol style="list-style-type: none"> 1. Having any of the following: <ol style="list-style-type: none"> a. Inorganic “fibrous or filamentary materials” specified in Category Code 1C010.c.; <u>or</u> b. Organic or carbon “fibrous or filamentary materials”, having all of the following characteristics: <ol style="list-style-type: none"> 1. “Specific modulus” exceeding 10.15×10^6 m; <u>and</u> 2. “Specific tensile strength” exceeding 17.7×10^4 m; <u>and</u> 2. Having any of the following characteristics: <ol style="list-style-type: none"> a. Resin or pitch specified in Category Code 1C008 or 1C009.b.;

Category Code	Item Description
	<p data-bbox="625 454 1267 555">b. ‘Dynamic Mechanical Analysis glass transition temperature (DMA T_g)’ equal to or exceeding 453 K (180°C) and having a phenolic resin; <u>or</u></p> <p data-bbox="625 566 1267 734">c. ‘Dynamic Mechanical Analysis glass transition temperature (DMA T_g)’ equal to or exceeding 505 K (232°C) and having a resin or pitch, not specified in Category Code 1C008 or 1C009.b., and not being a phenolic resin.</p> <p data-bbox="539 757 625 790"><u>Note 1</u></p> <p data-bbox="539 797 1267 931"><i>Metal or carbon-coated “fibrous or filamentary materials” (preforms) or “carbon fibre preforms”, not impregnated with resin or pitch, are specified by “fibrous or filamentary materials” in Category Code 1C010.a., 1C010.b. or 1C010.c.</i></p> <p data-bbox="539 947 625 981"><u>Note 2</u></p> <p data-bbox="539 987 1043 1021"><i>Category Code 1C010.e. does not include:</i></p> <p data-bbox="539 1037 1267 1171">a. <i>Epoxy resin “matrix” impregnated carbon “fibrous or filamentary materials” (prepregs) for the repair of “civil aircraft” structures or laminates, having all of the following characteristics:</i></p> <ol data-bbox="625 1182 1107 1328" style="list-style-type: none"> <li data-bbox="625 1182 1034 1216">1. <i>An area not exceeding 1 m²;</i> <li data-bbox="625 1234 1107 1267">2. <i>A length not exceeding 2.5 m; <u>and</u></i> <li data-bbox="625 1285 1011 1319">3. <i>A width exceeding 15 mm;</i> <p data-bbox="539 1339 1267 1507">b. <i>Fully or partially resin-impregnated or pitch-impregnated mechanically chopped, milled or cut carbon “fibrous or filamentary materials” 25 mm or less in length when using a resin or pitch other than those specified by Category Code 1C008 or 1C009.b.</i></p> <p data-bbox="539 1525 724 1559"><u>Technical Note</u></p> <p data-bbox="539 1565 1267 1800"><i>The ‘Dynamic Mechanical Analysis glass transition temperature (DMA T_g)’ for materials specified by Category Code 1C010.e. is determined using the method described in ASTM D 7028-07, or equivalent national standard, on a dry test specimen. In the case of thermoset materials, degree of cure of a dry test specimen is a minimum of 90% as defined by ASTM E 2160-04 or equivalent national standard.</i></p>

Category Code	Item Description
1C011	<p>Metals and compounds, as follows:</p> <p><u>N.B.</u> See also Division 2 of Part 1 of this Schedule and Category Code 1C111.</p> <p>a. Metals in particle sizes of less than 60 µm whether spherical, atomised, spheroidal, flaked or ground, manufactured from material consisting of 99% or more of zirconium, magnesium and alloys thereof;</p> <p><u>Technical Note</u> The natural content of hafnium in the zirconium (typically 2% to 7%) is counted with the zirconium.</p> <p><u>Note</u> Category Code 1C011.a. includes metals or alloys listed therein whether or not they are encapsulated in aluminium, magnesium, zirconium or beryllium.</p> <p>b. Boron or boron alloys, with a particle size of 60 µm or less, as follows;</p> <ol style="list-style-type: none"> 1. Boron with a purity of 85% by weight or more; 2. Boron alloys with a boron content of 85% by weight or more; <p><u>Note</u> Category Code 1C011.b. includes metals or alloys listed therein whether or not they are encapsulated in aluminium, magnesium, zirconium or beryllium.</p> <p>c. Guanidine nitrate (506-93-4);</p> <p>d. Nitroguanidine (NQ) (556-88-7).</p> <p><u>N.B.</u> See also Division 2 of Part 1 of this Schedule for metal powders mixed with other substances to form a mixture formulated for military purposes.</p>
1C012	<p>Materials as follows:</p> <p><u>Technical Note</u> These materials are typically used for nuclear heat sources.</p>

<i>Category Code</i>	<i>Item Description</i>
	<p>a. Plutonium in any form with a plutonium isotopic assay of plutonium-238 of more than 50% by weight;</p> <p><u>Note</u> <i>Category Code 1C012.a. does not include:</i></p> <p>a. Shipments with a plutonium content of 1 g or less;</p> <p>b. Shipments of 3 “effective grammes” or less when contained in a sensing component in instruments.</p> <p>b. “Previously separated” neptunium-237 in any form.</p> <p><u>Note</u> <i>Category Code 1C012.b. does not include shipments with a neptunium-237 content of 1 g or less.</i></p>
1C101	<p>Materials and devices for reduced observables such as radar reflectivity, ultraviolet/infrared signatures and acoustic signatures, other than those specified in Category Code 1C001, usable in ‘missiles’, “missile” sub-systems or unmanned aerial vehicles specified in Category Code 9A012 or 9A112.a.</p> <p><u>Note 1</u> <i>Category Code 1C101 includes:</i></p> <p>a. Structural materials and coatings specially designed for reduced radar reflectivity;</p> <p>b. Coatings, including paints, specially designed for reduced or tailored reflectivity or emissivity in the microwave, infrared or ultraviolet regions of the electromagnetic spectrum.</p> <p><u>Note 2</u> <i>Category Code 1C101 does not include coatings when specially used for the thermal control of satellites.</i></p> <p><u>Technical Note</u> <i>In Category Code 1C101, ‘missile’ means complete rocket systems and unmanned aerial vehicle systems capable of a range exceeding 300 km.</i></p>

<i>Category Code</i>	<i>Item Description</i>
1C102	Resaturated pyrolised carbon-carbon materials designed for space launch vehicles specified in Category Code 9A004 or sounding rockets specified in Category Code 9A104.
1C107	<p>Graphite and ceramic materials, other than those specified in Category Code 1C007, as follows:</p> <p>a. Fine grain graphites with a bulk density of 1.72 g/cm³ or greater, measured at 288 K (15°C), and having a grain size of 100 µm or less, usable for rocket nozzles and re-entry vehicle nose tips, which can be machined to any of the following products:</p> <ol style="list-style-type: none"> 1. Cylinders having a diameter of 120 mm or greater and a length of 50 mm or greater; 2. Tubes having an inner diameter of 65 mm or greater and a wall thickness of 25 mm or greater and a length of 50 mm or greater; <u>or</u> 3. Blocks having a size of 120 mm × 120 mm × 50 mm or greater; <p><u>N.B.</u> See also Category Code 0C004.</p> <p>b. Pyrolytic or fibrous reinforced graphites, usable for rocket nozzles and re-entry vehicle nose tips usable in “missiles”, space launch vehicles specified in Category Code 9A004 or sounding rockets specified in Category Code 9A104;</p> <p><u>N.B.</u> See also Category Code 0C004.</p> <p>c. Ceramic composite materials (dielectric constant less than 6 at any frequency from 100 MHz to 100 GHz) for use in radomes usable in “missiles”, space launch vehicles specified in Category Code 9A004 or sounding rockets specified in Category Code 9A104;</p> <p>d. Bulk machinable silicon-carbide reinforced unfired ceramic, usable for nose tips usable in “missiles”, space launch vehicles specified in Category Code 9A004 or sounding rockets specified in Category Code 9A104;</p>

<i>Category Code</i>	<i>Item Description</i>
1C111	<p>e. Reinforced silicon-carbide ceramic composites, usable for nose tips, re-entry vehicles and nozzle flaps usable in “missiles”, space launch vehicles specified in Category Code 9A004 or sounding rockets specified in Category Code 9A104.</p> <p>Propellants and constituent chemicals for propellants, other than those specified in Category Code 1C011, as follows:</p> <p>a. Propulsive substances:</p> <ol style="list-style-type: none"> 1. Spherical or spheroidal aluminium powder, other than that specified in Division 2 of Part 1 of this Schedule, in particle size of less than 200 μm and an aluminium content of 97% by weight or more, if at least 10% of the total weight is made up of particles of less than 63 μm, according to ISO 2591-1:1988 or national equivalents; <p><i>Technical Note</i> A particle size of 63 μm (ISO R-565) corresponds to 250 mesh (Tyler) or 230 mesh (ASTM standard E-11).</p> 2. Metal powders, other than that specified in Division 2 of Part 1 of this Schedule, as follows: <ol style="list-style-type: none"> a. Metal powders of zirconium, beryllium or magnesium, or alloys of these metals, if at least 90% of the total particles by particle volume or weight are made up of particles of less than 60 μm (determined by measurement techniques such as using a sieve, laser diffraction or optical scanning), whether spherical, atomised, spheroidal, flaked or ground, consisting 97% by weight or more of any of the following: <ol style="list-style-type: none"> 1. Zirconium; 2. Beryllium; <u>or</u> 3. Magnesium; <p><i>Technical Note</i> The natural content of hafnium in the zirconium (typically 2% to 7%) is counted with the zirconium.</p>

<i>Category Code</i>	<i>Item Description</i>
	<p data-bbox="624 454 1267 719">b. Metal powders of either boron or boron alloys with a boron content of 85% or more by weight, if at least 90% of the total particles by particle volume or weight are made up of particles of less than 60 µm (determined by measurement techniques such as using a sieve, laser diffraction or optical scanning), whether spherical, atomised, spheroidal, flaked or ground;</p> <p data-bbox="603 741 663 768"><i>Note</i></p> <p data-bbox="603 779 1267 943"><i>Category Codes 1C111a.2.a. and 1C111a.2.b. include any powder mixture with a multimodal particle distribution (e.g. a mixture of different grain sizes) if one or more modes in the powder mixture are specified in Division 2 of Part 2 of this Schedule.</i></p> <p data-bbox="539 965 1267 1025">3. Oxidiser substances usable in liquid propellant rocket engines as follows:</p> <p data-bbox="624 1048 1091 1075">a. Dinitrogen trioxide (10544-73-7);</p> <p data-bbox="624 1097 1267 1158">b. Nitrogen dioxide (10102-44-0)/dinitrogen tetroxide (10544-72-6);</p> <p data-bbox="624 1180 1114 1207">c. Dinitrogen pentoxide (10102-03-1);</p> <p data-bbox="624 1229 1107 1256">d. Mixed Oxides of Nitrogen (MON);</p> <p data-bbox="687 1279 871 1305"><i>Technical Note</i></p> <p data-bbox="687 1317 1267 1653"><i>Mixed Oxides of Nitrogen (MON) are solutions of Nitric Oxide (NO) in Dinitrogen Tetroxide/ Nitrogen Dioxide (N₂O₄/NO₂) that can be used in missile systems. There are a range of compositions that can be denoted as MON_i or MON_{ij}, where i and j are integers representing the percentage of Nitric Oxide in the mixture (e.g. MON₃ contains 3% Nitric Oxide, MON₂₅ 25% Nitric Oxide. An upper limit is MON₄₀, 40% by weight).</i></p> <p data-bbox="624 1675 1267 1736">e. See Inhibited Red Fuming Nitric Acid (IRFNA) in Division 2 of Part 1 of this Schedule;</p>

<i>Category Code</i>	<i>Item Description</i>
	<p>f. See compounds composed of fluorine and one or more of other halogens, oxygen or nitrogen in Division 2 of Part 1 of this Schedule and Category Code 1C238;</p> <p>4. Hydrazine derivatives as follows:</p> <p><u><i>N.B.</i></u> <i>See also Division 2 of Part 1 of this Schedule.</i></p> <p>a. Trimethylhydrazine (1741-01-1);</p> <p>b. Tetramethylhydrazine (6415-12-9);</p> <p>c. N,N diallylhydrazine (5164-11-4);</p> <p>d. Allylhydrazine (7422-78-8);</p> <p>e. Ethylene dihydrazine (6068-98-0);</p> <p>f. Monomethylhydrazine dinitrate;</p> <p>g. Unsymmetrical dimethylhydrazine nitrate;</p> <p>h. Hydrazinium azide (14546-44-2);</p> <p>i. 1,1-Dimethylhydrazinium azide (227955-52-4) / 1,2-Dimethylhydrazinium azide (299177-50-7);</p> <p>j. Hydrazinium dinitrate (13464-98-7);</p> <p>k. Diimido oxalic acid dihydrazine (3457-37-2);</p> <p>l. 2-hydroxyethylhydrazine nitrate (HEHN);</p> <p>m. See Hydrazinium perchlorate in Division 2 of Part 1 of this Schedule;</p> <p>n. Hydrazinium diperchlorate (13812-39-0);</p> <p>o. Methylhydrazine nitrate (MHN) (29674-96-2);</p> <p>p. 1,1-Diethylhydrazine nitrate (DEHN) / 1,2-Diethylhydrazine nitrate (DEHN) (363453-17-2);</p> <p>q. 3,6-dihydrazino tetrazine nitrate (1,4-dihydrazine nitrate) (DHTN);</p>

<i>Category Code</i>	<i>Item Description</i>
	<p>5. High energy density materials, other than that specified in Division 2 of Part 1 of this Schedule, usable in 'missiles' or unmanned aerial vehicles specified in Category Code 9A012 or 9A112.a., as follows:</p> <ol style="list-style-type: none"> a. Mixed fuel that incorporate both solid and liquid fuels, such as boron slurry, having a mass-based energy density of 40×10^6 J/kg or greater; b. Other high energy density fuels and fuel additives (e.g. cubane, ionic solutions, JP-10) having a volume-based energy density of 37.5×10^9 J/m³ or greater, measured at 20°C and one atmosphere (101.325 kPa) pressure; <p><i>Note</i> <i>Category Code 1C111.a.5.b. does not include fossil refined fuels and biofuels produced from vegetables, including fuels for engines certified for use in civil aviation, unless specially formulated for 'missiles' or unmanned aerial vehicles specified in Category Code 9A012 or 9A112.a.</i></p> <p><i>Technical Note</i> <i>In Category Code 1C111.a.5., 'missile' means complete rocket systems and unmanned aerial vehicle systems capable of a range exceeding 300 km.</i></p> <p>6. Hydrazine replacement fuels as follows:</p> <ol style="list-style-type: none"> a. 2-Dimethylaminoethylazide (DMAZ) (86147-04-8); <p>b. Polymeric substances:</p> <ol style="list-style-type: none"> 1. Carboxy-terminated polybutadiene (including carboxyl-terminated polybutadiene) (CTPB); 2. Hydroxy-terminated polybutadiene (including hydroxyl-terminated polybutadiene) (HTPB), other than that specified in Division 2 of Part 1 of this Schedule; 3. Polybutadiene-acrylic acid (PBAA); 4. Polybutadiene-acrylic acid-acrylonitrile (PBAN) (25265-19-4 / 68891-50-9);

<i>Category Code</i>	<i>Item Description</i>
	<p>5. Polytetrahydrofuran polyethylene glycol (TPEG);</p> <p><i>Technical Note</i> <i>Polytetrahydrofuran polyethylene glycol (TPEG) is a block co-polymer of poly 1,4-Butanediol (110-63-4) and polyethylene glycol (PEG) (25322-68-3).</i></p> <p>6. Polyglycidyl nitrate (PGN or poly-GLYN) (27814-48-8);</p> <p>c. Other propellant additives and agents:</p> <ol style="list-style-type: none"> 1. See carboranes, decaboranes, pentaboranes and derivatives thereof in Division 2 of Part 1 of this Schedule; 2. Triethylene glycol dinitrate (TEGDN) (111-22-8); 3. 2-Nitrodiphenylamine (119-75-5); 4. Trimethylolethane trinitrate (TMETN) (3032-55-1); 5. Diethylene glycol dinitrate (DEGDN) (693-21-0); 6. Ferrocene derivatives as follows: <ol style="list-style-type: none"> a. See catocene in Division 2 of Part 1 of this Schedule; b. See ethyl ferrocene in Division 2 of Part 1 of this Schedule; c. See propyl ferrocene in Division 2 of Part 1 of this Schedule; d. See n-butyl ferrocene in Division 2 of Part 1 of this Schedule; e. See pentyl ferrocene in Division 2 of Part 1 of this Schedule; f. See dicyclopentyl ferrocene in Division 2 of Part 1 of this Schedule; g. See dicyclohexyl ferrocene in Division 2 of Part 1 of this Schedule; h. See diethyl ferrocene in Division 2 of Part 1 of this Schedule;

<i>Category Code</i>	<i>Item Description</i>
	<ul style="list-style-type: none"> i. See dipropyl ferrocene in Division 2 of Part 1 of this Schedule; j. See dibutyl ferrocene in Division 2 of Part 1 of this Schedule; k. See dihexyl ferrocene in Division 2 of Part 1 of this Schedule; l. See acetyl ferrocene/1,1'-diacetyl ferrocene in Division 2 of Part 1 of this Schedule; m. See ferrocene carboxylic acids in Division 2 of Part 1 of this Schedule; n. See butacene in Division 2 of Part 1 of this Schedule; o. Other ferrocene derivatives usable as rocket propellant burning rate modifiers, other than those specified in Division 2 of Part 1 of this Schedule; <p><i>Note</i> Category Code 1C111.c.6.o. does not include ferrocene derivatives that contain a six carbon aromatic functional group attached to the ferrocene molecule.</p> <ul style="list-style-type: none"> 7. 4,5 diazidomethyl-2-methyl-1,2,3-triazole (iso-DAMTR), other than that specified in Division 2 of Part 1 of this Schedule. <p><i>Note</i> For propellants and constituent chemicals for propellants not specified in Category Code 1C111, see Division 2 of Part 1 of this Schedule.</p>
1C116	<p>Maraging steels, usable in 'missiles', having both of the following characteristics:</p> <p><i>N.B.</i> See also Category Code 1C216.</p> <ul style="list-style-type: none"> a. An ultimate tensile strength, measured at 293 K (20°C), equal to or greater than:

<i>Category Code</i>	<i>Item Description</i>
	<ol style="list-style-type: none"> 1. 0.9 GPa in the solution annealed stage; <u>or</u> 2. 1.5 GPa in the precipitation hardened stage; <u>and</u> <p>b. Any of the following forms:</p> <ol style="list-style-type: none"> 1. Sheet, plate or tubing with a wall or plate thickness equal to or less than 5 mm; 2. Tubular forms with a wall thickness equal to or less than 50 mm and having an inner diameter equal to or greater than 270 mm. <p><i>Technical Notes</i></p> <ol style="list-style-type: none"> 1. <i>Maraging steels are iron alloys:</i> <ol style="list-style-type: none"> a. <i>Generally characterised by high nickel, very low carbon content and the use of substitutional elements or precipitates to produce strengthening and age-hardening of the alloy; <u>and</u></i> b. <i>Subjected to heat treatment cycles to facilitate the martensitic transformation process (solution annealed stage) and subsequently age hardened (precipitation hardened stage).</i> 2. <i>In Category Code 1C116, 'missile' means complete rocket systems and unmanned aerial vehicle systems capable of a range exceeding 300 km.</i>
1C117	<p>Materials for the fabrication of 'missiles' components as follows:</p> <ol style="list-style-type: none"> a. Tungsten and alloys in particulate form with a tungsten content of 97% by weight or more and a particle size of 50×10^{-6} m (50 μm) or less; b. Molybdenum and alloys in particulate form with a molybdenum content of 97% by weight or more and a particle size of 50×10^{-6} m (50 μm) or less; c. Tungsten materials in solid form having all of the following characteristics: <ol style="list-style-type: none"> 1. Any of the following material compositions: <ol style="list-style-type: none"> a. Tungsten and alloys containing 97% by weight or more of tungsten;

<i>Category Code</i>	<i>Item Description</i>
	<ul style="list-style-type: none"> b. Copper infiltrated tungsten containing 80% by weight or more of tungsten; <u>or</u> c. Silver infiltrated tungsten containing 80% by weight or more of tungsten; <u>and</u> <p>2. Able to be machined to any of the following products:</p> <ul style="list-style-type: none"> a. Cylinders having a diameter of 120 mm or greater and a length of 50 mm or greater; b. Tubes having an inner diameter of 65 mm or greater and a wall thickness of 25 mm or greater and a length of 50 mm or greater; <u>or</u> c. Blocks having a size of 120 mm by 120 mm by 50 mm or greater. <p><i><u>Technical Note</u></i> <i>In Category Code 1C117, 'missile' means complete rocket systems and unmanned aerial vehicle systems capable of a range exceeding 300 km.</i></p>
1C118	<p>Titanium-stabilised duplex stainless steel (Ti-DSS) having all of the following characteristics:</p> <ul style="list-style-type: none"> a. Having all of the following characteristics: <ul style="list-style-type: none"> 1. Containing 17-23% by weight chromium and 4.5-7% by weight nickel; 2. Having a titanium content of greater than 0.10% by weight; <u>and</u> 3. A ferritic-austenitic microstructure (also referred to as a two-phase microstructure) of which at least 10% is austenite by volume (according to ASTM E-1181-87 or national equivalents); <u>and</u> b. Having any of the following forms: <ul style="list-style-type: none"> 1. Ingots or bars having a size of 100 mm or more in each dimension; 2. Sheets having a width of 600 mm or more and a thickness of 3 mm or less; <u>or</u>

<i>Category Code</i>	<i>Item Description</i>
1C202	<p data-bbox="539 454 1272 521">3. Tubes having an outer diameter of 600 mm or more and a wall thickness of 3 mm or less.</p> <p data-bbox="475 589 1272 656">Alloys, other than those specified in Category Code 1C002.b.3. or .b.4., as follows:</p> <p data-bbox="475 678 1272 745">a. Aluminium alloys having both of the following characteristics:</p> <ol data-bbox="539 757 1272 902" style="list-style-type: none"> <li data-bbox="539 757 1272 824">1. ‘Capable of’ an ultimate tensile strength of 460 MPa or more at 293 K (20°C); <u>and</u> <li data-bbox="539 835 1272 902">2. In the form of tubes or cylindrical solid forms (including forgings) with an outside diameter of more than 75 mm; <p data-bbox="475 925 1272 958">b. Titanium alloys having both of the following characteristics:</p> <ol data-bbox="539 969 1272 1126" style="list-style-type: none"> <li data-bbox="539 969 1272 1037">1. ‘Capable of’ an ultimate tensile strength of 900 MPa or more at 293 K (20°C); <u>and</u> <li data-bbox="539 1048 1272 1126">2. In the form of tubes or cylindrical solid forms (including forgings) with an outside diameter of more than 75 mm. <p data-bbox="475 1137 659 1171"><u>Technical Note</u></p> <p data-bbox="475 1182 1272 1249"><i>The phrase alloys ‘capable of’ encompasses alloys before or after heat treatment.</i></p>
1C210	<p data-bbox="475 1317 1272 1384">‘Fibrous or filamentary materials’ or prepregs, other than those specified in Category Code 1C010.a., b. or e., as follows:</p> <p data-bbox="475 1395 1272 1462">a. Carbon or aramid ‘fibrous or filamentary materials’ having either of the following characteristics:</p> <ol data-bbox="539 1473 1272 1563" style="list-style-type: none"> <li data-bbox="539 1473 1272 1518">1. A “specific modulus” of 12.7×10^6 m or greater; <u>or</u> <li data-bbox="539 1529 1272 1563">2. A “specific tensile strength” of 23.5×10^4 m or greater; <p data-bbox="475 1574 603 1608"><u>Note</u></p> <p data-bbox="475 1619 1272 1720"><i>Category Code 1C210.a. does not include aramid ‘fibrous or filamentary materials’ having 0.25% by weight or more of an ester based fibre surface modifier;</i></p> <p data-bbox="475 1731 1272 1798">b. Glass ‘fibrous or filamentary materials’ having both of the following characteristics:</p> <ol data-bbox="539 1809 1272 1850" style="list-style-type: none"> <li data-bbox="539 1809 1272 1850">1. A “specific modulus” of 3.18×10^6 m or greater; <u>and</u>

Category Code	Item Description
	<p>2. A “specific tensile strength” of 7.62×10^4 m or greater;</p> <p>c. Thermoset resin impregnated continuous “yarns”, “rovings”, “tows” or “tapes” with a width of 15 mm or less (prepregs), made from carbon or glass ‘fibrous or filamentary materials’ specified in Category Code 1C210.a. or b.</p> <p><u>Technical Note</u> The resin forms the matrix of the composite.</p> <p><u>Note</u> In Category Code 1C210, ‘fibrous or filamentary materials’ is restricted to continuous “monofilaments”, “yarns”, “rovings”, “tows” or “tapes”.</p>
1C216	<p>Maraging steel, other than that specified in Category Code 1C116, ‘capable of’ an ultimate tensile strength of 1,950 MPa or more, at 293 K (20°C).</p> <p><u>Note</u> Category Code 1C216 does not include forms in which all linear dimensions are 75 mm or less.</p> <p><u>Technical Note</u> The phrase maraging steel ‘capable of’ encompasses maraging steel before or after heat treatment.</p>
1C225	<p>Boron enriched in the boron-10 (^{10}B) isotope to greater than its natural isotopic abundance, as follows: elemental boron, compounds, mixtures containing boron, manufactures thereof, waste or scrap of any of the foregoing.</p> <p><u>Note</u> In Category Code 1C225, mixtures containing boron include boron loaded materials.</p> <p><u>Technical Note</u> The natural isotopic abundance of boron-10 is approximately 18.5 weight per cent (20 atom per cent).</p>

<i>Category Code</i>	<i>Item Description</i>
1C226	<p>Tungsten, tungsten carbide, and alloys containing more than 90% tungsten by weight, other than that specified by Category Code 1C117, having both of the following characteristics:</p> <ul style="list-style-type: none"> a. In forms with a hollow cylindrical symmetry (including cylinder segments) with an inside diameter between 100 mm and 300 mm; <u>and</u> b. A mass greater than 20 kg. <p><u>Note</u> <i>Category Code 1C226 does not include manufactures specially designed as weights or gamma-ray collimators.</i></p>
1C227	<p>Calcium having both of the following characteristics:</p> <ul style="list-style-type: none"> a. Containing less than 1,000 parts per million by weight of metallic impurities other than magnesium; <u>and</u> b. Containing less than 10 parts per million by weight of boron.
1C228	<p>Magnesium having both of the following characteristics:</p> <ul style="list-style-type: none"> a. Containing less than 200 parts per million by weight of metallic impurities other than calcium; <u>and</u> b. Containing less than 10 parts per million by weight of boron.
1C229	<p>Bismuth having both of the following characteristics:</p> <ul style="list-style-type: none"> a. A purity of 99.99% or greater by weight; <u>and</u> b. Containing less than 10 ppm (parts per million) by weight of silver.
1C230	<p>Beryllium metal, alloys containing more than 50% beryllium by weight, beryllium compounds, manufactures thereof, and waste or scrap of any of the foregoing, other than that specified in Division 2 of Part 1 of this Schedule.</p> <p><u>N.B.</u> <i>See also Division 2 of Part 1 of this Schedule.</i></p>

<i>Category Code</i>	<i>Item Description</i>
	<p><u>Note</u> <i>Category Code 1C230 does not include the following:</i></p> <ol style="list-style-type: none"> <li data-bbox="475 544 1268 611">a. <i>Metal windows for X-ray machines, or for bore-hole logging devices;</i> <li data-bbox="475 629 1268 730">b. <i>Oxide shapes in fabricated or semi-fabricated forms specially designed for electronic component parts or as substrates for electronic circuits;</i> <li data-bbox="475 748 1268 815">c. <i>Beryl (silicate of beryllium and aluminium) in the form of emeralds or aquamarines.</i>
1C231	Hafnium metal, alloys containing more than 60% hafnium by weight, hafnium compounds containing more than 60% hafnium by weight, manufactures thereof, and waste or scrap of any of the foregoing.
1C232	<p>Helium-3 (³He), mixtures containing helium-3, and products or devices containing any of the foregoing.</p> <p><u>Note</u> <i>Category Code 1C232 does not include a product or device containing less than 1 g of helium-3.</i></p>
1C233	<p>Lithium enriched in the lithium-6 (⁶Li) isotope to greater than its natural isotopic abundance, and products or devices containing enriched lithium, as follows: elemental lithium, alloys, compounds, mixtures containing lithium, manufactures thereof, waste or scrap of any of the foregoing.</p> <p><u>Note</u> <i>Category Code 1C233 does not include thermoluminescent dosimeters.</i></p> <p><u>Technical Note</u> <i>The natural isotopic abundance of lithium-6 is approximately 6.5 weight per cent (7.5 atom per cent).</i></p>

<i>Category Code</i>	<i>Item Description</i>
1C234	<p>Zirconium with a hafnium content of less than 1 part hafnium to 500 parts zirconium by weight, as follows: metal, alloys containing more than 50% zirconium by weight, compounds, manufactures thereof, waste or scrap of any of the foregoing, other than those specified in Category Code 0A001.f.</p> <p><u>Note</u> Category Code 1C234 does not include zirconium in the form of foil having a thickness of 0.1 mm or less.</p>
1C235	<p>Tritium, tritium compounds, mixtures containing tritium in which the ratio of tritium to hydrogen atoms exceeds 1 part in 1,000, and products or devices containing any of the foregoing.</p> <p><u>Note</u> Category Code 1C235 does not include a product or device containing less than 1.48×10^3 GBq (40 Ci) of tritium.</p>
1C236	<p>‘Radionuclides’ appropriate for making neutron sources based on alpha-n reaction, other than those specified in Category Codes 0C001 and 1C012.a., in the following forms:</p> <ol style="list-style-type: none"> a. Elemental; b. Compounds having a total activity of 37 GBq/kg (1 Ci/kg) or greater; c. Mixtures having a total activity of 37 GBq/kg (1 Ci/kg) or greater; d. Products or devices containing any of the foregoing. <p><u>Note</u> Category Code 1C236 does not include a product or device containing less than 3.7 GBq (100 millicuries) of activity.</p> <p><u>Technical Note</u> In Category Code 1C236, ‘radionuclides’ are any of the following:</p> <ul style="list-style-type: none"> – Actinium-225 (Ac-225) – Actinium-227 (Ac-227) – Californium-253 (Cf-253)

<i>Category Code</i>	<i>Item Description</i>
	– <i>Curium-240 (Cm-240)</i>
	– <i>Curium-241 (Cm-241)</i>
	– <i>Curium-242 (Cm-242)</i>
	– <i>Curium-243 (Cm-243)</i>
	– <i>Curium-244 (Cm-244)</i>
	– <i>Einsteinium-253 (Es-253)</i>
	– <i>Einsteinium-254 (Es-254)</i>
	– <i>Gadolinium-148 (Gd-148)</i>
	– <i>Plutonium-236 (Pu-236)</i>
	– <i>Plutonium-238 (Pu-238)</i>
	– <i>Polonium-208 (Po-208)</i>
	– <i>Polonium-209 (Po-209)</i>
	– <i>Polonium-210 (Po-210)</i>
	– <i>Radium-223 (Ra-223)</i>
	– <i>Thorium-227 (Th-227)</i>
	– <i>Thorium-228 (Th-228)</i>
	– <i>Uranium-230 (U-230)</i>
	– <i>Uranium-232 (U-232)</i>
1C237	<p>Radium-226 (²²⁶Ra), radium-226 alloys, radium-226 compounds, mixtures containing radium-226, manufactures thereof, and products or devices containing any of the foregoing.</p> <p><u>Note</u></p> <p><i>Category Code 1C237 does not include the following:</i></p> <ol style="list-style-type: none"> a. <i>Medical applicators;</i> b. <i>A product or device containing less than 0.37 GBq (10 millicuries) of radium-226.</i>
1C238	Chlorine trifluoride (ClF ₃).

<i>Category Code</i>	<i>Item Description</i>
1C239	High explosives, other than those specified in Division 2 of Part 1 of this Schedule, or substances or mixtures containing more than 2% by weight thereof, with a crystal density greater than 1.8 g/cm ³ and having a detonation velocity greater than 8,000 m/s.
1C240	<p>Nickel powder and porous nickel metal, other than those specified in Category Code 0C005, as follows:</p> <p>a. Nickel powder having both of the following characteristics:</p> <ol style="list-style-type: none"> 1. A nickel purity content of 99% or greater by weight; <u>and</u> 2. A mean particle size of less than 10 µm measured by American Society for Testing and Materials (ASTM) B330 standard; <p>b. Porous nickel metal produced from materials specified in Category Code 1C240.a.</p>
	<p><u>Note</u></p> <p><i>Category Code 1C240 does not include the following:</i></p> <ol style="list-style-type: none"> a. <i>Filamentary nickel powders;</i> b. <i>Single porous nickel sheets with an area of 1,000 cm² per sheet or less.</i>
	<p><u>Technical Note</u></p> <p><i>Category Code 1C240.b. refers to porous metal formed by compacting and sintering the materials in Category Code 1C240.a. to form a metal material with fine pores interconnected throughout the structure.</i></p>
1C241	<p>Rhenium, and alloys containing 90% by weight or more rhenium; and alloys of rhenium and tungsten containing 90% by weight or more of any combination of rhenium and tungsten, other than those specified in Category Code 1C226, having both of the following characteristics:</p> <ol style="list-style-type: none"> a. In forms with a hollow cylindrical symmetry (including cylinder segments) with an inside diameter between 100 mm and 300 mm; <u>and</u> b. A mass greater than 20 kg.

<i>Category Code</i>	<i>Item Description</i>
1C350	<p>Chemicals, which may be used as precursors for toxic chemical agents, as follows, and “chemical mixtures” containing one or more thereof:</p> <p><u><i>N.B.</i></u> <i>See also Division 2 of Part 1 of this Schedule and Category Code 1C450.</i></p> <ol style="list-style-type: none"> 1. Thiodiglycol (111-48-8); 2. Phosphorus oxychloride (10025-87-3); 3. Dimethyl methylphosphonate (756-79-6); 4. See Methyl phosphonyl difluoride (676-99-3) in Division 2 of Part 1 of this Schedule; 5. Methyl phosphonyl dichloride (676-97-1); 6. Dimethyl phosphite (DMP) (868-85-9); 7. Phosphorus trichloride (7719-12-2); 8. Trimethyl phosphite (TMP) (121-45-9); 9. Thionyl chloride (7719-09-7); 10. 3-Hydroxy-1-methylpiperidine (3554-74-3); 11. N,N-Diisopropyl-(beta)-aminoethyl chloride (96-79-7); 12. N,N-Diisopropyl-(beta)-aminoethane thiol (5842-07-9); 13. 3-Quinuclidinol (1619-34-7); 14. Potassium fluoride (7789-23-3); 15. 2-Chloroethanol (107-07-3); 16. Dimethylamine (124-40-3); 17. Diethyl ethylphosphonate (78-38-6); 18. Diethyl N,N-dimethylphosphoramidate (2404-03-7); 19. Diethyl phosphite (762-04-9); 20. Dimethylamine hydrochloride (506-59-2); 21. Ethyl phosphinyl dichloride (1498-40-4); 22. Ethyl phosphonyl dichloride (1066-50-8);

<i>Category Code</i>	<i>Item Description</i>
	23. See Ethyl phosphonyl difluoride (753-98-0) in Division 2 of Part 1 of this Schedule;
	24. Hydrogen fluoride (7664-39-3);
	25. Methyl benzilate (76-89-1);
	26. Methyl phosphinyl dichloride (676-83-5);
	27. N,N-Diisopropyl-(beta)-amino ethanol (96-80-0);
	28. Pinacolyl alcohol (464-07-3);
	29. See O-Ethyl O-2-diisopropylaminoethyl methylphosphonite (QL) (57856-11-8) in Division 2 of Part 1 of this Schedule;
	30. Triethyl phosphite (122-52-1);
	31. Arsenic trichloride (7784-34-1);
	32. Benzilic acid (76-93-7);
	33. Diethyl methylphosphonite (15715-41-0);
	34. Dimethyl ethylphosphonate (6163-75-3);
	35. Ethyl phosphinyl difluoride (430-78-4);
	36. Methyl phosphinyl difluoride (753-59-3);
	37. 3-Quinuclidone (3731-38-2);
	38. Phosphorus pentachloride (10026-13-8);
	39. Pinacolone (75-97-8);
	40. Potassium cyanide (151-50-8);
	41. Potassium bifluoride (7789-29-9);
	42. Ammonium hydrogen fluoride or ammonium bifluoride (1341-49-7);
	43. Sodium fluoride (7681-49-4);
	44. Sodium bifluoride (1333-83-1);
	45. Sodium cyanide (143-33-9);
	46. Triethanolamine (102-71-6);
	47. Phosphorus pentasulphide (1314-80-3);
	48. Di-isopropylamine (108-18-9);

<i>Category Code</i>	<i>Item Description</i>
	49. Diethylaminoethanol (100-37-8);
	50. Sodium sulphide (1313-82-2);
	51. Sulphur monochloride (10025-67-9);
	52. Sulphur dichloride (10545-99-0);
	53. Triethanolamine hydrochloride (637-39-8);
	54. N,N-Diisopropyl-(beta)-aminoethyl chloride hydrochloride (4261-68-1);
	55. Methylphosphonic acid (993-13-5);
	56. Diethyl methylphosphonate (683-08-9);
	57. N,N-Dimethylaminophosphoryl dichloride (677-43-0);
	58. Triisopropyl phosphite (116-17-6);
	59. Ethyldiethanolamine (139-87-7);
	60. O,O-Diethyl phosphorothioate (2465-65-8);
	61. O,O-Diethyl phosphorodithioate (298-06-6);
	62. Sodium hexafluorosilicate (16893-85-9);
	63. Methylphosphonothioic dichloride (676-98-2);
	64. Diethylamine (109-89-7).
	<u>Note 1</u>
	<i>Category Code 1C350 does not include “chemical mixtures” containing one or more of the chemicals specified in Category Codes 1C350.2., .6., .7., .8., .9., .10., .14., .15., .16., .19., .20., .24., .25., .30., .37., .38., .39., .40., .41., .42., .43., .44., .45., .46., .47., .48., .49., .50., .51., .52., .53., .58., .59., .60., .61., 62. and .64. in which no individually specified chemical constitutes more than 30% by the weight of the mixture.</i>
	<u>Note 2</u>
	<i>Category Code 1C350 does not include products identified as consumer goods and packaged for retail sale for personal use or packaged for individual use.</i>

<i>Category Code</i>	<i>Item Description</i>
1C351	<p>Human and animal pathogens and “toxins”, as follows:</p> <ol style="list-style-type: none"> a. Viruses, whether natural, enhanced or modified, either in the form of “isolated live cultures” or as material including living material which has been deliberately inoculated or contaminated with such cultures, as follows: <ol style="list-style-type: none"> 1. African horse sickness virus; 2. African swine fever virus; 3. Andes virus; 4. Avian influenza virus, which are <ol style="list-style-type: none"> a. Uncharacterised; <u>or</u> b. Defined in Annex I(2) EC Directive 2005/94/EC (O.J. L.10 14.1.2006 p. 16) as having high pathogenicity, as follows: <ol style="list-style-type: none"> 1. Type A viruses with an IVPI (intravenous pathogenicity index) in 6 week old chickens of greater than 1.2; <u>or</u> 2. Type A viruses of the subtypes H5 or H7 with genome sequences codified for multiple basic amino acids at the cleavage site of the haemagglutinin molecule similar to that observed for other HPAI viruses, indicating that the haemagglutinin molecule can be cleaved by a host ubiquitous protease; 5. Bluetongue virus; 6. Chapare virus; 7. Chikungunya virus; 8. Choclo virus; 9. Crimean-Congo hemorrhagic fever virus; 10. Dengue virus; 11. Dobrava-Belgrade virus; 12. Eastern equine encephalitis virus; 13. Ebolavirus: all members of the Ebolavirus genus;

<i>Category Code</i>	<i>Item Description</i>
	14. Foot-and-mouth disease virus;
	15. Goatpox virus;
	16. Guaranito virus;
	17. Hantaan virus;
	18. Hendra virus (Equine morbillivirus);
	19. Suid herpesvirus 1 (Pseudorabies virus) (Aujeszky's disease);
	20. Classical swine fever virus (Hog cholera virus);
	21. Japanese encephalitis virus;
	22. Junin virus;
	23. Kyasanur Forest disease virus;
	24. Laguna Negra virus;
	25. Lassa virus;
	26. Louping ill virus;
	27. Lujo virus;
	28. Lumpy skin disease virus;
	29. Lymphocytic choriomeningitis virus;
	30. Machupo virus;
	31. Marburgvirus: all members of the Marburgvirus genus;
	32. Monkeypox virus;
	33. Murray Valley encephalitis virus;
	34. Newcastle disease virus;
	35. Nipah virus;
	36. Omsk haemorrhagic fever virus;
	37. Oropouche virus;
	38. Peste-des-petits-ruminants virus;
	39. Swine vesicular disease virus;
	40. Powassan virus;

<i>Category Code</i>	<i>Item Description</i>
	<ul style="list-style-type: none"> 41. Rabies virus and all other members of the Lyssavirus genus; 42. Rift Valley fever virus; 43. Rinderpest virus; 44. Rocio virus; 45. Sabia virus; 46. Seoul virus; 47. Sheeppox virus; 48. Sin Nombre virus; 49. St. Louis encephalitis virus; 50. Porcine Teschovirus; 51. Tick-borne encephalitis virus (Far Eastern subtype); 52. Variola virus; 53. Venezuelan equine encephalitis virus; 54. Vesicular stomatitis virus; 55. Western equine encephalitis virus; 56. Yellow fever virus; 57. Severe acute respiratory syndrome-related coronavirus (SARS-related coronavirus); 58. Reconstructed 1918 influenza virus; b. Not used; c. Bacteria, whether natural, enhanced or modified, either in the form of “isolated live cultures” or as material including living material which has been deliberately inoculated or contaminated with such cultures, as follows: <ul style="list-style-type: none"> 1. Bacillus anthracis; 2. Brucella abortus; 3. Brucella melitensis; 4. Brucella suis; 5. Burkholderia mallei (Pseudomonas mallei);

<i>Category Code</i>	<i>Item Description</i>
	<ol style="list-style-type: none"> 6. Burkholderia pseudomallei (Pseudomonas pseudomallei); 7. Chlamydophila psittaci (formerly known as Chlamydia psittaci); 8. Clostridium argentinense (formerly known as Clostridium botulinum Type G), botulinum neurotoxin producing strains; 9. Clostridium baratii, botulinum neurotoxin producing strains; 10. Clostridium botulinum; 11. Clostridium butyricum, botulinum neurotoxin producing strains; 12. Clostridium perfringens epsilon toxin producing types; 13. Coxiella burnetii; 14. Francisella tularensis; 15. Mycoplasma capricolum subspecies capripneumoniae (strain F38); 16. Mycoplasma mycoides subspecies mycoides SC (small colony); 17. Rickettsia prowasecki; 18. Salmonella typhi; 19. Shiga toxin producing Escherichia coli (STEC) of serogroups O26, O45, O103, O104, O111, O121, O145, O157, and other shiga toxin producing serogroups; <p><i>Technical Note</i> <i>Shiga toxin producing Escherichia coli (STEC) is also known as enterohaemorrhagic E. coli (EHEC) or verocytotoxin producing E. coli (VTEC).</i></p> <ol style="list-style-type: none"> 20. Shigella dysenteriae; 21. Vibrio cholerae; 22. Yersinia pestis; <p>d. "Toxins", as follows, and "sub-unit of toxins" thereof:</p> <ol style="list-style-type: none"> 1. Botulinum toxins;

<i>Category Code</i>	<i>Item Description</i>
	<ol style="list-style-type: none"> 2. Clostridium perfringens alpha, beta 1, beta 2, epsilon and iota toxins; 3. Conotoxin; 4. Ricin; 5. Saxitoxin; 6. Shiga toxin; 7. Staphylococcus aureus enterotoxins, hemolysin alpha toxin, and toxic shock syndrome toxin (formerly known as Staphylococcus enterotoxin F); 8. Tetrodotoxin; 9. Verotoxin and shiga-like ribosome inactivating proteins; 10. Microcystin (Cyanginosin); 11. Aflatoxins; 12. Abrin; 13. Cholera toxin; 14. Diacetoxyscirpenol toxin; 15. T-2 toxin; 16. HT-2 toxin; 17. Modeccin toxin; 18. Volkensin toxin; 19. Viscum Album Lectin 1 (Viscumin);
	<p><u>Note</u></p> <p><i>Category Code 1C351.d. does not include botulinum toxins or conotoxins in product form meeting all of the following criteria:</i></p> <ol style="list-style-type: none"> 1. <i>Are pharmaceutical formulations designed for human administration in the treatment of medical conditions;</i> 2. <i>Are pre-packaged for distribution as medical products;</i> <i>and</i> 3. <i>Are authorised by a state authority to be marketed as medical products.</i>

Category Code	Item Description
	<p>e. Fungi, whether natural, enhanced or modified, either in the form of “isolated live cultures” or as material including living material which has been deliberately inoculated or contaminated with such cultures, as follows:</p> <ol style="list-style-type: none"> 1. <i>Coccidioides immitis</i>; 2. <i>Coccidioides posadasii</i>. <p><u>Note</u> Category Code 1C351 does not include “vaccines” or “immunotoxins”.</p>
1C353	<p>Genetic elements and genetically modified organisms, as follows:</p> <ol style="list-style-type: none"> a. Genetically modified organisms or genetic elements that contain nucleic acid sequences associated with pathogenicity of organisms specified in Category Code 1C351.a., 1C351.c., 1C351.e. or 1C354; b. Genetically modified organisms or genetic elements that contain nucleic acid sequences coding for any of the “toxins” specified in Category Code 1C351.d. or “sub-units of toxins” thereof. <p><u>Technical Notes</u></p> <ol style="list-style-type: none"> 1. <i>Genetically modified organisms include organisms in which the genetic material (nucleic acid sequences) has been altered in a way that does not occur naturally by mating and/or natural recombination, and encompasses those produced artificially in whole or in part.</i> 2. <i>Genetic elements include inter alia chromosomes, genomes, plasmids, transposons, and vectors whether genetically modified or unmodified, or chemically synthesised in whole or in part.</i> 3. <i>Nucleic acid sequences associated with the pathogenicity of any of the microorganisms specified in Category Code 1C351.a., 1C351.c., 1C351.e. or 1C354 means any sequence specific to the specified microorganism that:</i> <ol style="list-style-type: none"> a. <i>In itself or through its transcribed or translated products represents a significant hazard to human, animal or plant health; <u>or</u></i>

Category Code	Item Description
	<p data-bbox="539 454 1267 589">b. <i>Is known to enhance the ability of a specified microorganism, or any other organism into which it may be inserted or otherwise integrated, to cause serious harm to humans, animals or plant health.</i></p> <p data-bbox="475 607 536 633"><u>Note</u></p> <p data-bbox="475 645 1267 808"><i>Category Code 1C353 does not extend to nucleic acid sequences associated with the pathogenicity of enterohaemorrhagic Escherichia coli, serotype O157 and other verotoxin producing strains, other than those coding for the verotoxin, or for its sub-units.</i></p>
1C354	<p data-bbox="475 880 810 907">Plant pathogens, as follows:</p> <p data-bbox="475 929 1267 1059">a. Viruses, whether natural, enhanced or modified, either in the form of “isolated live cultures” or as material including living material which has been deliberately inoculated or contaminated with such cultures, as follows:</p> <ol data-bbox="539 1081 1267 1193" style="list-style-type: none"> <li data-bbox="539 1081 1267 1149">1. Andean potato latent virus (Potato Andean latent tymovirus); <li data-bbox="539 1167 930 1193">2. Potato spindle tuber viroid; <p data-bbox="475 1216 1267 1346">b. Bacteria, whether natural, enhanced or modified, either in the form of “isolated live cultures” or as material which has been deliberately inoculated or contaminated with such cultures, as follows:</p> <ol data-bbox="539 1368 1267 1760" style="list-style-type: none"> <li data-bbox="539 1368 914 1395">1. Xanthomonas albilineans; <li data-bbox="539 1417 1267 1507">2. Xanthomonas axonopodis pv. citri (Xanthomonas campestris pv. citri A) [Xanthomonas campestris pv. citri]; <li data-bbox="539 1529 1267 1597">3. Xanthomonas oryzae pv. oryzae (Pseudomonas campestris pv. oryzae); <li data-bbox="539 1619 1267 1709">4. Clavibacter michiganensis subsp. sepedonicus (Corynebacterium michiganensis subsp. sepedonicum or Corynebacterium sepedonicum); <li data-bbox="539 1731 1094 1760">5. Ralstonia solanacearum, race 3, biovar 2;

<i>Category Code</i>	<i>Item Description</i>
	<p>c. Fungi, whether natural, enhanced or modified, either in the form of “isolated live cultures” or as material which has been deliberately inoculated or contaminated with such cultures, as follows:</p> <ol style="list-style-type: none"> 1. Colletotrichum kahawae (Colletotrichum coffeanum var. virulans); 2. Cochliobolus miyabeanus (Helminthosporium oryzae); 3. Microcyclus ulei (syn. Dothidella ulei); 4. Puccinia graminis ssp. graminis var. graminis/Puccinia graminis ssp. graminis var. stakmanii (Puccinia graminis [syn. Puccinia graminis f. sp. tritici]); 5. Puccinia striiformis (syn. Puccinia glumarum); 6. Magnaporthe oryzae (Pyricularia oryzae); 7. Peronosclerospora philippinensis (Peronosclerospora sacchari); 8. Sclerophthora rayssiae var. zea; 9. Synchytrium endobioticum; 10. Tilletia indica; 11. Thecaphora solani.
1C450	<p>Toxic chemicals and toxic chemical precursors, as follows, and “chemical mixtures” containing one or more thereof:</p> <p><u>N.B.</u> See also Category Codes 1C350, 1C351.d. and Division 2 of Part 1 of this Schedule.</p> <p>a. Toxic chemicals, as follows:</p> <ol style="list-style-type: none"> 1. Amiton: O,O-Diethyl S-[2-(diethylamino)ethyl] phosphorothiolate (78-53-5) and corresponding alkylated or protonated salts; 2. PFIB: 1,1,3,3,3-Pentafluoro-2-(trifluoromethyl)-1-propene (382-21-8); 3. See BZ: 3-Quinuclidinyl benzilate (6581-06-2) in Division 2 of Part 1 of this Schedule;

Category Code	Item Description
	<p>4. Phosgene: Carbonyl dichloride (75-44-5);</p> <p>5. Cyanogen chloride (506-77-4);</p> <p>6. Hydrogen cyanide (74-90-8);</p> <p>7. Chloropicrin: Trichloronitromethane (76-06-2);</p> <p>b. Toxic chemical precursors, as follows:</p> <p>1. Chemicals, other than those specified in Division 2 of Part 1 of this Schedule or in Category Code 1C350, containing a phosphorus atom to which is bonded one methyl, ethyl or propyl (normal or iso) group but not further carbon atoms;</p> <p><i>Note</i> <i>Category Code 1C450.b.1. does not include Fonofos: O-Ethyl S-phenyl ethylphosphonothiolothionate (944-22-9).</i></p> <p>2. N,N-Dialkyl [methyl, ethyl or propyl (normal or iso)] phosphoramidic dihalides, other than N,N-Dimethylaminophosphoryl dichloride;</p> <p><i>N.B.</i> <i>See Category Code 1C350.57. for N,N-Dimethylaminophosphoryl dichloride.</i></p> <p>3. Dialkyl [methyl, ethyl or propyl (normal or iso)] N,N-dialkyl [methyl, ethyl or propyl (normal or iso)]-phosphoramidates, other than Diethyl-N,N-dimethylphosphoramidate which is specified in Category Code 1C350;</p> <p>4. N,N-Dialkyl [methyl, ethyl or propyl (normal or iso)] aminoethyl-2-chlorides and corresponding protonated salts, other than N,N-Diisopropyl-(beta)-aminoethyl chloride or N,N-Diisopropyl-(beta)-aminoethyl chloride hydrochloride which are specified in Category Code 1C350;</p> <p>5. N,N-Dialkyl [methyl, ethyl or propyl (normal or iso)] aminoethane-2-ols and corresponding protonated salts, other than N,N-Diisopropyl-(beta)-aminoethanol (96-80-0) and N,N-Diethylaminoethanol (100-37-8) which are specified in Category Code 1C350;</p>

Category Code	Item Description
	<p><u>Note</u> Category Code 1C450.b.5. does not include the following:</p> <ol style="list-style-type: none"> a. N,N-Dimethylaminoethanol (108-01-0) and corresponding protonated salts; b. Protonated salts of N,N-Diethylaminoethanol (100-37-8). <ol style="list-style-type: none"> 6. N,N-Dialkyl [methyl, ethyl or propyl (normal or iso)] aminoethane-2-thiols and corresponding protonated salts, other than N,N-Diisopropyl-(beta)-aminoethane thiol which is specified in Category Code 1C350; 7. See Category Code 1C350 for ethyldiethanolamine (139-87-7); 8. Methyldiethanolamine (105-59-9). <p><u>Note 1</u> Category Code 1C450 does not include “chemical mixtures” containing one or more of the chemicals specified in Category Codes 1C450.a.4., .a.5., .a.6., .a.7. and .b.8. in which no individually specified chemical constitutes more than 30% by weight of the mixture.</p> <p><u>Note 2</u> Category Code 1C450 does not include products identified as consumer goods packaged for retail sale for personal use or packaged for individual use.</p>
1D	Software
1D001	“Software” specially designed or modified for the “development”, “production” or “use” of equipment specified in Category Codes 1B001 to 1B003.
1D002	“Software” for the “development” of organic “matrix”, metal “matrix” or carbon “matrix” laminates or “composites”.

<i>Category Code</i>	<i>Item Description</i>
1D003	“Software” specially designed or modified to enable equipment to perform the functions of equipment specified in Category Code 1A004.c. or 1A004.d.
1D101	“Software” specially designed or modified for the operation or maintenance of goods specified in Category Code 1B101, 1B102, 1B115, 1B117, 1B118 or 1B119.
1D103	“Software” specially designed for analysis of reduced observables such as radar reflectivity, ultraviolet/infrared signatures and acoustic signatures.
1D201	“Software” specially designed for the “use” of goods specified in Category Code 1B201.
1E	Technology
1E001	“Technology” (according to the General Technology Note) for the “development” or “production” of equipment or materials specified in Category Code 1A002 to 1A005, 1A006.b., 1A007 or Category 1B or 1C.
1E002	Other “technology”, as follows: <ul style="list-style-type: none"> a. “Technology” for the “development” or “production” of polybenzothiazoles or polybenzoxazoles; b. “Technology” for the “development” or “production” of fluoroelastomer compounds containing at least one vinyl ether monomer; c. “Technology” for the design or “production” of the following ceramic powders or non-“composite” ceramic materials: <ul style="list-style-type: none"> 1. Ceramic powders having all of the following characteristics: <ul style="list-style-type: none"> a. Are of any of the following compositions: <ul style="list-style-type: none"> 1. Single or complex oxides of zirconium and complex oxides of silicon or aluminium;

<i>Category Code</i>	<i>Item Description</i>
	<ol style="list-style-type: none"> 2. Single nitrides of boron (cubic crystalline forms); 3. Single or complex carbides of silicon or boron; <u>or</u> 4. Single or complex nitrides of silicon; <p>b. Have any of the following total metallic impurities (excluding intentional additions):</p> <ol style="list-style-type: none"> 1. Less than 1,000 ppm for single oxides or carbides; <u>or</u> 2. Less than 5,000 ppm for complex compounds or single nitrides; <u>and</u> <p>c. Being any of the following:</p> <ol style="list-style-type: none"> 1. Zirconia (1314-23-4) with an average particle size equal to or less than 1 μm and no more than 10% of the particles larger than 5 μm; <u>or</u> 2. Other ceramic powders with an average particle size equal to or less than 5 μm and no more than 10% of the particles larger than 10 μm; <p>2. Non-“composite” ceramic materials composed of the materials specified in Category Code 1E002.c.1.;</p> <p><i>Note</i> <i>Category Code 1E002.c.2. does not include “technology” for the design or production of abrasives.</i></p> <p>d. Not used;</p> <p>e. “Technology” for the installation, maintenance or repair of materials specified in Category Code 1C001;</p> <p>f. “Technology” for the repair of “composite” structures, laminates or materials specified in Category Code 1A002, 1C007.c. or 1C007.d.;</p>

<i>Category Code</i>	<i>Item Description</i>
	<p><u>Note</u> <i>Category Code 1E002.f. does not include “technology” for the repair of “civil aircraft” structures using carbon “fibrous or filamentary materials” and epoxy resins, contained in “aircraft” manufacturers’ manuals.</i></p> <p>g. “Libraries” specially designed or modified to enable equipment to perform the functions of equipment specified in Category Code 1A004.c. or 1A004.d.</p>
1E101	<p>“Technology” (according to the General Technology Note) for the “use” of goods specified in Category Code 1A102, 1B001, 1B101, 1B102, 1B115 to 1B119, 1C001, 1C101, 1C107, 1C111, 1C116, 1C117, 1C118, 1D101 or 1D103.</p>
1E102	<p>“Technology” (according to the General Technology Note) for the “development” of “software” specified in Category Code 1D001, 1D101 or 1D103.</p>
1E103	<p>“Technology” for the regulation of temperature, pressure or atmosphere in autoclaves or hydroclaves, when used for the “production” of “composites” or partially processed “composites”.</p>
1E104	<p>“Technology” relating to the “production” of pyrolytically derived materials formed on a mould, mandrel or other substrate from precursor gases which decompose in the 1,573 K (1,300°C) to 3,173 K (2,900°C) temperature range at pressures of 130 Pa to 20 kPa.</p>
	<p><u>Note</u> <i>Category Code 1E104 includes “technology” for the composition of precursor gases, flow-rates and process control schedules and parameters.</i></p>

<i>Category Code</i>	<i>Item Description</i>
1E201	“Technology” (according to the General Technology Note) for the “use” of goods specified in Category Code 1A002, 1A007, 1A202, 1A225 to 1A227, 1B201, 1B225 to 1B234, 1C002.b.3. or .b.4., 1C010.b., 1C202, 1C210, 1C216, 1C225 to 1C241 or 1D201.
1E202	“Technology” (according to the General Technology Note) for the “development” or “production” of goods specified in Category Code 1A007, 1A202 or 1A225 to 1A227.
1E203	“Technology” (according to the General Technology Note) for the “development” of “software” specified in Category Code 1D201.

Category Code	Item Description
CATEGORY 2 — MATERIALS PROCESSING	
2A	<p>Systems, Equipment and Components</p> <p><u>N.B.</u> For quiet running bearings, see Division 2 of Part 1 of this Schedule.</p>
2A001	<p>Anti-friction bearings and bearing systems, as follows, and components therefor:</p> <p><u>N.B.</u> See also Category Code 2A101.</p> <p><u>Note</u> Category Code 2A001 does not include balls with tolerances specified by the manufacturer in accordance with ISO 3290 as grade 5 or worse.</p> <p>a. Ball bearings and solid roller bearings, having all tolerances specified by the manufacturer in accordance with ISO 492 Tolerance Class 4 (or national equivalents), or better, and having both rings and rolling elements (Ref. ISO 5593), made from monel or beryllium;</p> <p><u>Note</u> Category Code 2A001.a. does not include tapered roller bearings.</p> <p>b. Not used;</p> <p>c. Active magnetic bearing systems using any of the following:</p> <ol style="list-style-type: none"> 1. Materials with flux densities of 2 T or greater and yield strengths greater than 414 MPa; 2. All-electromagnetic 3D homopolar bias designs for actuators; <u>or</u> 3. High temperature (450 K (177°C) and above) position sensors.

<i>Category Code</i>	<i>Item Description</i>
2A101	<p>Radial ball bearings, other than those specified in Category Code 2A001, having all tolerances specified in accordance with ISO 492 Tolerance Class 2 (or ANSI/ABMA Std 20 Tolerance Class ABEC-9 or other national equivalents), or better and having all of the following characteristics:</p> <ol style="list-style-type: none"> a. An inner ring bore diameter between 12 mm and 50 mm; b. An outer ring outside diameter between 25 mm and 100 mm; <u>and</u> c. A width between 10 mm and 20 mm.
2A225	<p>Crucibles made of materials resistant to liquid actinide metals, as follows:</p> <ol style="list-style-type: none"> a. Crucibles having both of the following characteristics: <ol style="list-style-type: none"> 1. A volume of between 150 cm³ and 8,000 cm³; <u>and</u> 2. Made of or coated with any of the following materials, or combination of the following materials, having an overall impurity level of 2% or less by weight: <ol style="list-style-type: none"> a. Calcium fluoride (CaF₂); b. Calcium zirconate (metazirconate) (CaZrO₃); c. Cerium sulphide (Ce₂S₃); d. Erbium oxide (erbia) (Er₂O₃); e. Hafnium oxide (hafnia) (HfO₂); f. Magnesium oxide (MgO); g. Nitrided niobium-titanium-tungsten alloy (approximately 50% Nb, 30% Ti, 20% W); h. Yttrium oxide (yttria) (Y₂O₃); <u>or</u> i. Zirconium oxide (zirconia) (ZrO₂); b. Crucibles having both of the following characteristics: <ol style="list-style-type: none"> 1. A volume of between 50 cm³ and 2,000 cm³; <u>and</u> 2. Made of or lined with tantalum, having a purity of 99.9% or greater by weight;

<i>Category Code</i>	<i>Item Description</i>
2A226	<p>c. Crucibles having all of the following characteristics:</p> <ol style="list-style-type: none"> 1. A volume of between 50 cm³ and 2,000 cm³; 2. Made of or lined with tantalum, having a purity of 98% or greater by weight; <u>and</u> 3. Coated with tantalum carbide, nitride, boride, or any combination thereof. <p>Valves having all of the following characteristics:</p> <ol style="list-style-type: none"> a. A 'nominal size' of 5 mm or greater; b. Having a bellows seal; <u>and</u> c. Wholly made of or lined with aluminium, aluminium alloy, nickel, or nickel alloy containing more than 60% nickel by weight. <p><u>Technical Note</u> <i>For valves with different inlet and outlet diameters, the 'nominal size' in Category Code 2A226 refers to the smallest diameter.</i></p>
2B	<p>Test, Inspection and Production Equipment</p> <p><u>Technical Notes</u></p> <ol style="list-style-type: none"> 1. <i>Secondary parallel contouring axes, (e.g. the w-axis on horizontal boring mills or a secondary rotary axis the centre line of which is parallel to the primary rotary axis) are not counted in the total number of contouring axes. Rotary axes need not rotate over 360°. A rotary axis can be driven by a linear device (e.g. a screw or a rack-and-pinion).</i> 2. <i>For the purpose of Category 2B, the number of axes which can be coordinated simultaneously for "contouring control" is the number of axes along or around which, during processing of the workpiece, simultaneous and interrelated motions are performed between the workpiece and a tool. This does not include any additional axes along or around which other relative movement within the machine are performed such as:</i>

Category Code	Item Description
	<p>a. Wheel-dressing systems in grinding machines;</p> <p>b. Parallel rotary axes designed for mounting of separate workpieces;</p> <p>c. Co-linear rotary axes designed for manipulating the same workpiece by holding it in a chuck from different ends.</p> <p>3. Axis nomenclature must be in accordance with International Standard ISO 841:2001, Industrial automation systems and integration - Numerical control of machines - Coordinate system and Motion nomenclature.</p> <p>4. For the purposes of Category Codes 2B001 to 2B009, a “tilting spindle” is counted as a rotary axis.</p> <p>5. Stated “unidirectional positioning repeatability” may be used for each machine tool model as an alternative to individual machine tests and is determined as follows:</p> <p>a. Select five machines of a model to be evaluated;</p> <p>b. Measure the linear axis repeatability (R_{\uparrow}, R_{\downarrow}) according to ISO 230-2:2014 and evaluate “unidirectional positioning repeatability” for each axis of each of the five machines;</p> <p>c. Determine the arithmetic mean value of the “unidirectional positioning repeatability” – values for each axis of all five machines together. These arithmetic mean values of “unidirectional positioning repeatability” (\overline{UPR}) become the stated value of each axis for the model ($\overline{UPR}_x, \overline{UPR}_y, \dots$);</p> <p>d. Since the Category 2 list refers to each linear axis there will be as many stated “unidirectional positioning repeatability” values as there are linear axes;</p>

Category Code	Item Description
	<p>e. If any axis of a machine model not included under Category Codes 2B001.a. to 2B001.c. has a stated “unidirectional positioning repeatability” equal to or less than the specified “unidirectional positioning repeatability” of each machine tool model plus 0.7 μm, the builder should be required to reaffirm the accuracy level once every eighteen months.</p> <p>6. For the purposes of Category Codes 2B001.a. to 2B001.c., measurement uncertainty for the “unidirectional positioning repeatability” of machine tools, as defined in the International Standard ISO 230-2:2014 or national equivalents, must not be considered.</p> <p>7. For the purposes of Category Codes 2B001.a. to 2B001.c., the measurement of axes must be made according to test procedures in 5.3.2. of ISO 230-2:2014. Tests for axes longer than 2 m must be made over 2 m segments. Axes longer than 4 m require multiple tests (e.g., two tests for axes longer than 4 m and up to 8 m, three tests for axes longer than 8 m and up to 12 m), each over 2 m segments and distributed in equal intervals over the axis length. Test segments are equally spaced along the full axis length, with any excess length equally divided at the beginning, in between, and at the end of the test segments. The smallest “unidirectional positioning repeatability” value of all test segments is to be reported.</p>
2B001	<p>Machine tools and any combination thereof, for removing (or cutting) metals, ceramics or “composites”, which, according to the manufacturer’s technical specification, can be equipped with electronic devices for “numerical control”, as follows:</p> <p><u>N.B.</u> See also Category Code 2B201.</p> <p><u>Note 1</u> Category Code 2B001 does not include special purpose machine tools limited to the manufacture of gears. For such machines, see Category Code 2B003.</p> <p><u>Note 2</u> Category Code 2B001 does not include special purpose machine tools limited to the manufacture of any of the following:</p>

Category Code	Item Description
	<p>a. Crankshafts or camshafts;</p> <p>b. Tools or cutters;</p> <p>c. Extruder worms;</p> <p>d. Engraved or faceted jewellery parts;<u>or</u></p> <p>e. Dental prostheses.</p> <p><u>Note 3</u> A machine tool having at least two of the three turning, milling or grinding capabilities (e.g. a turning machine with milling capability), is treated as coming within those entries in Category Codes 2B001.a., .b. and .c. that are applicable to its capabilities.</p> <p><u>N.B.</u> For optical finishing machines, see Category Code 2B002.</p> <p>a. Machine tools for turning having two or more axes which can be coordinated simultaneously for “contouring control” having any of the following characteristics:</p> <ol style="list-style-type: none"> 1. “Unidirectional positioning repeatability” equal to or less (better) than 0.9 µm along one or more linear axes with a travel length less than 1 m; <u>or</u> 2. “Unidirectional positioning repeatability” equal to or less (better) than 1.1 µm along one or more linear axes with a travel length equal to or greater than 1 m; <p><u>Note 1</u> Category Code 2B001.a. does not include turning machines specially designed for producing contact lenses, having both of the following characteristics:</p> <ol style="list-style-type: none"> a. Machine controller limited to using ophthalmic based “software” for part programming data input; <u>and</u> b. No vacuum chucking. <p><u>Note 2</u> Category Code 2B001.a. does not include bar machines (Swissturn), limited to machining only bar feed through, if maximum bar diameter is equal to or less than 42 mm and there is no capability of mounting chucks. Machines may have drilling and/or milling capabilities for machining parts with diameters less than 42 mm.</p>

<i>Category Code</i>	<i>Item Description</i>
	<p>b. Machine tools for milling having any of the following characteristics:</p> <ol style="list-style-type: none"> 1. Three linear axes plus one rotary axis which can be coordinated simultaneously for “contouring control” having any of the following characteristics: <ol style="list-style-type: none"> a. “Unidirectional positioning repeatability” equal to or less (better) than 0.9 μm along one or more linear axes with a travel length less than 1 m; <u>or</u> b. “Unidirectional positioning repeatability” equal to or less (better) than 1.1 μm along one or more linear axes with a travel length equal to or greater than 1 m; 2. Five or more axes which can be coordinated simultaneously for “contouring control” having any of the following characteristics: <p><u><i>N.B.</i></u> <i>‘Parallel mechanism machine tools’ are specified in Category Code 2B001.b.2.d.</i></p> <ol style="list-style-type: none"> a. “Unidirectional positioning repeatability” equal to or less (better) than 0.9 μm along one or more linear axes with a travel length less than 1 m; b. “Unidirectional positioning repeatability” equal to or less (better) than 1.4 μm along one or more linear axes with a travel length equal to or greater than 1 m and less than 4 m; c. “Unidirectional positioning repeatability” equal to or less (better) than 6 μm along one or more linear axes with a travel length equal to or greater than 4 m; <u>or</u> d. Being a ‘parallel mechanism machine tool’; <p><u><i>Technical Note</i></u> <i>A ‘parallel mechanism machine tool’ is a machine tool having multiple rods which are linked with a platform and actuators; each of the actuators operates the respective rod simultaneously and independently.</i></p>

<i>Category Code</i>	<i>Item Description</i>
	<ul style="list-style-type: none"> 3. A “unidirectional positioning repeatability” for jig boring machines, equal to or less (better) than 1.1 μm along one or more linear axes; <u>or</u> 4. Fly cutting machines having all of the following characteristics: <ul style="list-style-type: none"> a. Spindle “run-out” and “camming” less (better) than 0.0004 mm TIR; <u>and</u> b. Angular deviation of slide movement (yaw, pitch and roll) less (better) than 2 seconds of arc, TIR over 300 mm of travel; c. Machine tools for grinding having any of the following characteristics: <ul style="list-style-type: none"> 1. Having all of the following characteristics: <ul style="list-style-type: none"> a. “Unidirectional positioning repeatability” equal to or less (better) than 1.1 μm along one or more linear axes; <u>and</u> b. Three or more axes which can be coordinated simultaneously for “contouring control”; <u>or</u> 2. Five or more axes which can be coordinated simultaneously for “contouring control” having any of the following characteristics: <ul style="list-style-type: none"> a. “Unidirectional positioning repeatability” equal to or less (better) than 1.1 μm along one or more linear axes with a travel length less than 1 m; b. “Unidirectional positioning repeatability” equal to or less (better) than 1.4 μm along one or more linear axes with a travel length equal to or greater than 1 m and less than 4 m; <u>or</u>

<i>Category Code</i>	<i>Item Description</i>
	<p data-bbox="624 454 1272 584">c. “Unidirectional positioning repeatability” equal to or less (better) than 6 μm along one or more linear axes with a travel length equal to or greater than 4 m;</p> <p data-bbox="539 607 600 633"><i>Note</i></p> <p data-bbox="539 645 1272 712"><i>Category Code 2B001.c. does not include grinding machines as follows:</i></p> <p data-bbox="539 730 1272 824">a. <i>Cylindrical external, internal, and external-internal grinding machines, having all of the following characteristics:</i></p> <ol data-bbox="624 846 1272 958" style="list-style-type: none"> <li data-bbox="624 846 1118 880">1. <i>Limited to cylindrical grinding; <u>and</u></i> <li data-bbox="624 898 1272 958">2. <i>Limited to a maximum workpiece capacity of 150 mm outside diameter or length;</i> <p data-bbox="539 981 1272 1077">b. <i>Machines designed specifically as jig grinders that do not have a z-axis or a w-axis, with a “unidirectional positioning repeatability” less (better) than 1.1 μm;</i></p> <p data-bbox="539 1099 810 1126">c. <i>Surface grinders.</i></p> <p data-bbox="475 1149 1272 1245">d. <i>Electrical discharge machines (EDM) of the non-wire type which have two or more rotary axes which can be coordinated simultaneously for “contouring control”;</i></p> <p data-bbox="475 1267 1272 1335">e. <i>Machine tools for removing metals, ceramics or “composites”, having all of the following characteristics:</i></p> <ol data-bbox="539 1357 1272 1812" style="list-style-type: none"> <li data-bbox="539 1357 1272 1384">1. <i>Removing material by means of any of the following:</i> <ol data-bbox="624 1402 1272 1559" style="list-style-type: none"> <li data-bbox="624 1402 1272 1462">a. <i>Water or other liquid jets, including those employing abrasive additives;</i> <li data-bbox="624 1480 906 1507">b. <i>Electron beam; <u>or</u></i> <li data-bbox="624 1525 914 1559">c. <i>“Laser” beam; <u>and</u></i> <li data-bbox="539 1581 1272 1641">2. <i>At least two rotary axes having all of the following characteristics:</i> <ol data-bbox="624 1664 1272 1812" style="list-style-type: none"> <li data-bbox="624 1664 1272 1731">a. <i>Can be coordinated simultaneously for “contouring control”; <u>and</u></i> <li data-bbox="624 1749 1272 1812">b. <i>A positioning “accuracy” of less (better) than 0.003°;</i>

<i>Category Code</i>	<i>Item Description</i>
2B002	<p>f. Deep-hole-drilling machines and turning machines modified for deep-hole-drilling, having a maximum depth-of-bore capability exceeding 5 m.</p> <p>“Numerically controlled” optical finishing machine tools equipped for selective material removal to produce non-spherical optical surfaces having all of the following characteristics:</p> <ol style="list-style-type: none"> a. Finishing the form to less (better) than 1 μm; b. Finishing to a roughness less (better) than 100 nm rms; c. Four or more axes which can be coordinated simultaneously for “contouring control”; <u>and</u> d. Using any of the following processes: <ol style="list-style-type: none"> 1. Magnetorheological finishing (‘MRF’); 2. Electrorheological finishing (‘ERF’); 3. ‘Energetic particle beam finishing’; 4. ‘Inflatable membrane tool finishing’; <u>or</u> 5. ‘Fluid jet finishing’. <p><u>Technical Note</u> For the purpose of Category Code 2B002:</p> <ol style="list-style-type: none"> a. ‘MRF’ is a material removal process using an abrasive magnetic fluid whose viscosity is controlled by a magnetic field. b. ‘ERF’ is a removal process using an abrasive fluid whose viscosity is controlled by an electric field. c. ‘Energetic particle beam finishing’ uses Reactive Atom Plasmas (RAP) or ion-beams to selectively remove material. d. ‘Inflatable membrane tool finishing’ is a process that uses a pressurised membrane that deforms to contact the workpiece over a small area. e. ‘Fluid jet finishing’ makes use of a fluid stream for material removal.

<i>Category Code</i>	<i>Item Description</i>
2B003	<p>“Numerically controlled” or manual machine tools, and specially designed components, controls and accessories therefor, specially designed for the shaving, finishing, grinding or honing of hardened ($R_c = 40$ or more) spur, helical and double-helical gears with a pitch diameter exceeding 1,250 mm and a face width of 15% of pitch diameter or larger finished to a quality of AGMA 14 or better (equivalent to ISO 1328 class 3).</p>
2B004	<p>Hot “isostatic presses” having all of the following characteristics, and specially designed components and accessories therefor:</p> <p><u>N.B.</u> <i>See also Category Codes 2B104 and 2B204.</i></p> <ol style="list-style-type: none"> a. A controlled thermal environment within the closed cavity and a chamber cavity with an inside diameter of 406 mm or more; <u>and</u> b. Having any of the following characteristics: <ol style="list-style-type: none"> 1. A maximum working pressure exceeding 207 MPa; 2. A controlled thermal environment exceeding 1,773 K (1,500°C); <u>or</u> 3. A facility for hydrocarbon impregnation and removal of resultant gaseous degradation products. <p><u>Technical Note</u> <i>The inside chamber dimension is that of the chamber in which both the working temperature and the working pressure are achieved and does not include fixtures. That dimension will be the smaller of either the inside diameter of the pressure chamber or the inside diameter of the insulated furnace chamber, depending on which of the two chambers is located inside the other.</i></p> <p><u>N.B.</u> <i>For specially designed dies, moulds and tooling, see Category Codes 1B003, 9B009 and Division 2 of Part 1 of this Schedule.</i></p>

<i>Category Code</i>	<i>Item Description</i>
2B005	<p>Equipment specially designed for the deposition, processing and in-process control of inorganic overlays, coatings and surface modifications, as follows, for non-electronic substrates, by processes shown in the Table and associated Notes following Category Code 2E003.f., and specially designed automated handling, positioning, manipulation and control components therefor:</p> <ol style="list-style-type: none"> a. Chemical vapour deposition (CVD) production equipment having both of the following characteristics: <ul style="list-style-type: none"> <u>N.B.</u> <i>See also Category Code 2B105.</i> <ol style="list-style-type: none"> 1. A process modified for one of the following: <ol style="list-style-type: none"> a. Pulsating CVD; b. Controlled nucleation thermal deposition (CNTD); <u>or</u> c. Plasma enhanced or plasma assisted CVD; <u>and</u> 2. Having any of the following characteristics: <ol style="list-style-type: none"> a. Incorporating high vacuum (equal to or less than 0.01 Pa) rotating seals; <u>or</u> b. Incorporating <i>in situ</i> coating thickness control; b. Ion implantation production equipment having beam currents of 5 mA or more; c. Electron beam physical vapour deposition (EB-PVD) production equipment incorporating power systems rated for over 80 kW and having any of the following: <ol style="list-style-type: none"> 1. A liquid pool level “laser” control system which regulates precisely the ingots feed rate; <u>or</u> 2. A computer controlled rate monitor operating on the principle of photo-luminescence of the ionised atoms in the evaporant stream to control the deposition rate of a coating containing two or more elements;

<i>Category Code</i>	<i>Item Description</i>
	<p>d. Plasma spraying production equipment having any of the following characteristics:</p> <ol style="list-style-type: none"> 1. Operating at reduced pressure controlled atmosphere (equal to or less than 10 kPa measured above and within 300 mm of the gun nozzle exit) in a vacuum chamber capable of evacuation down to 0.01 Pa prior to the spraying process; <u>or</u> 2. Incorporating <i>in situ</i> coating thickness control; <p>e. Sputter deposition production equipment capable of current densities of 0.1 mA/mm² or higher at a deposition rate of 15 µm/h or more;</p> <p>f. Cathodic arc deposition production equipment incorporating a grid of electromagnets for steering control of the arc spot on the cathode;</p> <p>g. Ion plating production equipment capable of the <i>in situ</i> measurement of any of the following:</p> <ol style="list-style-type: none"> 1. Coating thickness on the substrate and rate control; <u>or</u> 2. Optical characteristics. <p><u>Note</u> <i>Category Code 2B005 does not include chemical vapour deposition, cathodic arc, sputter deposition, ion plating or ion implantation equipment, specially designed for cutting or machining tools.</i></p>

Category Code	Item Description
2B006	<p>Dimensional inspection or measuring systems, equipment and “electronic assemblies”, as follows:</p> <p>a. Computer controlled or “numerically controlled” Coordinate Measuring Machines (CMM), having a three dimensional (volumetric) maximum permissible error of length measurement ($E_{0,MPE}$) at any point within the operating range of the machine (i.e. within the length of axes) equal to or less (better) than $(1.7 + L/1,000) \mu\text{m}$ (L is the measured length in mm), according to ISO 10360-2 (2009);</p> <p><i>Technical Note</i></p> <p><i>The $E_{0,MPE}$ of the most accurate configuration of the CMM specified by the manufacturer (e.g. best of the following: probe, stylus length, motion parameters, environment) and with “all compensations available” must be compared to the $1.7 + L/1,000 \mu\text{m}$ threshold.</i></p> <p><i>N.B.</i></p> <p><i>See also Category Code 2B206.</i></p> <p>b. Linear and angular displacement measuring instruments, as follows:</p> <p>1. ‘Linear displacement’ measuring instruments having any of the following:</p> <p><i>Note</i></p> <p><i>Interferometer and optical-encoder displacement measuring systems containing a “laser” are only included in Category Codes 2B006.b.1.c. and 2B206.c.</i></p> <p><i>Technical Note</i></p> <p><i>For the purpose of Category Code 2B006.b.1., ‘linear displacement’ means the change of distance between the measuring probe and the measured object.</i></p> <p>a. Non-contact type measuring systems with a “resolution” equal to or less (better) than $0.2 \mu\text{m}$ within a measuring range up to 0.2 mm;</p> <p>b. Linear Variable Differential Transformer (LVDT) systems having both of the following characteristics:</p>

<i>Category Code</i>	<i>Item Description</i>
	<ol style="list-style-type: none"> 1. Having any of the following characteristics: <ol style="list-style-type: none"> a. “Linearity” equal to or less (better) than 0.1% measured from 0 to the ‘full operating range’, for LVDTs with a ‘full operating range’ up to and including ± 5 mm; <u>or</u> b. “Linearity” equal to or less (better) than 0.1% measured from 0 to 5 mm for LVDTs with a ‘full operating range’ greater than ± 5 mm; <u>and</u> 2. Drift equal to or less (better) than 0.1% per day at a standard ambient test room temperature ± 1 K; <p><i>Technical Note</i> <i>For the purpose of Category Code 2B006.b.1.b., ‘full operating range’ is half of the total possible linear displacement of the LVDT. For example, LVDTs with a ‘full operating range’ up to and including ± 5 mm can measure a total possible linear displacement of 10 mm.</i></p> <ol style="list-style-type: none"> c. Measuring systems having all of the following characteristics: <ol style="list-style-type: none"> 1. Containing a “laser”; 2. A “resolution” over their full scale of 0.2 nm or less (better); <u>and</u> 3. Capable of achieving a “measurement uncertainty” equal to or less (better) than $(1.6 + L/2,000)$ nm (L is the measured length in mm) at any point within a measuring range, when compensated for the refractive index of air and measured over a period of 30 seconds at a temperature of $20 \pm 0.01^\circ\text{C}$; <u>or</u> d. “Electronic assemblies” specially designed to provide feedback capability in systems specified in Category Code 2B006.b.1.c.;

Category Code	Item Description
	<p><u>Note</u> <i>Category Code 2B006.b.1. does not include measuring interferometer systems, with an automatic control system that is designed to use no feedback techniques, containing a “laser” to measure slide movement errors of machine-tools, dimensional inspection machines or similar equipment.</i></p> <p>2. Angular displacement measuring instruments having an angular position “accuracy” equal to or less (better) than 0.00025°;</p> <p><u>Note</u> <i>Category Code 2B006.b.2. does not include optical instruments, such as autocollimators, using collimated light (e.g. “laser light”) to detect angular displacement of a mirror.</i></p> <p>c. Equipment for measuring surface roughness (including surface defects), by measuring optical scatter with a sensitivity of 0.5 nm or less (better).</p> <p><u>Note</u> <i>Category Code 2B006 includes machine tools, other than those specified by Category Code 2B001, that can be used as measuring machines if they meet or exceed the criteria specified for the measuring machine function.</i></p>
2B007	<p>“Robots” having any of the following characteristics and specially designed controllers and “end-effectors” therefor:</p> <p><u>N.B.</u> <i>See also Category Code 2B207.</i></p> <p>a. Capable in real-time of full three-dimensional image processing or full three-dimensional ‘scene analysis’ to generate or modify “programs” or to generate or modify numerical program data;</p>

Category Code	Item Description
	<p><u>Technical Note</u> The 'scene analysis' limitation does not include approximation of the third dimension by viewing at a given angle, or limited grey scale interpretation for the perception of depth or texture for the approved tasks (2½ D).</p> <p>b. Specially designed to comply with national safety standards applicable to potentially explosive munitions environments;</p> <p><u>Note</u> Category Code 2B007.b. does not include "robots" specially designed for paint-spraying booths.</p> <p>c. Specially designed or rated as radiation-hardened to withstand a total radiation dose greater than 5×10^3 Gy (silicon) without operational degradation; <u>or</u></p> <p><u>Technical Note</u> The term Gy (silicon) refers to the energy in Joules per kilogram absorbed by an unshielded silicon sample when exposed to ionising radiation.</p> <p>d. Specially designed to operate at altitudes exceeding 30,000 m.</p>
2B008	<p>Assemblies or units, specially designed for machine tools, or dimensional inspection or measuring systems and equipment, as follows:</p> <p>a. Linear position feedback units having an overall "accuracy" less (better) than $(800 + (600 \times L/1,000))$ nm (L equals the effective length in mm);</p> <p><u>N.B.</u> For "laser" systems, see also Category Codes 2B006.b.1.c., 2B006.b.1.d. and 2B206.c.</p> <p>b. Rotary position feedback units having an "accuracy" less (better) than 0.00025°;</p> <p><u>N.B.</u> For "laser" systems, see also Note to Category Code 2B006.b.2.</p>

Category Code	Item Description
	<p><u>Note</u> Category Codes 2B008.a. and 2B008.b. include units, which are designed to determine the positioning information for feedback control, such as inductive type devices, graduated scales, infrared systems or “laser” systems.</p> <p>c. “Compound rotary tables” and “tilting spindles”, capable of upgrading, according to the manufacturer’s specifications, machine tools to or above the levels specified in Category 2B.</p>
2B009	<p>Spin-forming machines and flow-forming machines, which, according to the manufacturer’s technical specification, can be equipped with “numerical control” units or a computer control and having both of the following characteristics:</p> <p><u>N.B.</u> See also Category Codes 2B109 and 2B209.</p> <p>a. Three or more axes which can be coordinated simultaneously for “contouring control”; <u>and</u></p> <p>b. A roller force more than 60 kN.</p> <p><u>Technical Note</u> For the purpose of Category Code 2B009, machines combining the function of spin-forming and flow-forming are regarded as flow-forming machines.</p>
2B104	<p>“Isostatic presses”, other than those specified in Category Code 2B004, having all of the following characteristics:</p> <p><u>N.B.</u> See also Category Code 2B204.</p> <p>a. Maximum working pressure of 69 MPa or greater;</p> <p>b. Designed to achieve and maintain a controlled thermal environment of 873 K (600°C) or greater; <u>and</u></p> <p>c. Possessing a chamber cavity with an inside diameter of 254 mm or greater.</p>

<i>Category Code</i>	<i>Item Description</i>
2B105	Chemical Vapour Deposition (CVD) furnaces, other than those specified in Category Code 2B005.a., designed or modified for the densification of carbon-carbon composites.
2B109	<p>Flow-forming machines, other than those specified in Category Code 2B009, and specially designed components as follows:</p> <p><u>N.B.</u> See also Category Code 2B209.</p> <p>a. Flow-forming machines having both of the following characteristics:</p> <ol style="list-style-type: none"> 1. According to the manufacturer's technical specification, can be equipped with "numerical control" units or a computer control, even when not equipped with such units; <u>and</u> 2. With more than two axes which can be coordinated simultaneously for "contouring control"; <p>b. Specially designed components for flow-forming machines specified in Category Code 2B009 or 2B109.a.</p> <p><u>Note</u> Category Code 2B109 does not include machines that are not usable in the production of propulsion components and equipment (e.g. motor cases) for systems specified in Category Code 9A005, 9A007.a. or 9A105.a.</p> <p><u>Technical Note</u> Machines combining the function of spin-forming and flow-forming are for the purpose of Category Code 2B109 regarded as flow-forming machines.</p>
2B116	<p>Vibration test systems, equipment and components therefor, as follows:</p> <p>a. Vibration test systems employing feedback or closed loop techniques and incorporating a digital controller, capable of vibrating a system at an acceleration equal to or greater than 10 g rms between 20 Hz and 2 kHz while imparting forces equal to or greater than 50 kN, measured 'bare table';</p>

<i>Category Code</i>	<i>Item Description</i>
	<p>b. Digital controllers, combined with specially designed vibration test software, with a 'real-time control bandwidth' greater than 5 kHz designed for use with vibration test systems specified in Category Code 2B116.a.;</p> <p><i>Technical Note</i> <i>In Category Code 2B116.b., 'real-time control bandwidth' means the maximum rate at which a controller can execute complete cycles of sampling, processing data and transmitting control signals.</i></p> <p>c. Vibration thrusters (shaker units), with or without associated amplifiers, capable of imparting a force equal to or greater than 50 kN, measured 'bare table', and usable in vibration test systems specified in Category Code 2B116.a.;</p> <p>d. Test piece support structures and electronic units designed to combine multiple shaker units in a system capable of providing an effective combined force equal to or greater than 50 kN, measured 'bare table', and usable in vibration systems specified in Category Code 2B116.a.</p> <p><i>Technical Note</i> <i>In Category Code 2B116, 'bare table' means a flat table, or surface, with no fixture or fittings.</i></p>
2B117	Equipment and process controls, other than those specified in Category Code 2B004, 2B005.a., 2B104 or 2B105, designed or modified for densification and pyrolysis of structural composite rocket nozzles and re-entry vehicle nose tips.
2B119	<p>Balancing machines and related equipment, as follows:</p> <p><i>N.B.</i> <i>See also Category Code 2B219.</i></p> <p>a. Balancing machines having all of the following characteristics:</p> <ol style="list-style-type: none"> 1. Not capable of balancing rotors/assemblies having a mass greater than 3 kg;

<i>Category Code</i>	<i>Item Description</i>
	<ol style="list-style-type: none"> 2. Capable of balancing rotors/assemblies at speeds greater than 12,500 rpm; 3. Capable of correcting unbalance in two planes or more; <u>and</u> 4. Capable of balancing to a residual specific unbalance of 0.2 g mm per kg of rotor mass; <p><i>Note</i> Category Code 2B119.a. does not include balancing machines designed or modified for dental or other medical equipment.</p> <ol style="list-style-type: none"> b. Indicator heads designed or modified for use with machines specified in Category Code 2B119.a. <p><i>Technical Note</i> Indicator heads are sometimes known as balancing instrumentation.</p>
2B120	<p>Motion simulators or rate tables having all of the following characteristics:</p> <ol style="list-style-type: none"> a. Two axes or more; b. Designed or modified to incorporate slip rings or integrated non-contact devices capable of transferring electrical power, signal information, or both; <u>and</u> c. Having any of the following characteristics: <ol style="list-style-type: none"> 1. For any single axis having all of the following characteristics: <ol style="list-style-type: none"> a. Capable of rates of 400 degrees/s or more, or 30 degrees/s or less; <u>and</u> b. A rate resolution equal to or less than 6 degrees/s and an accuracy equal to or less than 0.6 degrees/s; 2. Having a worst-case rate stability equal to or better (less) than plus or minus 0.05% averaged over 10 degrees or more; <u>or</u>

<i>Category Code</i>	<i>Item Description</i>
	<p data-bbox="539 454 1272 517">3. A positioning “accuracy” equal to or less (better) than 5 arc second.</p> <p data-bbox="475 539 560 568"><i>Note 1</i></p> <p data-bbox="475 580 1272 678"><i>Category Code 2B120 does not include rotary tables designed or modified for machine tools or for medical equipment. For machine tool rotary tables, see Category Code 2B008.</i></p> <p data-bbox="475 696 560 725"><i>Note 2</i></p> <p data-bbox="475 736 1272 869"><i>Motion simulators or rate tables that satisfy all the characteristics under Category Code 2B120 remain within that Code whether or not slip rings or integrated non-contact devices are fitted on them at time of export.</i></p>
2B121	<p data-bbox="475 938 1272 1037">Positioning tables (equipment capable of precise rotary positioning in any axes), other than those specified in Category Code 2B120, having all of the following characteristics:</p> <p data-bbox="475 1055 1272 1164"> a. Two axes or more; <u>and</u> b. A positioning “accuracy” equal to or less (better) than 5 arc second. </p> <p data-bbox="475 1189 539 1218"><i>Note</i></p> <p data-bbox="475 1229 1272 1328"><i>Category Code 2B121 does not include rotary tables designed or modified for machine tools or for medical equipment. For machine tool rotary tables, see Category Code 2B008.</i></p>
2B122	<p data-bbox="475 1395 1272 1527">Centrifuges capable of imparting accelerations above 100 g and designed or modified to incorporate slip rings or integrated non-contact devices capable of transferring electrical power, signal information, or both.</p> <p data-bbox="475 1547 539 1576"><i>Note</i></p> <p data-bbox="475 1588 1272 1686"><i>Centrifuges that come within the description in Category Code 2B122 remain within that Code whether or not slip rings or integrated non-contact devices are fitted on them at time of export.</i></p>

<i>Category Code</i>	<i>Item Description</i>
2B201	<p>Machine tools and any combination thereof, other than those specified in Category Code 2B001, as follows, for removing or cutting metals, ceramics or “composites”, which, according to the manufacturer’s technical specification, can be equipped with electronic devices for simultaneous “contouring control” in two or more axes:</p> <p><i>Technical Note</i></p> <p><i>Stated positioning accuracy levels derived under the following procedures from measurements made according to ISO 230-2:1988 or national equivalents may be used for each machine tool model if provided to, and accepted by, national authorities instead of individual machine tests. Determination of stated positioning accuracy:</i></p> <ol style="list-style-type: none"> <li data-bbox="464 931 1273 965"><i>a. Select five machines of a model to be evaluated;</i> <li data-bbox="464 981 1273 1048"><i>b. Measure the linear axis accuracies according to ISO 230-2:1988;</i> <li data-bbox="464 1064 1273 1167"><i>c. Determine the accuracy values (A) for each axis of each machine. The method of calculating the accuracy value is described in the ISO 230-2:1988 standard;</i> <li data-bbox="464 1182 1273 1285"><i>d. Determine the average accuracy value of each axis. This average value becomes the stated positioning accuracy of each axis for the model ($\hat{A}_x \hat{A}_y \dots$);</i> <li data-bbox="464 1301 1273 1404"><i>e. Since Category Code 2B201 refers to each linear axis, there will be as many stated positioning accuracy values as there are linear axes;</i> <li data-bbox="464 1420 1273 1648"><i>f. If any axis of a machine tool not included in Category Code 2B201.a., 2B201.b. or 2B201.c. has a stated positioning accuracy of 6 μm or better (less) for grinding machines, and 8 μm or better (less) for milling and turning machines, both according to ISO 230-2:1988, then the builder should be required to reaffirm the accuracy level once every eighteen months.</i>

<i>Category Code</i>	<i>Item Description</i>
	<p>a. Machine tools for milling having any of the following characteristics:</p> <ol style="list-style-type: none"> 1. Positioning accuracies with “all compensations available” equal to or less (better) than 6 μm according to ISO 230-2:1988 or national equivalents along any linear axis; 2. Two or more contouring rotary axes; <u>or</u> 3. Five or more axes which can be coordinated simultaneously for “contouring control”; <p><i>Note</i> <i>Category Code 2B201.a. does not include milling machines having the following characteristics:</i></p> <ol style="list-style-type: none"> a. <i>X-axis travel greater than 2 m; <u>and</u></i> b. <i>Overall positioning accuracy on the x-axis more (worse) than 30 μm.</i> <p>b. Machine tools for grinding having any of the following characteristics:</p> <ol style="list-style-type: none"> 1. Positioning accuracies with “all compensations available” equal to or less (better) than 4 μm according to ISO 230-2:1988 or national equivalents along any linear axis; 2. Two or more contouring rotary axes; <u>or</u> 3. Five or more axes which can be coordinated simultaneously for “contouring control”; <p><i>Note</i> <i>Category Code 2B201.b. does not include grinding machines as follows:</i></p> <ol style="list-style-type: none"> a. <i>Cylindrical external, internal, and external-internal grinding machines having both of the following characteristics:</i> <ol style="list-style-type: none"> 1. <i>Limited to a maximum workpiece capacity of 150 mm outside diameter or length; <u>and</u></i> 2. <i>Axes limited to x, z and c;</i>

Category Code	Item Description
	<p data-bbox="539 454 1273 584">b. Jig grinders that do not have a z-axis or a w-axis with an overall 'positioning accuracy' less (better) than 4 µm according to ISO 230-2:1988 or national equivalents.</p> <p data-bbox="480 607 1273 768">c. Machine tools for turning, that have positioning accuracies with "all compensations available" better (less) than 6 µm according to ISO 230-2:1988 along any linear axis (overall positioning) for machines capable of machining diameters greater than 35 mm;</p> <p data-bbox="539 790 603 819"><u>Note</u></p> <p data-bbox="539 831 1273 1028">Category Code 2B201.c. does not include bar machines (Swissturn), limited to machining only bar feed through, if maximum bar diameter is equal to or less than 42 mm and there is no capability of mounting chucks. Machines may have drilling or milling capabilities, or both for machining parts with diameters less than 42 mm.</p> <p data-bbox="480 1050 560 1079"><u>Note 1</u></p> <p data-bbox="480 1090 1273 1155">Category Code 2B201 does not include special purpose machine tools limited to the manufacture of any of the following parts:</p> <p data-bbox="480 1167 852 1319">a. Gears; b. Crankshafts or camshafts; c. Tools or cutters; <u>or</u> d. Extruder worms.</p> <p data-bbox="480 1341 560 1370"><u>Note 2</u></p> <p data-bbox="480 1382 1273 1512">A machine tool having at least two of the three turning, milling or grinding capabilities (e.g. a turning machine with milling capability) is treated as coming within those entries in Category Code 2B201.a., .b. or .c. that are applicable to its capabilities.</p> <p data-bbox="480 1534 560 1563"><u>Note 3</u></p> <p data-bbox="480 1574 1273 1671">Category Codes 2B201.a.3. and 2B201.b.3. include machines based on a parallel linear kinematic design (e.g., hexapods) that have 5 or more axes none of which are rotary axes.</p>

<i>Category Code</i>	<i>Item Description</i>
2B204	<p>“Isostatic presses”, other than those specified in Category Code 2B004 or 2B104, and related equipment, as follows:</p> <ol style="list-style-type: none"> a. “Isostatic presses” having both of the following characteristics: <ol style="list-style-type: none"> 1. Capable of achieving a maximum working pressure of 69 MPa or greater; <u>and</u> 2. A chamber cavity with an inside diameter in excess of 152 mm; b. Dies, moulds and controls, specially designed for “isostatic presses” specified in Category Code 2B204.a. <p><i>Technical Note</i> <i>In Category Code 2B204, the inside chamber dimension is that of the chamber in which both the working temperature and the working pressure are achieved and does not include fixtures. That dimension will be the smaller of either the inside diameter of the pressure chamber or the inside diameter of the insulated furnace chamber, depending on which of the two chambers is located inside the other.</i></p>
2B206	<p>Dimensional inspection machines, instruments or systems, other than those specified in Category Code 2B006, as follows:</p> <ol style="list-style-type: none"> a. Computer controlled or numerically controlled coordinate measuring machines (CMM) having either of the following characteristics: <ol style="list-style-type: none"> 1. Having only two axes and having a maximum permissible error of length measurement along any axis (one dimensional), identified as any combination of $E_{0x,MPE}$, $E_{0y,MPE}$, or $E_{0z,MPE}$, equal to or less (better) than $(1.25 + L/1,000) \mu\text{m}$ (where L is the measured length in mm) at any point within the operating range of the machine (i.e. within the length of the axis), according to ISO 10360-2 (2009); <u>or</u>

Category Code	Item Description
	<p>2. Three or more axes and having a three dimensional (volumetric) maximum permissible error of length measurement ($E_{0,MPE}$) equal to or less (better) than $(1.7 + L/800) \mu\text{m}$ (where L is the measured length in mm) at any point within the operating range of the machine (i.e. within the length of the axis), according to ISO 10360-2 (2009);</p> <p><i>Technical Note</i> <i>The $E_{0,MPE}$ of the most accurate configuration of the CMM specified according to ISO 10360-2 (2009) by the manufacturer (e.g. best of the following: probe, stylus, length, motion parameters, environments) and with all compensations available must be compared to the $(1.7 + L/800) \mu\text{m}$ threshold.</i></p> <p>b. Systems for simultaneous linear-angular inspection of hemishells, having both of the following characteristics:</p> <ol style="list-style-type: none"> 1. “Measurement uncertainty” along any linear axis equal to or less (better) than $3.5 \mu\text{m}$ per 5 mm; <u>and</u> 2. “Angular position deviation” equal to or less than 0.02°; <p>c. ‘Linear displacement’ measuring systems having all of the following characteristics:</p> <p><i>Technical Note</i> <i>For the purpose of Category Code 2B206.c., ‘linear displacement’ means the change of distance between the measuring probe and the measured object.</i></p> <ol style="list-style-type: none"> 1. Containing a “laser”; <u>and</u> 2. Maintaining, for at least 12 hours, at a temperature of $\pm 1 \text{ K}$ around a standard temperature and standard pressure, all of the following: <ol style="list-style-type: none"> a. A “resolution” over their full scale of $0.1 \mu\text{m}$ or better; <u>and</u> b. With a “measurement uncertainty” equal to or better (less) than $(0.2 + L/2,000) \mu\text{m}$ (L is the measured length in mm).

<i>Category Code</i>	<i>Item Description</i>
	<p data-bbox="539 454 600 488"><u>Note</u></p> <p data-bbox="539 495 1268 663"><i>Category Code 2B206.c. does not include measuring interferometer systems, without closed or open loop feedback, containing a laser to measure slide movement errors of machine tools, dimensional inspection machines, or similar equipment.</i></p> <p data-bbox="475 678 560 712"><u>Note 1</u></p> <p data-bbox="475 719 1268 819"><i>Machine tools that can be used as measuring machines are included if they meet or exceed the criteria specified for the machine tool function or the measuring machine function.</i></p> <p data-bbox="475 835 560 869"><u>Note 2</u></p> <p data-bbox="475 875 1268 976"><i>A machine specified in Category Code 2B206 is included in that Category Code if it exceeds the specifications stated therein anywhere within its operating range.</i></p> <p data-bbox="475 992 660 1025"><u>Technical Note</u></p> <p data-bbox="475 1032 1268 1111"><i>All parameters of measurement values in Category Code 2B206 represent plus/minus i.e. not total band.</i></p>
2B207	<p data-bbox="475 1173 1268 1240"><i>“Robots”, “end-effectors” and control units, other than those specified in Category Code 2B007, as follows:</i></p> <ol style="list-style-type: none"> <li data-bbox="475 1256 1268 1391">a. <i>“Robots” or “end-effectors” specially designed to comply with national safety standards applicable to handling high explosives (e.g. meeting electrical code ratings for high explosives);</i> <li data-bbox="475 1406 1268 1473">b. <i>Control units specially designed for any of the “robots” or “end-effectors” specified in Category Code 2B207.a.</i>

<i>Category Code</i>	<i>Item Description</i>
2B209	<p>Flow forming machines, spin forming machines capable of flow forming functions, other than those specified in Category Code 2B009 or 2B109, and mandrels, as follows:</p> <p>a. Machines having both of the following characteristics:</p> <ol style="list-style-type: none"> 1. Three or more rollers (active or guiding); <u>and</u> 2. Which, according to the manufacturer's technical specification, can be equipped with "numerical control" units or a computer control; <p><i>Note</i> <i>Category Code 2B209.a. includes machines which have only a single roller designed to deform metal plus two auxiliary rollers which support the mandrel, but do not participate directly in the deformation process.</i></p> <p>b. Rotor-forming mandrels designed to form cylindrical rotors of inside diameter between 75 mm and 400 mm.</p>
2B219	<p>Centrifugal multiplane balancing machines, fixed or portable, horizontal or vertical, as follows:</p> <p>a. Centrifugal balancing machines designed for balancing flexible rotors having a length of 600 mm or more and having all of the following characteristics:</p> <ol style="list-style-type: none"> 1. Swing or journal diameter greater than 75 mm; 2. Mass capability of from 0.9 kg to 23 kg; <u>and</u> 3. Capable of balancing speed of revolution greater than 5,000 rpm; <p>b. Centrifugal balancing machines designed for balancing hollow cylindrical rotor components and having all of the following characteristics:</p> <ol style="list-style-type: none"> 1. Journal diameter greater than 75 mm; 2. Mass capability of from 0.9 kg to 23 kg; 3. Capable of balancing to a residual imbalance equal to or less than 0.01 kg × mm/kg per plane; <u>and</u> 4. Belt drive type.

<i>Category Code</i>	<i>Item Description</i>
2B225	<p>Remote manipulators that can be used to provide remote actions in radiochemical separation operations or hot cells, having either of the following characteristics:</p> <ol style="list-style-type: none"> a. A capability of penetrating 0.6 m or more of hot cell wall (through-the-wall operation); <u>or</u> b. A capability of bridging over the top of a hot cell wall with a thickness of 0.6 m or more (over-the-wall operation). <p><i>Technical Note</i> Remote manipulators provide translation of human operator actions to a remote operating arm and terminal fixture. They may be of 'master/slave' type or operated by joystick or keypad.</p>
2B226	<p>Controlled atmosphere (vacuum or inert gas) induction furnaces, and power supplies therefor, as follows:</p> <p><i>N.B.</i> <i>See also Category 3B.</i></p> <ol style="list-style-type: none"> a. Furnaces having all of the following characteristics: <ol style="list-style-type: none"> 1. Capable of operation above 1,123 K (850°C); 2. Induction coils 600 mm or less in diameter; <u>and</u> 3. Designed for power inputs of 5 kW or more; b. Power supplies, with a specified power output of 5 kW or more, specially designed for furnaces specified in Category Code 2B226.a. <p><i>Note</i> <i>Category Code 2B226.a. does not include furnaces designed for the processing of semiconductor wafers.</i></p>
2B227	<p>Vacuum or other controlled atmosphere metallurgical melting and casting furnaces and related equipment as follows:</p> <ol style="list-style-type: none"> a. Arc remelt and casting furnaces having both of the following characteristics: <ol style="list-style-type: none"> 1. Consumable electrode capacities between 1,000 cm³ and 20,000 cm³; <u>and</u>

<i>Category Code</i>	<i>Item Description</i>
	<p>2. Capable of operating with melting temperatures above 1,973 K (1,700°C);</p> <p>b. Electron beam melting furnaces and plasma atomisation and melting furnaces, having both of the following characteristics:</p> <ol style="list-style-type: none"> 1. A power of 50 kW or greater; <u>and</u> 2. Capable of operating with melting temperatures above 1,473 K (1,200°C); <p>c. Computer control and monitoring systems specially configured for any of the furnaces specified in Category Code 2B227.a. or 2B227.b.</p>
2B228	<p>Rotor fabrication or assembly equipment, rotor straightening equipment, bellows-forming mandrels and dies, as follows:</p> <p>a. Rotor assembly equipment for assembly of gas centrifuge rotor tube sections, baffles, and end caps;</p> <p><i>Note</i> <i>Category Code 2B228.a. includes precision mandrels, clamps, and shrink fit machines.</i></p> <p>b. Rotor straightening equipment for alignment of gas centrifuge rotor tube sections to a common axis;</p> <p><i>Technical Note</i> <i>Equipment specified in Category Code 2B228.b. normally consists of precision measuring probes linked to a computer that subsequently controls the action of, e.g. pneumatic rams used for aligning the rotor tube sections.</i></p> <p>c. Bellows-forming mandrels and dies for producing single-convolution bellows.</p> <p><i>Technical Note</i> <i>In Category Code 2B228.c., the bellows have all of the following characteristics:</i></p> <ol style="list-style-type: none"> a. Inside diameter between 75 mm and 400 mm; b. Length equal to or greater than 12.7 mm; c. Single convolution depth greater than 2 mm; <u>and</u>

<i>Category Code</i>	<i>Item Description</i>
2B230	<p data-bbox="539 454 1267 521"><i>d. Made of high-strength aluminium alloys, maraging steel or high strength “fibrous or filamentary materials”.</i></p> <p data-bbox="475 589 1267 656">All types of ‘pressure transducers’ capable of measuring absolute pressures and having all of the following:</p> <p data-bbox="475 674 1267 801">a. Pressure sensing elements made of or protected by aluminium, aluminium alloy, aluminium oxide (alumina or sapphire), nickel, nickel alloy with more than 60% nickel by weight, or fully fluorinated hydrocarbon polymers;</p> <p data-bbox="475 819 1267 1021">b. Seals, if any, essential for sealing the pressure sensing element, and in direct contact with the process medium, made of or protected by aluminium, aluminium alloy, aluminum oxide (alumina or sapphire), nickel, nickel alloy with more than 60% nickel by weight, or fully fluorinated hydrocarbon polymers; <u>and</u></p> <p data-bbox="475 1039 1267 1240">c. Having either of the following characteristics:</p> <ol data-bbox="539 1088 1267 1240" style="list-style-type: none"> <li data-bbox="539 1088 1267 1155">1. A full scale of less than 13 kPa and an ‘accuracy’ of better than $\pm 1\%$ of full-scale; <u>or</u> <li data-bbox="539 1173 1267 1240">2. A full scale of 13 kPa or greater and an ‘accuracy’ of better than ± 130 Pa when measured at 13 kPa. <p data-bbox="475 1258 671 1281"><u>Technical Notes</u></p> <ol data-bbox="475 1299 1267 1478" style="list-style-type: none"> <li data-bbox="475 1299 1267 1366">1. <i>In Category Code 2B230, ‘pressure transducer’ means a device that converts a pressure measurement into a signal.</i> <li data-bbox="475 1384 1267 1478">2. <i>For the purpose of Category Code 2B230, ‘accuracy’ includes non-linearity, hysteresis and repeatability at ambient temperature.</i>

<i>Category Code</i>	<i>Item Description</i>
2B231	<p>Vacuum pumps having all of the following characteristics:</p> <ol style="list-style-type: none"> a. Input throat size equal to or greater than 380 mm; b. Pumping speed equal to or greater than 15 m³/s; <u>and</u> c. Capable of producing an ultimate vacuum better than 13 mPa. <p><u>Technical Notes</u></p> <ol style="list-style-type: none"> 1. The pumping speed is determined at the measurement point with nitrogen gas or air. 2. The ultimate vacuum is determined at the input of the pump with the input of the pump blocked off.
2B232	<p>High-velocity gun systems (propellant, gas, coil, electromagnetic, and electrothermal types, and other advanced systems) capable of accelerating projectiles to 1.5 km/s or greater.</p> <p><u>N.B.</u> See also Division 2 of Part 1 of this Schedule.</p>
2B233	<p>Bellows-sealed scroll-type compressors and bellows-sealed scroll-type vacuum pumps having all of the following characteristics:</p> <p><u>N.B.</u> See also Category Code 2B350.i.</p> <ol style="list-style-type: none"> a. Capable of an inlet volume flow rate of 50 m³/h or greater; b. Capable of a pressure ratio of 2:1 or greater; <u>and</u> c. Having all surfaces that come in contact with the process gas made from any of the following materials: <ol style="list-style-type: none"> 1. Aluminium or aluminium alloy; 2. Aluminium oxide; 3. Stainless steel; 4. Nickel or nickel alloy; 5. Phosphor bronze; <u>or</u> 6. Fluoropolymers.

<i>Category Code</i>	<i>Item Description</i>
2B350	<p>Chemical manufacturing facilities, equipment and components, as follows:</p> <p>a. Reaction vessels or reactors, with or without agitators, with total internal (geometric) volume greater than 0.1 m³ (100 litres) and less than 20 m³ (20,000 litres), where all surfaces that come in direct contact with the chemical(s) being processed or contained are made from any of the following materials:</p> <ol style="list-style-type: none"> 1. 'Alloys' with more than 25% nickel and 20% chromium by weight; 2. Fluoropolymers (polymeric or elastomeric materials with more than 35% fluorine by weight); 3. Glass (including vitrified or enamelled coating or glass lining); 4. Nickel or 'alloys' with more than 40% nickel by weight; 5. Tantalum or tantalum 'alloys'; 6. Titanium or titanium 'alloys'; 7. Zirconium or zirconium 'alloys'; <u>or</u> 8. Niobium (columbium) or niobium 'alloys'; <p>b. Agitators designed for use in reaction vessels or reactors specified in Category Code 2B350.a.; and impellers, blades or shafts designed for such agitators, where all surfaces of the agitator that come in direct contact with the chemical(s) being processed or contained are made from any of the following materials:</p> <ol style="list-style-type: none"> 1. 'Alloys' with more than 25% nickel and 20% chromium by weight; 2. Fluoropolymers (polymeric or elastomeric materials with more than 35% fluorine by weight); 3. Glass (including vitrified or enamelled coatings or glass lining); 4. Nickel or 'alloys' with more than 40% nickel by weight; 5. Tantalum or tantalum 'alloys'; 6. Titanium or titanium 'alloys';

<i>Category Code</i>	<i>Item Description</i>
	<p>7. Zirconium or zirconium ‘alloys’; <u>or</u></p> <p>8. Niobium (columbium) or niobium ‘alloys’;</p> <p>c. Storage tanks, containers or receivers with a total internal (geometric) volume greater than 0.1 m³ (100 litres) where all surfaces that come in direct contact with the chemical(s) being processed or contained are made from any of the following materials:</p> <ol style="list-style-type: none"> 1. ‘Alloys’ with more than 25% nickel and 20% chromium by weight; 2. Fluoropolymers (polymeric or elastomeric materials with more than 35% fluorine by weight); 3. Glass (including vitrified or enamelled coatings or glass lining); 4. Nickel or ‘alloys’ with more than 40% nickel by weight; 5. Tantalum or tantalum ‘alloys’; 6. Titanium or titanium ‘alloys’; 7. Zirconium or zirconium ‘alloys’; <u>or</u> 8. Niobium (columbium) or niobium ‘alloys’; <p>d. Heat exchangers or condensers with a heat transfer surface area greater than 0.15 m², and less than 20 m²; and tubes, plates, coils or blocks (cores) designed for such heat exchangers or condensers, where all surfaces that come in direct contact with the chemical(s) being processed are made from any of the following materials:</p> <ol style="list-style-type: none"> 1. ‘Alloys’ with more than 25% nickel and 20% chromium by weight; 2. Fluoropolymers (polymeric or elastomeric materials with more than 35% fluorine by weight); 3. Glass (including vitrified or enamelled coatings or glass lining); 4. Graphite or ‘carbon graphite’; 5. Nickel or ‘alloys’ with more than 40% nickel by weight; 6. Tantalum or tantalum ‘alloys’;

<i>Category Code</i>	<i>Item Description</i>
	<ol style="list-style-type: none"> 7. Titanium or titanium 'alloys'; 8. Zirconium or zirconium 'alloys'; 9. Silicon carbide; 10. Titanium carbide; <u>or</u> 11. Niobium (columbium) or niobium 'alloys'; <p>e. Distillation or absorption columns of internal diameter greater than 0.1 m; and liquid distributors, vapour distributors or liquid collectors designed for such distillation or absorption columns, where all surfaces that come in direct contact with the chemical(s) being processed are made from any of the following materials:</p> <ol style="list-style-type: none"> 1. 'Alloys' with more than 25% nickel and 20% chromium by weight; 2. Fluoropolymers (polymeric or elastomeric materials with more than 35% fluorine by weight); 3. Glass (including vitrified or enamelled coatings or glass lining); 4. Graphite or 'carbon graphite'; 5. Nickel or 'alloys' with more than 40% nickel by weight; 6. Tantalum or tantalum 'alloys'; 7. Titanium or titanium 'alloys'; 8. Zirconium or zirconium 'alloys'; <u>or</u> 9. Niobium (columbium) or niobium 'alloys'; <p>f. Remotely operated filling equipment in which all surfaces that come in direct contact with the chemical(s) being processed are made from any of the following materials:</p> <ol style="list-style-type: none"> 1. 'Alloys' with more than 25% nickel and 20% chromium by weight; <u>or</u> 2. Nickel or 'alloys' with more than 40% nickel by weight;

<i>Category Code</i>	<i>Item Description</i>
	<p>g. Valves and components, as follows:</p> <ol style="list-style-type: none"> 1. Valves, having both of the following characteristics: <ol style="list-style-type: none"> a. A 'nominal size' greater than 10 mm (3/8"); <u>and</u> b. All surfaces that come in direct contact with the chemical(s) being produced, processed, or contained are made from 'corrosion resistant materials'; 2. Valves, other than those specified in Category Code 2B350.g.1., having all of the following characteristics: <ol style="list-style-type: none"> a. A 'nominal size' equal to or greater than 25.4 mm (1") and equal to or less than 101.6 mm (4"); b. Casings (valve bodies) or preformed casing liners; c. A closure element designed to be interchangeable; <u>and</u> d. All surfaces of the casing (valve body) or preformed case liner that come in direct contact with the chemical(s) being produced, processed, or contained are made from 'corrosion resistant materials'; 3. Components, designed for valves specified in Category Code 2B350.g.1. or 2B350.g.2., in which all surfaces that come in direct contact with the chemical(s) being produced, processed, or contained are made from 'corrosion resistant materials', as follows: <ol style="list-style-type: none"> a. Casings (valve bodies); b. Preformed casing liners;

Category Code	Item Description
	<p data-bbox="539 454 735 488"><u>Technical Notes</u></p> <ol style="list-style-type: none"> <li data-bbox="539 499 1268 595">1. For the purpose of Category Code 2B350.g., ‘corrosion resistant materials’ means any of the following materials: <ol style="list-style-type: none"> <li data-bbox="624 611 1268 678">a. Nickel or alloys with more than 40% nickel by weight; <li data-bbox="624 694 1268 761">b. Alloys with more than 25% nickel and 20% chromium by weight; <li data-bbox="624 777 1268 873">c. Fluoropolymers (polymeric or elastomeric materials with more than 35% fluorine by weight); <li data-bbox="624 889 1268 963">d. Glass or glass-lined (including vitrified or enamelled coatings); <li data-bbox="624 978 1037 1012">e. Tantalum or tantalum alloys; <li data-bbox="624 1028 1023 1061">f. Titanium or titanium alloys; <li data-bbox="624 1077 1058 1111">g. Zirconium or zirconium alloys; <li data-bbox="624 1126 1212 1160">h. Niobium (columbium) or niobium alloys; <u>or</u> <li data-bbox="624 1176 1268 1424">i. Ceramic materials as follows: <ol style="list-style-type: none"> <li data-bbox="687 1227 1268 1294">1. Silicon carbide with a purity of 80% or more by weight; <li data-bbox="687 1310 1268 1377">2. Aluminium oxide (alumina) with a purity of 99.9% or more by weight; <li data-bbox="687 1393 1078 1424">3. Zirconium oxide (zirconia). <li data-bbox="539 1440 1268 1507">2. The ‘nominal size’ is defined as the smaller of the inlet and outlet diameters. <li data-bbox="475 1523 1268 1825">h. Multi-walled piping incorporating a leak detection port, in which all surfaces that come in direct contact with the chemical(s) being processed or contained are made from any of the following materials: <ol style="list-style-type: none"> <li data-bbox="539 1675 1268 1742">1. ‘Alloys’ with more than 25% nickel and 20% chromium by weight; <li data-bbox="539 1758 1268 1825">2. Fluoropolymers (polymeric or elastomeric materials with more than 35% fluorine by weight);

<i>Category Code</i>	<i>Item Description</i>
	<ol style="list-style-type: none"> 3. Glass (including vitrified or enamelled coatings or glass lining); 4. Graphite or 'carbon graphite'; 5. Nickel or 'alloys' with more than 40% nickel by weight; 6. Tantalum or tantalum 'alloys'; 7. Titanium or titanium 'alloys'; 8. Zirconium or zirconium 'alloys'; <u>or</u> 9. Niobium (columbium) or niobium 'alloys'; <p>i. Multiple-seal and seal-less pumps, with manufacturer's specified maximum flow-rate greater than 0.6 m³/hour, or vacuum pumps with manufacturer's specified maximum flow-rate greater than 5 m³/hour (under standard temperature (273 K (0°C)) and pressure (101.3 kPa) conditions), other than those specified in Category Code 2B233; and casings (pump bodies), preformed casing liners, impellers, rotors or jet pump nozzles designed for such pumps, in which all surfaces that come in direct contact with the chemical(s) being processed are made from any of the following materials:</p> <ol style="list-style-type: none"> 1. 'Alloys' with more than 25% nickel and 20% chromium by weight; 2. Ceramics; 3. Ferrosilicon (high silicon iron alloys); 4. Fluoropolymers (polymeric or elastomeric materials with more than 35% fluorine by weight); 5. Glass (including vitrified or enamelled coatings or glass lining); 6. Graphite or 'carbon graphite'; 7. Nickel or 'alloys' with more than 40% nickel by weight; 8. Tantalum or tantalum 'alloys'; 9. Titanium or titanium 'alloys'; 10. Zirconium or zirconium 'alloys'; <u>or</u> 11. Niobium (columbium) or niobium 'alloys';

Category Code	Item Description
	<p data-bbox="539 454 722 488"><u>Technical Note</u></p> <p data-bbox="539 499 1262 663"><i>In Category Code 2B350.i., the term seal refers to only those seals that come into direct contact with the chemical(s) being processed (or are designed to), and provide a sealing function where a rotary or reciprocating drive shaft passes through a pump body.</i></p> <p data-bbox="475 680 1262 913">j. Incinerators designed to destroy chemicals specified in Category Code 1C350, having specially designed waste supply systems, special handling facilities and an average combustion chamber temperature greater than 1,273 K (1,000°C), in which all surfaces in the waste supply system that come into direct contact with the waste products are made from or lined with any of the following materials:</p> <ol data-bbox="539 931 1262 1099" style="list-style-type: none"> <li data-bbox="539 931 1262 1003">1. ‘Alloys’ with more than 25% nickel and 20% chromium by weight; <li data-bbox="539 1014 759 1048">2. Ceramics; <u>or</u> <li data-bbox="539 1059 1262 1099">3. Nickel or ‘alloys’ with more than 40% nickel by weight. <p data-bbox="475 1117 536 1151"><u>Note</u></p> <p data-bbox="475 1162 1262 1326"><i>For the purpose of Category Code 2B350, the materials used for gaskets, packing, seals, screws, washers or other materials performing a sealing function do not determine the control status, provided that such components are designed to be interchangeable.</i></p> <p data-bbox="475 1344 671 1377"><u>Technical Notes</u></p> <ol data-bbox="475 1386 1262 1666" style="list-style-type: none"> <li data-bbox="475 1386 1262 1487">1. ‘Carbon graphite’ is a composition consisting of amorphous carbon and graphite, in which the graphite content is 8% or more by weight. <li data-bbox="475 1498 1262 1666">2. For the listed materials in the above entries, the term ‘alloy’ when not accompanied by a specific elemental concentration is understood as identifying those alloys where the identified metal is present in a higher percentage by weight than any other element.

<i>Category Code</i>	<i>Item Description</i>
2B351	<p>Toxic gas monitoring systems and their dedicated detecting components, other than those specified in Category Code 1A004, as follows; and detectors; sensor devices; and replaceable sensor cartridges therefor:</p> <ol style="list-style-type: none"> a. Designed for continuous operation and usable for the detection of chemical warfare agents or chemicals specified in Category Code 1C350, at concentrations of less than 0.3 mg/m³; <u>or</u> b. Designed for the detection of cholinesterase-inhibiting activity.
2B352	<p>Equipment capable of use in handling biological materials as follows:</p> <ol style="list-style-type: none"> a. Complete biological containment facilities at P3, P4 containment level; <p style="margin-left: 20px;"><i>Technical Note</i> P3 or P4 (BL3, BL4, L3, L4) containment levels are as specified in the WHO Laboratory Biosafety manual (3rd edition, Geneva 2004).</p> b. Fermenters and components as follows: <ol style="list-style-type: none"> 1. Fermenters capable of cultivation of pathogenic “microorganisms” or of live cells, for the production of pathogenic viruses or toxins, without the propagation of aerosols, having a total capacity of 20 litres or more; 2. Components designed for fermenters in Category Code 2B352.b.1. as follows: <ol style="list-style-type: none"> a. Cultivation chambers designed to be sterilised or disinfected <i>in situ</i>; b. Cultivation chamber holding devices; c. Process control units capable of simultaneously monitoring and controlling two or more fermentation system parameters (e.g. temperature, pH, nutrients, agitation, dissolved oxygen, air flow, foam control);

Category Code	Item Description
	<p data-bbox="539 454 724 483"><u>Technical Note</u></p> <p data-bbox="539 495 1262 591"><i>For the purpose of Category Code 2B352.b., fermenters include bioreactors, single-use (disposable) bioreactors, chemostats and continuous-flow systems.</i></p> <p data-bbox="475 613 1262 710">c. Centrifugal separators, capable of continuous separation without the propagation of aerosols, having all of the following characteristics:</p> <ol data-bbox="539 725 1262 943" style="list-style-type: none"> <li data-bbox="539 725 1078 754">1. Flow-rate exceeding 100 litres per hour; <li data-bbox="539 777 1209 806">2. Components of polished stainless steel or titanium; <li data-bbox="539 828 1262 891">3. One or more sealing joints within the steam containment area; <u>and</u> <li data-bbox="539 913 1238 943">4. Capable of <i>in situ</i> steam sterilisation in a closed state; <p data-bbox="539 965 724 994"><u>Technical Note</u></p> <p data-bbox="539 1005 1034 1034"><i>Centrifugal separators include decanters.</i></p> <p data-bbox="475 1057 1262 1117">d. Cross (tangential) flow filtration equipment and components as follows:</p> <ol data-bbox="539 1140 1262 1568" style="list-style-type: none"> <li data-bbox="539 1140 1262 1267">1. Cross (tangential) flow filtration equipment capable of separation of pathogenic microorganisms, viruses, toxins or cell cultures having all of the following characteristics: <ol data-bbox="624 1290 1262 1568" style="list-style-type: none"> <li data-bbox="624 1290 1262 1352">a. A total filtration area equal to or greater than 1 m²; <u>and</u> <li data-bbox="624 1375 1262 1480">b. Having any of the following characteristics: <ol data-bbox="687 1420 1262 1568" style="list-style-type: none"> <li data-bbox="687 1420 1262 1480">1. Capable of being sterilised or disinfected <i>in situ</i>; <u>or</u> <li data-bbox="687 1503 1262 1568">2. Using disposable or single-use filtration components;

Category Code	Item Description
	<p data-bbox="687 454 871 483"><u>Technical Note</u></p> <p data-bbox="687 495 1267 927"><i>In Category Code 2B352.d.1.b., sterilised denotes the elimination of all viable microbes from the equipment through the use of either physical (e.g. steam) or chemical agents. Disinfected denotes the destruction of potential microbial infectivity in the equipment through the use of chemical agents with a germicidal effect. Disinfection and sterilisation are distinct from sanitisation, the latter referring to cleaning procedures designed to lower the microbial content of equipment without necessarily achieving elimination of all microbial infectivity or viability.</i></p> <p data-bbox="539 949 600 978"><u>Note</u></p> <p data-bbox="539 990 1267 1055"><i>Category Code 2B352.d. does not include reverse osmosis equipment, as specified by the manufacturer.</i></p> <p data-bbox="539 1072 1267 1272">2. Cross (tangential) flow filtration components (e.g. modules, elements, cassettes, cartridges, units or plates) with filtration area equal to or greater than 0.2 m² for each component and designed for use in cross (tangential) flow filtration equipment specified in Category Code 2B352.d.;</p> <p data-bbox="475 1290 1267 1386">e. Steam, gas or vapour sterilisable freeze drying equipment with a condenser capacity of 10 kg of ice or more in 24 hours and less than 1,000 kg of ice in 24 hours;</p> <p data-bbox="475 1404 1267 1554">f. Protective and containment equipment, as follows:</p> <p data-bbox="539 1458 1267 1554">1. Protective full or half suits, or hoods dependent upon a tethered external air supply and operating under positive pressure;</p> <p data-bbox="603 1576 663 1606"><u>Note</u></p> <p data-bbox="603 1617 1267 1713"><i>Category Code 2B352.f.1. does not include suits designed to be worn with self-contained breathing apparatus.</i></p> <p data-bbox="539 1731 1267 1827">2. Biocontainment chambers, isolators, or biological safety cabinets having all of the following characteristics, for normal operation:</p>

<i>Category Code</i>	<i>Item Description</i>
	<p>a. Fully enclosed workspace where the operator is separated from the work by a physical barrier;</p> <p>b. Able to operate at negative pressure;</p> <p>c. Means to safely manipulate items in the workspace; <u>and</u></p> <p>d. Supply and exhaust air to and from the workspace is HEPA filtered;</p> <p><u>Note 1</u> <i>Category Code 2B352.f.2. includes Class III biosafety cabinets, as described in the latest edition of the WHO Laboratory Biosafety Manual or constructed in accordance with national standards, regulations or guidance.</i></p> <p><u>Note 2</u> <i>Category Code 2B352.f.2. does not include isolators specially designed for barrier nursing or transportation of infected patients.</i></p> <p>g. Aerosol inhalation equipment designed for aerosol challenge testing with “microorganisms”, “viruses” or “toxins” as follows:</p> <ol style="list-style-type: none"> 1. Whole-body exposure chambers having a capacity of 1 m³ or more; 2. Nose-only exposure apparatus utilising directed aerosol flow and having capacity for exposure of any of the following: <ol style="list-style-type: none"> a. 12 or more rodents; <u>or</u> b. 2 or more animals other than rodents; 3. Closed animal restraint tubes designed for use with nose-only exposure apparatus utilising directed aerosol flow; <p>h. Spray drying equipment capable of drying toxins or pathogenic microorganisms having all of the following characteristics:</p> <ol style="list-style-type: none"> 1. A water evaporation capacity of ≥ 0.4 kg/h and ≤ 400 kg/h;

<i>Category Code</i>	<i>Item Description</i>
	<ol style="list-style-type: none"> <li data-bbox="539 454 1272 622">2. The ability to generate a typical mean product particle size of $\leq 10 \mu\text{m}$ with existing fittings or by minimal modification of the spray-dryer with atomisation nozzles enabling generation of the required particle size; <u>and</u> <li data-bbox="539 633 1272 678">3. Capable of being sterilised or disinfected <i>in situ</i>.
2C	<p data-bbox="475 734 603 768">Materials</p> <p data-bbox="475 786 555 819">None.</p>
2D	<p data-bbox="475 887 603 920">Software</p>
2D001	<p data-bbox="475 1384 1272 1451">“Software”, other than that specified in Category Code 2D002, as follows:</p> <ol style="list-style-type: none"> <li data-bbox="475 1469 1272 1559">a. “Software” specially designed or modified for the “development” or “production” of equipment specified in Category Code 2A001 or 2B001; <li data-bbox="475 1581 1272 1671">b. “Software” specially designed or modified for the “use” of equipment specified in Category Code 2A001.c., 2B001 or 2B003 to 2B009.
2D002	<p data-bbox="475 1608 1272 1675"><u>Note</u></p> <p data-bbox="475 1686 1272 1751"><i>Category Code 2D001 does not include part programming “software” that generates “numerical control” codes for machining various parts.</i></p> <p data-bbox="475 1787 1272 1854">“Software” for electronic devices, even when residing in an electronic device or system, enabling such devices or systems to function as a “numerical control” unit, capable of coordinating simultaneously more than four axes for “contouring control”.</p> <p data-bbox="475 1865 1272 1933"><u>Note 1</u></p> <p data-bbox="475 1944 1272 2011"><i>Category Code 2D002 does not include “software” specially designed or modified for the operation of items not specified in Category 2.</i></p>

Category Code	Item Description
	<p><u>Note 2</u> <i>Category Code 2D002 does not include “software” for items specified in Category Code 2B002. See Category Codes 2D001 and 2D003 for “software” for items specified in Category Code 2B002.</i></p> <p><u>Note 3</u> <i>Category Code 2D002 does not include “software” that is exported with, and the minimum necessary for the operation of, items not specified in Category 2.</i></p>
2D003	<p>“Software”, designed or modified for the operation of equipment specified in Category Code 2B002, that converts optical design, workpiece measurements and material removal functions into “numerical control” commands to achieve the desired workpiece form.</p>
2D101	<p>“Software” specially designed or modified for the “use” of equipment specified in Category Code 2B104, 2B105, 2B109, 2B116, 2B117 or 2B119 to 2B122.</p> <p><u>N.B.</u> <i>See also Category Code 9D004.</i></p>
2D201	<p>“Software” specially designed for the “use” of equipment specified in Category Code 2B204, 2B206, 2B207, 2B209, 2B219 or 2B227.</p>
2D202	<p>“Software” specially designed or modified for the “development”, “production” or “use” of equipment specified in Category Code 2B201.</p> <p><u>Note</u> <i>Category Code 2D202 does not include part programming “software” that generates “numerical control” command codes but does not allow direct use of equipment for machining various parts.</i></p>

<i>Category Code</i>	<i>Item Description</i>
2D351	“Software”, other than that specified in Category Code 1D003, specially designed for the “use” of equipment specified in Category Code 2B351.
2E	Technology
2E001	<p>“Technology” (according to the General Technology Note) for the “development” of equipment or “software” specified in Category 2A, 2B or 2D.</p> <p><i>Note</i> <i>Category Code 2E001 includes “technology” for the integration of probe systems into coordinate measurement machines specified in Category Code 2B006.a.</i></p>
2E002	“Technology” (according to the General Technology Note) for the “production” of equipment specified in Category 2A or 2B.
2E003	<p>Other “technology” as follows:</p> <ol style="list-style-type: none"> a. “Technology” for the “development” of interactive graphics as an integrated part in “numerical control” units for preparation or modification of part programs; b. “Technology” for metal-working manufacturing processes, as follows: <ol style="list-style-type: none"> 1. “Technology” for the design of tools, dies or fixtures specially designed for any of the following processes: <ol style="list-style-type: none"> a. “Superplastic forming”; b. “Diffusion bonding”; <u>or</u> c. “Direct-acting hydraulic pressing”; 2. Technical data consisting of process methods or parameters as listed below used to control: <ol style="list-style-type: none"> a. “Superplastic forming” of aluminium alloys, titanium alloys or “superalloys”: <ol style="list-style-type: none"> 1. Surface preparation; 2. Strain rate;

<i>Category Code</i>	<i>Item Description</i>
	<ul style="list-style-type: none"> 3. Temperature; 4. Pressure; b. "Diffusion bonding" of "superalloys" or titanium alloys: <ul style="list-style-type: none"> 1. Surface preparation; 2. Temperature; 3. Pressure; c. "Direct-acting hydraulic pressing" of aluminium alloys or titanium alloys: <ul style="list-style-type: none"> 1. Pressure; 2. Cycle time; d. "Hot isostatic densification" of titanium alloys, aluminium alloys or "superalloys": <ul style="list-style-type: none"> 1. Temperature; 2. Pressure; 3. Cycle time; c. "Technology" for the "development" or "production" of hydraulic stretch-forming machines and dies therefor, for the manufacture of airframe structures; d. "Technology" for the "development" of generators of machine tool instructions (e.g. part programs) from design data residing inside "numerical control" units; e. "Technology" for the "development" of integration "software" for incorporation of expert systems for advanced decision support of shop floor operations into "numerical control" units; f. "Technology" for the application of inorganic overlay coatings or inorganic surface modification coatings (specified in column 3 of the Table entitled Deposition Techniques) to non-electronic substrates (specified in column 2 of that Table), by processes specified in column 1 of that Table and defined in the Technical Note.

Category Code	Item Description
	<p><u>Note</u> The Table entitled <i>Deposition Techniques and Technical Note</i> appear after Category Code 2E301.</p> <p><u>N.B.</u> This table should be read to specify the technology of a particular Coating Process only when the Resultant Coating in column 3 is in a paragraph directly across from the relevant Substrate under column 2. For example, Chemical Vapour Deposition (CVD) coating process technical data are included for the application of silicides to carbon-carbon, ceramic and metal “matrix” “composites” substrates, but are not included for the application of silicides to ‘cemented tungsten carbide’ (16), ‘silicon carbide’ (18) substrates. In the second case, the resultant coating is not listed in the paragraph under column 3 directly across from the paragraph under column 2 listing ‘cemented tungsten carbide’ (16), ‘silicon carbide’ (18).</p>
2E101	“Technology” (according to the General Technology Note) for the “use” of equipment or “software” specified in Category Code 2B004, 2B009, 2B104, 2B109, 2B116, 2B119 to 2B122 or 2D101.
2E201	“Technology” (according to the General Technology Note) for the “use” of equipment or “software” specified in Category Code 2A225, 2A226, 2B001, 2B006, 2B007.b., 2B007.c., 2B008, 2B009, 2B201, 2B204, 2B206, 2B207, 2B209, 2B225 to 2B233, 2D201 or 2D202.
2E301	“Technology” (according to the General Technology Note) for the “use” of goods specified in Category Codes 2B350 to 2B352.

TABLE – DEPOSITION TECHNIQUES

Notes

1. Bracketed numbers are explained in the Notes that appear after the table.
2. The coating processes under column 1 are further explained in the Technical Notes below.

1. Coating Process (1)	2. Substrate	3. Resultant Coating
A. Chemical Vapour Deposition (CVD)	“Superalloys”	Aluminides for internal passages
	Ceramics (19) and Low-expansion glasses (14)	Silicides Carbides Dielectric layers (15) Diamond Diamond-like carbon (17)
	Carbon-carbon, Ceramic and Metal “matrix” “composites”	Silicides Carbides Refractory metals Mixtures thereof (4) Dielectric layers (15) Aluminides Alloyed aluminides (2) Boron nitride
	Cemented tungsten carbide (16), Silicon carbide (18)	Carbides Tungsten Mixtures thereof (4) Dielectric layers (15)
	Molybdenum and Molybdenum alloys	Dielectric layers (15)
	Beryllium and Beryllium alloys	Dielectric layers (15) Diamond Diamond-like carbon (17)

1. Coating Process (1)	2. Substrate	3. Resultant Coating
	Sensor window materials (9)	Dielectric layers (15) Diamond Diamond-like carbon (17)
<p>B. Thermal-Evaporation Physical Vapour Deposition (TE-PVD)</p> <p>B.1 Physical Vapour Deposition (PVD): Electron-Beam (EB-PVD)</p>	<p>“Superalloys”</p> <p>Ceramics (19) and Low-expansion glasses (14)</p> <p>Corrosion resistant steel (7)</p> <p>Carbon-carbon, Ceramic and Metal “matrix” “composites”</p> <p>Cemented tungsten carbide (16), Silicon carbide (18)</p>	<p>Alloyed silicides Alloyed aluminides (2) MCrAlX (5) Modified zirconia (12) Silicides Aluminides Mixtures thereof (4)</p> <p>Dielectric layers (15)</p> <p>MCrAlX (5) Modified zirconia (12) Mixtures thereof (4)</p> <p>Silicides Carbides Refractory metals Mixtures thereof (4) Dielectric layers (15) Boron nitride</p> <p>Carbides Tungsten Mixtures thereof (4) Dielectric layers (15)</p>

1. Coating Process (1)	2. Substrate	3. Resultant Coating
B.2 Ion assisted resistive heating Physical Vapour Deposition (PVD) (Ion Plating)	Molybdenum and Molybdenum alloys	Dielectric layers (15)
	Beryllium and Beryllium alloys	Dielectric layers (15) Borides Beryllium
	Sensor window materials (9)	Dielectric layers (15)
	Titanium alloys (13)	Borides Nitrides
	Ceramics (19) and Low-expansion glasses (14)	Dielectric layers (15) Diamond-like carbon (17)
	Carbon-carbon, Ceramic and Metal “matrix” “composites”	Dielectric layers (15)
	Cemented tungsten carbide (16), Silicon carbide	Dielectric layers (15)
	Molybdenum and Molybdenum alloys	Dielectric layers (15)
B.3 Physical Vapour Deposition (PVD): “Laser” Vaporisation	Beryllium and Beryllium alloys	Dielectric layers (15)
	Sensor window materials (9)	Dielectric layers (15) Diamond-like carbon (17)
	Ceramics (19) and Low-expansion glasses (14)	Silicides Dielectric layers (15) Diamond-like carbon (17)
	Carbon-carbon, Ceramic and Metal “matrix” “composites”	Dielectric layers (15)

1. Coating Process (1)	2. Substrate	3. Resultant Coating
B.4 Physical Vapour Deposition (PVD): Cathodic Arc Discharge	Cemented tungsten carbide (16), Silicon carbide	Dielectric layers (15)
	Molybdenum and Molybdenum alloys	Dielectric layers (15)
	Beryllium and Beryllium alloys	Dielectric layers (15)
	Sensor window materials (9)	Dielectric layers (15) Diamond-like carbon (17)
	"Superalloys"	Alloyed silicides Alloyed aluminides (2) MCrAlX (5)
C. Pack cementation (See A above for out-of-pack cementation) (10)	Carbon-carbon, Ceramic and Metal "matrix" "composites"	Silicides Carbides Mixtures thereof (4)
	Titanium alloys (13)	Silicides Aluminides Alloyed aluminides (2)
	Refractory metals and alloys (8)	Silicides Oxides

1. Coating Process (1)	2. Substrate	3. Resultant Coating
D. Plasma spraying	“Superalloys”	MCrAlX (5) Modified zirconia (12) Mixtures thereof (4) Abradable Nickel-Graphite Abradable materials containing Ni-Cr-Al Abradable Al-Si-Polyester Alloyed aluminides (2)
	Aluminium alloys (6)	MCrAlX (5) Modified zirconia (12) Silicides Mixtures thereof (4)
	Refractory metals and alloys (8)	Aluminides Silicides Carbides
	Corrosion resistant steel (7)	MCrAlX (5) Modified zirconia (12) Mixtures thereof (4)
	Titanium alloys (13)	Carbides Aluminides Silicides Alloyed aluminides (2) Abradable Nickel-Graphite Abradable materials containing Ni-Cr-Al Abradable Al-Si-Polyester

1. Coating Process (1)	2. Substrate	3. Resultant Coating
E. Slurry Deposition	Refractory metals and alloys (8) Carbon-carbon, Ceramic and Metal “matrix” “composites”	Fused silicides Fused aluminides except for resistance heating elements Silicides Carbides Mixtures thereof (4)
F. Sputter Deposition	“Superalloys” Ceramics and Low-expansion glasses (14) Titanium alloys (13)	Alloyed silicides Alloyed aluminides (2) Noble metal modified aluminides (3) MCrAlX (5) Modified zirconia (12) Platinum Mixtures thereof (4) Silicides Platinum Mixtures thereof (4) Dielectric layers (15) Diamond-like carbon (17) Borides Nitrides Oxides Silicides Aluminides Alloyed aluminides (2) Carbides

1. Coating Process (1)	2. Substrate	3. Resultant Coating
	<p>Carbon-carbon, Ceramic and Metal “matrix” “composites”</p> <p>Cemented tungsten carbide (16), Silicon carbide (18)</p> <p>Molybdenum and Molybdenum alloys</p> <p>Beryllium and Beryllium alloys</p> <p>Sensor window materials (9)</p> <p>Refractory metals and alloys (8)</p>	<p>Silicides</p> <p>Carbides</p> <p>Refractory metals</p> <p>Mixtures thereof (4)</p> <p>Dielectric layers (15)</p> <p>Boron nitride</p> <p>Carbides</p> <p>Tungsten</p> <p>Mixtures thereof (4)</p> <p>Dielectric layers (15)</p> <p>Boron nitride</p> <p>Dielectric layers (15)</p> <p>Borides</p> <p>Dielectric layers (15)</p> <p>Beryllium</p> <p>Dielectric layers (15)</p> <p>Diamond-like carbon (17)</p> <p>Aluminides</p> <p>Silicides</p> <p>Oxides</p> <p>Carbides</p>
G. Ion Implantation	<p>High temperature bearing steels</p> <p>Titanium alloys (13)</p> <p>Beryllium and Beryllium alloys</p> <p>Cemented tungsten carbide (16)</p>	<p>Additions of Chromium Tantalum or Niobium (Columbium)</p> <p>Borides</p> <p>Nitrides</p> <p>Borides</p> <p>Carbides</p> <p>Nitrides</p>

TABLE — DEPOSITION TECHNIQUES — NOTES

1. The term ‘coating process’ includes coating repair and refurbishing as well as original coating.
2. The term ‘alloyed aluminide coating’ includes single or multiple-step coatings in which an element or elements are deposited prior to or during application of the aluminide coating, even if these elements are deposited by another coating process. It does not, however, include the multiple use of single-step pack cementation processes to achieve alloyed aluminides.
3. The term ‘noble metal modified aluminide’ coating includes multiple-step coatings in which the noble metal or noble metals are laid down by some other coating process prior to application of the aluminide coating.
4. The term ‘mixtures thereof’ includes infiltrated material, graded compositions, co-deposits and multilayer deposits and are obtained by one or more of the coating processes specified in the Table.
5. ‘MCrAlX’ refers to a coating alloy where M equals cobalt, iron, nickel or combinations thereof and X equals hafnium, yttrium, silicon, tantalum in any amount or other intentional additions over 0.01% by weight in various proportions and combinations, except:
 - a. CoCrAlY coatings which contain less than 22% by weight of chromium, less than 7% by weight of aluminium and less than 2% by weight of yttrium;
 - b. CoCrAlY coatings which contain 22% to 24% by weight of chromium, 10% to 12% by weight of aluminium and 0.5% to 0.7% by weight of yttrium; or
 - c. NiCrAlY coatings which contain 21% to 23% by weight of chromium, 10% to 12% by weight of aluminium and 0.9% to 1.1% by weight of yttrium.
6. The term ‘aluminium alloys’ refers to alloys having an ultimate tensile strength of 190 MPa or more measured at 293 K (20°C).
7. The term ‘corrosion resistant steel’ refers to AISI (American Iron and Steel Institute) 300 series or equivalent national standard steels.
8. ‘Refractory metals and alloys’ include the following metals and their alloys: niobium (columbium), molybdenum, tungsten and tantalum.
9. ‘Sensor window materials’ as follows: alumina, silicon, germanium, zinc sulphide, zinc selenide, gallium arsenide, diamond, gallium phosphide, sapphire and the following metal halides: sensor window materials of more than 40 mm diameter for zirconium fluoride and hafnium fluoride.

-
10. "Technology" for single-step pack cementation of solid airfoils is not included in Category 2.
 11. 'Polymers', as follows: polyimide, polyester, polysulphide, polycarbonates and polyurethanes.
 12. 'Modified zirconia' refers to additions of other metal oxides (e.g. calcia, magnesia, yttria, hafnia, rare earth oxides) to zirconia in order to stabilise certain crystallographic phases and phase compositions. Thermal barrier coatings made of zirconia, modified with calcia or magnesia by mixing or fusion, are not included.
 13. 'Titanium alloys' refers only to aerospace alloys having an ultimate tensile strength of 900 MPa or more measured at 293 K (20°C).
 14. 'Low-expansion glasses' refers to glasses which have a coefficient of thermal expansion of $1 \times 10^{-7} \text{ K}^{-1}$ or less measured at 293 K (20°C).
 15. 'Dielectric layers' are coatings constructed of multi-layers of insulator materials in which the interference properties of a design composed of materials of various refractive indices are used to reflect, transmit or absorb various wavelength bands. Dielectric layers refer to more than four dielectric layers or dielectric/metal "composite" layers.
 16. 'Cemented tungsten carbide' does not include cutting and forming tool materials consisting of tungsten carbide/(cobalt, nickel), titanium carbide/(cobalt, nickel), chromium carbide/nickel-chromium and chromium carbide/nickel.
 17. "Technology" specially designed to deposit diamond-like carbon on any of the following is not included in Category 2:

magnetic disk drives and heads, equipment for the manufacture of disposables, valves for faucets, acoustic diaphragms for speakers, engine parts for automobiles, cutting tools, punching-pressing dies, office automation equipment, microphones or medical devices or moulds, for casting or moulding of plastics, manufactured from alloys containing less than 5% beryllium.
 18. 'Silicon carbide' does not include cutting and forming tool materials.
 19. Ceramic substrates, as used in this Table, does not include ceramic materials containing 5% by weight, or greater, clay or cement content, either as separate constituents or in combination.

TABLE — DEPOSITION TECHNIQUES — TECHNICAL NOTE

Processes specified in Column 1 of the Table are defined as follows:

- a. Chemical Vapour Deposition (CVD) is an overlay coating or surface modification coating process wherein a metal, alloy, “composite”, dielectric or ceramic is deposited upon a heated substrate. Gaseous reactants are decomposed or combined in the vicinity of a substrate resulting in the deposition of the desired elemental, alloy or compound material on the substrate. Energy for this decomposition or chemical reaction process may be provided by the heat of the substrate, a glow discharge plasma, or “laser” irradiation.

Note 1

CVD includes the following processes: directed gas flow out-of-pack deposition, pulsating CVD, controlled nucleation thermal deposition (CNTD), plasma enhanced or plasma assisted CVD processes.

Note 2

Pack denotes a substrate immersed in a powder mixture.

Note 3

The gaseous reactants used in the out-of-pack process are produced using the same basic reactions and parameters as the pack cementation process, except that the substrate to be coated is not in contact with the powder mixture.

- b. Thermal Evaporation-Physical Vapour Deposition (TE-PVD) is an overlay coating process conducted in a vacuum with a pressure less than 0.1 Pa wherein a source of thermal energy is used to vaporise the coating material. This process results in the condensation, or deposition, of the evaporated species onto appropriately positioned substrates.

The addition of gases to the vacuum chamber during the coating process to synthesise compound coatings is an ordinary modification of the process.

The use of ion or electron beams, or plasma, to activate or assist the coating's deposition is also a common modification in this technique. The use of monitors to provide in-process measurement of optical characteristics and thickness of coatings can be a feature of these processes.

Specific TE-PVD processes are as follows:

1. Electron Beam PVD uses an electron beam to heat and evaporate the material which forms the coating;

2. Ion Assisted Resistive Heating PVD employs electrically resistive heating sources in combination with impinging ion beam(s) to produce a controlled and uniform flux of evaporated coating species;
3. “Laser” Vaporisation uses either pulsed or continuous wave “laser” beams to vaporise the material which forms the coating;
4. Cathodic Arc Deposition employs a consumable cathode of the material which forms the coating and has an arc discharge established on the surface by a momentary contact of a ground trigger. Controlled motion of arcing erodes the cathode surface creating a highly ionised plasma. The anode can be either a cone attached to the periphery of the cathode, through an insulator, or the chamber. Substrate biasing is used for non-line-of-sight deposition.

Note

This definition does not include random cathodic arc deposition with non-biased substrates.

5. Ion Plating is a special modification of a general TE-PVD process in which a plasma or an ion source is used to ionise the species to be deposited, and a negative bias is applied to the substrate in order to facilitate the extraction of the species from the plasma. The introduction of reactive species, evaporation of solids within the process chamber, and the use of monitors to provide in-process measurement of optical characteristics and thicknesses of coatings are ordinary modifications of the process.
- c. Pack Cementation is a surface modification coating or overlay coating process wherein a substrate is immersed in a powder mixture (a pack), that consists of:
1. The metallic powders that are to be deposited (usually aluminium, chromium, silicon or combinations thereof);
 2. An activator (normally a halide salt); and
 3. An inert powder, most frequently alumina.

The substrate and powder mixture is contained within a retort which is heated to between 1,030 K (757°C) and 1,375 K (1,102°C) for sufficient time to deposit the coating.

-
- d. Plasma Spraying is an overlay coating process wherein a gun (spray torch) which produces and controls a plasma accepts powder or wire coating materials, melts them and propels them towards a substrate, whereon an integrally bonded coating is formed. Plasma spraying constitutes either low pressure plasma spraying or high velocity plasma spraying.

Note 1

Low pressure means less than ambient atmospheric pressure.

Note 2

High velocity refers to nozzle-exit gas velocity exceeding 750 m/s calculated at 293 K (20°C) at 0.1 MPa.

- e. Slurry Deposition is a surface modification coating or overlay coating process wherein a metallic or ceramic powder with an organic binder is suspended in a liquid and is applied to a substrate by either spraying, dipping or painting, subsequent air or oven drying, and heat treatment to obtain the desired coating.
- f. Sputter Deposition is an overlay coating process based on a momentum transfer phenomenon, wherein positive ions are accelerated by an electric field towards the surface of a target (coating material). The kinetic energy of the impacting ions is sufficient to cause target surface atoms to be released and deposited on an appropriately positioned substrate.

Note 1

The Table refers only to triode, magnetron or reactive sputter deposition which is used to increase adhesion of the coating and rate of deposition and to radio frequency (RF) augmented sputter deposition used to permit vaporisation of non-metallic coating materials.

Note 2

Low-energy ion beams (less than 5 keV) can be used to activate the deposition.

- g. Ion Implantation is a surface modification coating process in which the element to be alloyed is ionised, accelerated through a potential gradient and implanted into the surface region of the substrate. This includes processes in which ion implantation is performed simultaneously with electron beam physical vapour deposition or sputter deposition.

Category Code	Item Description
CATEGORY 3 — ELECTRONICS	
3A	<p>Systems, Equipment and Components</p> <p><u>Note 1</u> <i>Equipment and components described in Category Code 3A001 or 3A002, other than those described in Category Code 3A001.a.3. to 3A001.a.10., 3A001.a.12. or 3A001.a.13., which are specially designed for or which have the same functional characteristics as other equipment are treated as coming within that description only if that other equipment is included in Division 2 of this Part.</i></p> <p><u>Note 2</u> <i>Integrated circuits described in Category Code 3A001.a.3. to 3A001.a.9., 3A001.a.12. or 3A001.a.13., which are unalterably programmed or designed for a specific function for another equipment are treated as coming within that description only if that other equipment is included in Division 2 of this Part.</i></p> <p><u>N.B.</u> <i>Where it is unclear if the other equipment is included in Division 2 of this Part, then the integrated circuit is treated as falling within Category Codes 3A001.a.3. to 3A001.a.9., 3A001.a.12. and 3A001.a.13. if it comes within the relevant description therein.</i></p>
3A001	<p>Electronic items as follows:</p> <p>a. General purpose integrated circuits, as follows:</p> <p><u>Note 1</u> <i>Category Code 3A001.a. includes wafers (finished or unfinished), in which the function has been determined, if it comes within the parameters set out therein.</i></p> <p><u>Note 2</u> <i>Integrated circuits include the following types:</i></p> <ul style="list-style-type: none"> – “Monolithic integrated circuits”; – “Hybrid integrated circuits”; – “Multichip integrated circuits”;

<i>Category Code</i>	<i>Item Description</i>
	<ul style="list-style-type: none"> – “Film type integrated circuits”, including silicon-on-sapphire integrated circuits; – “Optical integrated circuits”; – “Three dimensional integrated circuits”. <p>1. Integrated circuits designed or rated as radiation hardened to withstand any of the following:</p> <ul style="list-style-type: none"> a. A total dose of 5×10^3 Gy (silicon) or higher; b. A dose rate upset of 5×10^6 Gy (silicon)/s or higher; <u>or</u> c. A fluence (integrated flux) of neutrons (1 MeV equivalent) of 5×10^{13} n/cm² or higher on silicon, or its equivalent for other materials; <p><u>Note</u> <i>Category Code 3A001.a.I.c. does not include Metal Insulator Semiconductors (MIS).</i></p> <p>2. “Microprocessor microcircuits”, “microcomputer microcircuits”, microcontroller microcircuits, storage integrated circuits manufactured from a compound semiconductor, analogue-to-digital converters, digital-to-analogue converters, electro-optical or “optical integrated circuits” designed for “signal processing”, field programmable logic devices, custom integrated circuits for which either the function is unknown or the control status of the equipment in which the integrated circuit will be used is unknown, Fast Fourier Transform (FFT) processors, electrical erasable programmable read-only memories (EEPROMs), flash memories or static random-access memories (SRAMs), having any of the following characteristics:</p> <ul style="list-style-type: none"> a. Rated for operation at an ambient temperature above 398 K (125°C); b. Rated for operation at an ambient temperature below 218 K (-55°C); <u>or</u> c. Rated for operation over the entire ambient temperature range from 218 K (-55°C) to 398 K (125°C);

<i>Category Code</i>	<i>Item Description</i>
	<p data-bbox="603 454 667 488"><u>Note</u></p> <p data-bbox="603 495 1267 595"><i>Category Code 3A001.a.2. does not include integrated circuits for civil automobiles or railway train applications.</i></p> <p data-bbox="539 611 1267 745">3. “Microprocessor microcircuits”, “microcomputer microcircuits” and microcontroller microcircuits, manufactured from a compound semiconductor and operating at a clock frequency exceeding 40 MHz;</p> <p data-bbox="603 761 667 795"><u>Note</u></p> <p data-bbox="603 801 1267 902"><i>Category Code 3A001.a.3. includes digital signal processors, digital array processors and digital coprocessors.</i></p> <p data-bbox="539 918 722 952">4. Not used;</p> <p data-bbox="539 967 1267 1068">5. Analogue-to-Digital Converter (ADC) and Digital-to-Analogue Converter (DAC) integrated circuits, as follows:</p> <p data-bbox="624 1084 1267 1151">a. ADCs having any of the following characteristics:</p> <p data-bbox="687 1167 746 1200"><u>N.B.</u></p> <p data-bbox="687 1209 1066 1243"><i>See also Category Code 3A101.</i></p> <ol data-bbox="687 1258 1267 1827" style="list-style-type: none"> 1. A resolution of 8 bit or more, but less than 10 bit, with an output rate greater than 1,000 million words per second; 2. A resolution of 10 bit or more, but less than 12 bit, with an output rate greater than 500 million words per second; 3. A resolution of 12 bit or more, but less than 14 bit, with an output rate greater than 200 million words per second; 4. A resolution of 14 bit or more, but less than 16 bit, with an output rate greater than 250 million words per second; <u>or</u> 5. A resolution of 16 bit or more with an output rate greater than 65 million words per second;

Category Code	Item Description
	<p data-bbox="692 454 884 488"><u>Technical Notes</u></p> <ol data-bbox="692 499 1268 1832" style="list-style-type: none"> <li data-bbox="692 499 1268 566">1. A resolution of n bit corresponds to a quantisation of 2^n levels. <li data-bbox="692 577 1268 645">2. The number of bits in the output word is equal to the resolution of the ADC. <li data-bbox="692 656 1268 768">3. The output rate is the maximum output rate of the converter, regardless of the architecture or oversampling. <li data-bbox="692 779 1268 913">4. For 'multiple channel ADCs', the outputs are not aggregated and the output rate is the maximum output rate of any single channel. <li data-bbox="692 925 1268 1137">5. For 'interleaved ADCs' or for 'multiple channel ADCs' that are specified to have an interleaved mode of operation, the outputs are aggregated and the output rate is the maximum combined total output rate of all of the outputs. <li data-bbox="692 1149 1268 1317">6. Vendors may also refer to the output rate as sampling rate, conversion rate or throughput rate. It is often specified in megahertz (MHz) or mega samples per second (MSPS). <li data-bbox="692 1328 1268 1429">7. For the purpose of measuring output rate, one output word per second is equivalent to one Hertz or one sample per second. <li data-bbox="692 1440 1268 1585">8. 'Multiple channel ADCs' are defined as devices which integrate more than one ADC, designed so that each ADC has a separate analogue input. <li data-bbox="692 1597 1268 1832">9. 'Interleaved ADCs' are defined as devices which have multiple ADC units that sample the same analogue input at different times such that when the outputs are aggregated, the analogue input has been effectively sampled and converted at a higher sampling rate.

<i>Category Code</i>	<i>Item Description</i>
	<p>b. Digital-to-Analogue Converters (DAC) having any of the following characteristics:</p> <ol style="list-style-type: none"> 1. A resolution of 10 bit or more with an ‘adjusted update rate’ of greater than 3,500 MSPS; <u>or</u> 2. A resolution of 12 bit or more with an ‘adjusted update rate’ of greater than 1,250 MSPS and having any of the following characteristics: <ol style="list-style-type: none"> a. A “settling time” less than 9 ns to 0.024% of full scale from a full scale step; <u>or</u> b. A ‘Spurious Free Dynamic Range’ (SFDR) greater than 68 dBc (carrier) when synthesising a full scale analogue signal of 100 MHz or the highest full scale analogue signal frequency specified below 100 MHz; <p><u>Technical Notes</u></p> <ol style="list-style-type: none"> 1. ‘Spurious Free Dynamic Range’ (SFDR) is defined as the ratio of the RMS value of the carrier frequency (maximum signal component) at the input of the DAC to the RMS value of the next largest noise or harmonic distortion component at its output. 2. SFDR is determined directly from the specification table or from the characterisation plots of SFDR versus frequency. 3. A signal is defined to be full scale when its amplitude is greater than -3 dBfs (full scale). 4. ‘Adjusted update rate’ for DACs:

Category Code	Item Description
	<p>a. <i>For conventional (non-interpolating) DACs, the ‘adjusted update rate’ is the rate at which the digital signal is converted to an analogue signal and the output analogue values are changed by the DAC. For DACs where the interpolation mode may be bypassed (interpolation factor of one), the DAC should be considered as a conventional (non-interpolating) DAC.</i></p> <p>b. <i>For interpolating DACs (oversampling DACs), the ‘adjusted update rate’ is defined as the DAC update rate divided by the smallest interpolating factor. For interpolating DACs, the ‘adjusted update rate’ may be referred to by different terms including:</i></p> <ul style="list-style-type: none"> <i>– input data rate</i> <i>– input word rate</i> <i>– input sample rate</i> <i>– maximum total input bus rate</i> <i>– maximum DAC clock rate for DAC clock input.</i> <p>6. Electro-optical and “optical integrated circuits”, designed for “signal processing” and having all of the following characteristics:</p> <ul style="list-style-type: none"> a. One or more than one internal “laser” diode; b. One or more than one internal light detecting element; <u>and</u> c. Optical waveguides;

<i>Category Code</i>	<i>Item Description</i>
	<p>7. Field programmable logic devices having any of the following characteristics:</p> <ol style="list-style-type: none"> a. A maximum number of single-ended digital inputs/outputs of greater than 700; <u>or</u> b. An ‘aggregate one-way peak serial transceiver data rate’ of 500 Gb/s or greater; <p><u>Note</u> <i>Category Code 3A001.a.7. includes:</i></p> <ul style="list-style-type: none"> – <i>Simple Programmable Logic Devices (SPLDs)</i> – <i>Complex Programmable Logic Devices (CPLDs)</i> – <i>Field Programmable Gate Arrays (FPGAs)</i> – <i>Field Programmable Logic Arrays (FPLAs)</i> – <i>Field Programmable Interconnects (FPICs)</i> <p><u>Technical Notes</u></p> <ol style="list-style-type: none"> 1. <i>Maximum number of digital inputs/outputs in Category Code 3A001.a.7.a. is also referred to as the maximum user inputs/outputs or maximum available inputs/outputs, whether the integrated circuit is packaged or bare die.</i> 2. <i>‘Aggregate one-way peak serial transceiver data rate’ is the product of the peak serial one-way transceiver data rate times the number of transceivers on the FPGA.</i> <p>8. Not used;</p> <p>9. Neural network integrated circuits;</p> <p>10. Custom integrated circuits for which the function is unknown, or the control status of the equipment in which the integrated circuits will be used is unknown to the manufacturer, having any of the following characteristics:</p>

<i>Category Code</i>	<i>Item Description</i>
	<ul style="list-style-type: none"> a. Have more than 1,500 terminals; b. A typical “basic gate propagation delay time” of less than 0.02 ns; <u>or</u> c. An operating frequency exceeding 3 GHz; <p>11. Digital integrated circuits, other than those described in Category Codes 3A001.a.3. to 3A001.a.10. and 3A001.a.12., based upon any compound semiconductor and having either of the following characteristics:</p> <ul style="list-style-type: none"> a. An equivalent gate count of more than 3,000 (2 input gates); <u>or</u> b. A toggle frequency exceeding 1.2 GHz; <p>12. Fast Fourier Transform (FFT) processors having a rated execution time for an N-point complex FFT of less than $(N \log_2 N)/20,480$ ms, where N is the number of points;</p> <p><i>Technical Note</i> <i>When N is equal to 1,024 points, the formula in Category Code 3A001.a.12. gives an execution time of 500 μs.</i></p> <p>13. Direct Digital Synthesiser (DDS) integrated circuits having any of the following characteristics:</p> <ul style="list-style-type: none"> a. A Digital-to-Analogue Converter (DAC) clock frequency of 3.5 GHz or more and a DAC resolution of 10 bit or more, but less than 12 bit; <u>or</u> b. A DAC clock frequency of 1.25 GHz or more and a DAC resolution of 12 bit or more; <p><i>Technical Note</i> <i>The DAC clock frequency may be specified as the master clock frequency or the input clock frequency.</i></p>

Category Code	Item Description
	<p>b. Microwave or millimetre wave items, as follows:</p> <p><u>Technical Note</u></p> <p><i>For the purpose of Category Code 3A001.b., the parameter peak saturated power output may also be referred to on product data sheets as output power, saturated power output, maximum power output, peak power output, or peak envelope power output.</i></p> <p>1. Electronic vacuum tubes and cathodes, as follows:</p> <p><u>Note 1</u></p> <p><i>Category Code 3A001.b.1. does not include tubes designed or rated for operation in any frequency band and having both of the following characteristics:</i></p> <ol style="list-style-type: none"> a. <i>Does not exceed 31.8 GHz; <u>and</u></i> b. <i>Is “allocated by the ITU” for radio-communications services, but not for radio-determination.</i> <p><u>Note 2</u></p> <p><i>Category Code 3A001.b.1. does not include non-“space-qualified” tubes having all of the following characteristics:</i></p> <ol style="list-style-type: none"> a. <i>An average output power equal to or less than 50 W; <u>and</u></i> b. <i>Designed or rated for operation in any frequency band and having all of the following characteristics:</i> <ol style="list-style-type: none"> 1. <i>Exceeds 31.8 GHz but does not exceed 43.5 GHz; <u>and</u></i> 2. <i>Is “allocated by the ITU” for radio-communications services, but not for radio-determination.</i> <p>a. Travelling wave tubes, pulsed or continuous wave, as follows:</p> <ol style="list-style-type: none"> 1. Tubes operating at frequencies exceeding 31.8 GHz;

<i>Category Code</i>	<i>Item Description</i>
	<ol style="list-style-type: none"> <li data-bbox="691 454 1268 555">2. Tubes having a cathode heater element with a turn on time to rated RF power of less than 3 seconds; <li data-bbox="691 568 1268 701">3. Coupled cavity tubes, or derivatives thereof, with a “fractional bandwidth” of more than 7% or a peak power exceeding 2.5 kW; <li data-bbox="691 719 1268 1402">4. Helix tubes, or derivatives thereof, having any of the following characteristics: <ol style="list-style-type: none"> <li data-bbox="751 804 1268 969">a. An “instantaneous bandwidth” of more than one octave, and average power (expressed in kW) times frequency (expressed in GHz) of more than 0.5; <li data-bbox="751 987 1268 1120">b. An “instantaneous bandwidth” of one octave or less, and average power (expressed in kW) times frequency (expressed in GHz) of more than 1; <u>or</u> <li data-bbox="751 1137 1268 1171">c. Being “space-qualified”; <li data-bbox="627 1189 1268 1249">b. Crossed-field amplifier tubes with a gain of more than 17 dB; <li data-bbox="627 1267 1268 1402">c. Impregnated cathodes designed for electronic tubes producing a continuous emission current density at rated operating conditions exceeding 5 A/cm²; <li data-bbox="544 1420 1268 1821">2. Microwave “Monolithic Integrated Circuits” (MMIC) power amplifiers having any of the following characteristics: <ol style="list-style-type: none"> <li data-bbox="627 1541 1268 1673">a. Rated for operation at frequencies exceeding 2.7 GHz up to and including 6.8 GHz with a “fractional bandwidth” greater than 15%, and having any of the following characteristics: <ol style="list-style-type: none"> <li data-bbox="691 1691 1268 1821">1. A peak saturated power output greater than 75 W (48.75 dBm) at any frequency exceeding 2.7 GHz up to and including 2.9 GHz;

<i>Category Code</i>	<i>Item Description</i>
	<ol style="list-style-type: none"> <li data-bbox="691 454 1259 584">2. A peak saturated power output greater than 55 W (47.4 dBm) at any frequency exceeding 2.9 GHz up to and including 3.2 GHz; <li data-bbox="691 607 1259 736">3. A peak saturated power output greater than 40 W (46 dBm) at any frequency exceeding 3.2 GHz up to and including 3.7 GHz; <u>or</u> <li data-bbox="691 759 1259 889">4. A peak saturated power output greater than 20 W (43 dBm) at any frequency exceeding 3.7 GHz up to and including 6.8 GHz; <ol style="list-style-type: none"> <li data-bbox="628 911 1259 1305">b. Rated for operation at frequencies exceeding 6.8 GHz up to and including 16 GHz with a “fractional bandwidth” greater than 10%, and having any of the following characteristics: <ol style="list-style-type: none"> <li data-bbox="691 1059 1259 1189">1. A peak saturated power output greater than 10 W (40 dBm) at any frequency exceeding 6.8 GHz up to and including 8.5 GHz; <u>or</u> <li data-bbox="691 1211 1259 1305">2. A peak saturated power output greater than 5 W (37 dBm) at any frequency exceeding 8.5 GHz up to and including 16 GHz; <li data-bbox="628 1328 1259 1485">c. Rated for operation with a peak saturated power output greater than 3 W (34.77 dBm) at any frequency exceeding 16 GHz up to and including 31.8 GHz, and with a “fractional bandwidth” of greater than 10%; <li data-bbox="628 1507 1259 1637">d. Rated for operation with a peak saturated power output greater than 0.1 nW (-70 dBm) at any frequency exceeding 31.8 GHz up to and including 37 GHz; <li data-bbox="628 1659 1259 1825">e. Rated for operation with a peak saturated power output greater than 1 W (30 dBm) at any frequency exceeding 37 GHz up to and including 43.5 GHz, and with a “fractional bandwidth” of greater than 10%;

<i>Category Code</i>	<i>Item Description</i>
	<p>f. Rated for operation with a peak saturated power output greater than 31.62 mW (15 dBm) at any frequency exceeding 43.5 GHz up to and including 75 GHz, and with a “fractional bandwidth” of greater than 10%;</p> <p>g. Rated for operation with a peak saturated power output greater than 10 mW (10 dBm) at any frequency exceeding 75 GHz up to and including 90 GHz, and with a “fractional bandwidth” of greater than 5%; <u>or</u></p> <p>h. Rated for operation with a peak saturated power output greater than 0.1 nW (-70 dBm) at any frequency exceeding 90 GHz;</p> <p><i>Note 1</i> Not used.</p> <p><i>Note 2</i> Whether any MMIC whose rated operating frequency includes frequencies listed in more than one frequency range, as defined by Category Codes 3A001.b.2.a. to 3A001.b.2.h., is included in that Category is determined by the lowest peak saturated power output threshold.</p> <p><i>Note 3</i> Notes 1 and 2 in Category 3A mean that Category Code 3A001.b.2. does not include MMICs if they are specially designed for other applications, e.g. telecommunications, radar, automobiles.</p> <p>3. Discrete microwave transistors having any of the following characteristics:</p> <p>a. Rated for operation at frequencies exceeding 2.7 GHz up to and including 6.8 GHz and having any of the following characteristics:</p> <p>1. A peak saturated power output greater than 400 W (56 dBm) at any frequency exceeding 2.7 GHz up to and including 2.9 GHz;</p>

<i>Category Code</i>	<i>Item Description</i>
	<ol style="list-style-type: none"> <li data-bbox="691 454 1259 584">2. A peak saturated power output greater than 205 W (53.12 dBm) at any frequency exceeding 2.9 GHz up to and including 3.2 GHz; <li data-bbox="691 607 1259 736">3. A peak saturated power output greater than 115 W (50.61 dBm) at any frequency exceeding 3.2 GHz up to and including 3.7 GHz; <u>or</u> <li data-bbox="691 759 1259 889">4. A peak saturated power output greater than 60 W (47.78 dBm) at any frequency exceeding 3.7 GHz up to and including 6.8 GHz; <p data-bbox="628 911 1259 1003">b. Rated for operation at frequencies exceeding 6.8 GHz up to and including 31.8 GHz and having any of the following characteristics:</p> <ol style="list-style-type: none"> <li data-bbox="691 1025 1259 1155">1. A peak saturated power output greater than 50 W (47 dBm) at any frequency exceeding 6.8 GHz up to and including 8.5 GHz; <li data-bbox="691 1178 1259 1308">2. A peak saturated power output greater than 15 W (41.76 dBm) at any frequency exceeding 8.5 GHz up to and including 12 GHz; <li data-bbox="691 1330 1259 1460">3. A peak saturated power output greater than 40 W (46 dBm) at any frequency exceeding 12 GHz up to and including 16 GHz; <u>or</u> <li data-bbox="691 1482 1259 1612">4. A peak saturated power output greater than 7 W (38.45 dBm) at any frequency exceeding 16 GHz up to and including 31.8 GHz; <p data-bbox="628 1635 1259 1756">c. Rated for operation with a peak saturated power output greater than 0.5 W (27 dBm) at any frequency exceeding 31.8 GHz up to and including 37 GHz;</p>

<i>Category Code</i>	<i>Item Description</i>
	<p>d. Rated for operation with a peak saturated power output greater than 1 W (30 dBm) at any frequency exceeding 37 GHz up to and including 43.5 GHz; <u>or</u></p> <p>e. Rated for operation with a peak saturated power output greater than 0.1 nW (-70 dBm) at any frequency exceeding 43.5 GHz;</p> <p><u>Note 1</u> <i>Whether a transistor whose rated operating frequency includes frequencies listed in more than one frequency range, as defined by Category Codes 3A001.b.3.a. to 3A001.b.3.e., is included under that Category is determined by the lowest peak saturated power output threshold.</i></p> <p><u>Note 2</u> <i>Category Code 3A001.b.3. includes bare dice, dice mounted on carriers, or dice mounted in packages. Some discrete transistors may also be referred to as power amplifiers, but the status of these discrete transistors is determined by Category Code 3A001.b.3.</i></p> <p>4. Microwave solid state amplifiers and microwave assemblies/modules containing microwave solid state amplifiers, having any of the following characteristics:</p> <p>a. Rated for operation at frequencies exceeding 2.7 GHz up to and including 6.8 GHz with a “fractional bandwidth” greater than 15%, and having any of the following characteristics:</p> <ol style="list-style-type: none"> 1. A peak saturated power output greater than 500 W (57 dBm) at any frequency exceeding 2.7 GHz up to and including 2.9 GHz; 2. A peak saturated power output greater than 270 W (54.3 dBm) at any frequency exceeding 2.9 GHz up to and including 3.2 GHz;

<i>Category Code</i>	<i>Item Description</i>
	<ol style="list-style-type: none"> <li data-bbox="692 454 1259 584">3. A peak saturated power output greater than 200 W (53 dBm) at any frequency exceeding 3.2 GHz up to and including 3.7 GHz; <u>or</u> <li data-bbox="692 607 1259 736">4. A peak saturated power output greater than 90 W (49.54 dBm) at any frequency exceeding 3.7 GHz up to and including 6.8 GHz; <p data-bbox="628 759 1259 889">b. Rated for operation at frequencies exceeding 6.8 GHz up to and including 31.8 GHz with a “fractional bandwidth” greater than 10%, and having any of the following characteristics:</p> <ol style="list-style-type: none"> <li data-bbox="692 911 1259 1041">1. A peak saturated power output greater than 70 W (48.54 dBm) at any frequency exceeding 6.8 GHz up to and including 8.5 GHz; <li data-bbox="692 1064 1259 1193">2. A peak saturated power output greater than 50 W (47 dBm) at any frequency exceeding 8.5 GHz up to and including 12 GHz; <li data-bbox="692 1216 1259 1346">3. A peak saturated power output greater than 30 W (44.77 dBm) at any frequency exceeding 12 GHz up to and including 16 GHz; <u>or</u> <li data-bbox="692 1368 1259 1498">4. A peak saturated power output greater than 20 W (43 dBm) at any frequency exceeding 16 GHz up to and including 31.8 GHz; <p data-bbox="628 1520 1259 1650">c. Rated for operation with a peak saturated power output greater than 0.5 W (27 dBm) at any frequency exceeding 31.8 GHz up to and including 37 GHz;</p> <p data-bbox="628 1673 1259 1825">d. Rated for operation with a peak saturated power output greater than 2 W (33 dBm) at any frequency exceeding 37 GHz up to and including 43.5 GHz, and with a “fractional bandwidth” of greater than 10%;</p>

<i>Category Code</i>	<i>Item Description</i>
	<p>e. Rated for operation at frequencies exceeding 43.5 GHz and having any of the following characteristics:</p> <ol style="list-style-type: none"> 1. A peak saturated power output greater than 0.2 W (23 dBm) at any frequency exceeding 43.5 GHz up to and including 75 GHz, and with a “fractional bandwidth” of greater than 10%; 2. A peak saturated power output greater than 20 mW (13 dBm) at any frequency exceeding 75 GHz up to and including 90 GHz, and with a “fractional bandwidth” of greater than 5%; <u>or</u> 3. A peak saturated power output greater than 0.1 nW (-70 dBm) at any frequency exceeding 90 GHz; <u>or</u> <p>f. Rated for operation at frequencies above 2.7 GHz and having all of the following characteristics:</p> <ol style="list-style-type: none"> 1. A peak saturated power output (in watts), P_{sat}, greater than 400 divided by the maximum operating frequency (in GHz) squared [$P_{\text{sat}} > 400 \text{ W} \cdot \text{GHz}^2 / f_{\text{GHz}}^2$]; 2. A “fractional bandwidth” of 5% or greater; <u>and</u> 3. Any two sides perpendicular to one another with either length d (in cm) equal to or less than 15 divided by the lowest operating frequency in GHz [$d \leq 15 \text{ cm} \cdot \text{GHz} / f_{\text{GHz}}$]; <p><u>Technical Note</u></p> <p><i>2.7 GHz should be used as the lowest operating frequency (f_{GHz}) in the formula in Category Code 3A001.b.4.f.3., for amplifiers that have a rated operating range extending downward to 2.7 GHz and below [$d \leq 15 \text{ cm} \cdot \text{GHz} / 2.7 \text{ GHz}$].</i></p>

Category Code	Item Description
	<p><u>N.B.</u> MMIC power amplifiers should be evaluated against the criteria in Category Code 3A001.b.2.</p> <p><u>Note 1</u> Not used.</p> <p><u>Note 2</u> Whether an item whose rated operating frequency includes frequencies listed in more than one frequency range, as defined by Category Codes 3A001.b.4.a. to 3A001.b.4.e., is included in that Category is determined by the lowest peak saturated power output threshold.</p> <p><u>Note 3</u> Category Code 3A001.b.4. includes transmit/receive modules and transmit modules.</p> <p>5. Electronically or magnetically tunable band-pass or band-stop filters, having more than 5 tunable resonators capable of tuning across 1.5:1 frequency band (f_{\max}/f_{\min}) in less than 10 μs and having any of the following characteristics:</p> <ul style="list-style-type: none"> a. A band-pass bandwidth of more than 0.5% of centre frequency; <u>or</u> b. A band-stop bandwidth of less than 0.5% of centre frequency; <p>6. Not used;</p> <p>7. Converters and harmonic mixers having any of the following characteristics:</p> <ul style="list-style-type: none"> a. Designed to extend the frequency range of “signal analysers” beyond 90 GHz;

<i>Category Code</i>	<i>Item Description</i>
	<ul style="list-style-type: none"> b. Designed to extend the operating range of signal generators as follows: <ul style="list-style-type: none"> 1. Beyond 90 GHz; 2. To an output power greater than 100 mW (20 dBm) anywhere within the frequency range exceeding 43.5 GHz but not exceeding 90 GHz; c. Designed to extend the operating range of network analysers as follows: <ul style="list-style-type: none"> 1. Beyond 110 GHz; 2. To an output power greater than 31.62 mW (15 dBm) anywhere within the frequency range exceeding 43.5 GHz but not exceeding 90 GHz; 3. To an output power greater than 1 mW (0 dBm) anywhere within the frequency range exceeding 90 GHz but not exceeding 110 GHz; <u>or</u> d. Designed to extend the frequency range of microwave test receivers beyond 110 GHz; <p>8. Microwave power amplifiers containing tubes specified in Category Code 3A001.b.1. and having all of the following characteristics:</p> <ul style="list-style-type: none"> a. Operating frequencies above 3 GHz; b. An average output power to mass ratio exceeding 80 W/kg; <u>and</u> c. A volume of less than 400 cm³; <p><u>Note</u> <i>Category Code 3A001.b.8. does not include equipment designed or rated for operation in any frequency band which is “allocated by the ITU” for radio-communications services, but not for radio-determination.</i></p>

<i>Category Code</i>	<i>Item Description</i>
	<p>9. Microwave power modules (MPM), consisting of, at least, a travelling wave tube, a microwave “monolithic integrated circuit” and an integrated electronic power conditioner and having all of the following characteristics:</p> <ol style="list-style-type: none"> a. A ‘turn-on time’ from off to fully operational in less than 10 seconds; b. A volume less than the maximum rated power in watts multiplied by $10 \text{ cm}^3/\text{W}$; <u>and</u> c. An “instantaneous bandwidth” greater than 1 octave ($f_{\max} > 2f_{\min}$) and having any of the following characteristics: <ol style="list-style-type: none"> 1. For frequencies equal to or less than 18 GHz, an RF output power greater than 100 W; <u>or</u> 2. A frequency greater than 18 GHz; <p><u>Technical Notes</u></p> <ol style="list-style-type: none"> 1. To calculate the volume in Category Code 3A001.b.9.b., the following example is provided: for a maximum rated power of 20 W, the volume would be: $20 \text{ W} \times 10 \text{ cm}^3/\text{W} = 200 \text{ cm}^3$. 2. The ‘turn-on time’ in Category Code 3A001.b.9.a. refers to the time from fully-off to fully operational, i.e. it includes the warm-up time of the MPM. <p>10. Oscillators or oscillator assemblies, specified to operate with a single sideband (SSB) phase noise, in dBc/Hz, less (better) than $-(126 + 20\log_{10}F - 20\log_{10}f)$ anywhere within the range of $10 \text{ Hz} \leq F \leq 10 \text{ kHz}$;</p> <p><u>Technical Note</u></p> <p>In Category Code 3A001.b.10., F is the offset from the operating frequency in Hz and f is the operating frequency in MHz.</p>

<i>Category Code</i>	<i>Item Description</i>
	<p>11. “Frequency synthesiser” “electronic assemblies” having a “frequency switching time” as specified by any of the following:</p> <ol style="list-style-type: none"> a. Less than 156 ps; b. Less than 100 μs for any frequency change exceeding 1.6 GHz within the synthesised frequency range exceeding 4.8 GHz but not exceeding 10.6 GHz; c. Less than 250 μs for any frequency change exceeding 550 MHz within the synthesised frequency range exceeding 10.6 GHz but not exceeding 31.8 GHz; d. Less than 500 μs for any frequency change exceeding 550 MHz within the synthesised frequency range exceeding 31.8 GHz but not exceeding 43.5 GHz; e. Less than 1 ms for any frequency change exceeding 550 MHz within the synthesised frequency range exceeding 43.5 GHz but not exceeding 56 GHz; f. Less than 1 ms for any frequency change exceeding 2.2 GHz within the synthesised frequency range exceeding 56 GHz but not exceeding 90 GHz; <u>or</u> g. Less than 1 ms within the synthesised frequency range exceeding 90 GHz; <p><u><i>N.B.</i></u> <i>For general purpose “signal analysers”, signal generators, network analysers and microwave test receivers, see Category Codes 3A002.c., 3A002.d., 3A002.e. and 3A002.f., respectively.</i></p>

<i>Category Code</i>	<i>Item Description</i>
	<p>c. Acoustic wave devices as follows and specially designed components therefor:</p> <ol style="list-style-type: none"> 1. Surface acoustic wave and surface skimming (shallow bulk) acoustic wave devices, having any of the following characteristics: <ol style="list-style-type: none"> a. A carrier frequency exceeding 6 GHz; b. A carrier frequency exceeding 1 GHz, but not exceeding 6 GHz, and having any of the following characteristics: <ol style="list-style-type: none"> 1. A 'frequency side-lobe rejection' exceeding 65 dB; 2. A product of the maximum delay time and the bandwidth (time in μs and bandwidth in MHz) of more than 100; 3. A bandwidth greater than 250 MHz; <u>or</u> 4. A dispersive delay of more than 10 μs; <u>or</u> c. A carrier frequency of 1 GHz or less and having any of the following characteristics: <ol style="list-style-type: none"> 1. A product of the maximum delay time and the bandwidth (time in μs and bandwidth in MHz) of more than 100; 2. A dispersive delay of more than 10 μs; <u>or</u> 3. A 'frequency side-lobe rejection' exceeding 65 dB and a bandwidth greater than 100 MHz; <p><i>Technical Note</i> <i>'Frequency side-lobe rejection' is the maximum rejection value specified in data sheet.</i></p> <ol style="list-style-type: none"> 2. Bulk (volume) acoustic wave devices which permit the direct processing of signals at frequencies exceeding 6 GHz;

<i>Category Code</i>	<i>Item Description</i>
	<p data-bbox="544 454 1268 618">3. Acoustic-optic “signal processing” devices employing interaction between acoustic waves (bulk wave or surface wave) and light waves which permit the direct processing of signals or images, including spectral analysis, correlation or convolution;</p> <p data-bbox="544 640 603 667"><u>Note</u></p> <p data-bbox="544 680 1268 779"><i>Category Code 3A001.c. does not include acoustic wave devices that are limited to a single band pass, low pass, high pass or notch filtering, or resonating function.</i></p> <p data-bbox="480 797 1268 960">d. Electronic devices and circuits containing components, manufactured from “superconductive” materials, specially designed for operation at temperatures below the “critical temperature” of at least one of the “superconductive” constituents and having any of the following characteristics:</p> <ol data-bbox="544 983 1268 1196" style="list-style-type: none"> <li data-bbox="544 983 1268 1115">1. Current switching for digital circuits using “superconductive” gates with a product of delay time per gate (in seconds) and power dissipation per gate (in watts) of less than 10^{-14} J; <u>or</u> <li data-bbox="544 1133 1268 1196">2. Frequency selection at all frequencies using resonant circuits with Q-values exceeding 10,000; <p data-bbox="480 1218 932 1245">e. High energy devices, as follows:</p> <ol data-bbox="544 1267 1268 1464" style="list-style-type: none"> <li data-bbox="544 1267 836 1294">1. ‘Cells’, as follows: <ol data-bbox="624 1317 1268 1464" style="list-style-type: none"> <li data-bbox="624 1317 1268 1379">a. ‘Primary cells’ having an ‘energy density’ exceeding 550 Wh/kg at 20°C; <li data-bbox="624 1402 1268 1464">b. ‘Secondary cells’ having an ‘energy density’ exceeding 350 Wh/kg at 20°C; <p data-bbox="608 1487 804 1514"><u>Technical Notes</u></p> <ol data-bbox="624 1536 1268 1856" style="list-style-type: none"> <li data-bbox="624 1536 1268 1856">1. <i>For the purpose of Category Code 3A001.e.1., ‘energy density’ (Wh/kg) is calculated from the nominal voltage multiplied by the nominal capacity in ampere-hours (Ah) divided by the mass in kilograms. If the nominal capacity is not stated, energy density is calculated from the nominal voltage squared then multiplied by the discharge duration in hours divided by the discharge load in ohms and the mass in kilograms.</i>

Category Code	Item Description
	<p data-bbox="628 454 1257 618">2. For the purpose of Category Code 3A001.e.1., a 'cell' is defined as an electrochemical device, which has positive and negative electrodes, an electrolyte, and is a source of electrical energy. It is the basic building block of a battery.</p> <p data-bbox="628 640 1257 734">3. For the purpose of Category Code 3A001.e.1.a., a 'primary cell' is a 'cell' that is not designed to be charged by any other source.</p> <p data-bbox="628 757 1257 851">4. For the purpose of Category Code 3A001.e.1.b., a 'secondary cell' is a 'cell' that is designed to be charged by an external electrical source.</p> <p data-bbox="608 875 663 902"><u>Note</u></p> <p data-bbox="608 913 1257 976">Category Code 3A001.e.1. does not include batteries, including single-cell batteries.</p> <p data-bbox="544 999 1114 1025">2. High energy storage capacitors, as follows:</p> <p data-bbox="608 1048 663 1075"><u>N.B.</u></p> <p data-bbox="608 1086 1257 1149">See also Category Code 3A201.a. and Division 2 of Part 1 of this Schedule.</p> <p data-bbox="628 1171 1257 1265">a. Capacitors with a repetition rate of less than 10 Hz (single shot capacitors) and having all of the following characteristics:</p> <ol data-bbox="692 1288 1257 1485" style="list-style-type: none"> <li data-bbox="692 1288 1257 1350">1. A voltage rating equal to or more than 5 kV; <li data-bbox="692 1373 1257 1435">2. An energy density equal to or more than 250 J/kg; <u>and</u> <li data-bbox="692 1458 1257 1485">3. A total energy equal to or more than 25 kJ; <p data-bbox="628 1507 1257 1601">b. Capacitors with a repetition rate of 10 Hz or more (repetition rated capacitors) and having all of the following characteristics:</p> <ol data-bbox="692 1624 1257 1843" style="list-style-type: none"> <li data-bbox="692 1624 1257 1686">1. A voltage rating equal to or more than 5 kV; <li data-bbox="692 1709 1257 1771">2. An energy density equal to or more than 50 J/kg; <li data-bbox="692 1794 1257 1843">3. A total energy equal to or more than 100 J; <u>and</u>

Category Code	Item Description
	<p data-bbox="692 454 1259 517">4. A charge/discharge cycle life equal to or more than 10,000;</p> <p data-bbox="544 539 1259 667">3. “Superconductive” electromagnets and solenoids, specially designed to be fully charged or discharged in less than one second and having all of the following characteristics:</p> <p data-bbox="604 689 660 719"><u>N.B.</u></p> <p data-bbox="604 730 1003 759">See also Category Code 3A201.b.</p> <p data-bbox="604 781 660 810"><u>Note</u></p> <p data-bbox="604 822 1259 949">Category Code 3A001.e.3. does not include “superconductive” electromagnets or solenoids specially designed for Magnetic Resonance Imaging (MRI) medical equipment.</p> <p data-bbox="628 972 1259 1034">a. Energy delivered during the discharge exceeding 10 kJ in the first second;</p> <p data-bbox="628 1057 1259 1120">b. Inner diameter of the current carrying windings of more than 250 mm; <u>and</u></p> <p data-bbox="628 1142 1259 1234">c. Rated for a magnetic induction of more than 8 T or “overall current density” in the winding of more than 300 A/mm²;</p> <p data-bbox="544 1256 1259 1487">4. Solar cells, cell-interconnect-coverglass (CIC) assemblies, solar panels, and solar arrays, which are “space-qualified”, having a minimum average efficiency exceeding 20% at an operating temperature of 301 K (28°C) under simulated ‘AMO’ illumination with an irradiance of 1,367 watts per square metre (W/m²);</p> <p data-bbox="604 1509 788 1538"><u>Technical Note</u></p> <p data-bbox="604 1550 1259 1677">‘AMO’, or ‘Air Mass Zero’, refers to the spectral irradiance of sun light in the earth's outer atmosphere when the distance between the earth and sun is one astronomical unit (AU).</p> <p data-bbox="480 1700 1259 1762">f. Rotary input type absolute position encoders having an “accuracy” equal to or less (better) than 1 second of arc;</p>

<i>Category Code</i>	<i>Item Description</i>
	<p>g. Solid-state pulsed power switching thyristor devices and ‘thyristor modules’, using either electrically, optically, or electron radiation controlled switch methods and having any of the following characteristics:</p> <ol style="list-style-type: none"> 1. A maximum turn-on current rate of rise (di/dt) greater than 30,000 A/μs and off-state voltage greater than 1,100 V; <u>or</u> 2. A maximum turn-on current rate of rise (di/dt) greater than 2,000 A/μs and having both of the following characteristics: <ol style="list-style-type: none"> a. An off-state peak voltage equal to or greater than 3,000 V; <u>and</u> b. A peak (surge) current equal to or greater than 3,000 A; <p><u>Note 1</u> Category Code 3A001.g. includes:</p> <ul style="list-style-type: none"> – Silicon Controlled Rectifiers (SCRs) – Electrical Triggering Thyristors (ETTs) – Light Triggering Thyristors (LTTs) – Integrated Gate Commutated Thyristors (IGCTs) – Gate Turn-off Thyristors (GTOs) – MOS Controlled Thyristors (MCTs) – Solidtrons <p><u>Note 2</u> Category Code 3A001.g. does not include thyristor devices and ‘thyristor modules’ incorporated into equipment designed for civil railway or “civil aircraft” applications.</p> <p><u>Technical Note</u> For the purpose of Category Code 3A001.g., a ‘thyristor module’ contains one or more thyristor devices.</p> <p>h. Solid-state power semiconductor switches, diodes, or ‘modules’, having all of the following characteristics:</p>

Category Code	Item Description
	<ol style="list-style-type: none"> 1. Rated for a maximum operating junction temperature greater than 488 K (215°C); 2. Repetitive peak off-state voltage (blocking voltage) exceeding 300 V; <u>and</u> 3. Continuous current greater than 1 A. <p><u>Note 1</u> <i>Repetitive peak off-state voltage in Category Code 3A001.h. includes drain to source voltage, collector to emitter voltage, repetitive peak reverse voltage and peak repetitive off-state blocking voltage.</i></p> <p><u>Note 2</u> <i>Category Code 3A001.h. includes:</i></p> <ul style="list-style-type: none"> – <i>Junction Field Effect Transistors (JFETs)</i> – <i>Vertical Junction Field Effect Transistors (VJFETs)</i> – <i>Metal Oxide Semiconductor Field Effect Transistors (MOSFETs)</i> – <i>Double Diffused Metal Oxide Semiconductor Field Effect Transistor (DMOSFET)</i> – <i>Insulated Gate Bipolar Transistor (IGBT)</i> – <i>High Electron Mobility Transistors (HEMTs)</i> – <i>Bipolar Junction Transistors (BJTs)</i> – <i>Thyristors and Silicon Controlled Rectifiers (SCRs)</i> – <i>Gate Turn-Off Thyristors (GTOs)</i> – <i>Emitter Turn-Off Thyristors (ETOs)</i> – <i>PiN Diodes</i> – <i>Schottky Diodes</i> <p><u>Note 3</u> <i>Category Code 3A001.h. does not include switches, diodes, or ‘modules’, incorporated into equipment designed for civil automobile, civil railway or “civil aircraft” applications.</i></p>

<i>Category Code</i>	<i>Item Description</i>
3A002	<p data-bbox="539 454 724 488"><u>Technical Note</u></p> <p data-bbox="539 495 1259 595"><i>For the purpose of Category Code 3A001.h., ‘modules’ contain one or more solid-state power semiconductor switches or diodes.</i></p> <p data-bbox="475 663 1259 725">General purpose “electronic assemblies”, modules and equipment, as follows:</p> <p data-bbox="475 745 1155 779">a. Recording equipment and oscilloscopes, as follows:</p> <ol data-bbox="539 792 1259 1308" style="list-style-type: none"> <li data-bbox="539 792 724 826">1. Not used; <li data-bbox="539 842 724 875">2. Not used; <li data-bbox="539 891 724 925">3. Not used; <li data-bbox="539 940 724 974">4. Not used; <li data-bbox="539 990 724 1023">5. Not used; <li data-bbox="539 1039 1259 1308">6. Digital data recorders having all of the following characteristics: <ol data-bbox="624 1126 1259 1308" style="list-style-type: none"> <li data-bbox="624 1126 1259 1227">a. A sustained ‘continuous throughput’ of more than 6.4 Gbit/s to disk or solid-state drive memory; <u>and</u> <li data-bbox="624 1243 1259 1308">b. A processor that performs analysis of radio frequency signal data while it is being recorded; <p data-bbox="603 1328 799 1361"><u>Technical Notes</u></p> <ol data-bbox="539 1368 1259 1861" style="list-style-type: none"> <li data-bbox="624 1368 1259 1496">1. <i>For recorders with a parallel bus architecture, the ‘continuous throughput’ rate is the highest word rate multiplied by the number of bits in a word.</i> <li data-bbox="624 1512 1259 1675">2. <i>‘Continuous throughput’ is the fastest data rate the instrument can record to disk or solid-state drive memory without the loss of any information while sustaining the input digital data rate or digitiser conversion rate.</i> <li data-bbox="539 1691 1259 1861">7. Real-time oscilloscopes having a vertical root-mean-square (rms) noise voltage of less than 2% of full-scale at the vertical scale setting that provides the lowest noise value for any input 3 dB bandwidth of 60 GHz or greater per channel;

Category Code	Item Description
	<p data-bbox="603 454 663 483"><u>Note</u></p> <p data-bbox="603 495 1259 562"><i>Category Code 3A002.a.7. does not include equivalent-time sampling oscilloscopes.</i></p> <p data-bbox="475 577 659 607">b. Not used;</p> <p data-bbox="475 629 906 658">c. “Signal analysers”, as follows:</p> <ol data-bbox="544 680 1259 1361" style="list-style-type: none"> <li data-bbox="544 680 1259 808">1. “Signal analysers” having a 3 dB resolution bandwidth (RBW) exceeding 10 MHz anywhere within the frequency range exceeding 31.8 GHz but not exceeding 37 GHz; <li data-bbox="544 831 1259 958">2. “Signal analysers” having Displayed Average Noise Level (DANL) less (better) than -150 dBm/Hz anywhere within the frequency range exceeding 43.5 GHz but not exceeding 90 GHz; <li data-bbox="544 981 1259 1048">3. “Signal analysers” having a frequency exceeding 90 GHz; <li data-bbox="544 1070 1259 1361">4. “Signal analysers” having all of the following characteristics: <ol data-bbox="628 1144 1259 1361" style="list-style-type: none"> <li data-bbox="628 1144 1259 1211">a. “Real-time bandwidth” exceeding 170 MHz; <u>and</u> <li data-bbox="628 1234 1259 1361">b. 100% probability of discovery with less than a 3 dB reduction from full amplitude due to gaps or windowing effects of signals having a duration of 15 µs or less; <p data-bbox="687 1384 884 1413"><u>Technical Notes</u></p> <ol data-bbox="687 1435 1259 1778" style="list-style-type: none"> <li data-bbox="687 1435 1259 1563">1. <i>Probability of discovery in Category Code 3A002.c.4.b. is also referred to as probability of intercept or probability of capture.</i> <li data-bbox="687 1585 1259 1778">2. <i>For the purpose of Category Code 3A002.c.4.b., the duration for 100% probability of discovery is equivalent to the minimum signal duration necessary for the specified level measurement uncertainty.</i>

<i>Category Code</i>	<i>Item Description</i>
	<p data-bbox="603 454 667 488"><u>Note</u></p> <p data-bbox="603 495 1267 629"><i>Category Code 3A002.c.4. does not include those “signal analysers” using only constant percentage bandwidth filters (also known as octave or fractional octave filters).</i></p> <ol style="list-style-type: none"> <li data-bbox="539 645 1267 745">5. “Signal analysers” having a “frequency mask trigger” function with 100% probability of trigger (capture) for signals having a duration of 15 μs or less; <li data-bbox="475 763 1267 1861">d. Signal generators having any of the following characteristics: <ol style="list-style-type: none"> <li data-bbox="539 813 1267 947">1. Specified to generate pulse-modulated signals having all of the following characteristics, anywhere within the frequency range exceeding 31.8 GHz but not exceeding 37 GHz: <ol style="list-style-type: none"> <li data-bbox="624 965 1155 999">a. ‘Pulse duration’ of less than 25 ns; <u>and</u> <li data-bbox="624 1014 1182 1048">b. On/off ratio equal to or exceeding 65 dB; <li data-bbox="539 1064 1267 1160">2. An output power exceeding 100 mW (20 dBm) anywhere within the frequency range exceeding 43.5 GHz but not exceeding 90 GHz; <li data-bbox="539 1176 1267 1776">3. A “frequency switching time” as specified by any of the following: <ol style="list-style-type: none"> <li data-bbox="624 1261 810 1294">a. Not used; <li data-bbox="624 1310 1267 1413">b. Less than 100 μs for any frequency change exceeding 2.2 GHz within the frequency range exceeding 4.8 GHz but not exceeding 31.8 GHz; <li data-bbox="624 1429 810 1462">c. Not used; <li data-bbox="624 1478 1267 1612">d. Less than 500 μs for any frequency change exceeding 550 MHz within the frequency range exceeding 31.8 GHz but not exceeding 37 GHz; <u>or</u> <li data-bbox="624 1628 1267 1731">e. Less than 100 μs for any frequency change exceeding 2.2 GHz within the frequency range exceeding 37 GHz but not exceeding 90 GHz; <li data-bbox="624 1747 810 1780">f. Not used; <li data-bbox="539 1792 1267 1861">4. Single sideband (SSB) phase noise, in dBc/Hz, specified as being any of the following:

Category Code	Item Description
	<p>a. Less (better) than $-(126 + 20\log_{10}F - 20\log_{10}f)$ anywhere within the range of $10 \text{ Hz} \leq F \leq 10 \text{ kHz}$ anywhere within the frequency range exceeding 3.2 GHz but not exceeding 90 GHz; <u>or</u></p> <p>b. Less (better) than $-(206 - 20\log_{10}f)$ anywhere within the range of $10 \text{ kHz} < F \leq 100 \text{ kHz}$ anywhere within the frequency range exceeding 3.2 GHz but not exceeding 90 GHz; <u>or</u></p> <p><u>Technical Note</u> <i>In Category Code 3A002.b.4., F is the offset from the operating frequency in Hz and f is the operating frequency in MHz.</i></p> <p>5. A maximum frequency exceeding 90 GHz;</p> <p><u>Note 1</u> <i>For the purpose of Category Code 3A002.d., the term signal generators includes arbitrary waveform and function generators.</i></p> <p><u>Note 2</u> <i>Category Code 3A002.d. does not include equipment in which the output frequency is either produced by the addition or subtraction of two or more crystal oscillator frequencies, or by an addition or subtraction followed by a multiplication of the result.</i></p> <p><u>Technical Notes</u></p> <ol style="list-style-type: none"> 1. <i>The maximum frequency of an arbitrary waveform or function generator is calculated by dividing the sample rate, in samples/second, by a factor of 2.5.</i> 2. <i>For the purpose of Category Code 3A002.d.1.a., 'pulse duration' is defined as the time interval from the point on the leading edge that is 50% of the pulse amplitude to the point on the trailing edge that is 50% of the pulse amplitude.</i>

<i>Category Code</i>	<i>Item Description</i>
	<p>e. Network analysers having any of the following characteristics:</p> <ol style="list-style-type: none"> 1. An output power exceeding 31.62 mW (15 dBm) anywhere within the operating frequency range exceeding 43.5 GHz but not exceeding 90 GHz; 2. An output power exceeding 1 mW (0 dBm) anywhere within the operating frequency range exceeding 90 GHz but not exceeding 110 GHz; 3. ‘Non-linear vector measurement functionality’ at frequencies exceeding 50 GHz but not exceeding 110 GHz; <u>or</u> <p><i>Technical Note</i> ‘Non-linear vector measurement functionality’ is an instrument’s ability to analyse the test results of devices driven into the large-signal domain or the non-linear distortion range.</p> <ol style="list-style-type: none"> 4. A maximum operating frequency exceeding 110 GHz; <p>f. Microwave test receivers having both of the following characteristics:</p> <ol style="list-style-type: none"> 1. A maximum operating frequency exceeding 110 GHz; <u>and</u> 2. Being capable of measuring amplitude and phase simultaneously; <p>g. Atomic frequency standards being any of the following:</p> <ol style="list-style-type: none"> 1. “Space-qualified”; 2. Non-rubidium and having a long-term stability less (better) than 1×10^{-11}/month; <u>or</u> 3. Non-“space-qualified” and having all of the following characteristics: <ol style="list-style-type: none"> a. Being a rubidium standard; b. Long-term stability less (better) than 1×10^{-11}/month; <u>and</u> c. Total power consumption of less than 1 W;

<i>Category Code</i>	<i>Item Description</i>
	<p>h. “Electronic assemblies”, modules, or equipment, specified to perform all of the following:</p> <ol style="list-style-type: none"> 1. Analogue-to-digital conversions meeting any of the following: <ol style="list-style-type: none"> a. A resolution of 8 bit or more, but less than 10 bit, with an input sample rate greater than 1,300 million samples per second; b. A resolution of 10 bit or more, but less than 12 bit, with an input sample rate greater than 1,000 million samples per second; c. A resolution of 12 bit or more, but less than 14 bit, with an input sample rate greater than 1,000 million samples per second; d. A resolution of 14 bit or more but less than 16 bit, with an input sample rate greater than 400 million samples per second; <u>or</u> e. A resolution of 16 bit or more with an input sample rate greater than 180 million samples per second; <u>and</u> 2. Any of the following: <ol style="list-style-type: none"> a. Output of digitised data; b. Storage of digitised data; <u>or</u> c. Processing of digitised data. <p><u>N.B.</u> <i>Digital data recorders, oscilloscopes, “signal analysers”, signal generators, network analysers and microwave test receivers, are specified in Category Codes 3A002.a.6., 3A002.a.7., 3A002.c., 3A002.d., 3A002.e. and 3A002.f., respectively.</i></p> <p><u>Technical Note</u> <i>For multiple-channel “electronic assemblies” or modules, control status is determined by the highest single-channel specified performance of such multiple-channel “electronic assemblies” or modules.</i></p>

Category Code	Item Description
	<p><u>Note</u> <i>Category Code 3A002.h. includes ADC cards, waveform digitisers, data acquisition cards, signal acquisition boards and transient recorders.</i></p>
3A003	<p>Spray cooling thermal management systems employing closed loop fluid handling and reconditioning equipment in a sealed enclosure where a dielectric fluid is sprayed onto electronic components using specially designed spray nozzles that are designed to maintain electronic components within their operating temperature range, and specially designed components therefor.</p>
3A101	<p>Electronic equipment, devices and components, other than those specified in Category Code 3A001, as follows:</p> <ol style="list-style-type: none"> a. Analogue-to-digital converters, usable in “missiles”, designed to meet military specifications for ruggedised equipment; b. Accelerators capable of delivering electromagnetic radiation produced by bremsstrahlung from accelerated electrons of 2 MeV or greater, and systems containing those accelerators. <p><u>Note</u> <i>Category Code 3A101.b. does not include equipment specially designed for medical purposes.</i></p>
3A102	<p>‘Thermal batteries’ designed or modified for ‘missiles’.</p> <p><u>Technical Notes</u></p> <ol style="list-style-type: none"> 1. <i>In Category Code 3A102, ‘thermal batteries’ are single use batteries that contain a solid non-conducting inorganic salt as the electrolyte. These batteries incorporate a pyrolytic material that, when ignited, melts the electrolyte and activates the battery.</i> 2. <i>In Category Code 3A102, ‘missile’ means complete rocket systems and unmanned aerial vehicle systems capable of a range exceeding 300 km.</i>

<i>Category Code</i>	<i>Item Description</i>
3A201	<p>Electronic components, other than those specified in Category Code 3A001, as follows:</p> <ol style="list-style-type: none"> a. Capacitors having either of the following sets of characteristics: <ol style="list-style-type: none"> 1. a. Voltage rating greater than 1.4 kV; b. Energy storage greater than 10 J; c. Capacitance greater than 0.5 μF; <u>and</u> d. Series inductance less than 50 nH; <u>or</u> 2. a. Voltage rating greater than 750 V; b. Capacitance greater than 0.25 μF; <u>and</u> c. Series inductance less than 10 nH; b. Superconducting solenoidal electromagnets having all of the following characteristics: <ol style="list-style-type: none"> 1. Capable of creating magnetic fields greater than 2 T; 2. A ratio of length to inner diameter greater than 2; 3. Inner diameter greater than 300 mm; <u>and</u> 4. Magnetic field uniform to better than 1% over the central 50% of the inner volume; <p><u>Note</u> <i>Category Code 3A201.b. does not include magnets specially designed for and exported 'as parts of' medical nuclear magnetic resonance (NMR) imaging systems. For this purpose, the magnets and NMR imaging systems may be part of the same shipment or in separate shipments from different sources, provided the related export documents clearly specify that the separate shipments are dispatched 'as part of' the imaging systems.</i></p> c. Flash X-ray generators or pulsed electron accelerators having either of the following sets of characteristics: <ol style="list-style-type: none"> 1. a. An accelerator peak electron energy of 500 keV or greater but less than 25 MeV; <u>and</u> b. With a 'figure of merit' (K) of 0.25 or greater; <u>or</u>

Category Code	Item Description
	<p data-bbox="544 454 1264 568">2. a. An accelerator peak electron energy of 25 MeV or greater; <u>and</u> b. A ‘peak power’ greater than 50 MW.</p> <p data-bbox="544 589 603 618"><u>Note</u></p> <p data-bbox="544 629 1264 759">Category Code 3A201.c. does not include accelerators that are component parts of devices designed for purposes other than electron beam or X-ray radiation (e.g. electron microscopy) nor those designed for medical purposes.</p> <p data-bbox="544 779 735 808"><u>Technical Notes</u></p> <p data-bbox="544 819 1038 853">1. The ‘figure of merit’ K is defined as: $K = 1.7 \times 10^3 V^{2.65} Q$ V is the peak electron energy in million electron volts. If the accelerator beam pulse duration is less than or equal to $1 \mu\text{s}$, then Q is the total accelerated charge in Coulombs. If the accelerator beam pulse duration is greater than $1 \mu\text{s}$, then Q is the maximum accelerated charge in $1 \mu\text{s}$. Q equals the integral of i with respect to t, over the lesser of $1 \mu\text{s}$ or the time duration of the beam pulse ($Q = \int idt$), where i is beam current in amperes and t is time in seconds.</p> <p data-bbox="544 1272 1264 1339">2. ‘Peak power’ = (peak potential in volts) \times (peak beam current in amperes).</p> <p data-bbox="544 1357 1264 1487">3. In machines based on microwave accelerating cavities, the time duration of the beam pulse is the lesser of $1 \mu\text{s}$ or the duration of the bunched beam packet resulting from one microwave modulator pulse.</p> <p data-bbox="544 1505 1264 1606">4. In machines based on microwave accelerating cavities, the peak beam current is the average current in the time duration of a bunched beam packet.</p>

<i>Category Code</i>	<i>Item Description</i>
3A225	<p>Frequency changers or generators, other than those specified in Category Code 0B001.b.13., usable as a variable or fixed frequency motor drive, having all of the following characteristics:</p> <p><u>N.B.</u></p> <ol style="list-style-type: none"> 1. “Software” specially designed to enhance or release the performance of a frequency changer or generator to meet the characteristics of Category Code 3A225 is specified in Category Code 3D225. 2. “Technology” in the form of codes or keys to enhance or release the performance of a frequency changer or generator to meet the characteristics of Category Code 3A225 is specified in Category Code 3E225. <ol style="list-style-type: none"> a. Multiphase output providing a power of 40 VA or greater; b. Operating at a frequency of 600 Hz or more; <u>and</u> c. Frequency control better (less) than 0.2%. <p><u>Note</u></p> <p>Category Code 3A225 does not include frequency changers or generators if they have hardware, “software” or “technology” constraints that limit the performance to less than that specified above, provided they meet any of the following:</p> <ol style="list-style-type: none"> 1. They need to be returned to the original manufacturer to make the enhancements or release the constraints; 2. They require “software” as specified in Category Code 3D225 to enhance or release the performance to meet the characteristics of Category Code 3A225; <u>or</u> 3. They require “technology” in the form of keys or codes as specified in Category Code 3E225 to enhance or release the performance to meet the characteristics of Category Code 3A225. <p><u>Technical Notes</u></p> <ol style="list-style-type: none"> 1. Frequency changers in Category Code 3A225 are also known as converters or inverters.

<i>Category Code</i>	<i>Item Description</i>
	<p>2. <i>Frequency changers in Category Code 3A225 may be marketed as Generators, Electronic Test Equipment, AC Power Supplies, Variable Speed Motors Drives, Variable Speed Drives (VSDs), Variable Frequency Drives (VFDs), Adjustable Frequency Drives (AFDs), or Adjustable Speed Drives (ASDs).</i></p>
3A226	<p>High-power direct current power supplies, other than those specified in Category Code 0B001.j.6., having both of the following characteristics:</p> <ol style="list-style-type: none"> a. Capable of continuously producing, over a time period of 8 hours, 100 V or greater with current output of 500 A or greater; <u>and</u> b. Current or voltage stability better than 0.1% over a time period of 8 hours.
3A227	<p>High-voltage direct current power supplies, other than those specified in Category Code 0B001.j.5., having both of the following characteristics:</p> <ol style="list-style-type: none"> a. Capable of continuously producing, over a time period of 8 hours, 20 kV or greater with current output of 1 A or greater; <u>and</u> b. Current or voltage stability better than 0.1% over a time period of 8 hours.
3A228	<p>Switching devices, as follows:</p> <ol style="list-style-type: none"> a. Cold-cathode tubes, whether gas filled or not, operating similarly to a spark gap, having all of the following characteristics: <ol style="list-style-type: none"> 1. Containing three or more electrodes; 2. Anode peak voltage rating of 2.5 kV or more; 3. Anode peak current rating of 100 A or more; <u>and</u>

<i>Category Code</i>	<i>Item Description</i>
	<p>4. Anode delay time of 10 μs or less;</p> <p><u>Note</u> <i>Category Code 3A228 includes gas krytron tubes and vacuum spraytron tubes.</i></p> <p>b. Triggered spark-gaps having both of the following characteristics:</p> <ol style="list-style-type: none"> 1. An anode delay time of 15 μs or less; <u>and</u> 2. Rated for a peak current of 500 A or more; <p>c. Modules or assemblies with a fast switching function, other than those specified in Category Code 3A001.g. or 3A001.h., having all of the following characteristics:</p> <ol style="list-style-type: none"> 1. Anode peak voltage rating greater than 2 kV; 2. Anode peak current rating of 500 A or more; <u>and</u> 3. Turn-on time of 1 μs or less.
3A229	<p>High-current pulse generators as follows:</p> <p><u>N.B.</u> <i>See also Division 2 of Part 1 of this Schedule.</i></p> <p>a. Detonator firing sets (initiator systems, firesets), including electronically-charged, explosively-driven and optically-driven firing sets, other than those specified in Category Code 1A007.a., designed to drive multiple controlled detonators specified in Category Code 1A007.b.;</p> <p>b. Modular electrical pulse generators (pulsers) having all of the following characteristics:</p> <ol style="list-style-type: none"> 1. Designed for portable, mobile, or ruggedised-use; 2. Capable of delivering their energy in less than 15 μs into loads of less than 40 ohms; 3. Having an output greater than 100 A; 4. No dimension greater than 30 cm;

<i>Category Code</i>	<i>Item Description</i>
	<p>5. Weight less than 30 kg; <u>and</u></p> <p>6. Specified for use over an extended temperature range 223 K (-50°C) to 373 K (100°C) or specified as suitable for aerospace applications;</p> <p><i>Note</i> <i>Category Code 3A229.b. includes xenon flash-lamp drivers.</i></p> <p>c. Micro-firing units having all of the following characteristics:</p> <ol style="list-style-type: none"> 1. No dimension greater than 35 mm; 2. Voltage rating of equal to or greater than 1 kV; <u>and</u> 3. Capacitance of equal to or greater than 100 nF.
3A230	<p>High-speed pulse generators, and 'pulse heads' therefor, having both of the following characteristics:</p> <ol style="list-style-type: none"> a. Output voltage greater than 6 V into a resistive load of less than 55 ohms; <u>and</u> b. 'Pulse transition time' less than 500 ps. <p><i>Technical Notes</i></p> <ol style="list-style-type: none"> 1. <i>In Category Code 3A230, 'pulse transition time' is defined as the time interval between 10% and 90% voltage amplitude.</i> 2. <i>'Pulse heads' are impulse forming networks designed to accept a voltage step function and shape it into a variety of pulse forms that can include rectangular, triangular, step, impulse, exponential, or monocycle types. 'Pulse heads' can be an integral part of the pulse generator, they can be a plug-in module to the device or they can be an externally connected device.</i>

<i>Category Code</i>	<i>Item Description</i>
3A231	<p>Neutron generator systems, including tubes, having both of the following characteristics:</p> <ul style="list-style-type: none"> a. Designed for operation without an external vacuum system; <u>and</u> b. Utilising any of the following: <ul style="list-style-type: none"> 1. Electrostatic acceleration to induce a tritium-deuterium nuclear reaction; <u>or</u> 2. Electrostatic acceleration to induce a deuterium-deuterium nuclear reaction and capable of an output of 3×10^9 neutrons/s or greater.
3A232	<p>Multipoint initiation systems, other than those specified in Category Code 1A007, as follows:</p> <p><u>N.B.</u> <i>See also Division 2 of Part 1 of this Schedule.</i> <i>See Category Code 1A007.b. for detonators.</i></p> <ul style="list-style-type: none"> a. Not used; b. Arrangements using single or multiple detonators designed to nearly simultaneously initiate an explosive surface over an area greater than 5,000 mm² from a single firing signal with an initiation timing spread over the surface of less than 2.5 µs. <p><u>Note</u> <i>Category Code 3A232 does not include detonators using only primary explosives, such as lead azide.</i></p>
3A233	<p>Mass spectrometers, other than those specified in Category Code 0B002.g., capable of measuring ions of 230 atomic mass units or greater and having a resolution of better than 2 parts in 230, as follows, and ion sources therefor:</p> <ul style="list-style-type: none"> a. Inductively coupled plasma mass spectrometers (ICP/MS); b. Glow discharge mass spectrometers (GDMS); c. Thermal ionisation mass spectrometers (TIMS);

<i>Category Code</i>	<i>Item Description</i>
	<p>d. Electron bombardment mass spectrometers having both of the following features:</p> <ol style="list-style-type: none"> 1. A molecular beam inlet system that injects a collimated beam of analyte molecules into a region of the ion source where the molecules are ionised by an electron beam; <u>and</u> 2. One or more 'cold traps' that can be cooled to a temperature of 193 K (-80°C); <p>e. Not used;</p> <p>f. Mass spectrometers equipped with a microfluorination ion source designed for actinides or actinide fluorides.</p> <p><u>Technical Notes</u></p> <ol style="list-style-type: none"> 1. <i>Electron bombardment mass spectrometers in Category Code 3A233.d. are also known as electron impact mass spectrometers or electron ionisation mass spectrometers.</i> 2. <i>In Category Code 3A233.d.2., a 'cold trap' is a device that traps gas molecules by condensing or freezing them on cold surfaces. For the purpose of Category Code 3A233.d.2., a closed-loop gaseous helium cryogenic vacuum pump is not a 'cold trap'.</i>
3A234	<p>Striplines to provide low inductance path to detonators with the following characteristics:</p> <ol style="list-style-type: none"> a. Voltage rating greater than 2 kV; <u>and</u> b. Inductance of less than 20 nH.
<p>3B</p> <p>3B001</p>	<p>Test, Inspection and Production Equipment</p> <p>Equipment for the manufacturing of semiconductor devices or materials, as follows and specially designed components and accessories therefor:</p> <ol style="list-style-type: none"> a. Equipment designed for epitaxial growth, as follows: <ol style="list-style-type: none"> 1. Equipment capable of producing a layer of any material other than silicon with a thickness uniform to less than $\pm 2.5\%$ across a distance of 75 mm or more;

<i>Category Code</i>	<i>Item Description</i>
	<p data-bbox="603 454 667 488"><u>Note</u></p> <p data-bbox="603 495 1260 562"><i>Category Code 3B001.a.1. includes Atomic Layer Epitaxy (ALE) equipment.</i></p> <ol style="list-style-type: none"> <li data-bbox="539 577 1260 745">2. Metal Organic Chemical Vapour Deposition (MOCVD) reactors designed for compound semiconductor epitaxial growth of material having two or more of the following elements: aluminium, gallium, indium, arsenic, phosphorus, antimony, or nitrogen; <li data-bbox="539 763 1260 831">3. Molecular beam epitaxial growth equipment using gas or solid sources; <p data-bbox="475 846 1260 913">b. Equipment designed for ion implantation and having any of the following characteristics:</p> <ol style="list-style-type: none"> <li data-bbox="539 929 722 963">1. Not used; <li data-bbox="539 978 1260 1079">2. Being designed and optimised to operate at a beam energy of 20 keV or more and a beam current of 10 mA or more for hydrogen, deuterium or helium implant; <li data-bbox="539 1095 882 1128">3. Direct write capability; <li data-bbox="539 1144 1260 1245">4. A beam energy of 65 keV or more and a beam current of 45 mA or more for high energy oxygen implant into a heated semiconductor material “substrate”; <u>or</u> <li data-bbox="539 1261 1260 1395">5. Being designed and optimised to operate at a beam energy of 20 keV or more and a beam current of 10 mA or more for silicon implant into a semiconductor material “substrate” heated to 600°C or greater; <p data-bbox="475 1411 659 1444">c. Not used;</p> <p data-bbox="475 1460 659 1494">d. Not used;</p> <p data-bbox="475 1509 1260 1576">e. Automatic loading multi-chamber central wafer handling systems, having both of the following characteristics:</p> <ol style="list-style-type: none"> <li data-bbox="539 1592 1260 1762">1. Interfaces for wafer input and output, to which more than two functionally different ‘semiconductor process tools’ specified in Category Code 3B001.a.1., 3B001.a.2, 3B001.a.3. or 3B001.b. are designed to be connected; <u>and</u>

Category Code	Item Description
	<p>2. Designed to form an integrated system in a vacuum environment for ‘sequential multiple wafer processing’;</p> <p><u>Note</u> <i>Category Code 3B001.e. does not include automatic robotic wafer handling systems specially designed for parallel wafer processing.</i></p> <p><u>Technical Notes</u></p> <p>1. <i>For the purpose of Category Code 3B001.e., ‘semiconductor process tools’ refers to modular tools that provide physical processes for semiconductor production that are functionally different, such as deposition, implant or thermal processing.</i></p> <p>2. <i>For the purpose of Category Code 3B001.e., ‘sequential multiple wafer processing’ means the capability to process each wafer in different ‘semiconductor process tools’, such as by transferring each wafer from one tool to a second tool and on to a third tool with the automatic loading multi-chamber central wafer handling systems.</i></p> <p>f. Lithography equipment as follows:</p> <p>1. Align and expose step and repeat (direct step on wafer) or step and scan (scanner) equipment for wafer processing using photo-optical or X-ray methods and having any of the following characteristics:</p> <p>a. A light source wavelength shorter than 193 nm; <u>or</u></p> <p>b. Capable of producing a pattern with a ‘Minimum Resolvable Feature size’ (MRF) of 45 nm or less;</p>

Category Code	Item Description
	<p data-bbox="691 454 871 483"><u>Technical Note</u></p> <p data-bbox="691 495 1257 562">The 'Minimum Resolvable Feature size' (MRF) is calculated by the following formula:</p> $MRF = \frac{\left[\begin{array}{c} \text{an exposure light source} \\ \text{wavelength in nm} \end{array} \right] \times [K \text{ factor}]}{\text{numerical aperture}}$ <p data-bbox="691 712 999 741">where the K factor = 0.35</p> <p data-bbox="544 763 1257 824">2. Imprint lithography equipment capable of producing features of 45 nm or less;</p> <p data-bbox="604 846 663 875"><u>Note</u></p> <p data-bbox="604 887 1031 916">Category Code 3B001.f.2. includes:</p> <ul style="list-style-type: none"> <li data-bbox="632 938 1026 967">– Micro contact printing tools <li data-bbox="632 990 935 1019">– Hot embossing tools <li data-bbox="632 1041 1062 1070">– Nano-imprint lithography tools <li data-bbox="632 1093 1257 1122">– Step and flash imprint lithography (S-FIL) tools <p data-bbox="544 1137 1257 1198">3. Equipment specially designed for mask making having all of the following:</p> <ul style="list-style-type: none"> <li data-bbox="632 1220 1257 1281">a. A deflected focused electron beam, ion beam or "laser" beam; <u>and</u> <li data-bbox="632 1303 1257 1615">b. Having any of the following characteristics: <ul style="list-style-type: none"> <li data-bbox="691 1348 1257 1480">1. A full-width half-maximum (FWHM) spot size smaller than 65 nm and an image placement less than 17 nm (mean + 3 sigma); <u>or</u> <li data-bbox="691 1503 871 1532">2. Not used; <li data-bbox="691 1554 1257 1615">3. A second-layer overlay error of less than 23 nm (mean + 3 sigma) on the mask; <p data-bbox="544 1637 1257 1697">4. Equipment designed for device processing using direct writing methods, having all of the following:</p> <ul style="list-style-type: none"> <li data-bbox="632 1720 1158 1749">a. A deflected focused electron beam; and <li data-bbox="632 1771 1209 1800">b. Having any of the following characteristics:

<i>Category Code</i>	<i>Item Description</i>
	<ol style="list-style-type: none"> 1. A minimum beam size equal to or smaller than 15 nm; <u>or</u> 2. An overlay error less than 27 nm (mean + 3 sigma); <p>g. Masks and reticles, designed for integrated circuits specified in Category Code 3A001;</p> <p>h. Multi-layer masks with a phase shift layer not specified in Category Code 3B001.g. and having any of the following characteristics:</p> <ol style="list-style-type: none"> 1. Made on a mask “substrate blank” from glass specified as having less than 7 nm/cm birefringence; <u>or</u> 2. Designed to be used by lithography equipment having a light source wavelength less than 245 nm; <p><i>Note</i> <i>Category Code 3B001.h. does not include multi-layer masks with a phase shift layer designed for the fabrication of memory devices not specified in Category Code 3A001.</i></p> <p>i. Imprint lithography templates designed for integrated circuits specified in Category Code 3A001.</p>
3B002	<p>Test equipment specially designed for testing finished or unfinished semiconductor devices as follows and specially designed components and accessories therefor:</p> <ol style="list-style-type: none"> a. For testing S-parameters of transistor devices at frequencies exceeding 31.8 GHz; b. Not used; c. For testing microwave integrated circuits specified in Category Code 3A001.b.2.

<i>Category Code</i>	<i>Item Description</i>
3C	Materials
3C001	<p>Hetero-epitaxial materials consisting of a “substrate” having stacked epitaxially grown multiple layers of any of the following:</p> <ol style="list-style-type: none"> a. Silicon (Si); b. Germanium (Ge); c. Silicon carbide (SiC); <u>or</u> d. “III/V compounds” of gallium or indium. <p><i>Note</i> <i>Category Code 3C001.d. does not apply to a “substrate” having one or more P-type epitaxial layers of GaN, InGaN, AlGaN, InAlN, InAlGaN, GaP, InGaP, AlInP or InGaAlP, independent of the sequence of the elements, except if the P-type epitaxial layer is between N-type layers.</i></p>
3C002	<p>Resist materials as follows and “substrates” coated with the following resists:</p> <ol style="list-style-type: none"> a. Resists designed for semiconductor lithography as follows: <ol style="list-style-type: none"> 1. Positive resists adjusted (optimised) for use at wavelengths less than 245 nm but equal to or greater than 15 nm; 2. Resists adjusted (optimised) for use at wavelengths less than 15 nm but greater than 1 nm; b. All resists designed for use with electron beams or ion beams, with a sensitivity of 0.01 $\mu\text{coulomb}/\text{mm}^2$ or better; c. Not used; d. All resists optimised for surface imaging technologies; e. All resists designed or optimised for use with imprint lithography equipment specified in Category Code 3B001.f.2. that use either a thermal or photo-curable process.

<i>Category Code</i>	<i>Item Description</i>
3C003	<p>Organo-inorganic compounds as follows:</p> <ul style="list-style-type: none"> a. Organo-metallic compounds of aluminium, gallium or indium, having a purity (metal basis) better than 99.999%; b. Organo-arsenic, organo-antimony and organo-phosphorus compounds, having a purity (inorganic element basis) better than 99.999%. <p><u>Note</u> <i>Category Code 3C003 only includes compounds whose metallic, partly metallic or non-metallic element is directly linked to carbon in the organic part of the molecule.</i></p>
3C004	<p>Hydrides of phosphorus, arsenic or antimony, having a purity better than 99.999%, even diluted in inert gases or hydrogen.</p> <p><u>Note</u> <i>Category Code 3C004 does not include hydrides containing 20% molar or more of inert gases or hydrogen.</i></p>
3C005	<p>Silicon carbide (SiC), gallium nitride (GaN), aluminium nitride (AlN) or aluminium gallium nitride (AlGaN) semiconductor “substrates”, or ingots, boules, or other preforms of those materials, having resistivities greater than 10,000 ohm-cm at 20°C.</p>
3C006	<p>“Substrates” specified in Category Code 3C005 with at least one epitaxial layer of silicon carbide, gallium nitride, aluminium nitride or aluminium gallium nitride.</p>
3D	Software
3D001	<p>“Software” specially designed for the “development” or “production” of equipment specified in Category Codes 3A001.b. to 3A002.h. or Category 3B.</p>
3D002	<p>“Software” specially designed for the “use” of equipment specified in Category Code 3B001.a. to f., 3B002 or 3A225.</p>

<i>Category Code</i>	<i>Item Description</i>
3D003	<p data-bbox="464 450 1272 584">‘Physics-based’ simulation “software” specially designed for the “development” of lithographic, etching or deposition processes for translating masking patterns into specific topographical patterns in conductors, dielectrics or semiconductor materials.</p> <p data-bbox="464 600 663 633"><u>Technical Note</u></p> <p data-bbox="464 645 1272 779"><i>‘Physics-based’ in Category Code 3D003 means using computations to determine a sequence of physical cause and effect events based on physical properties (e.g. temperature, pressure, diffusion constants and semiconductor materials properties).</i></p> <p data-bbox="464 795 539 828"><u>Note</u></p> <p data-bbox="464 840 1272 936"><i>Libraries, design attributes or associated data for the design of semiconductor devices or integrated circuits are considered as “technology”.</i></p>
3D004	<p data-bbox="464 1003 1272 1070">“Software” specially designed for the “development” of equipment specified in Category Code 3A003.</p>
3D101	<p data-bbox="464 1137 1272 1205">“Software” specially designed or modified for the “use” of equipment specified in Category Code 3A101.b.</p>
3D225	<p data-bbox="464 1272 1272 1368">“Software” specially designed to enhance or release the performance of frequency changers or generators to meet the characteristics of Category Code 3A225.</p>
3E	Technology
3E001	<p data-bbox="464 1485 1272 1581">“Technology” (according to the General Technology Note) for the “development” or “production” of equipment or materials specified in Category 3A, 3B or 3C.</p> <p data-bbox="464 1597 560 1630"><u>Note 1</u></p> <p data-bbox="464 1641 1272 1738"><i>Category Code 3E001 does not include “technology” for the “production” of equipment or components specified in Category Code 3A003.</i></p>

Category Code	Item Description
3E002	<p><u>Note 2</u> <i>Category Code 3E001 does not include “technology” for the “development” or “production” of integrated circuits specified in Category Codes 3A001.a.3. to 3A001.a.12., having all of the following characteristics:</i></p> <ul style="list-style-type: none"> <i>a. Using “technology” at or above 0.13 μm; and</i> <i>b. Incorporating multi-layer structures with three or fewer metal layers.</i> <p>“Technology” (according to the General Technology Note) other than that specified in Category Code 3E001, for the “development” or “production” of a “microprocessor microcircuit”, “microcomputer microcircuit” or microcontroller microcircuit core, having an arithmetic logic unit with an access width of 32 bits or more and any of the following features or characteristics:</p> <ul style="list-style-type: none"> <i>a. A ‘vector processor unit’ designed to perform more than two calculations on floating-point vectors (one-dimensional arrays of 32-bit or larger numbers) simultaneously;</i> <p><u>Technical Note</u> <i>A ‘vector processing unit’ is a processor element with built-in instructions that perform multiple calculations on floating-point vectors (one-dimensional arrays of 32-bit or larger numbers) simultaneously, having at least one vector arithmetic logic unit and vector registers of at least 32 elements each.</i></p> <ul style="list-style-type: none"> <i>b. Designed to perform more than four 64-bit or larger floating-point operation results per cycle; <u>or</u></i> <i>c. Designed to perform more than eight 16-bit fixed-point multiply-accumulate results per cycle (e.g. digital manipulation of analogue information that has been previously converted into digital form, also known as digital “signal processing”).</i> <p><u>Note 1</u> <i>Category Code 3E002 does not include “technology” for multimedia extensions.</i></p>

Category Code	Item Description
3E003	<p data-bbox="475 454 560 488"><u>Note 2</u></p> <p data-bbox="475 495 1262 595"><i>Category Code 3E002 does not include “technology” for the “development” or “production” of micro-processor cores, having all of the following characteristics:</i></p> <ul style="list-style-type: none"> <li data-bbox="475 611 1091 645">a. <i>Using “technology” at or above 0.13 μm; <u>and</u></i> <li data-bbox="475 660 1262 730">b. <i>Incorporating multi-layer structures with five or fewer metal layers.</i> <p data-bbox="475 745 560 779"><u>Note 3</u></p> <p data-bbox="475 786 1262 855"><i>Category Code 3E002 includes “technology” for digital signal processors and digital array processors.</i></p> <p data-bbox="475 920 1262 990">Other “technology” for the “development” or “production” of the following:</p> <ul style="list-style-type: none"> <li data-bbox="475 1005 943 1039">a. Vacuum microelectronic devices; <li data-bbox="475 1055 1262 1155">b. Hetero-structure semiconductor electronic devices such as high electron mobility transistors (HEMT), hetero-bipolar transistors (HBT), quantum well and super lattice devices; <p data-bbox="539 1171 608 1205"><u>Note</u></p> <p data-bbox="539 1211 1262 1379"><i>Category Code 3E003.b. does not include “technology” for high electron mobility transistors (HEMT) operating at frequencies lower than 31.8 GHz and hetero-junction bipolar transistors (HBT) operating at frequencies lower than 31.8 GHz.</i></p> <ul style="list-style-type: none"> <li data-bbox="475 1395 995 1429">c. “Superconductive” electronic devices; <li data-bbox="475 1444 1235 1478">d. Substrates of films of diamond for electronic components; <li data-bbox="475 1494 1262 1563">e. Substrates of silicon-on-insulator (SOI) for integrated circuits in which the insulator is silicon dioxide; <li data-bbox="475 1579 1203 1612">f. Substrates of silicon carbide for electronic components; <li data-bbox="475 1628 1262 1697">g. Electronic vacuum tubes operating at frequencies of 31.8 GHz or higher.

<i>Category Code</i>	<i>Item Description</i>
3E101	“Technology” (according to the General Technology Note) for the “use” of equipment or “software” specified in Category Code 3A001.a.1. or 2., 3A101, 3A102 or 3D101.
3E102	“Technology” (according to the General Technology Note) for the “development” of “software” specified in Category Code 3D101.
3E201	“Technology” (according to the General Technology Note) for the “use” of equipment specified in Category Codes 3A001.e.2., 3A001.e.3., 3A001.g., 3A201, 3A225 to 3A234.
3E225	“Technology”, in the form of codes or keys, to enhance or release the performance of frequency changers or generators to meet the characteristics of Category Code 3A225.

Category Code	Item Description
CATEGORY 4 — COMPUTERS	
<i>Note 1</i>	
Computers, related equipment and “software” performing telecommunications or “local area network” functions with the performance characteristics in Category 5 – Part 1 (Telecommunications) are also treated as coming within that Category.	
<i>Note 2</i>	
Control units which directly interconnect the buses or channels of central processing units, “main storage” or disk controllers are not regarded as telecommunications equipment described in Category 5 – Part 1 (Telecommunications).	
<i>N.B.</i>	
For “software” specially designed for packet switching, see Category Code 5D001.	
4A	Systems, Equipment and Components
4A001	<p>Electronic computers and related equipment, having any of the following characteristics, and “electronic assemblies” and specially designed components therefor:</p> <p><i>N.B.</i></p> <p>See also Category Code 4A101.</p> <p>a. Specially designed to have any of the following characteristics:</p> <ol style="list-style-type: none"> 1. Rated for operation at an ambient temperature below 228 K (-45°C) or above 358 K (85°C); <u>or</u> <p><i>Note</i></p> <p>Category Code 4A001.a.1. does not apply to computers specially designed for civil automobile, railway train or “civil aircraft” applications.</p> <ol style="list-style-type: none"> 2. Radiation hardened to exceed any of the following specifications: <ol style="list-style-type: none"> a. Total Dose 5×10^3 Gy (silicon); b. Dose Rate Upset 5×10^6 Gy (silicon)/s; <u>or</u> c. Single Event Upset 1×10^{-8} Error/bit/day;

<i>Category Code</i>	<i>Item Description</i>
4A003	<p data-bbox="598 454 657 488"><u>Note</u></p> <p data-bbox="598 495 1262 562"><i>Category Code 4A001.a.2. does not include computers specially designed for “civil aircraft” applications.</i></p> <p data-bbox="472 577 651 611">b. Not used.</p> <p data-bbox="472 678 1262 779">“Digital computers”, “electronic assemblies”, and related equipment therefor, as follows, and specially designed components therefor:</p> <p data-bbox="472 795 555 828"><u>Note 1</u></p> <p data-bbox="472 835 1013 869"><i>Category Code 4A003 includes the following:</i></p> <ul data-bbox="472 884 1102 1120" style="list-style-type: none"> – <i>‘Vector processors’;</i> – <i>Array processors;</i> – <i>Digital signal processors;</i> – <i>Logic processors;</i> – <i>Equipment designed for “image enhancement”;</i> <p data-bbox="534 1135 719 1169"><u>Technical Note</u></p> <p data-bbox="534 1176 1262 1377"><i>A ‘vector processor’ is defined as a processor with built-in instructions that perform multiple calculations on floating-point vectors (one-dimensional arrays of 64-bit or larger numbers) simultaneously, having at least 2 vector functional units and at least 8 vector registers of at least 64 elements each.</i></p> <p data-bbox="472 1393 555 1426"><u>Note 2</u></p> <p data-bbox="472 1433 1262 1534"><i>The control status of the “digital computers” and related equipment described in Category Code 4A003 is determined by the control status of other equipment or systems provided:</i></p> <ul data-bbox="472 1550 1262 1702" style="list-style-type: none"> a. <i>The “digital computers” or related equipment are essential for the operation of the other equipment or systems;</i> b. <i>The “digital computers” or related equipment are not a “principal element” of the other equipment or systems; <u>and</u></i>

Category Code	Item Description
	<p><u>N.B. 1</u> <i>The control status of “signal processing” or “image enhancement” equipment specially designed for other equipment with functions limited to those required for the other equipment is determined by the control status of the other equipment even if it exceeds the “principal element” criterion.</i></p> <p><u>N.B. 2</u> <i>For the control status of “digital computers” or related equipment for telecommunications equipment, see Category 5 – Part 1 (Telecommunications).</i></p> <p>c. <i>The “technology” for the “digital computers” and related equipment is determined by Category 4E.</i></p> <p>a. <i>Not used;</i></p> <p>b. <i>“Digital computers” having an “Adjusted Peak Performance” (“APP”) exceeding 12.5 Weighted TeraFLOPS (WT);</i></p> <p>c. <i>“Electronic assemblies” specially designed or modified for enhancing performance by aggregation of processors so that the “APP” of the aggregation exceeds the limit specified in Category Code 4A003.b.;</i></p> <p><u>Note 1</u> <i>Category Code 4A003.c. includes only “electronic assemblies” and programmable interconnections not exceeding the limit specified in Category Code 4A003.b. when shipped as unintegrated “electronic assemblies”.</i></p> <p><u>Note 2</u> <i>Category Code 4A003.c. does not include “electronic assemblies” specially designed for a product or family of products whose maximum configuration does not exceed the limit specified in Category Code 4A003.b.</i></p>

<i>Category Code</i>	<i>Item Description</i>
	<p>d. Not used;</p> <p>e. Not used;</p> <p><i>N.B.</i> For “electronic assemblies”, modules or equipment, performing analogue-to-digital conversions, see Category Code 3A002.h.</p> <p>f. Not used;</p> <p>g. Equipment specially designed for aggregating the performance of “digital computers” by providing external interconnections which allows communications at unidirectional data rates exceeding 2 Gbyte/s per link.</p> <p><i>Note</i> Category Code 4A003.g. does not include internal interconnection equipment (e.g. backplanes and buses), passive interconnection equipment, “network access controllers” or “communications channel controllers”.</p>
4A004	<p>Computers as follows and specially designed related equipment, “electronic assemblies” and components therefor:</p> <p>a. “Systolic array computers”;</p> <p>b. “Neural computers”;</p> <p>c. “Optical computers”.</p>
4A005	<p>Systems, equipment, and components therefor, specially designed or modified for the generation, operation or delivery of, or communication with, “intrusion software”.</p>
4A101	<p>Analogue computers, “digital computers” or digital differential analysers, other than those specified in Category Code 4A001.a.1., which are ruggedised and designed or modified for use in space launch vehicles specified in Category Code 9A004 or sounding rockets specified in Category Code 9A104.</p>

<i>Category Code</i>	<i>Item Description</i>
4A102	<p>“Hybrid computers” specially designed for modelling, simulation or design integration of space launch vehicles specified in Category Code 9A004 or sounding rockets specified in Category Code 9A104.</p> <p><i>Note</i> Category Code 4A102 only extends to equipment supplied with “software” specified in Category Code 7D103 or 9D103.</p>
4B	<p>Test, Inspection and Production Equipment</p> <p>None.</p>
4C	<p>Materials</p> <p>None.</p>
4D	<p>Software</p> <p><i>Note</i> For “software” for equipment described in other Categories, please see the appropriate Category.</p>
4D001	<p>“Software” as follows:</p> <ol style="list-style-type: none"> a. “Software” specially designed or modified for the “development” or “production” of equipment or “software” specified in Category Codes 4A001 to 4A004, or Category 4D; b. “Software”, other than that specified in Category Code 4D001.a., specially designed or modified for the “development” or “production” of equipment, as follows: <ol style="list-style-type: none"> 1. “Digital computers” having an “Adjusted Peak Performance” (“APP”) exceeding 6 Weighted TeraFLOPS (WT); 2. “Electronic assemblies” specially designed or modified for enhancing performance by aggregation of processors so that the “APP” of the aggregation exceeds the limit in Category Code 4D001.b.1.

<i>Category Code</i>	<i>Item Description</i>
	<p><i>Note</i> Please see Technical Note on calculation of “APP” immediately after Category Code 4E001.</p>
4D004	<p>“Software” specially designed or modified for the generation, operation or delivery of, or communication with, “intrusion software”.</p>
4E	Technology
4E001	<p>a. “Technology” (according to the General Technology Note) for the “development”, “production” or “use” of equipment or “software” specified in Category 4A or 4D;</p> <p>b. “Technology”, other than that specified in Category Code 4E001.a., specially designed or modified for the “development” or “production” of equipment as follows:</p> <ol style="list-style-type: none"> 1. “Digital computers” having an “Adjusted Peak Performance” (“APP”) exceeding 6 Weighted TeraFLOPS (WT); 2. “Electronic assemblies” specially designed or modified for enhancing performance by aggregation of processors so that the “APP” of the aggregation exceeds the limit in Category Code 4E001.b.1.; <p>c. “Technology” for the “development” of “intrusion software”.</p> <p><i>Note</i> Please see Technical Note on calculation of “APP” immediately after Category Code 4E001.</p>

TECHNICAL NOTE ON “ADJUSTED PEAK PERFORMANCE” (“APP”)

“APP” is an adjusted peak rate at which “digital computers” perform 64-bit or larger floating-point additions and multiplications.

“APP” is expressed in Weighted TeraFLOPS (WT), in units of 10^{12} adjusted floating-point operations per second.

Abbreviations used in this Technical Note

n	number of processors in the “digital computer”
i	processor number (i,...n)
t_i	processor cycle time ($t_i = 1/F_i$)
F_i	processor frequency
R_i	peak floating-point calculating rate
W_i	architecture adjustment factor

Outline of “APP” calculation method

1. For each processor i, determine the peak number of 64-bit or larger floating-point operations, FPO_i , performed per cycle for each processor in the “digital computer”.

Note

In determining FPO, include only 64-bit or larger floating-point additions and/or multiplications. All floating-point operations must be expressed in operations per processor cycle; operations requiring multiple cycles may be expressed in fractional results per cycle. For processors not capable of performing calculations on floating-point operands of 64-bit or more, the effective calculating rate R is zero.

2. Calculate the floating-point rate R for each processor $R_i = FPO_i/t_i$.
3. Calculate “APP” as “APP” = $W_1 \times R_1 + W_2 \times R_2 + \dots + W_n \times R_n$.
4. For ‘vector processors’, $W_i = 0.9$. For non-‘vector processors’, $W_i = 0.3$.

Note 1

For processors that perform compound operations in a cycle, such as addition and multiplication, each operation is counted.

Note 2

For a pipelined processor the effective calculating rate R is the faster of the pipelined rate, once the pipeline is full, or the non-pipelined rate.

Note 3

The calculating rate R of each contributing processor is to be calculated at its maximum value theoretically possible before the “APP” of the combination is derived. Simultaneous operations are assumed to exist when the computer manufacturer claims concurrent, parallel, or simultaneous operation or execution in a manual or brochure for the computer.

Note 4

Do not include processors that are limited to input/output and peripheral functions (e.g. disk drive, communication and video display) when calculating “APP”.

Note 5

“APP” values are not to be calculated for processor combinations (inter)connected by “Local Area Networks”, Wide Area Networks, I/O shared connections/devices, I/O controllers and any communication interconnection implemented by “software”.

Note 6

“APP” values must be calculated for processor combinations containing processors specially designed to enhance performance by aggregation, operating simultaneously and sharing memory.

Technical Notes

1. Aggregate all processors and accelerators operating simultaneously and located on the same die.
2. Processor combinations share memory when any processor is capable of accessing any memory location in the system through the hardware transmission of cache lines or memory words, without the involvement of any software mechanism, which may be achieved using “electronic assemblies” specified in Category Code 4A003.c.

Note 7

A ‘vector processor’ is defined as a processor with built-in instructions that perform multiple calculations on floating-point vectors (one-dimensional arrays of 64-bit or larger numbers) simultaneously, having at least 2 vector functional units and at least 8 vector registers of at least 64 elements each.

Category Code	Item Description
---------------	------------------

CATEGORY 5 — TELECOMMUNICATIONS AND “INFORMATION SECURITY”

Part 1 — TELECOMMUNICATIONS

Note 1

Category 5 – Part 1 concerns components, test and “production” equipment and “software”, therefor which are specially designed for telecommunications equipment or systems.

N.B.

For “lasers” specially designed for telecommunications equipment or systems, see Category Code 6A005.

Note 2

“Digital computers”, related equipment or “software”, when essential for the operation and support of telecommunications equipment described in this Category, are regarded as specially designed components for the purposes of this Category, provided they are the standard models customarily supplied by the manufacturer. This includes operation, administration, maintenance, engineering or billing computer systems.

5A1	Systems, Equipment and Components
5A001	<p>Telecommunications systems, equipment, components and accessories, as follows:</p> <p>a. Any type of telecommunications equipment having any of the following characteristics, functions or features:</p> <ol style="list-style-type: none"> 1. Specially designed to withstand transitory electronic effects or electromagnetic pulse effects, both arising from a nuclear explosion; 2. Specially hardened to withstand gamma, neutron or ion radiation; <u>or</u> 3. Specially designed to operate outside the temperature range from 218 K (-55°C) to 397 K (124°C); <p><u>Note</u> <i>Category Code 5A001.a.3. applies only to electronic equipment.</i></p>

<i>Category Code</i>	<i>Item Description</i>
	<p data-bbox="539 454 603 488"><u>Note</u></p> <p data-bbox="539 495 1262 562"><i>Category Codes 5A001.a.2. and 5A001.a.3. do not include equipment designed or modified for use on board satellites.</i></p> <p data-bbox="475 577 1262 678">b. Telecommunications systems and equipment, and specially designed components and accessories therefor, having any of the following characteristics, functions or features:</p> <ol style="list-style-type: none"> <li data-bbox="539 696 1262 757">1. Being underwater untethered communications systems having any of the following characteristics: <ol style="list-style-type: none"> <li data-bbox="624 779 1262 840">a. An acoustic carrier frequency outside the range from 20 kHz to 60 kHz; <li data-bbox="624 862 1262 922">b. Using an electromagnetic carrier frequency below 30 kHz; <li data-bbox="624 945 1262 978">c. Using electronic beam steering techniques; <u>or</u> <li data-bbox="624 1001 1262 1093">d. Using “lasers” or light-emitting diodes (LEDs) with an output wavelength greater than 400 nm and less than 700 nm, in a “local area network”; <li data-bbox="539 1115 1262 1216">2. Being radio equipment operating in the 1.5 MHz to 87.5 MHz band and having all of the following characteristics: <ol style="list-style-type: none"> <li data-bbox="624 1238 1262 1330">a. Automatically predicting and selecting frequencies and “total digital transfer rates” per channel to optimise the transmission; <u>and</u> <li data-bbox="624 1352 1262 1682">b. Incorporating a linear power amplifier configuration having a capability to support multiple signals simultaneously at an output power of 1 kW or more in the frequency range of 1.5 MHz or more but less than 30 MHz, or 250 W or more in the frequency range of 30 MHz or more but not exceeding 87.5 MHz, over an “instantaneous bandwidth” of one octave or more and with an output harmonic and distortion content of better than -80 dB;

<i>Category Code</i>	<i>Item Description</i>
	<p>3. Being radio equipment employing “spread spectrum” techniques, including “frequency hopping” techniques, other than those specified in Category Code 5A001.b.4. and having any of the following characteristics:</p> <ul style="list-style-type: none"> a. User programmable spreading codes; <u>or</u> b. A total transmitted bandwidth which is 100 or more times the bandwidth of any one information channel and in excess of 50 kHz; <p><i>Note</i> <i>Category Code 5A001.b.3.b. does not apply to radio equipment specially designed for use with any of the following:</i></p> <ul style="list-style-type: none"> a. <i>Civil cellular radio-communications systems; <u>or</u></i> b. <i>Fixed or mobile satellite earth stations for commercial civil telecommunications.</i> <p><i>Note</i> <i>Category Code 5A001.b.3. does not include equipment designed to operate at an output power of 1 W or less.</i></p> <p>4. Being radio equipment employing ultra-wideband modulation techniques, having user programmable channelising codes, scrambling codes or network identification codes and having any of the following characteristics:</p> <ul style="list-style-type: none"> a. A bandwidth exceeding 500 MHz; <u>or</u> b. A “fractional bandwidth” of 20% or more; <p>5. Being digitally controlled radio receivers having all of the following characteristics:</p> <ul style="list-style-type: none"> a. Have more than 1,000 channels; b. A ‘channel switching time’ of less than 1 ms; c. Automatic searching or scanning of a part of the electromagnetic spectrum; <u>and</u> d. Identification of the received signals or the type of transmitter; <u>or</u>

Category Code	Item Description
	<p><u>Note</u></p> <p>Category Code 5A001.b.5. does not include radio equipment specially designed for use with civil cellular radio-communications systems.</p> <p><u>Technical Note</u></p> <p>‘Channel switching time’ means the time (i.e. delay) to change from one receiving frequency to another, to arrive at or within $\pm 0.05\%$ of the final specified receiving frequency. Items having a specified frequency range of less than $\pm 0.05\%$ around their centre frequency are defined to be incapable of channel frequency switching.</p> <p>6. Employing functions of digital “signal processing” to provide ‘voice coding’ output at rates of less than 2,400 bit/s.</p> <p><u>Technical Notes</u></p> <ol style="list-style-type: none"> 1. For variable rate ‘voice coding’, Category Code 5A001.b.6. applies to the ‘voice coding’ output of continuous speech. 2. For the purpose of Category Code 5A001.b.6., ‘voice coding’ is defined as the technique to take samples of human voice and then convert these samples into a digital signal, taking into account specific characteristics of human speech. <p>c. Optical fibres of more than 500 m in length and specified by the manufacturer as being capable of withstanding a ‘proof test’ tensile stress of 2×10^9 N/m² or more;</p> <p><u>N.B.</u></p> <p>For underwater umbilical cables, see Category Code 8A002.a.3.</p>

Category Code	Item Description
	<p data-bbox="539 454 724 488"><u>Technical Note</u></p> <p data-bbox="539 495 1265 730"><i>‘Proof Test’: on-line or off-line production screen testing that dynamically applies a prescribed tensile stress over a 0.5 m to 3 m length of fibre at a running rate of 2 m/s to 5 m/s while passing between capstans approximately 150 mm in diameter. The ambient temperature is a nominal 293 K (20°C) and relative humidity 40%. Equivalent national standards may be used for executing the proof test.</i></p> <p data-bbox="475 745 1265 813">d. “Electronically steerable phased array antennae” having any of the following characteristics:</p> <ol data-bbox="539 831 1265 1245" style="list-style-type: none"> 1. Rated for operation above 31.8 GHz, but not exceeding 57 GHz, and having an Effective Radiated Power (ERP) equal to or greater than +20 dBm (22.15 dBm Effective Isotropic Radiated Power (EIRP)); 2. Rated for operation above 57 GHz, but not exceeding 66 GHz, and having an ERP equal to or greater than +24 dBm (26.15 dBm EIRP); 3. Rated for operation above 66 GHz, but not exceeding 90 GHz, and having an ERP equal to or greater than +20 dBm (22.15 dBm EIRP); <u>or</u> 4. Rated for operation above 90 GHz; <p data-bbox="539 1263 603 1296"><u>Note</u></p> <p data-bbox="539 1303 1265 1438"><i>Category Code 5A001.d. does not include “electronically steerable phased array antennae” for landing systems with instruments meeting ICAO standards covering Microwave Landing Systems (MLS).</i></p> <p data-bbox="475 1456 1265 1554">e. Radio direction finding equipment operating at frequencies above 30 MHz and having all of the following characteristics, and specially designed components therefor:</p> <ol data-bbox="539 1572 1265 1722" style="list-style-type: none"> 1. “Instantaneous bandwidth” of 10 MHz or more; <u>and</u> 2. Capable of finding a Line Of Bearing (LOB) to non-cooperating radio transmitters with a signal duration of less than 1 ms;

<i>Category Code</i>	<i>Item Description</i>
	<p>f. Mobile telecommunications interception or jamming equipment, and monitoring equipment therefor, as follows, and specially designed components therefor:</p> <ol style="list-style-type: none"> 1. Interception equipment designed for the extraction of voice or data, transmitted over the air interface; 2. Interception equipment not specified in Category Code 5A001.f.1., designed for the extraction of client device or subscriber identifiers (e.g. IMSI, TIMSI or IMEI), signalling, or other metadata transmitted over the air interface; 3. Jamming equipment specially designed or modified to intentionally and selectively interfere with, deny, inhibit, degrade or seduce mobile telecommunication services and performing any of the following: <ol style="list-style-type: none"> a. Simulate the functions of Radio Access Network (RAN) equipment; b. Detect and exploit specific characteristics of the mobile telecommunications protocol employed (e.g. GSM); <u>or</u> c. Exploit specific characteristics of the mobile telecommunications protocol employed (e.g. GSM); 4. RF monitoring equipment designed or modified to identify the operation of items specified in Category Code 5A001.f.1., 5A001.f.2. or 5A001.f.3.; <p><u>Note</u> <i>Category Codes 5A001.f.1. and 5A001.f.2. do not include any of the following:</i></p> <ol style="list-style-type: none"> a. <i>Equipment specially designed for the interception of analogue Private Mobile Radio (PMR), IEEE 802.11 WLAN;</i> b. <i>Equipment designed for mobile telecommunications network operators; <u>or</u></i> c. <i>Equipment designed for the “development” or “production” of mobile telecommunications equipment or systems.</i>

Category Code	Item Description
	<p><u>N.B. 1</u> See also Division 2 of Part 1 of this Schedule.</p> <p><u>N.B. 2</u> For radio receivers, see Category Code 5A001.b.5.</p> <p>g. Passive Coherent Location (PCL) systems or equipment, specially designed for detecting and tracking moving objects by measuring reflections of ambient radio frequency emissions, supplied by non-radar transmitters;</p> <p><u>Technical Note</u> Non-radar transmitters may include commercial radio, television or cellular telecommunications base stations.</p> <p><u>Note</u> Category Code 5A001.g. does not include any of the following:</p> <p>a. Radio-astronomical equipment; <u>or</u></p> <p>b. Systems or equipment, that require any radio transmission from the target.</p> <p>h. Counter Improvised Explosive Device (IED) equipment and related equipment, as follows:</p> <ol style="list-style-type: none"> 1. Radio Frequency (RF) transmitting equipment, not specified in Category Code 5A001.f., designed or modified for prematurely activating or preventing the initiation of Improvised Explosive Devices; 2. Equipment using techniques designed to enable radio communications in the same frequency channels on which co-located equipment specified in Category Code 5A001.h.1. is transmitting; <p><u>N.B.</u> See also Division 2 of Part 1 of this Schedule.</p> <p>i. Not used;</p>

<i>Category Code</i>	<i>Item Description</i>
	<p>j. Internet Protocol (IP) network communications surveillance systems or equipment, and specially designed components therefor, having all of the following characteristics:</p> <ol style="list-style-type: none"> 1. Performing all of the following on a carrier class Internet Protocol (IP) network (e.g. national grade IP backbone): <ol style="list-style-type: none"> a. Analysis at the application layer (e.g. Layer 7 of Open Systems Interconnection (OSI) model (ISO/IEC 7498-1)); b. Extraction of selected metadata and application content (e.g. voice, video, messages, attachments); <u>and</u> c. Indexing of extracted data; <u>and</u> 2. Being specially designed to carry out all of the following: <ol style="list-style-type: none"> a. Execution of searches on the basis of 'hard selectors'; <u>and</u> <p><i><u>Technical Note</u></i> <i>'Hard selectors' means data or set of data, related to an individual (e.g. family name, given name, e-mail, street address, phone number or group affiliations).</i></p> <ol style="list-style-type: none"> b. Mapping of the relational network of an individual or of a group of people. <p><i><u>Note</u></i> <i>Category Code 5A001.j. does not include systems or equipment, specially designed for any of the following:</i></p> <ol style="list-style-type: none"> a. <i>Marketing purposes;</i> b. <i>Network Quality of Service (QoS); <u>or</u></i> c. <i>Quality of Experience (QoE).</i>

<i>Category Code</i>	<i>Item Description</i>
5A101	<p>Telemetry and telecontrol equipment, including ground equipment, designed or modified for ‘missiles’.</p> <p><u>Technical Note</u> <i>In Category Code 5A101, ‘missile’ means complete rocket systems and unmanned aerial vehicle systems capable of a range exceeding 300 km.</i></p> <p><u>Note</u> <i>Category Code 5A101 does not include:</i></p> <ul style="list-style-type: none"> <i>a. Equipment designed or modified for manned aircraft or satellites;</i> <i>b. Ground based equipment designed or modified for terrestrial or marine applications;</i> <i>c. Equipment designed for commercial, civil or ‘Safety of Life’ (e.g. data integrity, flight safety) GNSS services.</i>
5B1	Test, Inspection and Production Equipment
5B001	<p>Telecommunications test, inspection and production equipment, components and accessories, as follows:</p> <ul style="list-style-type: none"> a. Equipment and specially designed components or accessories therefor, specially designed for the “development” or “production” of equipment, functions or features, specified in Category Code 5A001; <p><u>Note</u> <i>Category Code 5B001.a. does not include optical fibre characterisation equipment.</i></p> <ul style="list-style-type: none"> b. Equipment and specially designed components or accessories therefor, specially designed for the “development” of any of the following telecommunication transmission or switching equipment: <ul style="list-style-type: none"> 1. Not used; 2. Equipment employing a “laser” and having any of the following characteristics: <ul style="list-style-type: none"> a. A transmission wavelength exceeding 1,750 nm; b. Not used;

<i>Category Code</i>	<i>Item Description</i>
	<p>c. Employing coherent optical transmission or coherent optical detection techniques; <u>or</u></p> <p><i>Note</i> <i>Category Code 5B001.b.2.c. includes equipment specially designed for the “development” of systems using an optical local oscillator in the receiving side to synchronise with a carrier “laser”.</i></p> <p><i>Technical Note</i> <i>For the purpose of Category Code 5B001.b.2.c., these techniques include optical heterodyne, homodyne or intradyne techniques.</i></p> <p>d. Employing analogue techniques and having a bandwidth exceeding 2.5 GHz; <u>or</u></p> <p><i>Note</i> <i>Category Code 5B001.b.2.d. does not include equipment specially designed for the “development” of commercial TV systems.</i></p> <p>3. Not used;</p> <p>4. Radio equipment employing Quadrature-Amplitude-Modulation (QAM) techniques above level 1,024;</p> <p>5. Not used.</p>
5C1	<p>Materials</p> <p>None.</p>
5D1 5D001	<p>Software</p> <p>“Software” as follows:</p> <p>a. “Software” specially designed or modified for the “development”, “production” or “use” of equipment, functions or features, specified in Category Code 5A001;</p> <p>b. Not used;</p>

<i>Category Code</i>	<i>Item Description</i>
	<p>c. Specific “software” specially designed or modified to provide characteristics, functions or features of equipment, specified in Category Code 5A001 or 5B001;</p> <p>d. “Software” specially designed or modified for the “development” of any of the following telecommunication transmission or switching equipment:</p> <ol style="list-style-type: none"> 1. Not used; 2. Equipment employing a “laser” and having any of the following characteristics: <ol style="list-style-type: none"> a. A transmission wavelength exceeding 1,750 nm; <u>or</u> b. Employing analogue techniques and having a bandwidth exceeding 2.5 GHz; <u>or</u> <p><i>Note</i> <i>Category Code 5D001.d.2.b. does not include “software” specially designed or modified for the “development” of commercial TV systems.</i></p> 3. Not used; 4. Radio equipment employing Quadrature-Amplitude-Modulation (QAM) techniques above level 1,024.
5D101	“Software” specially designed or modified for the “use” of equipment specified in Category Code 5A101.
5E1	Technology
5E001	<p>“Technology”, as follows:</p> <ol style="list-style-type: none"> a. “Technology” (according to the General Technology Note) for the “development”, “production” or “use” (excluding operation) of equipment, functions or features specified in Category Code 5A001 or “software” specified in Category Code 5D001.a.;

<i>Category Code</i>	<i>Item Description</i>
	<p>b. Specific “technology” as follows:</p> <ol style="list-style-type: none"> 1. “Required” “technology” for the “development” or “production” of telecommunications equipment specially designed to be used on board satellites; 2. “Technology” for the “development” or “use” of “laser” communication techniques with the capability of automatically acquiring and tracking signals and maintaining communications through exoatmosphere or sub-surface (water) media; 3. “Technology” for the “development” of digital cellular radio base station receiving equipment whose reception capabilities that allow multi-band, multi-channel, multi-mode, multi-coding algorithm or multi-protocol operation can be modified by changes in “software”; 4. “Technology” for the “development” of “spread spectrum” techniques, including “frequency hopping” techniques; <p><i>Note</i> <i>Category Code 5E001.b.4. does not apply to “technology” for the “development” of any of the following:</i></p> <ol style="list-style-type: none"> <i>a. Civil cellular radio-communications systems; <u>or</u></i> <i>b. Fixed or mobile satellite earth stations for commercial civil telecommunications.</i> <p>c. “Technology” (according to the General Technology Note) for the “development” or “production” of any of the following:</p> <ol style="list-style-type: none"> 1. Equipment employing digital techniques designed to operate at a “total digital transfer rate” exceeding 560 Gbit/s; <p><i>Technical Note</i> <i>For telecommunication switching equipment the “total digital transfer rate” is the unidirectional speed of a single interface, measured at the highest speed port or line.</i></p>

<i>Category Code</i>	<i>Item Description</i>
	<p>2. Equipment employing a “laser” and having any of the following characteristics:</p> <ul style="list-style-type: none"> a. A transmission wavelength exceeding 1,750 nm; b. Not used; c. Employing coherent optical transmission or coherent optical detection techniques; <p><i>Note</i> <i>Category Code 5E001.c.2.c. includes “technology” for the “development” or “production” of systems using an optical local oscillator in the receiving side to synchronise with a carrier “laser”.</i></p> <p><i>Technical Note</i> <i>For the purpose of Category Code 5E001.c.2.c., these techniques include optical heterodyne, homodyne or intradyne techniques.</i></p> <ul style="list-style-type: none"> d. Employing wavelength division multiplexing techniques of optical carriers at less than 100 GHz spacing; <u>or</u> e. Employing analogue techniques and having a bandwidth exceeding 2.5 GHz; <p><i>Note</i> <i>Category Code 5E001.c.2.e. does not include “technology” for the “development” or “production” of commercial TV systems.</i></p> <p><i>N.B.</i> <i>For “technology” for the “development” or “production” of non-telecommunications equipment employing a laser, see Category 6E.</i></p> <p>3. Equipment employing “optical switching” and having a switching time less than 1 ms;</p>

<i>Category Code</i>	<i>Item Description</i>
	<p>4. Radio equipment having any of the following characteristics:</p> <ul style="list-style-type: none"> a. Quadrature-Amplitude-Modulation (QAM) techniques above level 1,024; b. Operating at input or output frequencies exceeding 31.8 GHz; <u>or</u> <p><i>Note</i> <i>Category Code 5E001.c.4.b. does not include “technology” for the “development” or “production” of equipment designed or modified for operation in any frequency band which is “allocated by the ITU” for radio-communications services, but not for radio-determination.</i></p> <ul style="list-style-type: none"> c. Operating in the 1.5 MHz to 87.5 MHz band and incorporating adaptive techniques providing more than 15 dB suppression of an interfering signal; <u>or</u> <p>5. Not used;</p> <p>6. Mobile equipment having all of the following characteristics:</p> <ul style="list-style-type: none"> a. Operating at an optical wavelength greater than or equal to 200 nm and less or equal to 400 nm; <u>and</u> b. Operating as a “local area network”; <p>d. “Technology” (according to the General Technology Note) for the “development” or “production” of Microwave Monolithic Integrated Circuit (MMIC) power amplifiers specially designed for telecommunications and having any of the following characteristics:</p> <p><i>Technical Note</i> <i>For the purpose of Category Code 5E001.d., the parameter peak saturated power output may also be referred to on product data sheets as output power, saturated power output, maximum power output, peak power output, or peak envelope power output.</i></p>

<i>Category Code</i>	<i>Item Description</i>
	<ol style="list-style-type: none"> <li data-bbox="544 454 1273 1055">1. Rated for operation at frequencies exceeding 2.7 GHz up to and including 6.8 GHz with a “fractional bandwidth” greater than 15%, and having any of the following characteristics: <ol style="list-style-type: none"> <li data-bbox="624 607 1273 703">a. A peak saturated power output greater than 75 W (48.75 dBm) at any frequency exceeding 2.7 GHz up to and including 2.9 GHz; <li data-bbox="624 723 1273 819">b. A peak saturated power output greater than 55 W (47.4 dBm) at any frequency exceeding 2.9 GHz up to and including 3.2 GHz; <li data-bbox="624 840 1273 936">c. A peak saturated power output greater than 40 W (46 dBm) at any frequency exceeding 3.2 GHz up to and including 3.7 GHz; <u>or</u> <li data-bbox="624 956 1273 1055">d. A peak saturated power output greater than 20 W (43 dBm) at any frequency exceeding 3.7 GHz up to and including 6.8 GHz; <li data-bbox="544 1075 1273 1440">2. Rated for operation at frequencies exceeding 6.8 GHz up to and including 16 GHz with a “fractional bandwidth” greater than 10%, and having any of the following characteristics: <ol style="list-style-type: none"> <li data-bbox="624 1227 1273 1323">a. A peak saturated power output greater than 10 W (40 dBm) at any frequency exceeding 6.8 GHz up to and including 8.5 GHz; <u>or</u> <li data-bbox="624 1344 1273 1440">b. A peak saturated power output greater than 5 W (37 dBm) at any frequency exceeding 8.5 GHz up to and including 16 GHz; <li data-bbox="544 1460 1273 1588">3. Rated for operation with a peak saturated power output greater than 3 W (34.77 dBm) at any frequency exceeding 16 GHz up to and including 31.8 GHz, and with a “fractional bandwidth” of greater than 10%; <li data-bbox="544 1608 1273 1704">4. Rated for operation with a peak saturated power output greater than 0.1 nW (-70 dBm) at any frequency exceeding 31.8 GHz up to and including 37 GHz; <li data-bbox="544 1724 1273 1856">5. Rated for operation with a peak saturated power output greater than 1 W (30 dBm) at any frequency exceeding 37 GHz up to and including 43.5 GHz, and with a “fractional bandwidth” of greater than 10%;

<i>Category Code</i>	<i>Item Description</i>
5E101	<p>6. Rated for operation with a peak saturated power output greater than 31.62 mW (15 dBm) at any frequency exceeding 43.5 GHz up to and including 75 GHz, and with a “fractional bandwidth” of greater than 10%;</p> <p>7. Rated for operation with a peak saturated power output greater than 10 mW (10 dBm) at any frequency exceeding 75 GHz up to and including 90 GHz, and with a “fractional bandwidth” of greater than 5%; <u>or</u></p> <p>8. Rated for operation with a peak saturated power output greater than 0.1 nW (-70 dBm) at any frequency exceeding 90 GHz;</p> <p>e. “Technology” (according to the General Technology Note) for the “development” or “production” of electronic devices and circuits, specially designed for telecommunications and containing components manufactured from “superconductive” materials, specially designed for operation at temperatures below the “critical temperature” of at least one of the “superconductive” constituents and having any of the following characteristics:</p> <ol style="list-style-type: none"> 1. Current switching for digital circuits using “superconductive” gates with a product of delay time per gate (in seconds) and power dissipation per gate (in watts) of less than 10^{-14} J; <u>or</u> 2. Frequency selection at all frequencies using resonant circuits with Q-values exceeding 10,000.

Category Code	Item Description
---------------	------------------

Part 2 — “INFORMATION SECURITY”

Note 1

Not used.

Note 2

Category 5 – Part 2 does not include products when accompanying their user for the user’s personal use.

Note 3

Cryptography Note

Category Codes 5A002, 5A003, 5A004 and 5D002 do not include goods as follows:

- a. *Goods that meet all of the following:*
 1. *Generally available to the public by being sold, without restriction, from stock at retail selling points by means of any of the following:*
 - a. *Over-the-counter transactions;*
 - b. *Mail order transactions;*
 - c. *Electronic transactions; or*
 - d. *Telephone call transactions;*
 2. *The cryptographic functionality cannot easily be changed by the user; and*
 3. *Designed for installation by the user without further substantial support by the supplier;*
- b. *Hardware components or ‘executable software’, of existing goods described in paragraph a. of this Note, that have been designed for these existing items, meeting all of the following:*
 1. *“Information security” is not the primary function or set of functions of the component or ‘executable software’;*
 2. *The component or ‘executable software’ does not change any cryptographic functionality of the existing items, or add new cryptographic functionality to the existing items; and*
 3. *The feature set of the component or ‘executable software’ is fixed and is not designed or modified to customer specification.*

Category Code	Item Description
---------------	------------------

Technical Note

For the purpose of the Cryptography Note, ‘executable software’ means “software” in executable form, from an existing hardware component excluded from Category Code 5A002, 5A003 or 5A004 by the Cryptography Note.

Note

‘Executable software’ does not include complete binary images of the “software” running on an end-item.

Note to the Cryptography Note

1. *To meet paragraph a. of Note 3, all of the following must apply:*
 - a. *The item is of potential interest to a wide range of individuals and businesses; and*
 - b. *The price and information about the main functionality of the item are available before purchase without the need to consult the vendor or supplier. A simple price enquiry is not considered to be a consultation.*
2. *In determining eligibility of paragraph a. of Note 3, factors such as quantity, price, required technical skill, existing sales channels, typical customers, typical use or any exclusionary practices of the supplier may be taken into account.*

Note 4

Category 5 – Part 2 does not include goods incorporating or using “cryptography” and meeting all of the following:

- a. *The primary function or set of functions is not any of the following:*
 1. *“Information security”;*
 2. *A computer, including operating systems, parts and components therefor;*
 3. *Sending, receiving or storing information (except in support of entertainment, mass commercial broadcasts, digital rights management or medical records management); or*
 4. *Networking (includes operation, administration, management and provisioning); and*
- b. *The cryptographic functionality is limited to supporting their primary function or set of functions.*

<i>Category Code</i>	<i>Item Description</i>
5A2	Systems, Equipment and Components
5A002	<p data-bbox="480 506 1262 568">“Information security” systems, equipment and components, as follows:</p> <p data-bbox="480 591 1262 654">a. Systems, equipment and components for cryptographic “information security”, as follows:</p> <p data-bbox="544 674 600 701"><u><i>N.B.</i></u></p> <p data-bbox="544 719 1262 846"><i>For Global Navigation Satellite Systems (GNSS) receiving equipment containing or employing decryption, see Category Code 7A005 and for related decryption “software” and “technology”, see Category Codes 7D005 and 7E001.</i></p> <p data-bbox="544 869 1262 1032">1. Designed or modified to use “cryptography” employing digital techniques performing any cryptographic function other than authentication, digital signature or the execution of copy-protected “software”, and having any of the following characteristics:</p> <p data-bbox="608 1055 799 1081"><u><i>Technical Notes</i></u></p> <p data-bbox="632 1099 1262 1227">1. <i>Functions for authentication, digital signature and the execution of copy-protected “software” include their associated key management function.</i></p> <p data-bbox="632 1249 1262 1435">2. <i>Authentication includes all aspects of access control where there is no encryption of files or text except as directly related to the protection of passwords, Personal Identification Numbers (PINs) or similar data to prevent unauthorised access.</i></p> <p data-bbox="632 1458 1262 1525">a. <i>A “symmetric algorithm” employing a key length in excess of 56 bits; <u>or</u></i></p> <p data-bbox="695 1547 871 1574"><u><i>Technical Note</i></u></p> <p data-bbox="695 1592 1262 1653"><i>In Category 5 – Part 2, parity bits are not included in the key length.</i></p> <p data-bbox="632 1675 1262 1742">b. <i>An “asymmetric algorithm” where the security of the algorithm is based on any of the following:</i></p> <p data-bbox="695 1765 1262 1816">1. <i>Factorisation of integers in excess of 512 bits (e.g. RSA);</i></p>

<i>Category Code</i>	<i>Item Description</i>
	<p data-bbox="692 454 1267 584">2. Computation of discrete logarithms in a multiplicative group of a finite field of size greater than 512 bits (e.g. Diffie-Hellman over $\mathbb{Z}/p\mathbb{Z}$); <u>or</u></p> <p data-bbox="692 607 1267 736">3. Discrete logarithms in a group other than mentioned in Category Code 5A002.a.1.b.2. in excess of 112 bits (e.g. Diffie-Hellman over an elliptic curve);</p> <p data-bbox="544 759 603 786"><i>Note</i></p> <p data-bbox="544 808 1267 871"><i>Category Code 5A002.a. does not include any of the following:</i></p> <p data-bbox="544 893 1267 956">a. <i>Smart cards and smart card ‘readers/writers’ as follows:</i></p> <p data-bbox="628 978 1267 1072">1. <i>A smart card or an electronically readable personal document (e.g. token coin, e-passport) that meets any of the following:</i></p> <p data-bbox="692 1095 1267 1288">a. <i>The cryptographic capability is restricted for use in equipment or systems excluded from Category Code 5A002, 5A003 or 5A004 by Note 4 in Category 5 – Part 2 or entries b. to f. of this Note, and cannot be reprogrammed for any other use; <u>or</u></i></p> <p data-bbox="692 1310 1267 1337">b. <i>Having all of the following characteristics:</i></p> <p data-bbox="756 1359 1267 1453">1. <i>It is specially designed and limited to allow protection of ‘personal data’ stored within;</i></p> <p data-bbox="756 1476 1267 1606">2. <i>Has been, or can only be, personalised for public or commercial transactions or individual identification; <u>and</u></i></p> <p data-bbox="756 1628 1267 1691">3. <i>Where the cryptographic capability is not user accessible;</i></p>

Category Code	Item Description
	<p data-bbox="756 454 938 488"><u>Technical Note</u></p> <p data-bbox="756 495 1257 629">'Personal data' includes any data specific to a particular person or entity, such as the amount of money stored and data necessary for authentication.</p> <p data-bbox="628 645 1262 745">2. 'Readers/writers' specially designed or modified, and limited, for items specified in paragraph a.1. of this Note;</p> <p data-bbox="691 761 873 795"><u>Technical Note</u></p> <p data-bbox="691 801 1262 902">'Readers/writers' include equipment that communicates with smart cards or electronically readable documents through a network.</p> <p data-bbox="544 918 1262 985">b. Cryptographic equipment specially designed and limited for banking use or 'money transactions';</p> <p data-bbox="606 1001 788 1034"><u>Technical Note</u></p> <p data-bbox="606 1041 1262 1142">'Money transactions' in Category Code 5A002.a. Note b. includes the collection and settlement of fares or credit functions.</p> <p data-bbox="544 1158 1262 1426">c. Portable or mobile radiotelephones for civil use (e.g. for use with commercial civil cellular radio communication systems) that are not capable of transmitting encrypted data directly to another radiotelephone or equipment (other than Radio Access Network (RAN) equipment), nor of passing encrypted data through RAN equipment (e.g. Radio Network Controller (RNC) or Base Station Controller (BSC));</p> <p data-bbox="544 1442 1262 1648">d. Cordless telephone equipment not capable of end-to-end encryption where the maximum effective range of unboosted cordless operation (i.e. a single, unrelayed hop between terminal and home base station) is less than 400 metres according to the manufacturer's specifications;</p>

Category Code	Item Description
	<p>e. <i>Portable or mobile radiotelephones and similar client wireless devices for civil use, that implement only published or commercial cryptographic standards (except for anti-piracy functions, which may not be published) and also meet the provisions of paragraphs a.2. and a.3. of the Cryptography Note (Note 3 in Category 5 – Part 2), that have been customised for a specific civil industry application with features that do not affect the cryptographic functionality of these original non-customised devices;</i></p> <p>f. <i>Wireless “personal area network” equipment that implement only published or commercial cryptographic standards and where the cryptographic capability is limited to a nominal operating range not exceeding 30 metres according to the manufacturer’s specifications, or not exceeding 100 metres according to the manufacturer’s specifications for equipment that cannot interconnect with more than seven devices;</i></p> <p>g. <i>Equipment, all cryptographic capability specified by Category Code 5A002.a. of which meets any of the following characteristics:</i></p> <ol style="list-style-type: none"> 1. <i>It cannot be used; or</i> 2. <i>It can only be made useable by means of “cryptographic activation”.</i> <p><u><i>N.B.1</i></u> <i>See Category Code 5A002.a. for equipment that has undergone “cryptographic activation”.</i></p> <p><u><i>N.B.2</i></u> <i>See also Category Codes 5A002.b., 5D002.d. and 5E002.b.</i></p> <p>h. <i>Mobile telecommunications Radio Access Network (RAN) equipment designed for civil use, which also meet the provisions of paragraphs a.2. and a.3. of the Cryptography Note (Note 3 to Category 5 – Part 2), having an RF output power limited to 0.1 W (20 dBm) or less, and supporting 16 or fewer concurrent users;</i></p>

<i>Category Code</i>	<i>Item Description</i>
	<p data-bbox="539 454 1268 622">i. <i>Routers, switches or relays, where the “information security” functionality is limited to the tasks of “Operations, Administration or Maintenance” (“OAM”) implementing only published or commercial cryptographic standards; <u>or</u></i></p> <p data-bbox="539 640 1268 741">j. <i>General purpose computing equipment or servers, where the “information security” functionality meets all of the following:</i></p> <ol style="list-style-type: none"> <li data-bbox="628 757 1268 824">1. <i>Uses only published or commercial cryptographic standards; <u>and</u></i> <li data-bbox="628 842 1268 1088">2. <i>Is any of the following:</i> <ol style="list-style-type: none"> <li data-bbox="692 891 1268 958">a. <i>Integral to a CPU that meets the provisions of Note 3 to Category 5 – Part 2;</i> <li data-bbox="692 976 1268 1043">b. <i>Integral to an operating system that is not specified by Category Code 5D002; <u>or</u></i> <li data-bbox="692 1061 1268 1088">c. <i>Limited to “OAM” of the equipment.</i> <p data-bbox="480 1106 1268 1240">b. <i>Designed or modified to enable, by means of “cryptographic activation” an item to achieve or exceed the controlled performance levels for functionality specified in Category Code 5A002.a. that would not otherwise be enabled;</i></p> <p data-bbox="480 1258 1268 1326">c. <i>Designed or modified to use or perform “quantum cryptography”;</i></p> <p data-bbox="539 1344 727 1370"><u><i>Technical Note</i></u></p> <p data-bbox="539 1384 1268 1451"><i>“Quantum cryptography” is also known as Quantum Key Distribution (QKD).</i></p> <p data-bbox="480 1469 1268 1626">d. <i>Designed or modified to use cryptographic techniques to generate channelising codes, scrambling codes or network identification codes, for systems using ultra-wideband modulation techniques and having any of the following characteristics:</i></p> <ol style="list-style-type: none"> <li data-bbox="544 1644 1050 1671">1. <i>A bandwidth exceeding 500 MHz; <u>or</u></i> <li data-bbox="544 1688 1110 1715">2. <i>A “fractional bandwidth” of 20% or more;</i>

<i>Category Code</i>	<i>Item Description</i>
5A003	<p>e. Designed or modified to use cryptographic techniques to generate the spreading code for “spread spectrum” systems, other than those specified in Category Code 5A002.d., including the hopping code for “frequency hopping” systems.</p> <p>Systems, equipment and components, for non-cryptographic “information security”, as follows:</p> <p>a. Communications cable systems designed or modified using mechanical, electrical or electronic means to detect surreptitious intrusion;</p> <p><i>Note</i> <i>Category Code 5A003.a. only includes physical layer security.</i></p> <p>b. Specially designed or modified to reduce the compromising emanations of information-bearing signals beyond what is necessary for health, safety or electromagnetic interference standards.</p>
5A004	<p>Systems, equipment and components for defeating, weakening or bypassing “information security”, as follows:</p> <p>a. Designed or modified to perform ‘cryptanalytic functions’.</p> <p><i>Note</i> <i>Category Code 5A004.a. includes systems or equipment, designed or modified to perform ‘cryptanalytic functions’ by means of reverse engineering.</i></p> <p><i>Technical Note</i> <i>‘Cryptanalytic functions’ are functions designed to defeat cryptographic mechanisms in order to derive confidential variables or sensitive data, including clear text, passwords or cryptographic keys.</i></p>

<i>Category Code</i>	<i>Item Description</i>
5B2	Test, Inspection and Production Equipment
5B002	<p>“Information security” test, inspection and “production” equipment, as follows:</p> <ol style="list-style-type: none"> a. Equipment specially designed for the “development” or “production” of equipment specified in Category Code 5A002, 5A003, 5A004 or 5B002.b.; b. Measuring equipment specially designed to evaluate and validate the “information security” functions of the equipment specified in Category Code 5A002, 5A003 or 5A004, or of “software” specified in Category Code 5D002.a. or 5D002.c.
5C2	Materials
	None.
5D2	Software
5D002	<p>“Software” as follows:</p> <ol style="list-style-type: none"> a. “Software” specially designed or modified for the “development”, “production” or “use” of equipment specified in Category Code 5A002, 5A003 or 5A004, or of “software” specified in Category Code 5D002.c.; b. “Software” specially designed or modified to support “technology” specified in Category Code 5E002; c. Specific “software”, as follows: <ol style="list-style-type: none"> 1. “Software” having the characteristics of, or performing or simulating the functions of the equipment specified in Category Code 5A002, 5A003 or 5A004; 2. “Software” to certify “software” specified in Category Code 5D002.c.1.; <p><u>Note</u> <i>Category Code 5D002.c. does not apply to “software” limited to the tasks of “OAM” implementing only published or commercial cryptographic standards.</i></p>

<i>Category Code</i>	<i>Item Description</i>
<p data-bbox="363 651 416 685">5E2</p> <p data-bbox="352 703 427 736">5E002</p>	<p data-bbox="480 454 1262 584">d. “Software” designed or modified to enable, by means of “cryptographic activation”, an item to meet the criteria for functionality specified by Category Code 5A002.a., that would not otherwise be met.</p> <p data-bbox="480 651 624 685">Technology</p> <p data-bbox="480 703 783 736">“Technology” as follows:</p> <p data-bbox="480 754 1262 920">a. “Technology” (according to the General Technology Note) for the “development”, “production” or “use” of equipment specified in Category Code 5A002, 5A003, 5A004 or 5B002, or of “software” specified in Category Code 5D002.a. or 5D002.c.;</p> <p data-bbox="480 938 1262 1068">b. “Technology” to enable, by means of “cryptographic activation”, an item to meet the criteria for functionality specified by Category Code 5A002.a., that would not otherwise be met.</p> <p data-bbox="480 1086 539 1120"><u>Note</u></p> <p data-bbox="480 1128 1262 1258"><i>Category Code 5E002 includes “information security” technical data resulting from procedures carried out to evaluate or determine the implementation of functions, features or techniques specified in Category 5 – Part 2.</i></p>

<i>Category Code</i>	<i>Item Description</i>
CATEGORY 6 — SENSORS AND LASERS	
6A	Systems, Equipment and Components
6A001	<p>Acoustic systems, equipment and components, as follows:</p> <p>a. Marine acoustic systems, equipment and specially designed components therefor, as follows:</p> <p>1. Active (transmitting or transmitting-and-receiving) systems, equipment and specially designed components therefor, as follows:</p> <p><i>Note</i> <i>Category Code 6A001.a.1. does not include equipment as follows:</i></p> <p>a. <i>Depth sounders operating vertically below the apparatus, not including a scanning function exceeding $\pm 20^\circ$, and limited to measuring the depth of water, the distance of submerged or buried objects or fish finding;</i></p> <p>b. <i>Acoustic beacons, as follows:</i></p> <p>1. <i>Acoustic emergency beacons;</i></p> <p>2. <i>Pingers specially designed for relocating or returning to an underwater position.</i></p> <p>a. Acoustic seabed survey equipment as follows:</p> <p>1. Surface vessel survey equipment designed for seabed topographic mapping and having all of the following characteristics:</p> <p>a. Designed to take measurements at an angle exceeding 20° from the vertical;</p> <p>b. Designed to measure seabed topography at seabed depths exceeding 600 m;</p> <p>c. ‘Sounding resolution’ less than 2; <u>and</u></p>

<i>Category Code</i>	<i>Item Description</i>
	<p>d. 'Enhancement' of the depth accuracy through compensation for all of the following:</p> <ol style="list-style-type: none"> 1. Motion of the acoustic sensor; 2. In-water propagation from sensor to the seabed and back; <u>and</u> 3. Sound speed at the sensor; <p><i>Technical Notes</i></p> <ol style="list-style-type: none"> 1. 'Sounding resolution' is the swath width (degrees) divided by the maximum number of soundings per swath. 2. 'Enhancement' includes the ability to compensate by external means. <p>2. Underwater survey equipment designed for seabed topographic mapping and having any of the following:</p> <p><i>Technical Note</i></p> <p><i>The acoustic sensor pressure rating determines the depth rating of the equipment specified in Category Code 6A001.a.1.a.2.</i></p> <ol style="list-style-type: none"> a. Having all of the following characteristics: <ol style="list-style-type: none"> 1. Designed or modified to operate at depths exceeding 300 m; <u>and</u> 2. 'Sounding rate' greater than 3,800 m/s; <u>or</u>

Category Code	Item Description
	<p data-bbox="884 454 1062 483"><i>Technical Note</i></p> <p data-bbox="884 495 1262 860"><i>‘Sounding rate’ is the product of the maximum speed (m/s) at which the sensor can operate and the maximum number of soundings per swath assuming 100% coverage. For systems that produce soundings in two directions (3D sonars), the maximum of the ‘sounding rate’ in either direction should be used.</i></p> <p data-bbox="754 882 1262 1010">b. Survey equipment, not specified in Category Code 6A001.a.1.a.2.a., having all of the following characteristics:</p> <ol data-bbox="818 1032 1262 1852" style="list-style-type: none"> <li data-bbox="818 1032 1262 1099">1. Designed or modified to operate at depths exceeding 100 m; <li data-bbox="818 1122 1262 1211">2. Designed to take measurements at an angle exceeding 20° from the vertical; <li data-bbox="818 1234 1262 1536">3. Having any of the following characteristics: <ol data-bbox="884 1323 1262 1536" style="list-style-type: none"> <li data-bbox="884 1323 1262 1391">a. Operating frequency below 350 kHz; <u>or</u> <li data-bbox="884 1413 1262 1536">b. Designed to measure seabed topography at a range exceeding 200 m from the acoustic sensor; <u>and</u> <li data-bbox="818 1559 1262 1852">4. ‘Enhancement’ of the depth accuracy through compensation of all of the following: <ol data-bbox="884 1682 1262 1852" style="list-style-type: none"> <li data-bbox="884 1682 1262 1749">a. Motion of the acoustic sensor; <li data-bbox="884 1771 1262 1852">b. In-water propagation from sensor to the seabed and back; <u>and</u>

<i>Category Code</i>	<i>Item Description</i>
	<p style="text-align: center;">c. Sound speed at the sensor;</p> <p>3. Side Scan Sonar (SSS) or Synthetic Aperture Sonar (SAS), designed for seabed imaging and having all of the following characteristics, and specially designed transmitting and receiving acoustic arrays therefor:</p> <p>a. Designed or modified to operate at depths exceeding 500 m;</p> <p>b. An 'area coverage rate' of greater than 570 m²/s while operating at the maximum range that it can operate with an 'along track resolution' of less than 15 cm; <u>and</u></p> <p>c. An 'across track resolution' of less than 15 cm;</p> <p><u>Technical Notes</u></p> <p>1. 'Area coverage rate' (m²/s) is twice the product of the sonar range (m) and the maximum speed (m/s) at which the sensor can operate at that range.</p> <p>2. 'Along track resolution' (cm), for SSS only, is the product of azimuth (horizontal) beamwidth (degrees) and sonar range (m) and 0.873.</p> <p>3. 'Across track resolution' (cm) is 75 divided by the signal bandwidth (kHz).</p>

<i>Category Code</i>	<i>Item Description</i>
	<p>b. Systems or transmitting and receiving arrays, designed for object detection or location, having any of the following characteristics:</p> <ol style="list-style-type: none"> 1. A transmitting frequency below 10 kHz; 2. Sound pressure level exceeding 224 dB (reference 1 μPa at 1 m) for equipment with an operating frequency in the band from 10 kHz to 24 kHz inclusive; 3. Sound pressure level exceeding 235 dB (reference 1 μPa at 1 m) for equipment with an operating frequency in the band between 24 kHz and 30 kHz; 4. Forming beams of less than 1° on any axis and having an operating frequency of less than 100 kHz; 5. Designed to operate with an unambiguous display range exceeding 5,120 m; <u>or</u> 6. Designed to withstand pressure during normal operation at depths exceeding 1,000 m and having transducers with any of the following characteristics: <ol style="list-style-type: none"> a. Dynamic compensation for pressure; <u>or</u> b. Incorporating other than lead zirconate titanate as the transduction element;

Category Code	Item Description
	<p>c. Acoustic projectors (including transducers), incorporating piezoelectric, magnetostrictive, electrostrictive, electrodynamic or hydraulic elements operating individually or in a designed combination, and having any of the following characteristics:</p> <p><u>Note 1</u> Whether acoustic projectors (including transducers), which are not specified by Category Code 6A001 and which are specially designed for other equipment, is included in Category Code 6A001.c. is determined by whether the other equipment is specified in Division 2 of Part 2 of this Schedule.</p> <p><u>Note 2</u> Category Code 6A001.a.1.c. does not include electronic sources which direct the sound vertically only, or mechanical (e.g. air gun or vapour-shock gun) or chemical (e.g. explosive) sources.</p> <p><u>Note 3</u> Piezoelectric elements specified in Category Code 6A001.a.1.c. include those made from lead-magnesium-niobate/lead-titanate ($Pb(Mg_{1/3}Nb_{2/3})O_3$-$PbTiO_3$, or PMN-PT) single crystals grown from solid solution or lead-indium-niobate/lead-magnesium-niobate/lead-titanate ($Pb(In_{1/2}Nb_{1/2})O_3$-$Pb(Mg_{1/3}Nb_{2/3})O_3$-$PbTiO_3$, or PIN-PMN-PT) single crystals grown from solid solution.</p>

<i>Category Code</i>	<i>Item Description</i>
	<p>1. Operating at frequencies below 10 kHz and having any of the following characteristics:</p> <p>a. Not designed for continuous operation at 100% duty cycle and having a radiated ‘free-field Source Level (SL_{RMS})’ exceeding $(10\log(f) + 169.77)$ dB (reference $1 \mu\text{Pa}$ at 1 m) where f is the frequency in Hertz of maximum Transmitting Voltage Response (TVR) below 10 kHz; <u>or</u></p> <p>b. Designed for continuous operation at 100% duty cycle and having a continuously radiated ‘free-field Source Level (SL_{RMS})’ at 100% duty cycle exceeding $(10\log(f) + 159.77)$ dB (reference $1 \mu\text{Pa}$ at 1 m) where f is the frequency in Hertz of maximum Transmitting Voltage Response (TVR) below 10 kHz; <u>or</u></p> <p><i>Technical Note</i> <i>The ‘free-field Source Level (SL_{RMS})’ is defined along the maximum response axis and in the far field of the acoustic projector. It can be obtained from the Transmitting Voltage Response using the following equation: $SL_{RMS} = (TVR + 20\log V_{RMS})$ dB (reference $1 \mu\text{Pa}$ at 1 m), where SL_{RMS} is the source level, TVR is the Transmitting Voltage Response and V_{RMS} is the Driving Voltage of the Projector.</i></p> <p>2. Not used;</p> <p>3. Side-lobe suppression exceeding 22 dB;</p>

<i>Category Code</i>	<i>Item Description</i>
	<p>d. Acoustic systems and equipment, designed to determine the position of surface vessels or underwater vehicles and having all of the following characteristics, and specially designed components therefor:</p> <ol style="list-style-type: none"> 1. Detection range exceeding 1,000 m; <u>and</u> 2. Determined position error of less than 10 m rms (root mean square) when measured at a range of 1,000 m; <p><i>Note</i> <i>Category Code 6A001.a.1.d. includes:</i></p> <ol style="list-style-type: none"> a. <i>Equipment using coherent “signal processing” between two or more beacons and the hydrophone unit carried by the surface vessel or underwater vehicle;</i> b. <i>Equipment capable of automatically correcting speed-of-sound propagation errors for calculation of a point.</i> <p>e. Active individual sonars, specially designed or modified to detect, locate and automatically classify swimmers or divers, having all of the following characteristics, and specially designed transmitting and receiving acoustic arrays therefor:</p> <ol style="list-style-type: none"> 1. Detection range exceeding 530 m; 2. Determined position error of less than 15 m rms (root mean square) when measured at a range of 530 m; <u>and</u> 3. Transmitted pulse signal bandwidth exceeding 3 kHz; <p><i>N.B.</i> <i>For diver detection systems specially designed or modified for military use, see Division 2 of Part 1 of this Schedule.</i></p>

Category Code	Item Description
	<p data-bbox="692 454 751 483"><u>Note</u></p> <p data-bbox="692 495 1267 622"><i>For Category Code 6A001.a.1.e., where multiple detection ranges are specified for various environments, the greatest detection range is used.</i></p> <p data-bbox="544 645 1267 707">2. Passive systems, equipment and specially designed components therefor, as follows:</p> <p data-bbox="628 730 1267 792">a. Hydrophones having any of the following characteristics:</p> <p data-bbox="692 815 751 844"><u>Note</u></p> <p data-bbox="692 855 1267 983"><i>Whether hydrophones specially designed for other equipment is included in Category Code 6A001.a.2.a. is determined by whether the other equipment is included in that Category Code.</i></p> <p data-bbox="692 1005 874 1034"><u>Technical Note</u></p> <p data-bbox="692 1046 1267 1173"><i>Hydrophones consist of one or more sensing elements producing a single acoustic output channel. Those that contain multiple elements can be referred to as a hydrophone group.</i></p> <ol data-bbox="692 1196 1267 1780" style="list-style-type: none"> <li data-bbox="692 1196 1267 1258">1. Incorporating continuous flexible sensing elements; <li data-bbox="692 1281 1267 1442">2. Incorporating flexible assemblies of discrete sensing elements with either a diameter or length less than 20 mm and with a separation between elements of less than 20 mm; <li data-bbox="692 1464 1267 1780">3. Having any of the following sensing elements: <ol data-bbox="751 1550 1267 1780" style="list-style-type: none"> <li data-bbox="751 1550 991 1579">a. Optical fibres; <li data-bbox="751 1601 1267 1729">b. ‘Piezoelectric polymer films’ other than polyvinylidene-fluoride (PVDF) and its co-polymers {P(VDF-TrFE) and P(VDF-TFE)}; <li data-bbox="751 1751 1246 1780">c. ‘Flexible piezoelectric composites’;

<i>Category Code</i>	<i>Item Description</i>
	<p>d. Lead-magnesium-niobate/lead-titanate (i.e. $\text{Pb}(\text{Mg}_{1/3}\text{Nb}_{2/3})\text{O}_3$-$\text{PbTiO}_3$, or PMN-PT) piezoelectric single crystals grown from solid solution; <u>or</u></p> <p>e. Lead-indium-niobate/lead-magnesium-niobate/lead-titanate (i.e. $\text{Pb}(\text{In}_{1/2}\text{Nb}_{1/2})\text{O}_3$-$\text{Pb}(\text{Mg}_{1/3}\text{Nb}_{2/3})\text{O}_3$-$\text{PbTiO}_3$, or PIN-PMN-PT) piezoelectric single crystals grown from solid solution;</p> <p>4. A 'hydrophone sensitivity' better than -180 dB at any depth with no acceleration compensation;</p> <p>5. Designed to operate at depths exceeding 35 m with acceleration compensation; <u>or</u></p> <p>6. Designed for operation at depths exceeding 1,000 m;</p> <p><u>Technical Notes</u></p> <p>1. 'Piezoelectric polymer film' sensing elements consist of polarised polymer film that is stretched over and attached to a supporting frame or spool (mandrel).</p> <p>2. 'Flexible piezoelectric composite' sensing elements consist of piezoelectric ceramic particles or fibres combined with an electrically insulating, acoustically transparent rubber, polymer or epoxy compound, where the compound is an integral part of the sensing elements.</p>

Category Code	Item Description
	<p data-bbox="692 454 1267 853">3. 'Hydrophone sensitivity' is defined as twenty times the logarithm to the base 10 of the ratio of rms output voltage to a 1 V rms reference, when the hydrophone sensor, without a pre-amplifier, is placed in a plane wave acoustic field with an rms pressure of 1 μPa. For example, a hydrophone of -160 dB (reference 1 V per μPa) would yield an output voltage of 10^{-8} V in such a field, while one of -180 dB sensitivity would yield only 10^{-9} V output. Thus, -160 dB is better than -180 dB.</p> <p data-bbox="628 875 1267 936">b. Towed acoustic hydrophone arrays having any of the following characteristics:</p> <p data-bbox="692 958 874 987"><u>Technical Note</u></p> <p data-bbox="692 999 1267 1093"><i>Hydrophone arrays consist of a number of hydrophones providing multiple acoustic output channels.</i></p> <ol data-bbox="692 1115 1267 1330" style="list-style-type: none"> <li data-bbox="692 1115 1267 1245">1. Hydrophone group spacing of less than 12.5 m or 'able to be modified' to have hydrophone group spacing of less than 12.5 m; <li data-bbox="692 1267 1267 1330">2. Designed or 'able to be modified' to operate at depths exceeding 35 m; <p data-bbox="756 1352 938 1382"><u>Technical Note</u></p> <p data-bbox="756 1393 1267 1758"><i>'Able to be modified' in Category Codes 6A001.a.2.b.1. and 2. means having provisions to allow a change of the wiring or interconnections to alter hydrophone group spacing or operating depth limits. These provisions are: spare wiring exceeding 10% of the number of wires, hydrophone group spacing adjustment blocks or internal depth limiting devices that are adjustable or that control more than one hydrophone group.</i></p>

<i>Category Code</i>	<i>Item Description</i>
	<ol style="list-style-type: none"> 3. Heading sensors specified in Category Code 6A001.a.2.d.; 4. Longitudinally reinforced array hoses; 5. An assembled array of less than 40 mm in diameter; 6. Not used; 7. Hydrophone characteristics specified in Category Code 6A001.a.2.a.; <u>or</u> 8. Accelerometer-based hydro-acoustic sensors specified in Category Code 6A001.a.2.g.; <p>c. Processing equipment, specially designed for towed acoustic hydrophone arrays, having “user-accessible programmability” and time or frequency domain processing and correlation, including spectral analysis, digital filtering and beamforming using Fast Fourier or other transforms or processes;</p> <p>d. Heading sensors having all of the following characteristics:</p> <ol style="list-style-type: none"> 1. An accuracy of better than 0.5°; <u>and</u> 2. Designed to operate at depths exceeding 35 m or having an adjustable or removable depth sensing device in order to operate at depths exceeding 35 m; <p>e. Bottom or bay-cable hydrophone arrays, having any of the following characteristics:</p> <ol style="list-style-type: none"> 1. Incorporating hydrophones specified in Category Code 6A001.a.2.a.;

<i>Category Code</i>	<i>Item Description</i>
	<p>2. Incorporating multiplexed hydrophone group signal modules having all of the following characteristics:</p> <ul style="list-style-type: none"> a. Designed to operate at depths exceeding 35 m or having an adjustable or removable depth sensing device in order to operate at depths exceeding 35 m; <u>and</u> b. Capable of being operationally interchanged with towed acoustic hydrophone array modules; <u>or</u> <p>3. Incorporating accelerometer-based hydro-acoustic sensors specified in Category Code 6A001.a.2.g.;</p> <p>f. Processing equipment, specially designed for bottom or bay cable systems, having “user-accessible programmability” and time or frequency domain processing and correlation, including spectral analysis, digital filtering and beamforming using Fast Fourier or other transforms or processes;</p> <p>g. Accelerometer-based hydro-acoustic sensors having all of the following characteristics:</p> <ul style="list-style-type: none"> 1. Composed of three accelerometers arranged along three distinct axes; 2. Having an overall ‘acceleration sensitivity’ better than 48 dB (reference 1,000 mV rms per 1 g); 3. Designed to operate at depths greater than 35 m; <u>and</u> 4. Operating frequency below 20 kHz; <p><u>Note</u> <i>Category Code 6A001.a.2.g. does not include particle velocity sensors or geophones.</i></p>

<i>Category Code</i>	<i>Item Description</i>
	<p data-bbox="692 454 887 488"><u>Technical Notes</u></p> <ol data-bbox="692 499 1267 813" style="list-style-type: none"> <li data-bbox="692 499 1267 566">1. Accelerometer-based hydro-acoustic sensors are also known as vector sensors. <li data-bbox="692 577 1267 813">2. 'Acceleration sensitivity' is defined as twenty times the logarithm to the base 10 of the ratio of rms output voltage to a 1 V rms reference, when the hydro-acoustic sensor, without a preamplifier, is placed in a plane wave acoustic field with a rms acceleration of 1 g (i.e. 9.81 m/s²). <p data-bbox="544 835 608 869"><u>Note</u></p> <p data-bbox="544 880 1267 1014">Category Code 6A001.a.2. also includes receiving equipment, whether or not related in normal application to separate active equipment, and specially designed components therefor.</p> <ol data-bbox="480 1025 1267 1462" style="list-style-type: none"> <li data-bbox="480 1025 1267 1126">b. Correlation-velocity and Doppler-velocity sonar log equipment, designed to measure the horizontal speed of the equipment carrier relative to the seabed, as follows: <ol data-bbox="544 1149 1267 1462" style="list-style-type: none"> <li data-bbox="544 1149 1267 1216">1. Correlation-velocity sonar log equipment having any of the following characteristics: <ol data-bbox="624 1227 1267 1373" style="list-style-type: none"> <li data-bbox="624 1227 1267 1294">a. Designed to operate at distances between the carrier and the seabed exceeding 500 m; <u>or</u> <li data-bbox="624 1305 1267 1373">b. Having speed "accuracy" better than 1% of speed; <li data-bbox="544 1395 1267 1462">2. Doppler-velocity sonar log equipment having speed "accuracy" better than 1% of speed; <p data-bbox="544 1485 624 1518"><u>Note 1</u></p> <p data-bbox="544 1529 1267 1585">Category Code 6A001.b. does not include depth sounders limited to any of the following:</p> <ol data-bbox="544 1597 1267 1762" style="list-style-type: none"> <li data-bbox="544 1597 1267 1641">a. Measuring the depth of water; <li data-bbox="544 1653 1267 1720">b. Measuring the distance of submerged or buried objects; <u>or</u> <li data-bbox="544 1731 1267 1762">c. Fish finding.

<i>Category Code</i>	<i>Item Description</i>
	<p><u>Note 2</u> <i>Category Code 6A001.b. does not include equipment specially designed for installation on surface vessels.</i></p> <p>c. Not used.</p>
6A002	<p>Optical sensors or equipment and components therefor, as follows:</p> <p><u>N.B.</u> <i>See also Category Code 6A102.</i></p> <p>a. Optical detectors as follows:</p> <p>1. “Space-qualified” solid-state detectors as follows:</p> <p><u>Note</u> <i>For the purpose of Category Code 6A002.a.1., solid-state detectors include “focal plane arrays”.</i></p> <p>a. “Space-qualified” solid-state detectors having all of the following characteristics:</p> <ol style="list-style-type: none"> 1. A peak response in the wavelength range exceeding 10 nm but not exceeding 300 nm; <u>and</u> 2. A response of less than 0.1% relative to the peak response at a wavelength exceeding 400 nm; <p>b. “Space-qualified” solid-state detectors having all of the following characteristics:</p> <ol style="list-style-type: none"> 1. A peak response in the wavelength range exceeding 900 nm but not exceeding 1,200 nm; <u>and</u> 2. A response “time constant” of 95 ns or less; <p>c. “Space-qualified” solid-state detectors having a peak response in the wavelength range exceeding 1,200 nm but not exceeding 30,000 nm;</p>

Category Code	Item Description
	<p>d. "Space-qualified" "focal plane arrays" having more than 2,048 elements per array and having a peak response in the wavelength range exceeding 300 nm but not exceeding 900 nm;</p> <p>2. Image intensifier tubes and specially designed components therefor, as follows:</p> <p><u>Note</u></p> <p><i>Category Code 6A002.a.2. does not include non-imaging photomultiplier tubes having an electron sensing device in the vacuum space limited solely to any of the following:</i></p> <p>a. <i>A single metal anode; <u>or</u></i></p> <p>b. <i>Metal anodes with a centre-to-centre spacing greater than 500 μm.</i></p> <p><u>Technical Note</u></p> <p><i>'Charge multiplication' is a form of electronic image amplification and is defined as the generation of charge carriers as a result of an impact ionisation gain process. 'Charge multiplication' sensors may take the form of an image intensifier tube, solid state detector or "focal plane array".</i></p> <p>a. Image intensifier tubes having all of the following characteristics:</p> <ol style="list-style-type: none"> 1. A peak response in the wavelength range exceeding 400 nm but not exceeding 1,050 nm; 2. Electron image amplification using any of the following: <ol style="list-style-type: none"> a. A microchannel plate with a hole pitch (centre-to-centre spacing) of 12 μm or less; <u>or</u> b. An electron sensing device with a non-binned pixel pitch of 500 μm or less, specially designed or modified to achieve 'charge multiplication' other than by a microchannel plate; <u>and</u>

<i>Category Code</i>	<i>Item Description</i>
	<ul style="list-style-type: none"> 3. Any of the following photocathodes: <ul style="list-style-type: none"> a. Multialkali photocathodes (e.g. S-20 and S-25) having a luminous sensitivity exceeding 350 $\mu\text{A}/\text{lm}$; b. GaAs or GaInAs photocathodes; <u>or</u> c. Other “III/V compound” semiconductor photocathodes having a maximum “radiant sensitivity” exceeding 10 mA/W; b. Image intensifier tubes having all of the following characteristics: <ul style="list-style-type: none"> 1. A peak response in the wavelength range exceeding 1,050 nm but not exceeding 1,800 nm; 2. Electron image amplification using any of the following: <ul style="list-style-type: none"> a. A microchannel plate with a hole pitch (centre-to-centre spacing) of 12 μm or less; <u>or</u> b. An electron sensing device with a non-binned pixel pitch of 500 μm or less, specially designed or modified to achieve ‘charge multiplication’ other than by a microchannel plate; <u>and</u> 3. “III/V compound” semiconductor (e.g. GaAs or GaInAs) photocathodes and transferred electron photocathodes, having a maximum “radiant sensitivity” exceeding 15 mA/W; c. Specially designed components as follows: <ul style="list-style-type: none"> 1. Microchannel plates having a hole pitch (centre-to-centre spacing) of 12 μm or less;

<i>Category Code</i>	<i>Item Description</i>
	<p data-bbox="692 454 1272 618">2. An electron sensing device with a non-binned pixel pitch of 500 μm or less, specially designed or modified to achieve ‘charge multiplication’ other than by a microchannel plate;</p> <p data-bbox="692 636 1272 734">3. “III/V compound” semiconductor (e.g. GaAs or GaInAs) photocathodes and transferred electron photocathodes;</p> <p data-bbox="756 757 1272 958"><u>Note</u> Category Code 6A002.a.2.c.3. does not include compound semiconductor photocathodes designed to achieve a maximum “radiant sensitivity” of any of the following:</p> <p data-bbox="756 981 1272 1115">a. 10 mA/W or less at the peak response in the wavelength range exceeding 400 nm but not exceeding 1,050 nm; <u>or</u></p> <p data-bbox="756 1133 1272 1267">b. 15 mA/W or less at the peak response in the wavelength range exceeding 1,050 nm but not exceeding 1,800 nm.</p> <p data-bbox="544 1285 1272 1317">3. Non-“space-qualified” “focal plane arrays” as follows:</p> <p data-bbox="608 1335 1272 1469"><u>N.B.</u> ‘Microbolometer’ non-“space-qualified” “focal plane arrays” are only specified in Category Code 6A002.a.3.f.</p> <p data-bbox="608 1491 1272 1603"><u>Technical Note</u> Linear or two-dimensional multi-element detector arrays are referred to as “focal plane arrays”.</p> <p data-bbox="608 1621 1272 1733"><u>Note 1</u> Category Code 6A002.a.3. includes photoconductive arrays and photovoltaic arrays.</p> <p data-bbox="608 1751 1272 1814"><u>Note 2</u> Category Code 6A002.a.3. does not include:</p>

Category Code	Item Description
	<p>a. Multi-element (not to exceed 16 elements) encapsulated photoconductive cells using either lead sulphide or lead selenide;</p> <p>b. Pyroelectric detectors using any of the following:</p> <ol style="list-style-type: none"> 1. Triglycine sulphate and variants; 2. Lead-lanthanum-zirconium titanate and variants; 3. Lithium tantalate; 4. Polyvinylidene fluoride and variants; <u>or</u> 5. Strontium barium niobate and variants; <p>c. "Focal plane arrays" specially designed or modified to achieve 'charge multiplication' and limited by design to have a maximum "radiant sensitivity" of 10 mA/W or less for wavelengths exceeding 760 nm, having all of the following characteristics:</p> <ol style="list-style-type: none"> 1. Incorporating a response limiting mechanism designed not to be removed or modified; <u>and</u> 2. Any of the following characteristics: <ol style="list-style-type: none"> a. The response limiting mechanism is integral to or combined with the detector element; <u>or</u> b. The "focal plane array" is only operable with the response limiting mechanism in place. <p><u>Technical Note</u> A response limiting mechanism integral to the detector element is designed not to be removed or modified without rendering the detector inoperable.</p> <p>d. Thermopile arrays having less than 5,130 elements.</p>

<i>Category Code</i>	<i>Item Description</i>
	<p data-bbox="692 454 874 488"><u>Technical Note</u></p> <p data-bbox="692 495 1267 730"><i>‘Charge multiplication’ is a form of electronic image amplification and is defined as the generation of charge carriers as a result of an impact ionisation gain process. ‘Charge multiplication’ sensors may take the form of an image intensifier tube, solid state detector or “focal plane array”.</i></p> <ol style="list-style-type: none"> <li data-bbox="628 745 1267 813">a. Non-“space-qualified” “focal plane arrays” having all of the following characteristics: <ol style="list-style-type: none"> <li data-bbox="692 831 1267 931">1. Individual elements with a peak response within the wavelength range exceeding 900 nm but not exceeding 1,050 nm; <u>and</u> <li data-bbox="692 949 1267 1211">2. Any of the following characteristics: <ol style="list-style-type: none"> <li data-bbox="756 999 1267 1066">a. A response “time constant” of less than 0.5 ns; <u>or</u> <li data-bbox="756 1084 1267 1211">b. Specially designed or modified to achieve ‘charge multiplication’ and having a maximum “radiant sensitivity” exceeding 10 mA/W; <li data-bbox="628 1234 1267 1301">b. Non-“space-qualified” “focal plane arrays” having all of the following characteristics: <ol style="list-style-type: none"> <li data-bbox="692 1319 1267 1447">1. Have individual elements with a peak response in the wavelength range exceeding 1,050 nm but not exceeding 1,200 nm; <u>and</u> <li data-bbox="692 1464 1267 1729">2. Have any of the following characteristics: <ol style="list-style-type: none"> <li data-bbox="756 1514 1267 1581">a. A response “time constant” of 95 ns or less; <u>or</u> <li data-bbox="756 1599 1267 1729">b. Specially designed or modified to achieve ‘charge multiplication’ and having a maximum “radiant sensitivity” exceeding 10 mA/W;

<i>Category Code</i>	<i>Item Description</i>
	<p>c. Non-“space-qualified” non-linear (2-dimensional) “focal plane arrays” having individual elements with a peak response in the wavelength range exceeding 1,200 nm but not exceeding 30,000 nm;</p> <p><u><i>N.B.</i></u> <i>Silicon and other material based ‘microbolometer’ non-“space-qualified” “focal plane arrays” are only specified in Category Code 6A002.a.3.f.</i></p> <p>d. Non-“space-qualified” linear (1-dimensional) “focal plane arrays” having all of the following characteristics:</p> <ol style="list-style-type: none"> 1. Have individual elements with a peak response in the wavelength range exceeding 1,200 nm but not exceeding 3,000 nm; <u>and</u> 2. Any of the following characteristics: <ol style="list-style-type: none"> a. A ratio of ‘scan direction’ dimension of the detector element to the ‘cross-scan direction’ dimension of the detector element of less than 3.8; <u>or</u> b. Signal processing in the detector elements; <p><u><i>Note</i></u> <i>Category Code 6A002.a.3.d. does not include “focal plane arrays” (not to exceed 32 elements) having detector elements limited solely to germanium material.</i></p> <p><u><i>Technical Note</i></u> <i>For the purpose of Category Code 6A002.a.3.d., ‘cross-scan direction’ is defined as the axis parallel to the linear array of detector elements and the ‘scan direction’ is defined as the axis perpendicular to the linear array of detector elements.</i></p>

<i>Category Code</i>	<i>Item Description</i>
	<p>e. Non-“space-qualified” linear (1-dimensional) “focal plane arrays” having individual elements with a peak response in the wavelength range exceeding 3,000 nm but not exceeding 30,000 nm;</p> <p>f. Non-“space-qualified” non-linear (2-dimensional) infrared “focal plane arrays” based on ‘microbolometer’ material, having individual elements with an unfiltered response in the wavelength range equal to or exceeding 8,000 nm but not exceeding 14,000 nm;</p> <p><i>Technical Note</i> <i>For the purpose of Category Code 6A002.a.3.f., ‘microbolometer’ is defined as a thermal imaging detector that, as a result of a temperature change in the detector caused by the absorption of infrared radiation, is used to generate any usable signal.</i></p> <p>g. Non-“space-qualified” “focal plane arrays” having all of the following characteristics:</p> <ol style="list-style-type: none"> 1. Have individual detector elements with a peak response in the wavelength range exceeding 400 nm but not exceeding 900 nm; 2. Specially designed or modified to achieve ‘charge multiplication’ and having a maximum “radiant sensitivity” exceeding 10 mA/W for wavelengths exceeding 760 nm; <u>and</u> 3. Greater than 32 elements; <p>b. “Monospectral imaging sensors” and “multispectral imaging sensors”, designed for remote sensing applications and having any of the following characteristics:</p> <ol style="list-style-type: none"> 1. An Instantaneous-Field-Of-View (IFOV) of less than 200 μrad (microradians); <u>or</u>

<i>Category Code</i>	<i>Item Description</i>
	<p data-bbox="544 454 1268 853"> 2. Specified for operation in the wavelength range exceeding 400 nm but not exceeding 30,000 nm and having all of the following characteristics: <ol style="list-style-type: none"> <li data-bbox="632 568 1268 636">a. Providing output imaging data in digital format; <u>and</u> <li data-bbox="632 656 1268 853">b. Having any of the following characteristics: <ol style="list-style-type: none"> <li data-bbox="695 703 1011 736">1. “Space-qualified”; <u>or</u> <li data-bbox="695 757 1268 853">2. Designed for airborne operation, using other than silicon detectors, and having an IFOV of less than 2.5 mrad (milliradians); </p> <p data-bbox="544 875 1268 1077"> <u>Note</u> <i>Category Code 6A002.b.1. does not include “monospectral imaging sensors” with a peak response in the wavelength range exceeding 300 nm but not exceeding 900 nm and only incorporating any of the following non-“space-qualified” detectors or non-“space-qualified” “focal plane arrays”:</i> <ol style="list-style-type: none"> <li data-bbox="544 1099 1268 1167">a. <i>Charged Coupled Devices (CCD) not designed or modified to achieve ‘charge multiplication’; <u>or</u></i> <li data-bbox="544 1189 1268 1279">b. <i>Complementary Metal Oxide Semiconductor (CMOS) devices not designed or modified to achieve ‘charge multiplication’.</i> </p> <p data-bbox="480 1301 1268 1603"> c. ‘Direct view’ imaging equipment incorporating any of the following: <ol style="list-style-type: none"> <li data-bbox="544 1379 1268 1447">1. Image intensifier tubes specified in Category Code 6A002.a.2.a. or 6A002.a.2.b.; <li data-bbox="544 1469 1268 1536">2. “Focal plane arrays” specified in Category Code 6A002.a.3.; <u>or</u> <li data-bbox="544 1559 1268 1603">3. Solid state detectors specified in Category Code 6A002.a.1.; </p> <p data-bbox="544 1626 1268 1836"> <u>Technical Note</u> <i>‘Direct view’ refers to imaging equipment that presents a visual image to a human observer without converting the image into an electronic signal for television display, and that cannot record or store the image photographically, electronically or by any other means.</i> </p>

<i>Category Code</i>	<i>Item Description</i>
	<p data-bbox="544 454 603 483"><u>Note</u></p> <p data-bbox="544 495 1260 591"><i>Category Code 6A002.c. does not include equipment as follows, when incorporating other than GaAs or GaInAs photocathodes:</i></p> <ul style="list-style-type: none"> <li data-bbox="544 611 1260 674"><i>a. Industrial or civilian intrusion alarm, traffic or industrial movement control or counting systems;</i> <li data-bbox="544 694 847 723"><i>b. Medical equipment;</i> <li data-bbox="544 743 1260 806"><i>c. Industrial equipment used for inspection, sorting or analysis of the properties of materials;</i> <li data-bbox="544 826 1082 855"><i>d. Flame detectors for industrial furnaces;</i> <li data-bbox="544 875 1190 904"><i>e. Equipment specially designed for laboratory use.</i> <p data-bbox="480 925 1246 954">d. Special support components for optical sensors, as follows:</p> <ul style="list-style-type: none"> <li data-bbox="544 974 975 1003">1. “Space-qualified” cryocoolers; <li data-bbox="544 1023 1260 1205">2. Non-“space-qualified” cryocoolers having a cooling source temperature below 218 K (-55°C), as follows: <ul style="list-style-type: none"> <li data-bbox="628 1111 1260 1205">a. Closed cycle type with a specified Mean-Time-To-Failure (MTTF) or Mean-Time-Between-Failures (MTBF), exceeding 2,500 hours; <li data-bbox="628 1225 1260 1319">b. Joule-Thomson (JT) self-regulating minicoolers having bore (outside) diameters of less than 8 mm; <li data-bbox="544 1339 1260 1473">3. Optical sensing fibres specially fabricated either compositionally or structurally, or modified by coating, to be acoustically, thermally, inertially, electromagnetically or nuclear radiation sensitive; <p data-bbox="608 1494 667 1523"><u>Note</u></p> <p data-bbox="608 1534 1260 1630"><i>Category Code 6A002.d.3. does not include encapsulated optical sensing fibres specially designed for bore hole sensing applications.</i></p> <ul style="list-style-type: none"> <li data-bbox="480 1650 659 1680">e. Not used.

<i>Category Code</i>	<i>Item Description</i>
6A003	<p>Cameras, systems or equipment, and components therefor, as follows:</p> <p><u>N.B.</u> See also Category Code 6A203.</p> <p>a. Instrumentation cameras and specially designed components therefor, as follows:</p> <p><u>Note</u> <i>Instrumentation cameras, specified in Category Codes 6A003.a.3. to 6A003.a.5., with modular structures should be evaluated by their maximum capability, using plug-ins available according to the camera manufacturer's specifications.</i></p> <ol style="list-style-type: none"> 1. High-speed cinema recording cameras using any film format from 8 mm to 16 mm inclusive, in which the film is continuously advanced throughout the recording period, and that are capable of recording at framing rates exceeding 13,150 frames/s; <p><u>Note</u> <i>Category Code 6A003.a.1. does not include cinema recording cameras designed for civil purposes.</i></p> <ol style="list-style-type: none"> 2. Mechanical high speed cameras, in which the film does not move, capable of recording at rates exceeding 1,000,000 frames/s for the full framing height of 35 mm film, or at proportionately higher rates for lesser frame heights, or at proportionately lower rates for greater frame heights; 3. Mechanical or electronic streak cameras, as follows: <ol style="list-style-type: none"> a. Mechanical streak cameras having writing speeds exceeding 10 mm/μs; b. Electronic streak cameras having temporal resolution better than 50 ns; 4. Electronic framing cameras having a speed exceeding 1,000,000 frames/s;

<i>Category Code</i>	<i>Item Description</i>
	<p>5. Electronic cameras having all of the following characteristics:</p> <ol style="list-style-type: none"> a. An electronic shutter speed (gating capability) of less than 1 μs per full frame; <u>and</u> b. A read out time allowing a framing rate of more than 125 full frames/s; <p>6. Plug-ins having all of the following characteristics:</p> <ol style="list-style-type: none"> a. Specially designed for instrumentation cameras which have modular structures and which are specified in Category Code 6A003.a.; <u>and</u> b. Enabling these cameras to meet the characteristics specified in Category Code 6A003.a.3., 6A003.a.4. or 6A003.a.5., according to the manufacturer's specifications; <p>b. Imaging cameras as follows:</p> <p><u>Note</u> <i>Category Code 6A003.b. does not include television or video cameras, specially designed for television broadcasting.</i></p> <ol style="list-style-type: none"> 1. Video cameras incorporating solid state sensors, having a peak response in the wavelength range exceeding 10 nm, but not exceeding 30,000 nm and having all of the following characteristics: <ol style="list-style-type: none"> a. Having any of the following characteristics: <ol style="list-style-type: none"> 1. More than 4×10^6 "active pixels" per solid state array for monochrome (black and white) cameras; 2. More than 4×10^6 "active pixels" per solid state array for colour cameras incorporating three solid state arrays; <u>or</u> 3. More than 12×10^6 "active pixels" for solid state array colour cameras incorporating one solid state array; <u>and</u>

<i>Category Code</i>	<i>Item Description</i>
	<p data-bbox="632 454 1214 488">b. Having any of the following characteristics:</p> <ol data-bbox="695 506 1267 734" style="list-style-type: none"> <li data-bbox="695 506 1267 568">1. Optical mirrors specified in Category Code 6A004.a.; <li data-bbox="695 586 1267 649">2. Optical control equipment specified in Category Code 6A004.d.; <u>or</u> <li data-bbox="695 667 1267 734">3. The capability for annotating internally generated ‘camera tracking data’; <p data-bbox="608 757 802 790"><u>Technical Notes</u></p> <ol data-bbox="544 801 1267 1518" style="list-style-type: none"> <li data-bbox="632 801 1267 936">1. <i>For the purpose of this entry, digital video cameras should be evaluated by the maximum number of “active pixels” used for capturing moving images.</i> <li data-bbox="632 954 1267 1218">2. <i>For the purpose of this entry, ‘camera tracking data’ is the information necessary to define camera line of sight orientation with respect to the earth. This includes: 1) the horizontal angle the camera line of sight makes with respect to the earth’s magnetic field direction; and 2) the vertical angle between the camera line of sight and the earth’s horizon.</i> <li data-bbox="544 1236 1267 1518">2. Scanning cameras and scanning camera systems, having all of the following characteristics: <ol data-bbox="632 1326 1267 1518" style="list-style-type: none"> <li data-bbox="632 1326 1267 1388">a. A peak response in the wavelength range exceeding 10 nm, but not exceeding 30,000 nm; <li data-bbox="632 1406 1267 1469">b. Linear detector arrays with more than 8,192 elements per array; <u>and</u> <li data-bbox="632 1487 1267 1518">c. Mechanical scanning in one direction; <p data-bbox="608 1541 667 1574"><u>Note</u></p> <p data-bbox="608 1581 1267 1682"><i>Category Code 6A003.b.2. does not include scanning cameras and scanning camera systems, specially designed for any of the following:</i></p> <ol data-bbox="632 1697 1110 1727" style="list-style-type: none"> <li data-bbox="632 1697 1110 1727">a. <i>Industrial or civilian photocopiers;</i>

Category Code	Item Description
	<p data-bbox="632 454 1268 622">b. <i>Image scanners specially designed for civil, stationary, close proximity scanning applications (e.g. reproduction of images or print contained in documents, artwork or photographs); <u>or</u></i></p> <p data-bbox="632 640 927 674">c. <i>Medical equipment.</i></p> <p data-bbox="544 689 1268 786">3. <i>Imaging cameras incorporating image intensifier tubes specified in Category Code 6A002.a.2.a. or 6A002.a.2.b.;</i></p> <p data-bbox="544 804 1268 1122">4. <i>Imaging cameras incorporating “focal plane arrays” having any of the following characteristics:</i></p> <p data-bbox="632 891 1268 958">a. <i>Incorporating “focal plane arrays” specified in Category Codes 6A002.a.3.a. to 6A002.a.3.e.;</i></p> <p data-bbox="632 976 1268 1043">b. <i>Incorporating “focal plane arrays” specified in Category Code 6A002.a.3.f.; <u>or</u></i></p> <p data-bbox="632 1061 1268 1128">c. <i>Incorporating “focal plane arrays” specified in Category Code 6A002.a.3.g.;</i></p> <p data-bbox="608 1144 687 1178"><u>Note 1</u></p> <p data-bbox="608 1182 1268 1384"><i>Imaging cameras specified in Category Code 6A003.b.4. include “focal plane arrays” combined with sufficient “signal processing” electronics, beyond the read out integrated circuit, to enable as a minimum the output of an analogue or digital signal once power is supplied.</i></p> <p data-bbox="608 1402 687 1435"><u>Note 2</u></p> <p data-bbox="608 1440 1268 1608"><i>Category Code 6A003.b.4.a. does not include imaging cameras incorporating linear “focal plane arrays” with 12 elements or fewer, not employing time-delay-and-integration within the element and designed for any of the following:</i></p> <p data-bbox="632 1626 1268 1720">a. <i>Industrial or civilian intrusion alarm, traffic or industrial movement control or counting systems;</i></p> <p data-bbox="632 1738 1268 1839">b. <i>Industrial equipment used for inspection or monitoring of heat flows in buildings, equipment or industrial processes;</i></p>

Category Code	Item Description
	<p data-bbox="632 454 1267 551">c. Industrial equipment used for inspection, sorting or analysis of the properties of materials;</p> <p data-bbox="632 568 1267 633">d. Equipment specially designed for laboratory use; <u>or</u></p> <p data-bbox="632 651 927 685">e. Medical equipment.</p> <p data-bbox="608 703 687 736"><u>Note 3</u></p> <p data-bbox="608 745 1267 810">Category Code 6A003.b.4.b. does not include imaging cameras having any of the following characteristics:</p> <p data-bbox="632 828 1267 893">a. A maximum frame rate equal to or less than 9 Hz;</p> <p data-bbox="632 911 1206 945">b. Having all of the following characteristics:</p> <ol data-bbox="695 960 1267 1541" style="list-style-type: none"> <li data-bbox="695 960 1267 1057">1. Having a minimum horizontal or vertical 'Instantaneous-Field-of-View (IFOV)' of at least 10 mrad/pixel (milliradians/pixel); <li data-bbox="695 1075 1267 1140">2. Incorporating a fixed focal-length lens that is not designed to be removed; <li data-bbox="695 1158 1267 1223">3. Not incorporating a 'direct view' display; <u>and</u> <li data-bbox="695 1240 1267 1541">4. Having any of the following characteristics: <ol data-bbox="754 1328 1267 1541" style="list-style-type: none"> <li data-bbox="754 1328 1267 1424">a. No facility to obtain a viewable image of the detected field-of-view; <u>or</u> <li data-bbox="754 1442 1267 1541">b. The camera is designed for a single kind of application and designed not to be user modified; <u>or</u> <p data-bbox="632 1559 1267 1691">c. The camera is specially designed for installation into a civilian passenger land vehicle and has all of the following characteristics:</p> <ol data-bbox="695 1709 1267 1841" style="list-style-type: none"> <li data-bbox="695 1709 1267 1841">1. The placement and configuration of the camera within the vehicle are solely to assist the driver in the safe operation of the vehicle;

Category Code	Item Description
	<p data-bbox="694 454 1272 521">2. <i>Is only operable when installed in any of the following:</i></p> <p data-bbox="758 539 1272 674">a. <i>The civilian passenger land vehicle for which it was intended and the vehicle weighs less than 4,500 kg (gross vehicle weight); <u>or</u></i></p> <p data-bbox="758 689 1272 757">b. <i>A specially designed, authorised maintenance test facility; <u>and</u></i></p> <p data-bbox="694 772 1272 907">3. <i>Incorporates an active mechanism that forces the camera not to function when it is removed from the vehicle for which it was intended.</i></p> <p data-bbox="694 922 890 956"><u>Technical Notes</u></p> <p data-bbox="694 972 1272 1218">1. <i>'Instantaneous-Field-of-View (IFOV)' specified in Category Code 6A003.b.4. Note 3.b. is the lesser figure of the 'Horizontal IFOV' or the 'Vertical IFOV'. 'Horizontal IFOV' = horizontal Field of View (FOV) / number of horizontal detector elements 'Vertical IFOV' = vertical Field of View (FOV) / number of vertical detector elements</i></p> <p data-bbox="694 1352 1272 1585">2. <i>'Direct view' in Category Code 6A003.b.4. Note 3.b. refers to an imaging camera operating in the infrared spectrum that presents a visual image to a human observer using a near-to-eye micro display incorporating any light-security mechanism.</i></p> <p data-bbox="608 1608 691 1641"><u>Note 4</u></p> <p data-bbox="608 1648 1272 1715"><i>Category Code 6A003.b.4.c. does not include imaging cameras having any of the following characteristics:</i></p>

Category Code	Item Description
	<p>a. <i>Having all of the following characteristics:</i></p> <ol style="list-style-type: none"> 1. <i>Where the camera is specially designed for installation as an integrated component into indoor and wall-plug-operated systems or equipment, limited by design for a single kind of application, as follows:</i> <ol style="list-style-type: none"> a. <i>Industrial process monitoring, quality control, or analysis of the properties of materials;</i> b. <i>Laboratory equipment specially designed for scientific research;</i> c. <i>Medical equipment;</i> d. <i>Financial fraud detection equipment;</i> <i><u>and</u></i> 2. <i>Is only operable when installed in any of the following:</i> <ol style="list-style-type: none"> a. <i>The system(s) or equipment for which it was intended; <u>or</u></i> b. <i>A specially designed, authorised maintenance facility; <u>and</u></i> 3. <i>Incorporates an active mechanism that forces the camera not to function when it is removed from the system(s) or equipment for which it was intended;</i> <p>b. <i>Where the camera is specially designed for installation into a civilian passenger land vehicle or passenger and vehicle ferries, and has all of the following characteristics:</i></p> <ol style="list-style-type: none"> 1. <i>The placement and configuration of the camera within the vehicle or ferry is solely to assist the driver or operator in the safe operation of the vehicle or ferry;</i>

Category Code	Item Description
	<ol style="list-style-type: none"> 2. <i>Is only operable when installed in any of the following:</i> <ol style="list-style-type: none"> a. <i>The civilian passenger land vehicle for which it was intended and the vehicle weighs less than 4,500 kg (gross vehicle weight);</i> b. <i>The passenger and vehicle ferry for which it was intended and having a length overall (LOA) 65 m or greater; <u>or</u></i> c. <i>A specially designed, authorised maintenance test facility; <u>and</u></i> 3. <i>Incorporates an active mechanism that forces the camera not to function when it is removed from the vehicle for which it was intended;</i> c. <i>Limited by design to have a maximum “radiant sensitivity” of 10 mA/W or less for wavelengths exceeding 760 nm, and having all of the following characteristics:</i> <ol style="list-style-type: none"> 1. <i>Incorporating a response limiting mechanism designed not to be removed or modified;</i> 2. <i>Incorporates an active mechanism that forces the camera not to function when the response limiting mechanism is removed; <u>and</u></i> 3. <i>Not specially designed or modified for underwater use; <u>or</u></i> d. <i>Having all of the following characteristics:</i> <ol style="list-style-type: none"> 1. <i>Not incorporating a ‘direct view’ or electronic image display;</i> 2. <i>Has no facility to output a viewable image of the detected field of view;</i>

Category Code	Item Description
	<ol style="list-style-type: none"> 3. The “focal plane array” is only operable when installed in the camera for which it was intended; <u>and</u> 4. The “focal plane array” incorporates an active mechanism that forces it to be permanently inoperable when removed from the camera for which it was intended. 5. Imaging cameras incorporating solid-state detectors specified in Category Code 6A002.a.1.
6A004	<p>Optical equipment and components, as follows:</p> <p>a. Optical mirrors (reflectors) as follows:</p> <p><u>Technical Note</u> <i>For the purpose of Category Code 6A004.a., Laser Induced Damage Threshold (LIDT) is measured according to ISO 21254-1:2011.</i></p> <p><u>N.B.</u> <i>For optical mirrors specially designed for lithography equipment, see Category Code 3B001.</i></p> <ol style="list-style-type: none"> 1. “Deformable mirrors” having an active optical aperture greater than 10 mm and having any of the following characteristics, and specially designed components therefor: <ol style="list-style-type: none"> a. Having all of the following characteristics: <ol style="list-style-type: none"> 1. A mechanical resonant frequency of 750 Hz or more; <u>and</u> 2. Have more than 200 actuators; <u>or</u> b. A Laser Induced Damage Threshold (LIDT) being any of the following: <ol style="list-style-type: none"> 1. Greater than 1 kW/cm² using a “CW laser”; <u>or</u> 2. Greater than 2 J/cm² using 20 ns “laser” pulses at 20 Hz repetition rate;

Category Code	Item Description
	<p>2. Lightweight monolithic mirrors having an average “equivalent density” of less than 30 kg/m² and a total mass exceeding 10 kg;</p> <p><i>Note</i> <i>Category Code 6A004.a.2. does not include mirrors specially designed to direct solar radiation for terrestrial heliostat installations.</i></p> <p>3. Lightweight “composite” or foam mirror structures having an average “equivalent density” of less than 30 kg/m² and a total mass exceeding 2 kg;</p> <p><i>Note</i> <i>Category Code 6A004.a.3. does not include mirrors specially designed to direct solar radiation for terrestrial heliostat installations.</i></p> <p>4. Mirrors specially designed for beam steering mirror stages specified in Category Code 6A004.d.2.a. with a flatness of $\lambda/10$ or better (λ is equal to 633 nm) and having any of the following characteristics:</p> <ul style="list-style-type: none"> a. Diameter or major axis length greater than or equal to 100 mm; <u>or</u> b. Having all of the following characteristics: <ul style="list-style-type: none"> 1. Diameter or major axis length greater than 50 mm but less than 100 mm; <u>and</u> 2. A Laser Induced Damage Threshold (LIDT) being any of the following: <ul style="list-style-type: none"> a. Greater than 10 kW/cm² using a “CW laser”; <u>or</u> b. Greater than 20 J/cm² using 20 ns “laser” pulses at 20 Hz repetition rate; <p>b. Optical components made from zinc selenide (ZnSe) or zinc sulphide (ZnS) with transmission in the wavelength range exceeding 3,000 nm but not exceeding 25,000 nm and having any of the following characteristics:</p> <ul style="list-style-type: none"> 1. Exceeding 100 cm³ in volume; <u>or</u>

<i>Category Code</i>	<i>Item Description</i>
	<ol style="list-style-type: none"> <li data-bbox="544 454 1272 521">2. Exceeding 80 mm in diameter or length of major axis and 20 mm in thickness (depth); <li data-bbox="480 539 1272 600">c. “Space-qualified” components for optical systems, as follows: <ol style="list-style-type: none"> <li data-bbox="544 618 1272 719">1. Components lightweighted to less than 20% “equivalent density” compared with a solid blank of the same aperture and thickness; <li data-bbox="544 736 1272 869">2. Raw substrates, processed substrates having surface coatings (single-layer or multi-layer, metallic or dielectric, conducting, semiconducting or insulating) or having protective films; <li data-bbox="544 887 1272 1019">3. Segments or assemblies of mirrors designed to be assembled in space into an optical system with a collecting aperture equivalent to or larger than a single optic 1 m in diameter; <li data-bbox="544 1037 1272 1137">4. Components manufactured from “composite” materials having a coefficient of linear thermal expansion equal to or less than 5×10^{-6} in any coordinate direction; <li data-bbox="480 1155 1272 1189">d. Optical control equipment as follows: <ol style="list-style-type: none"> <li data-bbox="544 1207 1272 1339">1. Equipment specially designed to maintain the surface figure or orientation of the “space-qualified” components specified in Category Code 6A004.c.1. or 6A004.c.3.; <li data-bbox="544 1357 1272 1854">2. Steering, tracking, stabilisation and resonator alignment equipment as follows: <ol style="list-style-type: none"> <li data-bbox="632 1442 1272 1608">a. Beam steering mirror stages designed to carry mirrors having diameter or major axis length greater than 50 mm and having all of the following characteristics, and specially designed electronic control equipment therefor: <ol style="list-style-type: none"> <li data-bbox="695 1626 1272 1686">1. A maximum angular travel of ± 26 mrad or more; <li data-bbox="695 1704 1272 1765">2. A mechanical resonant frequency of 500 Hz or more; <u>and</u> <li data-bbox="695 1783 1272 1854">3. An angular “accuracy” of 10 μrad (microradians) or less (better);

<i>Category Code</i>	<i>Item Description</i>
	<p>b. Resonator alignment equipment having bandwidths equal to or more than 100 Hz and an “accuracy” of 10 μrad or less (better);</p> <p>3. Gimbals having all of the following characteristics:</p> <p>a. A maximum slew exceeding 5°;</p> <p>b. A bandwidth of 100 Hz or more;</p> <p>c. Angular pointing errors of 200 μrad (microradians) or less; <u>and</u></p> <p>d. Having any of the following characteristics:</p> <p>1. Exceeding 0.15 m but not exceeding 1 m in diameter or major axis length and capable of angular accelerations exceeding 2 rad (radians)/s²; <u>or</u></p> <p>2. Exceeding 1 m in diameter or major axis length and capable of angular accelerations exceeding 0.5 rad (radians)/s²;</p> <p>4. Not used;</p> <p>e. ‘Aspheric optical elements’ having all of the following characteristics:</p> <p>1. Largest dimension of the optical-aperture greater than 400 mm;</p> <p>2. Surface roughness less than 1 nm (rms) for sampling lengths equal to or greater than 1 mm; <u>and</u></p> <p>3. Coefficient of linear thermal expansion’s absolute magnitude less than 3×10^{-6}/K at 25°C.</p> <p><u>Technical Notes</u></p> <p>1. An ‘aspheric optical element’ is any element used in an optical system whose imaging surface or surfaces are designed to depart from the shape of an ideal sphere.</p> <p>2. It is not necessary to evaluate the surface roughness of the optical element against the criteria in Category Code 6A004.e.2. unless the optical element was designed or manufactured with the intent to meet, or exceed the control parameter.</p>

Category Code	Item Description
	<p><u>Note</u> Category Code 6A004.e. does not include ‘aspheric optical elements’ having any of the following characteristics:</p> <ol style="list-style-type: none"> a. Largest optical-aperture dimension less than 1 m and focal length to aperture ratio equal to or greater than 4.5:1; b. Largest optical-aperture dimension equal to or greater than 1 m and focal length to aperture ratio equal to or greater than 7:1; c. Designed as Fresnel, flyeye, stripe, prism or diffractive optical elements; d. Fabricated from borosilicate glass having a coefficient of linear thermal expansion greater than $2.5 \times 10^{-6}/K$ at 25°C; <u>or</u> e. An X-ray optical element having inner mirror capabilities (e.g. tube-type mirrors). <p><u>N.B.</u> For ‘aspheric optical elements’ specially designed for lithography equipment, see Category Code 3B001.</p>
6A005	<p>“Lasers”, other than those specified in Category Code 0B001.g.5. or 0B001.h.6., components and optical equipment, as follows:</p> <p><u>N.B.</u> See also Category Code 6A205.</p> <p><u>Note 1</u> Pulsed “lasers” include those that run in a continuous wave (CW) mode with pulses superimposed.</p> <p><u>Note 2</u> Excimer, semiconductor, chemical, CO, CO₂, and ‘non-repetitive pulsed’ Nd:glass “lasers” are only specified in Category Code 6A005.d.</p> <p><u>Technical Note</u> ‘Non-repetitive pulsed’ refers to “lasers” that produce either a single output pulse or that have a time interval between pulses exceeding one minute.</p>

Category Code	Item Description
	<p><u>Note 3</u> Category Code 6A005 includes fibre “lasers”.</p> <p><u>Note 4</u> The control status of “lasers” incorporating frequency conversion (i.e. wavelength change) by means other than one “laser” pumping another “laser” is determined by applying the control parameters for both the output of the source “laser” and the frequency-converted optical output.</p> <p><u>Note 5</u> Category Code 6A005 does not include “lasers” as follows:</p> <ul style="list-style-type: none"> a. Ruby with output energy below 20 J; b. Nitrogen; c. Krypton. <p><u>Technical Note</u> In Category Code 6A005, ‘Wall-plug efficiency’ is defined as the ratio of “laser” output power (or “average output power”) to total electrical input power required to operate the “laser”, including the power supply/conditioning and thermal conditioning/heat exchanger.</p> <ul style="list-style-type: none"> a. Non-“tunable” continuous wave “(CW) lasers” having any of the following characteristics: <ul style="list-style-type: none"> 1. Output wavelength less than 150 nm, and output power exceeding 1 W; 2. Output wavelength of 150 nm or more but not exceeding 510 nm, and output power exceeding 30 W; <p><u>Note</u> Category Code 6A005.a.2. does not include Argon “lasers” having an output power equal to or less than 50 W.</p> <ul style="list-style-type: none"> 3. Output wavelength exceeding 510 nm but not exceeding 540 nm, and any of the following characteristics: <ul style="list-style-type: none"> a. Single transverse mode output and output power exceeding 50 W; <u>or</u>

<i>Category Code</i>	<i>Item Description</i>
	<p>b. Multiple transverse mode output and output power exceeding 150 W;</p> <p>4. Output wavelength exceeding 540 nm but not exceeding 800 nm, and output power exceeding 30 W;</p> <p>5. Output wavelength exceeding 800 nm but not exceeding 975 nm, and any of the following characteristics:</p> <p>a. Single transverse mode output and output power exceeding 50 W; <u>or</u></p> <p>b. Multiple transverse mode output and output power exceeding 80 W;</p> <p>6. Output wavelength exceeding 975 nm but not exceeding 1,150 nm, and any of the following characteristics:</p> <p>a. Single transverse mode output and output power exceeding 200 W; <u>or</u></p> <p>b. Multiple transverse mode output, and any of the following characteristics:</p> <p>1. ‘Wall-plug efficiency’ exceeding 18% and output power exceeding 500 W; <u>or</u></p> <p>2. Output power exceeding 2 kW;</p> <p><u>Note 1</u></p> <p><i>Category Code 6A005.a.6.b. does not include multiple transverse mode, industrial “lasers” with output power exceeding 2 kW and not exceeding 6 kW with a total mass greater than 1,200 kg. For the purpose of this Note, total mass includes all components required to operate the “laser”, e.g. “laser”, power supply, heat exchanger, but excludes external optics for beam conditioning and/or delivery.</i></p>

Category Code	Item Description
	<p data-bbox="692 454 772 488"><u>Note 2</u></p> <p data-bbox="692 495 1267 595">Category Code 6A005.a.6.b. does not include multiple transverse mode, industrial “lasers” having any of the following characteristics:</p> <ol style="list-style-type: none"> <li data-bbox="692 613 1267 714">a. Output power exceeding 500 W but not exceeding 1 kW, and having all of the following characteristics: <ol style="list-style-type: none"> <li data-bbox="756 730 1267 797">1. Beam Parameter Product (BPP) exceeding 0.7 mm•mrad; <u>and</u> <li data-bbox="756 813 1267 880">2. ‘Brightness’ not exceeding 1,024 W/(mm•mrad)²; <li data-bbox="692 896 1267 996">b. Output power exceeding 1 kW but not exceeding 1.6 kW, and having a BPP exceeding 1.25 mm•mrad; <li data-bbox="692 1012 1267 1113">c. Output power exceeding 1.6 kW but not exceeding 2.5 kW, and having a BPP exceeding 1.7 mm•mrad; <li data-bbox="692 1128 1267 1229">d. Output power exceeding 2.5 kW but not exceeding 3.3 kW, and having a BPP exceeding 2.5 mm•mrad; <li data-bbox="692 1245 1267 1346">e. Output power exceeding 3.3 kW but not exceeding 4 kW, and having a BPP exceeding 3.5 mm•mrad; <li data-bbox="692 1361 1267 1462">f. Output power exceeding 4 kW but not exceeding 5 kW, and having a BPP exceeding 5 mm•mrad; <li data-bbox="692 1478 1267 1579">g. Output power exceeding 5 kW but not exceeding 6 kW, and having a BPP exceeding 7.2 mm•mrad; <li data-bbox="692 1594 1267 1695">h. Output power exceeding 6 kW but not exceeding 8 kW, and having a BPP exceeding 12 mm•mrad; <u>or</u> <li data-bbox="692 1711 1267 1812">i. Output power exceeding 8 kW but not exceeding 10 kW, and having a BPP exceeding 24 mm•mrad.

<i>Category Code</i>	<i>Item Description</i>
	<p data-bbox="758 454 940 483"><u>Technical Note</u></p> <p data-bbox="758 495 1267 658"><i>For the purpose of Category Code 6A005.a.6.b., Note 2.a., ‘brightness’ is defined as the output power of the “laser” divided by the squared Beam Parameter Product (BPP), i.e. (output power)/BPP².</i></p> <p data-bbox="544 678 1267 775">7. Output wavelength exceeding 1,150 nm but not exceeding 1,555 nm and any of the following characteristics:</p> <ul style="list-style-type: none"> <li data-bbox="632 795 1267 860">a. Single transverse mode output and output power exceeding 50 W; <u>or</u> <li data-bbox="632 880 1267 945">b. Multiple transverse mode output and output power exceeding 80 W; <u>or</u> <p data-bbox="544 965 1267 1028">8. Output wavelength exceeding 1,555 nm and output power exceeding 1 W;</p> <p data-bbox="480 1048 1267 1111">b. Non-“tunable” “pulsed lasers” having any of the following characteristics:</p> <ul style="list-style-type: none"> <li data-bbox="544 1131 1267 1196">1. Output wavelength less than 150 nm, and any of the following characteristics: <ul style="list-style-type: none"> <li data-bbox="632 1216 1267 1281">a. Output energy exceeding 50 mJ per pulse and “peak power” exceeding 1 W; <u>or</u> <li data-bbox="632 1301 1267 1330">b. “Average output power” exceeding 1 W; <li data-bbox="544 1350 1267 1447">2. Output wavelength of 150 nm or more but not exceeding 510 nm, and having any of the following characteristics: <ul style="list-style-type: none"> <li data-bbox="632 1467 1267 1532">a. Output power exceeding 1.5 J per pulse and “peak power” exceeding 30 W; <u>or</u> <li data-bbox="632 1552 1267 1581">b. “Average output power” exceeding 30 W; <p data-bbox="692 1601 751 1630"><u>Note</u></p> <p data-bbox="692 1641 1267 1736"><i>Category Code 6A005.b.2.b. does not include Argon “lasers” having an “average output power” equal to or less than 50 W.</i></p>

<i>Category Code</i>	<i>Item Description</i>
	<ol style="list-style-type: none"> <li data-bbox="544 454 1268 1048">3. Output wavelength exceeding 510 nm but not exceeding 540 nm, and any of the following characteristics: <ol style="list-style-type: none"> <li data-bbox="632 568 1268 801">a. Single transverse mode output, and any of the following characteristics: <ol style="list-style-type: none"> <li data-bbox="695 656 1268 719">1. Output energy exceeding 1.5 J per pulse and “peak power” exceeding 50 W; <u>or</u> <li data-bbox="695 734 1268 801">2. “Average output power” exceeding 50 W; <u>or</u> <li data-bbox="632 819 1268 1048">b. Multiple transverse mode output, and any of the following characteristics: <ol style="list-style-type: none"> <li data-bbox="695 907 1268 969">1. Output energy exceeding 1.5 J per pulse and “peak power” exceeding 150 W; <u>or</u> <li data-bbox="695 985 1268 1048">2. “Average output power” exceeding 150 W; <li data-bbox="544 1070 1268 1635">4. Output wavelength exceeding 540 nm but not exceeding 800 nm, and any of the following characteristics: <ol style="list-style-type: none"> <li data-bbox="632 1189 1268 1422">a. “Pulse duration” less than 1 ps, and any of the following characteristics: <ol style="list-style-type: none"> <li data-bbox="695 1274 1268 1337">1. Output energy exceeding 0.005 J per pulse and “peak power” exceeding 5 GW; <u>or</u> <li data-bbox="695 1352 1268 1422">2. “Average output power” exceeding 20 W; <u>or</u> <li data-bbox="632 1440 1268 1635">b. “Pulse duration” equal to or exceeding 1 ps, and any of the following characteristics: <ol style="list-style-type: none"> <li data-bbox="695 1525 1268 1588">1. Output energy exceeding 1.5 J per pulse and “peak power” exceeding 30 W; <u>or</u> <li data-bbox="695 1603 1268 1635">2. “Average output power” exceeding 30 W;

<i>Category Code</i>	<i>Item Description</i>
	<p>5. Output wavelength exceeding 800 nm but not exceeding 975 nm, and any of the following characteristics:</p> <ul style="list-style-type: none"> a. "Pulse duration" less than 1 ps, and any of the following characteristics: <ul style="list-style-type: none"> 1. Output energy exceeding 0.005 J per pulse and "peak power" exceeding 5 GW; <u>or</u> 2. Single transverse mode output and "average output power" exceeding 20 W; b. "Pulse duration" equal to or exceeding 1 ps and not exceeding 1 μs, and any of the following characteristics: <ul style="list-style-type: none"> 1. Output energy exceeding 0.5 J per pulse and "peak power" exceeding 50 W; 2. Single transverse mode output and "average output power" exceeding 20 W; <u>or</u> 3. Multiple transverse mode output and "average output power" exceeding 50 W; <u>or</u> c. "Pulse duration" exceeding 1 μs, and any of the following characteristics: <ul style="list-style-type: none"> 1. Output energy exceeding 2 J per pulse and "peak power" exceeding 50 W; 2. Single transverse mode output and "average output power" exceeding 50 W; <u>or</u> 3. Multiple transverse mode output and "average output power" exceeding 80 W; <p>6. Output wavelength exceeding 975 nm but not exceeding 1,150 nm, and any of the following characteristics:</p> <ul style="list-style-type: none"> a. "Pulse duration" of less than 1 ps, and any of the following characteristics:

<i>Category Code</i>	<i>Item Description</i>
	<ol style="list-style-type: none"> 1. Output “peak power” exceeding 2 GW per pulse; 2. “Average output power” exceeding 30 W; <u>or</u> 3. Output energy exceeding 0.002 J per pulse; <p>b. “Pulse duration” equal to or exceeding 1 ps and less than 1 ns, and any of the following characteristics:</p> <ol style="list-style-type: none"> 1. Output “peak power” exceeding 5 GW per pulse; 2. “Average output power” exceeding 50 W; <u>or</u> 3. Output energy exceeding 0.1 J per pulse; <p>c. “Pulse duration” equal to or exceeding 1 ns but not exceeding 1 μs, and any of the following characteristics:</p> <ol style="list-style-type: none"> 1. Single transverse mode output, and any of the following characteristics: <ol style="list-style-type: none"> a. “Peak power” exceeding 100 MW; b. “Average output power” exceeding 20 W limited by design to a maximum pulse repetition frequency less or equal to 1 kHz; c. ‘Wall-plug efficiency’ exceeding 12%, “average output power” exceeding 100 W, and capable of operating at a pulse repetition frequency greater than 1 kHz; d. “Average output power” exceeding 150 W, and capable of operating at a pulse repetition frequency greater than 1 kHz; <u>or</u> e. Output energy exceeding 2 J per pulse; <u>or</u>

<i>Category Code</i>	<i>Item Description</i>
	<ol style="list-style-type: none"> <li data-bbox="692 454 1272 853">2. Multiple transverse mode output, and any of the following characteristics: <ol style="list-style-type: none"> <li data-bbox="754 539 1272 573">a. “Peak power” exceeding 400 MW; <li data-bbox="754 589 1272 685">b. ‘Wall-plug efficiency’ exceeding 18% and “average output power” exceeding 500 W; <li data-bbox="754 701 1272 770">c. “Average output power” exceeding 2 kW; <u>or</u> <li data-bbox="754 786 1272 853">d. Output energy exceeding 4 J per pulse; <u>or</u> <li data-bbox="632 869 1272 936">d. “Pulse duration” exceeding 1 μs, and any of the following characteristics: <ol style="list-style-type: none"> <li data-bbox="692 952 1272 1019">1. Single transverse mode output, and any of the following characteristics: <ol style="list-style-type: none"> <li data-bbox="754 1034 1272 1068">a. “Peak power” exceeding 500 kW; <li data-bbox="754 1084 1272 1180">b. ‘Wall-plug efficiency’ exceeding 12% and “average output power” exceeding 100 W; <u>or</u> <li data-bbox="754 1196 1272 1265">c. “Average output power” exceeding 150 W; <u>or</u> <li data-bbox="692 1281 1272 1599">2. Multiple transverse mode output, and any of the following characteristics: <ol style="list-style-type: none"> <li data-bbox="754 1370 1272 1404">a. “Peak power” exceeding 1 MW; <li data-bbox="754 1420 1272 1516">b. ‘Wall-plug efficiency’ exceeding 18% and “average output power” exceeding 500 W; <u>or</u> <li data-bbox="754 1532 1272 1599">c. “Average output power” exceeding 2 kW; <li data-bbox="544 1615 1272 1803">7. Output wavelength exceeding 1,150 nm but not exceeding 1,555 nm, and any of the following characteristics: <ol style="list-style-type: none"> <li data-bbox="632 1733 1272 1803">a. “Pulse duration” not exceeding 1 μs, and any of the following characteristics:

<i>Category Code</i>	<i>Item Description</i>
	<ol style="list-style-type: none"> 1. Output energy exceeding 0.5 J per pulse and “peak power” exceeding 50 W; 2. Single transverse mode output and “average output power” exceeding 20 W; <u>or</u> 3. Multiple transverse mode output and “average output power” exceeding 50 W; <u>or</u> <p>b. “Pulse duration” exceeding 1 μs, and any of the following characteristics:</p> <ol style="list-style-type: none"> 1. Output energy exceeding 2 J per pulse and “peak power” exceeding 50 W; 2. Single transverse mode output and “average output power” exceeding 50 W; <u>or</u> 3. Multiple transverse mode output and “average output power” exceeding 80 W; <u>or</u> <p>8. Output wavelength exceeding 1,555 nm, and any of the following characteristics:</p> <ol style="list-style-type: none"> a. Output energy exceeding 100 mJ per pulse and “peak power” exceeding 1 W; <u>or</u> b. “Average output power” exceeding 1 W; <p>c. “Tunable” “lasers” having any of the following characteristics:</p> <ol style="list-style-type: none"> 1. Output wavelength less than 600 nm, and any of the following characteristics: <ol style="list-style-type: none"> a. Output energy exceeding 50 mJ per pulse and “peak power” exceeding 1 W; <u>or</u> b. Average or CW output power exceeding 1 W;

Category Code	Item Description
	<p data-bbox="608 454 667 483"><u>Note</u></p> <p data-bbox="608 495 1267 658">Category Code 6A005.c.1. does not include dye “lasers” or other liquid “lasers”, having a multimode output and a wavelength of 150 nm or more but not exceeding 600 nm and all of the following characteristics:</p> <ol data-bbox="544 680 1267 1424" style="list-style-type: none"> <li data-bbox="632 680 1267 748">1. Output energy less than 1.5 J per pulse or a “peak power” less than 20 W; <u>and</u> <li data-bbox="632 763 1267 792">2. Average or CW output power less than 20 W. <ol data-bbox="544 815 1267 1294" style="list-style-type: none"> <li data-bbox="544 815 1267 904">2. Output wavelength of 600 nm or more but not exceeding 1,400 nm, and any of the following characteristics: <ol data-bbox="632 927 1267 1077" style="list-style-type: none"> <li data-bbox="632 927 1267 994">a. Output energy exceeding 1 J per pulse and “peak power” exceeding 20 W; <u>or</u> <li data-bbox="632 1010 1267 1077">b. Average or CW output power exceeding 20 W; <u>or</u> <li data-bbox="544 1099 1267 1294">3. Output wavelength exceeding 1,400 nm, and any of the following characteristics: <ol data-bbox="632 1182 1267 1294" style="list-style-type: none"> <li data-bbox="632 1182 1267 1249">a. Output energy exceeding 50 mJ per pulse and “peak power” exceeding 1 W; <u>or</u> <li data-bbox="632 1265 1267 1294">b. Average or CW output power exceeding 1 W; <ol data-bbox="480 1317 1267 1424" style="list-style-type: none"> <li data-bbox="480 1317 1267 1384">d. Other “lasers”, not specified in Category Code 6A005.a., 6A005.b. or 6A005.c. as follows: <ol data-bbox="544 1400 1023 1424" style="list-style-type: none"> <li data-bbox="544 1400 1023 1424">1. Semiconductor “lasers” as follows: <p data-bbox="608 1447 687 1476"><u>Note 1</u></p> <p data-bbox="608 1487 1267 1585">Category Code 6A005.d.1. includes semiconductor “lasers” having optical output connectors (e.g. fibre optic pigtails).</p> <p data-bbox="608 1608 687 1637"><u>Note 2</u></p> <p data-bbox="608 1648 1267 1744">The control status of semiconductor “lasers” specially designed for other equipment is determined by the control status of the other equipment.</p>

<i>Category Code</i>	<i>Item Description</i>
	<ul style="list-style-type: none"> a. Individual single-transverse mode semiconductor “lasers” having any of the following characteristics: <ul style="list-style-type: none"> 1. Wavelength equal or less than 1,510 nm and average or CW output power, exceeding 1.5 W; <u>or</u> 2. Wavelength greater than 1,510 nm and average or CW output power, exceeding 500 mW; b. Individual, multiple-transverse mode semiconductor “lasers” having any of the following characteristics: <ul style="list-style-type: none"> 1. Wavelength of less than 1,400 nm, and average or CW output power exceeding 15 W; 2. Wavelength equal to or greater than 1,400 nm and less than 1,900 nm, and average or CW output power exceeding 2.5 W; <u>or</u> 3. Wavelength equal to or greater than 1,900 nm, and average or CW output power exceeding 1 W; c. Individual semiconductor “laser” ‘bars’, having any of the following characteristics: <ul style="list-style-type: none"> 1. Wavelength of less than 1,400 nm, and average or CW output power exceeding 100 W; 2. Wavelength equal to or greater than 1,400 nm and less than 1,900 nm, and average or CW output power exceeding 25 W; <u>or</u> 3. Wavelength equal to or greater than 1,900 nm, and average or CW output power exceeding 10 W;

<i>Category Code</i>	<i>Item Description</i>
	<p>d. Semiconductor “laser” ‘stacked arrays’ (two-dimensional arrays) having any of the following characteristics:</p> <ol style="list-style-type: none"> 1. Wavelength less than 1,400 nm, and having any of the following characteristics: <ol style="list-style-type: none"> a. Average or CW total output power less than 3 kW, and having average or CW output ‘power density’ greater than 500 W/cm²; b. Average or CW total output power equal to or exceeding 3 kW but less or equal to 5 kW, and having average or CW output ‘power density’ greater than 350 W/cm²; c. Average or CW total output power exceeding 5 kW; d. Peak pulsed ‘power density’ exceeding 2,500 W/cm²; <u>or</u> <p style="margin-left: 40px;"><i>Note</i> Category Code 6A005.d.1.d.1.d. does not include epitaxially-fabricated monolithic devices.</p> e. Spatially coherent average or CW total output power greater than 150 W; 2. Wavelength greater than or equal to 1,400 nm but less than 1,900 nm, and having any of the following characteristics: <ol style="list-style-type: none"> a. Average or CW total output power less than 250 W, and average or CW output ‘power density’ greater than 150 W/cm²;

<i>Category Code</i>	<i>Item Description</i>
	<p>b. Average or CW total output power equal to or exceeding 250 W but less or equal to 500 W, and having average or CW output ‘power density’ greater than 50 W/cm²;</p> <p>c. Average or CW total output power exceeding 500 W;</p> <p>d. Peak pulsed ‘power density’ exceeding 500 W/cm²; <u>or</u></p> <p><i>Note</i> <i>Category Code 6A005.d.1.d.2.d. does not include epitaxially-fabricated monolithic devices.</i></p> <p>e. Spatially coherent average or CW total output power, exceeding 15 W;</p> <p>3. Wavelength greater than or equal to 1,900 nm, and having any of the following characteristics:</p> <p>a. Average or CW output ‘power density’ greater than 50 W/cm²;</p> <p>b. Average or CW output power greater than 10 W; <u>or</u></p> <p>c. Spatially coherent average or CW total output power exceeding 1.5 W; <u>or</u></p> <p>4. At least one “laser” ‘bar’ specified in Category Code 6A005.d.1.c.;</p> <p><i>Technical Note</i> <i>For the purpose of Category Code 6A005.d.1.d., ‘power density’ means the total “laser” output power divided by the emitter surface area of the ‘stacked array’.</i></p>

Category Code	Item Description
	<p>e. Semiconductor “laser” ‘stacked arrays’, other than those specified in Category Code 6A005.d.1.d., having all of the following characteristics:</p> <ol style="list-style-type: none"> 1. Specially designed or modified to be combined with other ‘stacked arrays’ to form a larger ‘stacked array’; <u>and</u> 2. Integrated connections, common for both electronics and cooling; <p><u>Note 1</u> ‘Stacked arrays’, formed by combining semiconductor “laser” ‘stacked arrays’ specified by Category Code 6A005.d.1.e., that are not designed to be further combined or modified are specified by Category Code 6A005.d.1.d.</p> <p><u>Note 2</u> ‘Stacked arrays’, formed by combining semiconductor “laser” ‘stacked arrays’ specified by Category Code 6A005.d.1.e., that are designed to be further combined or modified are specified by Category Code 6A005.d.1.e.</p> <p><u>Note 3</u> Category Code 6A005.d.1.e. does not include modular assemblies of single ‘bars’ designed to be fabricated into end-to-end stacked linear arrays.</p> <p><u>Technical Notes</u></p> <ol style="list-style-type: none"> 1. Semiconductor “lasers” are commonly called “laser” diodes. 2. A ‘bar’ (also called a semiconductor “laser” ‘bar’, a “laser” diode ‘bar’ or diode ‘bar’) consists of multiple semiconductor “lasers” in a one-dimensional array. 3. A ‘stacked array’ consists of multiple ‘bars’ forming a two-dimensional array of semiconductor “lasers”.

<i>Category Code</i>	<i>Item Description</i>
	<ol style="list-style-type: none"> <li data-bbox="544 454 1268 521">2. Carbon monoxide (CO) “lasers” having any of the following characteristics: <ol style="list-style-type: none"> <li data-bbox="632 539 1268 607">a. Output energy exceeding 2 J per pulse and “peak power” exceeding 5 kW; <u>or</u> <li data-bbox="632 622 1268 656">b. Average or CW output power exceeding 5 kW; <li data-bbox="544 672 1268 739">3. Carbon dioxide (CO₂) “lasers” having any of the following characteristics: <ol style="list-style-type: none"> <li data-bbox="632 757 1268 790">a. CW output power exceeding 15 kW; <li data-bbox="632 806 1268 952">b. Pulsed output with a “pulse duration” exceeding 10 μs, and any of the following characteristics: <ol style="list-style-type: none"> <li data-bbox="695 891 1268 958">1. “Average output power” exceeding 10 kW; <u>or</u> <li data-bbox="695 974 1268 1008">2. “Peak power” exceeding 100 kW; <u>or</u> <li data-bbox="632 1023 1268 1249">c. Pulsed output with a “pulse duration” equal to or less than 10 μs, and any of the following characteristics: <ol style="list-style-type: none"> <li data-bbox="695 1137 1268 1171">1. Pulse energy exceeding 5 J per pulse; <u>or</u> <li data-bbox="695 1187 1268 1254">2. “Average output power” exceeding 2.5 kW; <li data-bbox="544 1265 1268 1834">4. Excimer “lasers” having any of the following characteristics: <ol style="list-style-type: none"> <li data-bbox="632 1355 1268 1556">a. Output wavelength not exceeding 150 nm, and any of the following characteristics: <ol style="list-style-type: none"> <li data-bbox="695 1440 1268 1507">1. Output energy exceeding 50 mJ per pulse; <u>or</u> <li data-bbox="695 1523 1268 1556">2. “Average output power” exceeding 1 W; <li data-bbox="632 1572 1268 1834">b. Output wavelength exceeding 150 nm but not exceeding 190 nm, and any of the following characteristics: <ol style="list-style-type: none"> <li data-bbox="695 1686 1268 1753">1. Output energy exceeding 1.5 J per pulse; <u>or</u> <li data-bbox="695 1769 1268 1834">2. “Average output power” exceeding 120 W;

<i>Category Code</i>	<i>Item Description</i>
	<p>c. Output wavelength exceeding 190 nm but not exceeding 360 nm, and any of the following characteristics:</p> <ol style="list-style-type: none"> 1. Output energy exceeding 10 J per pulse; <u>or</u> 2. “Average output power” exceeding 500 W; <u>or</u> <p>d. Output wavelength exceeding 360 nm, and any of the following characteristics:</p> <ol style="list-style-type: none"> 1. Output energy exceeding 1.5 J per pulse; <u>or</u> 2. “Average output power” exceeding 30 W; <p><u>N.B.</u> <i>For excimer “lasers” specially designed for lithography equipment, see Category Code 3B001.</i></p> <p>5. “Chemical lasers” as follows:</p> <ol style="list-style-type: none"> a. Hydrogen Fluoride (HF) “lasers”; b. Deuterium Fluoride (DF) “lasers”; c. “Transfer lasers”, as follows: <ol style="list-style-type: none"> 1. Oxygen Iodine (O₂-I) “lasers”; 2. Deuterium Fluoride-Carbon dioxide (DF-CO₂) “lasers”; <p>6. ‘Non-repetitive pulsed’ Nd: glass “lasers” having any of the following characteristics:</p> <ol style="list-style-type: none"> a. “Pulse duration” not exceeding 1 μs and output energy exceeding 50 J per pulse; <u>or</u> b. “Pulse duration” exceeding 1 μs and output energy exceeding 100 J per pulse; <p><u>Note</u> <i>‘Non-repetitive pulsed’ refers to “lasers” that produce either a single output pulse or that have a time interval between pulses exceeding one minute.</i></p>

<i>Category Code</i>	<i>Item Description</i>
	<p>e. Components as follows:</p> <ol style="list-style-type: none"> 1. Mirrors cooled either by ‘active cooling’ or by heat pipe cooling; <p><i>Technical Note</i> ‘Active cooling’ is a cooling technique for optical components using flowing fluids within the subsurface (nominally less than 1 mm below the optical surface) of the optical component to remove heat from the optic.</p> <ol style="list-style-type: none"> 2. Optical mirrors or transmissive or partially transmissive optical or electro-optical components, other than fused tapered fibre combiners and Multi-Layer Dielectric gratings (MLDs), specially designed for use with specified “lasers”; <p><i>Note</i> Fibre combiners and MLDs are specified in Category Code 6A005.e.3.</p> <ol style="list-style-type: none"> 3. Fibre “laser” components as follows: <ol style="list-style-type: none"> a. Multimode to multimode fused tapered fibre combiners having all of the following characteristics: <ol style="list-style-type: none"> 1. An insertion loss better (less) than or equal to 0.3 dB maintained at a rated total average or CW output power (excluding output power transmitted through the single mode core if present) exceeding 1,000 W; <u>and</u> 2. Number of input fibres equal to or greater than 3; b. Single mode to multimode fused tapered fibre combiners having all of the following characteristics: <ol style="list-style-type: none"> 1. An insertion loss better (less) than 0.5 dB maintained at a rated total average or CW output power exceeding 4,600 W; 2. Number of input fibres equal to or greater than 3; <u>and</u>

<i>Category Code</i>	<i>Item Description</i>
	<p data-bbox="692 454 1267 517">3. Having any of the following characteristics:</p> <p data-bbox="751 539 1267 667">a. A Beam Parameter Product (BPP) measured at the output not exceeding 1.5 mm•mrad for a number of input fibres not more than 5; <u>or</u></p> <p data-bbox="751 689 1267 786">b. A BPP measured at the output not exceeding 2.5 mm•mrad for a number of input fibres greater than 5;</p> <p data-bbox="628 808 1267 871">c. MLDs having all of the following characteristics:</p> <p data-bbox="692 893 1267 990">1. Designed for spectral or coherent beam combination of 5 or more fibre “lasers”; <u>and</u></p> <p data-bbox="692 1012 1267 1108">2. CW “Laser” Induced Damage Threshold (LIDT) greater than or equal to 10 kW/cm²;</p> <p data-bbox="480 1131 903 1160">f. Optical equipment as follows:</p> <p data-bbox="544 1182 600 1211"><u>N.B.</u></p> <p data-bbox="544 1223 1267 1319"><i>For shared aperture optical elements, capable of operating in “Super-High Power Laser” (“SHPL”) applications, see Division 2 of Part 1 of this Schedule.</i></p> <p data-bbox="544 1341 1267 1438">1. Dynamic wavefront (phase) measuring equipment capable of mapping at least 50 positions on a beam wavefront, and any of the following:</p> <p data-bbox="628 1460 1267 1556">a. Frame rates equal to or more than 100 Hz and phase discrimination of at least 5% of the beam’s wavelength; <u>or</u></p> <p data-bbox="628 1579 1267 1675">b. Frame rates equal to or more than 1,000 Hz and phase discrimination of at least 20% of the beam’s wavelength;</p> <p data-bbox="544 1697 1267 1794">2. “Laser” diagnostic equipment capable of measuring “SHPL” system angular beam steering errors of equal to or less than 10 µrad;</p>

<i>Category Code</i>	<i>Item Description</i>
	<ol style="list-style-type: none"> 3. Optical equipment and components, specially designed for a phased-array “SHPL” system for coherent beam combination to an “accuracy” of $\lambda/10$ at the designed wavelength, or 0.1 μm, whichever is the smaller; 4. Projection telescopes specially designed for use with “SHPL” systems; <p>g. ‘Laser acoustic detection equipment’ having all of the following characteristics:</p> <ol style="list-style-type: none"> 1. CW “laser” output power equal to or exceeding 20 mW; 2. “Laser” frequency stability equal to or better (less) than 10 MHz; 3. “Laser” wavelengths equal to or exceeding 1,000 nm but not exceeding 2,000 nm; 4. Optical system resolution better (less) than 1 nm; <u>and</u> 5. Optical Signal to Noise ratio equal to or exceeding 10^3. <p><u>Technical Note</u> ‘Laser acoustic detection equipment’ is sometimes referred to as a “Laser” Microphone or Particle Flow Detection Microphone.</p>
6A006	<p>“Magnetometers”, “magnetic gradiometers”, “intrinsic magnetic gradiometers”, underwater electric field sensors, “compensation systems”, and specially designed components therefor, as follows:</p> <p><u>N.B.</u> See also Category Code 7A103.d.</p> <p><u>Note</u> Category Code 6A006 does not include instruments specially designed for fishery applications or biomagnetic measurements for medical diagnostics.</p> <p>a. “Magnetometers” and sub-systems, as follows:</p> <ol style="list-style-type: none"> 1. “Magnetometers” using “superconductive” (SQUID) “technology” and having any of the following:

<i>Category Code</i>	<i>Item Description</i>
	<ul style="list-style-type: none"> a. SQUID systems designed for stationary operation, without specially designed sub-systems designed to reduce in-motion noise, and having a 'sensitivity' equal to or lower (better) than 50 fT (rms) per square root Hz at a frequency of 1 Hz; <u>or</u> b. SQUID systems having an in-motion-magnetometer 'sensitivity' lower (better) than 20 pT (rms) per square root Hz at a frequency of 1 Hz and specially designed to reduce in-motion noise; <ul style="list-style-type: none"> 2. "Magnetometers" using optically pumped or nuclear precession (proton/Overhauser) "technology" having a 'sensitivity' lower (better) than 20 pT (rms) per square root Hz at a frequency of 1 Hz; 3. "Magnetometers" using fluxgate "technology" having a 'sensitivity' equal to or lower (better) than 10 pT (rms) per square root Hz at a frequency of 1 Hz; 4. Induction coil "magnetometers" having a 'sensitivity' lower (better) than any of the following: <ul style="list-style-type: none"> a. 0.05 nT (rms) per square root Hz at frequencies of less than 1 Hz; b. 1×10^{-3} nT (rms) per square root Hz at frequencies of 1 Hz or more but not exceeding 10 Hz; <u>or</u> c. 1×10^{-4} nT (rms) per square root Hz at frequencies exceeding 10 Hz; 5. Fibre optic "magnetometers" having a 'sensitivity' lower (better) than 1 nT (rms) per square root Hz; <ul style="list-style-type: none"> b. Underwater electric field sensors having a 'sensitivity' lower (better) than 8 nanovolt per metre per square root Hz when measured at 1 Hz;

<i>Category Code</i>	<i>Item Description</i>
	<p>c. “Magnetic gradiometers” as follows:</p> <ol style="list-style-type: none"> 1. “Magnetic gradiometers” using multiple “magnetometers” specified in Category Code 6A006.a.; 2. Fibre optic “intrinsic magnetic gradiometers” having a magnetic gradient field ‘sensitivity’ lower (better) than 0.3 nT/m (rms) per square root Hz; 3. “Intrinsic magnetic gradiometers”, using “technology” other than fibre-optic “technology”, having a magnetic gradient field ‘sensitivity’ lower (better) than 0.015 nT/m (rms) per square root Hz; <p>d. “Compensation systems” for magnetic or underwater electric field sensors resulting in a performance equal to or better than the specified parameters of Category Code 6A006.a., 6A006.b. or 6A006.c.;</p> <p>e. Underwater electromagnetic receivers incorporating magnetic field sensors specified by Category Code 6A006.a. or underwater electric field sensors specified by Category Code 6A006.b.</p> <p><u>Technical Note</u> <i>For the purpose of Category Code 6A006, ‘sensitivity’ (noise level) is the root mean square of the device-limited noise floor which is the lowest signal that can be measured.</i></p>
6A007	<p>Gravity meters (gravimeters) and gravity gradiometers, as follows:</p> <p><u>N.B.</u> <i>See also Category Code 6A107.</i></p> <ol style="list-style-type: none"> a. Gravity meters designed or modified for ground use and having a static “accuracy” of less (better) than 10 μGal; <p><u>Note</u> <i>Category Code 6A007.a. does not include ground gravity meters of the quartz element (Worden) type.</i></p> <ol style="list-style-type: none"> b. Gravity meters designed for mobile platforms and having all of the following characteristics: <ol style="list-style-type: none"> 1. A static “accuracy” of less (better) than 0.7 mGal; <u>and</u>

<i>Category Code</i>	<i>Item Description</i>
	<p>2. An in-service (operational) “accuracy” of less (better) than 0.7 mGal having a ‘time-to-steady-state registration’ of less than 2 minutes under any combination of attendant corrective compensations and motional influences;</p> <p><i>Technical Note</i> For the purpose of Category Code 6A007.b., ‘time-to-steady-state registration’ (also referred to as the gravimeter’s response time) is the time over which the disturbing effects of platform induced accelerations (high frequency noise) are reduced.</p> <p>c. Gravity gradiometers.</p>
6A008	<p>Radar systems, equipment and assemblies having any of the following, and specially designed components thereof:</p> <p><i>N.B.</i> See also Category Code 6A108.</p> <p><i>Note</i> Category Code 6A008 does not include:</p> <ul style="list-style-type: none"> – Secondary surveillance radar (SSR); – Civil Automotive Radar; – Displays or monitors used for air traffic control (ATC); – Meteorological (weather) radar; – Precision approach radar (PAR) equipment conforming to ICAO standards and employing electronically steerable linear (1-dimensional) arrays or mechanically positioned passive antennae. <p>a. Operating at frequencies from 40 GHz to 230 GHz, and having any of the following characteristics:</p> <ol style="list-style-type: none"> 1. An average output power exceeding 100 mW; <u>or</u> 2. Locating “accuracy” of 1 m or less (better) in range and 0.2 degree or less (better) in azimuth; <p>b. A tunable bandwidth exceeding $\pm 6.25\%$ of the ‘centre operating frequency’;</p>

<i>Category Code</i>	<i>Item Description</i>
	<p data-bbox="544 454 727 488"><u>Technical Note</u></p> <p data-bbox="544 495 1260 562"><i>The ‘centre operating frequency’ equals one half of the sum of the highest plus the lowest specified operating frequencies.</i></p> <ul style="list-style-type: none"> <li data-bbox="480 577 1260 645">c. Capable of operating simultaneously on more than two carrier frequencies; <li data-bbox="480 660 1260 761">d. Capable of operating in synthetic aperture (SAR), inverse synthetic aperture (ISAR) radar mode, or sidelooking airborne (SLAR) radar mode; <li data-bbox="480 777 1177 810">e. Incorporating electronically steerable array antennae; <li data-bbox="480 826 1134 860">f. Capable of heightfinding non-cooperative targets; <li data-bbox="480 875 1260 976">g. Specially designed for airborne (balloon or airframe mounted) operation and having Doppler “signal processing” for the detection of moving targets; <li data-bbox="480 992 1260 1245">h. Employing processing of radar signals and using any of the following: <ul style="list-style-type: none"> <li data-bbox="544 1077 1082 1111">1. “Radar spread spectrum” techniques; <u>or</u> <li data-bbox="544 1126 1054 1160">2. “Radar frequency agility” techniques; <li data-bbox="480 1176 1260 1245">i. Providing ground-based operation with a maximum “instrumented range” exceeding 185 km; <p data-bbox="544 1261 608 1294"><u>Note</u></p> <p data-bbox="544 1301 1042 1335"><i>Category Code 6A008.i. does not include:</i></p> <ul style="list-style-type: none"> <li data-bbox="544 1350 1027 1384">a. <i>Fishing ground surveillance radar;</i> <li data-bbox="544 1400 1260 1868">b. <i>Ground radar equipment specially designed for enroute air traffic control and having all of the following characteristics:</i> <ul style="list-style-type: none"> <li data-bbox="632 1518 1260 1585">1. <i>A maximum “instrumented range” of 500 km or less;</i> <li data-bbox="632 1601 1260 1702">2. <i>Configured so that radar target data can be transmitted only one way from the radar site to one or more civil ATC centres;</i> <li data-bbox="632 1718 1260 1818">3. <i>Contains no provisions for remote control of the radar scan rate from the enroute ATC centre; <u>and</u></i> <li data-bbox="632 1834 991 1868">4. <i>Is permanently installed;</i>

Category Code	Item Description
	<p data-bbox="544 454 1007 488"><i>c. Weather balloon tracking radars.</i></p> <p data-bbox="480 506 1267 573"><i>j. Being “laser” radar or Light Detection and Ranging (LIDAR) equipment, and having any of the following characteristics:</i></p> <ol data-bbox="544 589 1267 954" style="list-style-type: none"> <li data-bbox="544 589 831 622"><i>1. “Space-qualified”;</i> <li data-bbox="544 638 1267 741"><i>2. Employing coherent heterodyne or homodyne detection techniques, and having an angular resolution of less (better) than 20 µrad (microradians); or</i> <li data-bbox="544 757 1267 954"><i>3. Designed for carrying out airborne bathymetric littoral surveys to International Hydrographic Organisation (IHO) Order 1a Standard (5th Edition February 2008) for Hydrographic Surveys or better, and using one or more “lasers” with a wavelength exceeding 400 nm but not exceeding 600 nm;</i> <p data-bbox="544 972 624 1005"><u><i>Note 1</i></u></p> <p data-bbox="544 1014 1267 1081"><i>LIDAR equipment specially designed for surveying is only specified in Category Code 6A008.j.3.</i></p> <p data-bbox="544 1099 624 1133"><u><i>Note 2</i></u></p> <p data-bbox="544 1142 1267 1209"><i>Category Code 6A008.j. does not include LIDAR equipment specially designed for meteorological observation.</i></p> <p data-bbox="544 1227 624 1261"><u><i>Note 3</i></u></p> <p data-bbox="544 1270 1267 1337"><i>Parameters in the IHO Order 1a Standard 5th Edition February 2008 are summarised as follows:</i></p> <ul data-bbox="544 1352 1267 1536" style="list-style-type: none"> <li data-bbox="544 1352 1267 1420"><i>– Horizontal Accuracy (95% Confidence Level) = 5 m + 5% of depth</i> <li data-bbox="544 1435 1267 1536"><i>– Depth Accuracy for Reduced Depths (95% confidence level) = $\pm\sqrt{a^2 + (b*d)^2}$, where:</i> <p data-bbox="608 1563 1267 1630"><i>a = 0.5 m = constant depth error, i.e. the sum of all constant depth errors</i></p> <p data-bbox="608 1646 1134 1680"><i>b = 0.013 = factor of depth dependent error</i></p> <p data-bbox="608 1695 1267 1762"><i>b*d = depth dependent error, i.e. the sum of all depth dependent errors</i></p> <p data-bbox="608 1778 727 1812"><i>d = depth</i></p>

Category Code	Item Description
	<p data-bbox="544 454 1268 521">– <i>Feature Detection = Cubic features > 2 m in depths up to 40 m; 10% of depth beyond 40 m.</i></p> <p data-bbox="480 539 1268 633">k. Having “signal processing” sub-systems using “pulse compression”, and having any of the following characteristics:</p> <ol data-bbox="544 656 1268 734" style="list-style-type: none"> <li data-bbox="544 656 1268 689">1. A “pulse compression” ratio exceeding 150; <u>or</u> <li data-bbox="544 701 1268 734">2. A compressed pulse width of less than 200 ns; <u>or</u> <p data-bbox="608 757 667 790"><u>Note</u></p> <p data-bbox="608 797 1268 898"><i>Category Code 6A008.k.2. does not include two dimensional ‘marine radar’ or ‘vessel traffic service’ radar, having all of the following characteristics:</i></p> <ol data-bbox="632 913 1268 1182" style="list-style-type: none"> <li data-bbox="632 913 1268 947">a. “Pulse compression” ratio not exceeding 150; <li data-bbox="632 958 1268 992">b. Compressed pulse width of greater than 30 ns; <li data-bbox="632 1003 1268 1081">c. Single and rotating mechanically scanned antenna; <li data-bbox="632 1093 1268 1126">d. Peak output power not exceeding 250 W; <u>and</u> <li data-bbox="632 1137 1268 1182">e. Not capable of “frequency hopping”. <p data-bbox="480 1193 1268 1261">1. Having data processing sub-systems, and having any of the following characteristics:</p> <ol data-bbox="544 1283 1268 1384" style="list-style-type: none"> <li data-bbox="544 1283 1268 1384">1. “Automatic target tracking” providing, at any antenna rotation, the predicted target position beyond the time of the next antenna beam passage; <u>or</u> <p data-bbox="608 1395 667 1429"><u>Note</u></p> <p data-bbox="608 1435 1268 1503"><i>Category Code 6A008.l.1. does not include conflict alert capability in ATC systems, or ‘marine radar’.</i></p> <ol data-bbox="544 1525 1268 1816" style="list-style-type: none"> <li data-bbox="544 1525 1268 1559">2. Not used; <li data-bbox="544 1570 1268 1603">3. Not used; <li data-bbox="544 1615 1268 1816">4. Configured to provide superposition and correlation, or fusion, of target data within six seconds from two or more “geographically dispersed” radar sensors to improve the aggregate performance beyond that of any single sensor specified in Category Code 6A008.f. or 6A008.i.

Category Code	Item Description
	<p><u>N.B.</u> See also Division 2 of Part 1 of this Schedule.</p> <p><u>Note</u> Category Code 6A008.l.4. does not include systems, equipment and assemblies used for 'vessel traffic service'.</p> <p><u>Technical Notes</u></p> <ol style="list-style-type: none"> 1. For the purpose of Category Code 6A008, 'marine radar' is a radar that is used to navigate safely at sea, inland waterways or near-shore environments. 2. For the purpose of Category Code 6A008, 'vessel traffic service' is a vessel traffic monitoring and control service similar to air traffic control for "aircraft".
6A102	<p>Radiation hardened 'detectors', other than those specified in Category Code 6A002, specially designed or modified for protecting against nuclear effects (e.g. electromagnetic pulse (EMP), X-rays, combined blast and thermal effects) and usable for "missiles", designed or rated to withstand radiation levels which meet or exceed a total irradiation dose of 5×10^5 rads (silicon).</p> <p><u>Technical Note</u> In Category Code 6A102, a 'detector' is defined as a mechanical, electrical, optical or chemical device that automatically identifies and records, or registers a stimulus such as an environmental change in pressure or temperature, an electrical or electromagnetic signal or radiation from a radioactive material. This includes devices that sense by one time operation or failure.</p>
6A107	<p>Gravity meters (gravimeters) and components for gravity meters and gravity gradiometers, as follows:</p> <ol style="list-style-type: none"> a. Gravity meters, other than those specified in Category Code 6A007.b., designed or modified for airborne or marine use, and having a static or operational accuracy equal to or less (better) than 0.7 milligal (mgal), and having a time-to-steady-state registration of two minutes or less;

<i>Category Code</i>	<i>Item Description</i>
6A108	<p>b. Specially designed components for gravity meters specified in Category Code 6A007.b. or 6A107.a. and gravity gradiometers specified in Category Code 6A007.c.</p> <p>Radar systems and tracking systems, other than those specified in Category Code 6A008, as follows:</p> <p>a. Radar and laser radar systems designed or modified for use in space launch vehicles specified in Category Code 9A004 or sounding rockets specified in Category Code 9A104;</p> <p><i>Note</i> <i>Category Code 6A108.a. includes the following:</i></p> <p>a. <i>Terrain contour mapping equipment;</i></p> <p>b. <i>Imaging sensor equipment;</i></p> <p>c. <i>Scene mapping and correlation (both digital and analogue) equipment;</i></p> <p>d. <i>Doppler navigation radar equipment.</i></p> <p>b. Precision tracking systems, usable for ‘missiles’, as follows:</p> <p>1. Tracking systems which use a code translator in conjunction with either surface or airborne references or navigation satellite systems to provide real-time measurements of in-flight position and velocity;</p> <p>2. Range instrumentation radars including associated optical/infrared trackers with all of the following capabilities:</p> <p>a. Angular resolution better than 1.5 milliradians;</p> <p>b. Range of 30 km or greater with a range resolution better than 10 m rms; <u>and</u></p> <p>c. Velocity resolution better than 3 m/s.</p> <p><i>Technical Note</i> <i>In Category Code 6A108.b., ‘missile’ means complete rocket systems and unmanned aerial vehicle systems capable of a range exceeding 300 km.</i></p>

<i>Category Code</i>	<i>Item Description</i>
6A202	Photomultiplier tubes having both of the following characteristics: <ol style="list-style-type: none"> a. Photocathode area of greater than 20 cm²; <u>and</u> b. Anode pulse rise time of less than 1 ns.
6A203	Cameras and components, other than those specified in Category Code 6A003, as follows: <p><u>N.B. 1</u></p> <p><i>“Software” specially designed to enhance or release the performance of a camera or imaging device to meet the characteristics of Category Code 6A203.a., 6A203.b. or 6A203.c. is specified in Category Code 6D203.</i></p> <p><u>N.B. 2</u></p> <p><i>“Technology” in the form of codes or keys to enhance or release the performance of a camera or imaging device to meet the characteristics of Category Code 6A203.a., 6A203.b. or 6A203.c. is specified in Category Code 6E203.</i></p> <p><u>Note</u></p> <p><i>Category Codes 6A203.a. to 6A203.c. do not include cameras or imaging devices if they have hardware, “software” or “technology” constraints that limit the performance to less than that specified above, provided they meet any of the following:</i></p> <ol style="list-style-type: none"> a. <i>They need to be returned to the original manufacturer to make the enhancements or release the constraints;</i> b. <i>They require “software” as specified in Category Code 6D203 to enhance or release the performance to meet the characteristics of Category Code 6A203; <u>or</u></i> c. <i>They require “technology” in the form of keys or codes as specified in Category Code 6E203 to enhance or release the performance to meet the characteristics of Category Code 6A203.</i> <ol style="list-style-type: none"> a. Streak cameras, and specially designed components therefor, as follows: <ol style="list-style-type: none"> 1. Streak cameras with writing speeds greater than 0.5 mm/μs;

<i>Category Code</i>	<i>Item Description</i>
	<ol style="list-style-type: none"> 2. Electronic streak cameras capable of 50 ns or less time resolution; 3. Streak tubes for cameras specified in Category Code 6A203.a.2.; 4. Plug-ins specially designed for use with streak cameras which have modular structures and that enable the performance specifications in Category Code 6A203.a.1. or 6A203.a.2.; 5. Synchronising electronics units, rotor assemblies consisting of turbines, mirrors and bearings specially designed for cameras specified in Category Code 6A203.a.1.; <p>b. Framing cameras, and specially designed components therefor, as follows:</p> <ol style="list-style-type: none"> 1. Framing cameras with recording rates greater than 225,000 frames per second; 2. Framing cameras capable of 50 ns or less frame exposure time; 3. Framing tubes and solid-state imaging devices having a fast image gating (shutter) time of 50 ns or less specially designed for cameras specified in Category Code 6A203.b.1. or 6A203.b.2.; 4. Plug-ins specially designed for use with framing cameras which have modular structures and that enable the performance specifications in Category Code 6A203.b.1. or 6A203.b.2.; 5. Synchronising electronics units, rotor assemblies consisting of turbines, mirrors and bearings specially designed for cameras specified in Category Code 6A203.b.1. or 6A203.b.2.; <p><u><i>Technical Note</i></u> <i>In Category Code 6A203.b., high speed single frame cameras can be used alone to produce a single image of a dynamic event, or several such cameras can be combined in a sequentially triggered system to produce multiple images of an event.</i></p>

<i>Category Code</i>	<i>Item Description</i>
	<p>c. Solid state or electron tube cameras, and specially designed components therefor, as follows:</p> <ol style="list-style-type: none"> 1. Solid-state cameras or electron tube cameras with a fast image gating (shutter) time of 50 ns or less; 2. Solid-state imaging devices and image intensifier tubes having a fast image gating (shutter) time of 50 ns or less specially designed for cameras specified in Category Code 6A203.c.1.; 3. Electro-optical shuttering devices (Kerr or Pockels cells) with a fast image gating (shutter) time of 50 ns or less; 4. Plug-ins specially designed for use with cameras which have modular structures and that enable the performance specifications in Category Code 6A203.c.1.; <p>d. Radiation-hardened TV cameras, or lenses therefor, specially designed or rated as radiation hardened to withstand a total radiation dose greater than 50×10^3 Gy (silicon) (5×10^6 rad (silicon)) without operational degradation.</p> <p><u>Technical Note</u> <i>The term Gy (silicon) refers to the energy in Joules per kilogram absorbed by an unshielded silicon sample when exposed to ionising radiation.</i></p>
6A205	<p>“Lasers”, “laser” amplifiers and oscillators, other than those specified in Category Codes 0B001.g.5., 0B001.h.6. and 6A005, as follows:</p> <p><u>N.B.</u> <i>For copper vapour lasers, see Category Code 6A005.b.</i></p> <p>a. Argon ion “lasers” having both of the following characteristics:</p> <ol style="list-style-type: none"> 1. Operating at wavelengths between 400 nm and 515 nm; <u>and</u> 2. An average output power greater than 40 W;

<i>Category Code</i>	<i>Item Description</i>
	<p>b. Tunable pulsed single-mode dye laser oscillators having all of the following characteristics:</p> <ol style="list-style-type: none"> 1. Operating at wavelengths between 300 nm and 800 nm; 2. An average output power greater than 1 W; 3. A repetition rate greater than 1 kHz; <u>and</u> 4. Pulse width less than 100 ns; <p>c. Tunable pulsed dye laser amplifiers and oscillators, having all of the following characteristics:</p> <ol style="list-style-type: none"> 1. Operating at wavelengths between 300 nm and 800 nm; 2. An average output power greater than 30 W; 3. A repetition rate greater than 1 kHz; <u>and</u> 4. Pulse width less than 100 ns; <p><i>Note</i> <i>Category Code 6A205.c. does not include single mode oscillators.</i></p> <p>d. Pulsed carbon dioxide “lasers” having all of the following characteristics:</p> <ol style="list-style-type: none"> 1. Operating at wavelengths between 9,000 nm and 11,000 nm; 2. A repetition rate greater than 250 Hz; 3. An average output power greater than 500 W; <u>and</u> 4. Pulse width of less than 200 ns; <p>e. Para-hydrogen Raman shifters designed to operate at 16 μm output wavelength and at a repetition rate greater than 250 Hz;</p> <p>f. Neodymium-doped (other than glass) “lasers” with an output wavelength between 1,000 nm and 1,100 nm having either of the following characteristics:</p> <ol style="list-style-type: none"> 1. Pulse-excited and Q-switched with a pulse duration equal to or more than 1 ns, and having either of the following characteristics: <ol style="list-style-type: none"> a. A single-transverse mode output with an average output power greater than 40 W; <u>or</u>

<i>Category Code</i>	<i>Item Description</i>
	<ul style="list-style-type: none"> b. A multiple-transverse mode output having an average power greater than 50 W; <u>or</u> 2. Incorporating frequency doubling to give an output wavelength between 500 nm and 550 nm with an average output power of more than 40 W; g. Pulsed carbon monoxide lasers, other than those specified in Category Code 6A005.d.2., having all of the following characteristics: <ul style="list-style-type: none"> 1. Operating at wavelengths between 5,000 nm and 6,000 nm; 2. A repetition rate greater than 250 Hz; 3. An average output power greater than 200 W; <u>and</u> 4. Pulse width of less than 200 ns.
6A225	<p>Velocity interferometers for measuring velocities exceeding 1 km/s during time intervals of less than 10 microseconds.</p> <p><u>Note</u> <i>Category Code 6A225 includes velocity interferometers such as VISARs (Velocity Interferometer Systems for Any Reflector), DLIs (Doppler Laser Interferometers) and PDV (Photonic Doppler Velocimeters) also known as Het-V (Heterodyne Velocimeters).</i></p>
6A226	<p>Pressure sensors, as follows:</p> <ul style="list-style-type: none"> a. Shock pressure gauges capable of measuring pressures greater than 10 GPa, including gauges made with manganin, ytterbium, and polyvinylidene bifluoride (PVBF, PVF₂); b. Quartz pressure transducers for pressures greater than 10 GPa.

<i>Category Code</i>	<i>Item Description</i>
6B	Test, Inspection and Production Equipment
6B004	<p>Optical equipment as follows:</p> <ol style="list-style-type: none"> a. Equipment for measuring absolute reflectance to an “accuracy” of equal to or better than 0.1% of the reflectance value; b. Equipment other than optical surface scattering measurement equipment, having an unobscured aperture of more than 10 cm, specially designed for the non-contact optical measurement of a non-planar optical surface figure (profile) to an “accuracy” of 2 nm or less (better) against the required profile. <p><i>Note</i> Category Code 6B004 does not include microscopes.</p>
6B007	Equipment to produce, align and calibrate land-based gravity meters with a static “accuracy” of better than 0.1 mGal.
6B008	<p>Pulse radar cross-section measurement systems having transmit pulse widths of 100 ns or less, and specially designed components therefor.</p> <p><i>N.B.</i> See also Category Code 6B108.</p>
6B108	<p>Systems, other than those specified in Category Code 6B008, specially designed for radar cross-section measurement usable for ‘missiles’ and their sub-systems.</p> <p><i>Technical Note</i> In Category Code 6B108, ‘missile’ means complete rocket systems and unmanned aerial vehicle systems capable of a range exceeding 300 km.</p>

<i>Category Code</i>	<i>Item Description</i>
6C	Materials
6C002	<p>Optical sensor materials as follows:</p> <ol style="list-style-type: none"> a. Elemental tellurium (Te) of purity levels of 99.9995% or more; b. Single crystals (including epitaxial wafers) of any of the following: <ol style="list-style-type: none"> 1. Cadmium zinc telluride (CdZnTe), with zinc content of less than 6% by 'mole fraction'; 2. Cadmium telluride (CdTe) of any purity level; <u>or</u> 3. Mercury cadmium telluride (HgCdTe) of any purity level. <p><i>Technical Note</i> <i>'Mole fraction' is defined as the ratio of moles of ZnTe to the sum of moles of CdTe and ZnTe present in the crystal.</i></p>
6C004	<p>Optical materials as follows:</p> <ol style="list-style-type: none"> a. Zinc selenide (ZnSe) and zinc sulphide (ZnS) "substrate blanks", produced by the chemical vapour deposition process and having any of the following characteristics: <ol style="list-style-type: none"> 1. A volume greater than 100 cm³; <u>or</u> 2. A diameter greater than 80 mm and a thickness of 20 mm or more; b. Electro-optic materials and non-linear optical materials, as follows: <ol style="list-style-type: none"> 1. Potassium titanyl arsenate (KTA) (59400-80-5); 2. Silver gallium selenide (AgGaSe₂, also known as AGSE) (12002-67-4); 3. Thallium arsenic selenide (Tl₃AsSe₃, also known as TAS) (16142-89-5); 4. Zinc germanium phosphide (ZnGeP₂, also known as ZGP, zinc germanium biphosphide or zinc germanium diphosphide); <u>or</u>

<i>Category Code</i>	<i>Item Description</i>
	<p>5. Gallium selenide (GaSe) (12024-11-2);</p> <p>c. Non-linear optical materials, other than those specified in Category Code 6C004.b., having any of the following characteristics:</p> <ol style="list-style-type: none"> 1. Having all of the following characteristics: <ol style="list-style-type: none"> a. Dynamic (also known as non-stationary) third order non-linear susceptibility ($\chi^{(3)}$, chi 3) of $10^{-6} \text{ m}^2/\text{V}^2$ or more; <u>and</u> b. Response time of less than 1 ms; <u>or</u> 2. Second order non-linear susceptibility ($\chi^{(2)}$, chi 2) of $3.3 \times 10^{-11} \text{ m/V}$ or more; <p>d. “Substrate blanks” of silicon carbide or beryllium beryllium (Be/Be) deposited materials, exceeding 300 mm in diameter or major axis length;</p> <p>e. Glass, including fused silica, phosphate glass, fluorophosphate glass, zirconium fluoride (ZrF_4) (7783-64-4) and hafnium fluoride (HfF_4) (13709-52-9) and having all of the following characteristics:</p> <ol style="list-style-type: none"> 1. A hydroxyl ion (OH^-) concentration of less than 5 ppm; 2. Integrated metallic purity levels of less than 1 ppm; <u>and</u> 3. High homogeneity (index of refraction variance) less than 5×10^{-6}; <p>f. Synthetically produced diamond material with an absorption of less than 10^{-5} cm^{-1} for wavelengths exceeding 200 nm but not exceeding 14,000 nm.</p>
6C005	<p>“Laser” materials as follows:</p> <p>a. Synthetic crystalline “laser” host material in unfinished form as follows:</p> <ol style="list-style-type: none"> 1. Titanium doped sapphire; 2. Not used;

<i>Category Code</i>	<i>Item Description</i>
	<p>b. Rare-earth-metal doped double-clad fibres having any of the following characteristics:</p> <ol style="list-style-type: none"> 1. Nominal “laser” wavelength of 975 nm to 1,150 nm, and having all of the following characteristics: <ol style="list-style-type: none"> a. Average core diameter equal to or greater than 25 µm; <u>and</u> b. Core ‘Numerical Aperture’ (‘NA’) less than 0.065; <u>or</u> <p><i>Note</i> <i>Category Code 6C005.b.1. does not include double-clad fibres having an inner glass cladding diameter exceeding 150 µm and not exceeding 300 µm.</i></p> 2. Nominal “laser” wavelength exceeding 1,530 nm, and having all of the following characteristics: <ol style="list-style-type: none"> a. Average core diameter equal to or greater than 20 µm; <u>and</u> b. Core ‘NA’ less than 0.1. <p><i>Technical Notes</i></p> <ol style="list-style-type: none"> 1. <i>For the purpose of Category Code 6C005, the core ‘Numerical Aperture’ (‘NA’) is measured at the emission wavelengths of the fibre.</i> 2. <i>Category Code 6C005.b. includes fibres assembled with end caps.</i>
6D	Software
6D001	“Software” specially designed for the “development” or “production” of equipment specified in Category Code 6A004, 6A005, 6A008 or 6B008.
6D002	“Software” specially designed for the “use” of equipment specified in Category Code 6A002.b., 6A008 or 6B008.

<i>Category Code</i>	<i>Item Description</i>
6D003	<p>Other “software” as follows:</p> <p>a. “Software” as follows:</p> <ol style="list-style-type: none"> 1. “Software” specially designed for acoustic beam forming for the “real-time processing” of acoustic data for passive reception using towed hydrophone arrays; 2. “Source code” for the “real-time processing” of acoustic data for passive reception using towed hydrophone arrays; 3. “Software” specially designed for acoustic beam forming for “real-time processing” of acoustic data for passive reception using bottom or bay cable systems; 4. “Source code” for “real-time processing” of acoustic data for passive reception using bottom or bay cable systems; 5. “Software” or “source code”, specially designed for all of the following: <ol style="list-style-type: none"> a. “Real-time processing” of acoustic data from sonar systems specified by Category Code 6A001.a.1.e.; <u>and</u> b. Automatically detecting, classifying and determining the location of divers or swimmers; <p><u>N.B.</u> <i>For diver detection “software” or “source code”, specially designed or modified for military use, see Division 2 of Part 1 of this Schedule.</i></p> <p>b. Not used;</p> <p>c. “Software” designed or modified for cameras incorporating “focal plane arrays” specified in Category Code 6A002.a.3.f. and designed or modified to remove a frame rate restriction and allow the camera to exceed the frame rate specified in Category Code 6A003.b.4. Note 3.a.;</p> <p>d. “Software” specially designed to maintain the alignment and phasing of segmented mirror systems consisting of mirror segments having a diameter or major axis length equal to or larger than 1 m;</p>

<i>Category Code</i>	<i>Item Description</i>
	<p>e. Not used;</p> <p>f. “Software” as follows:</p> <ol style="list-style-type: none"> 1. “Software” specially designed for magnetic and electric field “compensation systems” for magnetic sensors designed to operate on mobile platforms; 2. “Software” specially designed for magnetic and electric field anomaly detection on mobile platforms; 3. “Software” specially designed for “real-time processing” of electromagnetic data using underwater electromagnetic receivers specified in Category Code 6A006.e.; 4. “Source code” for “real-time processing” of electromagnetic data using underwater electromagnetic receivers specified in Category Code 6A006.e.; <p>g. “Software” specially designed to correct motional influences of gravity meters or gravity gradiometers;</p> <p>h. “Software” as follows:</p> <ol style="list-style-type: none"> 1. Air Traffic Control (ATC) “software” application “programs” designed to be hosted on general purpose computers located at Air Traffic Control centres and capable of accepting radar target data from more than four primary radars; 2. “Software” for the design or “production” of radomes and having all of the following characteristics: <ol style="list-style-type: none"> a. Specially designed to protect the “electronically steerable phased array antennae” specified in Category Code 6A008.e.; <u>and</u> b. Resulting in an antenna pattern having an ‘average side lobe level’ more than 40 dB below the peak of the main beam level. <p><i>Technical Note</i></p> <p><i>‘Average side lobe level’ in Category Code 6D003.h.2.b. is measured over the entire array excluding the angular extent of the main beam and the first two side lobes on either side of the main beam.</i></p>

<i>Category Code</i>	<i>Item Description</i>
6D102	“Software” specially designed or modified for the “use” of goods specified in Category Code 6A108.
6D103	<p>“Software” which processes post-flight, recorded data, enabling determination of vehicle position throughout its flight path, specially designed or modified for ‘missiles’.</p> <p><i>Technical Note</i> <i>In Category Code 6D103, ‘missile’ means complete rocket systems and unmanned aerial vehicle systems capable of a range exceeding 300 km.</i></p>
6D203	“Software” specially designed to enhance or release the performance of cameras or imaging devices to meet the characteristics of Category Codes 6A203.a. to 6A203.c.
6E	Technology
6E001	“Technology” (according to the General Technology Note) for the “development” of equipment, materials or “software” specified in Category 6A, 6B, 6C or 6D.
6E002	“Technology” (according to the General Technology Note) for the “production” of equipment or materials specified in Category 6A, 6B or 6C.
6E003	<p>Other “technology”, as follows:</p> <p>a. “Technology” as follows:</p> <ol style="list-style-type: none"> 1. Optical surface coating and treatment “technology”, “required” to achieve an ‘optical thickness’ uniformity of 99.5% or better for optical coatings 500 mm or more in diameter or major axis length and with a total loss (absorption and scatter) of less than 5×10^{-3}; <p><i>N.B.</i> <i>See also Category Code 2E003.f.</i></p>

Category Code	Item Description
	<p data-bbox="608 454 791 488"><u>Technical Note</u></p> <p data-bbox="608 495 1260 595"><i>'Optical thickness' is the mathematical product of the index of refraction and the physical thickness of the coating.</i></p> <p data-bbox="544 611 1260 745">2. Optical fabrication "technology" using single point diamond turning techniques to produce surface finish "accuracies" of better than 10 nm rms on non-planar surfaces exceeding 0.5 m²;</p> <p data-bbox="480 761 1260 925">b. "Technology" "required" for the "development", "production" or "use" of specially designed diagnostic instruments or targets in test facilities for "SHPL" testing or testing or evaluation of materials irradiated by "SHPL" beams.</p>
6E101	<p data-bbox="480 999 1260 1126">"Technology" (according to the General Technology Note) for the "use" of equipment or "software" specified in Category Code 6A002, 6A007.b. and .c., 6A008, 6A102, 6A107, 6A108, 6B108, 6D102 or 6D103.</p> <p data-bbox="480 1149 539 1182"><u>Note</u></p> <p data-bbox="480 1189 1260 1290"><i>Category Code 6E101 only specifies "technology" for equipment specified in Category Codes 6A002, 6A007 and 6A008 when it is designed for airborne applications and are usable in "missiles".</i></p>
6E201	<p data-bbox="480 1350 1260 1514">"Technology" (according to the General Technology Note) for the "use" of equipment specified in Category Code 6A003, 6A005.a.2., 6A005.b.2., 6A005.b.3., 6A005.b.4., 6A005.b.6., 6A005.c.2., 6A005.d.3.c., 6A005.d.4.c., 6A202, 6A203, 6A205, 6A225 or 6A226.</p> <p data-bbox="480 1536 539 1570"><u>Note</u></p> <p data-bbox="480 1576 1260 1704"><i>Category Code 6E201 only specifies "technology" for cameras specified in Category Code 6A003 if the cameras are also specified by any of the control parameters of Category Code 6A203.</i></p>

<i>Category Code</i>	<i>Item Description</i>
6E203	“Technology”, in the form of codes or keys, to enhance or release the performance of cameras or imaging devices to meet the characteristics of Category Codes 6A203.a. to 6A203.c.

<i>Category Code</i>	<i>Item Description</i>
CATEGORY 7 — NAVIGATION AND AVIONICS	
7A	Systems, Equipment and Components
	<p data-bbox="475 555 533 584"><u><i>N.B.</i></u> <i>For automatic pilots for underwater vehicles, see Category 8. For radar, see Category 6.</i></p>
7A001	<p data-bbox="475 734 1262 792">Accelerometers as follows and specially designed components therefor:</p> <p data-bbox="475 815 533 844"><u><i>N.B.</i></u> <i>See also Category Code 7A101.</i> <i>For angular or rotational accelerometers, see Category Code 7A001.b.</i></p> <ol data-bbox="475 981 1262 1796" style="list-style-type: none"> <li data-bbox="475 981 1262 1039">a. Linear accelerometers having any of the following characteristics: <ol style="list-style-type: none"> <li data-bbox="539 1061 1262 1397">1. Specified to function at linear acceleration levels less than or equal to 15 g, and having any of the following characteristics: <ol style="list-style-type: none"> <li data-bbox="624 1182 1262 1285">a. A “bias” “stability” of less (better) than 130 micro g with respect to a fixed calibration value over a period of one year; <u>or</u> <li data-bbox="624 1301 1262 1397">b. A “scale factor” “stability” of less (better) than 130 ppm with respect to a fixed calibration value over a period of one year; <li data-bbox="539 1413 1262 1688">2. Specified to function at linear acceleration levels exceeding 15 g but less than or equal to 100 g, and having all of the following characteristics: <ol style="list-style-type: none"> <li data-bbox="624 1532 1262 1599">a. A “bias” “repeatability” of less (better) than 1,250 micro g over a period of one year; <u>and</u> <li data-bbox="624 1615 1262 1688">b. A “scale factor” “repeatability” of less (better) than 1,250 ppm over a period of one year; <u>or</u> <li data-bbox="539 1704 1262 1796">3. Designed for use in inertial navigation or guidance systems and specified to function at linear acceleration levels exceeding 100 g;

<i>Category Code</i>	<i>Item Description</i>
7A002	<p data-bbox="539 454 600 488"><u>Note</u></p> <p data-bbox="539 495 1262 591"><i>Category Codes 7A001.a.1. and 7A001.a.2. do not include accelerometers limited to measurement of only vibration or shock.</i></p> <p data-bbox="475 611 1262 678">b. Angular or rotational accelerometers, specified to function at linear acceleration levels exceeding 100 g.</p> <p data-bbox="475 745 1262 813">Gyros or angular rate sensors, having any of the following characteristics, and specially designed components therefor:</p> <p data-bbox="475 831 536 864"><u>N.B.</u></p> <p data-bbox="475 871 852 904"><i>See also Category Code 7A102.</i></p> <p data-bbox="475 920 1262 987"><i>For angular or rotational accelerometers, see Category Code 7A001.b.</i></p> <p data-bbox="475 1003 1262 1099">a. Specified to function at linear acceleration levels less than or equal to 100 g, and having any of the following characteristics:</p> <ol data-bbox="539 1122 1262 1417" style="list-style-type: none"> <li data-bbox="539 1122 1262 1189">1. A rate range of less than 500 degrees per second, and having any of the following characteristics: <ol data-bbox="624 1205 1262 1417" style="list-style-type: none"> <li data-bbox="624 1205 1262 1339">a. A “bias” “stability” of less (better) than 0.5 degree per hour, when measured in a 1 g environment over a period of one month, and with respect to a fixed calibration value; <u>or</u> <li data-bbox="624 1355 1262 1417">b. An “angle random walk” of less (better) than or equal to 0.0035 degree per square root hour; <u>or</u> <p data-bbox="687 1440 748 1473"><u>Note</u></p> <p data-bbox="687 1480 1262 1547"><i>Category Code 7A002.a.1.b. does not include “spinning mass gyros”.</i></p> <ol data-bbox="539 1570 1262 1861" style="list-style-type: none"> <li data-bbox="539 1570 1262 1637">2. A rate range greater than or equal to 500 degrees per second, and having any of the following characteristics: <ol data-bbox="624 1653 1262 1861" style="list-style-type: none"> <li data-bbox="624 1653 1262 1787">a. A “bias” “stability” of less (better) than 4 degrees per hour, when measured in a 1 g environment over a period of three minutes, and with respect to a fixed calibration value; <u>or</u> <li data-bbox="624 1803 1262 1861">b. An “angle random walk” of less (better) than or equal to 0.1 degree per square root hour; <u>or</u>

<i>Category Code</i>	<i>Item Description</i>
7A003	<p style="text-align: center;"><u>Note</u> Category Code 7A002.a.2.b. does not include “spinning mass gyros”.</p> <p>b. Specified to function at linear acceleration levels exceeding 100 g.</p> <p>‘Inertial measurement equipment or systems’, having any of the following characteristics:</p> <p><u>N.B.</u> See also Category Code 7A103.</p> <p><u>Note 1</u> ‘Inertial measurement equipment or systems’ incorporate accelerometers or gyroscopes to measure changes in velocity and orientation in order to determine or maintain heading or position without requiring an external reference once aligned. ‘Inertial measurement equipment or systems’ include:</p> <ul style="list-style-type: none"> – Attitude and Heading Reference Systems (AHRSSs); – Gyrocompasses; – Inertial Measurement Units (IMUs); – Inertial Navigation Systems (INSs); – Inertial Reference Systems (IRSs); – Inertial Reference Units (IRUs). <p><u>Note 2</u> Category Code 7A003 does not include ‘inertial measurement equipment or systems’ which are certified for use on “civil aircraft” by civil authorities of one or more “participating states”.</p> <p><u>Technical Note</u> ‘Positional aiding references’ independently provide position, and include:</p> <p>a. Global Navigation Satellite Systems (GNSS);</p> <p>b. “Data-Based Referenced Navigation” (“DBRN”).</p>

<i>Category Code</i>	<i>Item Description</i>
	<p>a. Designed for “aircraft”, land vehicles or vessels, providing position without the use of ‘positional aiding references’, and having any of the following accuracies subsequent to normal alignment:</p> <ol style="list-style-type: none"> 1. 0.8 nautical miles per hour (nm/hr) “Circular Error Probable” (“CEP”) rate or less (better); 2. 0.5% distanced travelled “CEP” or less (better); <u>or</u> 3. Total drift of 1 nautical mile “CEP” or less (better) in a 24-hour period; <p><i>Technical Note</i></p> <p><i>The performance parameters in Category Codes 7A003.a.1., 7A003.a.2. and 7A003.a.3. typically apply to ‘inertial measurement equipment or systems’ designed for “aircraft”, vehicles and vessels, respectively. These parameters result from the utilisation of specialised non-positional aiding references (e.g. altimeter, odometer, velocity log). As a consequence, the specified performance values cannot be readily converted between these parameters. Equipment designed for multiple platforms are evaluated against each applicable Category Code 7A003.a.1., 7A003.a.2. or 7A003.a.3.</i></p> <p>b. Designed for “aircraft”, land vehicles or vessels, with an embedded ‘positional aiding reference’ and providing position after loss of all ‘positional aiding references’ for a period of up to 4 minutes, having an “accuracy” of less (better) than 10 meters “CEP”;</p> <p><i>Technical Note</i></p> <p><i>Category Code 7A003.b. refers to systems in which ‘inertial measurement equipment or systems’ and other independent ‘positional aiding references’ are built into a single unit (i.e. embedded) in order to achieve improved performance.</i></p>

<i>Category Code</i>	<i>Item Description</i>
	<p>c. Designed for “aircraft”, land vehicles or vessels, providing heading or True North determination and having any of the following characteristics:</p> <ol style="list-style-type: none"> 1. A maximum operating angular rate less (lower) than 500 deg/s and a heading “accuracy” without the use of ‘positional aiding references’ equal to or less (better) than 0.07 deg sec(Lat) (equivalent to 6 arc minutes rms at 45 degrees latitude); <u>or</u> 2. A maximum operating angular rate equal to or greater (higher) than 500 deg/s and a heading “accuracy” without the use of ‘positional aiding references’ equal to or less (better) than 0.2 deg sec(Lat) (equivalent to 17 arc minutes rms at 45 degrees latitude); <u>or</u> <p>d. Providing acceleration measurements or angular rate measurements, in more than one dimension, and having any of the following characteristics:</p> <ol style="list-style-type: none"> 1. Performance specified by Category Code 7A001 or 7A002 along any axis, without the use of any aiding references; <u>or</u> 2. Being “space-qualified” and providing angular rate measurements having an “angle random walk” along any axis of less (better) than or equal to 0.1 degree per square root hour. <p><u>Note</u> <i>Category Code 7A003.d.2. does not include ‘inertial measurement equipment or systems’ that contain “spinning mass gyros” as the only type of gyro.</i></p>
7A004	<p>‘Star trackers’ and components therefor, as follows:</p> <p><u>N.B.</u> <i>See also Category Code 7A104.</i></p> <p>a. ‘Star trackers’ with a specified azimuth “accuracy” of equal to or less (better) than 20 seconds of arc throughout the specified lifetime of the equipment;</p>

<i>Category Code</i>	<i>Item Description</i>
7A005	<p>b. Components specially designed for equipment specified in Category Code 7A004.a. as follows:</p> <ol style="list-style-type: none"> 1. Optical heads or baffles; 2. Data processing units. <p><i>Technical Note</i> ‘Star trackers’ are also referred to as stellar attitude sensors or gyro-astro compasses.</p> <p>Global Navigation Satellite Systems (GNSS) receiving equipment having any of the following characteristics and specially designed components therefor:</p> <p><i>N.B.</i> See also Category Code 7A105. For equipment specially designed for military use, see Division 2 of Part 1 of this Schedule.</p> <ol style="list-style-type: none"> a. Employing a decryption algorithm specially designed or modified for government use to access the ranging code for position and time; <u>or</u> b. Employing ‘adaptive antenna systems’. <p><i>Note</i> Category Code 7A005.b. does not include GNSS receiving equipment that only uses components designed to filter, switch or combine signals from multiple omni-directional antennae that do not implement adaptive antenna techniques.</p> <p><i>Technical Note</i> For the purpose of Category Code 7A005.b., ‘adaptive antenna systems’ dynamically generate one or more spatial nulls in an antenna array pattern by signal processing in the time domain or frequency domain.</p>

<i>Category Code</i>	<i>Item Description</i>
7A006	<p>Airborne altimeters operating at frequencies other than 4.2 GHz to 4.4 GHz inclusive and having any of the following characteristics:</p> <p><u>N.B.</u> <i>See also Category Code 7A106.</i></p> <p>a. “Power management”; <u>or</u></p> <p>b. Using phase shift key modulation.</p>
7A008	<p>Underwater sonar navigation systems using doppler velocity or correlation velocity logs integrated with a heading source and having a positioning “accuracy” of equal to or less (better) than 3% of distance travelled “Circular Error Probable” (“CEP”) and specially designed components therefor.</p> <p><u>Note</u> <i>Category Code 7A008 does not include systems specially designed for installation on surface vessels or systems requiring acoustic beacons or buoys to provide positioning data.</i></p> <p><u>N.B.</u> <i>See Category Code 6A001.a. for acoustic systems, and Category Code 6A001.b. for correlation-velocity and Doppler-velocity sonar log equipment.</i> <i>See Category Code 8A002 for other marine systems.</i></p>
7A101	<p>Linear accelerometers, other than those specified in Category Code 7A001, designed for use in inertial navigation systems or in guidance systems of all types, usable in ‘missiles’, having all of the following characteristics, and specially designed components therefor:</p> <p>a. A “bias” “repeatability” of less (better) than 1,250 micro g; <u>and</u></p> <p>b. A “scale factor” “repeatability” of less (better) than 1,250 ppm.</p> <p><u>Note</u> <i>Category Code 7A101 does not include accelerometers specially designed and developed as Measurement While Drilling (MWD) Sensors for use in downhole well service operations.</i></p>

Category Code	Item Description
	<p><u>Technical Notes</u></p> <ol style="list-style-type: none"> 1. In Category Code 7A101, 'missile' means complete rocket systems and unmanned aerial vehicle systems capable of a range exceeding 300 km. 2. In Category Code 7A101, the measurement of "bias" and "scale factor" refers to a one sigma standard deviation with respect to a fixed calibration over a period of one year.
7A102	<p>All types of gyros, other than those specified in Category Code 7A002, usable in 'missiles', with a rated "drift rate" 'stability' of less than 0.5° (1 sigma or rms) per hour in a 1 g environment and specially designed components therefor.</p> <p><u>Technical Notes</u></p> <ol style="list-style-type: none"> 1. In Category Code 7A102, 'missile' means complete rocket systems and unmanned aerial vehicle systems capable of a range exceeding 300 km. 2. In Category Code 7A102, 'stability' is defined as a measure of the ability of a specific mechanism or performance coefficient to remain invariant when continuously exposed to a fixed operating condition (IEEE Std 528-2001 paragraph 2.247).
7A103	<p>Instrumentation, navigation equipment and systems, other than those specified in Category Code 7A003, as follows; and specially designed components therefor:</p> <ol style="list-style-type: none"> a. Inertial or other equipment, using accelerometers or gyros as follows, and systems incorporating such equipment: <ol style="list-style-type: none"> 1. Accelerometers specified in Category Code 7A001.a.3., 7A001.b. or 7A101 or gyros specified in Category Code 7A002 or 7A102; <u>or</u> 2. Accelerometers specified in Category Code 7A001.a.1. or 7A001.a.2., designed for use in inertial navigation systems or in guidance systems of all types, and usable in 'missiles';

Category Code	Item Description
	<p data-bbox="539 454 600 488"><u>Note</u></p> <p data-bbox="539 495 1268 696"><i>Category Code 7A103.a.2. does not include equipment containing accelerometers specified in Category Code 7A001.a.1. or 7A001.a.2. where such accelerometers are specially designed and developed as MWD (Measurement While Drilling) sensors for use in down-hole well services operations.</i></p> <p data-bbox="475 712 1268 929"> b. Integrated flight instrument systems which include gyrostabilisers or automatic pilots, designed or modified for use in ‘missiles’; c. ‘Integrated navigation systems’, designed or modified for ‘missiles’ and capable of providing a navigational accuracy of 200 m Circle of Equal Probability or less; </p> <p data-bbox="539 945 724 978"><u>Technical Note</u></p> <p data-bbox="539 985 1268 1055"><i>An ‘integrated navigation system’ typically incorporates the following components:</i></p> <p data-bbox="539 1061 1268 1379"> a. <i>An inertial measurement device (e.g. an Attitude and Heading Reference System, inertial reference unit, or inertial navigation system);</i> b. <i>One or more external sensors used to update the position and/or velocity, either periodically or continuously throughout the flight (e.g. satellite navigation receiver, radar altimeter, and/or Doppler radar); and</i> c. <i>Integration hardware and software.</i> </p> <p data-bbox="475 1395 1268 1767"> d. Three axis magnetic heading sensors, designed or modified to be integrated with flight control and navigation systems, other than those specified in Category Code 6A006, having all of the following characteristics, and specially designed components therefor: <ol data-bbox="539 1581 1268 1767" style="list-style-type: none"> <li data-bbox="539 1581 1268 1650">1. Internal tilt compensation in pitch (± 90 degrees) and roll (± 180 degrees) axes; <u>and</u> <li data-bbox="539 1666 1268 1767">2. Capable of providing azimuthal accuracy better (less) than 0.5 degrees rms at latitude of ± 80 degrees, reference to local magnetic field. </p>

<i>Category Code</i>	<i>Item Description</i>
	<p data-bbox="539 456 600 488"><u>Note</u></p> <p data-bbox="539 497 1262 595"><i>Flight control and navigation systems in Category Code 7A103.d. include gyrostabilisers, automatic pilots and inertial navigation systems.</i></p> <p data-bbox="475 613 660 645"><u>Technical Note</u></p> <p data-bbox="475 654 1262 752"><i>In Category Code 7A103, 'missile' means complete rocket systems and unmanned aerial vehicle systems capable of a range exceeding 300 km.</i></p>
7A104	Gyro-astro compasses and other devices, other than those specified in Category Code 7A004, which derive position or orientation by means of automatically tracking celestial bodies or satellites and specially designed components therefor.
7A105	<p data-bbox="475 1025 1262 1155">Receiving equipment for Global Navigation Satellite Systems (GNSS; e.g. GPS, GLONASS, or Galileo), other than those specified in Category Code 7A005, having any of the following characteristics, and specially designed components therefor:</p> <p data-bbox="475 1173 1262 1729"> a. Designed or modified for use in space launch vehicles specified in Category Code 9A004, sounding rockets specified in Category Code 9A104 or unmanned aerial vehicles specified in Category Code 9A012 or 9A112.a.; <u>or</u> b. Designed or modified for airborne applications and having any of the following characteristics: <ol data-bbox="539 1406 1262 1729" style="list-style-type: none"> 1. Capable of providing navigation information at speeds in excess of 600 m/s; 2. Employing decryption, designed or modified for military or governmental services, to gain access to GNSS secured signal/data; <u>or</u> 3. Being specially designed to employ anti-jam features (e.g. null steering antenna or electronically steerable antenna) to function in an environment of active or passive countermeasures. </p>

<i>Category Code</i>	<i>Item Description</i>
	<p><u>Note</u> <i>Category Codes 7A105.b.2. and 7A105.b.3. do not include equipment designed for commercial, civil or 'Safety of Life' (e.g. data integrity, flight safety) GNSS services.</i></p>
7A106	<p>Altimeters, other than those specified in Category Code 7A006, of radar or laser radar type, designed or modified for use in space launch vehicles specified in Category Code 9A004 or sounding rockets specified in Category Code 9A104.</p>
7A115	<p>Passive sensors for determining bearing to specific electromagnetic source (direction finding equipment) or terrain characteristics, designed or modified for use in space launch vehicles specified in Category Code 9A004 or sounding rockets specified in Category Code 9A104.</p>
	<p><u>Note</u> <i>Category Code 7A115 includes sensors for the following equipment:</i></p> <ul style="list-style-type: none"> a. <i>Terrain contour mapping equipment;</i> b. <i>Imaging sensor equipment (both active and passive);</i> c. <i>Passive interferometer equipment.</i>
7A116	<p>Flight control systems and servo valves, as follows; designed or modified for use in space launch vehicles specified in Category Code 9A004 or sounding rockets specified in Category Code 9A104 or "missiles":</p> <ul style="list-style-type: none"> a. <i>Pneumatic, hydraulic, mechanical, electro-optical, or electro-mechanical flight control systems (including fly-by-wire and fly-by-light systems);</i> b. <i>Attitude control equipment;</i> c. <i>Flight control servo valves designed or modified for the systems specified in Category Code 7A116.a. or 7A116.b., and designed or modified to operate in a vibration environment greater than 10 g rms between 20 Hz and 2 kHz.</i>

<i>Category Code</i>	<i>Item Description</i>
7A117	“Guidance sets”, usable in “missiles” capable of achieving system accuracy of 3.33% or less of the range (e.g. a “CEP” of 10 km or less at a range of 300 km).
7B	Test, Inspection and Production Equipment
7B001	Test, calibration or alignment equipment, specially designed for equipment specified in Category 7A.
	<p><u>Note</u></p> <p>Category Code 7B001 does not include test, calibration or alignment equipment for ‘Maintenance Level I’ or ‘Maintenance Level II’.</p>
	<p><u>Technical Notes</u></p> <p>1. <u>‘Maintenance Level I’</u></p> <p>The failure of an inertial navigation unit is detected on the “aircraft” by indications from the Control and Display Unit (CDU) or by the status message from the corresponding sub-system. By following the manufacturer’s manual, the cause of the failure may be localised at the level of the malfunctioning Line Replaceable Unit (LRU). The operator then removes the LRU and replaces it with a spare.</p> <p>2. <u>‘Maintenance Level II’</u></p> <p>The defective LRU is sent to the maintenance workshop (the manufacturer’s or that of the operator responsible for level II maintenance). At the maintenance workshop, the malfunctioning LRU is tested by various appropriate means to verify and localise the defective Shop Replaceable Assembly (SRA) module responsible for the failure. This SRA is removed and replaced by an operative spare. The defective SRA (or possibly the complete LRU) is then shipped to the manufacturer. ‘Maintenance Level II’ does not include the disassembly or repair of controlled accelerometers or gyro sensors.</p>

<i>Category Code</i>	<i>Item Description</i>
7B002	<p>Equipment specially designed to characterise mirrors for ring “laser” gyros, as follows:</p> <p><u>N.B.</u></p> <p><i>See also Category Code 7B102.</i></p> <ol style="list-style-type: none"> a. Scatterometers having a measurement “accuracy” of 10 ppm or less (better); b. Profilometers having a measurement “accuracy” of 0.5 nm (5 angstrom) or less (better).
7B003	<p>Equipment specially designed for the “production” of equipment specified in Category 7A.</p> <p><u>Note</u></p> <p><i>Category Code 7B003 includes:</i></p> <ul style="list-style-type: none"> – Gyro tuning test stations; – Gyro dynamic balance stations; – Gyro run-in/motor test stations; – Gyro evacuation and fill stations; – Centrifuge fixtures for gyro bearings; – Accelerometer axis align stations; – Fibre optic gyro coil winding machines.
7B102	<p>Reflectometers specially designed to characterise mirrors, for “laser” gyros, having a measurement accuracy of 50 ppm or less (better).</p>
7B103	<p>“Production facilities” and “production equipment” as follows:</p> <ol style="list-style-type: none"> a. “Production facilities” specially designed for equipment specified in Category Code 7A117; b. “Production equipment”, and other test, calibration and alignment equipment, other than that specified in Category Codes 7B001 to 7B003, designed or modified to be used with equipment specified in Category 7A.

<i>Category Code</i>	<i>Item Description</i>
7C	Materials None.
7D	Software
7D001	“Software” specially designed or modified for the “development” or “production” of equipment specified in Category 7A or 7B.
7D002	“Source code” for the operation or maintenance of any inertial navigation equipment, including inertial equipment not specified in Category Code 7A003 or 7A004, or Attitude and Heading Reference Systems (‘AHRs’). <i>Note</i> <i>Category Code 7D002 does not include “source code” for the “use” of gimballed ‘AHRs’.</i> <i>Technical Note</i> <i>‘AHRs’ generally differ from Inertial Navigation Systems (INS) in that an ‘AHRs’ provides attitude and heading information and normally does not provide the acceleration, velocity and position information associated with an INS.</i>
7D003	Other “software” as follows: a. “Software” specially designed or modified to improve the operational performance or reduce the navigational error of systems to the levels specified in Category Code 7A003, 7A004 or 7A008; b. “Source code” for hybrid integrated systems which improves the operational performance or reduces the navigational error of systems to the level specified in Category Code 7A003 or 7A008 by continuously combining heading data with any of the following: 1. Doppler radar or sonar velocity data; 2. Global Navigation Satellite Systems (GNSS) reference data; <u>or</u>

<i>Category Code</i>	<i>Item Description</i>
7D004	<p>3. Data from “Data-Based Referenced Navigation” (“DBRN”) systems;</p> <p>c. Not used;</p> <p>d. Not used;</p> <p>e. Computer-Aided-Design (CAD) “software” specially designed for the “development” of “active flight control systems”, helicopter multi-axis fly-by-wire or fly-by-light controllers or helicopter “circulation-controlled anti-torque or circulation-controlled direction control systems”, whose “technology” is specified in Category Code 7E004.b., 7E004.c.1. or 7E004.c.2.</p> <p>“Source code” incorporating “development” “technology” specified in Category Code 7E004.a.2., 7E004.a.3., 7E004.a.5., 7E004.a.6. or 7E004.b., for any of the following:</p> <p>a. Digital flight management systems for “total control of flight”;</p> <p>b. Integrated propulsion and flight control systems;</p> <p>c. “Fly-by-wire systems” or “fly-by-light systems”;</p> <p>d. Fault-tolerant or self-reconfiguring “active flight control systems”;</p> <p>e. Not used;</p> <p>f. Air data systems based on surface static data; <u>or</u></p> <p>g. Three dimensional displays.</p> <p><u>Note</u> <i>Category Code 7D004 does not include “source code” associated with common computer elements and utilities (e.g. input signal acquisition, output signal transmission, computer program and data loading, built-in test, task scheduling mechanisms) not providing a specific flight control system function.</i></p>

<i>Category Code</i>	<i>Item Description</i>
7D005	“Software” specially designed to decrypt Global Navigation Satellite Systems (GNSS) ranging code designed for government use.
7D101	“Software” specially designed or modified for the “use” of equipment specified in Category Code 7A001 to 7A006, 7A101 to 7A106, 7A115, 7A116.a., 7A116.b., 7B001, 7B002, 7B003, 7B102 or 7B103.
7D102	<p>Integration “software” as follows:</p> <ol style="list-style-type: none"> a. Integration “software” for the equipment specified in Category Code 7A103.b.; b. Integration “software” specially designed for the equipment specified in Category Code 7A003 or 7A103.a.; c. Integration “software” designed or modified for the equipment specified in Category Code 7A103.c. <p><u>Note</u> <i>A common form of integration “software” employs Kalman filtering.</i></p>
7D103	<p>“Software” specially designed for modelling or simulation of the “guidance sets” specified in Category Code 7A117 or for their design integration with the space launch vehicles specified in Category Code 9A004 or sounding rockets specified in Category Code 9A104.</p> <p><u>Note</u> <i>“Software” specified in Category Code 7D103 remains within the description in that Category when combined with specially designed hardware specified in Category Code 4A102.</i></p>
7D104	“Software” specially designed or modified for the operation or maintenance of “guidance sets” specified in Category Code 7A117.

Category Code	Item Description
	<p><u>Note</u> <i>Category Code 7D104 includes “software”, specially designed or modified to enhance the performance of “guidance sets” to achieve or exceed the accuracy specified in Category Code 7A117.</i></p>
7E	Technology
7E001	<p>“Technology” (according to the General Technology Note) for the “development” of equipment or “software”, specified in Category 7A, 7B or Category Codes 7D001, 7D002, 7D003, 7D005 and 7D101 to 7D103.</p>
	<p><u>Note</u> <i>Category Code 7E001 includes key management “technology” exclusively for equipment specified in Category Code 7A005.a.</i></p>
7E002	<p>“Technology” (according to the General Technology Note) for the “production” of equipment specified in Category 7A or 7B.</p>
7E003	<p>“Technology” (according to the General Technology Note) for the repair, refurbishing or overhaul of equipment specified in Category Codes 7A001 to 7A004.</p>
	<p><u>Note</u> <i>Category Code 7E003 does not include maintenance “technology” directly associated with calibration, removal or replacement of damaged or unserviceable LRUs and SRAs of a “civil aircraft” as described in ‘Maintenance Level I’ or ‘Maintenance Level II’.</i></p>
	<p><u>N.B.</u> <i>See Technical Notes to Category Code 7B001.</i></p>
7E004	<p>Other “technology” as follows:</p> <ol style="list-style-type: none"> a. “Technology” for the “development” or “production” of any of the following: <ol style="list-style-type: none"> 1. Not used; 2. Air data systems based on surface static data only, i.e. which dispense with conventional air data probes;

<i>Category Code</i>	<i>Item Description</i>
	<ol style="list-style-type: none"> 3. Three dimensional displays for “aircraft”; 4. Not used; 5. Electric actuators (i.e. electromechanical, electrohydrostatic and integrated actuator package) specially designed for “primary flight control”; 6. “Flight control optical sensor array” specially designed for implementing “active flight control systems”; <u>or</u> 7. “DBRN” systems designed to navigate underwater, using sonar or gravity databases, that provide a positioning “accuracy” equal to or less (better) than 0.4 nautical miles; <p>b. “Development” “technology”, as follows, for “active flight control systems” (including “fly-by-wire systems” or “fly-by-light systems”):</p> <ol style="list-style-type: none"> 1. Photonic-based “technology” for sensing “aircraft” or flight control component state, transferring flight control data, or commanding actuator movement, “required” for “fly-by-light systems” “active flight control systems”; 2. Not used; 3. Real-time algorithms to analyse component sensor information to predict and preemptively mitigate impending degradation and failures of components within an “active flight control system”; <p><i>Note</i> <i>Category Code 7E004.b.3. does not include algorithms for purpose of off-line maintenance.</i></p> <ol style="list-style-type: none"> 4. Real-time algorithms to identify component failures and reconfigure force and moment controls to mitigate “active flight control system” degradations and failures; <p><i>Note</i> <i>Category Code 7E004.b.4. does not include algorithms for the elimination of fault effects through comparison of redundant data sources, or off-line pre-planned responses to anticipated failures.</i></p>

<i>Category Code</i>	<i>Item Description</i>
	<p>5. Integration of digital flight control, navigation and propulsion control data, into a digital flight management system for “total control of flight”;</p> <p><i>Note</i> <i>Category Code 7E004.b.5. does not include:</i></p> <ul style="list-style-type: none"> a. “Development” “technology” for integration of digital flight control, navigation and propulsion control data, into a digital flight management system for “flight path optimisation”; b. “Development” “technology” for “aircraft” flight instrument systems integrated solely for VOR, DME, ILS or MLS navigation or approaches. <p>6. Not used;</p> <p>7. “Technology” “required” for deriving the functional requirements for “fly-by-wire systems” having all of the following characteristics:</p> <ul style="list-style-type: none"> a. ‘Inner-loop’ airframe stability controls requiring loop closure rates of 40 Hz or greater; <u>and</u> <p><i>Technical Note</i> ‘Inner-loop’ refers to functions of “active flight control systems” that automate airframe stability controls.</p> <ul style="list-style-type: none"> b. Having any of the following characteristics: <ul style="list-style-type: none"> 1. Corrects an aerodynamically unstable airframe, measured at any point in the design flight envelope, that would lose recoverable control if not corrected within 0.5 seconds; 2. Couples controls in two or more axes while compensating for ‘abnormal changes in aircraft state’;

<i>Category Code</i>	<i>Item Description</i>
	<p data-bbox="756 454 938 488"><u>Technical Note</u></p> <p data-bbox="756 495 1268 629"><i>‘Abnormal changes in aircraft state’ include in-flight structural damage, loss of engine thrust, disabled control surface, or destabilising shifts in cargo load.</i></p> <p data-bbox="687 645 1268 712">3. Performs the functions specified in Category Code 7E004.b.5.; <u>or</u></p> <p data-bbox="756 728 815 761"><u>Note</u></p> <p data-bbox="756 768 1268 835"><i>Category Code 7E004.b.7.b.3. does not include autopilots.</i></p> <p data-bbox="687 851 1268 1052">4. Enables “aircraft” to have a stable controlled flight, other than during take-off or landing, at greater than 18 degrees angle of attack, 15 degrees side slip, 15 degrees/second pitch or yaw rate, or 90 degrees/second roll rate;</p> <p data-bbox="539 1068 1268 1169">8. “Technology” “required” for deriving the functional requirements for “fly-by-wire systems” to achieve all of the following:</p> <p data-bbox="624 1184 1268 1285">a. No loss of control of the “aircraft” in the event of a consecutive sequence of any two individual faults within the “fly-by-wire system”; <u>and</u></p> <p data-bbox="624 1301 1268 1402">b. Probability of loss of control of the “aircraft” being less (better) than 1×10^{-9} failures per flight hour;</p> <p data-bbox="539 1417 598 1451"><u>Note</u></p> <p data-bbox="539 1458 1268 1659"><i>Category Code 7E004.b. does not include technology associated with common computer elements and utilities (e.g. input signal acquisition, output signal transmission, computer program and data loading, built-in test, task scheduling mechanisms) not providing a specific flight control system function.</i></p> <p data-bbox="475 1675 1268 1742">c. “Technology” for the “development” of helicopter systems, as follows:</p> <p data-bbox="539 1758 1268 1859">1. Multi-axis fly-by-wire or fly-by-light controllers, which combine the functions of at least two of the following into one controlling element:</p>

<i>Category Code</i>	<i>Item Description</i>
	<ul style="list-style-type: none"> a. Collective controls; b. Cyclic controls; c. Yaw controls; 2. "Circulation-controlled anti-torque or circulation-controlled direction control systems"; 3. Rotor blades incorporating "variable geometry airfoils", for use in systems using individual blade control.
7E101	<p>"Technology" (according to the General Technology Note) for the "use" of equipment specified in Category Codes 7A001 to 7A006, 7A101 to 7A106, 7A115 to 7A117, 7B001, 7B002, 7B003, 7B102, 7B103 and 7D101 to 7D103.</p>
7E102	<p>"Technology" for protection of avionics and electrical sub-systems against electromagnetic pulse (EMP) and electromagnetic interference (EMI) hazards, from external sources, as follows:</p> <ul style="list-style-type: none"> a. Design "technology" for shielding systems; b. Design "technology" for the configuration of hardened electrical circuits and sub-systems; c. Design "technology" for the determination of hardening criteria of Category Codes 7E102.a. and 7E102.b.
7E104	<p>"Technology" for the integration of the flight control, guidance, and propulsion data into a flight management system for optimisation of rocket system trajectory.</p>

<i>Category Code</i>	<i>Item Description</i>
CATEGORY 8 — MARINE	
8A	Systems, Equipment and Components
8A001	<p>Submersible vehicles and surface vessels, as follows:</p> <p><u><i>N.B.</i></u> <i>For equipment for submersible vehicles, see:</i></p> <ul style="list-style-type: none"> – <i>Category 6 for sensors;</i> – <i>Categories 7 and 8 for navigation equipment;</i> – <i>Category 8A for underwater equipment.</i> <p>a. Manned, tethered submersible vehicles designed to operate at depths exceeding 1,000 m;</p> <p>b. Manned, untethered submersible vehicles having any of the following characteristics:</p> <ol style="list-style-type: none"> 1. Designed to ‘operate autonomously’ and having a lifting capacity of all the following: <ol style="list-style-type: none"> a. 10% or more of their weight in air; <u>and</u> b. 15 kN or more; 2. Designed to operate at depths exceeding 1,000 m; <u>or</u> 3. Having all of the following characteristics: <ol style="list-style-type: none"> a. Designed to continuously ‘operate autonomously’ for 10 hours or more; <u>and</u> b. ‘Range’ of 25 nautical miles or more; <p><u><i>Technical Notes</i></u></p> <ol style="list-style-type: none"> 1. <i>For the purpose of Category Code 8A001.b., ‘operate autonomously’ means fully submerged, without snorkel, all systems working and cruising at minimum speed at which the submersible can safely control its depth dynamically by using its depth planes only, with no need for a support vessel or support base on the surface, seabed or shore, and containing a propulsion system for submerged or surface use.</i> 2. <i>For the purpose of Category Code 8A001.b., ‘range’ means half the maximum distance a submersible vehicle can ‘operate autonomously’.</i>

<i>Category Code</i>	<i>Item Description</i>
	<ul style="list-style-type: none"> c. Unmanned, tethered submersible vehicles designed to operate at depths exceeding 1,000 m and having any of the following characteristics: <ul style="list-style-type: none"> 1. Designed for self-propelled manoeuvre using propulsion motors or thrusters specified in Category Code 8A002.a.2.; <u>or</u> 2. Fibre optic data link; d. Unmanned, untethered submersible vehicles having any of the following characteristics: <ul style="list-style-type: none"> 1. Designed for deciding a course relative to any geographical reference without real-time human assistance; 2. Acoustic data or command link; <u>or</u> 3. Optical data or command link exceeding 1,000 m; e. Ocean salvage systems with a lifting capacity exceeding 5 MN for salvaging objects from depths exceeding 250 m and having any of the following: <ul style="list-style-type: none"> 1. Dynamic positioning systems capable of position keeping within 20 m of a given point provided by the navigation system; <u>or</u> 2. Seafloor navigation and navigation integration systems, for depths exceeding 1,000 m and with positioning “accuracies” to within 10 m of a predetermined point; f. Not used; g. Not used; h. Not used; i. Not used.
8A002	<p>Marine systems, equipment and components, as follows:</p> <p><u>N.B.</u></p> <p><i>For underwater communications systems, see Category 5 – Part 1 – Telecommunications.</i></p>

<i>Category Code</i>	<i>Item Description</i>
	<p>a. Systems, equipment and components, specially designed or modified for submersible vehicles and designed to operate at depths exceeding 1,000 m, as follows:</p> <ol style="list-style-type: none"> 1. Pressure housings or pressure hulls with a maximum inside chamber diameter exceeding 1.5 m; 2. Direct current propulsion motors or thrusters; 3. Umbilical cables, and connectors therefor, using optical fibre and having synthetic strength members; 4. Components manufactured from material specified in Category Code 8C001; <p><i>Technical Note</i> <i>Category Code 8A002.a.4. includes 'syntactic foam' specified in Category Code 8C001 when an intermediate stage of manufacture has been performed and it is not yet in the final component form.</i></p> <p>b. Systems specially designed or modified for the automated control of the motion of submersible vehicles specified in Category Code 8A001, using navigation data, having closed loop servo-controls and having any of the following functions:</p> <ol style="list-style-type: none"> 1. Enabling a vehicle to move within 10 m of a predetermined point in the water column; 2. Maintaining the position of the vehicle within 10 m of a predetermined point in the water column; <u>or</u> 3. Maintaining the position of the vehicle within 10 m while following a cable on or under the seabed; <p>c. Fibre optic pressure hull penetrators;</p> <p>d. Underwater vision systems specially designed or modified for remote operation with an underwater vehicle, employing techniques to minimise the effects of back scatter and including range-gated illuminators or "laser" systems;</p> <p>e. Not used;</p> <p>f. Not used;</p>

<i>Category Code</i>	<i>Item Description</i>
	<p>g. Light systems specially designed or modified for underwater use, as follows:</p> <ol style="list-style-type: none"> 1. Stroboscopic light systems capable of a light output energy of more than 300 J per flash and a flash rate of more than 5 flashes per second; 2. Argon arc light systems specially designed for use below 1,000 m; <p>h. “Robots” specially designed for underwater use, controlled by using a dedicated computer and having any of the following characteristics:</p> <ol style="list-style-type: none"> 1. Systems that control the “robot” using information from sensors which measure force or torque applied to an external object, distance to an external object, or tactile sense between the “robot” and an external object; <u>or</u> 2. The ability to exert a force of 250 N or more or a torque of 250 Nm or more and using titanium based alloys or “composite” “fibrous or filamentary materials” in their structural members; <p>i. Remotely controlled articulated manipulators specially designed or modified for use with submersible vehicles and having any of the following characteristics:</p> <ol style="list-style-type: none"> 1. Systems which control the manipulator using information from sensors which measure any of the following: <ol style="list-style-type: none"> a. Torque or force applied to an external object; <u>or</u> b. Tactile sense between the manipulator and an external object; <u>or</u> 2. Controlled by proportional master-slave techniques and having 5 degrees of ‘freedom of movement’ or more; <p><i><u>Technical Note</u></i> <i>Only functions having proportionally related motion control using positional feedback are counted when determining the number of degrees of ‘freedom of movement’.</i></p>

<i>Category Code</i>	<i>Item Description</i>
	<p>j. Air independent power systems specially designed for underwater use, as follows:</p> <ol style="list-style-type: none"> 1. Brayton or Rankine cycle engine air independent power systems having any of the following: <ol style="list-style-type: none"> a. Chemical scrubber or absorber systems, specially designed to remove carbon dioxide, carbon monoxide and particulates from recirculated engine exhaust; b. Systems specially designed to use a monoatomic gas; c. Devices or enclosures, specially designed for underwater noise reduction in frequencies below 10 kHz, or special mounting devices for shock mitigation; <u>or</u> d. Systems having all of the following characteristics: <ol style="list-style-type: none"> 1. Specially designed to pressurise the products of reaction or for fuel reformation; 2. Specially designed to store the products of the reaction; <u>and</u> 3. Specially designed to discharge the products of the reaction against a pressure of 100 kPa or more; 2. Diesel cycle engine air independent systems having all of the following: <ol style="list-style-type: none"> a. Chemical scrubber or absorber systems, specially designed to remove carbon dioxide, carbon monoxide and particulates from recirculated engine exhaust; b. Systems specially designed to use a monoatomic gas; c. Devices or enclosures, specially designed for underwater noise reduction in frequencies below 10 kHz, or special mounting devices for shock mitigation; <u>and</u>

<i>Category Code</i>	<i>Item Description</i>
	<p>d. Specially designed exhaust systems that do not exhaust continuously the products of combustion;</p> <p>3. “Fuel cell” air independent power systems with an output exceeding 2 kW and having any of the following:</p> <p>a. Devices or enclosures, specially designed for underwater noise reduction in frequencies below 10 kHz, or special mounting devices for shock mitigation; <u>or</u></p> <p>b. Systems having all of the following characteristics:</p> <ol style="list-style-type: none"> 1. Specially designed to pressurise the products of reaction or for fuel reformation; 2. Specially designed to store the products of the reaction; <u>and</u> 3. Specially designed to discharge the products of the reaction against a pressure of 100 kPa or more; <p>4. Stirling cycle engine air independent power systems having all of the following:</p> <p>a. Devices or enclosures, specially designed for underwater noise reduction in frequencies below 10 kHz, or special mounting devices for shock mitigation; <u>and</u></p> <p>b. Specially designed exhaust systems which discharge the products of combustion against a pressure of 100 kPa or more;</p> <p>k. Not used;</p> <p>l. Not used;</p> <p>m. Not used;</p> <p>n. Not used;</p> <p>o. Propellers, power transmission systems, power generation systems and noise reduction systems, as follows:</p> <ol style="list-style-type: none"> 1. Not used;

<i>Category Code</i>	<i>Item Description</i>
	<p>2. Water-screw propeller, power generation systems or transmission systems, designed for use on vessels, as follows:</p> <ul style="list-style-type: none"> a. Controllable-pitch propellers and hub assemblies, rated at more than 30 MW; b. Internally liquid-cooled electric propulsion engines with a power output exceeding 2.5 MW; c. “Superconductive” propulsion engines or permanent magnet electric propulsion engines, with a power output exceeding 0.1 MW; d. Power transmission shaft systems incorporating “composite” material components and capable of transmitting more than 2 MW; e. Ventilated or base-ventilated propeller systems, rated at more than 2.5 MW; <p>3. Noise reduction systems designed for use on vessels of 1,000 tonnes displacement or more, as follows:</p> <ul style="list-style-type: none"> a. Systems that attenuate underwater noise at frequencies below 500 Hz and consist of compound acoustic mounts for the acoustic isolation of diesel engines, diesel generator sets, gas turbines, gas turbine generator sets, propulsion motors or propulsion reduction gears, specially designed for sound or vibration isolation and having an intermediate mass exceeding 30% of the equipment to be mounted; b. ‘Active noise reduction or cancellation systems’ or magnetic bearings, specially designed for power transmission systems; <p><u>Technical Note</u> ‘Active noise reduction or cancellation systems’ incorporate electronic control systems capable of actively reducing equipment vibration by the generation of anti-noise or anti-vibration signals directly to the source.</p>

<i>Category Code</i>	<i>Item Description</i>
	<p>p. Pumpjet propulsion systems having all of the following characteristics:</p> <ol style="list-style-type: none"> 1. Power output exceeding 2.5 MW; <u>and</u> 2. Using divergent nozzle and flow conditioning vane techniques to improve propulsive efficiency or reduce propulsion-generated underwater-radiated noise; <p>q. Underwater swimming and diving equipment as follows:</p> <ol style="list-style-type: none"> 1. Closed circuit rebreathers; 2. Semi-closed circuit rebreathers; <p><u>Note</u> <i>Category Code 8A002.q. does not include individual rebreathers for personal use when accompanying their users.</i></p> <p><u>N.B.</u> <i>For equipment and devices specially designed for military use, see Division 2 of Part 1 of this Schedule.</i></p> <p>r. Diver deterrent acoustic systems specially designed or modified to disrupt divers and having a sound pressure level equal to or exceeding 190 dB (reference 1 µPa at 1 m) at frequencies of 200 Hz and below.</p> <p><u>Note 1</u> <i>Category Code 8A002.r. does not include diver deterrent systems based on underwater explosive devices, air guns or combustible sources.</i></p> <p><u>Note 2</u> <i>Category Code 8A002.r. includes diver deterrent acoustic systems that use spark gap sources, also known as plasma sound sources.</i></p>
8B	Test, Inspection and Production Equipment
8B001	Water tunnels having a background noise of less than 100 dB (reference 1 µPa, 1 Hz), in the frequency range from 0 Hz to 500 Hz and designed for measuring acoustic fields generated by a hydro-flow around propulsion system models.

<i>Category Code</i>	<i>Item Description</i>
8C	Materials
8C001	<p>‘Syntactic foam’ designed for underwater use and having all of the following characteristics:</p> <p><i>N.B.</i></p> <p><i>See also Category Code 8A002.a.4.</i></p> <p>a. Designed for marine depths exceeding 1,000 m; <u>and</u></p> <p>b. A density less than 561 kg/m³.</p> <p><i>Technical Note</i></p> <p><i>‘Syntactic foam’ consists of hollow spheres of plastic or glass embedded in a resin matrix.</i></p>
8D	Software
8D001	“Software” specially designed or modified for the “development”, “production” or “use” of equipment or materials, specified in Category 8A, 8B or 8C.
8D002	Specific “software” specially designed or modified for the “development”, “production”, repair, overhaul or refurbishing (re-machining) of propellers specially designed for underwater noise reduction.
8E	Technology
8E001	“Technology” (according to the General Technology Note) for the “development” or “production” of equipment or materials specified in Category 8A, 8B or 8C.
8E002	<p>Other “technology”, as follows:</p> <p>a. “Technology” for the “development”, “production”, repair, overhaul or refurbishing (re-machining) of propellers specially designed for underwater noise reduction;</p> <p>b. “Technology” for the overhaul or refurbishing of equipment specified in Category Code 8A001, 8A002.b., 8A002.j., 8A002.o. or 8A002.p.</p>

<i>Category Code</i>	<i>Item Description</i>
	<p>c. “Technology” (according to the General Technology Note) for the “development” or “production” of any of the following:</p> <ol style="list-style-type: none"> 1. Surface-effect vehicles (fully skirted variety) having all of the following characteristics: <ol style="list-style-type: none"> a. Maximum design speed, fully loaded, exceeding 30 knots in a significant wave height of 1.25 m or more; b. Cushion pressure exceeding 3,830 Pa; <u>and</u> c. Light-ship-to-full-load displacement ratio of less than 0.70; 2. Surface-effect vehicles (rigid sidewalls) with a maximum design speed, fully loaded, exceeding 40 knots in a significant wave height of 3.25 m or more; 3. Hydrofoil vessels with active systems for automatically controlling foil systems, with a maximum design speed, fully loaded, of 40 knots or more in a significant wave height of 3.25 m or more; <u>or</u> 4. ‘Small waterplane area vessels’ having any of the following characteristics: <ol style="list-style-type: none"> a. Full load displacement exceeding 500 tonnes with a maximum design speed, fully loaded, exceeding 35 knots in a significant wave height of 3.25 m or more; <u>or</u> b. Full load displacement exceeding 1,500 tonnes with a maximum design speed, fully loaded, exceeding 25 knots in a significant wave height of 4 m or more. <p><u>Technical Note</u> A ‘small waterplane area vessel’ is defined by the following formula: waterplane area at an operational design draft less than $2 \times (\text{displaced volume at the operational design draft})^{2/3}$.</p>

Category Code	Item Description
CATEGORY 9 — AEROSPACE AND PROPULSION	
9A	Systems, Equipment and Components
	<p><u>N.B.</u> For propulsion systems designed or rated against neutron or transient ionising radiation, see Division 2 of Part 1 of this Schedule.</p>
9A001	<p>Aero gas turbine engines having any of the following characteristics:</p> <p><u>N.B.</u> See also Category Code 9A101.</p> <p>a. Incorporating any of the “technologies” specified in Category Code 9E003.a., 9E003.h. or 9E003.i.; <u>or</u></p> <p><u>Note 1</u> Category Code 9A001.a. does not include aero gas turbine engines which meet all of the following:</p> <p>a. Certified by the civil aviation authority of a “participating state”; <u>and</u></p> <p>b. Intended to power non-military manned “aircraft” for which any of the following has been issued by civil aviation authority of a “participating state” for the “aircraft” with this specific engine type:</p> <ol style="list-style-type: none"> 1. A civil type certificate; <u>or</u> 2. An equivalent document recognised by the International Civil Aviation Organisation (ICAO). <p><u>Note 2</u> Category Code 9A001.a. does not include aero gas turbine engines designed for Auxiliary Power Units (APUs) approved by the civil aviation authority of a “participating state”.</p> <p>b. Designed to power an “aircraft” to cruise at Mach 1 or higher, for more than 30 minutes.</p>

<i>Category Code</i>	<i>Item Description</i>
9A002	<p>‘Marine gas turbine engines’ with an ISO standard continuous power rating of 24,245 kW or more and a specific fuel consumption not exceeding 0.219 kg/kWh in the power range from 35% to 100%, and specially designed assemblies and components therefor.</p> <p><u>Note</u> The term ‘marine gas turbine engines’ includes those industrial, or aero-derivative, gas turbine engines adapted for a ship’s electric power generation or propulsion.</p>
9A003	<p>Specially designed assemblies or components, incorporating any of the “technologies” specified in Category Code 9E003.a., 9E003.h. or 9E003.i., for any of the following aero gas turbine engines:</p> <ul style="list-style-type: none"> a. Specified in Category Code 9A001; <u>or</u> b. Whose design or production origins are either non-“participating state” or unknown to the manufacturer.
9A004	<p>Space launch vehicles, “spacecraft”, “spacecraft buses”, “spacecraft payloads”, “spacecraft” on-board systems or equipment, and terrestrial equipment, as follows:</p> <p><u>N.B.</u> See also Category Code 9A104.</p> <ul style="list-style-type: none"> a. Space launch vehicles; b. “Spacecraft”; c. “Spacecraft buses”; d. “Spacecraft payloads” incorporating items specified in Category Code 3A001.b.1.a.4., 3A002.g., 5A001.a.1., 5A001.b.3., 5A002.c., 5A002.e., 6A002.a.1., 6A002.a.2., 6A002.b., 6A002.d., 6A003.b., 6A004.c., 6A004.e., 6A008.d., 6A008.e., 6A008.k., 6A008.l. or 9A010.c.; e. On-board systems or equipment, specially designed for “spacecraft” and having any of the following functions: <ul style="list-style-type: none"> 1. ‘Command and telemetry data handling’;

Category Code	Item Description
	<p><u>Note</u> For the purpose of Category Code 9A004.e.1., 'command and telemetry data handling' includes bus data management, storage, and processing.</p> <p>2. 'Payload data handling'; <u>or</u></p> <p><u>Note</u> For the purpose of Category Code 9A004.e.2., 'payload data handling' includes payload data management, storage, and processing.</p> <p>3. 'Attitude and orbit control';</p> <p><u>Note</u> For the purpose of Category Code 9A004.e.3., 'attitude and orbit control' includes sensing and actuation to determine and control the position and orientation of a "spacecraft".</p> <p><u>N.B.</u> For equipment specially designed for military use, see Division 2 of Part 1 of this Schedule.</p> <p>f. Terrestrial equipment, specially designed for "spacecraft" as follows:</p> <ol style="list-style-type: none"> 1. Telemetry and telecommand equipment; 2. Simulators.
9A005	<p>Liquid rocket propulsion systems containing any of the systems or components, specified in Category Code 9A006.</p> <p><u>N.B.</u> See also Category Codes 9A105 and 9A119.</p>
9A006	<p>Systems and components, specially designed for liquid rocket propulsion systems, as follows:</p> <p><u>N.B.</u> See also Category Codes 9A106, 9A108 and 9A120.</p>

<i>Category Code</i>	<i>Item Description</i>
	<ul style="list-style-type: none"> a. Cryogenic refrigerators, flightweight dewars, cryogenic heat pipes or cryogenic systems, specially designed for use in space vehicles and capable of restricting cryogenic fluid losses to less than 30% per year; b. Cryogenic containers or closed-cycle refrigeration systems, capable of providing temperatures of 100 K (-173°C) or less for “aircraft” capable of sustained flight at speeds exceeding Mach 3, launch vehicles or “spacecraft”; c. Slush hydrogen storage or transfer systems; d. High pressure (exceeding 17.5 MPa) turbo pumps, pump components or their associated gas generator or expander cycle turbine drive systems; e. High-pressure (exceeding 10.6 MPa) thrust chambers and nozzles therefor; f. Propellant storage systems using the principle of capillary containment or positive expulsion (i.e. with flexible bladders); g. Liquid propellant injectors with individual orifices of 0.381 mm or smaller in diameter (an area of $1.14 \times 10^{-3} \text{ cm}^2$ or smaller for non-circular orifices) and specially designed for liquid rocket engines; h. One-piece carbon-carbon thrust chambers or one-piece carbon-carbon exit cones, with densities exceeding 1.4 g/cm^3 and tensile strengths exceeding 48 MPa.
9A007	<p>Solid rocket propulsion systems having any of the following characteristics:</p> <p><u>N.B.</u> See also Category Codes 9A107 and 9A119.</p> <ul style="list-style-type: none"> a. Total impulse capacity exceeding 1.1 MNs; b. Specific impulse of 2.4 kNs/kg or more, when the nozzle flow is expanded to ambient sea level conditions for an adjusted chamber pressure of 7 MPa; c. Stage mass fractions exceeding 88% and propellant solid loadings exceeding 86%;

Category Code	Item Description
9A008	<p>d. Components specified in Category Code 9A008; <u>or</u></p> <p>e. Insulation and propellant bonding systems, using direct-bonded motor designs to provide a 'strong mechanical bond' or a barrier to chemical migration between the solid propellant and case insulation material.</p> <p><i><u>Technical Note</u></i> '<i>Strong mechanical bond</i>' means bond strength equal to or more than propellant strength.</p> <p>Components specially designed for solid rocket propulsion systems, as follows:</p> <p><i><u>N.B.</u></i> See also Category Code 9A108.</p> <p>a. Insulation and propellant bonding systems, using liners to provide a 'strong mechanical bond' or a barrier to chemical migration between the solid propellant and case insulation material;</p> <p><i><u>Technical Note</u></i> '<i>Strong mechanical bond</i>' means bond strength equal to or more than propellant strength.</p> <p>b. Filament-wound "composite" motor cases exceeding 0.61 m in diameter or having 'structural efficiency ratios (PV/W)' exceeding 25 km;</p> <p><i><u>Technical Note</u></i> '<i>Structural efficiency ratio (PV/W)</i>' is the burst pressure (P) multiplied by the vessel volume (V) divided by the total pressure vessel weight (W).</p> <p>c. Nozzles with thrust levels exceeding 45 kN or nozzle throat erosion rates of less than 0.075 mm/s;</p> <p>d. Movable nozzle or secondary fluid injection thrust vector control systems, capable of any of the following:</p> <ol style="list-style-type: none"> 1. Omni-axial movement exceeding $\pm 5^\circ$; 2. Angular vector rotations of 20°/s or more; <u>or</u> 3. Angular vector accelerations of 40°/s² or more.

<i>Category Code</i>	<i>Item Description</i>
9A009	<p>Hybrid rocket propulsion systems having any of the following characteristics:</p> <p><u>N.B.</u> See also Category Codes 9A109 and 9A119.</p> <ul style="list-style-type: none"> a. Total impulse capacity exceeding 1.1 MNs; <u>or</u> b. Thrust levels exceeding 220 kN in vacuum exit conditions.
9A010	<p>Specially designed components, systems and structures, for launch vehicles, launch vehicle propulsion systems or “spacecraft”, as follows:</p> <p><u>N.B.</u> See also Category Codes 1A002 and 9A110.</p> <ul style="list-style-type: none"> a. Components and structures, each exceeding 10 kg and specially designed for launch vehicles manufactured using any of the following: <ul style="list-style-type: none"> 1. “Composite” materials consisting of “fibrous or filamentary materials” specified in Category Code 1C010.e. and resins specified in Category Code 1C008 or 1C009.b.; 2. Metal “matrix” “composites” reinforced by any of the following: <ul style="list-style-type: none"> a. Material specified in Category Code 1C007; b. “Fibrous or filamentary materials” specified in Category Code 1C010; <u>or</u> c. Aluminides specified in Category Code 1C002.a.; <u>or</u> 3. Ceramic “matrix” “composite” materials specified in Category Code 1C007; <p><u>Note</u> The weight cut-off is not relevant for nose cones.</p>

<i>Category Code</i>	<i>Item Description</i>
	<ul style="list-style-type: none"> b. Components and structures, specially designed for launch vehicle propulsion systems specified in Category Codes 9A005 to 9A009 manufactured using any of the following: <ul style="list-style-type: none"> 1. “Fibrous or filamentary materials” specified in Category Code 1C010.e. and resins specified in Category Code 1C008 or 1C009.b.; 2. Metal “matrix” “composites” reinforced by any of the following: <ul style="list-style-type: none"> a. Materials specified in Category Code 1C007; b. “Fibrous or filamentary materials” specified in Category Code 1C010; <u>or</u> c. Aluminides specified in Category Code 1C002.a.; <u>or</u> 3. Ceramic “matrix” “composite” materials specified in Category Code 1C007; c. Structural components and isolation systems, specially designed to control actively the dynamic response or distortion of “spacecraft” structures; d. Pulsed liquid rocket engines with thrust-to-weight ratios equal to or more than 1 kN/kg and a response time (the time required to achieve 90% of total rated thrust from start-up) of less than 30 ms.
9A011	<p>Ramjet, scramjet or combined cycle engines, and specially designed components therefor.</p> <p><u>N.B.</u> See also Category Codes 9A111 and 9A118.</p>
9A012	<p>“Unmanned aerial vehicles” (“UAVs”), unmanned “airships”, related equipment and components, as follows:</p> <p><u>N.B.</u> See also Category Code 9A112.</p>

<i>Category Code</i>	<i>Item Description</i>
	<p>a. “UAVs” or unmanned “airships”, designed to have controlled flight out of the direct ‘natural vision’ of the ‘operator’ and having any of the following characteristics:</p> <ol style="list-style-type: none"> 1. Having all of the following characteristics: <ol style="list-style-type: none"> a. A maximum ‘endurance’ greater than or equal to 30 minutes but less than 1 hour; <u>and</u> b. Designed to take-off and have stable controlled flight in wind gusts equal to or exceeding 46.3 km/h (25 knots); <u>or</u> 2. A maximum ‘endurance’ of 1 hour or greater; <p><i>Technical Notes</i></p> <ol style="list-style-type: none"> 1. <i>For the purpose of Category Code 9A012.a., ‘operator’ is a person who initiates or commands the “UAV” or unmanned “airship” flight.</i> 2. <i>For the purpose of Category Code 9A012.a., ‘endurance’ is to be calculated for ISA conditions (ISO 2533:1975) at sea level in zero wind.</i> 3. <i>For the purpose of Category Code 9A012.a., ‘natural vision’ means unaided human sight, with or without corrective lenses.</i> <p>b. Related equipment and components, as follows:</p> <ol style="list-style-type: none"> 1. Not used; 2. Not used; 3. Equipment or components, specially designed to convert a manned “aircraft” or manned “airship”, to a “UAV” or unmanned “airship”, specified in Category Code 9A012.a.; 4. Air breathing reciprocating or rotary internal combustion type engines, specially designed or modified to propel “UAVs” or unmanned “airships”, at altitudes above 15,240 metres (50,000 feet).

<i>Category Code</i>	<i>Item Description</i>
9A101	<p>Turbojet and turbofan engines, other than those specified in Category Code 9A001, as follows:</p> <p>a. Engines having both of the following characteristics:</p> <ol style="list-style-type: none"> 1. 'Maximum thrust value' greater than 400 N (achieved un-installed) excluding civil certified engines with a 'maximum thrust value' greater than 8,890 N (achieved un-installed); <u>and</u> 2. Specific fuel consumption of 0.15 kg/N/hr or less (at maximum continuous power at sea level static conditions using the ICAO standard atmosphere); <p><i>Technical Note</i></p> <p><i>For the purpose of Category Code 9A101.a.1., 'maximum thrust value' is the manufacturer's demonstrated maximum thrust for the engine type un-installed. The civil type certified thrust value will be equal to or less than the manufacturer's demonstrated maximum thrust for the engine type.</i></p> <p>b. Engines designed or modified for use in "missiles" or unmanned aerial vehicles specified in Category Code 9A012 or 9A112.a.</p>
9A102	<p>'Turboprop engine systems' specially designed for unmanned aerial vehicles specified in Category Code 9A012 or 9A112.a., and specially designed components therefor, having a 'maximum power' greater than 10 kW.</p> <p><i>Note</i></p> <p><i>Category Code 9A102 does not include civil certified engines.</i></p> <p><i>Technical Notes</i></p> <ol style="list-style-type: none"> 1. <i>For the purpose of Category Code 9A102, a 'turboprop engine system' incorporates all of the following:</i> <ol style="list-style-type: none"> a. <i>Turboshaft engine; <u>and</u></i> b. <i>Power transmission system to transfer the power to a propeller.</i>

<i>Category Code</i>	<i>Item Description</i>
	<p>2. <i>For the purpose of Category Code 9A102, the ‘maximum power’ is achieved un-installed at sea level static conditions using the ICAO standard atmosphere.</i></p>
9A104	<p>Sounding rockets, capable of a range of at least 300 km.</p> <p><u>N.B.</u> See also Category Code 9A004.</p>
9A105	<p>Liquid propellant rocket engines or gel propellant rocket motors, as follows:</p> <p><u>N.B.</u> See also Category Code 9A119.</p> <p>a. Liquid propellant rocket engines or gel propellant rocket motors, usable in “missiles”, other than those specified in Category Code 9A005, integrated, or designed or modified to be integrated, into a liquid propellant or gel propellant propulsion system which has a total impulse capacity equal to or greater than 1.1 MNs;</p> <p>b. Liquid propellant rocket engines or gel propellant rocket motors, usable in complete rocket systems or unmanned aerial vehicles, capable of a range of 300 km, other than those specified in Category Code 9A005 or 9A105.a., integrated, or designed or modified to be integrated, into a liquid propellant or gel propellant propulsion system which has a total impulse capacity equal to or greater than 0.841 MNs.</p>
9A106	<p>Systems or components, other than those specified in Category Code 9A006 as follows, specially designed for liquid rocket propulsion systems:</p> <p>a. Not used;</p> <p>b. Rocket nozzles and combustion chambers, usable in “missiles”, space launch vehicles specified in Category Code 9A004 or sounding rockets specified in Category Code 9A104;</p> <p>c. Thrust vector control sub-systems, usable in “missiles”;</p>

Category Code	Item Description
	<p data-bbox="544 454 724 483"><u>Technical Note</u></p> <p data-bbox="544 495 1259 562"><i>Examples of methods of achieving thrust vector control specified in Category Code 9A106.c. are:</i></p> <ul style="list-style-type: none"> <li data-bbox="544 577 794 607">a. <i>Flexible nozzle;</i> <li data-bbox="544 622 1002 651">b. <i>Fluid or secondary gas injection;</i> <li data-bbox="544 667 922 696">c. <i>Movable engine or nozzle;</i> <li data-bbox="544 712 1259 786">d. <i>Deflection of exhaust gas stream (jet vanes or probes);<u>or</u></i> <li data-bbox="544 801 746 831">e. <i>Thrust tabs.</i> <p data-bbox="480 853 1259 1021">d. Liquid, slurry and gel propellant (including oxidisers) control systems, and specially designed components therefor, usable in “missiles”, designed or modified to operate in vibration environments greater than 10 g rms between 20 Hz and 2 kHz.</p> <p data-bbox="544 1043 603 1072"><u>Note</u></p> <p data-bbox="544 1084 1259 1151"><i>The only servo valves, pumps and gas turbines specified in Category Code 9A106.d., are the following:</i></p> <ul style="list-style-type: none"> <li data-bbox="544 1167 1259 1290">a. <i>Servo valves designed for flow rates equal to or greater than 24 litres per minute, at an absolute pressure equal to or greater than 7 MPa, that have an actuator response time of less than 100 ms;</i> <li data-bbox="544 1312 1259 1435">b. <i>Pumps, for liquid propellants, with shaft speeds equal to or greater than 8,000 rpm at a maximum operating mode or with discharge pressures equal to or greater than 7 MPa;</i> <li data-bbox="544 1458 1259 1559">c. <i>Gas turbines, for liquid propellant turbopumps, with shaft speeds equal to or greater than 8,000 rpm at the maximum operating mode.</i> <p data-bbox="480 1581 1259 1682">e. Combustion chambers and nozzles, usable in “missiles”, space launch vehicles specified in Category Code 9A004 or sounding rockets specified in Category Code 9A104.</p>

<i>Category Code</i>	<i>Item Description</i>
9A107	<p>Solid propellant rocket engines, usable in complete rocket systems or unmanned aerial vehicles, capable of a range of 300 km, other than those specified in Category Code 9A007, having total impulse capacity equal to or greater than 0.841 MNs.</p> <p><u>N.B.</u> See also Category Code 9A119.</p>
9A108	<p>Components, other than those specified in Category Code 9A008, as follows, specially designed for solid rocket propulsion systems:</p> <ol style="list-style-type: none"> a. Rocket motor cases and “insulation” components therefor, usable in “missiles”, space launch vehicles specified in Category Code 9A004 or sounding rockets specified in Category Code 9A104; b. Rocket nozzles, usable in “missiles”, space launch vehicles specified in Category Code 9A004 or sounding rockets specified in Category Code 9A104; c. Thrust vector control sub-systems, usable in “missiles”. <p><u>Technical Note</u> <i>Examples of methods of achieving thrust vector control specified in Category Code 9A108.c. are:</i></p> <ol style="list-style-type: none"> a. <i>Flexible nozzle;</i> b. <i>Fluid or secondary gas injection;</i> c. <i>Movable engine or nozzle;</i> d. <i>Deflection of exhaust gas stream (jet vanes or probes);</i> <u>or</u> e. <i>Thrust tabs.</i>

<i>Category Code</i>	<i>Item Description</i>
9A109	<p>Hybrid rocket motors and specially designed components, as follows:</p> <ol style="list-style-type: none"> a. Hybrid rocket motors usable in complete rocket systems or unmanned aerial vehicles, capable of 300 km, other than those specified in Category Code 9A009, having a total impulse capacity equal to or greater than 0.841 MNs, and specially designed components therefor; b. Specially designed components for hybrid rocket motors specified in Category Code 9A009 that are usable in “missiles”. <p><u>N.B.</u> See also Category Codes 9A009 and 9A119.</p>
9A110	<p>Composite structures, laminates and manufactures thereof, other than those specified in Category Code 9A010, specially designed for use in ‘missiles’ or the sub-systems specified in Category Code 9A005, 9A007, 9A105, 9A106.c., 9A107, 9A108.c., 9A116 or 9A119.</p> <p><u>N.B.</u> See also Category Code 1A002.</p> <p><u>Technical Note</u> In Category Code 9A110, ‘missile’ means complete rocket systems and unmanned aerial vehicle systems capable of a range exceeding 300 km.</p>
9A111	<p>Pulse jet engines, usable in “missiles” or unmanned aerial vehicles specified in Category Code 9A012 or 9A112.a., and specially designed components therefor.</p> <p><u>N.B.</u> See also Category Codes 9A011 and 9A118.</p>

<i>Category Code</i>	<i>Item Description</i>
9A112	<p>“Unmanned aerial vehicles” (“UAVs”), other than those specified in Category Code 9A012, as follows:</p> <ol style="list-style-type: none"> a. “Unmanned aerial vehicles” (“UAVs”) capable of a range of 300 km; b. “Unmanned aerial vehicles” (“UAVs”) having all of the following characteristics: <ol style="list-style-type: none"> 1. Having any of the following characteristics: <ol style="list-style-type: none"> a. An autonomous flight control and navigation capability; <u>or</u> b. Capability of controlled flight out of direct vision range involving a human operator; <u>and</u> 2. Having any of the following characteristics: <ol style="list-style-type: none"> a. Incorporating an aerosol dispensing system or mechanism with a capacity greater than 20 litres; <u>or</u> b. Designed or modified to incorporate an aerosol dispensing system or mechanism with a capacity greater than 20 litres. <p><u>Technical Notes</u></p> <ol style="list-style-type: none"> 1. <i>An aerosol consists of particulate or liquids other than fuel components, by products or additives, as part of the “payload” to be dispersed in the atmosphere. Examples of aerosols include pesticides for crop dusting and dry chemicals for cloud seeding.</i> 2. <i>An aerosol dispensing system or mechanism contains all those devices (mechanical, electrical, hydraulic, etc.), which are necessary for storage and dispersion of an aerosol into the atmosphere. This includes the possibility of aerosol injection into the combustion exhaust vapour and into the propeller slip stream.</i>

<i>Category Code</i>	<i>Item Description</i>
9A115	<p>Launch support equipment as follows:</p> <ul style="list-style-type: none"> a. Apparatus and devices for handling, control, activation or launching, designed or modified for space launch vehicles specified in Category Code 9A004, sounding rockets specified in Category Code 9A104 or unmanned aerial vehicles specified in Category Code 9A012 or 9A112.a.; b. Vehicles for transport, handling, control, activation or launching, designed or modified for space launch vehicles specified in Category Code 9A004 or sounding rockets specified in Category Code 9A104.
9A116	<p>Re-entry vehicles, usable in “missiles”, and equipment designed or modified therefor, as follows:</p> <ul style="list-style-type: none"> a. Re-entry vehicles; b. Heat shields and components therefor, fabricated of ceramic or ablative materials; c. Heat sinks and components therefor, fabricated of light-weight, high heat capacity materials; d. Electronic equipment specially designed for re-entry vehicles.
9A117	<p>Staging mechanisms, separation mechanisms, and interstages, usable in “missiles”.</p> <p><u><i>N.B.</i></u> <i>See also Category Code 9A121.</i></p>
9A118	<p>Devices to regulate combustion usable in engines, which are usable in “missiles” or unmanned aerial vehicles specified in Category Code 9A012 or 9A112.a., specified in Category Code 9A011 or 9A111.</p>

<i>Category Code</i>	<i>Item Description</i>
9A119	Individual rocket stages, usable in complete rocket systems or unmanned aerial vehicles, capable of a range of 300 km, other than those specified in Category Codes 9A005, 9A007, 9A009, 9A105, 9A107 and 9A109.
9A120	<p>Liquid propellant tanks, other than those specified in Category Code 9A006, specially designed for propellants specified in Category Code 1C111 or 'other liquid propellants', used in rocket systems capable of delivering at least a 500 kg payload to a range of at least 300 km.</p> <p><u>Note</u> <i>In Category Code 9A120, 'other liquid propellants' includes, but is not limited to, propellants specified in Division 2 of Part 1 of this Schedule.</i></p>
9A121	<p>Umbilical and interstage electrical connectors specially designed for "missiles", space launch vehicles specified in Category Code 9A004 or sounding rockets specified in Category Code 9A104.</p> <p><u>Technical Note</u> <i>Interstage connectors referred to in Category Code 9A121 also include electrical connectors installed between the "missile", space launch vehicle or sounding rocket and their payload.</i></p>
9A350	<p>Spraying or fogging systems, specially designed or modified for fitting to aircraft, "lighter-than-air vehicles" or unmanned aerial vehicles, and specially designed components therefor, as follows:</p> <ol style="list-style-type: none"> a. Complete spraying or fogging systems capable of delivering, from a liquid suspension, an initial droplet 'VMD' of less than 50 µm at a flow rate of greater than two litres per minute; b. Spray booms or arrays of aerosol generating units capable of delivering, from a liquid suspension, an initial droplet 'VMD' of less than 50 µm at a flow rate of greater than two litres per minute; c. Aerosol generating units specially designed for fitting to systems specified in Category Codes 9A350.a. and .b.

Category Code	Item Description
	<p><u>Note</u> Aerosol generating units are devices specially designed or modified for fitting to aircraft such as nozzles, rotary drum atomisers and similar devices.</p> <p><u>Note</u> Category Code 9A350 does not include spraying or fogging systems and components that are demonstrated not to be capable of delivering biological agents in the form of infectious aerosols.</p> <p><u>Technical Notes</u></p> <ol style="list-style-type: none"> 1. Droplet size for spray equipment or nozzles specially designed for use on aircraft, "lighter-than-air vehicles" or unmanned aerial vehicles should be measured using either of the following: <ol style="list-style-type: none"> a. Doppler laser method; b. Forward laser diffraction method. 2. In Category Code 9A350, 'VMD' means Volume Median Diameter and for water-based systems this equates to Mass Median Diameter (MMD).
<p>9B</p> <p>9B001</p>	<p>Test, Inspection and Production Equipment</p> <p>Equipment, tooling and fixtures, specially designed for manufacturing gas turbine blades, vanes or "tip shroud" castings, as follows:</p> <ol style="list-style-type: none"> a. Directional solidification or single crystal casting equipment; b. Casting tooling, manufactured from refractory metals or ceramics, as follows: <ol style="list-style-type: none"> 1. Cores; 2. Shells (moulds); 3. Combined core and shell (mould) units; c. Directional-solidification or single-crystal additive-manufacturing equipment.

<i>Category Code</i>	<i>Item Description</i>
9B002	<p>On-line (real-time) control systems, instrumentation (including sensors) or automated data acquisition and processing equipment, having all of the following characteristics:</p> <ul style="list-style-type: none"> a. Specially designed for the “development” of gas turbine engines, assemblies or components; <u>and</u> b. Incorporating “technology” specified in Category Code 9E003.h. or 9E003.i.
9B003	<p>Equipment specially designed for the “production” or test of gas turbine brush seals designed to operate at tip speeds exceeding 335 m/s and temperatures in excess of 773 K (500°C), and specially designed components or accessories therefor.</p>
9B004	<p>Tools, dies or fixtures, for the solid state joining of “superalloy”, titanium or intermetallic airfoil-to-disk combinations described in Category Code 9E003.a.3. or 9E003.a.6. for gas turbines.</p>
9B005	<p>On-line (real-time) control systems, instrumentation (including sensors) or automated data acquisition and processing equipment, specially designed for use with any of the following:</p> <p><u>N.B.</u> See also Category Code 9B105.</p> <ul style="list-style-type: none"> a. Wind tunnels designed for speeds of Mach 1.2 or more; <p><u>Note</u> Category Code 9B005.a. does not include wind tunnels specially designed for educational purposes and having a ‘test section size’ (measured laterally) of less than 250 mm.</p> <p><u>Technical Note</u> ‘Test section size’ means the diameter of the circle, or the side of the square, or the longest side of the rectangle, at the largest test section location.</p> <ul style="list-style-type: none"> b. Devices for simulating flow-environments at speeds exceeding Mach 5, including hot-shot tunnels, plasma arc tunnels, shock tubes, shock tunnels, gas tunnels and light gas guns; <u>or</u>

<i>Category Code</i>	<i>Item Description</i>
	c. Wind tunnels or devices, other than two-dimensional sections, capable of simulating Reynolds number flows exceeding 25×10^6 .
9B006	Acoustic vibration test equipment capable of producing sound pressure levels of 160 dB or more (referenced to 20 μ Pa) with a rated output of 4 kW or more at a test cell temperature exceeding 1,273 K (1,000°C), and specially designed quartz heaters therefor. <u>N.B.</u> <i>See also Category Code 9B106.</i>
9B007	Equipment specially designed for inspecting the integrity of rocket motors and using Non-Destructive Test (NDT) techniques other than planar X-ray or basic physical or chemical analysis.
9B008	Direct measurement wall skin friction transducers specially designed to operate at a test flow total (stagnation) temperature exceeding 833 K (560°C).
9B009	Tooling specially designed for producing turbine engine powder metallurgy rotor components capable of operating at stress levels of 60% of Ultimate Tensile Strength (UTS) or more and metal temperatures of 873 K (600°C) or more.
9B010	Equipment specially designed for the production of items specified in Category Code 9A012.
9B105	'Aerodynamic test facilities' for speeds of Mach 0.9 or more, usable for 'missiles' and their sub-systems. <u>N.B.</u> <i>See also Category Code 9B005.</i>

Category Code	Item Description
	<p><u>Note</u></p> <p>Category Code 9B105 does not include wind tunnels for speeds of Mach 3 or less with dimension of the 'test cross section size' equal to or less than 250 mm.</p> <p><u>Technical Notes</u></p> <ol style="list-style-type: none"> 1. In Category Code 9B105, 'aerodynamics test facilities' includes wind tunnels and shock tunnels for the study of airflow over objects. 2. In Note to Category Code 9B105, 'test cross section size' means the diameter of the circle, or the side of the square, or the longest side of the rectangle, or the major axis of the ellipse at the largest 'test cross section' location. 'Test cross section' is the section perpendicular to the flow direction. 3. In Category Code 9B105, 'missile' means complete rocket systems and unmanned aerial vehicle systems capable of a range exceeding 300 km.
9B106	<p>Environmental chambers and anechoic chambers, as follows:</p> <ol style="list-style-type: none"> a. Environmental chambers having all of the following characteristics: <ol style="list-style-type: none"> 1. Capable of simulating any of the following flight conditions: <ol style="list-style-type: none"> a. Altitude equal to or greater than 15 km; <u>or</u> b. Temperature range from below 223 K (-50°C) to above 398 K (+125°C); <u>and</u> 2. Incorporating, or 'designed or modified' to incorporate, a shaker unit or other vibration test equipment to produce vibration environments equal to or greater than 10 g rms, measured 'bare table', between 20 Hz and 2 kHz while imparting forces equal to or greater than 5 kN;

Category Code	Item Description
	<p><i>Technical Notes</i></p> <ol style="list-style-type: none"> 1. <i>Category Code 9B106.a.2. describes systems that are capable of generating a vibration environment with a single wave (e.g. a sine wave) and systems capable of generating a broad band random vibration (i.e. power spectrum).</i> 2. <i>In Category Code 9B106.a.2., ‘designed or modified’ means the environmental chamber provides appropriate interfaces (e.g. sealing devices) to incorporate a shaker unit or other vibration test equipment as specified in Category Code 2B116.</i> 3. <i>In Category Code 9B106.a.2., ‘bare table’ means a flat table, or surface, with no fixture or fittings.</i> <p>b. Environmental chambers capable of simulating all of the following flight conditions:</p> <ol style="list-style-type: none"> 1. Acoustic environments at an overall sound pressure level of 140 dB or greater (referenced to 20 µPa) or with a total rated acoustic power output of 4 kW or greater; <u>and</u> 2. Having any of the following characteristics: <ol style="list-style-type: none"> a. Altitude equal to greater than 15 km; <u>or</u> b. Temperature range from below 223 K (-50°C) to above 398 K (+125°C).
9B115	Specially designed “production equipment” for the systems, sub-systems and components specified in Category Codes 9A005 to 9A009, 9A011, 9A101, 9A102, 9A105 to 9A109, 9A111, 9A116 to 9A120.

<i>Category Code</i>	<i>Item Description</i>
9B116	<p>Specially designed “production facilities” for the space launch vehicles specified in Category Code 9A004, or systems, sub-systems, and components specified in Category Codes 9A005 to 9A009, 9A011, 9A101, 9A102, 9A104 to 9A109, 9A111, 9A116 to 9A120 or ‘missiles’.</p> <p><i>Technical Note</i> <i>In Category Code 9B116, ‘missile’ means complete rocket systems and unmanned aerial vehicle systems capable of a range exceeding 300 km.</i></p>
9B117	<p>Test benches and test stands for solid or liquid propellant rockets or rocket motors, having either of the following characteristics:</p> <ol style="list-style-type: none"> a. The capacity to handle more than 68 kN of thrust; <u>or</u> b. Capable of simultaneously measuring the three axial thrust components.
9C	Materials
9C108	<p>“Insulation” material in bulk form and “interior lining”, other than those specified in Category Code 9A008, for rocket motor cases usable in “missiles” or specially designed for solid propellant rocket engines specified in Category Code 9A007 or 9A107.</p> <p><i>Technical Note</i> <i>In Category Code 9C108, ‘missile’ means complete rocket systems and unmanned aerial vehicle systems capable of a range exceeding 300 km.</i></p>
9C110	<p>Resin impregnated fibre preregs and metal coated fibre preforms therefor, for composite structures, laminates and manufactures specified in Category Code 9A110, made either with organic matrix or metal matrix utilising fibrous or filamentary reinforcements having a “specific tensile strength” greater than 7.62×10^4 m and a “specific modulus” greater than 3.18×10^6 m.</p> <p><i>N.B.</i> <i>See also Category Codes 1C010 and 1C210.</i></p>

Category Code	Item Description
	<p><i>Note</i></p> <p><i>The only resin impregnated fibre prepregs specified in Category Code 9C110 are those using resins with a glass transition temperature (T_g), after cure, exceeding 418 K (145°C) as determined by ASTM D4065 or equivalent.</i></p>
9D	Software
9D001	“Software” specially designed or modified for the “development” of equipment or “technology”, specified in Category Codes 9A001 to 9A119, Category 9B or Category Code 9E003.
9D002	“Software” specially designed or modified for the “production” of equipment specified in Category Codes 9A001 to 9A119 or Category 9B.
9D003	“Software” incorporating “technology” specified in Category Code 9E003.h. and used in “FADEC Systems” for systems specified in Category 9A or equipment specified in Category 9B.
9D004	<p>Other “software” as follows:</p> <ol style="list-style-type: none"> a. 2D or 3D viscous “software”, validated with wind tunnel or flight test data required for detailed engine flow modelling; b. “Software” for testing aero gas turbine engines, assemblies or components, specially designed to collect, reduce and analyse data in real time and capable of feedback control, including the dynamic adjustment of test articles or test conditions, as the test is in progress; c. “Software” specially designed to control directional solidification or single crystal material growth in equipment specified in Category Code 9B001.a. or 9B001.c.; d. Not used; e. “Software” specially designed or modified for the operation of items specified in Category Code 9A012;

<i>Category Code</i>	<i>Item Description</i>
	f. “Software” specially designed to design the internal cooling passages of aero gas turbine blades, vanes and “tip shrouds”; g. “Software” having all of the following characteristics: <ol style="list-style-type: none"> 1. Specially designed to predict aero thermal, aeromechanical and combustion conditions in aero gas turbine engines; <u>and</u> 2. Theoretical modelling predictions of the aero thermal, aeromechanical and combustion conditions, which have been validated with actual aero gas turbine engine (experimental or production) performance data.
9D005	“Software” specially designed or modified for the operation of items specified in Category Code 9A004.e. or 9A004.f.
9D101	“Software” specially designed or modified for the “use” of goods specified in Category Code 9B105, 9B106, 9B116 or 9B117.
9D103	“Software” specially designed for modelling, simulation or design integration of the space launch vehicles specified in Category Code 9A004, or sounding rockets specified in Category Code 9A104, or “missiles” or the sub-systems specified in Category Code 9A005, 9A007, 9A105, 9A106.c., 9A107, 9A108.c., 9A116 or 9A119. <u>Note</u> <i>“Software” specified in Category Code 9D103 remains within the description of that Category when combined with specially designed hardware specified in Category Code 4A102.</i>
9D104	“Software” as follows: <ol style="list-style-type: none"> a. “Software” specially designed or modified for the “use” of goods specified in Category Code 9A001, 9A005, 9A006.d., 9A006.g., 9A007.a., 9A009.a., 9A010.d., 9A011, 9A101, 9A102, 9A105, 9A106.d., 9A107, 9A109, 9A111, 9A115.a., 9A117 or 9A118.;

<i>Category Code</i>	<i>Item Description</i>
	<p>b. “Software” specially designed or modified for the operation or maintenance of sub-systems or equipment specified in Category Code 9A008.d., 9A106.c., 9A108.c. or 9A116.d.</p>
9D105	<p>“Software” specially designed or modified to coordinate the function of more than one sub-system, other than that specified in Category Code 9D004.e., in space launch vehicles specified in Category Code 9A004 or sounding rockets specified in Category Code 9A104 or ‘missiles’.</p> <p><u>Technical Note</u> <i>In Category Code 9D105, ‘missile’ means complete rocket systems and unmanned aerial vehicle systems capable of a range exceeding 300 km.</i></p>
9E	<p>Technology</p> <p><u>Note</u> <i>“Development” or “production” “technology” specified in Category Codes 9E001 to 9E003 for gas turbine engines remains within the description of that Category when used for repair or overhaul. Excluded from that Category are: technical data, drawings or documentation for maintenance activities directly associated with calibration, removal or replacement of damaged or unserviceable line replaceable units, including replacement of whole engines or engine modules.</i></p>
9E001	<p>“Technology” (according to the General Technology Note) for the “development” of equipment or “software”, specified in Category Code 9A001.b., 9A004 to 9A012, 9A350, Category 9B or 9D.</p>
9E002	<p>“Technology” (according to the General Technology Note) for the “production” of equipment specified in Category Code 9A001.b., 9A004 to 9A011, 9A350 or Category 9B.</p> <p><u>N.B.</u> <i>For “technology” for the repair of structures, laminates or materials, see Category Code 1E002.f.</i></p>

<i>Category Code</i>	<i>Item Description</i>
9E003	<p>Other “technology” as follows:</p> <ol style="list-style-type: none"> a. “Technology” “required” for the “development” or “production” of any of the following gas turbine engine components or systems: <ol style="list-style-type: none"> 1. Gas turbine blades, vanes or “tip shrouds”, made from directionally solidified (DS) or single crystal (SC) alloys and having (in the 001 Miller Index Direction) a stress-rupture life exceeding 400 hours at 1,273 K (1,000°C) at a stress of 200 MPa, based on the average property values; 2. Combustors having any of the following characteristics: <ol style="list-style-type: none"> a. Thermally decoupled liners designed to operate at ‘combustor exit temperature’ exceeding 1,883 K (1,610°C); b. Non-metallic liners; c. Non-metallic shells; <u>or</u> d. Liners designed to operate at ‘combustor exit temperature’ exceeding 1,883 K (1,610°C) and having holes that meet the parameters specified by Category Code 9E003.c.; <p><u>Note</u> <i>The “required” “technology” for holes in Category Code 9E003.a.2. is limited to the derivation of the geometry and location of the holes.</i></p> <p><u>Technical Note</u> <i>‘Combustor exit temperature’ is the bulk average gas path total (stagnation) temperature between the combustor exit plane and the leading edge of the turbine inlet guide vane (i.e. measured at engine station T40 as defined in SAE ARP 755A) when the engine is running in a ‘steady state mode’ of operation at the certificated maximum continuous operating temperature.</i></p>

Category Code	Item Description
	<p data-bbox="692 454 874 488"><u>Technical Note</u></p> <p data-bbox="692 495 1259 696"><i>The term ‘steady state mode’ defines engine operation conditions, where the engine parameters, such as thrust/power, rpm and others, have no appreciable fluctuations, when the ambient air temperature and pressure at the engine inlet are constant.</i></p> <p data-bbox="544 714 600 748"><u>N.B.</u></p> <p data-bbox="544 754 1259 822"><i>See Category Code 9E003.c. for “technology” “required” for manufacturing cooling holes.</i></p> <p data-bbox="544 840 1107 873">3. Components that are any of the following:</p> <ul style="list-style-type: none"> <li data-bbox="632 889 1259 987">a. Manufactured from organic “composite” materials designed to operate above 588 K (315°C); <li data-bbox="632 1005 1259 1854">b. Manufactured from any of the following: <ul style="list-style-type: none"> <li data-bbox="692 1055 1259 1122">1. Metal “matrix” “composites” reinforced by any of the following: <ul style="list-style-type: none"> <li data-bbox="756 1140 1259 1207">a. Materials specified in Category Code 1C007; <li data-bbox="756 1225 1259 1323">b. “Fibrous or filamentary materials” specified in Category Code 1C010; <u>or</u> <li data-bbox="756 1341 1259 1408">c. Aluminides specified in Category Code 1C002.a.; <u>or</u> <li data-bbox="692 1426 1259 1494">2. Ceramic “matrix” “composites” specified in Category Code 1C007; <u>or</u> <li data-bbox="632 1512 1259 1854">c. Stators, vanes, blades, tip seals (shrouds), rotating blings, rotating blisks, or ‘splitter ducts’, that are all of the following: <ul style="list-style-type: none"> <li data-bbox="692 1624 1259 1691">1. Not specified in Category Code 9E003.a.3.a.; <li data-bbox="692 1709 1259 1742">2. Designed for compressors or fans; <u>and</u> <li data-bbox="692 1760 1259 1854">3. Manufactured from material specified in Category Code 1C010.e. with resins specified in Category Code 1C008;

Category Code	Item Description
	<p data-bbox="692 454 874 483"><u>Technical Note</u></p> <p data-bbox="692 495 1259 591"><i>A ‘splitter duct’ performs the initial separation of the air-mass flow between the bypass and core sections of the engine.</i></p> <p data-bbox="544 611 1259 707">4. Uncooled turbine blades, vanes or “tip shrouds”, designed to operate at a ‘gas path temperature’ of 1,373 K (1,100°C) or more;</p> <p data-bbox="608 728 790 757"><u>Technical Note</u></p> <p data-bbox="608 768 1259 967"><i>‘Gas path temperature’ is the bulk average gas path total (stagnation) temperature at the leading edge plane of the turbine component when the engine is running in a ‘steady state mode’ of operation at the certificated or specified maximum continuous operating temperature.</i></p> <p data-bbox="692 987 874 1016"><u>Technical Note</u></p> <p data-bbox="692 1028 1259 1227"><i>The term ‘steady state mode’ defines engine operation conditions, where the engine parameters, such as thrust/power, rpm and others, have no appreciable fluctuations, when the ambient air temperature and pressure at the engine inlet are constant.</i></p> <p data-bbox="544 1247 1259 1379">5. Cooled turbine blades, vanes, “tip shrouds” other than those described in Category Code 9E003.a.1., designed to operate at a ‘gas path temperature’ of 1,693 K (1,420°C) or more;</p> <p data-bbox="608 1400 790 1429"><u>Technical Note</u></p> <p data-bbox="608 1440 1259 1639"><i>‘Gas path temperature’ is the bulk average gas path total (stagnation) temperature at the leading edge plane of the turbine component when the engine is running in a ‘steady state mode’ of operation at the certificated or specified maximum continuous operating temperature.</i></p>

<i>Category Code</i>	<i>Item Description</i>
	<p data-bbox="692 454 874 488"><u>Technical Note</u></p> <p data-bbox="692 495 1259 696"><i>The term ‘steady state mode’ defines engine operation conditions, where the engine parameters, such as thrust/power, rpm and others, have no appreciable fluctuations, when the ambient air temperature and pressure at the engine inlet are constant.</i></p> <p data-bbox="544 712 1259 1014"> 6. Airfoil-to-disk blade combinations using solid state joining; 7. Gas turbine engine components using “diffusion bonding” “technology” specified in Category Code 2E003.b.; 8. ‘Damage tolerant’ gas turbine engine rotor components using powder metallurgy materials specified in Category Code 1C002.b.; <u>or</u> </p> <p data-bbox="608 1030 790 1064"><u>Technical Note</u></p> <p data-bbox="608 1070 1259 1171"><i>‘Damage tolerant’ components are designed using methodology and substantiation to predict and limit crack growth.</i></p> <p data-bbox="544 1187 1259 1321"> 9. Not used; 10. Not used; 11. Hollow fan blades; </p> <p data-bbox="480 1337 1259 1868"> b. “Technology” “required” for the “development” or “production” of any of the following: <ol data-bbox="544 1420 1259 1635" style="list-style-type: none"> 1. Wind tunnel aero-models equipped with non-intrusive sensors capable of transmitting data from the sensors to the data acquisition system; <u>or</u> 2. “Composite” propeller blades or propfans, capable of absorbing more than 2,000 kW at flight speeds exceeding Mach 0.55; </p> <p data-bbox="480 1650 1259 1868"> c. “Technology” “required” for manufacturing cooling holes, in gas turbine engine components incorporating any of the “technologies” specified by Category Code 9E003.a.1., 9E003.a.2. or 9E003.a.5., and having any of the following characteristics: <ol data-bbox="544 1839 1114 1868" style="list-style-type: none"> 1. Having all of the following characteristics: </p>

<i>Category Code</i>	<i>Item Description</i>
	<ul style="list-style-type: none"> a. Minimum ‘cross-sectional area’ less than 0.45 mm²; b. ‘Hole shape ratio’ greater than 4.52; <u>and</u> c. ‘Incidence angle’ equal to or less than 25°; <u>or</u> <p>2. Having all of the following characteristics:</p> <ul style="list-style-type: none"> a. Minimum ‘cross-sectional area’ less than 0.12 mm²; b. ‘Hole shape ratio’ greater than 5.65; <u>and</u> c. ‘Incidence angle’ more than 25°; <p><u>Note</u> <i>Category Code 9E003.c. does not include “technology” for manufacturing constant radius cylindrical holes that are straight through and enter and exit on the external surfaces of the component.</i></p> <p><u>Technical Notes</u></p> <ul style="list-style-type: none"> 1. <i>For the purpose of Category Code 9E003.c., the ‘cross-sectional area’ is the area of the hole in the plane perpendicular to the hole axis.</i> 2. <i>For the purpose of Category Code 9E003.c., ‘hole shape ratio’ is the nominal length of the axis of the hole divided by the square root of its minimum ‘cross-sectional area’.</i> 3. <i>For the purpose of Category Code 9E003.c., ‘incidence angle’ is the acute angle measured between the plane tangential to the aerofoil surface and the hole axis at the point where the hole axis enters the aerofoil surface.</i> 4. <i>Techniques for manufacturing holes in Category Code 9E003.c. include “laser”, water jet, Electro-Chemical Machining (ECM) or Electrical Discharge Machining (EDM) methods.</i> <p>d. “Technology” “required” for the “development” or “production” of helicopter power transfer systems or tilt rotor or tilt wing “aircraft” power transfer systems;</p>

<i>Category Code</i>	<i>Item Description</i>
	<p>e. “Technology” for the “development” or “production” of reciprocating diesel engine ground vehicle propulsion systems having all of the following characteristics:</p> <ol style="list-style-type: none"> 1. ‘Box volume’ of 1.2 m³ or less; 2. An overall power output of more than 750 kW based on 80/1269/EEC, ISO 2534 or national equivalents; <u>and</u> 3. Power density of more than 700 kW/m³ of ‘box volume’; <p><u>Technical Note</u></p> <p>‘Box volume’ in Category Code 9E003.e. is the product of three perpendicular dimensions measured in the following way:</p> <p><u>Length:</u></p> <p>The length of the crankshaft from front flange to flywheel face;</p> <p><u>Width:</u></p> <p>The widest of any of the following:</p> <ol style="list-style-type: none"> a. The outside dimension from valve cover to valve cover; b. The dimensions of the outside edges of the cylinder heads; <u>or</u> c. The diameter of the flywheel housing; <p><u>Height:</u></p> <p>The largest of any of the following:</p> <ol style="list-style-type: none"> a. The dimension of the crankshaft centre-line to the top plane of the valve cover (or cylinder head) plus twice the stroke; <u>or</u> b. The diameter of the flywheel housing.

<i>Category Code</i>	<i>Item Description</i>
	<p>f. “Technology” “required” for the “production” of specially designed components for high output diesel engines, as follows:</p> <ol style="list-style-type: none"> 1. “Technology” “required” for the “production” of engine systems having all of the following components employing ceramics materials specified in Category Code 1C007: <ol style="list-style-type: none"> a. Cylinder liners; b. Pistons; c. Cylinder heads; <u>and</u> d. One or more other components (including exhaust ports, turbochargers, valve guides, valve assemblies or insulated fuel injectors); 2. “Technology” “required” for the “production” of turbocharger systems with single-stage compressors and having all of the following characteristics: <ol style="list-style-type: none"> a. Operating at pressure ratios of 4:1 or higher; b. Mass flow in the range from 30 kg to 130 kg per minute; <u>and</u> c. Variable flow area capability within the compressor or turbine sections; 3. “Technology” “required” for the “production” of fuel injection systems with a specially designed multifuel (e.g. diesel or jet fuel) capability covering a viscosity range from diesel fuel (2.5 cSt at 310.8 K (37.8°C)) down to gasoline fuel (0.5 cSt at 310.8 K (37.8°C)) and having all of the following characteristics: <ol style="list-style-type: none"> a. Injection amount in excess of 230 mm³ per injection per cylinder; <u>and</u> b. Electronic control features specially designed for switching governor characteristics automatically depending on fuel property to provide the same torque characteristics by using the appropriate sensors;

<i>Category Code</i>	<i>Item Description</i>
	<p data-bbox="480 454 1259 651">g. “Technology” “required” for the “development” or “production” of ‘high output diesel engines’ for solid, gas phase or liquid film (or combinations thereof) cylinder wall lubrication and permitting operation to temperatures exceeding 723 K (450°C), measured on the cylinder wall at the top limit of travel of the top ring of the piston;</p> <p data-bbox="544 674 727 701"><u>Technical Note</u></p> <p data-bbox="544 719 1259 846"><i>‘High output diesel engines’ are diesel engines with a specified brake mean effective pressure of 1.8 MPa or more at a speed of 2,300 rpm, provided the rated speed is 2,300 rpm or more.</i></p> <p data-bbox="480 869 1259 925">h. “Technology” for gas turbine engine “FADEC systems” as follows:</p> <ol data-bbox="544 947 1259 1413" style="list-style-type: none"> <li data-bbox="544 947 1259 1115">1. “Development” “technology” for deriving the functional requirements for the components necessary for the “FADEC system” to regulate engine thrust or shaft power (e.g. feedback sensor time constants and accuracies, fuel valve slew rate); <li data-bbox="544 1137 1259 1261">2. “Development” or “production” “technology” for control and diagnostic components unique to the “FADEC system” and used to regulate engine thrust or shaft power; <li data-bbox="544 1283 1259 1413">3. “Development” “technology” for the control law algorithms, including “source code”, unique to the “FADEC system” and used to regulate engine thrust or shaft power; <p data-bbox="544 1435 603 1462"><u>Note</u></p> <p data-bbox="544 1480 1259 1740"><i>Category Code 9E003.h. does not include technical data related to engine “aircraft” integration required by the relevant civil aviation certification authorities of a “participating state” to be published for general airline use (e.g. installation manuals, operating instructions, instructions for continued airworthiness) or interface functions (e.g. input/output processing, airframe thrust or shaft power demand).</i></p>

<i>Category Code</i>	<i>Item Description</i>
	<p>i. “Technology” for adjustable flow path systems designed to maintain engine stability for gas generator turbines, fan or power turbines, or propelling nozzles, as follows:</p> <ol style="list-style-type: none"> 1. “Development” “technology” for deriving the functional requirements for the components that maintain engine stability; 2. “Development” or “production” “technology” for components unique to the adjustable flow path system and that maintain engine stability; 3. “Development” “technology” for the control law algorithms, including “source code”, unique to the adjustable flow path system and that maintain engine stability; <p><u>Note</u> <i>Category Code 9E003.i. does not include “development” or “production” “technology” for any of the following:</i></p> <ol style="list-style-type: none"> a. <i>Inlet guide vanes;</i> b. <i>Variable pitch fans or propfans;</i> c. <i>Variable compressor vanes;</i> d. <i>Compressor bleed valves; <u>or</u></i> e. <i>Adjustable flow path geometry for reverse thrust.</i> <p>j. “Technology” “required” for the “development” of wing-folding systems designed for fixed-wing “aircraft” powered by gas turbine engines.</p> <p><u>N.B.</u> <i>For “technology” “required” for the “development” of wing-folding systems designed for fixed-wing “aircraft”, see also Division 2 of Part 1 of this Schedule.</i></p>

<i>Category Code</i>	<i>Item Description</i>
9E101	<p>a. “Technology” (according to the General Technology Note) for the “development” of goods specified in Category Code 9A101, 9A102, 9A104 to 9A111, 9A112.a. or 9A115 to 9A121.</p> <p>b. “Technology” (according to the General Technology Note) for the “production” of ‘UAVs’ specified in Category Code 9A012 or goods specified in Category Code 9A101, 9A102, 9A104 to 9A111, 9A112.a. or 9A115 to 9A121.</p> <p><i>Technical Note</i> In Category Code 9E101.b., ‘UAV’ means unmanned aerial vehicle systems capable of a range exceeding 300 km.</p>
9E102	<p>“Technology” (according to the General Technology Note) for the “use” of space launch vehicles specified in Category Code 9A004, goods specified in Category Codes 9A005 to 9A011, ‘UAVs’ specified in Category Code 9A012 or goods specified in Category Code 9A101, 9A102, 9A104 to 9A111, 9A112.a., 9A115 to 9A121, 9B105, 9B106, 9B115, 9B116, 9B117, 9D101 or 9D103.</p> <p><i>Technical Note</i> In Category Code 9E102, ‘UAV’ means unmanned aerial vehicle systems capable of a range exceeding 300 km.</p>

Made on 27 June 2017.

NG HOW YUE
Permanent Secretary,
Ministry of Trade and Industry,
Singapore.

[Customs (Conf.) 0117/2003/PTA; MTI 66/1-2-24 PT1 VOL3;
 AG/LEGIS/SL/300/2015/1 Vol. 9]